Table 70 Optimized "**perfect**" **isogrid-stiffened** equivalent elliposidal shell. Design margins from Load Set 1 (+mode 1 and +mode 2 imperfection shapes) corresponding to the design optimized with the use of only mode 1 and mode 2 imperfection shapes. These margins are developed via the seven analyses of the type listed in Table 30. Wimp = 0.0001 inch.

A typical margin with the meanings of the indices, a, b, c, d, e, explained:

```
                                  a            b
5  3.895E-03  (STFBK1(1,1)/STFBK1A(1,1))/STFBK1F(1,1)-1; F.S.= 1.00
                    c d e      c  d e       c  d e
```

"STFBK" means "Stiffener buckling"
a = "A" means "Allowable value"
b = "F" means "Factor of safety"
c = Imperfection mode number, (1 or 2 in the cases explored here)
d = Load set number (1 or 2 in the cases explored here)
Load set 1 means "use +mode 1 and +mode 2 imperfection shapes"
Load set 2 means "use -mode 1 and -mode 2 imperfection shapes"
e = Region number:
(1 or 2 Region 1 is from the axis of revolution to xlimit,
that is, 0 < x < xlimit.
Region 2 is from xlimit to the equator,
that is, xlimit < x < semi-major axis.)

*** RESULTS FOR LOAD SET NO. 1 (+mode 1 and +mode 2 imperfections) ***
MARGINS CORRESPONDING TO CURRENT DESIGN (F.S.= FACTOR OF SAFETY)

MARGIN NO.	CURRENT VALUE	DEFINITION
1	**-5.564E-03**	**(CLAPS1(1)/CLAPS1A(1)) / CLAPS1F(1)-1; F.S.= 1.00**
2	2.324E-01	(GENBK1(1)/GENBK1A(1)) / GENBK1F(1)-1; F.S.= 1.00
3	1.510E+00	(SKNBK1(1,1)/SKNBK1A(1,1))/SKNBK1F(1,1)-1; F.S.= 1.00
4	1.726E+00	(SKNBK1(1,2)/SKNBK1A(1,2))/SKNBK1F(1,2)-1; F.S.= 1.00
5	**3.895E-03**	**(STFBK1(1,1)/STFBK1A(1,1))/STFBK1F(1,1)-1; F.S.= 1.00**
6	4.329E-01	(STFBK1(1,2)/STFBK1A(1,2))/STFBK1F(1,2)-1; F.S.= 1.00
7	**1.821E-01**	**(SKNST1A(1,1)/SKNST1(1,1))/SKNST1F(1,1)-1; F.S.= 1.00**
8	**-1.323E-02**	**(SKNST1A(1,2)/SKNST1(1,2))/SKNST1F(1,2)-1; F.S.= 1.00**
9	**5.500E-03**	**(STFST1A(1,1)/STFST1(1,1))/STFST1F(1,1)-1; F.S.= 1.00**
10	**-2.193E-02**	**(STFST1A(1,2)/STFST1(1,2))/STFST1F(1,2)-1; F.S.= 1.00**
11	6.640E-01	(WAPEX1A(1)/WAPEX1(1)) / WAPEX1F(1)-1; F.S.= 1.00
12	**-5.564E-03**	**(CLAPS2(1)/CLAPS2A(1)) / CLAPS2F(1)-1; F.S.= 1.00**
13	2.326E-01	(GENBK2(1)/GENBK2A(1)) / GENBK2F(1)-1; F.S.= 1.00
14	1.510E+00	(SKNBK2(1,1)/SKNBK2A(1,1))/SKNBK2F(1,1)-1; F.S.= 1.00
15	1.726E+00	(SKNBK2(1,2)/SKNBK2A(1,2))/SKNBK2F(1,2)-1; F.S.= 1.00
16	**4.598E-04**	**(STFBK2(1,1)/STFBK2A(1,1))/STFBK2F(1,1)-1; F.S.= 1.00**
17	4.367E-01	(STFBK2(1,2)/STFBK2A(1,2))/STFBK2F(1,2)-1; F.S.= 1.00
18	**1.824E-01**	**(SKNST2A(1,1)/SKNST2(1,1))/SKNST2F(1,1)-1; F.S.= 1.00**
19	**-1.567E-02**	**(SKNST2A(1,2)/SKNST2(1,2))/SKNST2F(1,2)-1; F.S.= 1.00**
20	**2.061E-03**	**(STFST2A(1,1)/STFST2(1,1))/STFST2F(1,1)-1; F.S.= 1.00**
21	**-2.219E-02**	**(STFST2A(1,2)/STFST2(1,2))/STFST2F(1,2)-1; F.S.= 1.00**
22	6.645E-01	(WAPEX2A(1)/WAPEX2(1)) / WAPEX2F(1)-1; F.S.= 1.00