

Домашнее задание № 4

- 1) На мастер-ноде в файле `pg_hba.conf` добавлены настройки для 3-й реплики PostgreSQL

```
(ikonstbai) 89.169.182.244
GNU nano 4.8 /etc/postgresql/12/main/pg_hba.conf
# Noninteractive access to all databases is required during automatic
# maintenance (custom daily cronjobs, replication, and similar tasks).
#
# Database administrative login by Unix domain socket
local all postgres trust
# TYPE DATABASE USER ADDRESS METHOD
# "local" is for Unix domain socket connections only
local all all trust
# IPv4 local connections:
host all all 127.0.0.1/32 trust
# IPv6 local connections:
host all all ::1/128 trust
# Allow replication connections from localhost, by a user with the
# replication privilege.
local replication all peer
host replication all 127.0.0.1/32 md5
host replication all ::1/128 md5
# 1st replica
#host all all 158.160.25.129/32 md5
#host replication postgres 158.160.25.129/32 md5
# 2nd replica
host all all 130.193.42.24/32 md5
host replication postgres 130.193.42.24/32 md5
```

- 2) На слэйв-ноде с 3-й репликой в файле `postgresql.conf` в разделе `REPLICATION` раскомментировать настройку `recovery_min_apply_delay` и задать значение отставания по времени, например, 30 сек.

```
#wal_retrieve_retry_interval = 5s # in milliseconds; 0 disables
# time to wait before retrying to
# retrieve WAL after a failed attempt
recovery_min_apply_delay = 30s # minimum delay for applying changes during recovery
# - Subscribers -
# These settings are ignored on a publisher
```

- 3) На мастер-ноде остановить `postgresql` и проверить статус

```
(ikonstbai) 89.169.182.244
root@compute-vm-2-2-20-ssd-1764047789103:~# service postgresql stop
root@compute-vm-2-2-20-ssd-1764047789103:~# service postgresql status
• postgresql.service - PostgreSQL RDBMS
  Loaded: loaded (/lib/systemd/system/postgresql.service; enabled; vendor preset: enabled)
  Active: inactive (dead) since Fri 2025-11-28 17:25:37 UTC; 5 days ago
  Process: 50326 ExecStart=/bin/true (code=exited, status=0/SUCCESS)
  Main PID: 50326 (code=exited, status=0/SUCCESS)

Nov 28 16:36:52 compute-vm-2-2-20-ssd-1764047789103 systemd[1]: Starting PostgreSQL RDBMS...
Nov 28 16:36:52 compute-vm-2-2-20-ssd-1764047789103 systemd[1]: Finished PostgreSQL RDBMS.
Nov 28 17:25:37 compute-vm-2-2-20-ssd-1764047789103 systemd[1]: postgresql.service: Succeeded.
Nov 28 17:25:37 compute-vm-2-2-20-ssd-1764047789103 systemd[1]: Stopped PostgreSQL RDBMS.
root@compute-vm-2-2-20-ssd-1764047789103:~#
```

- 4) На слейв-ноде с 3-й репликой попробовать удалить БД

```
postgres=# DROP DATABASE test3;  
ERROR:  cannot execute DROP DATABASE in a read-only transaction  
postgres=#
```

- 5) Перевести слейв-ноду командой `pg_ctl promote` в режим мастера и удалить БД

```
postgres=# DROP DATABASE test3;  
DROP DATABASE  
postgres=#
```