

Домашнее задание № 8

- 1) На хосте в файле hosts прописать IP-адреса подключаемых нод

```
# Here's another example of host id
# leading 0s:

#db-[99:101]-node.example.com
[build_app]
158.160.87.110

[prod_app]
158.160.86.160
```

- 2) Запустить playbook на хосте в директории, где расположен файл hw08.yaml
ansible-playbook hw08.yaml

```
(ikonstbai) 158.160.94.192
root@compute-vm-2-2-10-ssd-master:/home/ikonstbai/hw08# ansible-playbook hw08.yaml

PLAY [provisioning build environment] *****

TASK [Gathering Facts] *****
The authenticity of host '158.160.87.110 (158.160.87.110)' can't be established.
ECDSA key fingerprint is SHA256:0g4qsUIP0Ws3qZ2oY2gfGwzm2SR8/frPGoC8kv2B15Y.
Are you sure you want to continue connecting (yes/no)? yes
ok: [158.160.87.110]

TASK [Ensure default-jdk package is present] *****
changed: [158.160.87.110]

TASK [Ensure maven package is present] *****
changed: [158.160.87.110]

TASK [Copy build-app data] *****
changed: [158.160.87.110]

TASK [Build app package] *****
changed: [158.160.87.110]

TASK [Send war-file to host] *****
changed: [158.160.87.110]

PLAY [provisioning prod environment] *****

TASK [Gathering Facts] *****
The authenticity of host '158.160.86.160 (158.160.86.160)' can't be established.
ECDSA key fingerprint is SHA256:p2bg4/97myUQ7QmBaeITpLmti1VoLXXQnIfC4wR7DU.
Are you sure you want to continue connecting (yes/no)? yes
ok: [158.160.86.160]

TASK [Ensure tomcat package is present] *****
changed: [158.160.86.160]

TASK [Ensure tomcat service is started] *****
ok: [158.160.86.160]

TASK [Copy war-file to prod env] *****
changed: [158.160.86.160]

PLAY RECAP *****
158.160.86.160      : ok=4    changed=2    unreachable=0    failed=0
158.160.87.110     : ok=6    changed=5    unreachable=0    failed=0

root@compute-vm-2-2-10-ssd-master:/home/ikonstbai/hw08#
```

3) Приложение доступно по адресу **IP VM:8080/hello-1.0**

Boxfuse Sample App: X +

← ⓘ ↻  http://158.160.86.160:8080/hello-1.0/

Congratulations!



boxfuse

You have successfully launched your Instance!

This Instance is running on **null** and has the id **null**.

It is based on the Image **null** generated from **null**

Now it's your turn!

Check out [this app](#) from GitHub, modify it, and give it version 2.
You are now ready to fuse and **deploy it with zero downtime** using the commands you already know.

Alternatively you can go back to the [Boxfuse Console](#),
and simply create your own.

If you need any help the [documentation](#) is there for you,
or simply shoot us an email at support@boxfuse.com

Say goodbye to snowflake servers.

Enjoy Boxfuse!