

Multiplying Polynomials in Python

At this point, you have created a nice toolbox of functions for dealing with lists of coefficients as polynomials. Create a file called `poly.py` and copy the following functions into it:

- `evaluate_polynomial`
- `polynomial_to_string`
- `add_polynomials`
- `scalar_polynomial_multiply`
- `subtract_polynomial`

Now, create another file in the same directory called `test.py`. Type this into that file:

```
1  import poly
2
3  polynomial_a = [9.0, -4.0, 3.0, -5.0]
4  print('Polynomial A =', poly.polynomial_to_string(polynomial_a))
5
6  polynomial_b = [-9.0, 0.0, 4.0, 2.0, 1.0]
7  print('Polynomial B =', poly.polynomial_to_string(polynomial_b))
8
9  # Evaluation
10 value_of_b = poly.evaluate_polynomial(polynomial_b, 3)
11 print('Polynomial B at 3 =', value_of_b)
12
13 # Adding
14 a_plus_b = poly.add_polynomials(polynomial_a, polynomial_b)
15 print('A + B =', poly.polynomial_to_string(a_plus_b))
16
17 # Scalar multiplication
18 b_scalar = poly.scalar_polynomial_multiply(-3.2, polynomial_b)
19 print('-3.2 * Polynomial B =', poly.polynomial_to_string(b_scalar))
20
21 # Subtraction
22 a_minus_b = poly.subtract_polynomial(polynomial_a, polynomial_b)
23 print('A - B =', poly.polynomial_to_string(a_minus_b))
```

When you run it, you should get the following:

```
1 Polynomial A = -5.0x^3 + 3.0x^2 + -4.0x + 9.0
2 Polynomial B = 1.0x^4 + 2.0x^3 + 4.0x^2 + -9.0
3 Polynomial B at 3 = 162.0
4 A + B = 1.0x^4 + -3.0x^3 + 7.0x^2 + -4.0x
5 -3.2 * Polynomial B = -3.2x^4 + -6.4x^3 + -12.8x^2 + 28.8
6 A - B = -1.0x^4 + -7.0x^3 + -1.0x^2 + -4.0x + 18.0
```

You are now ready to implement the multiplication of polynomials. The function will look like this:

```
1 def multiply_polynomials(a, b):
2     ...Your code here...
```

It will return a list of coefficients.

In an exercise in the last chapter, you were asked “ Let’s say I have two polynomials, p_1 and p_2 . p_1 has degree 23. p_2 has degree 12. What is the degree of their product?” The answer was $23 + 12 = 35$.

In our implementation, a polynomial of degree 23 is held in a list of length 24.

In Python, we will be trying to multiply a polynomial a and a polynomial b represented as lists. What is the degree of that product?

```
1 result_degree = (len(a) - 1) + (len(b) - 1)
```

Now, we need to create an array of zeros that is one longer than that. Here is a cute Python trick: If you have a list, you can replicate it using the `*` operator.

```
1 a = [5,7]
2 b = a * 4
3 print(b)
4 # [5, 7, 5, 7, 5, 7, 5, 7]
```

Here is how you will get a list of zeros:

```
1 result = [0.0] * (result_degree + 1)
```

We will step through a , getting the index and value of each entry. You can do this in one

line using enumerate:

```
1 for a_degree, a_coefficient in enumerate(a):
```

For each of those, we will step through the entire b polynomial. As you multiply together each term, you will add it to the appropriate coefficient of the result.

Here is the whole function:

```
1 def multiply_polynomials(a, b): # What is the degree of the resulting
2 polynomial? result_degree = (len(a) - 1) + (len(b) - 1)
3
4     # Make a list of zeros to hold the coefficients result = [0.0] * (result_degree + 1)
5     (result_degree + 1)
6
7     # Iterate over the indices and values of a for a_degree,
8     a_coefficient in enumerate(a):
9
10        # Iterate over the indices and values of b for b_degree,
11        b_coefficient in enumerate(b):
12
13            # Calculate the resulting monomial coefficient =
14            a_coefficient * b_coefficient degree = a_degree + b_degree
15
16            # Add it to the right bucket
17            result[degree] = result[degree] + coefficient
18
19     return result
```

Take a long look at that function. When you understand it, type it into `poly.py`.

In `test.py`, try out the new function:

```
1 # Multiplication
2 a_times_b = poly.multiply_polynomials(polynomial_a, polynomial_b)
3 print('A x B =', poly.polynomial_to_string(a_times_b))
```

This is an example of a *nested loop*. The outer loop steps through the polynomial a. For each step it takes, the inner loop steps through the entire polynomial b.

1.1 Something surprising about lists

You can imagine that you might want to create two very similar polynomials. Let's say polynomial c is $x^2 + 2x + 1$ and polynomial d is $x^2 - 2x + 1$. You might think you are very

clever to just alter that degree 1 coefficient like this:

```
1 c = [1.0, 2.0, 1.0]
2 d = c
3 d[1] = -2.0
```

If you printed out `c`, you would get `[1.0, -2.0, 1.0]`. Why? You assigned two variables (`c` and `d`) to the *the same list*. So, when you use one reference (`d`) to change the list, you see the change if you look at the list from either reference. *FIXME: Diagram of two references to the same list here.*

To create two separate lists, you would need to explicitly make a copy:

```
1 c = [1.0, 2.0, 1.0]
2 d = c.copy()
3 d[1] = -2.0
```

This is a draft chapter from the Kontinua Project. Please see our website (<https://kontinua.org/>) for more details.

Answers to Exercises

