



CONTENTS

1	HTML	3
1.1	HTML Elements	3
1.2	Attributes	3
1.3	HTML Document Structure	4
1.4	Web Development and HTML	7
1.5	Metadata	7
1.6	Div Elements	8
1.7	Semantic HTML	10
1.8	Headings and Sections	12
1.9	Text Elements	14
1.10	Links	16
1.11	Lists	16
1.11.1	Unordered Lists	17
1.11.2	Ordered Lists	17
1.12	Navigation	20
1.13	Tables	22
1.14	Forms	26
1.15	Images	28
2	Introduction to Text	33
2.1	Newlines and Carriage Returns	33
2.2	ASCII	33
2.3	UTF-8	33

A	Answers to Exercises	35
Index		41

HTML

HTML, an abbreviation for Hypertext Markup Language, is the standard language for creating web pages and web applications. It is a cornerstone technology of the World Wide Web and forms the structure and layout of web content.

1.1 HTML Elements

An HTML document is composed of a series of elements, which are denoted by tags. Elements have an opening tag and a closing tag with content in between. Some elements, however, are self-closing and do not contain any content.

An element consists of three parts:

- **Opening tag:** The opening tag is the start of an element. The format of it is `<tagname>`.
- **Content:** Content is the data or information between the tags.
- **Closing tag:** The closing tag indicates the end of an element. The format of it is `</tagname>`.

For example, the paragraph tag `<p>` is used to denote a paragraph:

```
1 <p>This is a paragraph.</p>
```

This applies to a lot of HTML elements but not every one. There are HTML elements that are self-closing. A self-closing element does not require a closing tag. The image tag `<img>` is an example of a self-closing element.

```
1 
```

1.2 Attributes

Attributes provide additional information about HTML elements. For some elements like `img`, they are required for the element to function correctly. They are always specified in the opening tag and consist of a name and value pair.

The syntax for attributes is:

```
1 <tagname attribute="value">Content</tagname>
```

There are so many attributes available, we cannot cover them all here. However, some common attributes that work on most elements include:

- **id**: The `id` attribute specifies a unique identifier for an element (should be unique within the entire page)
- **class**: The `class` attribute specifies one or more class names for styling with CSS
- **style**: The `style` attribute specifies inline CSS styling
- **title**: The `title` attribute specifies additional information displayed as a tooltip

Examples:

```
1 <p id="intro" class="highlight">
2   Introduction paragraph
3 </p>
4
5 <div style="color: blue; font-size: 16px;">
6   Styled text
7 </div>
8
9 
```

1.3 HTML Document Structure

A typical HTML document has a specific structure. Every HTML5 document begins with a DOCTYPE declaration, which tells the browser which version of HTML to expect.

The basic structure of an HTML document is:

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Page Title</title>
5 </head>
6 <body>
7   <!-- Content goes here -->
8 </body>
```

```
9 | </html>
```

The main components are:

- **DOCTYPE declaration:** This informs the browser about the version of HTML. For HTML5, it is `<!DOCTYPE html>`.
- **html:** The `html` element is the root element that wraps all other content.
- **head:** This element contains metadata and information about the page, including:
 - `<title>`: This element sets the title of the page, which appears in the browser tab.
 - `<meta>`: This element includes metadata such as character encoding, and view-port settings.
- **body:** The body element contains all the visible content of the web page.

Here is a more complete example:

```
1 | <!DOCTYPE html>
2 | <html lang="en">
3 | <head>
4 |   <meta charset="UTF-8">
5 |   <meta name="viewport" content="width=device-width, initial-scale=1.0">
6 |   <title>My Website</title>
7 | </head>
8 | <body>
9 |   <h1>Welcome</h1>
10 |   <p>This is my website.</p>
11 | </body>
12 | </html>
```

Exercise 1 Building a Full HTML Document

Create the beginning of a web page for a chocolate chip cookie recipe. Add the DOCTYPE declaration, the `html` element, a head with a title that says "Chocolate Chip Cookies", and move the following content into the body.

Working Space

```
1 <body>
2   <h1 id="recipe-title">Chocolate
   ↳ Chip Cookies</h1>
3   <p class="intro" title="A short
   ↳ recipe description">
4     This recipe makes soft and
     ↳ sweet chocolate chip
     ↳ cookies.
5   </p>
6 </body>
```

Write a full HTML5 page that wraps this content correctly.

Answer on Page 35

After this exercise, the page should look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

Figure 1.1: HTML Structure Exercise Output

1.4 Web Development and HTML

The Web Development trio consists of three essential languages that work together to create modern web applications. These languages are HTML, CSS, and JavaScript.

- **HTML:** HTML provides the structure and content of web pages. It defines what elements exist on the page. Think of it as the skeleton and meat of a web page.
- **CSS:** Cascading Style Sheets (CSS) handles the presentation and styling. It controls how elements look, including colors, fonts, spacing, and layout. Think of it as the clothing and makeup that makes the page visually appealing.
- **JavaScript:** JavaScript adds interactivity and behavior. It enables dynamic content changes, form validation, animations, and user interactions. Think of it as the brain that allows the page to respond to actions like clicking a button or submitting a form.

1.5 Metadata

Metadata is information about the HTML document that is not directly displayed on the page. The information is provided through a series of `<meta>` tags with certain attributes and their corresponding values. These are placed in the `<head>` section and provides important information to browsers, search engines, and developers.

Common metadata elements include:

- `<meta charset="UTF-8">`: This line specifies the character encoding of the document. UTF-8 is the standard encoding for web pages.
- `<meta name="viewport" content="width=device-width, initial-scale=1.0">`: This line configures the viewport for responsive design. This tells mobile browsers how to scale the page.
- `<meta name="description" content="...">`: This line provides a brief description of the page content for search engines.
- `<meta name="keywords" content="...">`: This line lists relevant keywords for search engine optimization (SEO).
- `<meta name="author" content="...">`: This line specifies the author of the document.

Example of using multiple meta tags:

```
1 <head>
2   <meta charset="UTF-8">
3   <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
4     <meta name="description" content="A tutorial about web development">
5     <meta name="keywords" content="HTML, CSS, JavaScript">
6     <meta name="author" content="John Doe">
7     <title>Web Development Tutorial</title>
8 </head>
```

1.6 Div Elements

The `<div>` element is a generic container used to group content together. The name “div” stands for “division.” `<div>` has no specific meaning to it. It is a neutral wrapper used for layout, styling, or organizing content with CSS and JavaScript.

The `<div>` element is one of the most commonly used HTML elements in existing applications. It is often used with `class` or `id` attributes to apply styling or add behavior.

Here’s a basic example:

```
1 <div class="container">
2     <h2>Section Title</h2>
3     <p>This is some content inside a div.</p>
4 </div>
```

As mentioned, it is one of the most commonly used HTML elements. Here’s an example with multiple divs for layout:

```
1 <div class="header">
2     <h1>Website Title</h1>
3 </div>
4
5 <div class="content">
6     <p>Main content goes here.</p>
7 </div>
8
9 <div class="footer">
10    <p>© 2024 My Website</p>
11 </div>
```

Exercise 2 Grouping Recipe Content with div

Group the recipe title and introduction paragraph into a div. Add a "class" attribute to the div with the value "recipe-header".

Working Space

```
1 <body>
2   <h1 id="recipe-title">Chocolate
   ↳ Chip Cookies</h1>
3   <p class="intro" title="A short
   ↳ recipe description">
4     This recipe makes soft and
       ↳ sweet chocolate chip
       ↳ cookies.
5   </p>
6 </body>
```

Add two more p elements for ingredients and steps in the body. Place the p elements into two separate div elements. The ingredients div should have a class attribute with a value of "ingredients-section". The steps div should have a class attribute with a value of "steps-section".

Answer on Page 35

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

Ingredients

Steps

Figure 1.2: HTML Div Exercise Output

1.7 Semantic HTML

Unlike `<div>` elements, Semantic HTML elements are elements that clearly describe their meaning to both the browser and the developer. This improves code readability, helps with search engine optimization (SEO), and makes pages more accessible to assistive technologies like screen readers.

Semantic elements follow a logical structure that reflects the content of the page. Some common semantic elements include:

- `<header>`: The `header` element represents the top section of the page or a section, typically containing the logo, navigation, or introductory content.
- `<nav>`: The `nav` element contains navigation links to other pages or sections.
- `<main>`: The `main` element specifies the main content area of the page.
- `<article>`: The `article` element represents independent, self-contained content that could stand alone, such as a blog post or news article.
- `<section>`: The `section` element defines a generic section of content. This is preferred instead of using multiple `divs` for grouping related content.
- `<aside>`: The `aside` element contains supplementary content like sidebars, ads, or related links.
- `<footer>`: The `footer` element represents the bottom section of a page or section.

Here is an example of using semantic elements to structure a simple blog page:

```
1 <header>
2   <h1>My Blog</h1>
3   <nav>
4     <a href="/">Home</a>
5     <a href="/about">About</a>
6     <a href="/contact">Contact</a>
7   </nav>
8 </header>
9
10 <main>
11   <article>
12     <h2>Article Title</h2>
13     <p>Article content here...</p>
14   </article>
15
16   <aside>
17     <h3>Related Posts</h3>
18     <ul>
19       <li><a href="#post1">Post 1</a></li>
20       <li><a href="#post2">Post 2</a></li>
21     </ul>
22   </aside>
23 </main>
24
25 <footer>
26   <p>&copy; 2026 My Blog. All rights reserved.</p>
27 </footer>
```

Exercise 3 Using Semantic Elements

Replace general `div` containers with semantic elements where they make sense. Use `header` for the “recipe-header”. Use `section` for the “ingredients-section” and “steps-section”. Afterwards, put these inside a `main` element. Add a footer for the bottom note. There will be no content in the footer for now.

Working Space

```
1 <body>
2   <div class="recipe-header">
3     <h1 id="recipe-title">Chocolate
      ↳ Chip Cookies</h1>
4     <p class="intro" title="A short
      ↳ recipe description">
5       This recipe makes soft and
        ↳ sweet chocolate chip
          ↳ cookies.
6     </p>
7   </div>
8
9   <div class="ingredients-section">
10    <p>Ingredients</p>
11  </div>
12
13  <div class="steps-section">
14    <p>Steps</p>
15  </div>
16 </body>
```

Answer on Page 36

After this, the web page should still look the same from the previous exercise.

1.8 Headings and Sections

HTML provides six levels of headings, ranging from `<h1>` to `<h6>`. Headings establish a hierarchical structure for page content. `<h1>` is the most important and typically used once per page for the main title, while `<h6>` is the least important.

```

1 <h1>Main Page Title</h1>
2 <h2>Major Section</h2>
3 <h3>Subsection</h3>
4 <h4>Sub-subsection</h4>
5 <h5>Minor heading</h5>
6 <h6>Least important heading</h6>

```

Headings are important for defining the structure of the content and improving accessibility. They allow users to quickly scan the page and understand the organization of information. Proper use of headings also benefits SEO by signaling the importance of content to search engines.

Exercise 4 Adding Section Headings

Replace the p elements in the ingredients and steps sections with h2 tags.

Working Space

```

1 <main>
2   <section
3     ↪ class="ingredients-section">
4     <p>Ingredients</p>
5   </section>
6   <section class="steps-section">
7     <p>Steps</p>
8   </section>
9 </main>

```

Update the main content to include headings both the Ingredients and Steps sections. Add an id attribute to each heading with the value "ingredients" and "steps" respectively.

Answer on Page 36

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

Ingredients

Steps

Figure 1.3: HTML Headings Exercise Output

1.9 Text Elements

HTML provides several elements for formatting text content. Here is a list of some of the most commonly used ones:

- `<p>`: The `p` element defines a paragraph. Browsers automatically add space before and after.
- `<br>`: The `br` element inserts a line break. This is a self-closing element.
- `<hr>`: The `hr` element displays a horizontal line. This is a self-closing element.
- `<strong>`: The `strong` element indicates strong importance. This is typically displayed in bold.
- `<em>`: The `em` element indicates emphasis. This is typically displayed in italics.
- `<b>`: The `b` element displays bold text without semantic importance.
- `<i>`: The `i` element displays italic text without semantic emphasis.
- `<mark>`: The `mark` element highlights text with a yellow background.
- `<code>`: The `code` element displays text in monospace font for code.

Examples:

```
1 <p>This is a <strong>important</strong> point.</p>
2
3 <p>This word is <em>emphasized</em>.</p>
4
```

```
5 <p><code>var x = 5;</code></p>
6
7 <p>This is <mark>highlighted</mark> text.</p>
```

Exercise 5 Using Text Elements

Working Space

Add a `p` element in the footer section of the cookie recipe page. The paragraph should say: "**Important Note:** Make sure not to overbake the cookies, or they will become hard."

```
1 <footer>
2 </footer>
```

Add a paragraph element inside of the footer element. Use the `strong` element to make "Important Note:" bold.

Answer on Page 36

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

Ingredients

Steps

Important Note: Make sure not to overbake the cookies, or they will become hard.

Figure 1.4: HTML Text Exercise Output

1.10 Links

Links are created using the `<a>` (anchor) element with the `href` attribute specifying the destination.

```
1 <a href="https://www.example.com">Visit Example</a>
```

Links can point to various destinations:

- **External websites:** `<a href="https://www.google.com">External Site</a>`. This will navigate the user to Google.
- **Other pages within the same site:** `<a href="about.html">About</a>`. This will navigate the user to the `about.html` page within the same website.
- **Email addresses:** `<a href="mailto:email@example.com">Email</a>`. This will open the user's email to send an email to the specified address.
- **Phone numbers:** `<a href="tel:+1234567890">Call Us</a>`. This will initiate a phone call on devices that support it. This can be useful for mobile users.
- **Specific locations on the same page:** `<a href="#section2">Jump to Section 2</a>` (where `<h2 id="section2">Section 2</h2>`). When the link is clicked, the page will scroll to the header with the id "section2".

Apart from the `href` attribute, here are some other useful attributes for links:

- `target="_blank"`: This attribute and value pair opens the link in a new tab.
- `target="_self"`: This attribute and value pair opens the link in the same tab. This is the normal behavior if the `target` attribute is not specified.
- `title="tooltip"`: This attribute and value pair displays text when the user hovers over the link like a tooltip.

1.11 Lists

HTML supports two main types of lists to organize content. These include unordered lists and ordered lists. Both types of lists use the `<li>` element to define individual list items.

1.11.1 Unordered Lists

Unordered lists display items with bullet points. As the name suggests, the order of items is not important like the items of a shopping list. They use the `<ul>` tag with list items defined by `<li>`:

```
1 <ul>
2   <li>Apples</li>
3   <li>Bananas</li>
4   <li>Oranges</li>
5 </ul>
```

This would render an unordered list as:

- Apples
- Bananas
- Oranges

1.11.2 Ordered Lists

Ordered lists display items with numbers or other counters. As the name suggests, the order of items is important, like steps in a recipe. They use the `<ol>` tag:

```
1 <ol>
2   <li>First step</li>
3   <li>Second step</li>
4   <li>Third step</li>
5 </ol>
```

The output of the above code would be:

1. First step
2. Second step
3. Third step

The `<ol>` tag supports the `type` attribute to customize or change the default numbering style. So instead of numbers, you can use letters or Roman numerals. Some of the common attributes include:

- `type="a"`: Lowercase letters (a, b, c...).
- `type="A"`: Uppercase letters (A, B, C...).
- `type="i"`: Lowercase Roman numerals (i, ii, iii...)
- `type="I"`: Uppercase Roman numerals (I, II, III...)

Exercise 6 Ingredients and Steps Lists

Use lists to show the cookie ingredients and the baking steps. The ingredients should be an unordered list, and the steps should be an ordered list.

Working Space

```

1 <section
  ↳ class="ingredients-section">
2   <h2
    ↳ id="ingredients">Ingredients</h2>
3   <!-- Add an unordered list of
    ↳ ingredients here -->
4 </section>
5
6 <section class="steps-section">
7   <h2 id="steps">Steps</h2>
8   <!-- Add an ordered list of steps
    ↳ here -->
9 </section>

```

Here is the list of ingredients:

2 1/4 cups flour. 1 teaspoon baking soda.
1 teaspoon salt. 1 cup butter, 3/4 cup
sugar. 3/4 cup brown sugar, 2 eggs. 2
cups chocolate chips.

Here is the list of steps:

Preheat the oven to 375°F. Mix the dry
ingredients in one bowl. Mix the but-
ter, sugar, brown sugar, and eggs in an-
other bowl. Stir the dry ingredients into
the wet ingredients. Add the chocolate
chips. Scoop the dough onto a baking
sheet. Bake for 9 to 11 minutes.

Answer on Page 37

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

Ingredients

- 2 1/4 cups flour
- 1 teaspoon baking soda
- 1 teaspoon salt
- 1 cup butter
- 3/4 cup sugar
- 3/4 cup brown sugar
- 2 eggs
- 2 cups chocolate chips

Steps

1. Preheat the oven to 375°F.
2. Mix the dry ingredients in one bowl.
3. Mix the butter, sugar, brown sugar, and eggs in another bowl.
4. Stir the dry ingredients into the wet ingredients.
5. Add the chocolate chips.
6. Scoop the dough onto a baking sheet.
7. Bake for 9 to 11 minutes.

Important Note: Make sure not to overbake the cookies, or they will become hard.

Figure 1.5: HTML Lists Exercise Output

1.12 Navigation

The `<nav>` element is used to wrap navigational links within a navigation section. It's a semantic element that helps structure the page and signal to assistive technologies that this section contains navigation. This is commonly used for site menus, table of contents, or any set of links that help users navigate the website.

```
1 <nav>
2   <ul>
3     <li><a href="/">Home</a></li>
4     <li><a href="/about">About</a></li>
5     <li><a href="/services">Services</a></li>
6     <li><a href="/contact">Contact</a></li>
7   </ul>
8 </nav>
```

Exercise 7 Creating a Simple Navigation Bar

Add a navigation bar to the top of the cookie page within the header element. The navigation should link to the “Ingredients” and “Steps” sections.

Working Space

```
1 <header>
2   <h1 id="recipe-title">Chocolate
   ↳ Chip Cookies</h1>
3   <p class="intro" title="A short
   ↳ recipe description">
4     This recipe makes soft and
       ↳ sweet chocolate chip
       ↳ cookies.
5   </p>
6
7   <!-- Add navigation here -->
8 </header>
```

Insert a nav element with links to each section. Each link should use the href attribute to point to the corresponding section's id (e.g., href="#ingredients" and href="#steps") within the same page.

Answer on Page 37

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

- [Ingredients](#)
- [Steps](#)

Ingredients

- 2 1/4 cups flour
- 1 teaspoon baking soda
- 1 teaspoon salt
- 1 cup butter
- 3/4 cup sugar
- 3/4 cup brown sugar
- 2 eggs
- 2 cups chocolate chips

Steps

1. Preheat the oven to 375°F.
2. Mix the dry ingredients in one bowl.
3. Mix the butter, sugar, brown sugar, and eggs in another bowl.
4. Stir the dry ingredients into the wet ingredients.
5. Add the chocolate chips.
6. Scoop the dough onto a baking sheet.
7. Bake for 9 to 11 minutes.

Important Note: Make sure not to overbake the cookies, or they will become hard.

Figure 1.6: HTML Navigation Exercise Output

1.13 Tables

Tables organize data into rows and columns. They are created using the `<table>` tag. However, that is used as a container for table elements necessary to render the layout of the table. Those table elements include:

- `<tr>`: The `tr` element defines a table row
- `<th>`: The `th` element defines a table header cell. By default, it is displayed in bold and centered. It is used to indicate that the cell is a header for a column or row.
- `<td>`: The `td` element defines a table data cell. It is used for regular cells that contain data.
- `<thead>`: The `thead` element groups header rows.

- `<tbody>`: The `tbody` element groups body rows.
- `<tfoot>`: The `tfoot` element groups footer rows.
- `<caption>`: The `caption` element provides a title for the table.

Here's a basic table example:

```

1 <table>
2   <caption>Monthly Sales</caption>
3   <thead>
4     <tr>
5       <th>Month</th>
6       <th>Sales</th>
7     </tr>
8   </thead>
9   <tbody>
10    <tr>
11      <td>January</td>
12      <td>$5000</td>
13    </tr>
14    <tr>
15      <td>February</td>
16      <td>$6000</td>
17    </tr>
18  </tbody>
19  <tfoot>
20    <tr>
21      <th>Total</th>
22      <td>$11000</td>
23    </tr>
24  </tfoot>
25 </table>

```

The output of the above code would be:

Table 1.1: Monthly Sales

Month	Sales
January	\$5000
February	\$6000
Total	\$11000

There are attributes that can be applied to table cells to make them span multiple rows or columns. These attributes are `rowspan` (row span) and `colspan` (column span). These attributes are used to merge cells together, which can be useful for creating more complex table layouts. `colspan` is used to make a cell span across multiple columns, while `rowspan` is used to make a cell span across multiple rows. The value of these attributes specifies the number of rows or columns the cell should span.

Here's an example of how to use them:

```
1 <table>
2   <tr>
3     <th colspan="2">Personal Information</th>
4   </tr>
5   <tr>
6     <td>Name</td>
7     <td>John Doe</td>
8   </tr>
9   <tr>
10    <th>Age</th>
11    <th rowspan="2">Skills</th>
12  </tr>
13  <tr>
14    <td>30</td>
15  </tr>
16  <tr>
17    <td colspan="2">HTML, CSS, JavaScript</td>
18  </tr>
19 </table>
```

The output of the above code would be:

Personal Information	
Name	John Doe
Age	Skills (spans 2 rows)
HTML, CSS, JavaScript	

Exercise 8 Recipe Facts Table

Create a new section for recipe facts. Inside the section, add a h2 heading with the text "Recipe Facts".

Working Space

```
1 <section>
2   <h2>Baking Tips</h2>
3 </section>
```

Add a table that shows basic facts about the chocolate chip cookie recipe, such as prep time, bake time, and servings. The table must have three rows and two columns. Add a border attribute to the <table> element with a value of "1" to make the table borders visible.

Prep Time	15 minutes
Bake Time	10 minutes
Servings	24 cookies

Answer on Page 38

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

- [Ingredients](#)
- [Steps](#)

Ingredients

- 2 1/4 cups flour
- 1 teaspoon baking soda
- 1 teaspoon salt
- 1 cup butter
- 3/4 cup sugar
- 3/4 cup brown sugar
- 2 eggs
- 2 cups chocolate chips

Steps

1. Preheat the oven to 375°F.
2. Mix the dry ingredients in one bowl.
3. Mix the butter, sugar, brown sugar, and eggs in another bowl.
4. Stir the dry ingredients into the wet ingredients.
5. Add the chocolate chips.
6. Scoop the dough onto a baking sheet.
7. Bake for 9 to 11 minutes.

Recipe Facts

Prep Time	15 minutes
Bake Time	10 minutes
Servings	24 cookies

Important Note: Make sure not to overbake the cookies, or they will become hard.

Figure 1.7: HTML Tables Exercise Output

1.14 Forms

Forms allow users to input and submit data. The `<form>` element contains form controls and is submitted to a server to process the provided data. The most common form controls include text fields, checkboxes, radio buttons, and submit buttons. These form controls are created using input elements.

Here's an example of a basic form structure with various input elements:

```
1 <form>
2   <label for="name">Name:</label>
3   <input type="text" id="name" name="name" required>
4
5   <label for="email">Email:</label>
6   <input type="email" id="email" name="email">
7
8   <input type="submit" value="Submit">
9 </form>
```

The `label` element is used to provide a label for form controls. The `for` attribute of the label should match the `id` of the corresponding input element to associate them together.

Input fields have various types, each serving a different purpose. The “`type`” attribute indicates the type of input field. Here’s a list of the most common input types:

- `type="text"`: This is a single-line text input.
- `type="email"`: This is a single-line email input with validation that ensures the entered value is a valid email address.
- `type="password"`: This is a single-line password input (text is hidden).
- `type="number"`: This is a single-line numeric input.
- `type="checkbox"`: This is a checkbox for multiple selections.
- `type="radio"`: This is a radio button for single selection.
- `type="file"`: This is a file upload input.
- `type="date"`: This is a date picker input.
- `type="submit"`: This is a submit button.
- `type="reset"`: This is a reset button that will clear all form fields.

There are more form control elements besides the “`input`” element. Other form elements include:

- `<textarea>`: This is a multi-line text input.
- `<select>`: This is a dropdown menu. A dropdown is a list of options that can be expanded to show all available options.
- `<option>`: These are options within a dropdown.
- `<fieldset>`: This groups related form elements.

- `<legend>`: This is the title for a fieldset.

Here's an example that includes various form controls and uses fieldsets to group related information:

```
1 <form>
2   <fieldset>
3     <legend>Personal Information</legend>
4
5     <label for="username">Username:</label>
6     <input type="text" id="username" name="username">
7
8     <label for="password">Password:</label>
9     <input type="password" id="password" name="password">
10  </fieldset>
11
12  <fieldset>
13    <legend>Preferences</legend>
14
15    <label>
16      <input type="checkbox" name="newsletter">
17      Subscribe to newsletter
18    </label>
19
20    <label for="country">Country:</label>
21    <select id="country" name="country">
22      <option>Select a country</option>
23      <option value="usa">USA</option>
24      <option value="uk">UK</option>
25      <option value="ca">Canada</option>
26    </select>
27  </fieldset>
28
29  <button type="submit">Submit</button>
30 </form>
```

1.15 Images

Images are added using the `<img>` element, which is self-closing.

The basic syntax for the `<img>` element is:

```
1 
```

The most essential attributes for the `<img>` element are:

- `src`: The path to the image file. This is a required attribute that specifies the source of the image. The source path can route to an image file within the application or an external URL similar to a link. If the image cannot be found at the specified path, the browser will display a broken image icon. The `src` attribute is crucial for the image to load properly on the webpage. It is important to ensure that the path is correct and that the image file exists at that location.
- `alt`: This is alternative text displayed if the image cannot load or for screen readers. The `alt` attribute should provide a concise description of the image content.

Images come in various sizes. To control the display size of an image, you can use the `width` and `height` attributes.

- `width`: This specifies the width of the image in pixels or percentage.
- `height`: This specifies the height of the image in pixels or percentage.

Here's an example of using the `width` and `height` attributes to specify the dimensions of an image:

```
1 
```

For the next exercise, we will add an image to the cookie recipe page. Use the image below as a reference for the image you will add to the page.



Figure 1.8: Image of chocolate chip cookies

Exercise 9 The Recipe Image

Add a picture of the cookies to the recipe page add the bottom of the header element.

Working Space

```
1 <header>
2   <h1 id="recipe-title">Chocolate
   ↳ Chip Cookies</h1>
3   <p class="intro" title="A short
   ↳ recipe description">
4     This recipe makes soft and
   ↳ sweet chocolate chip
   ↳ cookies.
5   </p>
6
7   <!-- nav is here. Just showing
   ↳ the header for context -->
8
9   <!-- Add the image element here
   ↳ -->
10 </header>
```

Add an `<img>` element with the source set to "cookies.jpg". Make sure that the image file is in the same folder as your HTML file. The `alt` attribute should be set to "Fresh chocolate chip cookies on a plate". Set the width of the image to 500 pixels and the height to 300 pixels.

Answer on Page 38

After this exercise, the page should now look like the following:

Chocolate Chip Cookies

This recipe makes soft and sweet chocolate chip cookies.

- [Ingredients](#)
- [Steps](#)



Ingredients

- 2 1/4 cups flour
- 1 teaspoon baking soda
- 1 teaspoon salt
- 1 cup butter
- 3/4 cup sugar
- 3/4 cup brown sugar
- 2 eggs
- 2 cups chocolate chips

Steps

1. Preheat the oven to 375°F.
2. Mix the dry ingredients in one bowl.
3. Mix the butter, sugar, brown sugar, and eggs in another bowl.
4. Stir the dry ingredients into the wet ingredients.
5. Add the chocolate chips.
6. Scoop the dough onto a baking sheet.
7. Bake for 9 to 11 minutes.

Recipe Facts

Prep Time	15 minutes
Bake Time	10 minutes
Servings	24 cookies

Important Note: Make sure not to overbake the cookies, or they will become hard.

Figure 1.9: HTML Images Exercise Output

Introduction to Text

In computer systems, text is represented in files as a sequence of characters, each of which corresponds to a specific number, known as a character code. These character codes are then stored in the file as binary data.

2.1 Newlines and Carriage Returns

Two of the character codes that have special meanings are the newline (often represented as `'\n'`) and the carriage return (often represented as `'\r'`).

The newline character signifies the end of a line of text and the beginning of a new one. If you parse a text file with a Python script, it will see your 'enter' key press as a new line symbol. The carriage return character moves the cursor to the beginning of the line. The use of these characters can vary between operating systems. Unix-based systems (like Linux and MacOS) use the newline character to indicate the end of a line, while Windows systems use a combination of a carriage return and a newline (`'\r\n'`).

2.2 ASCII

The American Standard Code for Information Interchange (ASCII) is one of the earliest character encodings. It uses 7 bits to represent each character, allowing it to define up to $2^7 = 128$ different characters. These include the English alphabet (in both lower and upper cases), digits, punctuation symbols, control characters (like newline and carriage return), and some other symbols.

2.3 UTF-8

UTF-8 (8-bit Unicode Transformation Format) is a variable-width character encoding that can represent every character in the Unicode standard, yet remains backward-compatible with ASCII. For the ASCII range (0-127), UTF-8 is identical to ASCII. However, it can use additional bytes (up to 4 bytes in total) to represent characters that are not included in ASCII, such as characters from other languages, emojis, and many other symbols. This has made UTF-8 a widely used encoding in many modern systems.

Answers to Exercises

Answer to Exercise 1 (on page 6)

```
1  <!DOCTYPE html>
2  <html>
3  <head>
4    <title>Chocolate Chip Cookies</title>
5  </head>
6  <body>
7    <h1 id="recipe-title">Chocolate Chip Cookies</h1>
8    <p class="intro" title="A short recipe description">
9      This recipe makes soft and sweet chocolate chip cookies.
10   </p>
11 </body>
12 </html>
```

Answer to Exercise 2 (on page 9)

```
1  <body>
2    <div class="recipe-header">
3      <h1 id="recipe-title">Chocolate Chip Cookies</h1>
4      <p class="intro" title="A short recipe description">
5        This recipe makes soft and sweet chocolate chip cookies.
6      </p>
7    </div>
8
9    <div class="ingredients-section">
10     <p>Ingredients</p>
11   </div>
12
13   <div class="steps-section">
14     <p>Steps</p>
15   </div>
16 </body>
```

Answer to Exercise 3 (on page 12)

```
1 <body>
2   <header>
3     <h1 id="recipe-title">Chocolate Chip Cookies</h1>
4     <p class="intro" title="A short recipe description">
5       This recipe makes soft and sweet chocolate chip cookies.
6     </p>
7   </header>
8
9   <main>
10    <section class="ingredients-section">
11      <p>Ingredients</p>
12    </section>
13
14    <section class="steps-section">
15      <p>Steps</p>
16    </section>
17  </main>
18
19  <footer>
20  </footer>
21 </body>
```

Answer to Exercise 4 (on page 13)

```
1 <main>
2   <section class="ingredients-section">
3     <h2 id="ingredients">Ingredients</h2>
4   </section>
5
6   <section class="steps-section">
7     <h2 id="steps">Steps</h2>
8   </section>
9 </main>
```

Answer to Exercise 5 (on page 15)

```
1 <footer>
2   <p><strong>Important Note:</strong> Make sure not to overbake the cookies, or
   ↳ they will become hard.</p>
```

```
3 </footer>
```

Answer to Exercise 6 (on page 19)

```
1 <section class="ingredients-section">
2   <h2 id="ingredients">Ingredients</h2>
3   <ul>
4     <li>2 1/4 cups flour</li>
5     <li>1 teaspoon baking soda</li>
6     <li>1 teaspoon salt</li>
7     <li>1 cup butter</li>
8     <li>3/4 cup sugar</li>
9     <li>3/4 cup brown sugar</li>
10    <li>2 eggs</li>
11    <li>2 cups chocolate chips</li>
12  </ul>
13 </section>
14
15 <section class="steps-section">
16   <h2 id="steps">Steps</h2>
17   <ol>
18     <li>Preheat the oven to 375°F.</li>
19     <li>Mix the dry ingredients in one bowl.</li>
20     <li>Mix the butter, sugar, brown sugar, and eggs in another bowl.</li>
21     <li>Stir the dry ingredients into the wet ingredients.</li>
22     <li>Add the chocolate chips.</li>
23     <li>Scoop the dough onto a baking sheet.</li>
24     <li>Bake for 9 to 11 minutes.</li>
25   </ol>
26 </section>
```

Answer to Exercise 7 (on page 21)

```
1 <header>
2   <h1 id="recipe-title">Chocolate Chip Cookies</h1>
3   <p class="intro" title="A short recipe description">
4     This recipe makes soft and sweet chocolate chip cookies.
5   </p>
6
7   <nav>
8     <ul>
9       <li><a href="#ingredients">Ingredients</a></li>
10      <li><a href="#steps">Steps</a></li>
11    </ul>
```

```
12     </nav>
13 </header>
```

Answer to Exercise 8 (on page 25)

```
1 <section>
2   <h2>Recipe Facts</h2>
3   <table border="1">
4     <caption>Chocolate Chip Cookie Recipe Facts</caption>
5     <tbody>
6       <tr>
7         <td>Prep Time</td>
8         <td>15 minutes</td>
9       </tr>
10      <tr>
11        <td>Bake Time</td>
12        <td>10 minutes</td>
13      </tr>
14      <tr>
15        <td>Servings</td>
16        <td>24 cookies</td>
17      </tr>
18    </tbody>
19  </table>
20 </section>
```

Answer to Exercise 9 (on page 30)

```
1 <header>
2   <h1 id="recipe-title">Chocolate Chip Cookies</h1>
3   <p class="intro" title="A short recipe description">
4     This recipe makes soft and sweet chocolate chip cookies.
5   </p>
6
7   <nav>
8     <ul>
9       <li><a href="#ingredients">Ingredients</a></li>
10      <li><a href="#steps">Steps</a></li>
11    </ul>
12  </nav>
13
14  
```

15

`</header>`



INDEX

ASCII, [33](#)

carriage return, [33](#)

HTML, [3](#)

- attributes, [3](#)

- div, [8](#)

- elements of, [3](#)

- forms, [26](#)

- headings, [12](#)

- images, [28](#)

- links, [16](#)

- lists, [16](#)

- metadata, [7](#)

- navigation, [20](#)

- semantic elements, [10](#)

- structure of, [4](#)

- tables, [22](#)

- text formatting, [14](#)

newline, [33](#)

text, [33](#)

UTF-8, [33](#)

Web Development

- HTML, [7](#)