

Other Graph Algorithms and Proofs

This chapter is an overview of other graph algorithms, proofs, and concepts that are important to know. We will first cover adjacency matrices, then Prim's algorithm for minimum spanning trees, isomorphism, and topological sorting for directed acyclic graphs (DAGs). A lot of these are very advanced graph theory topics, so you won't be tested on too heavily of these topics. Many of these appear on AP/IB exams, or in advanced college level CS classes.

1.1 Adjacency Matrices

Recall that we can represent graphs as lists of data called adjacency lists. In code, this could look like the following:

- A: [B, C]
- B: [A, D]
- C: [A]
- D: [B]

This represents the following graph




Figure 1.1: A simple (undirected unweighted) graph used to make an adjacency list and adjacency matrix.

We could also represent the same data as a *matrix*, which we have covered in linear algebra. The *adjacency matrix* is 2D array (as compared to an adjacency list, which consists of multiple 1D arrays) where $\text{matrix}[i][j]$ indicates whether an edge exists from vertex i to vertex j . Commonly, $\text{matrix}[i][j] = 1$ if and only if the edge from vertex i to vertex j exists, else $\text{matrix}[i][j] = 0$.¹ The above graph in Figure 1.1 can be represented as:

$$A = \begin{bmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \end{bmatrix}$$

For *undirected* graphs, the adjacency matrix is symmetric, and thusly $n \times n$, meaning that the transpose of matrix is the same matrix!

$$A = A^T$$




Figure 1.2: A simple graph with an added loop on vertex D.

By convention, a diagonal entry such as $\text{matrix}[k][k]$, where $(k \in \mathbb{Z})$, is non-zero only if there is a loop from a vertex to itself. The value of the entry represents the number of such loops. In this case, there are two edges from vertex (D) to itself in Figure 1.2, so the corresponding diagonal entry is (2).

For *directed* graphs, the adjacency matrix appears a bit different. A *directed adjacency matrix* represents a directed graph, where edges have a direction (arrows). When $A_{ij} = 1$, then an edge exists from vertex i to vertex j .

¹If the edges are weighted, the $\text{matrix}[i][j]$ is equal to the weight, or 0 if the edge does not exist.




Figure 1.3: A simple directed graph used to make an adjacency matrix.

The resulting adjacency matrix is

$$A = \begin{bmatrix} 0 & 1 & 1 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Notice how, now, $A \neq A^T$, because the edges are directional.

Exercise 1 Adjacency Matrix Exercise

Working Space

The following is an adjacency matrix for a weighted (undirected) graph.

	A	B	C	D	E	F	G
A	0	4	2	0	0	0	0
B	4	0	1	5	0	0	0
C	2	1	0	8	10	0	0
D	0	5	8	0	2	6	0
E	0	0	10	2	0	3	7
F	0	0	0	6	3	0	4
G	0	0	0	0	7	4	0

Draw the corresponding graph with weighted edges.

Answer on Page 11

1.2 Prim's Algorithm and Kruskal's Algorithm for Minimum Spanning Trees

Prim's Algorithm is minimum spanning tree

FIXME <https://github.com/KontinuaFoundation/sequence/issues/315>

1.3 A* (A-star) Search Algorithm

The last shortest path we will discuss in this chapter is the *A-star Algorithm*, more commonly represented as *A* Algorithm*. In essence, it is an extension of Dijkstra's Algorithm in combination with a *priority-based heuristic function*. A heuristic is an introduced estimated cost from any node to the goal.

The key behind this implementation is the following function

$$f(n) = g(n) + h(n)$$

where

- $g(n)$: the cost of the path from the start node (usually S) to the current node n
- $h(n)$: the *heuristic* function that estimates the remaining cost from n to the goal (usually E)
- $f(n) = g(n) + h(n)$: the estimated total cost of a path from S to E passing through node n

1.3.1 The Path Cost $g(n)$

$g(n)$ remains to be the same value that we used in Dijkstra's and other shortest path algorithms.

When moving from a node u to an adjacent node v , the path cost is *updated* as

$$g(v) = g(u) + c(u, v)$$

where $c(u, v)$ is the cost of traversing the edge from u to v . As we discussed in the chapter on Dijkstra's, we have a decision to make upon each visit to a node: Each time we visit a node, we have a decision to make:

$$\text{if } \text{dist}[u] + w(u, v) < \text{dist}[v] \text{ then update } \text{dist}[v]$$

1.3.2 The Heuristic Function $h(n)$

The heuristic $h(n)$ function depends on the problem domain. Its purpose is to estimate the remaining cost from node n to the goal. While this is a difficult task, we can use basic algebra to make an informed guess.

For example, in a map-based pathfinding problem, $h(n)$ may be the straight-line distance, or *Euclidean distance* between node n and the goal. Since the actual path cannot be shorter than the Euclidean distance, this provides a reasonable estimate of the remaining cost. If a node's location is represented on a 2D plane (such as a map or graph) (x_n, y_n) and the goal location as (x_g, y_g) , the Euclidean Heuristic

$$h(n) = \sqrt{(x_g - x_n)^2 + (y_g - y_n)^2}$$

Alternatively, many 2D games use a similar either *taxicab distance* (typically for 4-way movement),

$$h(n) = |x_g - x_n| + |y_g - y_n|$$

or *Chebyshev distance* (typically for 8-way movement in a game)

$$d = \max(|x_2 - x_1|, |y_2 - y_1|)$$

which takes the maximum of the horizontal and vertical movements.

Sometimes, graphs without direct spatial meaning become more difficult to work with because there is no obvious notion of distance between two nodes.

For general graphs, such as social networks, communication networks, or dependency graphs, the heuristic must be derived from problem-specific knowledge. For example, a social network application might use information such as mutual connections, community membership, or other metadata to estimate how *close* a user is to a target user.

In many cases, however, no suitable heuristic is known. In these situations, the heuristic is often defined as

$$h(n) = 0$$

for all nodes n . Substituting this into the A* evaluation function gives

$$f(n) = g(n)$$

which causes A* to reduce to Dijkstra's algorithm. While this guarantees an optimal path, it loses the efficiency gains that a good heuristic can provide.

There is an important property that the Heuristic Function must satisfy:

$$h(n) \leq \text{true remaining cost}$$

When an admissible heuristic is used (such that $h(n) \leq \text{true remaining cost}$), A* is guaranteed to find an optimal path if one exists.

1.3.3 The Total Estimated Distance $f(n)$ and Priority Queues

The purpose of the function

$$f(n) = g(n) + h(n)$$

is to assign a priority to each node during the search. Recall from our discussion of priority queues that each element is associated with a priority value, and the element with the highest (or lowest) priority is removed first.

In A^* , the priority of a node is its estimated total distance $f(n)$. Nodes with smaller values of $f(n)$ are considered more promising because they represent paths that appear likely to reach the goal with a lower total cost.

As with Dijkstra's algorithm, A^* maintains a priority queue containing nodes that have been discovered but not yet fully explored. However, instead of prioritizing nodes solely by their known distance from the start node, A^* prioritizes nodes according to their estimated total distance

$$\text{priority}(n) = f(n)$$

At each step, the node with the smallest $f(n)$ value is removed from the priority queue and explored. When a neighboring node is discovered, its path cost $g(n)$ is updated, a new heuristic estimate $h(n)$ is calculated, and a new value of $f(n)$ is computed.

There are some good references about this in your digital resources, as well as a fun Minecraft-based explanation [here](#).

1.4 Injection, Surjection, Bijection, and Isomorphism

Let's talk about Graph Isomorphism. To do this, we must first introduce the terms of *injection*, *surjection*, and *bijection*. These are types of functions in set theory as well as mathematics.

Definition 1 (Injection). *A function $f : A \rightarrow B$ is injective if different inputs always produce different outputs. Importantly, this means no two integers map to the same output.*

Definition 2 (Surjection). *A function $f : A \rightarrow B$ is surjective if every element of B is hit by at least one element of A . In essence, all of the elements of B are covered.*

Definition 3 (Bijection). *A function $f : A \rightarrow B$ is bijective if it is both injective and surjective. Ultimately, the function creates no collisions and hits all functions of B .*

Exercise 2 Bijective, Surjective, Injective Exercise

Determine whether each function is injective, surjective, bijective, or none of these.

Working Space

1. $f : \{1, 2, 3\} \rightarrow \{a, b, c, d\}$ defined by

$$f(1) = a, \quad f(2) = b, \quad f(3) = c.$$

2. $g : \{1, 2, 3, 4\} \rightarrow \{a, b, c\}$ defined by

$$g(1) = a, \quad g(2) = b, \quad g(3) = c, \quad g(4) = a.$$

3. $h : \{1, 2, 3\} \rightarrow \{a, b, c\}$ defined by

$$h(1) = b, \quad h(2) = c, \quad h(3) = a.$$

Answer on Page 11

Now, let's talk about *Isomorphism*. A *graph isomorphism* is a bijection between the vertex sets of two graphs that preserves adjacency. Thus, an isomorphism not only matches vertices one-to-one, but also preserves the structure of the graph.

Definition 4 (Graph Isomorphism). Let $G = (V_G, E_G)$ and $H = (V_H, E_H)$ be graphs. An isomorphism from G to H is a bijection

$$f : V_G \rightarrow V_H$$

such that for all vertices $u, v \in V_G$,

$$\{u, v\} \in E_G \iff \{f(u), f(v)\} \in E_H.$$

If such a function exists, we say that G and H are isomorphic and write

$$G \cong H.$$




Figure 1.4: Two graphs that are isomorphic. Graph G (left) and Graph H (right).

We are able to say that these graphs (Figure 1.4) are isomorphic as one vertex from G can be paired with one vertex from H, while maintaining the same edge connections.




Figure 1.5: Graph X and Y; not isomorphic.

In Figure 1.5, we can see the vertices are not isomorphic without adding or subtracting edges. For example, Graph X does not have a vertex with 3 edges, unlike Graph Y.

If any of these differ, the graphs are not isomorphic:

- Number of vertices
- Number of edges
- Degree sequence (if degree sequences are intact, it does not guarantee isomorphism)
- Number of connected components
- Number of cycles of a given length
- Chromatic number

Example.

A common example that you will not be tested on but is important to know is the following. We may need to introduce a definition first.

Definition 5 (Clique). *A clique is a set of vertices in a graph such that every pair of distinct vertices is connected by an edge.*

Definition 6 (Clique Subgraph). *A k -clique is exactly a subgraph isomorphic to the complete graph K_k . A 3-clique would be a clique of size 3, called K_3 .*

Now, given two graphs G and H , how can we determine G contain a subgraph isomorphic to H , a graph of smaller to equal size to G ?

This may be easy if G and H are pretty small, but the math becomes infinitely harder as the number of vertices and edges go up.

We can simplify this by transforming the inputs of a clique problem to inputs of the subgraph isomorphism problem.

The clique problem gives us a graph M and a threshold k . The output of this is whether M contains a clique of size at least k .

To transform this into an instance of the subgraph isomorphism problem, construct a smaller subgraph $H = K_k$, the complete graph on k vertices, and let $G = M$, the larger graph.

We now ask the subgraph isomorphism question:

Does G contain a subgraph isomorphic to H ?

Since H is the complete graph K_k , a subgraph of G isomorphic to H must contain k vertices where every pair of vertices is connected by an edge. By definition, this is exactly a k -clique.

Therefore,

M contains a k -clique $\iff G$ contains a subgraph isomorphic to K_k .

This shows that every instance of the Clique problem can be transformed into an instance of the Subgraph Isomorphism problem.

1.5 Travelling Salesperson Problem and Nearest Neighbour


1.6 Topological Sort and DAGs

1.7 Proofs

This is a draft chapter from the Kontinua Project. Please see our website (<https://kontinua.org/>) for more details.

Answers to Exercises

Answer to Exercise 1 (on page 3)



Answer to Exercise 2 (on page 7)

1. Injective, but not surjective. No two inputs map to the same output, but d is never

reached.

2. Surjective, but not injective. Every element of the codomain is reached, but both 1 and 4 map to a .
3. Bijective. Every element of the codomain is reached exactly once.



INDEX

A* Algorithm, 4
A-star Algorithm, 4
adjacency matrix, 2

bijection, 6

Chebyshev distance, 5

directed adjacency matrix, 2

Euclidean distance, 5

graph isomorphism, 7

heuristic, 4

injection, 6
Isomorphism, 7

matrix, 2

surjection, 6

taxicab distance, 5