

# 1204315 - Wireless Mobile Application Programming

Manasawee Kaenampornpan


มนัสวี แก่นอำพรพันธ์

manasaweek@gmail.com

Maharakham University


# Segue

## A Simplified Map of Segues and Delegates for Swift




<http://www.MakeAppPie.Com>


# Create single view project




# เพิ่ม Editor->Embed In->Navigation Controller





# เพิ่ม Navigation Bar




# เพิ่ม Label



# เพิ่ม Bar Button ที่มุมบน



# Connect Label to viewController





# ลบ โค้ด ให้เหลือแค่ viewDidLoad

```
import UIKit

class ViewController: UIViewController {

    @IBOutlet weak var colorLabel: UILabel!

    override func viewDidLoad() {
        super.viewDidLoad()
        // Do any additional setup after loading the view,
        typically from a nib.
    }

    override func didReceiveMemoryWarning() {
        super.didReceiveMemoryWarning()
        // Dispose of any resources that can be recreated.
    }

}
```

# จะได้

```
import UIKit


class ViewController: UIViewController {

    @IBOutlet weak var colorLabel: UILabel!

    override func viewDidLoad() {
        super.viewDidLoad()
        // Do any additional setup after loading the view,
        typically from a nib.
    }

}
```

# สร้าง Cocoa Touch Class ที่เป็น subclass ของ UIViewController จาก *File->New->File...*



# ลบ โค้ด ให้เหลือแค่ viewDidLoad

```
import UIKit

class ColorTwoViewController: UIViewController {

    override func viewDidLoad() {
        super.viewDidLoad()

        // Do any additional setup after loading the view.
    }

    override func didReceiveMemoryWarning() {
        super.didReceiveMemoryWarning()
        // Dispose of any resources that can be recreated.
    }

    /*
    // MARK: - Navigation

    // In a storyboard-based application, you will often
    want to do a little preparation before navigation
    override func prepareForSegue(segue: UIStoryboardSegue!,
    sender: AnyObject!) {
        // Get the new view controller using
        segue.destinationViewController.
        // Pass the selected object to the new view
        controller.
    }
    */
}
```

# จะได้

```
import UIKit

class ColorTwoViewController: UIViewController {




    override func viewDidLoad() {
        super.viewDidLoad()

        // Do any additional setup after loading the view.
    }


    /*
    // MARK: - Navigation

    // In a storyboard-based application, you will often
    want to do a little preparation before navigation
    override func prepareForSegue(segue: UIStoryboardSegue!,
        sender: AnyObject!) {
        // Get the new view controller using
        segue.destinationViewController.
        // Pass the selected object to the new view
        controller.
    }
    */
}
```


# สร้าง New View Controller



# Ctrl-ลากจาก Color Button ไปหา new Controller เพื่อเพิ่ม Segue




# Set identifier เป็น mySegue








# ใน identity inspector set Custom Class ให้เป็น ColorTwoViewController




# เพิ่ม Navigation Bar



# เพิ่ม Bar Button item -> Save




# เพิ่ม Label และปุ่ม Red Green Blue ดังรูป




# เพิ่ม outlet

- colorLabel
- titleLabel




# เพิ่ม Action

- saveColor set Type UIBarButtonItem
- colorSelectionButton เลือก 3 ปุ่ม Red Green Blue พร้อมกัน set UIButton



```
// Created by Jay on  
10/17/2557 BE.  
// Copyright (c) 2557 Jay.  
// All rights reserved.  
  
import UIKit  
protocol  
ColorTwoViewControllerDel  
egate{  
func myVCDidFinish  
(controller:  
ColorTwoViewControlle  
r,text:String)  
}  
  
class ColorTwoViewController:  
UIViewController {  
  
var delegate:  
ColorTwoViewControlle  
rDelegate? = nil  
  
var colorString = ""  
  
@IBOutlet weak var  
colorLabel: UILabel!  
  
@IBOutlet weak var  
titleLabel: UILabel!  
  
@IBAction func  
colorSelectionButton  
(sender: UIButton) {  
colorLabel.text =  
sender.  
titleLabel!.  
text!  
}  
  
@IBAction func saveColor  
(sender:  
UIBarButtonItem) {  
if (delegate != nil)  
{  
delegate!.  
myVCDidFinish  
(self, text:
```



```
// Created by Jay on  
10/17/2557 BE.  
// Copyright (c) 2557 Jay.  
// All rights reserved.  
  
import UIKit  
protocol  
ColorTwoViewControllerDel  
egate{  
func myVCDidFinish  
(controller:  
ColorTwoViewControlle  
r,text:String)  
}  
  
class ColorTwoViewController:  
UIViewController {  
  
var delegate:  
ColorTwoViewControlle  
rDelegate? = nil  
  
var colorString = ""  
  
@IBOutlet weak var  
colorLabel: UILabel!  
  
@IBOutlet weak var  
titleLabel: UILabel!  
  
@IBAction func  
colorSelectionButton  
(sender: UIButton) {  
colorLabel.text =  
sender.titleLabel!  
!.text!
```

# เพิ่มโค้ดใน action และ viewDidLoad

```
import UIKit
protocol ColorTwoViewControllerDelegate{
    func myVCDidFinish(controller:ColorTwoViewController,text:String)
}

class ColorTwoViewController: UIViewController {

    var delegate:ColorTwoViewControllerDelegate? = nil

    var colorString = ""

    @IBOutlet weak var colorLabel: UILabel!

    @IBOutlet weak var titleLabel: UILabel!

    @IBAction func colorSelectionButton(sender: UIButton) {
        colorLabel.text = sender.titleLabel!.text!
    }

    @IBAction func saveColor(sender: UIBarButtonItem) {
        if (delegate != nil) {
            delegate!.myVCDidFinish(self, text: colorLabel!.text!)
        }
    }

    override func viewDidLoad() {
        super.viewDidLoad()

        // Do any additional setup after loading the view.
        colorLabel.text = colorString
    }
}
```

# เพื่อส่งค่าระหว่าง View เพิ่มโค้ดใน ViewController

```
import UIKit

class ViewController: UIViewController, ColorTwoViewControllerDelegate {
    @IBOutlet var colorLabel : UILabel!
    override func viewDidLoad() {
        super.viewDidLoad()
        // Do any additional setup after loading the view, typically from a nib.
    }
    func myVCDidFinish(controller: ColorTwoViewController, text: String) {
        colorLabel.text = "Co: " + text
        controller.navigationController?.popViewControllerAnimated(true)
    }
    override func prepareForSegue(segue: UIStoryboardSegue, sender: AnyObject!) {
        if segue.identifier == "mySegue"{
            let vc = segue.destinationViewController as ColorTwoViewController
            vc.colorString = colorLabel.text!
            vc.delegate = self
        }
    }
}
```



# เพื่อส่งค่าระหว่าง View เพิ่มโค้ดใน ColorTwoViewController

```
import UIKit
protocol ColorTwoViewControllerDelegate{
    func myVCDidFinish(controller:ColorTwoViewController,text:String)
}

class ColorTwoViewController: UIViewController {

    var delegate:ColorTwoViewControllerDelegate? = nil

    var colorString = ""

    @IBOutlet weak var colorLabel: UILabel!

    @IBOutlet weak var titleLabel: UILabel!

    @IBAction func colorSelectionButton(sender: UIButton) {
        colorLabel.text = sender.titleLabel!.text!
    }

    @IBAction func saveColor(sender: UIBarButtonItem) {
        if (delegate != nil) {
            delegate!.myVCDidFinish(self, text: colorLabel!.text!)
        }
    }

    override func viewDidLoad() {
        super.viewDidLoad()

        // Do any additional setup after loading the view.
        colorLabel.text = colorString
    }
}
```

# เพื่อส่งค่าระหว่าง View เพิ่มโค้ดใน ViewController

```
import UIKit
```

```
class ViewController: UIViewController, ColorTwoViewControllerDelegate {  
    @IBOutlet var colorLabel : UILabel!  
    override func viewDidLoad() {  
        super.viewDidLoad()  
        // Do any additional setup after loading the view, typically from a nib.  
    }  
    func myVCDidFinish(controller: ColorTwoViewController, text: String) {  
        colorLabel.text = "Co: " + text  
        controller.navigationController?.popViewControllerAnimated(true)  
    }  
    override func prepareForSegue(segue: UIStoryboardSegue, sender: AnyObject!) {  
        if segue.identifier == "mySegue"{  
            let vc = segue.destinationViewController as ColorTwoViewController  
            vc.colorString = colorLabel.text!  
            vc.delegate = self  
        }  
    }  
}
```

# References

- <http://makeapppie.com/2014/07/01/swift-swift-using-segues-and-delegates-in-navigation-controllers-part-1-the-template/>