

ProSoft v8.4.11 System Configuration Guide

This document includes ProSoft proprietary or confidential information and may not be redistributed or disclosed without prior written permission.

All information herein is provide "AS IS" based on the state of the ProSoft system as of the release date. ProSoft reserves the right to make changes to this document without prior notice.

Disclaimer

NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, IS MADE IN RELATION TO THE CONTENTS OF THIS DOCUMENT REGARDING INCLUDING BUT NOT LIMITED TO AVAILABILITY, ACCURACY, RELIABILITY, NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR A PURPOSE. IN NO EVENT SHALL PROSOFT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO DIRECT, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, OR DUE TO BUSINESS INTERRUPTION, OR ANY LOSS OF PROFIT, REVENUE, BUSINESS OPPORTUNITY, OR DATA THAT MAY ARISE FROM THE USE OF THE INFORMATION IN THIS DOCUMENT.

Copyright

ProSoft is registered trademark of ProSoft Corporation. Other products mentioned in this document may be trademarks of their respective owners.

© ProSoft 2024.

Table of Contents

- [About this guide](#)
- [Preliminary tasks](#)
 - [Server requirements](#)
 - [Networking](#)
 - [Licenses and certificates](#)
- [Configuration](#)
 - [Using the GUI](#)
 - [Using a CLI](#)
- [System administration](#)
 - [Availability and provisioning](#)
 - [Troubleshooting](#)
 - [Decommissioning](#)

About this guide

This guide was prepared to aid administrators in installing, configuring, administrating, and troubleshooting the software system.

Preliminary tasks

In order for the installation procedure to continue without any errors or interruption, the servers to be used for the installation, the network devices to be used to access the server and the clients, and the licenses and

certificates required to use the software system must be ready. To meet these prerequisites, follow the instructions below.

Server requirements

The system has to be installed on a server that meets the following minimum hardware requirements:

- 7 quad-core 64-bit AMD processors
- 128 GB RAM
- A 2 TB SSD
- 2 x 1 TB SCSI hard drives for redundancy

Networking

Since the system will be accessed over a network, the following must be in place:

- A 1000BASE-T (i.e. gigabit) Ethernet
- A proxy to manage the server traffic listening on port 9595
- TCP/IP protocol in place on the server

Licenses and certificates

During the installation of the system, licenses and certificates will be required for the system to validate the installation and give access to administrative users. Make sure

- the licenses (i.e. the 2 *.lic files) are in the root directory where the server is to be installed
- the authentication certificates are in the ./cert directory under the root

Configuration

The system's configuration involves making the correct settings required by the server. This can be done either through the GUI or the CLI.

Using the GUI

This involves using the application's Administration Console.

- Double click the **ProSoft** icon on the desktop to launch the console
- In the console window, pick the **Tools > Settings** menu item. A window will pop up
- In the **Settings** window, various settings can be found grouped according to the functionality they are related to:
 - The **Users** group on the left is where you can add or remove users, set their credentials and the security groups they belong to, and assign them the directories under which the resources managed by **ProSoft®** are located
 - The **Resources** group in the middle is for setting the directories the system uses to store various resources it generates and manages
 - The **System** group on the right is for assigning the various values the system uses as defaults for marshalling and managing its data

Using the CLI

This involves running certain scripts—found in the .\admin directory under the root—through the command line. The script to be run depends on the settings to be configured.

- Launch a terminal with elevated (i.e. **admin**) privileges
- On the command line, navigate to the root directory

```
C:\>cd \ProSoft\admin  
C:\ProSoft\admin>
```

- At this point, you should have the licenses (the *.lic files) under the root—i.e. the C:\ProSoft\ directory—and the certificates (the *.cert files) under the C:\ProSoft\admin\ directory. Run the script named sys_config.ps and check the output messages

```
C:\>ProSoft\admin\sys_config.ps  
>> Configuring system...  
>> Licenses discovered...  
>> Certificates discovered...  
>> Disks partitioned: 100%  
>> Indexes created  
>> Done  
C:\>ProSoft\admin
```

- If any of these messages do not appear, you should suspend the configuration procedure and troubleshoot. For this, see the [Troubleshooting](#) section below
- After the script has completed, you can exit the terminal

System initialization

The system has to be initialized as follows.

- Open a terminal with elevated privileges and navigate to the root directory
- Run the sys_init.ps script

System administration

The system provides a number of facilities some of which cannot be offered unattended. For this, the system administrator has to perform the following tasks.

Availability and provisioning

Availability is measured based on the following criteria:

- The purchased number of seats with the license
- How many seats have been provisioned
- Whether the provisioned seat and the resources available to it are accessible via the network and using the assigned credentials

To provide seats to users, the following procedure must be used:

- Using the **Properties** menu, open the **Seats** window
- Check the number of seats used on the left panel. If there are none left, you have to purchase additional seats

- Check the group the user is a member of to see whether it matches the use properties of the available seats
- Assign the user to the seat by filling in his credentials in the middle panel
- Finally, click on the **Provision** button on the bottom right of the window

Troubleshooting

Troubleshooting is an essential part of system maintenance. All troubleshooting must be done with the following general procedure:

- Check the error code, error message, and core-dump if any
- Find the error code in the lookup table attached to this guide
- Follow the instructions for diagnosing the root cause of the problem

Decommissioning

If for some reason the system fails to meet your needs, there are a number of steps to decommission the system:

- Running the `.\admin\decomm_sys.ps` script to gather information on what should be backed up
- Backing up the legacy data based on the generated report
- Releasing the certificates
- Removing the licenses
- Uninstalling the software