

Capital.com Public API (1.0.0)

The Capital.com API allows direct access to the latest version of our trading engine.

General information

- Base URL: <https://api-capital.backend-capital.com/>
- Base demo URL: <https://demo-api-capital.backend-capital.com/>
- In order to use the endpoints a session should be launched. This can be done using the `POST /session` endpoint.
- Session is active for 10 minutes. In case your inactivity is longer than this period then an error will occur upon next request.
- The API covers the full range of available instruments, licences and trading functionality.

Getting started

To use the API the following simple steps should be taken:

- **Create a trading account**
Note that a demo account can be used.
- **Turn on Two-Factor Authentication (2FA)**
2FA should be turned on prior to API key generation. [Instruction for 2FA enabling](#).
- **Generate an API key**
To generate the API key, go to Settings > API integrations > Generate new key. There you will need to enter the label of the key, set the custom password for it and an optional expiration date, enter the 2FA code and that's it.
- **You are all set!**

Available functionality

Market data

- Receive real-time prices for the whole range of available assets with the REST and WebSocket API.
- Get the price history for the whole range of assets.

Trading functionality

- Open positions, set stop and limit orders, set stop loss and take profit levels.
- Review and change financial account settings (trading modes, leverage sizes).
- Review trades and orders history.

Examples and collections

- Postman collection: <https://github.com/capital-com-sv/capital-api-postman>
- Trading bot based on the RSI indicator values: <https://github.com/capital-com-sv/api-java-samples>

Changelog

November 28, 2023

- Added an opportunity to adjust the balance of the Demo account using the `POST /accounts/topUp` endpoint

October 05, 2023

- Limit of 1 request per second is set for the `POST /session` endpoint.

August 04, 2023

- Added an opportunity to view the whole list of available markets using the `GET /markets` endpoint

July 04, 2023

- Set maximum date range for parameters `from`, `to`, `lastPeriod` to 1 day for the `GET /history/activity`

March 23, 2022

- Limit of 1000 requests per hour is set for the `POST /positions` and `POST /workingorders` in Demo.

March 16, 2022

- WebSocket API endpoints added to Swagger documentation.

February 10, 2022

- Release of the first version of the REST and WebSocket API.

Authentication

How to start new session?

There are 2 ways to start the session:

- Using your API key, login and password details.
- Using your API key, login and encrypted password details.

Using your API key, login and password details

Using your API key, login and encrypted password details

- ### Encryption request example:

Encrypted password example:

Seite 4 von 89

After starting the session

On starting the session you will receive the `CST` and `X-SECURITY-TOKEN` parameters in the response headers. `CST` is an authorization token, `X-SECURITY-TOKEN` shows which financial account is used for the trades. These headers should be passed on subsequent requests to the API. Both tokens are valid for 10 minutes after the last use.

Symbology

- **Financial accounts**

`accountId` is the ID of your financial account. Each financial account has its unique ID. To view the full list of the available financial accounts, use the `GET /accounts` endpoint. To find out which financial account is used for trading operations in the API please go to the `GET /session` endpoint. To change the financial account use: `PUT /session`.

- **Epic**

Epic is the name of the market pair. You can use the `GET /markets{?searchTerm}` endpoint to find the market pairs you are interested in. A simple market name like 'Bitcoin' or 'BTC' can be requested with the `searchTerm` parameter and you will receive the full list of the market pairs associated with it. The `GET /marketnavigation` endpoint can be used to obtain asset group names. These names can be used with the `GET /marketnavigation/{nodeId}` endpoint to view the list of assets under the corresponding group.

- **Watchlists**

The Watchlist is the list of assets which can be seen and created on the platform. The `GET /watchlists` endpoint returns the existing watchlists on your account. Each watchlist has an `id` parameter which can be used to obtain the corresponding list of assets: `GET /watchlists/{watchlistId}`

Orders and positions

- When opening a position using the `POST /positions` endpoint a `dealReference` parameter is included in the response. However, a successful response does not always mean

that the position has been successfully opened. The status of the position can be confirmed using `GET /confirms/{dealReference}`. This will produce the status of the position together with the `affectedDeals` array. Note that several positions can be opened at a time: this info will be shown in the `affectedDeals` array.

- It is important to ensure that the correct trading mode is in use with the API. To find out which trading mode is set on your financial account use the `GET /accounts/preferences` method. The `hedgingMode` parameter value shows whether the hedging mode is engaged. This value can be altered using endpoint: `PUT /accounts/preferences`.
- The leverages set for trades can be obtained using the `GET /accounts/preferences` endpoint. To change leverages, use `PUT /accounts/preferences`.
- Note: Stop loss and take profit values cannot be set when conducting trades with real stocks.

FAQ

Which kind of APIs do you have?

On Capital.com we suggest both REST and WebSocket API. In case of WebSocket API real-time prices updates for max 40 instruments at a time.

Do you have any limitations on your API?

Yes, we do have several limitations in our Capital.com API. Here is the list:

- You have max **100 attempts per 24hrs** to successfully generate API keys.
- The maximum request rate is **10 per second** per user.
- The maximum request rate is **1 per 0.1 seconds** per user when opening positions or creating orders. Otherwise the position/order requests are going to be rejected.
- WebSocket session duration is **10 minutes**. In order to keep the session live use the ping endpoint.
- REST session is also active for **10 minutes**. In case your inactivity is longer than this period then an error will occur upon next request.

- `POST /session` endpoint limit is **1 request per second** per API key.
- `POST /positions` and `POST /workingorders` endpoint limit is **1000 requests per hour** in the Demo account.
- `POST /accounts/topUp` endpoint limits: **10 requests per second** and **100 requests per account per day**.
- The balance of the Demo account cannot exceed 100000.
- The WebSocket API allows subscription to a maximum of **40 instruments**.
- WebSocket streaming falls off when the financial account is changed with the help of the `PUT /session` endpoint.

Does your API support all the instruments?

Yes, Capital.com API supports all of the instruments which you can find on the platform.

How to start using Capital.com API?

In order to start using our Capital.com API you should first of all generate an API key in the `Settings` > `API integrations` section on the platform. Upon doing so you will be able to use this key and your account credentials to authorise for the API usage with the `POST /session` method.

Can I use Capital.com API on the Demo account?

Sure. In order to use your Demo account with our API you should mention the following service as Base URL: <https://demo-api-capital.backend-capital.com/>

How to generate an API key?

In order to generate an API Key you should log in to your account, go to the `Settings` > `API`

`integrations` section and click on the `Generate API key` button.

In case your 2FA is turned off you will be asked to switch on this function to ensure safe and secure keys usage.

Next you will be presented with the `Generate new key` window where you will be able to name your API Key, add an API key password and set an expiration date (if needed). By default the validity of the API key is 1 year.

After that you should enter your 2FA code and wait for an API Key to be generated. Once an API Key is generated you will see an API Key itself. Please, make sure to save this data as it is shown only once.

Congratulations. You should have successfully managed to integrate our API functionality. In case you have any questions - feel free to contact us (support@capital.com). We will be glad to help you.

Which kind of API Key privileges can I have?

Currently we have only 1 type of the API Keys privileges which allows trading. No Read Only API Keys can be generated.

What does a Custom password field mean during the API key generation process?

A `Custom password` field allows you to generate a separate password for your API key. You should use this `Custom password` for the API key in order to start the session.

How can I pause or launch an API key?

In order to pause or launch an API key you can click on the `Pause` or `Play` icons next to the API key in the `Settings` > `API integrations` section. This functionality allows you to either disable or enable a key when you need to do it without deleting a key itself and re-generating a new one.

How can I view more information about the API key?

In order to view more information about the API key you have generated please click on an **Eye** icon next to the key in the **Settings** > **API integrations** section.

I don't see my API Key. What could have happened?

There are 2 reasons for your API Key to be deleted:

- your account status has changed to either **SUSPENDED** or **BLOCKED**;
- your API Key has reached an expiration date.

In all other cases your API Keys should work as expected.

I see "*****" instead of my API Key. How can I find a full API Key information?

According to the existing procedure the only moment you can see your API Key is during its creation. After that it will always be masked.

In case you have lost your API Key or didn't record it, you will have to create a new one and make sure that you store a new key in a secure place.

WebSocket API

In order to start using WebSocket connect to **wss://api-streaming-capital.backend-capital.com/connect**.

In order to keep the connection alive, ping service at least once every 10 minutes.

More information regarding the WebSocket API requests and responses parameters can be found in the table below:

Parameter	Description
destination	The subscription destination which performs as an analogue for the request endpoint in the REST API model.
correlationId	Is set to understand for which request the message was received. Helps to track the correlation between the subscription destination and response.
cst	Access token identifying the client. Can be received upon starting the session. Is equal to <code>CST</code> parameter.
securityToken	Account token or account id identifying the client's current account. Can be received upon starting the session. Is equal to <code>X-SECURITY-TOKEN</code> parameter.
payload	An object which contains the data regarding the corresponding markets.

Subscribe to market data

Destination: `marketData.subscribe`

Subscribe to the price updates by mentioning the epics
The maximum number of epics: 40

Request message example:

```
{
  "destination": "marketData.subscribe",
  "correlationId": "1",
  "cst": "zvKT26****nsHKk",
  "securityToken": "g6K90****QKvCS7",
  "payload": {
    "epics": [
      "OIL_CRUDE"
    ]
  }
}
```

```
}
```

Example of the response message about successful subscription:

```
{
  "status": "OK",
  "destination": "marketData.subscribe",
  "correlationId": "1",
  "payload": {
    "subscriptions": {
      "OIL_CRUDE": "PROCESSED"
    }
  }
}
```

Example of the response message with market data updates:

```
{
  "status": "OK",
  "destination": "quote",
  "payload": {
    "epic": "OIL_CRUDE",
    "product": "CFD",
    "bid": 93.87,
    "bidQty": 4976.0,
    "ofr": 93.9,
    "ofrQty": 5000.0,
    "timestamp": 1660297190627
  }
}
```

Unsubscribe from market data

Destination: `marketData.unsubscribe`

Unsubscribe from the prices updates

Request message example:

```
{
  "destination": "marketData.unsubscribe",
  "correlationId": "2",
  "cst": "zvkt26****nsHKk",
  "securityToken": "g6K90****QKvCS7",
  "payload": {
    "epics": [
      "OIL_CRUDE"
    ]
  }
}
```

Example of the response message about successful unsubscription:

```
{
  "status": "OK",
  "destination": "marketData.unsubscribe",
  "correlationId": "2",
  "payload": {
    "subscriptions": {
      "OIL_CRUDE": "PROCESSED"
    }
  }
}
```

Subscribe to OHLC market data

Destination: `OHLCMarketData.subscribe`

Subscribe to the candlestick bars updates by mentioning the epics, resolutions and bar type

List of request payload parameters:

Parameter	Format	Required?	Description
epics	string[]	YES	The list of instruments epics Notes:

			- Max number of epics is limited to 40
resolutions	string[]	NO	The list of resolutions of requested prices Notes: - Default value: <code>MINUTE</code> - Possible values: <code>MINUTE</code>, <code>MINUTE_5</code>, <code>MINUTE_15</code>, <code>MINUTE_30</code>, <code>HOURL</code>, <code>HOURL_4</code>, <code>DAY</code>, <code>WEEK</code>
type	string	NO	Type of candlesticks Notes: - Default value: <code>classic</code> - Possible values: <code>classic</code>, <code>heikin-ashi</code>

Request message example:

```
{
  "destination": "OHLMarketData.subscribe",
  "correlationId": "3",
  "cst": "zvkt26****nsHKk",
  "securityToken": "g6K90****QKvCS7",
  "payload": {
    "epics": [
      "OIL_CRUDE",
      "AAPL"
    ],
    "resolutions": [
      "MINUTE_5"
    ],
    "type": "classic"
  }
}
```

Example of the response message about successful subscription:

```
{
  "status": "OK",
  "destination": "OHLMarketData.subscribe",
  "correlationId": "3",
  "payload": {
    "subscriptions": {
```

```
    "OIL_CRUDE:MINUTE_5:classic": "PROCESSED",
    "AAPL:MINUTE_5:classic": "PROCESSED"
  }
}
```

Example of the response message with market data updates:

```
{
  "status": "OK",
  "destination": "ohlc.event",
  "payload": {
    "resolution": "MINUTE_5",
    "epic": "AAPL",
    "type": "classic",
    "priceType": "bid",
    "t": 1671714000000,
    "h": 134.95,
    "l": 134.85,
    "o": 134.86,
    "c": 134.88
  }
}
```

Unsubscribe from OHLC market data

Destination: `OHLCMarketData.unsubscribe`

Unsubscribe from candlestick bars updates for specific epics, resolutions and bar types.

The general principle is as follows: you unsubscribe from the parameter you mention in the request. In case you mention epic you unsubscribe from all of the corresponding bar types and resolutions.

List of request payload parameters:

Parameter	Format	Required?	Description
epics	string[]	YES	The list of instruments epics to be unsubscribed

resolutions	string[]	NO	The list of price resolutions to be unsubscribed Notes: - Default value: All possible values - Possible values: <code>MINUTE</code>, <code>MINUTE_5</code>, <code>MINUTE_15</code>, <code>MINUTE_30</code>, <code>HOURL</code>, <code>HOURL_4</code>, <code>DAY</code>, <code>WEEK</code>
types	string[]	NO	Types of candlesticks to be unsubscribed Notes: - Default value: all possible values - Possible values: <code>classic</code>, <code>heikin-ashi</code>

Request message example:

```
// Unsubscribe from candlestick bars updates of OIL_CRUDE epic with MINUTE and
{
  "destination": "OHLCMarketData.unsubscribe",
  "correlationId": "4",
  "cst": "zvKT26****nsHKk",
  "securityToken": "g6K90****QKvCS7",
  "payload": {
    "epics": [
      "OIL_CRUDE"
    ],
    "resolutions": [
      "MINUTE",
      "MINUTE_5"
    ],
    "types": [
      "heikin-ashi"
    ]
  }
}
```

Example of the response message about successful unsubscription:

```
{
  "status": "OK",
  "destination": "OHLCMarketData.unsubscribe",
  "correlationId": "4",
```

```
"payload": {  
  "subscriptions": {  
    "OIL_CRUDE:MINUTE_5:heikin-ashi": "PROCESSED",  
    "OIL_CRUDE:MINUTE:heikin-ashi": "PROCESSED"  
  }  
}
```

Ping the service

Destination: `ping`

Ping the service for keeping the connection alive

Request message example:

```
{  
  "destination": "ping",  
  "correlationId": "5",  
  "cst": "zvkT26****nsHKk",  
  "securityToken": "g6K90****QKvCS7"  
}
```

Response message example:

```
{  
  "status": "OK",  
  "destination": "ping",  
  "correlationId": "5",  
  "payload": {}  
}
```

REST API

Find below the list of all available REST API endpoints

General

Get server time

Test connectivity to the API and get the current server time

Authentication is not required for this endpoint

Responses

> 200 OK

GET

/api/v1/time



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
import http.client

conn = http.client.HTTPSConnection("api-capital.backend-capital.com")
payload = ''
headers = {}
conn.request("GET", "/api/v1/time", payload, headers)
res = conn.getresponse()
data = res.read()
print(data.decode("utf-8"))
```

Response samples

200**Content type**

application/json

Copy

```
{
  "serverTime": 1649259764171
}
```

Ping the service

Ping the service to keep a trading session alive

HEADER PARAMETERS

X-SECURITY-TOKEN	string
Example:	ENTER_OBTAINED_SECURITY_TOKEN
	Account token or account id identifying the client's current account
CST	string
Example:	ENTER_OBTAINED_CST_TOKEN
	Access token identifying the client

Responses

> 200 OK**GET** /api/v1/ping

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/ping", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy

```
{
  "status": "OK"
}
```

Session

Encryption key

Get the encryption key to use in order to send the API key password in an encrypted form

HEADER PARAMETERS

— X-CAP-API-KEY

string

Example: `ENTER_GENERATED_API_KEY`

The API key obtained from Settings > API Integrations page on the Capital.com trading platform

Responses

> 200 OK

GET /api/v1/session/encryptionKey

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/session/encryptionKey",
Method.Get);
request.AddHeader("X-CAP-API-KEY", "ENTER_GENERATED_API_KEY");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy

```
{
  "encryptionKey":
    "MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAxOZgr4OMjNBMKpR+fZpxrDGGwI
  "timeStamp": 1649058606014
}
```

Session details

Returns the user's session details

HEADER PARAMETERS

X-SECURITY-TOKEN	string	Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token or account id identifying the client's current account
CST	string	Example: <code>ENTER_OBTAINED_CST_TOKEN</code> Access token identifying the client

Responses

> 200 OK

GET /api/v1/session



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/session", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy

```
{
  "clientId": "12345678",
  "accountId": "12345678901234567",
  "timezoneOffset": 3,
  "locale": "en",
  "currency": "USD",
  "streamEndpoint": "wss://api-streaming-capital.backend-capital.com/"
}
```

Create new session

Create a trading session, obtaining session tokens for subsequent API access

Session is active for 10 minutes. In case your inactivity is longer than this period then you need to create a new session

Endpoint limit: 1 request per second

List of request body parameters:

Parameter	Format	Required?	Description
identifier	string	YES	Client login identifier
password	string	YES	API key custom password
encryptedPassword	boolean	NO	Whether the password has been encrypted. Default value: <code>false</code>

HEADER PARAMETERS

→ **X-CAP-API-KEY** string
Example: `ENTER_GENERATED_API_KEY`
The API key obtained from Settings > API Integrations page on the Capital.com trading platform

REQUEST BODY SCHEMA: `application/json`

object

Responses

> **200 OK**

> **400 Bad Request**

> **401 Unauthorized**

> **429 Too Many Requests**

POST

/api/v1/session



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "identifier": "ENTER_YOUR_EMAIL",
  "password": "ENTER_YOUR_PASSWORD"
}
```

Response samples

200

400

401

429

Content type

text/plain

Example

Success: Session created (basic password)



Copy

```
{
  "accountType": "CFD",
  "accountInfo": {
    "balance": 92.89,
    "deposit": 90.38,
    "profitLoss": 2.51,
    "available": 64.66
  },
  "currencyIsoCode": "USD",
  "currencySymbol": "$",
  "currentAccountId": "12345678901234567",
  "streamingHost": "wss://api-streaming-capital.backend-
capital.com/"
}
```



```
"accounts": [  
  {  
    "accountId": "12345678901234567",  
    "accountName": "USD",  
    "preferred": true,  
    "accountType": "CFD",  
    "currency": "USD",  
    "symbol": "$",  
    "balance": {  
      "balance": 92.89,  
      "deposit": 90.38,  
      "profitLoss": 2.51,  
      "available": 64.66  
    }  
  },  
  {  
    "accountId": "12345678907654321",  
    "accountName": "EUR",  
    "preferred": false,  
    "accountType": "CFD",  
    "currency": "EUR",  
    "symbol": "€",  
    "balance": {  
      "balance": 0.0,  
      "deposit": 0.0,  
      "profitLoss": 0.0,  
      "available": 0.0  
    }  
  }  
],  
"clientId": "12345678",  
"timezoneOffset": 3,  
"hasActiveDemoAccounts": true,  
"hasActiveLiveAccounts": true,  
"trailingStopsEnabled": false  
}
```

Switches active account

Switch active account

List of request body parameters:

Parameter	Format	Required?	Description
accountId	string	YES	The identifier of the account being switched to

HEADER PARAMETERS

X-SECURITY-TOKEN	string	Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token identifying the client's current account
CST	string	Example: <code>ENTER_OBTAINED_CST_TOKEN</code> Access token identifying the client

REQUEST BODY SCHEMA: `application/json`

object

Responses

> 200 OK

> 400 Bad Request

PUT /api/v1/session

Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "accountId": "12345678907654321"
}
```

Response samples

200

400

Content type

application/json

Copy

```
{
  "trailingStopsEnabled": false,
  "dealingEnabled": true,
  "hasActiveDemoAccounts": false,
  "hasActiveLiveAccounts": true
}
```

Log out of the current session

Log out of the current session

HEADER PARAMETERS

X-SECURITY-TOKEN	string
Example:	ENTER_OBTAINED_SECURITY_TOKEN
	Account token identifying the client's current account
CST	string
Example:	ENTER_OBTAINED_CST_TOKEN
	Access token identifying the client

Responses

> 200 OK

DELETE

/api/v1/session



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/session", Method.Delete);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

text/plain

Copy

```
{
  "status": "SUCCESS"
}
```

Accounts

All accounts

Returns a list of accounts belonging to the logged-in client

HEADER PARAMETERS

X-SECURITY-TOKEN	string
Example:	ENTER_OBTAINED_SECURITY_TOKEN
	Account token identifying the client's current account
CST	string
Example:	ENTER_OBTAINED_CST_TOKEN
	Access token identifying the client

Responses

> 200 OK

GET

/api/v1/accounts



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-
```

```
capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/accounts", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  - "accounts": [
    + { ... },
    + { ... }
  ]
}
```

Account preferences

Returns account preferences, i.e. leverage settings and trading mode

HEADER PARAMETERS

X-SECURITY-TOKEN	string
Example: ENTER_OBTAINED_SECURITY_TOKEN	
Account token identifying the client's current account	
CST	string

Example: `ENTER_OBTAINED_CST_TOKEN`

Access token identifying the client

Responses

> 200 OK

GET /api/v1/accounts/preferences

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/accounts/preferences", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "hedgingMode": false,
  - "leverages": {
    + "SHARES": { ... },
    + "CURRENCIES": { ... },
    + "INDICES": { ... },
    + "CRYPTOCURRENCIES": { ... },
    + "COMMODITIES": { ... }
  }
}
```

Update account preferences

Update account preferences

List of request body parameters:

Parameter	Format	Required?	Description
leverages	object	NO	Set new leverage values
hedgingMode	boolean	NO	Enable or disable hedging mode

HEADER PARAMETERS

X-SECURITY-TOKEN	string	Example: ENTER_OBTAINED_SECURITY_TOKEN Account token identifying the client's current account
CST	string	Example: ENTER_OBTAINED_CST_TOKEN Access token identifying the client

REQUEST BODY SCHEMA: application/json

object

Responses

> 200 OK

> 400 Bad Request

PUT

/api/v1/accounts/preferences



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "leverages": {
    "SHARES": 5,
    "CURRENCIES": 10,
    "INDICES": 20,
    "CRYPTOCURRENCIES": 2,
    "COMMODITIES": 5
  },
  "hedgingMode": false
}
```

Response samples

200

400

Content type

application/json

Copy

```
{
  "status": "SUCCESS"
}
```

Account activity history

Returns the account activity history

All query parameters are optional for this request

The maximum possible date range between `from` and `to` parameters is 1 day. If only one of the parameters is specified (`from` or `to`), the 1-day date range will be selected by default

Possible enum values for parameters in FIQL filter:

Parameter	ENUM
source	CLOSE_OUT , DEALER , SL , SYSTEM , TP , USER
status	ACCEPTED , CREATED , EXECUTED , EXPIRED , REJECTED , MODIFIED , MODIFY_REJECT , CANCELLED , CANCEL_REJECT , UNKNOWN
type	POSITION , WORKING_ORDER , EDIT_STOP_AND_LIMIT , SWAP , SYSTEM

QUERY PARAMETERS

from	string Example: <code>from=2022-01-17T15:09:47</code> Start date. Date format: YYYY-MM-DDTHH:MM:SS (e.g. 2022-04-01T01:01:00). Filtration by date based on dateUTC parameter
to	string Example: <code>to=2022-01-17T15:10:05</code> End date. Date format: YYYY-MM-DDTHH:MM:SS (e.g. 2022-04-01T01:01:00). Filtration by date based on dateUTC parameter
lastPeriod	integer Example: <code>lastPeriod=600</code> Limits the timespan in seconds through to current time (not applicable if a

date range has been specified). Cannot be bigger than current Unix timestamp value. Default = 600, max = 86400

detailed

boolean

Example: `detailed=true`

Indicates whether to retrieve additional details about the activity. False by default

dealId

string

Example: `dealId={{dealId}}`

Get activity information for specific dealId

filter

string

Example:

`filter=source!=DEALER;type!=POSITION;status==REJECTED;epic==OIL_CRUDE,GOLD`

Filter activity list using FIQL. List of supported parameters: epic, source, status, type

HEADER PARAMETERS

X-SECURITY-TOKEN

string

Example: `ENTER_OBTAINED_SECURITY_TOKEN`

Account token identifying the client's current account

CST

string

Example: `ENTER_OBTAINED_CST_TOKEN`

Access token identifying the client

Responses

> 200 OK

> 400 Bad Request

GET

/api/v1/history/activity



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/history/activity?from=2022-01-17T15:09:47&to=2022-01-17T15:10:05&lastPeriod=600&detailed=true&dealId={{dealId}}&filter=source!=DEALER;type!=POSITION;status==REJECTED;epic==OIL,Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

400

Content type

application/json

Example

Success: Filter list by date



Copy

Expand all

Collapse all

```
{
  - "activities": [
    + { ... },
    + { ... },
    + { ... }
  ]
}
```

Account transactions history

Returns the transaction history. By default returns the transactions within the last 10 minutes

All query parameters are optional for this request

QUERY PARAMETERS

from	string Example: <code>from=2021-08-10T00:00:00</code> Start date. Date format: YYYY-MM-DDTHH:MM:SS (e.g. 2022-04-01T01:01:00). Filtration by date based on dateUTC parameter
to	string Example: <code>to=2021-09-10T00:00:01</code> End date. Date format: YYYY-MM-DDTHH:MM:SS (e.g. 2022-04-01T01:01:00). Filtration by date based on dateUTC parameter
lastPeriod	integer Example: <code>lastPeriod=600</code> Limits the timespan in seconds through to current time (not applicable if a date range has been specified). Cannot be bigger than current Unix timestamp value. Default = 600
type	string Example: <code>type=DEPOSIT</code> Transaction type. Possible values: INACTIVITY_FEE, RESERVE, VOID, UNRESERVE, WRITE_OFF_OR_CREDIT, CREDIT_FACILITY, FX_COMMISSION, COMPLAINT_SETTLEMENT, DEPOSIT, WITHDRAWAL, REFUND, WITHDRAWAL_MONEY_BACK, TRADE, SWAP, TRADE_COMMISSION, TRADE_COMMISSION_GSL, NEGATIVE_BALANCE_PROTECTION, TRADE_CORRECTION, CHARGEBACK, ADJUSTMENT, BONUS, TRANSFER, CORPORATE_ACTION, CONVERSION, REBATE, TRADE_SLIPPAGE_PROTECTION

HEADER PARAMETERS

X-SECURITY-TOKEN	string Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token identifying the client's current account
------------------	--

CST

string

Example: ENTER_OBTAINED_CST_TOKEN

Access token identifying the client

Responses

> 200 OK

GET

/api/v1/history/transactions



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/history/transactions?from=2021-08-10T00:00:00&to=2021-09-10T00:00:01&lastPeriod=600&type=DEPOSIT",
Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Example

Success: Get list of transactions within last hour



Copy

Expand all

Collapse all

```
{
  - "transactions": [
    + { ... },
    + { ... }
  ]
}
```

Adjust balance of Demo account

Adjust the balance of the current Demo account.

Note: The balance of the Demo account cannot exceed 100000.

Limits:

- 10 requests per second;
- 100 requests per account per day.

List of request body parameters:

Parameter	Format	Required?	Description
amount	number	YES	The amount of funds that will be added to the Demo account balance Notes: - Min value = -400000 - Max value = 400000

HEADER PARAMETERS

X-SECURITY-TOKEN string

Example: ENTER_OBTAINED_SECURITY_TOKEN

Account token identifying the client's current account

CST

string

Example: ENTER_OBTAINED_CST_TOKEN

Access token identifying the client

REQUEST BODY SCHEMA: application/json

object

Responses

> 200 OK

> 400 Bad Request

POST

/api/v1/accounts/topUp



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "amount": 1000
}
```

Response samples

200

400

Content type

application/json

Copy

```
{
  "successful": true
}
```

Trading

Position/Order confirmation

Returns a deal confirmation for the given deal reference

In case of mentioning the order prefix formed because of the position creation the opened positions IDs will be shown in the `affectedDeals` array

PATH PARAMETERS

→ **dealReference** string
required
Example: `{{dealReference}}`
Deal reference for an unconfirmed trade

HEADER PARAMETERS

→ **X-SECURITY-TOKEN** string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

→ **CST** string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

Responses

> 200 OK

> 404 Not Found

GET

/api/v1/confirm/{dealReference}



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
import http.client

conn = http.client.HTTPSConnection("api-capital.backend-capital.com")
payload = ''
headers = {
    'X-SECURITY-TOKEN': 'ENTER_OBTAINED_SECURITY_TOKEN',
    'CST': 'ENTER_OBTAINED_CST_TOKEN'
}
conn.request("GET", "/api/v1/confirm/{dealReference}", payload,
headers)
res = conn.getresponse()
data = res.read()
print(data.decode("utf-8"))
```

Response samples

200

404

Content type

application/json

Copy

Expand all

Collapse all

```
{
```

```
"date": "2022-04-06T07:32:19.193",
"status": "OPEN",
"dealStatus": "ACCEPTED",
"epic": "SILVER",
"dealReference": "o_fcc7e6c0-c150-48aa-bf66-d6c6da071f1a",
"dealId": "006011e7-0001-54c4-0000-000080560043",
- "affectedDeals": [
  + { ... }
],
"level": 24.285,
"size": 1,
"direction": "BUY",
"guaranteedStop": false,
"trailingStop": false
}
```

Trading > Positions

All positions

Returns all open positions for the active account

HEADER PARAMETERS

X-SECURITY-TOKEN	string Example: ENTER_OBTAINED_SECURITY_TOKEN Account token identifying the client's current account
CST	string Example: ENTER_OBTAINED_CST_TOKEN Access token identifying the client

Responses

> 200 OK

GET /api/v1/positions



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/positions", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "positions": [
    + { ... },
    + { ... }
  ]
}
```

```
}
```

Create position

Create orders and positions

Please note that when creating the position an order is created first with the 'o_' prefix in the `dealReference` parameter

List of request body parameters:

Parameter	Format	Required?	Description
direction	string	YES	Deal direction Must be <code>BUY</code> or <code>SELL</code>
epic	string	YES	Instrument epic identifier
size	number	YES	Deal size
guaranteedStop	boolean	NO	Must be <code>true</code> if a guaranteed stop is required Notes: - Default value: <code>false</code> - If <code>guaranteedStop</code> equals <code>true</code> , then set <code>stopLevel</code> , <code>stopDistance</code> or <code>stopAmount</code> - Cannot be set if <code>trailingStop</code> is <code>true</code> - Cannot be set if <code>hedgingMode</code> is <code>true</code>
trailingStop	boolean	NO	Must be <code>true</code> if a trailing stop is required Notes: - Default value: <code>false</code> - If <code>trailingStop</code> equals <code>true</code> , then set <code>stopDistance</code> - Cannot be set if <code>guaranteedStop</code> is <code>true</code>
stopLevel	number	NO	Price level when a stop loss will be triggered
			Distance between current and stop loss triggering price

stopDistance	number	NO	Notes: - Required parameter if <code>trailingStop</code> is <code>true</code>
stopAmount	number	NO	Loss amount when a stop loss will be triggered
profitLevel	number	NO	Price level when a take profit will be triggered
profitDistance	number	NO	Distance between current and take profit triggering price
profitAmount	number	NO	Profit amount when a take profit will be triggered

HEADER PARAMETERS

X-SECURITY-TOKEN	string	Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token identifying the client's current account
CST	string	Example: <code>ENTER_OBTAINED_CST_TOKEN</code> Access token identifying the client

REQUEST BODY SCHEMA: `application/json`

object

Responses

> 200 OK

> 400 Bad Request

POST

/api/v1/positions



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "epic": "SILVER",
  "direction": "BUY",
  "size": 1,
  "guaranteedStop": true,
  "stopLevel": 20,
  "profitLevel": 27
}
```

Response samples

200

400

Content type

application/json

Example

Success: Create simple position



Copy

```
{
  "dealReference": "o_98c0de50-9cd5-4481-8d81-890c525eeb49"
}
```

Single position

Returns an open position for the active account by deal identifier

PATH PARAMETERS

→ dealId string
required
Example: `{{dealId}}`
Permanent deal reference for a confirmed trade

HEADER PARAMETERS

→ X-SECURITY-TOKEN string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

→ CST string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

Responses

> 200 OK

> 404 Not Found

GET /api/v1/positions/{dealId}

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/positions/{dealId}", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
```



```
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");  
RestResponse response = await client.ExecuteAsync(request);  
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{  
  - "position": {  
    "contractSize": 1,  
    "createdDate": "2022-04-06T10:49:52.056",  
    "createdDateUTC": "2022-04-06T07:49:52.056",  
    "dealId": "006011e7-0001-54c4-0000-00008056005e",  
    "dealReference": "p_006011e7-0001-54c4-0000-00008056005e",  
    "workingOrderId": "006011e7-0001-54c4-0000-00008056005c",  
    "size": 1,  
    "leverage": 20,  
    "upl": -0.022,  
    "direction": "BUY",  
    "level": 21.059,  
    "currency": "USD",  
    "guaranteedStop": false  
  },  
  - "market": {
```

```
    "instrumentName": "Silver",
    "expiry": "-",
    "marketStatus": "TRADEABLE",
    "epic": "SILVER",
    "symbol": "Natural Gas",
    "instrumentType": "COMMODITIES",
    "lotSize": 1,
    "high": 21.167,
    "low": 20.823,
    "percentageChange": 1.8478,
    "netChange": 0.381,
    "bid": 21.037,
    "offer": 21.057,
    "updateTime": "2022-04-06T10:53:35.389",
    "updateTimeUTC": "2022-04-06T07:53:35.389",
    "delayTime": 0,
    "streamingPricesAvailable": true,
    "scalingFactor": 1,
+   "marketModes": [ ... ]
  }
}
```

Update position

Update the position

List of request body parameters:

Parameter	Format	Required?	Description
guaranteedStop	boolean	NO	Must be <code>true</code> if a guaranteed stop is required Notes: - Default value: <code>false</code> - If <code>guaranteedStop</code> equals <code>true</code>, then set <code>stopLevel</code>, <code>stopDistance</code> or <code>stopAmount</code> - Cannot be set if <code>trailingStop</code> is <code>true</code>

			- Cannot be set if <code>hedgingMode</code> is <code>true</code>
<code>trailingStop</code>	<code>boolean</code>	NO	Must be <code>true</code> if a trailing stop is required Notes: - Default value: <code>false</code> - If <code>trailingStop</code> equals <code>true</code>, then set <code>stopDistance</code> - Cannot be set if <code>guaranteedStop</code> is <code>true</code>
<code>stopLevel</code>	<code>number</code>	NO	Price level when a stop loss will be triggered
<code>stopDistance</code>	<code>number</code>	NO	Distance between current and stop loss triggering price Notes: - Required parameter if <code>trailingStop</code> is <code>true</code>
<code>stopAmount</code>	<code>number</code>	NO	Loss amount when a stop loss will be triggered
<code>profitLevel</code>	<code>number</code>	NO	Price level when a take profit will be triggered
<code>profitDistance</code>	<code>number</code>	NO	Distance between current and take profit triggering price
<code>profitAmount</code>	<code>number</code>	NO	Profit amount when a take profit will be triggered

PATH PARAMETERS

→ `dealId` required `string`
 Example: `{{dealId}}`
 Permanent deal reference for a confirmed trade

HEADER PARAMETERS

→ `X-SECURITY-TOKEN` `string`
 Example: `ENTER_OBTAINED_SECURITY_TOKEN`
 Account token identifying the client's current account

→ `CST` `string`
 Example: `ENTER_OBTAINED_CST_TOKEN`
 Access token identifying the client

REQUEST BODY SCHEMA: application/json

object

Responses

> 200 OK

> 400 Bad Request

> 404 Not Found

PUT

/api/v1/positions/{dealId}



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "guaranteedStop": true,
  "stopDistance": 3,
  "profitAmount": 2
}
```

Response samples

200

400

404

Content type

application/json

Copy

```
{
  "dealReference": "p_006011e7-0001-54c4-0000-000080560068"
}
```

Close position

Close the position

PATH PARAMETERS

→ dealId string
required
Example: `{{dealId}}`
Permanent deal reference for a confirmed trade

HEADER PARAMETERS

→ X-SECURITY-TOKEN string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

→ CST string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

Responses

> 200 OK

> 404 Not Found

DELETE /api/v1/positions/{dealId} 

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/positions/{dealId}",
Method.Delete);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy

```
{
  "dealReference": "p_006011e7-0001-54c4-0000-000080560068"
}
```

Trading > Orders

All working orders

Returns all open working orders for the active account

HEADER PARAMETERS

X-SECURITY-TOKEN	string Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token identifying the client's current account
CST	string Example: <code>ENTER_OBTAINED_CST_TOKEN</code> Access token identifying the client

Responses

> 200 OK

GET /api/v1/workingorders

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
import http.client

conn = http.client.HTTPSConnection("api-capital.backend-capital.com")
payload = ''
headers = {
    'X-SECURITY-TOKEN': 'ENTER_OBTAINED_SECURITY_TOKEN',
    'CST': 'ENTER_OBTAINED_CST_TOKEN'
}
conn.request("GET", "/api/v1/workingorders", payload, headers)
```

```
res = conn.getResponse()
data = res.read()
print(data.decode("utf-8"))
```

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  - "workingOrders": [
    + { ... },
    + { ... }
  ]
}
```

Create working order

Create a limit or stop order

List of request body parameters:

Parameter	Format	Required?	Description
direction	string	YES	Order direction Must be BUY or SELL
epic	string	YES	Instrument epic identifier
size	number	YES	Order size
level	number	YES	Order price
type	string	YES	Order type Must be LIMIT or STOP

goodTillDate	string	NO	Order cancellation date in UTC time Date format: <code>YYYY-MM-DDTHH:MM:SS</code> (e.g. <code>2022-06-09T01:01:00</code>)
guaranteedStop	boolean	NO	Must be <code>true</code> if a guaranteed stop is required Notes: - Default value: <code>false</code> - If <code>guaranteedStop</code> equals <code>true</code> , then set <code>stopLevel</code> , <code>stopDistance</code> or <code>stopAmount</code> - Cannot be set if <code>trailingStop</code> is <code>true</code> - Cannot be set if <code>hedgingMode</code> is <code>true</code>
trailingStop	boolean	NO	Must be <code>true</code> if a trailing stop is required Notes: - Default value: <code>false</code> - If <code>trailingStop</code> equals <code>true</code> , then set <code>stopDistance</code> - Cannot be set if <code>guaranteedStop</code> is <code>true</code>
stopLevel	number	NO	Price level when a stop loss will be triggered
stopDistance	number	NO	Distance between current and stop loss triggering price Notes: - Required parameter if <code>trailingStop</code> is <code>true</code>
stopAmount	number	NO	Loss amount when a stop loss will be triggered
profitLevel	number	NO	Price level when a take profit will be triggered
profitDistance	number	NO	Distance between current and take profit triggering price
profitAmount	number	NO	Profit amount when a take profit will be triggered

HEADER PARAMETERS

`X-SECURITY-TOKEN` string

Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

CST

string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

REQUEST BODY SCHEMA: `application/json`

object

Responses

> 200 OK

> 400 Bad Request

POST

/api/v1/workingorders



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "epic": "SILVER",
  "direction": "BUY",
  "size": 1,
  "level": 20,
  "type": "LIMIT"
}
```

Response samples

200

400

Content type

application/json

Example

Success: Create limit order



Copy

```
{
  "dealReference": "o_307bb379-6dd8-4ea7-8935-faf725f0e0a3"
}
```

Update working order

Update a limit or stop order

List of request body parameters:

Parameter	Format	Required?	Description
level	number	NO	Order price
goodTillDate	string	NO	Order cancellation date in UTC time Date format: <code>YYYY-MM-DDTHH:MM:SS</code> (e.g. <code>2022-06-09T01:01:00</code>)
guaranteedStop	boolean	NO	Must be <code>true</code> if a guaranteed stop is required Notes: - Default value: <code>false</code> - If <code>guaranteedStop</code> equals <code>true</code> , then set <code>stopLevel</code> , <code>stopDistance</code> or <code>stopAmount</code> - Cannot be set if <code>trailingStop</code> is <code>true</code> - Cannot be set if <code>hedgingMode</code> is <code>true</code>

trailingStop	boolean	NO	Must be <code>true</code> if a trailing stop is required Notes: - Default value: <code>false</code> - If <code>trailingStop</code> equals <code>true</code>, then set <code>stopDistance</code> - Cannot be set if <code>guaranteedStop</code> is <code>true</code>
stopLevel	number	NO	Price level when a stop loss will be triggered
stopDistance	number	NO	Distance between current and stop loss triggering price Notes: - Required parameter if <code>trailingStop</code> is <code>true</code>
stopAmount	number	NO	Loss amount when a stop loss will be triggered
profitLevel	number	NO	Price level when a take profit will be triggered
profitDistance	number	NO	Distance between current and take profit triggering price
profitAmount	number	NO	Profit amount when a take profit will be triggered

PATH PARAMETERS

→ `dealId` string
required
 Example: `{{dealId}}`
 Permanent deal reference for an order

HEADER PARAMETERS

→ `X-SECURITY-TOKEN` string
 Example: `ENTER_OBTAINED_SECURITY_TOKEN`
 Account token identifying the client's current account

→ `CST` string
 Example: `ENTER_OBTAINED_CST_TOKEN`
 Access token identifying the client

REQUEST BODY SCHEMA: `application/json`

object

Responses

> 200 OK

> 404 Not Found

PUT

/api/v1/workingorders/{dealId}



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "goodTillDate": "2022-06-09T01:01:00",
  "guaranteedStop": true,
  "stopDistance": 4,
  "profitDistance": 4
}
```

Response samples

200

404

Content type

application/json

Copy

```
{  
  "dealReference": "o_56e73aad-45fe-4058-a05b-569b1a6e8ba0"  
}
```

Delete working order

Delete a limit or stop order

PATH PARAMETERS

→ dealId string
required
Example: `{{dealId}}`
Permanent deal reference for an order

HEADER PARAMETERS

→ X-SECURITY-TOKEN string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

→ CST string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

Responses

> 200 OK

> 404 Not Found

DELETE /api/v1/workingorders/{dealId}



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/workingorders/{{dealId}}",
Method.Delete);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy

```
{
  "dealReference": "o_38323f0c-241a-43b3-8edf-a75d2ae989a5"
}
```

Markets Info > Markets

All top-level market categories

Returns all top-level nodes (market categories) in the market navigation hierarchy

HEADER PARAMETERS

X-SECURITY-TOKEN	string
Example:	ENTER_OBTAINED_SECURITY_TOKEN
	Account token identifying the client's current account
CST	string
Example:	ENTER_OBTAINED_CST_TOKEN
	Access token identifying the client

Responses

> 200 OK

GET

/api/v1/marketnavigation



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/marketnavigation", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```


Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  - "nodes": [
    + { ... },
    + { ... },
    + { ... }
  ]
}
```

All category sub-nodes

Returns all sub-nodes (markets) of the given node (market category) in the market navigation hierarchy

PATH PARAMETERS

→ **nodeId** string
required
Example: `{{nodeId}}`
Identifier of the node to browse

QUERY PARAMETERS

→ **limit** integer
Example: `limit=500`
The maximum number of the markets in answer. Default = 500, max = 500

HEADER PARAMETERS

→ **X-SECURITY-TOKEN** string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`

CST

Account token identifying the client's current account

string

Example: `ENTER_OBTAINED_CST_TOKEN`

Access token identifying the client

Responses

> 200 OK

> 400 Bad Request

GET /api/v1/marketnavigation/{nodeId}

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/marketnavigation/{nodeId}?limit=500", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

400

Content type

application/json

Example

Success: List of category sub-nodes



Copy

Expand all

Collapse all

```
{
  - "nodes": [
    + { ... },
    + { ... },
    + { ... },
    + { ... },
    + { ... },
    + { ... },
    + { ... },
    + { ... }
  ]
}
```

Markets details

Returns the details of all or specific markets

If query parameters are not specified in the request, the list of all available markets will be returned

Request can include one of the query parameters: `searchTerm` or `epics`

If both `searchTerm` or `epics` parameters are specified in the request, only `searchTerm` will be used (due to higher priority)

QUERY PARAMETERS

`searchTerm`

string

Example: `searchTerm=silver`

The term to be used in the search. Has higher priority, than 'epics' parameter meaning that in case both `searchTerm` and `epic` are mentioned

epics

only searchTerm is taken into consideration.

string

Example: `epics=SILVER,NATURALGAS`

The epics of the market, separated by a comma. Max number of epics is limited to 50

HEADER PARAMETERS

X-SECURITY-TOKEN

string

Example: `ENTER_OBTAINED_SECURITY_TOKEN`

Account token identifying the client's current account

CST

string

Example: `ENTER_OBTAINED_CST_TOKEN`

Access token identifying the client

Responses

> 200 OK

> 400 Bad Request

GET /api/v1/markets

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
    ...
}
```

```
//  
var client = new RestClient(options);  
var request = new RestRequest("/api/v1/markets?  
searchTerm=silver&epics=SILVER,NATURALGAS", Method.Get);  
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");  
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");  
RestResponse response = await client.ExecuteAsync(request);  
Console.WriteLine(response.Content);
```

Response samples

200

400

Content type

application/json

Example

Successful response: searchTerm



Copy

Expand all

Collapse all

```
{  
  - "markets": [  
    + { ... },  
    + { ... }  
  ]  
}
```

Single market details

Returns the details of the given market

PATH PARAMETERS

→ epic
required

string

Example: `{{epic}}`

The epic of the market

HEADER PARAMETERS

|

X-SECURITY-TOKEN	string
Example:	ENTER_OBTAINED_SECURITY_TOKEN
Account token identifying the client's current account	
CST	string
Example:	ENTER_OBTAINED_CST_TOKEN
Access token identifying the client	

Responses

> 200 OK

> 404 Not Found

GET /api/v1/markets/{epic}

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/markets/{epic}", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{
  - "instrument": {
    "epic": "SILVER",
    "symbol": "Silver",
    "expiry": "-",
    "name": "Silver",
    "lotSize": 1,
    "type": "COMMODITIES",
    "guaranteedStopAllowed": true,
    "streamingPricesAvailable": true,
    "currency": "USD",
    "marginFactor": 10,
    "marginFactorUnit": "PERCENTAGE",
    + "openingHours": { ... },
    + "overnightFee": { ... }
  },
  - "dealingRules": {
    + "minStepDistance": { ... },
    + "minDealSize": { ... },
    + "maxDealSize": { ... },
    + "minSizeIncrement": { ... },
    + "minGuaranteedStopDistance": { ... },
    + "minStopOrProfitDistance": { ... },
    + "maxStopOrProfitDistance": { ... },
    "marketOrderPreference": "AVAILABLE_DEFAULT_ON",
    "trailingStopsPreference": "NOT_AVAILABLE"
  },
}
```

```
- "snapshot": {
  "marketStatus": "TRADEABLE",
  "netChange": -0.627,
  "percentageChange": -0.27,
  "updateTime": "2022-04-06T11:23:00.955",
  "delayTime": 0,
  "bid": 22.041,
  "offer": 22.061,
  "high": 22.098,
  "low": 21.926,
  "decimalPlacesFactor": 3,
  "scalingFactor": 1,
  + "marketModes": [ ... ]
}
```

Markets Info > Prices

Historical prices

Returns historical prices for a particular instrument

All query parameters are optional for this request

By default returns the minute prices within the last 10 minutes

PATH PARAMETERS

→ epic
required

string
Example: {{epic}}
Instrument epic

QUERY PARAMETERS

|

resolution	string Example: <code>resolution=MINUTE</code> Defines the resolution of requested prices. Possible values are MINUTE, MINUTE_5, MINUTE_15, MINUTE_30, HOUR, HOUR_4, DAY, WEEK
max	integer Example: <code>max=10</code> The maximum number of the values in answer. Default = 10, max = 1000
from	string Example: <code>from=2022-02-24T00:00:00</code> Start date. Date format: YYYY-MM-DDTHH:MM:SS (e.g. 2022-04-01T01:01:00). Filtration by date based on snapshotTimeUTC parameter
to	string Example: <code>to=2022-02-24T01:00:00</code> End date. Date format: YYYY-MM-DDTHH:MM:SS (e.g. 2022-04-01T01:01:00). Filtration by date based on snapshotTimeUTC parameter

HEADER PARAMETERS

X-SECURITY-TOKEN	string Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token identifying the client's current account
CST	string Example: <code>ENTER_OBTAINED_CST_TOKEN</code> Access token identifying the client

Responses

> 200 OK

> 400 Bad Request

GET /api/v1/prices/{epic}



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/prices/{epic}}?resolution=MINUTE&max=10&from=2022-02-24T00:00:00&to=2022-02-24T01:00:00", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

400

Content type

application/json

Example

Success: Default response



Copy

Expand all

Collapse all

{

"prices": [

```
- prices : [  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... },  
  + { ... }  
],  
"instrumentType": "COMMODITIES"  
}
```

Markets Info > Client Sentiment

Client sentiment for markets

Returns the client sentiment for the given market

QUERY PARAMETERS

→ marketIds string
Example: `marketIds=SILVER,NATURALGAS`
Comma separated list of market identifiers

HEADER PARAMETERS

→ X-SECURITY-TOKEN string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

CST

string

Example: ENTER_OBTAINED_CST_TOKEN

Access token identifying the client

Responses

> 200 OK

> 404 Not Found

GET

/api/v1/clientsentiment



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-  
capital.com")  
{  
    MaxTimeout = -1,  
};  
var client = new RestClient(options);  
var request = new RestRequest("/api/v1/clientsentiment?  
marketIds=SILVER,NATURALGAS", Method.Get);  
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");  
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");  
RestResponse response = await client.ExecuteAsync(request);  
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "clientSentiments": [
    + { ... },
    + { ... }
  ]
}
```

Client sentiment for market

Returns the client sentiment for the given market

PATH PARAMETERS

→ **marketId** string
required
Example: `{{marketId}}`
Market identifier

HEADER PARAMETERS

→ **X-SECURITY-TOKEN** string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

→ **CST** string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

Responses

> 200 OK

> 404 Not Found

GET /api/v1/clientsentiment/{marketId} 

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/clientsentiment/{marketId}",
Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy

```
{
  "marketId": "SILVER",
  "longPositionPercentage": 91.85,
  "shortPositionPercentage": 8.15
}
```

Watchlists

All watchlists

Returns all watchlists belonging to the current user

HEADER PARAMETERS

X-SECURITY-TOKEN	string
Example:	ENTER_OBTAINED_SECURITY_TOKEN
	Account token identifying the client's current account
CST	string
Example:	ENTER_OBTAINED_CST_TOKEN
	Access token identifying the client

Responses

> 200 OK

GET

/api/v1/watchlists



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/watchlists", Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

Content type

application/json

Copy Expand all Collapse all

```
{
  - "watchlists": [
    + { ... },
    + { ... }
  ]
}
```

Create watchlist

Create a watchlist

List of request body parameters:

Parameter	Format	Required?	Description
name	string	YES	Watchlist name

			Min length = 1 Max length = 20
epics	array[string]	NO	List of market epics to be associated with this new watchlist

HEADER PARAMETERS

X-SECURITY-TOKEN	string Example: ENTER_OBTAINED_SECURITY_TOKEN Account token identifying the client's current account
CST	string Example: ENTER_OBTAINED_CST_TOKEN Access token identifying the client

REQUEST BODY SCHEMA: application/json

object

Responses

> 200 OK

> 400 Bad Request

POST

/api/v1/watchlists



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy Expand all Collapse all

```
{
  - "epics": [
    "SILVER",
    "NATURALGAS"
  ],
  "name": "Lorem"
}
```

Response samples

200

400

Content type

application/json

Example

Success: Watchlist created



Copy

```
{
  "watchlistId": "123458",
  "status": "SUCCESS"
}
```

Single watchlist

Returns a watchlist for the given watchlist identifier

PATH PARAMETERS

→ watchlistId required	string Example: {{watchlistId}} Identifier of the watchlist
--	--

HEADER PARAMETERS

|

X-SECURITY-TOKEN	string Example: ENTER_OBTAINED_SECURITY_TOKEN Account token identifying the client's current account
CST	string Example: ENTER_OBTAINED_CST_TOKEN Access token identifying the client

Responses

> 200 OK

> 404 Not Found

GET /api/v1/watchlists/{watchlistId}

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/watchlists/{watchlistId}",
Method.Get);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "markets": [
    + { ... },
    + { ... }
  ]
}
```

Add market to watchlist

Add a market to the watchlist

List of request body parameters:

Parameter	Format	Required?	Description
epic	string	YES	Instrument epic identifier

PATH PARAMETERS

→ watchlistId

required

string

Example: {{watchlistId}}

Identifier of the watchlist

HEADER PARAMETERS

→ X-SECURITY-TOKEN

string

Example: ENTER_OBTAINED_SECURITY_TOKEN

Account token identifying the client's current account

→ CST

string

Example: ENTER_OBTAINED_CST_TOKEN

Access token identifying the client

REQUEST BODY SCHEMA: application/json

object

Responses

> 200 OK

> 404 Not Found

PUT

/api/v1/watchlists/{watchlistId}



Request samples

Payload

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Content type

application/json

Copy

```
{
  "epic": "SILVER"
}
```

Response samples

200

404

Content type

application/json

Copy

```
{  
  "status": "SUCCESS"  
}
```

Delete watchlist

Delete the watchlist

PATH PARAMETERS

→ watchlistId string
required
Example: `{{watchlistId}}`
Identifier of the watchlist

HEADER PARAMETERS

→ X-SECURITY-TOKEN string
Example: `ENTER_OBTAINED_SECURITY_TOKEN`
Account token identifying the client's current account

→ CST string
Example: `ENTER_OBTAINED_CST_TOKEN`
Access token identifying the client

Responses

> 200 OK

> 404 Not Found

DELETE

/api/v1/watchlists/{watchlistId}



Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
};
var client = new RestClient(options);
var request = new RestRequest("/api/v1/watchlists/{watchlistId}",
Method.Delete);
request.AddHeader("X-SECURITY-TOKEN", "ENTER_OBTAINED_SECURITY_TOKEN");
request.AddHeader("CST", "ENTER_OBTAINED_CST_TOKEN");
RestResponse response = await client.ExecuteAsync(request);
Console.WriteLine(response.Content);
```

Response samples

200

404

Content type

application/json

Copy

```
{
  "status": "SUCCESS"
}
```

Remove market from watchlist

Remove a market from the watchlist

PATH PARAMETERS

watchlistId required	string Example: <code>{{watchlistId}}</code> Identifier of the watchlist
epic required	string Example: <code>{{epic}}</code> Instrument epic identifier

HEADER PARAMETERS

X-SECURITY-TOKEN	string Example: <code>ENTER_OBTAINED_SECURITY_TOKEN</code> Account token identifying the client's current account
CST	string Example: <code>ENTER_OBTAINED_CST_TOKEN</code> Access token identifying the client

Responses

> 200 OK

> 404 Not Found

DELETE `/api/v1/watchlists/{watchlistId}/{epic}`

Request samples

C#

cURL

HTTP

Java

JavaScript

NodeJS

PHP

Python

Copy

```
var options = new RestClientOptions("https://api-capital.backend-capital.com")
{
    MaxTimeout = -1,
```