Android Bot SDK Customization Guide

A practical reference to the appearance, layout, message, and input options exposed by the Android Bot SDK. Each example shows the relevant call or extension point; apply configuration before creating the BotChatFragment unless noted otherwise.

Scope

The options below are based on the SDKConfig API, SDKConfiguration options, and the repository sample app. The SDK supports both quick configuration and deeper UI replacement through custom fragments. Examples use Java; adapt resource IDs, drawable names, and app-specific fragment classes to your project.

1. Replace the chat regions

You can supply a custom header, message-content area, or composer/footer. Extend the matching base fragment so SDK interactions and lifecycle hooks remain available, then register it during app setup.

```
SDKConfig.addCustomHeaderFragment(new MyHeaderFragment());
SDKConfig.addCustomContentFragment(new MyContentFragment());
SDKConfig.addCustomFooterFragment(new MyFooterFragment());
```

Extension points: BaseHeaderFragment, BaseContentFragment, and BaseFooterFragment. The sample app contains CustomHeaderFragment, CustomContentFragment, and CustomFooterFragment as implementation references.

2. Header visibility and controls

Show or hide the SDK header, its minimize control, and the SDK action bar. These controls are useful when the host app provides its own navigation chrome.

```
SDKConfig.setIsShowHeader(true);
SDKConfig.showHeaderMinimize(false);
SDKConfig.setIsShowActionBar(false);
```

Use a custom header fragment when the header layout or actions need to be redesigned, rather than only toggled.

3. Colors, bubbles, and local branding

A local BrandingModel can override the branding response. It covers bot and user bubble colors and text, widget body and header colors, composer/footer, buttons, borders, divider, bot name, footer hint, and bubble style. Enable local branding when applying it.

```
BrandingModel brand = new BrandingModel();
brand.setBotchatBgColor("#F3F5F8");
brand.setBotchatTextColor("#202 124");
brand.setUserchatBgColor("#0D6EFD");
brand.setUserchatTextColor("#FFFFFF");
brand.setWidgetHeaderColor("#0D6EFD");
brand.setWidgetFooterColor("#FFFFFF");
brand.setWidgetFooterHintText("Type your message...");
brand.setWidgetBodyColor("#FFFFFF");
brand.setButtonActiveBgColor("#0D6EFD");
brand.setButtonActiveTextColor("#FFFFFF");
brand.setChatBubbleStyle("square");
SDKConfig.setLocalBranding(true, brand);
```

BrandingModel also exposes inactive button colors, footer hint/border colors, general widget text/border/divider colors, and button border color. The sample app demonstrates local branding setup.

4. Fonts and status bar

Set the typefaces used by SDK text and optionally synchronize the Android status bar color with the chat header.

```
SDKConfig.setFontFamily(regularTypeface, semiBoldTypeface, boldTypeface);
SDKConfig.setIsUpdateStatusBarColor(true);
```

Pass Android Typeface instances, for example from app font resources. The font call expects regular, semibold, and bold in that order.

5. Message timestamps

Enable or disable timestamps for bot and user messages. You can also set the bubble timestamp format using a Java date/time pattern.

```
SDKConfig.setIsTimeStampsRequired(true);  // false hides timestamps
SDKConfig.setBubbleDateFormat("MMM dd 'at' h:mm a");
```

The SDK default format is defined in SDKConfiguration. Choose a valid format compatible with the SDK timestamp formatter.

6. Bot avatar and response icon

Set the agent avatar using a local Drawable and/or an image URL. The response icon can be hidden, or positioned at the top/bottom of a response.

```
SDKConfig.setAgentAvatar(agentDrawable, "https://example.com/agent.png");
SDKConfig.setIsShowIcon(true);
SDKConfig.setIsShowIconTop(false);
```

The SDK also supports setting the icon resource or URL through SDKConfiguration.BubbleColors when direct lower-level configuration is needed.

7. Composer options and AI attribution

The sample app exposes toggles for attachments, microphone input, and text-to-speech through OverrideKoreConfig. The “Answered by AI” label can be shown or hidden through SDKConfig.

```
SDKConfiguration.OverrideKoreConfig.showAttachment = true;
SDKConfiguration.OverrideKoreConfig.showASRMicroPhone = true;
SDKConfiguration.OverrideKoreConfig.showTextToSpeech = true;
SDKConfig.setShowAnsweredByAI(false);
```

For a fully custom composer, extend BaseFooterFragment and register it as described in section 1.

8. Custom message templates

Replace the rendering for a supported message template type by registering a custom ViewHolder class. The app supplies the named template and holder implementation.

```
SDKConfig.setCustomTemplateViewHolder("link", LinkTemplateHolder.class);
```

A direct custom View can also be registered for a template name with setCustomTemplateView(String, View). Use a custom ViewHolder when the template needs data binding for each message.

9. Additional chat behavior

The SDK exposes optional behavior settings that affect the chat experience. The following examples use the public configuration object shown in the SDK sample.

```
SDKConfiguration.OverrideKoreConfig.isEmojiShortcutEnable = true;
SDKConfiguration.OverrideKoreConfig.history_enable = true;
SDKConfiguration.OverrideKoreConfig.paginated_scroll_enable = true;
```

Other exposed flags include history loading, pagination batch size and loading label, initial history call, hamburger menu, and button click handling. These are behavior settings rather than visual themes; confirm the desired behavior with the app team before changing them.

10. App and conversation integration

The app can supply custom bot data and socket query parameters, set a device ID, and observe connection status. These hooks integrate the SDK with the host app and do not change chat styling.

```
SDKConfig.setCustomData(customData);
SDKConfig.setQueryParams(queryParams);
SDKConfig.setDeviceId(deviceId);
SDKConfig.setBotStatusUpdateListener(botStatusListener);
```

SDKConfig.initialize(...) configures bot identity and endpoints. Use it as part of SDK setup; credentials and endpoint values are environment-specific and are omitted from this guide.

Quick reference

Customization	SDK entry point
Custom header/content/footer	addCustomHeaderFragment / addCustomContentFragment / addCustomFooterFragment
Header, minimize, action bar	setIsShowHeader / showHeaderMinimize / setIsShowActionBar
Branding and colors	setLocalBranding(true, BrandingModel)
Fonts	setFontFamily(regular, semiBold, bold)
Timestamps	setIsTimeStampsRequired / setBubbleDateFormat
Avatar and message icon	setAgentAvatar / setIsShowIcon / setIsShowIconTop
Composer features	OverrideKoreConfig.showAttachment / showASRMicroPhone / showTextToSpeech
AI attribution	setShowAnsweredByAI
Message templates	setCustomTemplateViewHolder / setCustomTemplateView

Implementation notes

- Register fragment overrides and visual settings before adding BotChatFragment, as in the sample app.
- The three custom fragment hooks replace major chat regions; they require Android fragment and view implementations in the client app.
- BrandingModel is a bounded set of styling properties. For layouts outside those properties, use the custom fragment extension points.
- API names and options in this guide reflect the SDK source currently in this repository; verify against the exact SDK version integrated by the client.