

```

mysql> /* MY SQL DCL COMMANDS */
mysql> -- DCL: Data control language commands are used to control access to data in
the database-mainly to grant or revoke privileges to users.
mysql> /* common privilages
/*> select
/*> insert
/*> update
/*> delete
/*> all privilages -full access */
mysql> -- user creation
mysql> /* create user "username" identified by "password"; */
mysql> /* Grant & revoke */
mysql> /* Grant privilege on table_name to username;
/*> revoke privilege on table_name to username; */

```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ')' at line 5

```

mysql> create table students(
-> sno int primary key,
-> sname varchar(30),
-> semail varchar(20)
-> );
Query OK, 0 rows affected (0.06 sec)

```

```

mysql> insert into students values(111,'praveen','praveen@gmail.com');
Query OK, 1 row affected (0.02 sec)

```

```

mysql> select * from students;
+-----+-----+-----+
| sno | sname | semail |
+-----+-----+-----+
| 111 | praveen | praveen@gmail.com |
+-----+-----+-----+
1 row in set (0.00 sec)

```

```

mysql> insert into students
values(222,'jayakumar','jayakumar@gmail.com'),(333,'sanjay
kumar','sanjay@gmail.com');
Query OK, 2 rows affected (0.04 sec)
Records: 2 Duplicates: 0 Warnings: 0

```

```

mysql> select * from students;
+-----+-----+-----+
| sno | sname | semail |
+-----+-----+-----+
| 111 | praveen | praveen@gmail.com |
| 222 | jayakumar | jayakumar@gmail.com |
| 333 | sanjay kumar | sanjay@gmail.com |

```

```
+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> create user tony identified by 'mark85';
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> create user stark identified by 'mark50';
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> grant select,insert,update on students to tony;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> grant select,drop on students to stark;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> select * from students;
```

```
+-----+-----+-----+
| sno | sname      | semail      |
+-----+-----+-----+
| 111 | praveen    | praveen@gmail.com |
| 222 | jayakumar  | jayakumar@gmail.com |
| 333 | sanjay kumar | sanjay@gmail.com |
| 444 | mahi       | mahi@gmail.com |
+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> select * from students;
```

```
+-----+-----+-----+
| sno | sname      | semail      |
+-----+-----+-----+
| 111 | tony stark  | ironman@gmail.com |
| 222 | jayakumar  | jayakumar@gmail.com |
| 333 | sanjay kumar | sanjay@gmail.com |
| 444 | mahi       | mahi@gmail.com |
+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> revoke update on students from tony;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> revoke insert on students from tony;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> revoke select on students from stark;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> create table students(
-> sno int primary key,
```

```
-> sname varchar(30),
-> semail varchar(20)
-> );
```

Query OK, 0 rows affected (0.07 sec)

```
mysql> insert into students values(111,'praveen','praveen@gmail.com');
```

Query OK, 1 row affected (0.01 sec)

```
mysql> insert into students
values(222,'jayakumar','jayakumar@gmail.com'),(333,'sanjay
kumar','sanjay@gmail.com');
```

Query OK, 2 rows affected (0.01 sec)

Records: 2 Duplicates: 0 Warnings: 0

```
mysql> revoke update on students from tony;
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> select * from students;
```

sno	sname	semail
111	praveen	praveen@gmail.com
222	jayakumar	jayakumar@gmail.com
333	sanjay kumar	sanjay@gmail.com

3 rows in set (0.00 sec)

```
mysql> create table emp(
-> emp_id int primary key,
-> ename varchar(30),
-> ^C
```

```
mysql> create table emp(
-> emp_id int auto_increment primary key,
-> ename varchar(30),
-> esal decimal(10,2)
-> );
```

Query OK, 0 rows affected (0.03 sec)

```
mysql> insert into emp(ename,esal) values('praveen',2000.0);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> select * from emp;
```

emp_id	ename	esal
1	praveen	2000.00

1 row in set (0.00 sec)

```
mysql> insert into emp(ename,esal) values('jayakumar',3000.0);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from emp;
```

emp_id	ename	esal
1	praveen	2000.00
2	jayakumar	3000.00

```
2 rows in set (0.00 sec)
```

```
mysql> create table backup_emp as
-> select * from emp;
```

```
Query OK, 2 rows affected (0.07 sec)
```

```
Records: 2 Duplicates: 0 Warnings: 0
```

```
mysql> show tables;
```

Tables_in_cg_mysql
backup_emp
company_staff
departments
doctors
emp
employees
students

```
7 rows in set (0.00 sec)
```

```
mysql> select * from backup_emp;
```

emp_id	ename	esal
1	praveen	2000.00
2	jayakumar	3000.00

```
2 rows in set (0.00 sec)
```

```
mysql> -- computed columns
```

```
mysql> -- A computed column in MySQL, also known as a generated column, is a
column whose value is derived from an expression involving other columns in the
same table.
```

```
mysql> create table products(
```

```
-> product_id int auto_increment primary key,
```

```
-> product_name varchar(30),
```

```
-> price decimal(10,2),
```

```
-> quantity int,
```

```
-> totalamount decimal(10,2)generated always as(price*quantity)stored
```

->);

Query OK, 0 rows affected (0.04 sec)

mysql> desc products;

Field	Type	Null	Key	Default	Extra
product_id	int	NO	PRI	NULL	auto_increment
product_name	varchar(30)	YES		NULL	
price	decimal(10,2)	YES		NULL	
quantity	int	YES		NULL	
totalamount	decimal(10,2)	YES		NULL	STORED GENERATED

5 rows in set (0.01 sec)

mysql> insert into products(product_name,price,quantity)values('pc',20000,2);

Query OK, 1 row affected (0.01 sec)

mysql> select * from products;

product_id	product_name	price	quantity	totalamount
1	pc	20000.00	2	40000.00

1 row in set (0.00 sec)

mysql> insert into products(product_name,price,quantity)values('laptop',40000,6);

Query OK, 1 row affected (0.01 sec)

mysql> select * from products;

product_id	product_name	price	quantity	totalamount
1	pc	20000.00	2	40000.00
2	laptop	40000.00	6	240000.00

2 rows in set (0.00 sec)

mysql> update products set price=25000 where product_id=2;

Query OK, 1 row affected (0.01 sec)

Rows matched: 1 Changed: 1 Warnings: 0

mysql> select * from products;

product_id	product_name	price	quantity	totalamount
1	pc	20000.00	2	40000.00
2	laptop	25000.00	6	150000.00

2 rows in set (0.00 sec)

```
mysql> insert into products(product_name,price,quantity)values('moblie',20000,3);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from products;
```

product_id	product_name	price	quantity	totalamount
1	pc	20000.00	2	40000.00
2	laptop	25000.00	6	150000.00
3	moblie	20000.00	3	60000.00

```
3 rows in set (0.00 sec)
```

```
mysql> update products set quantity=3 where product_id=2;
```

```
Query OK, 1 row affected (0.04 sec)
```

```
Rows matched: 1  Changed: 1  Warnings: 0
```

```
mysql> select * from products;
```

product_id	product_name	price	quantity	totalamount
1	pc	20000.00	2	40000.00
2	laptop	25000.00	3	75000.00
3	moblie	20000.00	3	60000.00

```
3 rows in set (0.00 sec)
```

```
mysql> notee
```