

DAY 10: Dictionary and Statements

→ Dict is a collection of key : value pair key must be unique and it should be immutable datatypes(int,str,tuple). It is represented in { }

Eg:

```
details = {1:2,  
'name':'praveen',  
(1,2):[1,2]}  
print(details)
```

Accessing:

→ dict can access by calling key, we will get value from that key

syntax → dict['key']

→ get () method is also used to get the value from that key

syntax → dict.get(key)

Eg:

```
data ={'name':'praveen',
```

```
'balance':7000,
```

```
'adr':589102962346,
```

```
'pan':'GXPITNS457'}
```

```
print(data['adr'])
```

```
print(data.get('name'))
```

Update()

→ method is used to update a key , incase if the key is not present inside the dict then it will add that key:value

syntax → dict.update({key:value})

→ There is another way to update a key

syntax → dict[key]=value

Eg:

```
data.update({'balance':1000000})
```

```
data['ac']=452236897
```

```
values()
```

→ It is used to get all the value from the dict

syntax → dict.values()

Eg:

```
data.values()
```

```
Keys ()
```

→ it is used to get all the keys from the dict

syntax → dict.keys()

Eg:

```
data.keys()
```

```
items()
```

→ it is used to get the both key: values pair in the dict

syntax → dict.items()

Eg:

```
data.items( )
```

```
clear ()
```

→ it is used to delete all the key: values pair in the dict

syntax → dict.clear()

Eg:

```
data.clear()
```

Statements

if

→ if condition become true, then it will execute inside block of code

→ incase it become false, then it will never entry inside block

Eg:

```
age=int(input("enter your age:"))  
if age>=18:  
    print('eligible to vote')  
    print(age)
```

if-else

→ else for if statement is a fall -back statement, incase if condition is false then else block will execute

Eg:

```
age=int(input("enter your age:"))  
if age>=18:  
    print(f'your {age} eligible to vote')  
else:  
    print(f'your {age} you have to wait {18-age}')
```