

ACAN library for Teensy 3.1 / 3.2, 3.5, 3.6

Version 1.0.0

Pierre Molinaro

October xxx, 2017

Contents

1	Versions	2
2	Features	3
3	Data flow	3
4	A simple example: LoopBackDemo	5
5	The CANMessage class	7
6	Driver instances	7
7	Alternate pins	8
8	Sending data frames	8
8.1	tryToSend for sending data frames	8
8.2	Driver transmit buffer size	9
8.3	The transmitBufferSize method	9
8.4	The transmitBufferCount method	10
8.5	The transmitBufferPeakCount method	10
9	Sending remote frames	10
10	Retrieving received messages using the receive method	10
10.1	Driver receive buffer size	12
10.2	The receiveBufferSize method	12
10.3	The receiveBufferCount method	12
10.4	The receiveBufferPeakCount method	12
11	Configuration	12
12	Primary filters	13
12.1	Primary filter example	13
12.2	Primary filter as pass-all filter	14
12.3	Primary filter for matching several identifiers	15
12.4	Primary filter conformance	16

12.5 The receive method revisited	16
13 Secondary filters	17
13.1 Secondary filters, without primary filter	17
13.2 Primary and secondary filters	18
13.3 Secondary filter as pass-all filter	18
13.4 Secondary filter conformance	19
13.5 The receive method revisited	19
14 The dispatchReceivedMessage method	20
15 The ACAN::begin method reference	22
15.1 The ACAN::begin method prototype	22
15.2 The error code	22
15.2.1 CAN Bit setting too far from wished rate	23
15.2.2 CAN Bit inconsistent configuration error	23
15.2.3 Too much primary filters error	24
15.3 Primary filters conformance error	24
15.3.1 Too much secondary filters error	24
15.3.2 Secondary filter conformance error	24
15.3.3 No alternate Tx pin error	24
15.3.4 No alternate Rx pin error	24
16 ACANSettings class reference	24
16.1 The ACANSettings constructor: computation of the CAN bit settings	24
16.2 The checkCANBitSettingConsistency method	27
16.3 The actualBitRate method	28
16.4 The exactBitRate method	29
16.5 The ppmFromWishedBitRate method	29
16.6 The samplePointFromBitStart method	29
16.7 Properties of the ACANSettings class	30
16.7.1 The mListenOnlyMode property	30
16.7.2 The mSelfReceptionMode property	30
16.7.3 The mLoopBackMode property	30
16.7.4 The mMessageIRQPriority property	31
17 CAN controller state	31
17.1 The controllerState method	31
17.2 The receiveErrorCounter method	31
17.3 The transmitErrorCounter method	31

1 Versions

Version	Date	Comment
1.0.0	October xxx, 2017	Initial release

2 Features

The `ACAN` library is a CAN ("Controller Area Network") driver for Teensy 3.x. It has been designed to make it easy to start and to be easily configurable:

- default configuration sends and receives any frame – no default filter to provide;
- efficient built-in CAN bit settings computation from user bit rate;
- user can fully define its own CAN bit setting values;
- reception filters are easily defined – up to 14 primary filters and 18 secondary filters;
- reception filters accept call back functions;
- driver transmit buffer size is customisable;
- driver receive buffer size is customisable;
- overflow of the driver receive buffer is detectable;
- *loop back, self reception, listing only* FlexCAN controller modes are selectable.

3 Data flow

The [figure 1](#) illustrates message flow for sending and receiving CAN messages.

FlexCAN controller is hardware, a module of the micro-controller. It implements 16 MBs (*Mailboxes or Message Buffers*), used for the *data frame transmit buffer*, *remote frame transmit buffer(s)*, *reception FIFO* and *reception filters*. The actual partition depends from the selected configuration – see [table 1](#) and [section 11 page 12](#).

<code>settings.mConfiguration</code>	Reception	Sending remote frames	Sending data frames
<code>k8_0_Filters</code>	8 (MB0 ... MB7)	7 (MB8 ... MB14)	1 (MB15)
<code>k10_6_Filters</code>	10 (MB0 ... MB9)	5 (MB10 ... MB14)	1 (MB15)
<code>k12_12_Filters</code>	12 (MB0 ... MB11)	3 (MB12 ... MB14)	1 (MB15)
<code>k14_18_Filters</code>	14 (MB0 ... MB13)	1 (MB14)	1 (MB15)

Table 1 – FlexCAN MBs assignments, following `settings.mConfiguration` value

Sending messages. The FlexCAN hardware makes sending data frames different from sending remote frames. For both, user code calls the `tryToSend` method – see [section 8 page 8](#) for sending data frames, and [section 9 page 10](#) for sending remote frames. The data frames are stored in the *Driver Transmit Buffer*, before to be moved by the message interrupt service routine into the *data frame transmit buffer*. The size of the *Driver Transmit Buffer* is 16 by default – see [section 8.2 page 9](#) for changing the default value.

Receiving messages. The FlexCAN *CAN Protocol Engine* transmits all correct frames to the *reception filters*. By default, they are configured as pass-all, see [section 12 page 13](#) and [section 13 page 17](#) for configuring them. Messages that pass the filters are stored in the *Reception FIFO*. Its depth is not configurable – it is always 6-message. The message interrupt service routine transfers the messages from *Reception FIFO* to the *Driver Receive Buffer*. The size of the *Driver Receive Buffer* is 32 by default – see [section 10.1 page 12](#) for changing the default value. Three user methods are available:




Figure 1 – Message flow in ACAN driver and FlexCAN controller

- the available method returns `false` if the *Driver Receive Buffer* is empty, and `true` otherwise;
- the receive method retrieves messages from the *Driver Receive Buffer* – see [section 10 page 10](#), [section 12.5 page 16](#) and [section 13.5 page 19](#);
- the `dispatchReceivedMessage` method if you have defined primary and / or secondary filters that name a call-back function – see [section 14 page 20](#).

Sequentiality. The ACAN driver and the configuration of the FlexCAN controller ensures sequentiality of data messages. This means that if an user program calls `tryToSend` first for a message M_1 and then for a message M_2 , the message M_1 will be always retrieved by `receive` or `dispatchReceivedMessage` before the message M_2 .

4 A simple example: LoopBackDemo

The following code is a sample code for introducing the ACAN library. It runs on Teensy 3.1 / 3.2, Teensy 3.5 and Teensy 3.6. It demonstrates how to configure the driver, to send a CAN message, and to receive a CAN message.

Note it runs without any external hardware, it uses the *loop back* mode and the *self reception* mode.

```

1  #include <ACAN.h>
2
3  void setup () {
4      Serial.begin (9600) ;
5      Serial.println ("Hello") ;
6      ACANSettings settings (125 * 1000) ; // 125 kbit/s
7      settings.mLoopBackMode = true ;
8      settings.mSelfReceptionMode = true ;
9      const uint32_t errorCode = ACAN::can0.begin (settings) ;
10     if (0 == errorCode) {
11         Serial.println ("ACAN::can0 ok") ;
12     }else{
13         Serial.print ("Error ACAN::can0: 0x") ;
14         Serial.println (errorCode, HEX) ;
15     }
16 }
17
18 static unsigned gSendDate = 0 ;
19 static unsigned gSentCount = 0 ;
20 static unsigned gReceivedCount = 0 ;
21
22 void loop () {
23     CANMessage message ;
24     if (gSendDate < millis ()) {
25         message.id = 0x542 ;
26         const bool ok = ACAN::can0.tryToSend (message) ;
27         if (ok) {
28             gSendDate += 2000 ;
29             gSentCount += 1 ;
30             Serial.print ("Sent: ") ;
31             Serial.println (gSentCount) ;
32         }
33     }
34     if (ACAN::can0.receive (message)) {

```

```

35     gReceivedCount += 1 ;
36     Serial.print ("Received: ") ;
37     Serial.println (gReceivedCount) ;
38 }
39 }

```

Line 1. This line includes the ACAN library.

Line 6. Configuration is a four-step operation. This line is the first step. It instantiates the `settings` object of the `ACANSettings` class. The constructor has one parameter: the wished CAN bit rate. It returns a `settings` object fully initialized with CAN bit settings for the wished bit rate, and default values for other configuration properties.

Lines 7 and 8. This is the second step. You can override the values of the properties of `settings` object. Here, the `mLoopBackMode` and `mSelfReceptionMode` properties are set to `true` – they are `false` by default. These two properties fully enables *loop back*, that is you can run this demo sketch even if you have no connection to a physical CAN network. The [section 16.7 page 30](#) lists all properties you can override.

Line 9. This is the third step, configuration of the `ACAN::can0` driver with `settings` values. You cannot change the `ACAN::can0` name – see [section 6 page 7](#). The driver is configured for being able to send any (standard / extended, data / remote) frame, and to receive all (standard / extended, data / remote) frames. If you want to define reception filters, see [section 12 page 13](#) and [section 13 page 17](#).

Lines 10 to 15. Last step: the configuration of the `ACAN::can0` driver returns an error code, stored in the `errorCode` constant. It has the value 0 if all is ok – see [section 15.2 page 22](#).

Line 18. The `gSendDate` global variable is used for sending a CAN message every 2 s.

Line 19. The `gSentCount` global variable counts the number of sent messages.

Line 20. The `gReceivedCount` global variable counts the number of received messages.

Line 23. The message object is fully initialized by the default constructor, it represents a standard data frame, with an identifier equal to 0, and without any data – see [section 5 page 7](#).

Line 24. It tests if it is time to send a message.

Line 25. Set the message identifier. In a real code, we set here message data, and for an extended frame the `ext` boolean property.

Line 26. We try to send the data message. Actually, we try to transfer it into the *Driver transmit buffer*. The transfer succeeds if the buffer is not full. The `tryToSend` method returns `false` if the buffer is full, and `true` otherwise. Note the returned value only tells if the transfer into the *Driver transmit buffer* is successful or not: we have no way to know if the frame is actually sent on the the CAN network.

Lines 27 to 32. We act the successfull transfer by setting `gSendDate` to the next send date and incrementing the `gSentCount` variable. Note if the transfer did fail, the send date is not changed, so the `tryToSend` method will be called on the execution of the `loop` function.

Line 34. As the FlexCAN controller is configured in *loop back* mode (see lines 7 and 8), all sent messages are received. The `receive` method returns `false` if no message is available from the *driver reception buffer*. It returns `true` if a message has been successfully removed from the *driver reception buffer*. This message is assigned to the `message` object.

Lines 35 to 37. If a message has been received, the `gReceivedCount` is incremented and displayed.

5 The `CANMessage` class

A *CAN message* is an object that contains all CAN frame user informations. All properties are initialized by default, and represent a standard data frame, with an identifier equal to 0, and without any data.

```
class CANMessage {
public : uint32_t id = 0 ; // Frame identifier
public : bool ext = false ; // false -> standard frame, true -> extended
public : bool rtr = false ; // false -> data frame, true -> remote frame
public : uint8_t idx = 0 ;
public : uint8_t len = 0 ; // Length of data
public : union {
#ifdef __UINT64_TYPE__
    uint64_t data64 ; // Caution: subject to endianness
#endif
    uint32_t data32 [2] ; // Caution: subject to endianness
    uint16_t data16 [4] ; // Caution: subject to endianness
    uint8_t data [8] = {0, 0, 0, 0, 0, 0, 0, 0} ;
} ;
} ;
```

Note the message datas are defined by an **union**. So message datas can be seen as eight bytes, four 16-bits unsigned integers, two 32-bits, or one 64-bits. Be aware that multi-byte integers are subject to endianness (Cortex M4 processors of Teensy 3.x are little-endian).

The `idx` property is not used in CAN frames, but:

- for a received message, it contains the acceptance filter index (see [section 12.5 page 16](#) and [section 13.5 page 19](#));
- it is not used on sending messages.

6 Driver instances

Driver instances are global variables. You cannot choose their names, they are defined by the library.

Teensy	Driver name
Teensy 3.1 / 3.2	<code>ACAN::can0</code>
Teensy 3.5	<code>ACAN::can0</code>
Teensy 3.6	<code>ACAN::can0</code> , <code>ACAN::can1</code>

Table 2 – Driver global variables

Code snippets in this document uses `ACAN::can0`. They also apply to `ACAN::can1` of Teensy 3.6.

Note. Drivers variables are `ACAN` class static properties. This choice may seem strange. However, a common error is to declare its own driver variable:

```
ACAN myCAN ; // Don't do that, it is an error !!!
```

Declaring drivers variables as ACAN class static properties¹ enables the compiler to raise an error if you try to declare your own driver variable.

7 Alternate pins

For using alternate pins, just set `mUseAlternateTxPin` and / or `mUseAlternateRxPin` properties of settings object:

```
ACANSettings settings (125 * 1000) ;
settings.mUseAlternateRxPin = true ;
settings.mUseAlternateTxPin = true ;
const uint32_t errorCode = ACAN::can0.begin (settings) ;
```

By default, these properties are set to `false`. The following table lists default and alternate pins. Note that `ACAN::can1` does not support alternate pins. Trying to set alternate pin for `ACAN::can1` raises error bits in the value returned by `begin` (see [section 15 page 22](#)).

Teensy	Driver name	Default Tx pin	Alternate Tx pin	Default Rx pin	Alternate Rx pin
Teensy 3.1 / 3.2	ACAN::can0	3	32	4	25
Teensy 3.5	ACAN::can0	3	29	4	30
Teensy 3.6	ACAN::can0	3	29	4	30
Teensy 3.6	ACAN::can1	33	No alternate Tx pin	34	No alternate Rx pin

Table 3 – Alternate CAN Tx and Rx pins

8 Sending data frames

Note. This section applies only to **data** frames. For sending remote frames, see [section 9 page 10](#).

8.1 `tryToSend` for sending data frames

Call the method `tryToSend` for sending data frames; it returns:

- `true` if the message has been successfully transmitted to driver transmit buffer; note that does not mean that the CAN frame has been actually sent;
- `false` if the message has not been successfully transmitted to driver transmit buffer, it was full.

So it is wise to systematically test the returned value. One way to achieve this is to loop while there is no room in driver transmit buffer:

```
while (!ACAN::can0.tryToSend (message)) {
    yield () ;
}
```

A better way is to use a global variable to note if message has been successfully transmitted to driver transmit buffer. For example, for sending a message every 2 seconds:

¹The ACAN constructor is declared `private`.


```
static unsigned gSendDate = 0 ;

void loop () {
    CANMessage message ;
    if (gSendDate < millis ()) {
        // Initialize message properties
        const bool ok = ACAN::can0.tryToSend (message) ;
        if (ok) {
            gSendDate += 2000 ;
        }
    }
}
```

An other hint to use a global boolean variable as a flag that remains true while the frame has not been sent.

```
static bool gSendMessage = false ;

void loop () {
    ...
    if (frame_should_be_sent) {
        gSendMessage = true ;
    }
    ...
    if (gSendMessage) {
        CANMessage message ;
        // Initialize message properties
        const bool ok = ACAN::can0.tryToSend (message) ;
        if (ok) {
            gSendMessage = false ;
        }
    }
    ...
}
```

8.2 Driver transmit buffer size

By default, driver transmit buffer size is 16. You can change this default value by setting the `mTransmitBufferSize` property of `settings` variable:

```
ACANSettings settings (125 * 1000) ;
settings.mTransmitBufferSize = 30 ;
const uint32_t errorCode = ACAN::can0.begin (settings) ;
...
```

As the size of `CANMessage` class is 16 bytes, the actual size of the driver transmit buffer is the value of `settings.mTransmitBufferSize * 16`.

8.3 The `transmitBufferSize` method

The `transmitBufferSize` method returns the size of the driver transmit buffer, that is the value of `settings.mTransmitBufferSize`.

```
const uint32_t s = ACAN::can0.transmitBufferSize () ;
```

8.4 The transmitBufferCount method

The transmitBufferCount method returns the current number of messages in the transmit buffer.

```
const uint32_t n = ACAN::can0.transmitBufferCount () ;
```

8.5 The transmitBufferPeakCount method

The transmitBufferPeakCount method returns the peak value of message count in the transmit buffer.

```
const uint32_t max = ACAN::can0.transmitBufferPeakCount () ;
```

If the transmit buffer is full when tryToSend is called, the return value is false. In such case, the following calls of transmitBufferPeakCount will return transmitBufferSize ()+1.

So, when transmitBufferPeakCount returns a value lower or equal to transmitBufferSize (), it means that calls to tryToSend have always returned true.

9 Sending remote frames

Note. This section applies only to **remote** frames. For sending data frames, see [section 8 page 8](#).

The hardware design of the FlexCAN module makes sending remote frames different from data frames.

However, for sending remote frames, you also invoke the tryToSend method. This method understands if a remote frame should be sent, the rtr property of its argument is set (it is cleared by default, denoting a data frame).

```
CanMessage message ;
message.rtr = true ; // Remote frame
...
const bool sent = ACAN::can0.tryToSend (message) ;
...
```

The FlexCAN module embedded in Teensy 3.x microcontrollers implements 16 *mailboxes*, for sending and receiving CAN frames. Following the settings.mConfiguration, it allocates 7, 5, 3 or 1 MBs for sending remote frames, as indicating by the [table 4 page 13](#). By default, settings.mConfiguration is set to k12_12_Filters, as remote frames are rarely needed.

10 Retrieving received messages using the receive method

There are two ways for retrieving received messages :

- using the receive method, as explained in this section;
- using the dispatchReceivedMessage method (see [section 14 page 20](#)).

This is a basic example:

```

void setup () {
    ACANSettings settings (125 * 1000) ;
    ...
    const uint32_t errorCode = ACAN::can0.begin (settings) ; // No receive filter
    ...
}

void loop () {
    CANMessage message ;
    if (ACAN::can0.receive (message)) {
        // Handle received message
    }
}

```

The receive method:

- returns false if the driver receive buffer is empty, message argument is not modified;
- returns true if a message has been removed from the driver receive buffer, and the message argument is assigned.

You need to manually dispatch the received messages. If you did not provide any receive filter, you should check the `rtr` bit (remote or data frame?), the `ext` bit (standard or extended frame), and the `id` (identifier value). The following snippet dispatches three messages:

```

void setup () {
    ACANSettings settings (125 * 1000) ;
    ...
    const uint32_t errorCode = ACAN::can0.begin (settings) ; // No receive filter
    ...
}

void loop () {
    CANMessage message ;
    if (ACAN::can0.receive (message)) {
        if (!message.rtr && message.ext && (message.id == 0x123456)) {
            handle_myMessage_0 (message) ; // Extended data frame, id is 0x123456
        } else if (!message.rtr && !message.ext && (message.id == 0x234)) {
            handle_myMessage_1 (message) ; // Standard data frame, id is 0x234
        } else if (message.rtr && !message.ext && (message.id == 0x542)) {
            handle_myMessage_2 (message) ; // Standard remote frame, id is 0x542
        }
    }
    ...
}

```

The `handle_myMessage_0` function has the following header:

```

void handle_myMessage_0 (const CANMessage & inMessage) {
    ...
}

```

So are the header of the `handle_myMessage_1` and the `handle_myMessage_2` functions.

10.1 Driver receive buffer size

By default, the driver receive buffer size is 32. You can change this default value by setting the `mReceiveBufferSize` property of settings variable:

```
ACANSettings settings (125 * 1000) ;
settings.mReceiveBufferSize = 100 ;
const uint32_t errorCode = ACAN::can0.begin (settings) ;
...
```

As the size of `CANMessage` class is 16 bytes, the actual size of the driver receive buffer is the value of `settings.mReceiveBufferSize * 16`.

10.2 The `receiveBufferSize` method

The `receiveBufferSize` method returns the size of the driver receive buffer, that is the value of `settings.mReceiveBufferSize`.

```
const uint32_t s = ACAN::can0.receiveBufferSize () ;
```

10.3 The `receiveBufferCount` method

The `receiveBufferCount` method returns the current number of messages in the driver receive buffer.

```
const uint32_t n = ACAN::can0.receiveBufferCount () ;
```

10.4 The `receiveBufferPeakCount` method

The `receiveBufferPeakCount` method returns the peak value of message count in the driver receive buffer.

```
const uint32_t max = ACAN::can0.receiveBufferPeakCount () ;
```

Note the driver receive buffer may overflow, if messages are not retrieved (by calls of `receive` or `dispatchReceivedMessage` methods). If an overflow occurs, further calls of `ACAN::can0.receiveBufferPeakCount ()` return `ACAN::can0.receiveBufferSize ()+1`.

11 Configuration

The `mConfiguration` property of the settings variable defines the FlexCAN module configuration – see [table 4](#). By default, its value is `ACANSettings::k12_12_Filters`.

You can easily override the default configuration:

```
void setup () {
    ACANSettings settings (125 * 1000) ;
    settings.mConfiguration = ACANSettings::k14_18_Filters ;
    const uint32_t errorCode = ACAN::can0.begin (settings) ; // No receive filter
    ...
}
```

settings.mConfiguration	Primary filters section 12 page 13	Secondary filters section 13 page 17	MB for sending remote frames section 9 page 10
k8_0_Filters	8	0	7
k10_6_Filters	10	6	5
k12_12_Filters	12	12	3
k14_18_Filters	14	18	1

Table 4 – FlexCAN configuration, following settings.mConfiguration value

12 Primary filters

A first step is to define *receive filters*². The *receive filters* are set to the FlexCAN module, so filtering is performed by hardware, without any CPU charge. The messages that pass the filters are transferred into the FlexCAN Rx FIFO by the FlexCAN module, and transferred into the driver receive buffer by the driver. So the receive method only gets messages that have passed the filters.

The driver lets you to define two kinds of filters: *primary filters* and *secondary filters*³. Making the difference is required by FlexCAN hardware design: *primary filters* are more powerful than *secondary filters*.

12.1 Primary filter example

For defining *primary filters*⁴, you write:

```
void setup () {
    ACANSettings settings (125 * 1000) ;
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
        ACANPrimaryFilter (kData, kStandard, 0x234),    // Filter #1
        ACANPrimaryFilter (kRemote, kStandard, 0x542)   // Filter #2
    } ;
    const uint32_t errorCode = ACAN::can0.begin (settings,
                                                primaryFilters, // The filter array
                                                3) ; // Filter array size
    ...
}

void loop () {
    CANMessage message ;
    if (ACAN::can0.receive (message)) { // Only frames that pass a filter are retrieved
        if (!message.rtr && message.ext && (message.id == 0x123456)) {
            handle_myMessage_0 (message) ; // Extended data frame, id is 0x123456
        } else if (!message.rtr && !message.ext && (message.id == 0x234)) {
            handle_myMessage_1 (message) ; // Standard data frame, id is 0x234
        } else if (message.rtr && !message.ext && (message.id == 0x542)) {
            handle_myMessage_2 (message) ; // Standard remote frame, id is 0x542
        }
    }
}
...
```

²The second step is to use the `dispatchReceivedMessage` method instead of the `receive` method, see [section 14 page 20](#).

³The *primary filters* and *secondary filters* terms are used in this document for simplicity. FlexCAN documentation names them respectively Rx FIFO filter Table Elements Affected by Rx Individual Masks and Rx FIFO filter Table Elements Affected by Rx FIFO Global Mask.

⁴For *secondary filters*, see [section 13 page 17](#).

```
}
```

Each element of the `primaryFilters` constant array defines an acceptance filter. Should be specified⁵:

- the required kind: data frames (`kData`) or remote frames (`kRemote`);
- the required format: standard frames (`kStandard`) or extended frames (`kExtended`);
- the required identifier value.

Maximum number of *primary filters*. The number of *primary filters* is limited: 12 by default, as the default value of `settings.mConfiguration` is `ACANSettings::k12_12_Filters`. See [section 11 page 12](#) for getting the number of *primary filters* for each configuration, and for setting your own configuration.

Test order. The FlexCAN hardware examines the filters in the increasing order of their indexes in the `primaryFilters` constant array. As soon as a match occurs, the message is transferred to Rx FIFO buffer and the examination process is completed. If no match occurs, the message is lost.

A consequence is if a filter appears twice, the second occurrence will never match. In the next example, the Filter #3 will never match, as it is identical to filter #1.

```
void setup () {
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
        ACANPrimaryFilter (kData, kStandard, 0x234),   // Filter #1
        ACANPrimaryFilter (kRemote, kStandard, 0x542), // Filter #2
        ACANPrimaryFilter (kData, kStandard, 0x234)    // Filter #3
    };
    ...
}
```

12.2 Primary filter as pass-all filter

You can specify a primary filter that matches any frame:

```
ACANPrimaryFilter ()
```

You can use it for accepting all frames that did not match previous filters:

```
void setup () {
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
        ACANPrimaryFilter (kData, kStandard, 0x234),   // Filter #1
        ACANPrimaryFilter (kRemote, kStandard, 0x542), // Filter #2
        ACANPrimaryFilter ()                          // Filter #3
    }; // Filter #3 catches any message that did not match filters #0, #1 and #2
    ...
}
```

Be aware if the pass-all filter is not the last one, following ones will never match.

⁵There is a fourth optional argument, that is `NULL` by default – see [section 14 page 20](#).

```

void setup () {
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
        ACANPrimaryFilter (kData, kStandard, 0x234),    // Filter #1
        ACANPrimaryFilter (),                          // Filter #2
        ACANPrimaryFilter (kRemote, kStandard, 0x542)   // Filter #3
    } ; // Filter #3 will never match
    ...
}

```

12.3 Primary filter for matching several identifiers

A primary filter can be configured for matching several identifiers⁶. You provide two values: a `filter_mask` and a `filter_acceptance`. A message with an identifier is accepted if:

$$\text{filter_mask} \& \text{identifier} = \text{filter_acceptance}$$

The `&` operator is the bit-wise *and* operator.

Let's take an example: the filter should match standard data frames with identifiers equal to 0x540, 0x541, 0x542 and 0x543. The four identifiers differs by the two lower bits. As a standard identifiers are 11-bits wide, the `filter_mask` is 0x7FC. The filter acceptance is 0x540. The filter is declared by:

```

...
    ACANPrimaryFilter (kData,      // Accept only data frames
                      kStandard,  // Accept only standard frames
                      0x7FC,      // Filter mask
                      0x540)      // Filter acceptance
    ...
}

```

For a standard frame (11-bit identifier), both `filter_mask` and a `filter_acceptance` should be lower or equal to 0x7FF.

For an extended frame (29-bit identifier), both `filter_mask` and a `filter_acceptance` should be lower or equal to 0x1FFF_FFFF.

Be aware that the `filter_mask` and a `filter_acceptance` must also conform to the following constraint: if a bit is clear in the `filter_mask`, the corresponding bit of the `filter_acceptance` should also be clear. In other words, `filter_mask` and a `filter_acceptance` should check:

$$\text{filter_mask} \& \text{filter_acceptance} = \text{filter_acceptance}$$

For example, the filter mask 0x7FC and the filter acceptance 0x541 do not conform because the bit 0 of `filter_mask` is clear and the bit 0 of the filter acceptance is set.

A non conform filter never matches.

⁶A *secondary filter* cannot be configured for matching several identifiers.

12.4 Primary filter conformance

The pass-all primary filter ([section 12.2 page 14](#)) always conforms.

For a primary filter for matching several identifiers, see [section 12.3 page 15](#).

For a primary filter for one single identifier:

- for a standard frame (11-bit identifier), the given identifier value should be lower or equal to 0x7FF;
- for a extended frame (29-bit identifier), the given identifier value should be lower or equal to 0x1FFF_FFFF.

If one or more primary filters do not conform, the execution of the `begin` method returns an error – see [table 5 page 23](#).

12.5 The receive method revisited

The `receive` method retrieves a received message. When you define primary filters, the value of the `idx` property of the message is the matching filter index. For example:

```
void setup () {
  ACANSettings settings (125 * 1000) ;
  ...
  const ACANPrimaryFilter primaryFilters [] = {
    ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
    ACANPrimaryFilter (kData, kStandard, 0x234),    // Filter #1
    ACANPrimaryFilter (kRemote, kStandard, 0x542)   // Filter #2
  } ;
  const uint32_t errorCode = ACAN::can0.begin (settings, primaryFilters, 3) ;
  ...
}

void loop () {
  CANMessage message ;
  if (ACAN::can0.receive (message)) { // Only frames that pass a filter are retrieved
    switch (message.idx) {
      case 0:
        handle_myMessage_0 (message) ; // Extended data frame, id is 0x123456
        break ;
      case 1:
        handle_myMessage_1 (message) ; // Standard data frame, id is 0x234
        break ;
      case 2:
        handle_myMessage_2 (message) ; // Standard remote frame, id is 0x542
        break ;
      default:
        break ;
    }
  }
  ...
}
```

An improvement is to use the `dispatchReceivedMessage` method – see [section 14 page 20](#).

13 Secondary filters

Depending from the configuration, you can define several *secondary filters* – see [table 4 page 13](#).

13.1 Secondary filters, without primary filter

This is an example without primary filter, and with secondary filters:

```
void setup () {
    ACANSettings settings (125 * 1000) ;
    ...
    const ACANSecondaryFilter secondaryFilters [] = {
        ACANSecondaryFilter (kData, kExtended, 0x123456), // Filter #0
        ACANSecondaryFilter (kData, kStandard, 0x234),    // Filter #1
        ACANSecondaryFilter (kRemote, kStandard, 0x542)   // Filter #2
    } ;
    const uint32_t errorCode = ACAN::can0.begin (settings,
                                                NULL, 0, // No primary filter
                                                secondaryFilters, // The filter array
                                                3) ; // Filter array size
    ...
    void loop () {
        CANMessage message ;
        if (ACAN::can0.receive (message)) { // Only frames that pass a filter are retrieved
            if (!message.rtr && message.ext && (message.id == 0x123456)) {
                handle_myMessage_0 (message) ; // Extended data frame, id is 0x123456
            } else if (!message.rtr && !message.ext && (message.id == 0x234)) {
                handle_myMessage_1 (message) ; // Standard data frame, id is 0x234
            } else if (message.rtr && !message.ext && (message.id == 0x542)) {
                handle_myMessage_2 (message) ; // Standard remote frame, id is 0x542
            }
        }
        ...
    }
}
```

Each element of the `secondaryFilters` constant array defines an acceptance filter. Should be specified⁷:

- the required kind: data frames (`kData`) or remote frames (`kRemote`);
- the required format: standard frames (`kStandard`) or extended frames (`kExtended`);
- the required identifier value.

Maximum number of *secondary filters*. The number of *secondary filters* is limited: 12 by default, as the default value of `settings.mConfiguration` is `ACANSettings::k12_12_Filters`. See [section 11 page 12](#) for getting the number of *primary filters* for each configuration, and for changing default value.

Test order. The FlexCAN hardware examines the filters in the increasing order of their indexes in the `secondaryFilters` constant array. As soon as a match occurs, the message is transferred to Rx FIFO buffer and the examination process is completed. If no match occurs, the message is lost.

A consequence is if a filter appears twice, the second occurrence will never match.

⁷There is a fourth optional argument, that is `NULL` by default – see [section 14 page 20](#).

13.2 Primary and secondary filters

This is an example with one primary filter, and two secondary filters:

```
void setup () {
    ACANSettings settings (125 * 1000) ;
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
    } ;
    const ACANSecondaryFilter secondaryFilters [] = {
        ACANSecondaryFilter (kData, kStandard, 0x234), // Filter #1
        ACANSecondaryFilter (kRemote, kStandard, 0x542) // Filter #2
    } ;
    const uint32_t errorCode = ACAN::can0.begin (settings,
                                                primaryFilters,
                                                1, // Primary filter array size
                                                secondaryFilters,
                                                2) ; // Secondary filter array size
    ...
}

void loop () {
    CANMessage message ;
    if (ACAN::can0.receive (message)) { // Only frames that pass a filter are retrieved
        if (!message.rtr && message.ext && (message.id == 0x123456)) {
            handle_myMessage_0 (message) ; // Extended data frame, id is 0x123456
        } else if (!message.rtr && !message.ext && (message.id == 0x234)) {
            handle_myMessage_1 (message) ; // Standard data frame, id is 0x234
        } else if (message.rtr && !message.ext && (message.id == 0x542)) {
            handle_myMessage_2 (message) ; // Standard remote frame, id is 0x542
        }
    }
    ...
}
```

Test order. The FlexCAN hardware performs sequentially:

- testing the primary filters in the increasing order of their indexes in the `primaryFilters` constant array;
- as soon as a match with a primary filter occurs, the message is transferred to Rx FIFO buffer and the examination process is completed;
- if no match occurs, testing the secondary filters in the increasing order of their indexes in the `secondaryFilters` constant array;
- as soon as a match with a secondary filter occurs, the message is transferred to Rx FIFO buffer and the examination process is completed;
- if no match occurs, the message is lost.

A consequence is if a filter appears twice, the second occurrence will never match. If a secondary filter matches the same message that a primary filter, the secondary filter will never match.

13.3 Secondary filter as pass-all filter

You can specify a secondary filter that matches any frame:

```
ACANSecondaryFilter ()
```

You can use it for accepting all frames that did not match previous filters:

```
void setup () {
  ...
  const ACANSecondaryFilter secondaryFilters [] = {
    ACANSecondaryFilter (kData, kExtended, 0x123456), // Filter #0
    ACANSecondaryFilter (kData, kStandard, 0x234),    // Filter #1
    ACANSecondaryFilter (kRemote, kStandard, 0x542),  // Filter #2
    ACANSecondaryFilter (),                          // Filter #3
  } ; // Filter #3 catches any message that did not match filters #0, #1 and #2
  ...
}
```

Be aware if the pass-all filter is not the last one, following ones will never match.

```
void setup () {
  ...
  const ACANSecondaryFilter primaryFilters [] = {
    ACANSecondaryFilter (kData, kExtended, 0x123456), // Filter #0
    ACANSecondaryFilter (kData, kStandard, 0x234),    // Filter #1
    ACANSecondaryFilter (),                          // Filter #2
    ACANSecondaryFilter (kRemote, kStandard, 0x542)  // Filter #3
  } ; // Filter #3 will never match
  ...
}
```

If you use a primary pass-all filter, secondary filters will never match:

```
void setup () {
  ...
  const ACANPrimaryFilter primaryFilters [] = {
    ACANPrimaryFilter (kData, kExtended, 0x123456) // Filter #0
    ACANPrimaryFilter (),                          // Filter #1 - pass-all
  } ;
  const ACANSecondaryFilter secondaryFilters [] = {
    ACANSecondaryFilter (kData, kStandard, 0x234), // Filter never matches
    ACANSecondaryFilter (kRemote, kStandard, 0x542) // Filter never matches
  } ;
  ...
}
```

13.4 Secondary filter conformance

The pass-all secondary filter ([section 13.3 page 18](#)) always conforms.

For a standard frame (11-bit identifier), a secondary filter definition is conform if the given identifier value is lower or equal to 0x7FF.

For an extended frame (29-bit identifier), a secondary filter definition is conform if the given identifier value is lower or equal to 0x1FFF_FFFF.

13.5 The receive method revisited

The `receive` method retrieves a received message. When you define primary and secondary filters, the value of the `idx` property of the message is the matching filter index. Filters are numbering from

0, starting by the first element of the first primary filter array until the last one, and continuing from the first element of the secondary filter array, until its last element. So the the `idx` property of the message can be used for dispatching the received message:

```
void setup () {
    ACANSettings settings (125 * 1000) ;
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456), // Filter #0
    } ;
    const ACANSecondaryFilter secondaryFilters [] = {
        ACANSecondaryFilter (kData, kStandard, 0x234), // Filter #1
        ACANSecondaryFilter (kRemote, kStandard, 0x542) // Filter #2
    } ;
    const uint32_t errorCode = ACAN::can0.begin (settings,
                                                primaryFilters, 1,
                                                secondaryFilters, 2) ;

    ...
}

void loop () {
    CANMessage message ;
    if (ACAN::can0.receive (message)) { // Only frames that pass a filter are retrieved
        switch (message.idx) {
            case 0:
                handle_myMessage_0 (message) ; // Extended data frame, id is 0x123456
                break ;
            case 1:
                handle_myMessage_1 (message) ; // Standard data frame, id is 0x234
                break ;
            case 2:
                handle_myMessage_2 (message) ; // Standard remote frame, id is 0x542
                break ;
            default:
                break ;
        }
    }
    ...
}
```

An improvement is to use the `dispatchReceivedMessage` method – see [section 14 page 20](#).

14 The `dispatchReceivedMessage` method

The last improvement is to call the `dispatchReceivedMessage` method – do not call the `receive` method any more. You can use it if you have defined primary and / or secondary filters that name a call-back function.

The primary and secondary filter constructors have as a last argument a call back function pointer. It defaults to `NULL`, so until now the code snippets do not use it.

For enabling the use of the `dispatchReceivedMessage` method, you add to each filter definition as last argument the function that will handle the message. In the `loop` function, call the `dispatchReceivedMessage` method: it dispatches the messages to the call back functions.

```
void setup () {
```

```

ACANSettings settings (125 * 1000) ;
...
const ACANPrimaryFilter primaryFilters [] = {
    ACANPrimaryFilter (kData, kExtended, 0x123456, handle_myMessage_0)
} ;
const ACANSecondaryFilter secondaryFilters [] = {
    ACANSecondaryFilter (kData, kStandard, 0x234, handle_myMessage_1),
    ACANSecondaryFilter (kRemote, kStandard, 0x542, handle_myMessage_2)
} ;
const uint32_t errorCode = ACAN::can0.begin (settings,
                                             primaryFilters, 1,
                                             secondaryFilters, 2) ;

...
}

void loop () {
    ACAN::can0.dispatchReceivedMessage () ; // Do not use ACAN::can0.receive any more
    ...
}

```

The `dispatchReceivedMessage` method handles one message at a time. More precisely:

- if it returns `false`, the driver receive buffer was empty;
- if it returns `true`, the driver receive buffer was not empty, one message has been removed and dispatched.

So, the return value can be used for emptying and dispatching all received messages:

```

void loop () {
    while (ACAN::can0.dispatchReceivedMessage ()) {
    }
    ...
}

```

If a filter definition does not name a call back function, the corresponding messages are lost. In the code below, filter #1 does not name a call back function, standard data frames with identifier 0x234 are lost.

```

void setup () {
    ...
    const ACANPrimaryFilter primaryFilters [] = {
        ACANPrimaryFilter (kData, kExtended, 0x123456, handle_myMessage_0)
    } ;
    const ACANSecondaryFilter secondaryFilters [] = {
        ACANSecondaryFilter (kData, kStandard, 0x234), // Filter #1
        ACANSecondaryFilter (kRemote, kStandard, 0x542, handle_myMessage_2)
    } ;
    ...
}

```

The `dispatchReceivedMessage` method has an optional argument – `NULL` by default: a function name. This function is called for every message that passes the receive filters, with an argument equal to the matching filter index:

```

void filterMatchFunction (const uint32_t inFilterIndex) {
    ...
}

```

```

}

void loop () {
    ACAN::can0.dispatchReceivedMessage (filterMatchFunction) ;
    ...
}

```

You can use this function for maintaining statistics about receiver filter matches.

15 The ACAN::begin method reference

15.1 The ACAN::begin method prototype

The begin method prototype is:

```

uint32_t ACAN::begin (const ACANSettings & inSettings,
                     const ACANPrimaryFilter inPrimaryFilters [] = NULL,
                     const uint32_t inPrimaryFilterCount = 0,
                     const ACANSecondaryFilter inSecondaryFilters [] = NULL,
                     const uint32_t inSecondaryFilterCount = 0) ;

```

The four last arguments have default values.

Omitting the last argument makes no secondary filter is defined:

```

const uint32_t errorCode = ACAN::can0.begin (settings,
                                             primaryFilters, primaryFilterCount,
                                             secondaryFilters) ;

```

Omitting the last two arguments makes no secondary filter is defined:

```

const uint32_t errorCode = ACAN::can0.begin (settings, primaryFilters, primaryFilterCount) ;

```

Omitting the last three or the last four arguments makes no primary and no secondary filter is defined – so any (data / remote, standard / extended) frame is received:

```

const uint32_t errorCode = ACAN::can0.begin (settings, primaryFilters) ;

```

```

const uint32_t errorCode = ACAN::can0.begin (settings) ;

```

15.2 The error code

The begin method returns an error code. The value 0 denotes no error. Otherwise, you consider every bit as an error flag, as described in [table 5](#). An error code could report several errors.

The ACAN class defines bit error masks as public static constant properties:

```

public: static const uint32_t kCANBitConfigurationTooFarFromWishedBitRate = 1 << 0 ;
public: static const uint32_t kCANBitInconsistentConfiguration           = 1 << 1 ;
public: static const uint32_t kTooMuchPrimaryFilters                    = 1 << 2 ;
public: static const uint32_t kNotConformPrimaryFilter                  = 1 << 3 ;
public: static const uint32_t kTooMuchSecondaryFilters                  = 1 << 4 ;
public: static const uint32_t kNotConformSecondaryFilter                = 1 << 5 ;
public: static const uint32_t kNoAlternateTxPinForCan1                  = 1 << 6 ;
public: static const uint32_t kNoAlternateRxPinForCan1                  = 1 << 7 ;

```

Error Codes									Comment	Link
31 – 8	7	6	5	4	3	2	1	0		
0 ... 0	0	0	0	0	0	0	0	0	No error	
0 ... 0	0	0	0	0	0	0	0	1	CAN Bit configuration too far from wished bit rate	section 15.2.1 page 23
0 ... 0	0	0	0	0	0	0	1	0	Inconsistent CAN Bit configuration	section 15.2.2 page 23
0 ... 0	x	x	x	x	x	1	0	0	Too much primary filters	section 15.2.3 page 24
0 ... 0	x	x	x	x	1	x	0	0	Primary filter conformance error	section 15.3 page 24
0 ... 0	x	x	x	1	x	x	0	0	Too much secondary filters	section 15.3.1 page 24
0 ... 0	x	x	1	x	x	x	0	0	Secondary filter conformance error	section 15.3.2 page 24
0 ... 0	x	1	x	x	x	x	0	0	ACAN::can1 has no Tx alternate pin	section 15.3.3 page 24
0 ... 0	1	x	x	x	x	x	0	0	ACAN::can1 has no Rx alternate pin	section 15.3.4 page 24

Table 5 – The ACAN::begin method error codes

For example, you can write:

```
const uint32_t errorCode = ACAN::can0.begin (settings,
                                             primaryFilters, primaryFilterCount,
                                             secondaryFilters, secondaryFilterCount) ;

if (errorCode != 0) {
    // Error(s)
    if (errorCode & ACAN::kTooMuchPrimaryFilters) {
        // Error: too much primary filters
    }
    ...
}
```

15.2.1 CAN Bit setting too far from wished rate

This error is raised when the `mBitConfigurationClosedToWishedRate` of the `settings` object is false. This means that the `ACANSettings` constructor cannot compute a CAN bit configuration close enough to the wished bit rate. When the `begin` is called with `settings.mBitConfigurationClosedToWishedRate` false, this error is reported. For example:

```
void setup () {
    ACANSettings settings (1) ; // 1 bit/s !!!
    // Here, settings.mBitConfigurationClosedToWishedRate is false
    const uint32_t errorCode = ACAN::can0.begin (settings) ;
    // Here, errorCode == ACAN::kCANBitConfigurationTooFarFromWishedBitRateErrorMask
}
```

This error is a fatal error, the driver and the FlexCAN module are not configured. See [section 16.1 page 24](#) for a discussion about CAN bit setting computation.

15.2.2 CAN Bit inconsistent configuration error

This error is raised when you have changed the CAN bit properties (`mBitRatePrescaler`, `mPropagationSegment`, `mPhaseSegment1`, `mPhaseSegment2`, `mRJV`), and one or more resulting values are inconsistent. See [section 16.2 page 27](#).

15.2.3 Too much primary filters error

The number of *primary filters* is limited. See [section 11 page 12](#) for getting the number of *primary filters* for each configuration, and for changing default value.

15.3 Primary filters conformance error

One or several primary filters do not conform: see [section 12.4 page 16](#). Comment out primary filter definitions until finding the faulty definition.

15.3.1 Too much secondary filters error

The number of *secondary filters* is limited. See [section 11 page 12](#) for getting the number of *secondary filters* for each configuration, and for changing default value.

15.3.2 Secondary filter conformance error

One or several secondary filters do not conform: see [section 13.4 page 19](#). Comment out secondary filter definitions until finding the faulty definition.

15.3.3 No alternate Tx pin error

In the Teensy 3.6, `ACAN::can1` does not support alternate Tx pin.

15.3.4 No alternate Rx pin error

In the Teensy 3.6, `ACAN::can1` does not support alternate Rx pin.

16 ACANSettings class reference

Note. The `ACANSettings` class is not Arduino specific. You can compile it on your desktop computer with your favorite C++ compiler.

16.1 The `ACANSettings` constructor: computation of the CAN bit settings

The constructor of the `ACANSettings` has one mandatory argument: the wished bit rate. It tries to compute the CAN bit settings for this bit rate. If it succeeds, the constructed object has its `mBitConfigurationClosedToWishedRate` property set to `true`, otherwise it is set to `false`. For example:

```
void setup () {  
    ACANSettings settings (1 * 1000 * 1000) ; // 1 Mbit/s  
    // Here, settings.mBitConfigurationClosedToWishedRate is true  
    ...  
}
```


16.1 The ACANSettings constructor: computation of the CAN bit settings

Of course, CAN bit computation always succeeds for classical bit rates: 1 Mbit/s, 500 kbit/s, 250 kbit/s, 125 kbit/s. But CAN bit computation can also succeed for some unusual bit rates, as 842 kbit/s. You can check the result by computing actual bit rate, and the distance from the wished bit rate:

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (842 * 1000) ; // 842 kbit/s
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
  Serial.print ("actual_bit_rate: ") ;
  Serial.println (settings.actualBitRate ()) ; // 842105 bit/s
  Serial.print ("distance: ") ;
  Serial.println (settings.ppmFromWishedBitRate ()) ; // 124 ppm
  ...
}
```

The actual bit rate is 842,105 bit/s, and its distance from wished bit rate is 124 ppm. "ppm" stands for "part-per-million", and 1 ppm = 10^{-6} . In other words, 10,000 ppm = 1%.

By default, a wished bit rate is accepted if the distance from the computed actual bit rate is lower or equal to 1,000 ppm = 0.1 %. You can change this default value by adding your own value as second argument of ACANSettings constructor:

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (842 * 1000, 100) ; // 842 kbit/s, max distance is 100 ppm
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 0 (--> is false)
  Serial.print ("actual_bit_rate: ") ;
  Serial.println (settings.actualBitRate ()) ; // 842105 bit/s
  Serial.print ("distance: ") ;
  Serial.println (settings.ppmFromWishedBitRate ()) ; // 124 ppm
  ...
}
```

The second argument does not change the CAN bit computation, it only changes the acceptance test. For example, you can specify that you want the computed actual bit to be exactly the wished bit rate:

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (500 * 1000, 0) ; // 500 kbit/s, max distance is 0 ppm
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
  Serial.print ("actual_bit_rate: ") ;
  Serial.println (settings.actualBitRate ()) ; // 500,000 bit/s
  Serial.print ("distance: ") ;
  Serial.println (settings.ppmFromWishedBitRate ()) ; // 0 ppm
  ...
}
```

The fastest exact bit rate is 3,2 Mbit/s. It works when the FlexCAN module is configured in both *loop back* mode ([section 16.7.3 page 30](#)) and *self reception* mode ([section 16.7.2 page 30](#)). Note bit rates above 1 Mbit/s do not conform to the ISO-11898; CAN transceivers as MCP2551 require the bit rate lower or equal to 1 Mbit/s.

The slowest exact bit rate is 2.5 kbit/s. Note many CAN transceivers as the MCP2551 provide "*detection of ground fault (permanent Dominant) on TXD input*". For example, the MCP2551 constraints the

16.1 The ACANSettings constructor: computation of the CAN bit settings

bit rate to be greater or equal to 16 kbit/s. If you want to work with slower bit rates and you need a transceiver, use one without this detection, as the PCA82C250.

In any way, the bit rate computation always gives an actual bit rate closest from the wished bit rate. For example:

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (440 * 1000) ; // 440 kbit/s
  Serial.print ( "mBitConfigurationClosedToWishedRate:_\n" ) ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 0 (--> is false)
  Serial.print ( "actual_bit_rate:_\n" ) ;
  Serial.println (settings.actualBitRate () ) ; // 444,444 bit/s
  Serial.print ( "distance:_\n" ) ;
  Serial.println (settings.ppmFromWishedBitRate () ) ; // 10,100 ppm
  ...
}
```

You can get the details of the CAN bit decomposition. For example:

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (440 * 1000) ; // 440 kbit/s
  Serial.print ( "mBitConfigurationClosedToWishedRate:_\n" ) ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 0 (--> is false)
  Serial.print ( "actual_bit_rate:_\n" ) ;
  Serial.println (settings.actualBitRate () ) ; // 444,444 bit/s
  Serial.print ( "distance:_\n" ) ;
  Serial.println (settings.ppmFromWishedBitRate () ) ; // 10,100 ppm
  Serial.print ( "Bit_rate_prescaler:_\n" ) ;
  Serial.println (settings.mBitRatePrescaler) ; // BRP = 2
  Serial.print ( "Propagation_segment:_\n" ) ;
  Serial.println (settings.mPropagationSegment) ; // PropSeg = 6
  Serial.print ( "Phase_segment_1:_\n" ) ;
  Serial.println (settings.mPhaseSegment1) ; // PS1 = 5
  Serial.print ( "Phase_segment_2:_\n" ) ;
  Serial.println (settings.mPhaseSegment2) ; // PS2 = 6
  Serial.print ( "Resynchronization_Jump_Width:_\n" ) ;
  Serial.println (settings.mRJW) ; // RJW = 4
  Serial.print ( "Triple_Sampling:_\n" ) ;
  Serial.println (settings.mTripleSampling) ; // 0, meaning single sampling
  Serial.print ( "Sample_Point:_\n" ) ;
  Serial.println (settings.samplePointFromBitStart () ) ; // 68, meaning 68%
  Serial.print ( "Consistency:_\n" ) ;
  Serial.println (settings.checkCANBitSettingConsistency () ) ; // 0, meaning Ok
  ...
}
```

The samplePointFromBitStart method returns sample point, expressed in per-cent of the bit duration from the beginning of the bit.

Note the computation may calculate a bit decomposition too far from the wished bit rate, but it is always consistent. You can check this by calling the checkCANBitSettingConsistency method.

You can change the property values for adapting to the particularities of your CAN network propagation time. By example, you can increment the mPhaseSegment1 value, and decrement the mPhaseSegment2 value in order to sample the CAN Rx pin later.

```
void setup () {
```

```

Serial.begin (9600) ;
ACANSettings settings (500 * 1000) ; // 500 kbit/s
Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
settings.mPhaseSegment1 ++ ; // 5 -> 6: safe, 1 <= PS1 <= 8
settings.mPhaseSegment2 -- ; // 5 -> 4: safe, 2 <= PS2 <= 8 and RJW <= PS2
Serial.print ("Sample Point: ") ;
Serial.println (settings.samplePointFromBitStart ()) ; // 75, meaning 75%
Serial.print ("actual_bit_rate: ") ;
Serial.println (settings.actualBitRate ()) ; // 500000: ok, bit rate did not change
Serial.print ("Consistency: ") ;
Serial.println (settings.checkCANBitSettingConsistency ()) ; // 0, meaning Ok
...
}

```

Be aware to always respect CAN bit timing consistency! The constraints are:

$$\begin{aligned}
 1 &\leq \text{mBitRatePrescaler} \leq 256 \\
 1 &\leq \text{mRJW} \leq 4 \\
 1 &\leq \text{mPropagationSegment} \leq 8 \\
 \text{Single sampling: } 1 &\leq \text{mPhaseSegment1} \leq 8 \\
 \text{Triple sampling: } 2 &\leq \text{mPhaseSegment1} \leq 8 \\
 2 &\leq \text{mPhaseSegment2} \leq 8 \\
 \text{mRJW} &\leq \text{mPhaseSegment2}
 \end{aligned}$$

Resulting actual bit rate is given by:

$$\text{Actual bit rate} = \frac{16 \text{ MHz}}{\text{mBitRatePrescaler} \cdot (1 + \text{mPropagationSegment} + \text{mPhaseSegment1} + \text{mPhaseSegment2})}$$

And sampling point (in per-cent unit) are given by:

$$\text{Sampling point (single sampling)} = 100 \cdot \frac{1 + \text{mPropagationSegment} + \text{mPhaseSegment1}}{1 + \text{mPropagationSegment} + \text{mPhaseSegment1} + \text{mPhaseSegment2}}$$

$$\text{Sampling first point (triple sampling)} = 100 \cdot \frac{\text{mPropagationSegment} + \text{mPhaseSegment1}}{1 + \text{mPropagationSegment} + \text{mPhaseSegment1} + \text{mPhaseSegment2}}$$

16.2 The checkCANBitSettingConsistency method

This method checks the CAN bit decomposition (given by mBitRatePrescaler, mPropagationSegment, mPhaseSegment1, mPhaseSegment2, mRJW property values) is consistent.

```

void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (500 * 1000) ; // 500 kbit/s
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
  settings.mPhaseSegment1 = 0 ; // Error, mPhaseSegment1 should be >= 1 (and <= 8)
  Serial.print ("Consistency: 0x") ;
}

```

```
Serial.println (settings.checkCANBitSettingConsistency (), HEX) ; // 0x10, meaning error
...
}
```

The checkCANBitSettingConsistency method returns 0 if CAN bit decomposition is consistent. Otherwise, the returned value is a bit field that can report several errors – see [table 6](#).

Error Codes												Error
31 – 11	10	9	8	7	6	5	4	3	2	1	0	
0 ... 0	0	0	0	0	0	0	0	0	0	0	0	No error
0 ... 0	x	x	x	x	x	x	x	x	x	x	1	mBitRatePrescaler == 0
0 ... 0	x	x	x	x	x	x	x	x	x	1	x	mBitRatePrescaler > 256
0 ... 0	x	x	x	x	x	x	x	x	1	x	x	mPropagationSegment == 0
0 ... 0	x	x	x	x	x	x	x	1	x	x	x	mPropagationSegment > 8
0 ... 0	x	x	x	x	x	x	1	x	x	x	x	mPhaseSegment1 == 0
0 ... 0	x	x	x	x	x	1	x	x	x	x	x	mPhaseSegment1 > 8
0 ... 0	x	x	x	x	1	x	x	x	x	x	x	mPhaseSegment2 == 0
0 ... 0	x	x	x	1	x	x	x	x	x	x	x	mPhaseSegment2 > 8
0 ... 0	x	x	1	x	x	x	x	x	x	x	x	mRJW == 0
0 ... 0	x	1	x	x	x	x	x	x	x	x	x	mRJW > 4
0 ... 0	1	x	x	x	x	x	x	x	x	x	x	mRJW > mPhaseSegment2

Table 6 – The ACANSettings::checkCANBitSettingConsistency method error codes

The ACANSettings class defines static constant properties that can be used as mask error:

```
public: static const uint32_t kBitRatePrescalerIsZero           = 1 << 0 ;
public: static const uint32_t kBitRatePrescalerIsGreaterThan256 = 1 << 1 ;
public: static const uint32_t kPropagationSegmentIsZero        = 1 << 2 ;
public: static const uint32_t kPropagationSegmentIsGreaterThan8 = 1 << 3 ;
public: static const uint32_t kPhaseSegment1IsZero             = 1 << 4 ;
public: static const uint32_t kPhaseSegment1IsGreaterThan8     = 1 << 5 ;
public: static const uint32_t kPhaseSegment2IsZero             = 1 << 6 ;
public: static const uint32_t kPhaseSegment2IsGreaterThan8     = 1 << 7 ;
public: static const uint32_t kRJWIsZero                        = 1 << 8 ;
public: static const uint32_t kRJWIsGreaterThan4               = 1 << 9 ;
public: static const uint32_t kRJWIsGreaterThanPhaseSegment2  = 1 << 10 ;
```

16.3 The actualBitRate method

The actualBitRate method returns the actual bit computed from mBitRatePrescaler, mPropagationSegment, mPhaseSegment1, mPhaseSegment2, mRJW property values.

```
void setup () {
    Serial.begin (9600) ;
    ACANSettings settings (440 * 1000) ; // 440 kbit/s
    Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
    Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 0 (--> is false)
    Serial.print ("actual_bit_rate: ") ;
    Serial.println (settings.actualBitRate ()) ; // 444,444 bit/s
    ...
}
```

Note. If CAN bit settings are not consistent (see [section 16.2 page 27](#)), the returned value is irrelevant.

16.4 The exactBitRate method

The `exactBitRate` method returns `true` if the actual bit rate is equal to the wished bit rate, and `false` otherwise.

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (842 * 1000) ; // 842 kbit/s
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
  Serial.print ("actual_bit_rate: ") ;
  Serial.println (settings.actualBitRate ()) ; // 842105 bit/s
  Serial.print ("distance: ") ;
  Serial.println (settings.ppmFromWishedBitRate ()) ; // 124 ppm
  Serial.print ("Exact: ") ;
  Serial.println (settings.exactBitRate ()) ; // 0 (---> false)
  ...
}
```

Note. If CAN bit settings are not consistent (see [section 16.2 page 27](#)), the returned value is irrelevant.

16.5 The ppmFromWishedBitRate method

The `ppmFromWishedBitRate` method returns the distance from the actual bit rate to the wished bit rate, expressed in part-per-million (ppm): $1 \text{ ppm} = 10^{-6}$. In other words, $10,000 \text{ ppm} = 1\%$.

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (842 * 1000) ; // 842 kbit/s
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
  Serial.print ("actual_bit_rate: ") ;
  Serial.println (settings.actualBitRate ()) ; // 842105 bit/s
  Serial.print ("distance: ") ;
  Serial.println (settings.ppmFromWishedBitRate ()) ; // 124 ppm
  ...
}
```

Note. If CAN bit settings are not consistent (see [section 16.2 page 27](#)), the returned value is irrelevant.

16.6 The samplePointFromBitStart method

The `samplePointFromBitStart` method returns the distance of sample point from the start of the CAN bit, expressed in part-per-cent (ppc): $1 \text{ ppc} = 1\% = 10^{-2}$. If triple sampling is selected, the returned value is the distance of the first sample point from the start of the CAN bit. It is a good practice to get sample point from 65% to 80%.

```
void setup () {
  Serial.begin (9600) ;
  ACANSettings settings (500 * 1000) ; // 500 kbit/s
  Serial.print ("mBitConfigurationClosedToWishedRate: ") ;
  Serial.println (settings.mBitConfigurationClosedToWishedRate) ; // 1 (--> is true)
}
```

```

Serial.print ( "Sample_point:␣" ) ;
Serial.println ( settings.samplePointFromBitStart () ) ; // 68 --> 68%
...
}

```

Note. If CAN bit settings are not consistent (see [section 16.2 page 27](#)), the returned value is irrelevant.

16.7 Properties of the ACANSettings class

All properties of the ACANSettings class are declared public and are initialized ([table 7](#)). The default values of properties from mWhishedBitRate until mTripleSampling corresponds to a CAN bit rate of 250,000 bit/s.

Property	Type	Initial value	Comment
mWhishedBitRate	uint32_t	250,000	See section 16.1 page 24
mBitRatePrescaler	uint16_t	4	See section 16.1 page 24
mPropagationSegment	uint8_t	5	See section 16.1 page 24
mPhaseSegment1	uint8_t	5	See section 16.1 page 24
mPhaseSegment2	uint8_t	5	See section 16.1 page 24
mRJV	uint8_t	4	See section 16.1 page 24
mTripleSampling	bool	false	See section 16.1 page 24
mBitConfigurationClosedToWishedRate	bool	true	See section 16.1 page 24
mListenOnlyMode	bool	false	See section 16.7.1 page 30
mSelfReceptionMode	bool	false	See section 16.7.2 page 30
mLoopBackMode	bool	false	See section 16.7.3 page 30
mConfiguration	tConfiguration	k12_12_Filters	See section 11 page 12
mUseAlternateTxPin	bool	false	See section 7 page 8
mUseAlternateRxPin	bool	false	See section 7 page 8
mMessageIRQPriority	uint8_t	64	See section 16.7.4 page 31
mReceiveBufferSize	uint16_t	32	See section 10.1 page 12
mTransmitBufferSize	uint16_t	16	See section 8.2 page 9

Table 7 – Properties of the ACANSettings class

16.7.1 The mListenOnlyMode property

This boolean property corresponds to the LOM bit of the FlexCAN CTRL1 control register.

16.7.2 The mSelfReceptionMode property

This boolean property corresponds to the complement of the SRXDIS bit of the FlexCAN MCR control register.

16.7.3 The mLoopBackMode property

This boolean property corresponds to the LBP bit of the FlexCAN CTRL1 control register.

16.7.4 The `mMessageIRQPriority` property

This property sets the priority of the *CAN message* interrupt. Highest priority is 0, lowest is 255.

17 CAN controller state

Three methods return the CAN controller state, the receive error counter and the transmit error counter.

17.1 The `controllerState` method

```
public: tControllerState controllerState (void) const ;
```

This method returns the current state (*error active*, *error passive*, *bus off*) of the CAN controller. The `tControllerState` type is defined by an enumeration:

```
typedef enum {kActive, kPassive, kBusOff} tControllerState ;
```

17.2 The `receiveErrorCounter` method

```
public: uint32_t receiveErrorCounter (void) const ;
```

17.3 The `transmitErrorCounter` method

```
public: uint32_t transmitErrorCounter (void) const ;
```

As the `CANx_ESR` FlexCAN control register does not return a valid value when the CAN controller is in the *bus off* state, the value 256 is forced.