Campaign Object

An Account Engagement campaign tracks the first interaction that a person has with your online marketing materials. Associate your assets to an Account Engagement campaign to organize and track your marketing efforts. Learn more about Account Engagement campaigns in Salesforce Help.

Include the authentication header with every request. For information on how to authenticate, see Authentication.

Resource Name OperationsDescription

Campaign Create POST Create a campaign record.

Campaign Read GET Request information for a single campaign.

Campaign Query GET Request information for the campaigns that match the specified criteria.

Campaign Update POST Update a campaign's information, including campaign fields.

Note: We recommend using Salesforce Connected Campaigns. When Connected Campaigns is enabled, only Campaign Read and Campaign Query are available.

Create a campaign with the specified fields.

You can use any campaign field as a parameter. For a list of campaign fields, see Campaign.

Create a campaign with the name New Campaign and a cost of 2,000.

Request information for a single campaign.

Replace <ID> with the Account Engagement ID of the campaign.

Request information for the campaign with ID 12341xxx.

Request information about the campaigns that match the specified criteria. You can specify which campaigns and which fields to request. A maximum of 200 campaigns are returned, unless you specify the output as mobile. If you specify the output as mobile, then all campaigns are returned.

Note: To request information about a specific campaign, use Campaign Read.

Use these parameters to specify which campaigns are returned. Parameters can be used in any combination and in any order unless otherwise specified.

Notes:

Parameters must be URL-encoded.

Dates and times must use GNU Date Input Syntax (yyyy-mm-dd:hh:ss).

For a full listing of campaign fields see Object Field References.

Parameter	Type	Possible Values	Description
created_after	string	<pre>today, yesterday, last_7_days, this_month, last_month,<custom_time< pre=""></custom_time<></pre>	Request campaigns created after the specified date and time. Example: To request forms created in 2020, use >/api/campaigns/version/3/do/query? created after=2019-12-31 24:59:59.
created_before	string	<pre>today, yesterday, last_7_days, this_month, last_month, <custom_time></custom_time></pre>	Request campaigns created before the specified date and time.
id_greater_thar	nintege	rAny positive integer	Request campaigns that have an Account Engagement ID greater than the specified number.
id_less_than	intege	rAny positive integer	Returns campaigns that have an Account Engagement ID less than the specified number.
name	string	string	Request campaigns with the specified name.
updated_after	string	<pre>today, yesterday, last_7_days, this_month, last_month, <custom time=""></custom></pre>	Request campaigns that were last updated after the specified date and time.
updated_before	string	<pre>today, yesterday, last_7_days, this_month, last_month, <custom_time></custom_time></pre>	Request campaigns that were last updated before the specified date and time.

Use these parameters to specify which campaign fields are returned, and how the campaigns are sorted.

Parameter Type Possible Values Description

Parameter	Type	Possible Values	Description
limit	integer	Any integer from 1 through 200.	The number of campaigns to return. Default value is 200.
offset	integer		The number of campaigns to omit from the response (the number to "skip over"). Example: Retrieve a list of campaigns, omitting the 50 most recently updated campaigns. Sort the query by the updated_at field and use offset=50: api/campaign/version/3/do/query? sort by=updated at&offset=50
sort_by	string	<pre>created_at,id, name, updated at,cost</pre>	The field by which the results are sorted. See Sort Order.
sort_order	_	ascending, descending	The sort order. The default value depends on which $\verb sort_by $ value you specify. See Sort Order.
1100 1	to oppositive	which field A cocupt F	bacacament uses to sent the requite. Different fields have different default sent

Use <code>sort_by</code> to specify which field Account Engagement uses to sort the results. Different fields have different default sort orders.

Value Default Sort OrderDescription

created_at descending Sort the results by the campaigns' created_at timestamps.

id ascending Sort the results by the campaigns' id fields.

name ascending Sort the results by the campaigns' name fields.

updated at **descending** Sort the results by the campaigns' updated at timestamps.

cost descending Sort the results by the campaigns' cost fields.

Request a list of campaigns, sorted in ascending order by cost.

Update a campaign's information, including campaign fields. Fields that aren't specified in the request aren't changed. To clear a field, use a null value.

Returns an updated version of the campaign.

Replace < ID> with the Account Engagement ID of the campaign.

You can use any campaign field as a parameter. For a list of campaign fields, see Object Field References.

To update a campaign's name to "March Webinar" and reset the cost as blank, use the following POST command:

The XML response for a query request contains information about multiple campaigns. The XML response for a read request contains information about a single campaign.

Tag Description

<result>
Parent tag. Contains the campaigns that match the parameters specified in your query.

<total_results>The number of campaigns selected by the query. **Note:** The query request returns a maximum of 200 campaigns. If your query matches more than 200 campaigns, you can make several requests to retrieve all matching records.

<campaign> The information for a single campaign. For information about campaign fields, see Campaign.

Tag Description

<campaign> The information for a single campaign. For information about campaign fields, see Campaign.