Модуль пользовательского интерфейса App(): ReactElement NavigationEntry(): ReactElement HorizontalPicker(props: HorizontalPickerProps): ReactElement TextInput(props: TextInputProps): ReactElement LoginScreen(): ReactElement RegisterScreen(): ReactElement HistoryScreen(): ReactElement HomeDrawer(): ReactElement PaymentMethodComponent(props: PMProps): ReactElement AddCard(): ReactElement PaymentsList(): ReactElement ProfileScreen(): ReactElement Status(): ReactElement Pointer(): ReactElement HomeScreen(): ReactElement RideRequest(): ReactElement DriverOnRideStatus(): ReactElement SearchBlock(): ReactElement SearchResultsBlock(): ReactElement ChooseClass(): ReactElement CustomerRideStatus(): ReactElement



+setAuthToken(token: string): AxiosInstance +post<K, T>(route: string, data: K): Promise<Response<T>> +get<K, T>(route: string, config: K): Promise<Response<T>> ConnectionGatewayAPI -authToken: string -isClient: boolean -listeners: Array<WSMessage => void> -socket: Socket | null +setIsClient(isClient: boolean) +setAuthToken(token: string) +addEventListener(listener: WSMessage => void): () => void +connect() +send<T>(event: WSMessageType, data: T) +disconnect() -retryConnection()

axios: AxiosInstance

+initialize()

PaymentsAPI

-restGatewayAPI: RestGatewayAPI

+getPaymentMethods(): Promise<Response<Array<PaymentMethod>>>
+setAsDefaultMethod(id: number): Promise<Response<unknown>>
+addCard(data: CardMethodDetails): Promise<Response<unknown>>
+createPaymentIntent(data: CreatePaymentIntentInput):
Promise<Response<string>>
+removePaymentMethod(id: number): Promise<Response<unknown>>
+paymentFinished(data: PaymentFinishedInput):
Promise<Response<unknown>>

NavigationService
-navigationRef: NavigationContainerRef<any> | null
+setNavigationRef(ref: NavigationContainerRef<any>
+goBack()

MapService
-map: MutableRefObject<MapView>
+getMapRef(): MutableRefObject<MapView>
+animateCamera(location: Location, zoom: number)
+animateToRegion(pos1: Location, pos2: Location)

HatestLocation: Location

+initialize()
+getLocation(): Location

+subscribeToPositionChange(Location => void):
() => void

Модуль работы с хранилищем

userReducer(state: UserState, action: Action<any>):
UserState
historyReducer(state: HistoryState, action:
Action<any>): HistoryState
paymentsReducer(state: PaymentsState, action:
Action<any>): PaymentsState
homeReducer(state: HomeState, action:
Action<any>): HomeState
rootReducer(state: ApplicationState, action:
Action<any>): ApplicationState

-restGatewayAPI: RestGatewayAPI
-connectionGatewayAPI: ConnectionGatewayAPI
+decode(data: Location):
Promise<Response<ExtendedLocation>>
+updateMyLocation(data: Location):
+requestRide(data: ExtendedRequestRide)
+answerToRideRequest(answer: WSMessageType)
+fetchPlaces(toSearch: string):
Promise<Response<Array<ExtendedLocation>>>
+calculateRideData(from: ExtendedLocation, to:
ExtendedLocation):
Promise<Response<RideRequest>>
+declineRideRequest()
+updateRideStatus(status: RideStatus)

-restGatewayAPI: RestGatewayAPI
-login(email: string, password: string):
Promise<Response<Tokens>>
+register(data: RegisterPayload):
Promise<Response<Tokens>>
+refreshTokens<K, T>(token: string):
Promise<Response<Tokens>>

ProfileAPI

+getUser(): Promise<Response<User>>>

HistoryAPI

-restGatewayAPI: RestGatewayAPI

Promise<Response<Array<Ride>>>

getHistory()

restGatewayAPI: RestGatewayAPI

<enumeration>> WSMessageType
RideRequest
RideStatusChange
RideAccept
RideStopSearch
RideTimeout
LocationUpdate

Tokens
+token: string
+refreshToken: string

+calculatedTime: number
+route: Array<Location>
+to: ExtendedLocation
+from: ExtendedLocation
+cost: number
+carClass: CarClass

<enumeration>> CardBrand
Visa
Mastercard
AmericanExpress

+id: number +carBrand: string +carClass: CarClass +balance: number

<enumeration>> CarClass

Economy

Comfort

Business

+id: number
+client: User
+driver: User
+const: number
+payment: Optional<Payment>
+startTime: number
+endTime: number
+to: string
+from: string
+status: RideStatus
+paid: boolean

<enumeration>> RideStatus
Starting
InProgress
Completed
NoRide

+id: number
+email: string
+phone: string
+firstName: string
+lastName: string
+gender: Gender
+driver: Optional<Driver>

<enumeration>>
PaymentMethodType

Cash
Card

Location
+latitude: number
+longitude: number

<<enumeration>> Gender
Male
Female

ExtendedLocation
+latitude: number
+longitude: number
+readableDescription: string

RideRequest
+calculatedTime: number
+route: Array<Location>
+classes: Record<CarClass, number>

+id: number +type: PaymentMethodType +isDefault: boolean +details: Optional<PaymentMethodDetails>

PaymentMethod

PaymentMethodDetails

+id: number

+lastFour: string

+exp: string

+holder: string

+brand: CardBrand

+stripePaymentId: string

AuthService Repository -authDataRepository: AuthDataRepository -tokenProvider: TokenProvider -userService: UserService AuthDataRepository hasher: Hasher AuthController +constructor(authService: AuthService, tokenProvider: -authService: AuthService TokenProvider, userService: UserService, hasher: Hasher) -constructor(authService: AuthService) +login(email: string, password: string): Promise<Tokens> +login(data: LoginInput): Promise<Tokens> UserRepository +register(data: RegisterInput): Promise<Tokens> +register(data: RegisterInput): Promise<Tokens> refreshTokens(data: RefreshInput): Promise<Tokens> -refreshTokens(data: RefreshInput): Promise<Tokens> **UserService DriverRepository** -userRepository: UserRepository -driverRepository: DriverRepository -paymentService: PaymentService UserController -rideRepository: RideRepository RideRepository -userService: UserService +constructor(userRepository: UserRepository, +constructor(userService: UserService) driverRepository: DriverRepository, paymentService: +getUser(req: Request): Promise<User> PaymentService, rideRepository: RideRepository) **PaymentRepository** +getHistory(req: Request): Promise<Array<Ride>> +getUser(id: number): Promise<User> +getCurrentStatus(eq: Request): Promise<Ride | null> +createUser(data: RegisterInput): Promise<User> +getHistory(id: number): Promise<Array<Ride>> +getLatestRide(id: number): Promise<Ride | null> PaymentMethodRepository PaymentService -paymentRepository: PaymentRepository -paymentMethodRepository: PaymentMethodRepository PaymentMethodDetailsRepository -paymentMethodDetailsRepository: PaymentMethodDetailsRepository PaymentController -userRepository: UserRepository -paymentService: PaymentService -rideRepository: RideRepository +constructor(paymentService: PaymentService) +getPaymentMethods(): +constructor(paymentRepository: PaymentRepository, -stripeSecretKey: string Promise<Array<PaymentMethod>> paymentMethodRepository: PaymentMethodRepository, -usdRate: number +setDefaultMethod(req: Request, data: paymentMethodDetailsRepository: -stripe: StripeSDK SetAsDefaultOrRemoveInput): Promise<StatusWrapper> PaymentMethodDetailsRepository, userRepository: +createIntent(email: string, amount: number, +addCard(req: Request, data: AddCardInput): UserRepository, rideRepository: RideRepository, stripe: requestThreeDSecure: string, cusromerId: Promise<StatusWrapper> Optional<number>): Promise<CreateIntentOutput> +createPaymentIntent(req: Request, data: +getPaymentMethods(): CreatePaymentIntentInput): Promise<Array<PaymentMethod>> Promise<CreatePaymentIntentOutput> +setDefaultMethod(userId: number, methodId: number) +confirmPayment(req: Request, data: +addCard(req: Request, data: AddCardInput) ConfirmPaymentInput): Promise<StatusWrapper> +createPaymentIntent(userId: number, data: +removePaymentMethod(req: Request, data: CreatePaymentIntentInput): +client: Client SetAsDefaultOrRemoveInput): Promise<StatusWrapper> Promise<CreatePaymentIntentOutput> +confirmPayment(userId: number, data: ConfirmPaymentInput) +removePaymentMethod(userId: number, methodId: Directions -maps: GoogleMaps mockDirections: string +constructor(maps: GoogleMaps) MapsService +getDirection(from: Location, to: Location): -places: Places directions: Directions Geocoding MapsController +constructor(geocoding: Geocoding, places: Places, -maps: GoogleMaps -mapsService: MapsService -mockGeocoding: string directions: Directions) +constructor(mapsService: MapsService) +decode(data: Location): Promise<ExtendedLocation> -geoUtils: GeoUtils +decode(data: DecodeInput): Promise<DecodeOutput> +constructor(geoUtils: GeoUtils, maps: GoogleMaps) +getDirection(from: Location, to: Location): +direction(data: DirectionInput): Promise<DirectionOutput> decode(data: Location): Promise<ExtendedLocation> Promise<DirectionOutput> +places(data: PlacesInput): Promise<PlacesOutput> +searchPlaces(toSearch: string): Promise<Array<ExtendedLocation>> Places -maps: GoogleMaps -mockPlaces: string RTCService -constructor(maps: GoogleMaps) +search(toSearch: string): -idBasedSocketHolder: Map<number, Socket> -socketBasedIdHolder: WeakMap<Socket, number> Promise<Array<ExtendedLocation>> -clientDataHolder: Map<number, SocketUserInfo> -driverDataHolder: Map<number, DriverSocketUserInfo> -tokenProvider: TokenProvider RTCController -userService: UserService -rtcService: RTCService -geoUtils: GeoUtils -rideRepository: RideRepository +constructor(rtcService: RTCService) +constructor(tokenProvider: TokenProvider, userService: +handleConnection(socket: Socket) +handleDisconnect(socket: Socket) UserService, geoUtils: GeoUtils, rideRepository: RideRepository) +handleLocationUpdate(data: WithUserRole<Location>, socket: Socket) +getUserFromSocket(socket: Socket): Promise<User> +handleRideRequest(data: +addUser(socket: Socket) WithUserRole<ExtendedRideRequest>, socket: Socket) +removeUser(socket: Socket) +handleRideStopSearch(socket: Socket) +handleLocationUpdate(data: WithUserRole<Location>, +handleRideStatusChange(data: socket: Socket) WithUserRole<RideStatus>, socket: Socket) handleRideRequest(data: WithUserRole<ExtendedRideRequest>, socket: Socket) +handleRideStopSearch(socket: Socket) +handleRideStatusChange(data: VithUserRole<RideStatus>, socket: Socket)

ГУИР.400201.107 РР.1

| Изм Лист № докум. Подп. Дата Разраб. Филиппович Пров. Ковальчук Т. контр. Ковальчук Реценз. Подп. Ковальчук Реценз.

І. контр

Клинцевич

ЭВМ, ар. 850501