

# Package ‘RAINBOW’

November 8, 2019

**Type** Package

**Title** Genome-Wide Association Study with SNP-Set Methods

**Version** 0.1.13

**Maintainer** Kosuke Hamazaki <hamazaki@ut-biomet.org>

**Description** By using 'RAINBOW' (Reliable Association INference By Optimizing Weights), users can test multiple SNPs (Single Nucleotide Polymorphisms) simultaneously by kernel-based (SNP-set) methods. This package can also be applied to haplotype-based GWAS (Genome-Wide Association Study). Users can test not only additive effects but also dominance and epistatic effects. In detail, please check our preprint on bioRxiv: Kosuke Hamazaki and Hiroyoshi Iwata (2019) <doi:10.1101/612028>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.5.0)

**Imports** Rcpp, rrBLUP, rgl, tcltk, Matrix, cluster, MASS, pbmcapply, optimx, methods

**LinkingTo** Rcpp, RcppEigen

**RoxygenNote** 6.1.1

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**Author** Kosuke Hamazaki [aut, cre],  
Hiroyoshi Iwata [aut, ctb]

## R topics documented:

CalcThreshold . . . . .	2
cumsumPos . . . . .	3
design.Z . . . . .	4
EM3.cpp . . . . .	4
EM3.linker.cpp . . . . .	7
EMM.cpp . . . . .	10
EMM1.cpp . . . . .	14
EMM2.cpp . . . . .	16
genesetmap . . . . .	17
genetrait . . . . .	18

MAF.cut . . . . .	20
make.full . . . . .	20
manhattan . . . . .	21
manhattan.plus . . . . .	22
manhattan2 . . . . .	22
manhattan3 . . . . .	23
modify.data . . . . .	24
qq . . . . .	25
RAINBOW . . . . .	25
RGWAS.epistasis . . . . .	25
RGWAS.menu . . . . .	29
RGWAS.multisnp . . . . .	29
RGWAS.normal . . . . .	35
RGWAS.twostep . . . . .	39
RGWAS.twostep.epi . . . . .	44
Rice_genotype_map . . . . .	49
Rice_genotype_score . . . . .	50
Rice_phenotype . . . . .	50
Rice_Zhao_etal . . . . .	51
score.calc . . . . .	52
score.calc.epistasis.LR . . . . .	53
score.calc.epistasis.score . . . . .	55
score.calc.LR . . . . .	56
score.calc.LR.MC . . . . .	59
score.calc.MC . . . . .	61
score.calc.score . . . . .	62
score.calc.score.MC . . . . .	64
score.cpp . . . . .	66
score.linker.cpp . . . . .	67
See . . . . .	68
spectralG.cpp . . . . .	69
SS_gwas . . . . .	70
welcome_to_RGWAS . . . . .	71
<b>Index</b>	<b>72</b>

---

CalcThreshold

*Function to calculate threshold for GWAS*


---

## Description

Calculate thresholds for the given GWAS (genome-wide association studies) result by the Benjamini-Hochberg method or Bonferroni method.

## Usage

```
CalcThreshold(input, sig.level = 0.05, method = "BH")
```

**Arguments**

input	Data frame of GWAS results where the first column is the marker names, the second and third column is the chromosome and map position, and the fourth column is $-\log_{10}(p)$ for each marker.
sig.level	Significance level for the threshold. The default is 0.05. You can also assign vector of significance levels.
method	Two methods are offered: "BH" : Benjamini-Hochberg method. To control FDR, use this method. "Bonf" : Bonferroni method. To perform simple correction of multiple testing, use this method. You can also assign both of them by 'method = c("BH", "Bonf")'

**Value**

The value of the threshold. If there is no threshold, it returns NA.

**References**

- Benjamini, Y. and Hochberg, Y. (1995) Controlling the false discovery rate: a practical and powerful approach to multiple testing. *J R Stat Soc.* 57(1): 289-300.
- Storey, J.D. and Tibshirani, R. (2003) Statistical significance for genomewide studies. *Proc Natl Acad Sci.* 100(16): 9440-9445.

---

cumsumPos

---

*Function to calculate cumulative position (beyond chromosome)*


---

**Description**

Function to calculate cumulative position (beyond chromosome)

**Usage**

```
cumsumPos(map)
```

**Arguments**

map	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position.
-----	---

**Value**

Cumulative position (beyond chromosome) will be returned.

---

design.Z	<i>Function to generate design matrix (Z)</i>
----------	---

---

**Description**

Function to generate design matrix (Z)

**Usage**

```
design.Z(pheno.labels, geno.names)
```

**Arguments**

pheno.labels	A vector of genotype (line; accession; variety) names which correspond to phenotypic values.
geno.names	A vector of genotype (line; accession; variety) names for marker genotype data (duplication is not recommended).

**Value**

Z of  $y = X\beta + Zu + e$ . Design matrix, which is useful for GS or GWAS.

---

EM3.cpp	<i>Equation of mixed model for multi-kernel (slow, general version)</i>
---------	---

---

**Description**

This function solves the following multi-kernel linear mixed effects model.

$$y = X\beta + \sum_{l=1}^L Z_l u_l + \epsilon$$

$$\text{where } \text{Var}[y] = \sum_{l=1}^L Z_l K_l Z_l' \sigma_l^2 + I \sigma_e^2.$$

**Usage**

```
EM3.cpp(y, X0 = NULL, ZETA, eigen.G = NULL, eigen.SGS = NULL,
  tol = NULL, optimizer = "nlnmb", traceInside = 0, n.thres = 450,
  REML = TRUE, pred = TRUE)
```

**Arguments**

y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X0	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA	A list of variance matrices and its design matrices of random effects. You can use more than one kernel matrix. For example, ZETA = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D)) (A for additive, D for dominance) Please set names of lists "Z" and "K"!
eigen.G	A list with

	<b>\$values</b> Eigen values
	<b>\$vectors</b> Eigen vectors
	The result of the eigen decomposition of $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
eigen.SGS	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $SGS$ , where $S = I - X(X'X)^{-1}X'$ , $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
tol	The tolerance for detecting linear dependencies in the columns of $G = ZKZ'$ . Eigen vectors whose eigen values are less than "tol" argument will be omitted from results. If tol is NULL, top 'n' eigen values will be effective.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
traceInside	Perform trace for the optimization if traceInside $\geq 1$ , and this argument shows the frequency of reports.
n.thres	If $n \geq n.thres$ , perform EMM1.cpp. Else perform EMM2.cpp.
REML	You can choose which method you will use, "REML" or "ML". If REML = TRUE, you will perform "REML", and if REML = FALSE, you will perform "ML".
pred	If TRUE, the fitting values of y is returned.

## Value

<b>\$y.pred</b>	The fitting values of $y = X\beta + Zu$
<b>\$Vu</b>	Estimator for $\sigma_u^2$ , all of the genetic variance
<b>\$Ve</b>	Estimator for $\sigma_e^2$
<b>\$beta</b>	BLUE( $\beta$ )
<b>\$u</b>	BLUP( $u$ )
<b>\$weights</b>	The proportion of each genetic variance (corresponding to each kernel of ZETA) to Vu
<b>\$LL</b>	Maximized log-likelihood (full or restricted, depending on method)
<b>\$Vinv</b>	The inverse of $V = Vu \times ZKZ' + Ve \times I$
<b>\$Hinv</b>	The inverse of $H = ZKZ' + \lambda I$

## References

- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.
- Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet*. 44(7): 821-824.

**Examples**

```

#### Import RAINBOW
require(RAINBOW)

#### Load example datasets
data("Rice_Zhao_etal")
Rice_genotype_score <- Rice_Zhao_etal$genotypeScore
Rice_genotype_map <- Rice_Zhao_etal$genotypeMap
Rice_phenotype <- Rice_Zhao_etal$phenotype

#### View each dataset
See(Rice_genotype_score)
See(Rice_genotype_map)
See(Rice_phenotype)

#### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_phenotype[, trait.name, drop = FALSE])

#### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_genotype_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_genotype_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

#### Estimate additive genetic relationship matrix & epistatic relationship matrix
K.A <- rrBLUP::A.mat(x) #### rrBLUP package can be installed by install.packages("rrBLUP")
K.AA <- K.A * K.A #### additive x additive epistatic effects

#### Modify data
Z <- design.Z(phenotype.labels = rownames(y),
              genotype.names = rownames(K.A)) #### design matrix for random effects
phenotype.mat <- y[rownames(Z), , drop = FALSE]
ZETA <- list(A = list(Z = Z, K = K.A),
            AA = list(Z = Z, K = K.AA))

#### Solve multi-kernel linear mixed effects model (2 random effects)
EM3.res <- EM3.cpp(y = phenotype.mat, X = NULL, ZETA = ZETA)
(Vu <- EM3.res$Vu) #### estimated genetic variance
(Ve <- EM3.res$Ve) #### estimated residual variance
(weights <- EM3.res$weights) #### estimated proportion of two genetic variances
(herit <- Vu * weights / (Vu + Ve)) #### genomic heritability (additive, additive x additive)

(beta <- EM3.res$beta) #### Here, this is an intercept.
u <- EM3.res$u #### estimated genotypic values (additive, additive x additive)
See(u)

#### Perform genomic prediction with 10-fold cross validation (multi-kernel)

```

```

noNA <- !is.na(c(pheno.mat))    ### NA (missing) in the phenotype data

phenoNoNA <- pheno.mat[noNA, , drop = FALSE]    ### remove NA
ZETANoNA <- ZETA
ZETANoNA <- lapply(X = ZETANoNA, FUN = function (List) {
  List$Z <- List$Z[noNA, ]

  return(List)
})    ### remove NA

nFold <- 10    ### # of folds
nLine <- nrow(phenoNoNA)
idCV <- sample(1:nLine %% nFold)    ### assign random ids for cross-validation
idCV[idCV == 0] <- nFold

yPred <- rep(NA, nLine)

for (noCV in 1:nFold) {
  print(paste0("Fold: ", noCV))
  yTrain <- phenoNoNA
  yTrain[idCV == noCV, ] <- NA    ### prepare test data

  EM3.resCV <- EM3.cpp(y = yTrain, X = NULL, ZETA = ZETANoNA)    ### prediction
  yTest <- EM3.resCV$y.pred    ### predicted values

  yPred[idCV == noCV] <- yTest[idCV == noCV]
}

### Plot the results
plotRange <- range(phenoNoNA, yPred)
plot(x = phenoNoNA, y = yPred, xlim = plotRange, ylim = plotRange,
     xlab = "Observed values", ylab = "Predicted values",
     main = "Results of Genomic Prediction (multi-kernel)",
     cex.lab = 1.5, cex.main = 1.5, cex.axis = 1.3)
abline(a = 0, b = 1, col = 2, lwd = 2, lty = 2)
R2 <- cor(x = phenoNoNA[, 1], y = yPred) ^ 2
text(x = plotRange[2] - 10,
     y = plotRange[1] + 10,
     paste0("R2 = ", round(R2, 3)),
     cex = 1.5)

```

---

EM3.linker.cpp

---

*Equation of mixed model for multi-kernel (fast, for limited cases)*


---

## Description

This function solves multi-kernel mixed model using fastlmm.snpset approach (Lippert et al., 2014). This function can be used only when the kernels other than genomic relationship matrix are linear kernels.

## Usage

```
EM3.linker.cpp(y0, X0 = NULL, ZETA = NULL, Zs0 = NULL, Ws0,
  Gammas0 = lapply(Ws0, function(x) diag(ncol(x))), gammas.diag = TRUE,
  X.fix = TRUE, eigen.SGS = NULL, eigen.G = NULL, tol = NULL,
  bounds = c(1e-06, 1e+06), optimizer = "nllminb", traceInside = 0,
  n.thres = 450, spectral.method = NULL, REML = TRUE, pred = TRUE)
```

## Arguments

<code>y0</code>	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
<code>X0</code>	A $n \times p$ matrix. You should assign mean vector ( <code>rep(1, n)</code> ) and covariates. NA is not allowed.
<code>ZETA</code>	A list of variance (relationship) matrix ( $K$ ; $m \times m$ ) and its design matrix ( $Z$ ; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, <code>ZETA = list(A = list(Z = Z, K = K))</code> Please set names of list "Z" and "K"!
<code>Zs0</code>	A list of design matrices ( $Z$ ; $n \times m$ matrix) for $W$ s. For example, <code>Zs0 = list(A.part = Z.A.part, D.part = Z.D.part)</code>
<code>Ws0</code>	A list of low rank matrices ( $W$ ; $m \times k$ matrix). This forms linear kernel $K = WTW'$ . For example, <code>Ws0 = list(A.part = W.A, D.part = W.D)</code>
<code>Gammas0</code>	A list of matrices for weighting SNPs ( $\Gamma$ ; $k \times k$ matrix). This forms linear kernel $K = WTW'$ . For example, if there is no weighting, <code>Gammas0 = lapply(Ws0, function(x) diag(ncol(x)))</code>
<code>gammas.diag</code>	If each $\Gamma$ is the diagonal matrix, please set this argument TRUE. The calculation time can be saved.
<code>X.fix</code>	If you repeat this function and when <code>X0</code> is fixed during iterations, please set this argument TRUE.
<code>eigen.SGS</code>	<p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p> <p>The result of the eigen decomposition of <math>SGS</math>, where <math>S = I - X(X'X)^{-1}X'</math>, <math>G = ZKZ'</math>. You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.</p>
<code>eigen.G</code>	<p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p> <p>The result of the eigen decomposition of <math>G = ZKZ'</math>. You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.</p>
<code>tol</code>	The tolerance for detecting linear dependencies in the columns of $G = ZKZ'$ . Eigen vectors whose eigen values are less than "tol" argument will be omitted from results. If tol is NULL, top 'n' eigen values will be effective.
<code>bounds</code>	Lower and upper bounds for weights.
<code>optimizer</code>	The function used in the optimization process. We offer "optim", "optimx", and "nllminb" functions.



traceInside	Perform trace for the optimization if traceInside >= 1, and this argument shows the frequency of reports.
n.thres	If $n \geq n.thres$ , perform EMM1.cpp. Else perform EMM2.cpp.
spectral.method	The method of spectral decomposition. In this function, "eigen" : eigen decomposition and "cholesky" : cholesky and singular value decomposition are offered. If this argument is NULL, either method will be chosen according to the dimension of Z and X.
REML	You can choose which method you will use, "REML" or "ML". If REML = TRUE, you will perform "REML", and if REML = FALSE, you will perform "ML".
pred	If TRUE, the fitting values of y is returned.

### Value

**\$y.pred** The fitting values of y  $y = X\beta + Zu$

**\$Vu** Estimator for  $\sigma_u^2$ , all of the genetic variance

**\$Ve** Estimator for  $\sigma_e^2$

**\$beta** BLUE( $\beta$ )

**\$u** BLUP( $u$ )

**\$weights** The proportion of each genetic variance (corresponding to each kernel of ZETA) to Vu

**\$LL** Maximized log-likelihood (full or restricted, depending on method)

**\$Vinv** The inverse of  $V = Vu \times ZKZ' + Ve \times I$

**\$Hinv** The inverse of  $H = ZKZ' + \lambda I$

### References

Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.

Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet*. 44(7): 821-824.

Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

### Examples

```
### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_genoscore <- Rice_Zhao_etal$genoScore
Rice_genomap <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno

### View each dataset
```

```

See(Rice_genotype_score)
See(Rice_genotype_map)
See(Rice_pheno)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_pheno[, trait.name, drop = FALSE])

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_genotype_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_genotype_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate additive genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("rrBLUP")

### Modify data
Z <- design.Z(pheno.labels = rownames(y),
              geno.names = rownames(K.A)) ### design matrix for random effects
pheno.mat <- y[rownames(Z), , drop = FALSE]
ZETA <- list(A = list(Z = Z, K = K.A))

### Including the additional linear kernel for chromosome 12
chrNo <- 12
W.A <- x[, map$chr == chrNo] ### marker genotype data of chromosome 12

Zs0 <- list(A.part = Z)
Ws0 <- list(A.part = W.A) ### This will be regarded as linear kernel
### for the variance-covariance matrix of another random effects.

### Solve multi-kernel linear mixed effects model (2 random effects)
EM3.linker.res <- EM3.linker.cpp(y0 = pheno.mat, X0 = NULL, ZETA = ZETA,
                               Zs0 = Zs0, Ws0 = Ws0)
(Vu <- EM3.linker.res$Vu) ### estimated genetic variance
(Ve <- EM3.linker.res$Ve) ### estimated residual variance
(weights <- EM3.linker.res$weights) ### estimated proportion of two genetic variances
(herit <- Vu * weights / (Vu + Ve)) ### genomic heritability (all chromosomes, chromosome 12)

(beta <- EM3.linker.res$beta) ### Here, this is an intercept.
u <- EM3.linker.res$u ### estimated genotypic values (all chromosomes, chromosome 12)
See(u)

```

---

EMM.cpp

---

*Equation of mixed model for one kernel, a wrapper of two methods*


---

## Description

This function estimates maximum-likelihood (ML/REML; restricted maximum likelihood) solutions for the following mixed model.

$$y = X\beta + Zu + \epsilon$$

where  $\beta$  is a vector of fixed effects and  $u$  is a vector of random effects with  $Var[u] = K\sigma_u^2$ . The residual variance is  $Var[\epsilon] = I\sigma_e^2$ .

### Usage

```
EMM.cpp(y, X = NULL, ZETA, eigen.G = NULL, eigen.SGS = NULL,
  n.thres = 450, reestimation = FALSE, lam.len = 4,
  init.range = c(1e-06, 100), init.one = 0.5, conv.param = 1e-06,
  count.max = 20, bounds = c(1e-06, 1e+06), tol = NULL,
  optimizer = "nlminb", traceInside = 0, REML = TRUE,
  silent = TRUE, plot.l = FALSE, SE = FALSE, return.Hinv = TRUE)
```

### Arguments

y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA	A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
eigen.G	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
eigen.SGS	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $SGS$ , where $S = I - X(X'X)^{-1}X'$ , $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
n.thres	If $n \geq n.thres$ , perform EMM1.cpp. Else perform EMM2.cpp.
reestimation	If TRUE, EMM2.cpp is performed when the estimation by EMM1.cpp may not be accurate.
lam.len	The number of initial values you set. If this number is large, the estimation will be more accurate, but computational cost will be large. We recommend setting this value $3 \leq lam.len \leq 6$ .
init.range	The range of the initial parameters. For example, if lam.len = 5 and init.range = c(1e-06, 1e02), corresponding initial heritabilities will be calculated as seq(1e-06, 1 - 1e-02, length = 5), and then initial lambdas will be set.
init.one	The initial parameter if lam.len = 1.

conv.param	The convergence parameter. If the difference of log-likelihood by updating the parameter "lambda" is smaller than this conv.param, the iteration steps will be stopped.
count.max	Sometimes algorithms won't converge for some initial parameters. So if the iteration steps reach to this argument, you can stop the calculation even if algorithm doesn't converge.
bounds	Lower and Upper bounds of the parameter lambda. If the updated parameter goes out of this range, the parameter is reset to the value in this range.
tol	The tolerance for detecting linear dependencies in the columns of $G = ZKZ'$ . Eigen vectors whose eigen values are less than "tol" argument will be omitted from results. If tol is NULL, top 'n' eigen values will be effective.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
traceInside	Perform trace for the optimization if traceInside $\geq 1$ , and this argument shows the frequency of reports.
REML	You can choose which method you will use, "REML" or "ML". If REML = TRUE, you will perform "REML", and if REML = FALSE, you will perform "ML".
silent	If this argument is TRUE, warning messages will be shown when estimation is not accurate.
plot.l	If you want to plot log-likelihood, please set plot.l = TRUE. We don't recommend plot.l = TRUE when lam.len $\geq 2$ .
SE	If TRUE, standard errors are calculated.
return.Hinv	If TRUE, the function returns the inverse of $H = ZKZ' + \lambda I$ where $\lambda = \sigma_e^2 / \sigma_u^2$ . This is useful for GWAS.

### Value

<b>\$Vu</b>	Estimator for $\sigma_u^2$
<b>\$Ve</b>	Estimator for $\sigma_e^2$
<b>\$beta</b>	BLUE( $\beta$ )
<b>\$u</b>	BLUP( $u$ )
<b>\$LL</b>	Maximized log-likelihood (full or restricted, depending on method)
<b>\$beta.SE</b>	Standard error for $\beta$ (If SE = TRUE)
<b>\$u.SE</b>	Standard error for $u^* - u$ (If SE = TRUE)
<b>\$Hinv</b>	The inverse of $H = ZKZ' + \lambda I$ (If return.Hinv = TRUE)
<b>\$Hinv2</b>	The inverse of $H2 = ZKZ' / \lambda + I$ (If return.Hinv = TRUE)
<b>\$lambda</b>	Estimators for $\lambda = \sigma_e^2 / \sigma_u^2$ (If $n \geq n.thres$ )
<b>\$lambdas</b>	Lambdas for each initial values (If $n \geq n.thres$ )
<b>\$reest</b>	If parameter estimation may not be accurate, reest = 1, else reest = 0 (If $n \geq n.thres$ )
<b>\$counts</b>	The number of iterations until convergence for each initial values (If $n \geq n.thres$ )

### References

- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.
- Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet*. 44(7): 821-824.

**Examples**

```

### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_geno_score <- Rice_Zhao_etal$genoScore
Rice_geno_map <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno

### View each dataset
See(Rice_geno_score)
See(Rice_geno_map)
See(Rice_pheno)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_pheno[, trait.name, drop = FALSE])

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_geno_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_geno_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("rrBLUP")

### Modify data
modify.res <- modify.data(pheno.mat = y, geno.mat = x, return.ZETA = TRUE)
pheno.mat <- modify.res$pheno.modi
ZETA <- modify.res$ZETA

### Solve linear mixed effects model
EMM.res <- EMM.cpp(y = pheno.mat, X = NULL, ZETA = ZETA)
(Vu <- EMM.res$Vu)   ### estimated genetic variance
(Ve <- EMM.res$Ve)   ### estimated residual variance
(herit <- Vu / (Vu + Ve)) ### genomic heritability

(beta <- EMM.res$beta) ### Here, this is an intercept.
u <- EMM.res$u   ### estimated genotypic values
See(u)

### Perform genomic prediction with 10-fold cross validation

noNA <- !is.na(c(pheno.mat))   ### NA (missing) in the phenotype data

phenoNoNA <- pheno.mat[noNA, , drop = FALSE]   ### remove NA
ZETANoNA <- ZETA
ZETANoNA$A$Z <- ZETA$A$Z[noNA, ]   ### remove NA

nFold <- 10   ### # of folds
nLine <- nrow(phenoNoNA)

```

```

idCV <- sample(1:nLine % nFold)  ### assign random ids for cross-validation
idCV[idCV == 0] <- nFold

yPred <- rep(NA, nLine)

for (noCV in 1:nFold) {
  yTrain <- phenoNoNA
  yTrain[idCV == noCV, ] <- NA  ### prepare test data

  EMM.resCV <- EMM.cpp(y = yTrain, X = NULL, ZETA = ZETANoNA)  ### prediction
  yTest <- EMM.resCV$beta + EMM.resCV$u  ### predicted values

  yPred[idCV == noCV] <- (yTest[noNA])[idCV == noCV]
}

### Plot the results
plotRange <- range(phenoNoNA, yPred)
plot(x = phenoNoNA, y = yPred, xlim = plotRange, ylim = plotRange,
     xlab = "Observed values", ylab = "Predicted values",
     main = "Results of Genomic Prediction",
     cex.lab = 1.5, cex.main = 1.5, cex.axis = 1.3)
abline(a = 0, b = 1, col = 2, lwd = 2, lty = 2)
R2 <- cor(x = phenoNoNA[, 1], y = yPred) ^ 2
text(x = plotRange[2] - 10,
     y = plotRange[1] + 10,
     paste0("R2 = ", round(R2, 3)),
     cex = 1.5)

```

EMM1.cpp

*Equation of mixed model for one kernel, GEMMA-based method (implemented by Rcpp)*

## Description

This function solves the single-kernel linear mixed effects model by GEMMA (genome wide efficient mixed model association; Zhou et al., 2012) approach.

## Usage

```

EMM1.cpp(y, X = NULL, ZETA, eigen.G = NULL, lam.len = 4,
  init.range = c(1e-04, 100), init.one = 0.5, conv.param = 1e-06,
  count.max = 15, bounds = c(1e-06, 1e+06), tol = NULL,
  REML = TRUE, silent = TRUE, plot.l = FALSE, SE = FALSE,
  return.Hinv = TRUE)

```

## Arguments

y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA	A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!

eigen.G	<p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p> <p>The result of the eigen decomposition of <math>G = ZKZ'</math>. You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.</p>
lam.len	The number of initial values you set. If this number is large, the estimation will be more accurate, but computational cost will be large. We recommend setting this value $3 \leq \text{lam.len} \leq 6$ .
init.range	The range of the initial parameters. For example, if lam.len = 5 and init.range = c(1e-06, 1e02), corresponding initial heritabilities will be calculated as seq(1e-06, 1 - 1e-02, length = 5), and then initial lambdas will be set.
init.one	The initial parameter if lam.len = 1.
conv.param	The convergence parameter. If the difference of log-likelihood by updating the parameter "lambda" is smaller than this conv.param, the iteration steps will be stopped.
count.max	Sometimes algorithms won't converge for some initial parameters. So if the iteration steps reach to this argument, you can stop the calculation even if algorithm doesn't converge.
bounds	Lower and Upper bounds of the parameter $1 / \text{lambda}$ . If the updated parameter goes out of this range, the parameter is reset to the value in this range.
tol	The tolerance for detecting linear dependencies in the columns of $G = ZKZ'$ . Eigen vectors whose eigen values are less than "tol" argument will be omitted from results. If tol is NULL, top 'n' eigen values will be effective.
REML	You can choose which method you will use, "REML" or "ML". If REML = TRUE, you will perform "REML", and if REML = FALSE, you will perform "ML".
silent	If this argument is TRUE, warning messages will be shown when estimation is not accurate.
plot.l	If you want to plot log-likelihood, please set plot.l = TRUE. We don't recommend plot.l = TRUE when lam.len $\geq 2$ .
SE	If TRUE, standard errors are calculated.
return.Hinv	If TRUE, the function returns the inverse of $H = ZKZ' + \lambda I$ where $\lambda = \sigma_e^2 / \sigma_u^2$ . This is useful for GWAS.

## Value

<b>\$Vu</b>	Estimator for $\sigma_u^2$
<b>\$Ve</b>	Estimator for $\sigma_e^2$
<b>\$beta</b>	BLUE( $\beta$ )
<b>\$u</b>	BLUP( $u$ )
<b>\$LL</b>	Maximized log-likelihood (full or restricted, depending on method)
<b>\$beta.SE</b>	Standard error for $\beta$ (If SE = TRUE)
<b>\$u.SE</b>	Standard error for $u^* - u$ (If SE = TRUE)
<b>\$Hinv</b>	The inverse of $H = ZKZ' + \lambda I$ (If return.Hinv = TRUE)

**\$Hinv2** The inverse of  $H2 = ZKZ'/\lambda + I$  (If return.Hinv = TRUE)

**\$lambda** Estimators for  $\lambda = \sigma_e^2/\sigma_u^2$

**\$lambdas** Lambdas for each initial values

**\$reest** If parameter estimation may not be accurate, reest = 1, else reest = 0

**\$counts** The number of iterations until convergence for each initial values

## References

Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.

Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet*. 44(7): 821-824.

---

EMM2.cpp

*Equation of mixed model for one kernel, EMMA-based method (implemented by Rcpp)*

---

## Description

This function solves single-kernel linear mixed model by EMMA (efficient mixed model association; Kang et al., 2008) approach.

## Usage

```
EMM2.cpp(y, X = NULL, ZETA, eigen.G = NULL, eigen.SGS = NULL,
  tol = NULL, optimizer = "nlsminb", traceInside = 0, REML = TRUE,
  bounds = c(1e-09, 1e+09), SE = FALSE, return.Hinv = FALSE)
```

## Arguments

- |           |  |
|-----------|--|
| y         | A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.  |
| X         | A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.  |
| ZETA      | A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!   |
| eigen.G   | <p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p> <p>The result of the eigen decomposition of <math>G = ZKZ'</math>. You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.</p> |
| eigen.SGS | <p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p>   |



The result of the eigen decomposition of  $SGS$ , where  $S = I - X(X'X)^{-1}X'$ ,  $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.

tol	The tolerance for detecting linear dependencies in the columns of $G = ZKZ'$ . Eigen vectors whose eigen values are less than "tol" argument will be omitted from results. If tol is NULL, top 'n' eigen values will be effective.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
traceInside	Perform trace for the optimization if traceInside $\geq 1$ , and this argument shows the frequency of reports.
REML	You can choose which method you will use, "REML" or "ML". If REML = TRUE, you will perform "REML", and if REML = FALSE, you will perform "ML".
bounds	Lower and Upper bounds of the parameter lambda. If the updated parameter goes out of this range, the parameter is reset to the value in this range.
SE	If TRUE, standard errors are calculated.
return.Hinv	If TRUE, the function returns the inverse of $H = ZKZ' + \lambda I$ where $\lambda = \sigma_e^2 / \sigma_u^2$ . This is useful for GWAS.

#### Value

**\$Vu** Estimator for  $\sigma_u^2$

**\$Ve** Estimator for  $\sigma_e^2$

**\$beta** BLUE( $\beta$ )

**\$u** BLUP( $u$ )

**\$LL** Maximized log-likelihood (full or restricted, depending on method)

**\$beta.SE** Standard error for  $\beta$  (If SE = TRUE)

**\$u.SE** Standard error for  $u^* - u$  (If SE = TRUE)

**\$Hinv** The inverse of  $H = ZKZ' + \lambda I$  (If return.Hinv = TRUE)

#### References

Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.

---

genesetmap

*Function to generate map for gene set*

---

#### Description

Function to generate map for gene set

#### Usage

```
genesetmap(map, gene.set, cumulative = FALSE)
```

**Arguments**

map	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position.
gene.set	Gene information with the format of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "map" argument.
cumulative	If this argument is TRUE, cumulative position will be returned.

**Value**

Map for gene set.

---

genetrail	<i>Generate pseudo phenotypic values</i>
-----------	--

---

**Description**

This function generates pseudo phenotypic values according to the following formula.

$$y = X\beta + Zu + e$$

where effects of major genes are regarded as fixed effects  $\beta$  and polygenetic effects are regarded as random effects  $u$ . The variances of  $u$  and  $e$  are automatically determined by the heritability.

**Usage**

```
genetrail(x, sample.sets = NULL, candidate = NULL, pos = NULL,
  x.par = NULL, ZETA = NULL, x2 = NULL, num.qtn = 3,
  weight = c(2, 1, 1), qtn.effect = rep("A", num.qtn), prop = 1,
  polygene.weight = 1, polygene = TRUE, h2 = 0.6,
  h.correction = FALSE, seed = NULL, plot = TRUE, saveAt = NULL,
  subpop = NULL, return.all = FALSE, seed.env = TRUE)
```

**Arguments**

x	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
sample.sets	A n.sample x n.mark genotype matrix. Markers with fixed effects (QTNs) are chosen from sample.sets. If sample.sets = NULL, sample.sets = x.
candidate	If you want to fix QTN positions, please set the number where SNPs to be fixed are located in your data (so not position). If candidate = NULL, QTNs were randomly sampled from sample.sets or x.
pos	A n.mark x 1 vector. Cumulative position (over chromosomes) of each marker.
x.par	If you don't want to match the sampling population and the genotype data to QTN effects, then use this argument as the latter.

ZETA	<p>A list of covariance (relationship) matrix (<math>K: m \times m</math>) and its design matrix (<math>Z: n \times m</math>) of random effects. Please set names of list "Z" and "K"! You can use more than one kernel matrix. For example,</p> <p><code>ZETA = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D))</code></p> <p><b>Z.A, Z.D</b> Design matrix (<math>n \times m</math>) for the random effects. So, in many cases, you can use the identity matrix.</p> <p><b>K.A, K.D</b> Different kernels which express some relationships between lines. For example, K.A is additive relationship matrix for the covariance between lines, and K.D is dominance relationship matrix.</p>
x2	A genotype matrix to calculate additive relationship matrix when Z.ETA = NULL. If Z.ETA = NULL & x2 = NULL, A.mat(x) will be calculated as kernel matrix.
num.qtn	The number of QTNs
weight	The weights for each QTN by their standard deviations. Negative value is also allowed.
qtn.effect	Additive of dominance for each marker effect. This argument should be the same length as num.qtn.
prop	The proportion of effects of QTNs to polygenetic effects.
polygene.weight	If there are multiple kernels, this argument determines the weights of each kernel effect.
polygene	If polygene = FALSE, pseudo phenotypes with only QTN effects will be generated.
h2	The wide-sense heritability for generating phenotypes. $0 \leq h2 < 1$
h.correction	If TRUE, this function will generate phenotypes to match the genomic heritability and "h2".
seed	If seed is not NULL, some fixed phenotypic values will be generated according to set.seed(seed)
plot	If TRUE, boxplot for generated phenotypic values will be drawn.
saveAt	When drawing any plot, you can save plots in png format. In saveAt, you should substitute the name you want to save. When saveAt = NULL, the plot is not saved.
subpop	If there is subpopulation structure, you can draw boxplots divide by subpopulations. n.sample x n.subpop matrix. Please indicate the subpopulation information by (0, 1) for each element. (0 means that line doesn't belong to that subpopulation, and 1 means that line belongs to that subpopulation)
return.all	If FALSE, only returns generated phenotypic values. If TRUE, this function will return other information such as positions of candidate QTNs.
seed.env	If TRUE, this function will generate different environment effects every time.

## Value

**trait** Generated phenotypic values

**u** Generated genotype values

**e** Generated environmental effects

**candidate** The numbers where QTNs are located in your data (so not position).

**qtn.position** QTN positions

**heritability** Genomic heritability for generated phenotypic values.

---

MAF.cut	<i>Function to remove the minor alleles</i>
---------	---

---

**Description**

Function to remove the minor alleles

**Usage**

```
MAF.cut(x.0, map.0 = NULL, min.MAF = 0.05, max.MS = 0.05,
        return.MAF = FALSE)
```

**Arguments**

x.0	A $n \times m$ original marker genotype matrix.
map.0	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is removed from the original marker genotype data.
max.MS	Specifies the maximum missing rate (MS). If a marker has a MS more than max.MS, it is removed from the original marker genotype data.
return.MAF	If TRUE, MAF will be returned.

**Value**

**\$x** The modified marker genotype data whose SNPs with  $MAF \leq min.MAF$  were removed.  
**\$map** The modified map information whose SNPs with  $MAF \leq min.MAF$  were removed.  
**\$before** Minor allele frequencies of the original marker genotype.  
**\$after** Minor allele frequencies of the modified marker genotype.

---

make.full	<i>Change a matrix to full-rank matrix</i>
-----------	--

---

**Description**

Change a matrix to full-rank matrix

**Usage**

```
make.full(X)
```

**Arguments**

X	A $n \times p$ matrix which you want to change into full-rank matrix.
---	---

**Value**

A full-rank matrix

---

manhattan	<i>Draw manhattan plot</i>
-----------	----------------------------

---

## Description

Draw manhattan plot

## Usage

```
manhattan(input, sig.level = 0.05, method.thres = "BH", y.max = NULL,
  cex.lab = 1, lwd.thres = 1, plot.col1 = c("dark blue",
  "cornflowerblue"), cex.axis.x = 1, cex.axis.y = 1, plot.type = "p",
  plot.pch = 16)
```

## Arguments

input	Data frame of GWAS results where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for detemining threshold of significance. "BH" and "Bonferroni" are offered.
y.max	The maximum value for the vertical axis of manhattan plot. If NULL, automatically determined.
cex.lab	The font size of the labels.
lwd.thres	The line width for the threshold.
plot.col1	This argument determines the color of the manhattan plot. You should substitute this argument as color vector whose length is 2. plot.col1[1] for odd chromosomes and plot.col1[2] for even chromosomes.
cex.axis.x	The font size of the x axis.
cex.axis.y	The font size of the y axis.
plot.type	This argument determines the type of the manhattan plot. See the help page of "plot".
plot.pch	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".

## Value

Draw manhattan plot

---

manhattan.plus	<i>Add points of <math>-\log_{10}(p)</math> corrected by kernel methods to manhattan plot</i>
----------------	---

---

### Description

Add points of  $-\log_{10}(p)$  corrected by kernel methods to manhattan plot

### Usage

```
manhattan.plus(input, checks, plot.col1 = c("dark blue",
      "cornflowerblue"), plot.col3 = c("red3", "orange3"), plot.type = "p",
      plot.pch = 16)
```

### Arguments

input	Data frame of GWAS results where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
checks	The marker numbers whose $-\log_{10}(p)$ s are corrected by kernel methods.
plot.col1	This argument determines the color of the manhattan plot. You should substitute this argument as a color vector whose length is 2. plot.col1[1] for odd chromosomes and plot.col1[2] for even chromosomes.
plot.col3	Color of $-\log_{10}(p)$ corrected by kernel methods. plot.col3[1] for odd chromosomes and plot.col3[2] for even chromosomes
plot.type	This argument determines the type of the manhattan plot. See the help page of "plot".
plot.pch	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".

### Value

Draw manhattan plot

---

manhattan2	<i>Draw manhattan plot (another method)</i>
------------	---

---

### Description

Draw manhattan plot (another method)

### Usage

```
manhattan2(input, sig.level = 0.05, method.thres = "BH",
      plot.col2 = 1, plot.type = "p", plot.pch = 16, cum.pos = NULL,
      lwd.thres = 1, cex.lab = 1, cex.axis = 1)
```

**Arguments**

input	Data frame of GWAS results where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for determining threshold of significance. "BH" and "Bonferroni" are offered.
plot.col2	Color of the manhattan plot. color changes with chromosome and it starts from plot.col2 + 1 (so plot.col2 = 1 means color starts from red.)
plot.type	This argument determines the type of the manhattan plot. See the help page of "plot".
plot.pch	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".
cum.pos	Cumulative position (over chromosomes) of each marker
lwd.thres	The line width for the threshold.
cex.lab	The font size of the labels.
cex.axis	The font size of the axes.

**Value**

Draw manhattan plot

---

manhattan3	<i>Draw the effects of epistasis (3d plot and 2d plot)</i>
------------	--

---

**Description**

Draw the effects of epistasis (3d plot and 2d plot)

**Usage**

```
manhattan3(input, cum.pos, plot.epi.3d = TRUE, plot.epi.2d = TRUE,
  main.epi.3d = NULL, main.epi.2d = NULL, saveName = NULL)
```

**Arguments**

input	Data frame of GWAS results where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
cum.pos	Cumulative position (over chromosomes) of each marker
plot.epi.3d	If TRUE, draw 3d plot
plot.epi.2d	If TRUE, draw 2d plot
main.epi.3d	The title of 3d plot. If this argument is NULL, trait name is set as the title.
main.epi.2d	The title of 2d plot. If this argument is NULL, trait name is set as the title.
saveName	When drawing any plot, you can save plots in png format. In saveName, you should substitute the name you want to save. When saveAt = NULL, the plot is not saved.

**Value**

Draw 3d plot and 2d plot to show epistatic effects

---

modify.data	<i>Function to modify genotype and phenotype data to match</i>
-------------	--

---

**Description**

Function to modify genotype and phenotype data to match

**Usage**

```
modify.data(pheno.mat, geno.mat, pheno.labels = NULL,
            geno.names = NULL, map = NULL, return.ZETA = TRUE,
            return.GWAS.format = FALSE)
```

**Arguments**

pheno.mat	A $n_1 \times p$ matrix of phenotype data. rownames(pheno.mat) should be genotype (line; accession; variety) names.
geno.mat	A $n_2 \times m$ matrix of marker genotype data. rownames(geno.mat) should be genotype (line; accession; variety) names.
pheno.labels	A vector of genotype (line; accession; variety) names which correpond to phenotypic values.
geno.names	A vector of genotype (line; accession; variety) names for marker genotype data (duplication is not recommended).
map	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position.
return.ZETA	If this argument is TRUE, the list for mixed model equation (ZETA) will be returned.
return.GWAS.format	If this argument is TRUE, phenotype and genotype data for GWAS will be returned.

**Value**

**\$geno.modi** The modified marker genotype data.  
**\$pheno.modi** The modified phenotype data.  
**\$ZETA** The list for mixed model equation (ZETA).  
**\$pheno.GWAS** GWAS formatted phenotype data.  
**\$geno.GWAS** GWAS formatted marker genotype data.



---

qq	<i>Draw qq plot</i>
----	---------------------

---

**Description**

Draw qq plot

**Usage**

```
qq(scores)
```

**Arguments**

scores                      A vector of  $-\log_{10}(p)$  for each marker

**Value**

Draw qq plot

---

RAINBOW	<i>RAINBOW: Perform Genome-Wide Association Study (GWAS) By Kernel-Based Methods</i>
---------	--

---

### Description

By using 'RAINBOW' (Reliable Association Inference By Optimizing Weights), users can test multiple SNPs (Single Nucleotide Polymorphisms) simultaneously by kernel-based (SNP-set) methods. Users can test not only additive effects but also dominance and epistatic effects. In detail, please check our preprint on bioRxiv: Kosuke Hamazaki and Hiroyoshi Iwata (2019) <doi:10.1101/612028>.

---

RGWAS.epistasis	<i>Check epistatic effects by kernel-based GWAS (genome-wide association studies)</i>
-----------------	---

---

### Description

Check epistatic effects by kernel-based GWAS (genome-wide association studies)

### Usage

```
RGWAS.epistasis(pheno, geno, ZETA = NULL, covariate = NULL,
  covariate.factor = NULL, structure.matrix = NULL, n.PC = 0,
  min.MAF = 0.02, n.core = 1, test.method = "LR",
  dominance.eff = TRUE, haplotype = TRUE, num.hap = NULL,
  window.size.half = 5, window.slide = 1, chi0.mixture = 0.5,
  optimizer = "nlopt", gene.set = NULL, plot.epi.3d = TRUE,
  plot.epi.2d = TRUE, main.epi.3d = NULL, main.epi.2d = NULL,
  saveName = NULL, verbose = TRUE, verbose2 = FALSE, count = TRUE,
  time = TRUE)
```

**Arguments**

pheno	Data frame where the first column is the line name (gid). The remaining columns should be a phenotype to test.
geno	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position. Columns 4 and higher contain the marker scores for each line, coded as -1, 0, 1 = aa, Aa, AA.
ZETA	<p>A list of covariance (relationship) matrix (<math>K: m \times m</math>) and its design matrix (<math>Z: n \times m</math>) of random effects. Please set names of list "Z" and "K"! You can use more than one kernel matrix. For example,</p> <p><code>ZETA = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D))</code></p> <p><b>Z.A, Z.D</b> Design matrix (<math>n \times m</math>) for the random effects. So, in many cases, you can use the identity matrix.</p> <p><b>K.A, K.D</b> Different kernels which express some relationships between lines. For example, K.A is additive relationship matrix for the covariance between lines, and K.D is dominance relationship matrix.</p>
covariate	A $n \times 1$ vector or a $n \times p_1$ matrix. You can insert continuous values, such as other traits or genotype score for special markers. This argument is regarded as one of the fixed effects.
covariate.factor	A $n \times p_2$ dataframe. You should assign a factor vector for each column. Then RGWAS changes this argument into model matrix, and this model matrix will be included in the model as fixed effects.
structure.matrix	You can use structure matrix calculated by structure analysis when there are population structure. You should not use this argument with n.PC > 0.
n.PC	Number of principal components to include as fixed effects. Default is 0 (equals K model).
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
n.core	Setting n.core > 1 will enable parallel execution on a machine with multiple cores (use only at UNIX command line).
test.method	<p>RGWAS supports two methods to test effects of each SNP-set.</p> <p><b>"LR"</b> Likelihood-ratio test, relatively slow, but accurate (default).</p> <p><b>"score"</b> Score test, much faster than LR, but sometimes overestimate <math>-\log_{10}(p)</math>.</p>
dominance.eff	If this argument is TRUE, dominance effect is included in the model, and additive x dominance and dominance x dominance are also tested as epistatic effects. When you use inbred lines, please set this argument FALSE.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.

<code>window.size.half</code>	This argument decides how many SNPs (around the SNP you want to test) are used to calculate K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
<code>window.slide</code>	This argument determines how often you test markers. If <code>window.slide = 1</code> , every marker will be tested. If you want to perform SNP set by bins, please set <code>window.slide = 2 * window.size.half + 1</code> .
<code>chi0.mixture</code>	RAINBOW assumes the deviance is considered to follow $a \times \text{chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ , where $r$ is the degree of freedom. The argument <code>chi0.mixture</code> is a $(0 \leq a < 1)$ , and default is 0.5.
<code>optimizer</code>	The function used in the optimization process. We offer "optim", "optimx", and "nllminb" functions.
<code>gene.set</code>	If you have information of gene (or haplotype block), you can use it to perform kernel-based GWAS. You should assign your gene information to <code>gene.set</code> in the form of a "data.frame" (whose dimension is (the number of gene) $\times$ 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
<code>plot.epi.3d</code>	If TRUE, draw 3d plot
<code>plot.epi.2d</code>	If TRUE, draw 2d plot
<code>main.epi.3d</code>	The title of 3d plot. If this argument is NULL, trait name is set as the title.
<code>main.epi.2d</code>	The title of 2d plot. If this argument is NULL, trait name is set as the title.
<code>saveName</code>	When drawing any plot, you can save plots in png format. In <code>saveName</code> , you should substitute the name you want to save. When <code>saveName = NULL</code> , the plot is not saved.
<code>verbose</code>	If this argument is TRUE, messages for the current steps will be shown.
<code>verbose2</code>	If this argument is TRUE, welcome message will be shown.
<code>count</code>	When <code>count</code> is TRUE, you can know how far RGWAS has ended with percent display.
<code>time</code>	When <code>time</code> is TRUE, you can know how much time it took to perform RGWAS.

## Value

**\$map** Map information for SNPs which are tested epistatic effects.

**\$scores** **\$scores** This is the matrix which contains  $-\log_{10}(p)$  calculated by the test about epistasis effects.

**\$x, \$y** The information of the positions of SNPs detected by regular GWAS. These vectors are used when drawing plots. Each output corresponds to the replication of row and column of scores.

**\$z** This is a vector of **\$scores**. This vector is also used when drawing plots.

## References

- Storey, J.D. and Tibshirani, R. (2003) Statistical significance for genomewide studies. *Proc Natl Acad Sci.* 100(16): 9440-9445.
- Yu, J. et al. (2006) A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. *Nat Genet.* 38(2): 203-208.

Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.

Endelman, J.B. (2011) Ridge Regression and Other Kernels for Genomic Selection with R Package rrBLUP. *Plant Genome J.* 4(3): 250.

Endelman, J.B. and Jannink, J.L. (2012) Shrinkage Estimation of the Realized Relationship Matrix. *G3 Genes, Genomes, Genet.* 2(11): 1405-1413.

Su, G. et al. (2012) Estimating Additive and Non-Additive Genetic Variances and Predicting Genetic Merits Using Genome-Wide Dense Single Nucleotide Polymorphism Markers. *PLoS One*. 7(9): 1-7.

Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet.* 44(7): 821-824.

Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.

Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

Jiang, Y. and Reif, J.C. (2015) Modeling epistasis in genomic selection. *Genetics*. 201(2): 759-768.

## Examples

```
### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_geno_score <- Rice_Zhao_etal$genoScore
Rice_geno_map <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno

### View each dataset
See(Rice_geno_score)
See(Rice_geno_map)
See(Rice_pheno)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_pheno[, trait.name, drop = FALSE])

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_geno_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_geno_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("RAINBOW")

### Modify data
```

```

modify.data.res <- modify.data(pheno.mat = y, geno.mat = x, map = map,
                               return.ZETA = TRUE, return.GWAS.format = TRUE)
pheno.GWAS <- modify.data.res$pheno.GWAS
geno.GWAS <- modify.data.res$geno.GWAS
ZETA <- modify.data.res$ZETA

### View each data for RAINBOW
See(pheno.GWAS)
See(geno.GWAS)
str(ZETA)

### Check epistatic effects (by regarding 11 SNPs as one SNP-set)
epistasis.res <- RGWAS.epistasis(pheno = pheno.GWAS, geno = geno.GWAS, ZETA = ZETA,
                                n.PC = 4, test.method = "score", gene.set = NULL,
                                window.size.half = 5, window.slide = 11)

See(epistasis.res$scores$scores)

```

---

RGWAS.menu

---

*Print the R code which you should perform for RAINBOW GWAS*


---

### Description

Print the R code which you should perform for RAINBOW (Reliable Association INference By Optimizing Weights).

### Usage

```
RGWAS.menu()
```

### Value

The R code which you should perform for RAINBOW GWAS

---

RGWAS.multisnp

---

*Testing multiple SNPs simultaneously for GWAS*


---

### Description

This function performs SNP-set GWAS (genome-wide association studies), which tests multiple SNPs (single nucleotide polymorphisms) simultaneously. The model of SNP-set GWAS is

$$y = X\beta + Qv + Z_c u_c + Z_r u_r + \epsilon,$$

where  $y$  is the vector of phenotypic values,  $X\beta$  and  $Qv$  are the terms of fixed effects,  $Z_c u_c$  and  $Z_r u_r$  are the term of random effects and  $e$  is the vector of residuals.  $X\beta$  indicates all of the fixed effects other than population structure, and often this term also plays a role as an intercept.  $Qv$  is the term to correct the effect of population structure.  $Z_c u_c$  is the term of polygenetic effects, and suppose

that  $u_c$  follows the multivariate normal distribution whose variance-covariance matrix is the genetic covariance matrix.  $u_c \sim MVN(0, K_c \sigma_c^2)$ .  $Z_r u_r$  is the term of effects for SNP-set of interest, and suppose that  $u_r$  follows the multivariate normal distribution whose variance-covariance matrix is the Gram matrix (linear, exponential, or gaussian kernel) calculated from marker genotype which belong to that SNP-set. Therefore,  $u_r \sim MVN(0, K_r \sigma_r^2)$ . Finally, the residual term is assumed to identically and independently follow a normal distribution as shown in the following equation.  $e \sim MVN(0, I \sigma_e^2)$ .

## Usage

```
RGWAS.multisnp(pheno, geno, ZETA = NULL, covariate = NULL,
  covariate.factor = NULL, structure.matrix = NULL, n.PC = 0,
  min.MAF = 0.02, test.method = "LR", n.core = 1,
  kernel.method = "linear", kernel.h = "tuned", haplotype = TRUE,
  num.hap = NULL, test.effect = "additive", window.size.half = 5,
  window.slide = 1, chi0.mixture = 0.5, gene.set = NULL,
  weighting.center = TRUE, weighting.other = NULL, sig.level = 0.05,
  method.thres = "BH", plot.qq = TRUE, plot.Manhattan = TRUE,
  plot.method = 1, plot.col1 = c("dark blue", "cornflowerblue"),
  plot.col2 = 1, plot.type = "p", plot.pch = 16, saveName = NULL,
  main.qq = NULL, main.man = NULL, plot.add.last = FALSE,
  return.EMM.res = FALSE, optimizer = "nlsminb", thres = TRUE,
  verbose = TRUE, verbose2 = FALSE, count = TRUE, time = TRUE)
```

## Arguments

pheno	Data frame where the first column is the line name (gid). The remaining columns should be a phenotype to test.
geno	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position. Columns 4 and higher contain the marker scores for each line, coded as -1, 0, 1 = aa, Aa, AA.
ZETA	<p>A list of covariance (relationship) matrix (<math>K: m \times m</math>) and its design matrix (<math>Z: n \times m</math>) of random effects. Please set names of list "Z" and "K"! You can use more than one kernel matrix. For example,</p> <p><b>ZETA</b> = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D))</p> <p><b>Z.A, Z.D</b> Design matrix (<math>n \times m</math>) for the random effects. So, in many cases, you can use the identity matrix.</p> <p><b>K.A, K.D</b> Different kernels which express some relationships between lines.</p> <p>For example, K.A is additive relationship matrix for the covariance between lines, and K.D is dominance relationship matrix.</p>
covariate	A $n \times 1$ vector or a $n \times p_1$ matrix. You can insert continuous values, such as other traits or genotype score for special markers. This argument is regarded as one of the fixed effects.
covariate.factor	A $n \times p_2$ dataframe. You should assign a factor vector for each column. Then RGWAS changes this argument into model matrix, and this model matrix will be included in the model as fixed effects.
structure.matrix	You can use structure matrix calculated by structure analysis when there are population structure. You should not use this argument with $n.PC > 0$ .

n.PC	Number of principal components to include as fixed effects. Default is 0 (equals K model).
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
test.method	RGWAS supports two methods to test effects of each SNP-set. <b>"LR"</b> Likelihood-ratio test, relatively slow, but accurate (default). <b>"score"</b> Score test, much faster than LR, but sometimes overestimate $-\log_{10}(p)$ .
n.core	Setting n.core > 1 will enable parallel execution on a machine with multiple cores (use only at UNIX command line).
kernel.method	It determines how to calculate kernel. There are three methods. <b>"gaussian"</b> It is the default method. Gaussian kernel is calculated by distance matrix. <b>"exponential"</b> When this method is selected, exponential kernel is calculated by distance matrix. <b>"linear"</b> When this method is selected, linear kernel is calculated by A.mat. So local genomic relation matrix is regarded as kernel.
kernel.h	The hyper parameter for gaussian or exponential kernel. If kernel.h = "tuned", this hyper parameter is calculated as the median of off-diagonals of distance matrix of genotype data.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
test.effect	Effect of each marker to test. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". You also can choose more than one effect, for example, test.effect = c("additive", "aditive+dominance")
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculated K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .
chi0.mixture	RAINBOW assumes the deviance is considered to follow a $x \text{ chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ . where r is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
gene.set	If you have information of gene (or haplotype block), you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.

weighting.center	In kernel-based GWAS, weights according to the Gaussian distribution (centered on the tested SNP) are taken into account when calculating the kernel if Rainbow = TRUE. If weighting.center = FALSE, weights are not taken into account.
weighting.other	You can set other weights in addition to weighting.center. The length of this argument should be equal to the number of SNPs. For example, you can assign SNP effects from the information of gene annotation.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for determining threshold of significance. "BH" and "Bonferroni" are offered.
plot.qq	If TRUE, draw qq plot.
plot.Manhattan	If TRUE, draw manhattan plot.
plot.method	If this argument = 1, the default manhattan plot will be drawn. If this argument = 2, the manhattan plot with axis based on Position (bp) will be drawn. Also, this plot's color is changed by all chromosomes.
plot.col1	This argument determines the color of the manhattan plot. You should substitute this argument as color vector whose length is 2. plot.col1[1] for odd chromosomes and plot.col1[2] for even chromosomes
plot.col2	Color of the manhattan plot. color changes with chromosome and it starts from plot.col2 + 1 (so plot.col2 = 1 means color starts from red.)
plot.type	This argument determines the type of the manhattan plot. See the help page of "plot".
plot.pch	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".
saveName	When drawing any plot, you can save plots in png format. In saveName, you should substitute the name you want to save. When saveName = NULL, the plot is not saved.
main.qq	The title of qq plot. If this argument is NULL, trait name is set as the title.
main.man	The title of manhattan plot. If this argument is NULL, trait name is set as the title.
plot.add.last	If saveName is not NULL and this argument is TRUE, then you can add lines or dots to manhattan plots. However, you should also write "dev.off()" after adding something.
return.EMM.res	When return.EMM.res = TRUE, the results of equation of mixed models are included in the result of RGWAS.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
thres	If thres = TRUE, the threshold of the manhattan plot is included in the result of RGWAS. When return.EMM.res or thres is TRUE, the results will be "list" class.
verbose	If this argument is TRUE, messages for the current steps will be shown.
verbose2	If this argument is TRUE, welcome message will be shown.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.
time	When time is TRUE, you can know how much time it took to perform RGWAS.



## Details

P-value for each SNP-set is calculated by performing the LR test or the score test (Lippert et al., 2014).

In the LR test, first, the function solves the multi-kernel mixed model and calculates the maximum restricted log likelihood. Then it performs the LR test by using the fact that the deviance

$$D = 2 \times (LL_{alt} - LL_{null})$$

follows the chi-square distribution.

In the score test, the maximization of the likelihood is only performed for the null model. In other words, the function calculates the score statistic without solving the multi-kernel mixed model for each SNP-set. Then it performs the score test by using the fact that the score statistic follows the chi-square distribution.

## Value

**\$D** Dataframe which contains the information of the map you input and the results of RGWAS (-log10(p)) which correspond to the map. If there are more than one test.effects, then multiple lists for each test.effect are returned respectively.

**\$thres** A vector which contains the information of threshold determined by FDR = 0.05.

**\$EMM.res** This output is a list which contains the information about the results of "EMM" performed at first in regular GWAS. If you want to know details, see the description for the function "EMM1" or "EMM2".

## References

- Storey, J.D. and Tibshirani, R. (2003) Statistical significance for genomewide studies. *Proc Natl Acad Sci.* 100(16): 9440-9445.
- Yu, J. et al. (2006) A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. *Nat Genet.* 38(2): 203-208.
- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics.* 178(3): 1709-1723.
- Endelman, J.B. (2011) Ridge Regression and Other Kernels for Genomic Selection with R Package rrBLUP. *Plant Genome J.* 4(3): 250.
- Endelman, J.B. and Jannink, J.L. (2012) Shrinkage Estimation of the Realized Relationship Matrix. *G3 Genes, Genomes, Genet.* 2(11): 1405-1413.
- Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet.* 44(7): 821-824.
- Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics.* 29(12): 1526-1533.
- Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics.* 30(22): 3206-3214.

## Examples

```

### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_geno_score <- Rice_Zhao_etal$genoScore
Rice_geno_map <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno

### View each dataset
See(Rice_geno_score)
See(Rice_geno_map)
See(Rice_pheno)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_pheno[, trait.name, drop = FALSE])

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_geno_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_geno_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("rrBLUP")

### Modify data
modify.data.res <- modify.data(pheno.mat = y, geno.mat = x, map = map,
                              return.ZETA = TRUE, return.GWAS.format = TRUE)
pheno.GWAS <- modify.data.res$pheno.GWAS
geno.GWAS <- modify.data.res$geno.GWAS
ZETA <- modify.data.res$ZETA

### View each data for RAINBOW
See(pheno.GWAS)
See(geno.GWAS)
str(ZETA)

### Perform SNP-set GWAS (by regarding 21 SNPs as one SNP-set)
SNP_set.res <- RGWAS.multisnp(pheno = pheno.GWAS, geno = geno.GWAS,
                             ZETA = ZETA, n.PC = 4, test.method = "LR",
                             kernel.method = "linear", gene.set = NULL,
                             test.effect = "additive", window.size.half = 10,
                             window.slide = 21)
See(SNP_set.res$D) ### Column 4 contains -log10(p) values for markers

### Perform SNP-set GWAS 2 (by regarding 11 SNPs as one SNP-set with sliding window)
### It will take almost 25 minutes...
SNP_set.res2 <- RGWAS.multisnp(pheno = pheno.GWAS, geno = geno.GWAS,
                              ZETA = ZETA, n.PC = 4, test.method = "LR",
                              kernel.method = "linear", gene.set = NULL,
                              test.effect = "additive", window.size.half = 5,

```

```

                                window.slide = 1)
See(SNP_set.res2$D)  ### Column 4 contains -log10(p) values for markers

```

RGWAS.normal

*Perform normal GWAS (test each single SNP)***Description**

This function performs single-SNP GWAS (genome-wide association studies). The model of GWAS is

$$y = X\beta + S_i\alpha_i + Qv + Zu + \epsilon,$$

where  $y$  is the vector of phenotypic values,  $X\beta$ ,  $S_i\alpha_i$ ,  $Qv$  are the terms of fixed effects,  $Zu$  is the term of random effects and  $e$  is the vector of residuals.  $X\beta$  indicates all of the fixed effects other than the effect of SNPs to be tested and of population structure, and often this term also plays a role as an intercept. For  $S_i\alpha_i$ ,  $S_i$  is the  $i$ th marker of genotype data and  $\alpha_i$  is the effect of that marker.  $Qv$  is the term to correct the effect of population structure.  $Zu$  is the term of polygenetic effects, and suppose that  $u$  follows the multivariate normal distribution whose variance-covariance matrix is the genetic covariance matrix.  $u \sim MVN(0, K\sigma_u^2)$ . Finally, the residual term is assumed to identically and independently follow a normal distribution as shown in the following equation.  $e \sim MVN(0, I\sigma_e^2)$ .

**Usage**

```

RGWAS.normal(pheno, geno, ZETA = NULL, covariate = NULL,
  covariate.factor = NULL, structure.matrix = NULL, n.PC = 0,
  min.MAF = 0.02, P3D = TRUE, n.core = 1, sig.level = 0.05,
  method.thres = "BH", plot.qq = TRUE, plot.Manhattan = TRUE,
  plot.method = 1, plot.col1 = c("dark blue", "cornflowerblue"),
  plot.col2 = 1, plot.type = "p", plot.pch = 16, saveName = NULL,
  main.qq = NULL, main.man = NULL, plot.add.last = FALSE,
  return.EMM.res = FALSE, optimizer = "nllminb", thres = TRUE,
  verbose = TRUE, verbose2 = FALSE, count = TRUE, time = TRUE)

```

**Arguments**

- |       |  |
|-------|--|
| pheno | Data frame where the first column is the line name (gid). The remaining columns should be a phenotype to test.   |
| geno  | Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position. Columns 4 and higher contain the marker scores for each line, coded as -1, 0, 1 = aa, Aa, AA.  |
| ZETA  | <p>A list of covariance (relationship) matrix (<math>K</math>: <math>m \times m</math>) and its design matrix (<math>Z</math>: <math>n \times m</math>) of random effects. Please set names of list "Z" and "K"! You can use more than one kernel matrix. For example,</p> <p><code>ZETA = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D))</code></p> <p><b>Z.A, Z.D</b> Design matrix (<math>n \times m</math>) for the random effects. So, in many cases, you can use the identity matrix.</p> <p><b>K.A, K.D</b> Different kernels which express some relationships between lines.</p> |

	For example, K.A is additive relationship matrix for the covariance between lines, and K.D is dominance relationship matrix.
covariate	A $n \times 1$ vector or a $n \times p_1$ matrix. You can insert continuous values, such as other traits or genotype score for special markers. This argument is regarded as one of the fixed effects.
covariate.factor	A $n \times p_2$ dataframe. You should assign a factor vector for each column. Then RGWAS changes this argument into model matrix, and this model matrix will be included in the model as fixed effects.
structure.matrix	You can use structure matrix calculated by structure analysis when there are population structure. You should not use this argument with n.PC > 0.
n.PC	Number of principal components to include as fixed effects. Default is 0 (equals K model).
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
P3D	When P3D = TRUE, variance components are estimated by REML only once, without any markers in the model. When P3D = FALSE, variance components are estimated by REML for each marker separately.
n.core	Setting n.core > 1 will enable parallel execution on a machine with multiple cores.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for detemining threshold of significance. "BH" and "Bonferroni" are offered.
plot.qq	If TRUE, draw qq plot.
plot.Manhattan	If TRUE, draw manhattan plot.
plot.method	If this argument = 1, the default manhattan plot will be drawn. If this argument = 2, the manhattan plot with axis based on Position (bp) will be drawn. Also, this plot's color is changed by all chromosomes.
plot.col1	This argument determines the color of the manhattan plot. You should substitute this argument as color vector whose length is 2. plot.col1[1] for odd chromosomes and plot.col1[2] for even chromosomes
plot.col2	Color of the manhattan plot. color changes with chromosome and it starts from plot.col2 + 1 (so plot.col2 = 1 means color starts from red.)
plot.type	This argument determines the type of the manhattan plot. See the help page of "plot".
plot.pch	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".
saveName	When drawing any plot, you can save plots in png format. In saveName, you should substitute the name you want to save. When saveName = NULL, the plot is not saved.
main.qq	The title of qq plot. If this argument is NULL, trait name is set as the title.
main.man	The title of manhattan plot. If this argument is NULL, trait name is set as the title.
plot.add.last	If saveName is not NULL and this argument is TRUE, then you can add lines or dots to manhattan plots. However, you should also write "dev.off()" after adding something.

return.EMM.res	When return.EMM.res = TRUE, the results of equation of mixed models are included in the result of RGWAS.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlnmb" functions.
thres	If thres = TRUE, the threshold of the manhattan plot is included in the result of RGWAS. When return.EMM.res or thres is TRUE, the results will be "list" class.
verbose	If this argument is TRUE, messages for the current steps will be shown.
verbose2	If this argument is TRUE, welcome message will be shown.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.
time	When time is TRUE, you can know how much time it took to perform RGWAS.

### Details

P-value for each marker is calculated by performing F-test against the F-value as follows (Kennedy et al., 1992).

$$F = \frac{(L'\hat{b})'[L'(X'H^{-1}X)^{-1}L]^{-1}(L'\hat{b})}{f\hat{\sigma}_u^2},$$

where  $b$  is the vector of coefficients of the fixed effects, which combines  $\beta$ ,  $\alpha_i$ ,  $v$  in the horizontal direction and  $L$  is a matrix to indicate which effects in  $b$  are tested.  $H$  is calculated by dividing the estimated variance-covariance matrix for the phenotypic values by  $\sigma_u^2$ , and is calculated by  $H = ZKZ' + \hat{\lambda}I$ .  $\hat{\lambda}$  is the maximum likelihood estimator of the ratio between the residual variance and the additive genetic variance.  $\hat{b}$  is the maximum likelihood estimator of  $b$  and is calculated by  $\hat{b} = (X'H^{-1}X)^{-1}X'H^{-1}y$ .  $f$  is the number of the fixed effects to be tested, and  $\hat{\sigma}_u^2$  is estimated by the following formula.

$$\hat{\sigma}_u^2 = \frac{(y - X\hat{b})'H^{-1}(y - X\hat{b})}{n - p},$$

where  $n$  is the sample size and  $p$  is the number of the all fixed effects. We calculated each p-value using the fact that the above F-value follows the F distribution with the degree of freedom  $(f, n - p)$ .

### Value

**\$D** Dataframe which contains the information of the map you input and the results of RGWAS (-log10(p)) which correspond to the map.

**\$thres** A vector which contains the information of threshold determined by FDR = 0.05.

**\$EMM.res** This output is a list which contains the information about the results of "EMM" performed at first in regular GWAS. If you want to know details, see the description for the function "EMM1" or "EMM2".

### References

- Kennedy, B.W., Quinton, M. and van Arendonk, J.A. (1992) Estimation of effects of single genes on quantitative traits. *J Anim Sci.* 70(7): 2000-2012.
- Storey, J.D. and Tibshirani, R. (2003) Statistical significance for genomewide studies. *Proc Natl Acad Sci.* 100(16): 9440-9445.
- Yu, J. et al. (2006) A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. *Nat Genet.* 38(2): 203-208.

Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics*. 178(3): 1709-1723.

Kang, H.M. et al. (2010) Variance component model to account for sample structure in genome-wide association studies. *Nat Genet*. 42(4): 348-354.

Zhang, Z. et al. (2010) Mixed linear model approach adapted for genome-wide association studies. *Nat Genet*. 42(4): 355-360.

Endelman, J.B. (2011) Ridge Regression and Other Kernels for Genomic Selection with R Package rrBLUP. *Plant Genome J*. 4(3): 250.

Endelman, J.B. and Jannink, J.L. (2012) Shrinkage Estimation of the Realized Relationship Matrix. *G3 Genes, Genomes, Genet*. 2(11): 1405-1413.

Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet*. 44(7): 821-824.

## Examples

```
### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_geno_score <- Rice_Zhao_etal$genoScore
Rice_geno_map <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno

### View each dataset
See(Rice_geno_score)
See(Rice_geno_map)
See(Rice_pheno)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_pheno[, trait.name, drop = FALSE])

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_geno_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_geno_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("rrBLUP")

### Modify data
modify.data.res <- modify.data(pheno.mat = y, geno.mat = x, map = map,
                              return.ZETA = TRUE, return.GWAS.format = TRUE)
pheno.GWAS <- modify.data.res$pheno.GWAS
geno.GWAS <- modify.data.res$geno.GWAS
ZETA <- modify.data.res$ZETA

### View each data for RAINBOW
See(pheno.GWAS)
```

```
See(geno.GWAS)
str(ZETA)
```

```
### Perform single-SNP GWAS
normal.res <- RGWAS.normal(pheno = pheno.GWAS, geno = geno.GWAS,
                          ZETA = ZETA, n.PC = 4, P3D = TRUE)
See(normal.res$D) ### Column 4 contains -log10(p) values for markers
```

---

RGWAS.twostep	<i>Perform normal GWAS (genome-wide association studies) first, then perform SNP-set GWAS for relatively significant markers</i>
---------------	--

---

## Description

Perform normal GWAS (genome-wide association studies) first, then perform SNP-set GWAS for relatively significant markers

## Usage

```
RGWAS.twostep(pheno, geno, ZETA = NULL, covariate = NULL,
               covariate.factor = NULL, structure.matrix = NULL, n.PC = 0,
               min.MAF = 0.02, n.core = 1, check.size = 40, check.gene.size = 4,
               kernel.percent = 0.1, GWAS.res.first = NULL, P3D = TRUE,
               test.method.1 = "normal", test.method.2 = "LR",
               kernel.method = "linear", kernel.h = "tuned", haplotype = TRUE,
               num.hap = NULL, test.effect.1 = "additive",
               test.effect.2 = "additive", window.size.half = 5, window.slide = 1,
               chi0.mixture = 0.5, optimizer = "nlminb", gene.set = NULL,
               weighting.center = TRUE, weighting.other = NULL, sig.level = 0.05,
               method.thres = "BH", plot.qq.1 = TRUE, plot.Manhattan.1 = TRUE,
               plot.qq.2 = TRUE, plot.Manhattan.2 = TRUE, plot.method = 1,
               plot.col1 = c("dark blue", "cornflowerblue"), plot.col2 = 1,
               plot.col3 = c("red3", "orange3"), plot.type = "p", plot.pch = 16,
               saveName = NULL, main.qq.1 = NULL, main.man.1 = NULL,
               main.qq.2 = NULL, main.man.2 = NULL, plot.add.last = FALSE,
               return.EMM.res = FALSE, thres = TRUE, verbose = TRUE,
               verbose2 = FALSE, count = TRUE, time = TRUE)
```

## Arguments

pheno	Data frame where the first column is the line name (gid). The remaining columns should be a phenotype to test.
geno	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position. Columns 4 and higher contain the marker scores for each line, coded as -1, 0, 1 = aa, Aa, AA.
ZETA	A list of covariance (relationship) matrix ( $K$ : $m \times m$ ) and its design matrix ( $Z$ : $n \times m$ ) of random effects. Please set names of list "Z" and "K"! You can use more than one kernel matrix. For example, $ZETA = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D))$

	<b>Z.A, Z.D</b> Design matrix ( $n \times m$ ) for the random effects. So, in many cases, you can use the identity matrix.
	<b>K.A, K.D</b> Different kernels which express some relationships between lines. For example, K.A is additive relationship matrix for the covariance between lines, and K.D is dominance relationship matrix.
covariate	A $n \times 1$ vector or a $n \times p_1$ matrix. You can insert continuous values, such as other traits or genotype score for special markers. This argument is regarded as one of the fixed effects.
covariate.factor	A $n \times p_2$ dataframe. You should assign a factor vector for each column. Then RGWAS changes this argument into model matrix, and this model matrix will be included in the model as fixed effects.
structure.matrix	You can use structure matrix calculated by structure analysis when there are population structure. You should not use this argument with $n.PC > 0$ .
n.PC	Number of principal components to include as fixed effects. Default is 0 (equals K model).
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
n.core	Setting $n.core > 1$ will enable parallel execution on a machine with multiple cores (use only at UNIX command line).
check.size	This argument determines how many SNPs (around the SNP detected by normal GWAS) you will recalculate $-\log_{10}(p)$ .
check.gene.size	This argument determines how many genes (around the genes detected by normal GWAS) you will recalculate $-\log_{10}(p)$ . This argument is valid only when you assign "gene.set" argument.
kernel.percent	This argument determines how many SNPs are detected by normal GWAS. For example, when $kernel.percent = 0.1$ , SNPs whose value of $-\log_{10}(p)$ is in the top 0.1 percent are chosen as candidate for recalculation by SNP-set GWAS.
GWAS.res.first	If you have already performed normal GWAS and have the result, you can skip performing normal GWAS.
P3D	When $P3D = TRUE$ , variance components are estimated by REML only once, without any markers in the model. When $P3D = FALSE$ , variance components are estimated by REML for each marker separately.
test.method.1	RGWAS supports two methods to test effects of each SNP-set for 1st GWAS. <b>"normal"</b> Normal GWAS (default). <b>"score"</b> Score test, much faster than LR, but sometimes overestimate $-\log_{10}(p)$ .
test.method.2	RGWAS supports two methods to test effects of each SNP-set for 2nd GWAS. <b>"LR"</b> Likelihood-ratio test, relatively slow, but accurate (default). <b>"score"</b> Score test, much faster than LR, but sometimes overestimate $-\log_{10}(p)$ .
kernel.method	It determines how to calculate kernel. There are three methods. <b>"gaussian"</b> It is the default method. Gaussian kernel is calculated by distance matrix. <b>"exponential"</b> When this method is selected, exponential kernel is calculated by distance matrix. <b>"linear"</b> When this method is selected, linear kernel is calculated by A.mat.



	So local genomic relation matrix is regarded as kernel.
kernel.h	The hyper parameter for gaussian or exponential kernel. If kernel.h = "tuned", this hyper parameter is calculated as the median of off-diagonals of distance matrix of genotype data.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
test.effect.1	Effect of each marker to test for 1st GWAS. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". you can assign only one test effect for the 1st GWAS!
test.effect.2	Effect of each marker to test for 2nd GWAS. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". You also can choose more than one effect, for example, test.effect = c("additive", "aditive+dominance")
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculated K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .
chi0.mixture	RAINBOW assumes the deviance is considered to follow $a \times \text{chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ . where r is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlnmb" functions.
gene.set	If you have information of gene (or haplotype block), you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
weighting.center	In kernel-based GWAS, weights according to the Gaussian distribution (centered on the tested SNP) are taken into account when calculating the kernel if Rainbow = TRUE. If weighting.center = FALSE, weights are not taken into account.
weighting.other	You can set other weights in addition to weighting.center. The length of this argument should be equal to the number of SNPs. For example, you can assign SNP effects from the information of gene annotation.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for detemining threshold of significance. "BH" and "Bonferroni" are offered.

<code>plot.qq.1</code>	If TRUE, draw qq plot for normal GWAS.
<code>plot.Manhattan.1</code>	If TRUE, draw manhattan plot for normal GWAS.
<code>plot.qq.2</code>	If TRUE, draw qq plot for SNP-set GWAS.
<code>plot.Manhattan.2</code>	If TRUE, draw manhattan plot for SNP-set GWAS.
<code>plot.method</code>	If this argument = 1, the default manhattan plot will be drawn. If this argument = 2, the manhattan plot with axis based on Position (bp) will be drawn. Also, this plot's color is changed by all chromosomes.
<code>plot.col1</code>	This argument determines the color of the manhattan plot. You should substitute this argument as color vector whose length is 2. <code>plot.col1[1]</code> for odd chromosomes and <code>plot.col1[2]</code> for even chromosomes
<code>plot.col2</code>	Color of the manhattan plot. color changes with chromosome and it starts from <code>plot.col2 + 1</code> (so <code>plot.col2 = 1</code> means color starts from red.)
<code>plot.col3</code>	Color of the points of manhattan plot which are added after the reestimation by SNP-set method. You should substitute this argument as color vector whose length is 2. <code>plot.col3[1]</code> for odd chromosomes and <code>plot.col3[2]</code> for even chromosomes.
<code>plot.type</code>	This argument determines the type of the manhattan plot. See the help page of "plot".
<code>plot.pch</code>	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".
<code>saveName</code>	When drawing any plot, you can save plots in png format. In <code>saveName</code> , you should substitute the name you want to save. When <code>saveName = NULL</code> , the plot is not saved.
<code>main.qq.1</code>	The title of qq plot for normal GWAS. If this argument is NULL, trait name is set as the title.
<code>main.man.1</code>	The title of manhattan plot for normal GWAS. If this argument is NULL, trait name is set as the title.
<code>main.qq.2</code>	The title of qq plot for SNP-set GWAS. If this argument is NULL, trait name is set as the title.
<code>main.man.2</code>	The title of manhattan plot for SNP-set GWAS. If this argument is NULL, trait name is set as the title.
<code>plot.add.last</code>	If <code>saveName</code> is not NULL and this argument is TRUE, then you can add lines or dots to manhattan plots. However, you should also write <code>"dev.off()"</code> after adding something.
<code>return.EMM.res</code>	When <code>return.EMM.res = TRUE</code> , the results of equation of mixed models are included in the result of RGWAS.
<code>thres</code>	If <code>thres = TRUE</code> , the threshold of the manhattan plot is included in the result of RGWAS. When <code>return.EMM.res</code> or <code>thres</code> is TRUE, the results will be "list" class.
<code>verbose</code>	If this argument is TRUE, messages for the current steps will be shown.
<code>verbose2</code>	If this argument is TRUE, welcome message will be shown.
<code>count</code>	When <code>count</code> is TRUE, you can know how far RGWAS has ended with percent display.
<code>time</code>	When <code>time</code> is TRUE, you can know how much time it took to perform RGWAS.

**Value**

**\$D** Dataframe which contains the information of the map you input and the results of RGWAS ( $-\log_{10}(p)$ ) which correspond to the map.  $-\log_{10}(p)$  by normal GWAS and recalculated  $-\log_{10}(p)$  by SNP-set GWAS will be obtained. If there are more than one test.effects, then multiple lists for each test.effect are returned respectively.

**\$thres** A vector which contains the information of threshold determined by  $FDR = 0.05$ .

**\$EMM.res** This output is a list which contains the information about the results of "EMM" performed at first in normal GWAS. If you want to know details, see the description for the function "EMM1" or "EMM2".

**References**

- Kennedy, B.W., Quinton, M. and van Arendonk, J.A. (1992) Estimation of effects of single genes on quantitative traits. *J Anim Sci.* 70(7): 2000-2012.
- Storey, J.D. and Tibshirani, R. (2003) Statistical significance for genomewide studies. *Proc Natl Acad Sci.* 100(16): 9440-9445.
- Yu, J. et al. (2006) A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. *Nat Genet.* 38(2): 203-208.
- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics.* 178(3): 1709-1723.
- Kang, H.M. et al. (2010) Variance component model to account for sample structure in genome-wide association studies. *Nat Genet.* 42(4): 348-354.
- Zhang, Z. et al. (2010) Mixed linear model approach adapted for genome-wide association studies. *Nat Genet.* 42(4): 355-360.
- Endelman, J.B. (2011) Ridge Regression and Other Kernels for Genomic Selection with R Package rrBLUP. *Plant Genome J.* 4(3): 250.
- Endelman, J.B. and Jannink, J.L. (2012) Shrinkage Estimation of the Realized Relationship Matrix. *G3 Genes, Genomes, Genet.* 2(11): 1405-1413.
- Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet.* 44(7): 821-824.
- Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics.* 29(12): 1526-1533.
- Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics.* 30(22): 3206-3214.

**Examples**

```
### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_geno_score <- Rice_Zhao_etal$genoScore
Rice_geno_map <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno
```

```

### View each dataset
See(Rice_genotype_score)
See(Rice_genotype_map)
See(Rice_phenotype)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
y <- as.matrix(Rice_phenotype[, trait.name, drop = FALSE])

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_genotype_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_genotype_map)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("rrBLUP")

### Modify data
modify.data.res <- modify.data(phenotype.mat = y, genotype.mat = x, map = map,
                              return.ZETA = TRUE, return.GWAS.format = TRUE)
phenotype.GWAS <- modify.data.res$phenotype.GWAS
genotype.GWAS <- modify.data.res$genotype.GWAS
ZETA <- modify.data.res$ZETA

### View each data for RAINBOW
See(phenotype.GWAS)
See(genotype.GWAS)
str(ZETA)

### Perform two step SNP-set GWAS (single-snp GWAS -> SNP-set GWAS for significant markers)
twostep.SNP_set.res <- RGWAS.twostep(phenotype = phenotype.GWAS, genotype = genotype.GWAS, ZETA = ZETA,
                                   kernel.percent = 0.2, n.PC = 4, test.method.2 = "LR",
                                   kernel.method = "linear", gene.set = NULL,
                                   test.effect.2 = "additive", window.size.half = 3,
                                   window.slide = 2)

See(twostep.SNP_set.res$D)
### Column 4 contains -log10(p) values for markers with the first method (single-SNP GWAS)
### Column 5 contains -log10(p) values for markers with the second method (SNP-set GWAS)

```

---

RGWAS.twostep.epi

---

*Perform normal GWAS (genome-wide association studies) first, then  
check epistatic effects for relatively significant markers*


---

## Description

Perform normal GWAS (genome-wide association studies) first, then check epistatic effects for relatively significant markers

## Usage

```
RGWAS.twostep.epi(pheno, geno, ZETA = NULL, covariate = NULL,
  covariate.factor = NULL, structure.matrix = NULL, n.PC = 0,
  min.MAF = 0.02, n.core = 1, check.size.epi = 4,
  epistasis.percent = 0.05, check.epi.max = 200, your.check = NULL,
  GWAS.res.first = NULL, P3D = TRUE, test.method = "LR",
  dominance.eff = TRUE, haplotype = TRUE, num.hap = NULL,
  optimizer = "nlsminb", window.size.half = 5, window.slide = 1,
  chi0.mixture = 0.5, gene.set = NULL, sig.level = 0.05,
  method.thres = "BH", plot.qq.1 = TRUE, plot.Manhattan.1 = TRUE,
  plot.epi.3d = TRUE, plot.epi.2d = TRUE, plot.method = 1,
  plot.col1 = c("dark blue", "cornflowerblue"), plot.col2 = 1,
  plot.type = "p", plot.pch = 16, saveName = NULL,
  main.qq.1 = NULL, main.man.1 = NULL, main.epi.3d = NULL,
  main.epi.2d = NULL, verbose = TRUE, verbose2 = FALSE,
  count = TRUE, time = TRUE)
```

## Arguments

pheno	Data frame where the first column is the line name (gid). The remaining columns should be a phenotype to test.
geno	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position. Columns 4 and higher contain the marker scores for each line, coded as -1, 0, 1 = aa, Aa, AA.
ZETA	<p>A list of covariance (relationship) matrix (<math>K</math>: <math>m \times m</math>) and its design matrix (<math>Z</math>: <math>n \times m</math>) of random effects. Please set names of list "Z" and "K"! You can use more than one kernel matrix. For example,</p> <p><code>ZETA = list(A = list(Z = Z.A, K = K.A), D = list(Z = Z.D, K = K.D))</code></p> <p><b>Z.A, Z.D</b> Design matrix (<math>n \times m</math>) for the random effects. So, in many cases, you can use the identity matrix.</p> <p><b>K.A, K.D</b> Different kernels which express some relationships between lines.</p> <p>For example, K.A is additive relationship matrix for the covariance between lines, and K.D is dominance relationship matrix.</p>
covariate	A $n \times 1$ vector or a $n \times p_1$ matrix. You can insert continuous values, such as other traits or genotype score for special markers. This argument is regarded as one of the fixed effects.
covariate.factor	A $n \times p_2$ dataframe. You should assign a factor vector for each column. Then RGWAS changes this argument into model matrix, and this model matrix will be included in the model as fixed effects.
structure.matrix	You can use structure matrix calculated by structure analysis when there are population structure. You should not use this argument with $n.PC > 0$ .
n.PC	Number of principal components to include as fixed effects. Default is 0 (equals K model).
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
n.core	Setting $n.core > 1$ will enable parallel execution on a machine with multiple cores (use only at UNIX command line).

check.size.epi	This argument determines how many SNPs (around the SNP detected by normal GWAS) you will check epistasis.
epistasis.percent	This argument determines how many SNPs are detected by normal GWAS. For example, when epistasis.percent = 0.1, SNPs whose value of $-\log_{10}(p)$ is in the top 0.1 percent are chosen as candidate for checking epistasis.
check.epi.max	It takes a lot of time to check epistasis, so you can decide the maximum number of SNPs to check epistasis.
your.check	Because there are less SNPs that can be tested in epistasis than in kernel-based GWAS, you can select which SNPs you want to test. If you use this argument, please set the number where SNPs to be tested are located in your data (so not position). In the default setting, your_check = NULL and epistasis between SNPs detected by GWAS will be tested.
GWAS.res.first	If you have already performed regular GWAS and have the result, you can skip performing normal GWAS.
P3D	When P3D = TRUE, variance components are estimated by REML only once, without any markers in the model. When P3D = FALSE, variance components are estimated by REML for each marker separately.
test.method	RGWAS supports two methods to test effects of each SNP-set. <b>"LR"</b> Likelihood-ratio test, relatively slow, but accurate (default). <b>"score"</b> Score test, much faster than LR, but sometimes overestimate $-\log_{10}(p)$ .
dominance.eff	If this argument is TRUE, dominance effect is included in the model, and additive x dominance and dominance x dominance are also tested as epistatic effects. When you use inbred lines, please set this argument FALSE.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlnmb" functions.
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculated K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .
chi0.mixture	RAINBOW assumes the deviance is considered to follow a $x \text{chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ , where r is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
gene.set	If you have information of gene (or haplotype block), you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the

	first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for determining threshold of significance. "BH" and "Bonferroni" are offered.
plot.qq.1	If TRUE, draw qq plot for normal GWAS.
plot.Manhattan.1	If TRUE, draw manhattan plot for normal GWAS.
plot.epi.3d	If TRUE, draw 3d plot
plot.epi.2d	If TRUE, draw 2d plot
plot.method	If this argument = 1, the default manhattan plot will be drawn. If this argument = 2, the manhattan plot with axis based on Position (bp) will be drawn. Also, this plot's color is changed by all chromosomes.
plot.col1	This argument determines the color of the manhattan plot. You should substitute this argument as color vector whose length is 2. plot.col1[1] for odd chromosomes and plot.col1[2] for even chromosomes
plot.col2	Color of the manhattan plot. color changes with chromosome and it starts from plot.col2 + 1 (so plot.col2 = 1 means color starts from red.)
plot.type	This argument determines the type of the manhattan plot. See the help page of "plot".
plot.pch	This argument determines the shape of the dot of the manhattan plot. See the help page of "plot".
saveName	When drawing any plot, you can save plots in png format. In saveName, you should substitute the name you want to save. When saveName = NULL, the plot is not saved.
main.qq.1	The title of qq plot for normal GWAS. If this argument is NULL, trait name is set as the title.
main.man.1	The title of manhattan plot for normal GWAS. If this argument is NULL, trait name is set as the title.
main.epi.3d	The title of 3d plot. If this argument is NULL, trait name is set as the title.
main.epi.2d	The title of 2d plot. If this argument is NULL, trait name is set as the title.
verbose	If this argument is TRUE, messages for the current steps will be shown.
verbose2	If this argument is TRUE, welcome message will be shown.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.
time	When time is TRUE, you can know how much time it took to perform RGWAS.

## Value

**\$first** The results of first normal GWAS will be returned.

**\$epistasis \$map** Map information for SNPs which are tested epistatic effects.

**\$scores \$scores** This is the matrix which contains  $-\log_{10}(p)$  calculated by the test about epistasis effects.

**\$x, \$y** The information of the positions of SNPs detected by regular GWAS. These vectors are used when drawing plots. Each output correspond to the replication of row and column of scores.

**\$z** This is a vector of \$scores. This vector is also used when drawing plots.

## References

- Kennedy, B.W., Quinton, M. and van Arendonk, J.A. (1992) Estimation of effects of single genes on quantitative traits. *J Anim Sci.* 70(7): 2000-2012.
- Storey, J.D. and Tibshirani, R. (2003) Statistical significance for genomewide studies. *Proc Natl Acad Sci.* 100(16): 9440-9445.
- Yu, J. et al. (2006) A unified mixed-model method for association mapping that accounts for multiple levels of relatedness. *Nat Genet.* 38(2): 203-208.
- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics.* 178(3): 1709-1723.
- Kang, H.M. et al. (2010) Variance component model to account for sample structure in genome-wide association studies. *Nat Genet.* 42(4): 348-354.
- Zhang, Z. et al. (2010) Mixed linear model approach adapted for genome-wide association studies. *Nat Genet.* 42(4): 355-360.
- Endelman, J.B. (2011) Ridge Regression and Other Kernels for Genomic Selection with R Package rrBLUP. *Plant Genome J.* 4(3): 250.
- Endelman, J.B. and Jannink, J.L. (2012) Shrinkage Estimation of the Realized Relationship Matrix. *G3 Genes, Genomes, Genet.* 2(11): 1405-1413.
- Su, G. et al. (2012) Estimating Additive and Non-Additive Genetic Variances and Predicting Genetic Merits Using Genome-Wide Dense Single Nucleotide Polymorphism Markers. *PLoS One.* 7(9): 1-7.
- Zhou, X. and Stephens, M. (2012) Genome-wide efficient mixed-model analysis for association studies. *Nat Genet.* 44(7): 821-824.
- Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics.* 29(12): 1526-1533.
- Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics.* 30(22): 3206-3214.
- Jiang, Y. and Reif, J.C. (2015) Modeling epistasis in genomic selection. *Genetics.* 201(2): 759-768.

## Examples

```
### Import RAINBOW
require(RAINBOW)

### Load example datasets
data("Rice_Zhao_etal")
Rice_geno_score <- Rice_Zhao_etal$genoScore
Rice_geno_map <- Rice_Zhao_etal$genoMap
Rice_pheno <- Rice_Zhao_etal$pheno

### View each dataset
See(Rice_geno_score)
See(Rice_geno_map)
See(Rice_pheno)

### Select one trait for example
trait.name <- "Flowering.time.at.Arkansas"
```



```

y <- Rice_pheno[, trait.name, drop = FALSE]

### Remove SNPs whose MAF <= 0.05
x.0 <- t(Rice_genomap_score)
MAF.cut.res <- MAF.cut(x.0 = x.0, map.0 = Rice_genomap)
x <- MAF.cut.res$x
map <- MAF.cut.res$map

### Estimate genetic relationship matrix
K.A <- rrBLUP::A.mat(x) ### rrBLUP package can be installed by install.packages("rrBLUP")

### Modify data
modify.data.res <- modify.data(pheno.mat = y, geno.mat = x, map = map,
                              return.ZETA = TRUE, return.GWAS.format = TRUE)
pheno.GWAS <- modify.data.res$pheno.GWAS
geno.GWAS <- modify.data.res$geno.GWAS
ZETA <- modify.data.res$ZETA

### View each data for RAINBOW
See(pheno.GWAS)
See(geno.GWAS)
str(ZETA)

### Perform two-step epistasis GWAS (single-snp GWAS -> Check epistasis for significant markers)
twostep.epi.res <- RGWAS.twostep.epi(pheno = pheno.GWAS, geno = geno.GWAS, ZETA = ZETA,
                                     n.PC = 4, test.method = "LR", gene.set = NULL,
                                     window.size.half = 10, window.slide = 21)

See(twostep.epi.res$epistasis$scores)

```

---

Rice\_genomap

---

*Physical map of rice genome*


---

## Description

A dataset containing the information of physical map of rice genome (Zhao et al., 2010; PLoS One 5(5): e10780).

## Format

A data frame with 1311 rows and 3 variables:

**marker** marker name for each marker, character

**chr** chromosome number for each marker, integer

**pos** physical position for each marker, integer, (b.p.)

**Source**

<http://www.ricediversity.org/data/>

**References**

Zhao K, Wright M, Kimball J, Eizenga G, McClung A, Kovach M, Tyagi W, Ali ML, Tung CW, Reynolds A, Bustamante CD, McCouch SR (2010). Genomic Diversity and Introgression in *O. sativa* Reveal the Impact of Domestication and Breeding on the Rice Genome. *PLoS One*. 2010; 5(5): e10780.

---

Rice_genotype_score	<i>Marker genotype of rice genome</i>
---------------------	---------------------------------------

---

**Description**

A dataset containing the information of marker genotype (scored with -1, 0, 1) of rice genome (Zhao et al., 2010; *PLoS One* 5(5): e10780).

**Format**

A data frame with 1311 rows and 395 variables:

Each column shows the marker genotype of each accession. The column names are the names of accessions and the rownames are the names of markers.

**Source**

<http://www.ricediversity.org/data/>

**References**

Zhao K, Wright M, Kimball J, Eizenga G, McClung A, Kovach M, Tyagi W, Ali ML, Tung CW, Reynolds A, Bustamante CD, McCouch SR (2010). Genomic Diversity and Introgression in *O. sativa* Reveal the Impact of Domestication and Breeding on the Rice Genome. *PLoS One*. 2010; 5(5): e10780.

---

Rice_pheno	<i>Phenotype data of rice field trial</i>
------------	---

---

**Description**

A dataset containing the information of phenotype data of rice field trial (Zhao et al., 2011; *Nat Comm* 2:467).

**Format**

A data frame with 413 rows and 36 variables:

Phenotypic data of 36 traits obtained by the field trial with 413 genotypes.

**Source**

<http://www.ricediversity.org/data/>

**References**

Zhao, K. et al. (2011) Genome-wide association mapping reveals a rich genetic architecture of complex traits in *Oryza sativa*. Nat Commun. 2: 467.

---

Rice_Zhao_etal	<i>Rice_Zhao_etal:</i>
----------------	------------------------

---

**Description**

A list containing the information of marker genotype of rice genome (Zhao et al., 2010; PLoS One 5(5): e10780) and phenotype data of rice field trial (Zhao et al., 2011; Nat Comm 2:467).

**Usage**

Rice\_Zhao\_etal

**Format**

A list of 3 data frames:

**\$genoScore** marker genotype, [Rice\\_genoscore](#)

**\$genoMap** physical map, [Rice\\_genomap](#)

**\$pheno** phenotype, [Rice\\_pheno](#)

**Details**

Marker genotype and phenotype data of rice by Zhao et al., 2010.

**Source**

<http://www.ricediversity.org/data/>

**References**

Zhao K, Wright M, Kimball J, Eizenga G, McClung A, Kovach M, Tyagi W, Ali ML, Tung CW, Reynolds A, Bustamante CD, McCouch SR (2010). Genomic Diversity and Introgression in *O. sativa* Reveal the Impact of Domestication and Breeding on the Rice Genome. PLoS One. 2010; 5(5): e10780. Zhao, K. et al. (2011) Genome-wide association mapping reveals a rich genetic architecture of complex traits in *Oryza sativa*. Nat Commun. 2: 467.

**See Also**

[Rice\\_genoscore](#), [Rice\\_genomap](#), [Rice\\_pheno](#)

score.calc

*Calculate  $-\log_{10}(p)$  for single-SNP GWAS***Description**

Calculate  $-\log_{10}(p)$  of each SNP by the Wald test.

**Usage**

```
score.calc(M.now, ZETA.now, y, X.now, Hinv, P3D = TRUE,
  optimizer = "nlminb", eigen.G = NULL, min.MAF = 0.02,
  count = TRUE)
```

**Arguments**

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
ZETA.now	A list of variance (relationship) matrix ( $K$ ; $m \times m$ ) and its design matrix ( $Z$ ; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, <code>ZETA = list(A = list(Z = Z, K = K))</code> Please set names of list "Z" and "K"!
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector ( <code>rep(1, n)</code> ) and covariates. NA is not allowed.
Hinv	The inverse of $H = ZKZ' + \lambda I$ where $\lambda = \sigma_e^2 / \sigma_u^2$ .
P3D	When <code>P3D = TRUE</code> , variance components are estimated by REML only once, without any markers in the model. When <code>P3D = FALSE</code> , variance components are estimated by REML for each marker separately.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
eigen.G	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

**Value**

$-\log_{10}(p)$  for each marker

## References

- Kennedy, B.W., Quinton, M. and van Arendonk, J.A. (1992) Estimation of effects of single genes on quantitative traits. *J Anim Sci.* 70(7): 2000-2012.
- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics.* 178(3): 1709-1723.
- Kang, H.M. et al. (2010) Variance component model to account for sample structure in genome-wide association studies. *Nat Genet.* 42(4): 348-354.
- Zhang, Z. et al. (2010) Mixed linear model approach adapted for genome-wide association studies. *Nat Genet.* 42(4): 355-360.

---

score.calc.epistasis.LR

*Calculate -log10(p) of epistatic effects by LR test*

---

## Description

Calculate -log10(p) of epistatic effects by LR test

## Usage

```
score.calc.epistasis.LR(M.now, y, X.now, ZETA.now, eigen.SGS = NULL,
  eigen.G = NULL, optimizer = "nlsminb", map, haplotype = TRUE,
  num.hap = NULL, window.size.half = 5, window.slide = 1,
  chi0.mixture = 0.5, gene.set = NULL, dominance.eff = TRUE,
  min.MAF = 0.02, count = TRUE)
```

## Arguments

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA.now	A list of variance (relationship) matrix ( $K; m \times m$ ) and its design matrix ( $Z; n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
eigen.SGS	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $SGS$ , where $S = I - X(X'X)^{-1}X'$ , $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
eigen.G	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors

	The result of the eigen decomposition of $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
map	Data frame of map information where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculate K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .
chi0.mixture	RAINBOW assumes the tdeviance is considered to follow $a \times \text{chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ , where r is the degree of freedom. The argument chi0.mixture is a ( $0 \leq a < 1$ ), and default is 0.5.
gene.set	If you have information of gene, you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
dominance.eff	If this argument is TRUE, dominance effect is included in the model, and additive x dominance and dominance x dominance are also tested as epistatic effects. When you use inbred lines, please set this argument FALSE.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

$-\log_{10}(p)$  of epistatic effects for each SNP-set

### References

Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.

Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

Jiang, Y. and Reif, J.C. (2015) Modeling epistasis in genomic selection. *Genetics*. 201(2): 759-768.

---

score.calc.epistasis.score

*Calculate -log10(p) of epistatic effects with score test*

---

## Description

Calculate -log10(p) of epistatic effects with score test

## Usage

```
score.calc.epistasis.score(M.now, y, X.now, ZETA.now, Gu, Ge, P0, map,
  haplotype = TRUE, num.hap = NULL, window.size.half = 5,
  window.slide = 1, chi0.mixture = 0.5, gene.set = NULL,
  dominance.eff = TRUE, min.MAF = 0.02, count = TRUE)
```

## Arguments

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA.now	A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
Gu	A $n \times n$ matrix. You should assign $ZKZ'$ , where K is covariance (relationship) matrix and Z is its design matrix.
Ge	A $n \times n$ matrix. You should assign identity matrix I (diag(n)).
P0	A $n \times n$ matrix. The Moore-Penrose generalized inverse of $SV0S$ , where $S = X(X'X)^{-1}X'$ and $V0 = \sigma_u^2Gu + \sigma_e^2Ge$ . $\sigma_u^2$ and $\sigma_e^2$ are estimators of the null model.
map	Data frame of map information where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is -log10(p) for each marker.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating -log10(p). (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.

window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculate K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If <code>window.slide = 1</code> , every marker will be tested. If you want to perform SNP set by bins, please set <code>window.slide = 2 * window.size.half + 1</code> .
chi0.mixture	RAINBOW assumes the test statistic $l1'F/l1$ is considered to follow a $\chi^2$ distribution with $df = 0 + (1 - a) \times \chi^2(df = r)$ , where $l1$ is the first derivative of the log-likelihood and $F$ is the Fisher information. And $r$ is the degree of freedom. The argument <code>chi0.mixture</code> is a $(0 \leq a < 1)$ , and default is 0.5.
gene.set	If you have information of gene, you can use it to perform kernel-based GWAS. You should assign your gene information to <code>gene.set</code> in the form of a "data.frame" (whose dimension is (the number of gene) $\times$ 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
dominance.eff	If this argument is TRUE, dominance effect is included in the model, and additive $\times$ dominance and dominance $\times$ dominance are also tested as epistatic effects. When you use inbred lines, please set this argument FALSE.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

$-\log_{10}(p)$  of epistatic effects for each SNP-set

### References

- Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.
- Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.
- Jiang, Y. and Reif, J.C. (2015) Modeling epistasis in genomic selection. *Genetics*. 201(2): 759-768.

---

score.calc.LR	<i>Calculate <math>-\log_{10}(p)</math> of each SNP-set by the LR test</i>
---------------	--

---

### Description

This function calculates  $-\log_{10}(p)$  of each SNP-set by the LR (likelihood-ratio) test. First, the function solves the multi-kernel mixed model and calculates the maximum restricted log likelihood. Then it performs the LR test by using the fact that the deviance

$$D = 2 \times (LL_{alt} - LL_{null})$$

follows the chi-square distribution.



## Usage

```
score.calc.LR(M.now, y, X.now, ZETA.now, LL0, eigen.SGS = NULL,
  eigen.G = NULL, optimizer = "nlminb", map,
  kernel.method = "linear", kernel.h = "tuned", haplotype = TRUE,
  num.hap = NULL, test.effect = "additive", window.size.half = 5,
  window.slide = 1, chi0.mixture = 0.5, weighting.center = TRUE,
  weighting.other = NULL, gene.set = NULL, min.MAF = 0.02,
  count = TRUE)
```

## Arguments

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA.now	A list of variance (relationship) matrix ( $K$ ; $m \times m$ ) and its design matrix ( $Z$ ; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, <code>ZETA = list(A = list(Z = Z, K = K))</code> Please set names of list "Z" and "K"!
LL0	The log-likelihood for the null model.
eigen.SGS	<p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p> <p>The result of the eigen decomposition of <math>SGS</math>, where <math>S = I - X(X'X)^{-1}X'</math>, <math>G = ZKZ'</math>. You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.</p>
eigen.G	<p>A list with</p> <p><b>\$values</b> Eigen values</p> <p><b>\$vectors</b> Eigen vectors</p> <p>The result of the eigen decomposition of <math>G = ZKZ'</math>. You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.</p>
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
map	Data frame of map information where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
kernel.method	<p>It determines how to calculate kernel. There are three methods.</p> <p><b>"gaussian"</b> It is the default method. Gaussian kernel is calculated by distance matrix.</p> <p><b>"exponential"</b> When this method is selected, exponential kernel is calculated by distance matrix.</p> <p><b>"linear"</b> When this method is selected, linear kernel is calculated by A.mat.</p>

kernel.h	The hyper-parameter for gaussian or exponential kernel. If kernel.h = "tuned", this hyper parameter is calculated as the median of off-diagonals of distance matrix of genotype data.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
test.effect	Effect of each marker to test. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". You also can choose more than one effect, for example, test.effect = c("additive", "aditive+dominance")
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculated K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .
chi0.mixture	RAINBOW assumes the deviance is considered to follow a $x \text{ chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ . where r is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
weighting.center	In kernel-based GWAS, weights according to the Gaussian distribution (centered on the tested SNP) are taken into account when calculating the kernel if Rainbow = TRUE. If weighting.center = FALSE, weights are not taken into account.
weighting.other	You can set other weights in addition to weighting.center. The length of this argument should be equal to the number of SNPs. For example, you can assign SNP effects from the information of gene annotation.
gene.set	If you have information of gene, you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

$-\log_{10}(p)$  for each SNP-set

### References

Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.

Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

---

score.calc.LR.MC	<i>Calculate <math>-\log_{10}(p)</math> of each SNP-set by the LR test (multi-cores)</i>
------------------	--

---

## Description

This function calculates  $-\log_{10}(p)$  of each SNP-set by the LR (likelihood-ratio) test. First, the function solves the multi-kernel mixed model and calculates the maximum restricted log likelihood. Then it performs the LR test by using the fact that the deviance

$$D = 2 \times (LL_{alt} - LL_{null})$$

follows the chi-square distribution.

## Usage

```
score.calc.LR.MC(M.now, y, X.now, ZETA.now, LL0, eigen.SGS = NULL,
  eigen.G = NULL, n.core = 2, map, kernel.method = "linear",
  kernel.h = "tuned", haplotype = TRUE, num.hap = NULL,
  test.effect = "additive", window.size.half = 5, window.slide = 1,
  optimizer = "nllminb", chi0.mixture = 0.5, weighting.center = TRUE,
  weighting.other = NULL, gene.set = NULL, min.MAF = 0.02,
  count = TRUE)
```

## Arguments

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA.now	A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
LL0	The log-likelihood for the null model.
eigen.SGS	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $SGS$ , where $S = I - X(X'X)^{-1}X'$ , $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
eigen.G	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors

	The result of the eigen decomposition of $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
n.core	Setting n.core > 1 will enable parallel execution on a machine with multiple cores.
map	Data frame of map information where the first column is the marker names, the second and third column is the chromosome and map position, and the fourth column is $-\log_{10}(p)$ for each marker.
kernel.method	It determines how to calculate kernel. There are three methods. <b>"gaussian"</b> It is the default method. Gaussian kernel is calculated by distance matrix. <b>"exponential"</b> When this method is selected, exponential kernel is calculated by distance matrix. <b>"linear"</b> When this method is selected, linear kernel is calculated by A.mat.
kernel.h	The hyper parameter for gaussian or exponential kernel. If kernel.h = "tuned", this hyper parameter is calculated as the median of off-diagonals of distance matrix of genotype data.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating $-\log_{10}(p)$ . (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
test.effect	Effect of each marker to test. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". You also can choose more than one effect, for example, test.effect = c("additive", "additive+dominance")
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculate K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlopt" functions.
chi0.mixture	RAINBOW assumes the deviance is considered to follow $a \times \text{chisq}(df = 0) + (1 - a) \times \text{chisq}(df = r)$ , where r is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
weighting.center	In kernel-based GWAS, weights according to the Gaussian distribution (centered on the tested SNP) are taken into account when calculating the kernel if Rainbow = TRUE. If weighting.center = FALSE, weights are not taken into account.
weighting.other	You can set other weights in addition to weighting.center. The length of this argument should be equal to the number of SNPs. For example, you can assign SNP effects from the information of gene annotation.

gene.set	If you have information of gene, you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

-log10(p) for each SNP-set

### References

- Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.
- Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

---

score.calc.MC	<i>Calculate -log10(p) for single-SNP GWAS (multi-cores)</i>
---------------	--

---

### Description

Calculate -log10(p) of each SNP by the Wald test.

### Usage

```
score.calc.MC(M.now, ZETA.now, y, X.now, Hinv, n.core = 2, P3D = TRUE,
  optimizer = "nllminb", eigen.G = NULL, min.MAF = 0.02,
  count = TRUE)
```

### Arguments

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
ZETA.now	A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
Hinv	The inverse of $H = ZKZ' + \lambda I$ where $\lambda = \sigma_e^2 / \sigma_u^2$ .
n.core	Setting n.core > 1 will enable parallel execution on a machine with multiple cores.

P3D	When P3D = TRUE, variance components are estimated by REML only once, without any markers in the model. When P3D = FALSE, variance components are estimated by REML for each marker separately.
optimizer	The function used in the optimization process. We offer "optim", "optimx", and "nlminb" functions.
eigen.G	A list with <b>\$values</b> Eigen values <b>\$vectors</b> Eigen vectors The result of the eigen decomposition of $G = ZKZ'$ . You can use "spectralG.cpp" function in RAINBOW. If this argument is NULL, the eigen decomposition will be performed in this function. We recommend you assign the result of the eigen decomposition beforehand for time saving.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

-log10(p) for each marker

### References

- Kennedy, B.W., Quinton, M. and van Arendonk, J.A. (1992) Estimation of effects of single genes on quantitative traits. *J Anim Sci.* 70(7): 2000-2012.
- Kang, H.M. et al. (2008) Efficient Control of Population Structure in Model Organism Association Mapping. *Genetics.* 178(3): 1709-1723.
- Kang, H.M. et al. (2010) Variance component model to account for sample structure in genome-wide association studies. *Nat Genet.* 42(4): 348-354.
- Zhang, Z. et al. (2010) Mixed linear model approach adapted for genome-wide association studies. *Nat Genet.* 42(4): 355-360.

---

score.calc.score	<i>Calculate -log10(p) of each SNP-set by the score test</i>
------------------	--

---

### Description

This function calculates -log10(p) of each SNP-set by the score test. First, the function calculates the score statistic without solving the multi-kernel mixed model for each SNP-set. Then it performs the score test by using the fact that the score statistic follows the chi-square distribution.

### Usage

```
score.calc.score(M.now, y, X.now, ZETA.now, LL0, Gu, Ge, P0, map,
  kernel.method = "linear", kernel.h = "tuned", haplotype = TRUE,
  num.hap = NULL, test.effect = "additive", window.size.half = 5,
  window.slide = 1, chi0.mixture = 0.5, weighting.center = TRUE,
  weighting.other = NULL, gene.set = NULL, min.MAF = 0.02,
  count = TRUE)
```

**Arguments**

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA.now	A list of variance (relationship) matrix ( $K$ ; $m \times m$ ) and its design matrix ( $Z$ ; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
LL0	The log-likelihood for the null model.
Gu	A $n \times n$ matrix. You should assign $ZKZ'$ , where K is covariance (relationship) matrix and Z is its design matrix.
Ge	A $n \times n$ matrix. You should assign identity matrix I (diag(n)).
P0	$n \times n$ matrix. The Moore-Penrose generalized inverse of $SV0S$ , where $S = X(X'X)^{-1}X'$ and $V0 = \sigma_u^2 Gu + \sigma_e^2 Ge$ . $\sigma_u^2$ and $\sigma_e^2$ are estimators of the null model.
map	Data frame of map information where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is -log10(p) for each marker.
kernel.method	It determines how to calculate kernel. There are three methods. <b>"gaussian"</b> It is the default method. Gaussian kernel is calculated by distance matrix. <b>"exponential"</b> When this method is selected, exponential kernel is calculated by distance matrix. <b>"linear"</b> When this method is selected, linear kernel is calculated by A.mat.
kernel.h	The hyper parameter for gaussian or exponential kernel. If kernel.h = "tuned", this hyper parameter is calculated as the median of off-diagonals of distance matrix of genotype data.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating -log10(p). (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
test.effect	Effect of each marker to test. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". You also can choose more than one effect, for example, test.effect = c("additive", "aditive+dominance")
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculated K.SNP. More precisely, the number of SNPs will be $2 * \text{window.size.half} + 1$ .
window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = $2 * \text{window.size.half} + 1$ .

chi0.mixture	RAINBOW assumes the test statistic $l1'F/l1$ is considered to follow a $\chi^2$ distribution with $df = 0 + (1 - a) \times \chi^2(df = r)$ , where $l1$ is the first derivative of the log-likelihood and $F$ is the Fisher information. And $r$ is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
weighting.center	In kernel-based GWAS, weights according to the Gaussian distribution (centered on the tested SNP) are taken into account when calculating the kernel if Rainbow = TRUE. If weighting.center = FALSE, weights are not taken into account.
weighting.other	You can set other weights in addition to weighting.center. The length of this argument should be equal to the number of SNPs. For example, you can assign SNP effects from the information of gene annotation.
gene.set	If you have information of gene, you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) $\times$ 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

$-\log_{10}(p)$  for each SNP-set

### References

Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.

Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

---

score.calc.score.MC	<i>Calculate <math>-\log_{10}(p)</math> of each SNP-set by the score test (multi-cores)</i>
---------------------	---

---

### Description

This function calculates  $-\log_{10}(p)$  of each SNP-set by the score test. First, the function calculates the score statistic without solving the multi-kernel mixed model for each SNP-set. Then it performs the score test by using the fact that the score statistic follows the chi-square distribution.

### Usage

```
score.calc.score.MC(M.now, y, X.now, ZETA.now, LL0, Gu, Ge, P0,
  n.core = 2, map, kernel.method = "linear", kernel.h = "tuned",
  haplotype = TRUE, num.hap = NULL, test.effect = "additive",
  window.size.half = 5, window.slide = 1, chi0.mixture = 0.5,
  weighting.center = TRUE, weighting.other = NULL, gene.set = NULL,
  min.MAF = 0.02, count = TRUE)
```



**Arguments**

M.now	A n.sample x n.mark genotype matrix where n.sample is sample size and n.mark is the number of markers.
y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
X.now	A $n \times p$ matrix. You should assign mean vector (rep(1, n)) and covariates. NA is not allowed.
ZETA.now	A list of variance (relationship) matrix (K; $m \times m$ ) and its design matrix (Z; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, ZETA = list(A = list(Z = Z, K = K)) Please set names of list "Z" and "K"!
LL0	The log-likelihood for the null model.
Gu	A $n \times n$ matrix. You should assign $ZKZ'$ , where K is covariance (relationship) matrix and Z is its design matrix.
Ge	A $n \times n$ matrix. You should assign identity matrix I (diag(n)).
P0	A $n \times n$ matrix. The Moore-Penrose generalized inverse of $SV0S$ , where $S = X(X'X)^{-1}X'$ and $V0 = \sigma_u^2 Gu + \sigma_e^2 Ge$ . $\sigma_u^2$ and $\sigma_e^2$ are estimators of the null model.
n.core	Setting n.core > 1 will enable parallel execution on a machine with multiple cores.
map	Data frame of map information where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is -log10(p) for each marker.
kernel.method	It determines how to calculate kernel. There are three methods. <b>"gaussian"</b> It is the default method. Gaussian kernel is calculated by distance matrix. <b>"exponential"</b> When this method is selected, exponential kernel is calculated by distance matrix. <b>"linear"</b> When this method is selected, linear kernel is calculated by A.mat.
kernel.h	The hyper parameter for gaussian or exponential kernel. If kernel.h = "tuned", this hyper parameter is calculated as the median of off-diagonals of distance matrix of genotype data.
haplotype	If the number of lines of your data is large (maybe > 100), you should set haplotype = TRUE. When haplotype = TRUE, haplotype-based kernel will be used for calculating -log10(p). (So the dimension of this gram matrix will be smaller.) The result won't be changed, but the time for the calculation will be shorter.
num.hap	When haplotype = TRUE, you can set the number of haplotypes which you expect. Then similar arrays are considered as the same haplotype, and then make kernel(K.SNP) whose dimension is num.hap x num.hap. When num.hap = NULL (default), num.hap will be set as the maximum number which reflects the difference between lines.
test.effect	Effect of each marker to test. You can choose "test.effect" from "additive", "dominance" and "additive+dominance". You also can choose more than one effect, for example, test.effect = c("additive", "aditive+dominance")
window.size.half	This argument decides how many SNPs (around the SNP you want to test) are used to calculated K.SNP. More precisely, the number of SNPs will be 2 * window.size.half + 1.

window.slide	This argument determines how often you test markers. If window.slide = 1, every marker will be tested. If you want to perform SNP set by bins, please set window.slide = 2 * window.size.half + 1.
chi0.mixture	RAINBOW assumes the test statistic $l'F/l$ is considered to follow a $\chi^2$ distribution with $df = 0 + (1 - a) \times \chi^2(df = r)$ , where $l$ is the first derivative of the log-likelihood and $F$ is the Fisher information. And $r$ is the degree of freedom. The argument chi0.mixture is a $(0 \leq a < 1)$ , and default is 0.5.
weighting.center	In kernel-based GWAS, weights according to the Gaussian distribution (centered on the tested SNP) are taken into account when calculating the kernel if Rainbow = TRUE. If weighting.center = FALSE, weights are not taken into account.
weighting.other	You can set other weights in addition to weighting.center. The length of this argument should be equal to the number of SNPs. For example, you can assign SNP effects from the information of gene annotation.
gene.set	If you have information of gene, you can use it to perform kernel-based GWAS. You should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "geno" argument.
min.MAF	Specifies the minimum minor allele frequency (MAF). If a marker has a MAF less than min.MAF, it is assigned a zero score.
count	When count is TRUE, you can know how far RGWAS has ended with percent display.

### Value

$-\log_{10}(p)$  for each SNP-set

### References

- Listgarten, J. et al. (2013) A powerful and efficient set test for genetic markers that handles confounders. *Bioinformatics*. 29(12): 1526-1533.
- Lippert, C. et al. (2014) Greater power and computational efficiency for kernel-based association testing of sets of genetic variants. *Bioinformatics*. 30(22): 3206-3214.

---

score.cpp

*Calculate  $-\log_{10}(p)$  by score test (slow, for general cases)*

---

### Description

Calculate  $-\log_{10}(p)$  by score test (slow, for general cases)

### Usage

score.cpp(y, Gs, Gu, Ge, P0, chi0.mixture = 0.5)

**Arguments**

y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
Gs	A list of kernel matrices you want to test. For example, Gs = list(A.part = K.A.part, D.part = K.D.part)
Gu	A $n \times n$ matrix. You should assign $ZKZ'$ , where K is covariance (relationship) matrix and Z is its design matrix.
Ge	A $n \times n$ matrix. You should assign identity matrix I (diag(n)).
P0	A $n \times n$ matrix. The Moore-Penrose generalized inverse of $SV0S$ , where $S = X(X'X)^{-1}X'$ and $V0 = \sigma_u^2Gu + \sigma_e^2Ge$ . $\sigma_u^2$ and $\sigma_e^2$ are estimators of the null model.
chi0.mixture	RAINBOW assumes the test statistic $l1'F/l1$ is considered to follow a $x$ chisq(df = 0) + (1 - a) x chisq(df = r). where l1 is the first derivative of the log-likelihood and F is the Fisher information. And r is the degree of freedom. The argument chi0.mixture is a (0 <= a < 1), and default is 0.5.

**Value**

-log10(p) calculated by score test

---

score.linker.cpp	<i>Calculate -log10(p) by score test (fast, for limited cases)</i>
------------------	--

---

**Description**

Calculate -log10(p) by score test (fast, for limited cases)

**Usage**

```
score.linker.cpp(y, Ws, Gammas, gammas.diag = TRUE, Gu, Ge, P0,
  chi0.mixture = 0.5)
```

**Arguments**

y	A $n \times 1$ vector. A vector of phenotypic values should be used. NA is allowed.
Ws	A list of low rank matrices ( $ZW$ ; $n \times k$ matrix). This forms linear kernel $ZKZ' = ZW\Gamma(ZW)'$ . For example, Ws = list(A.part = ZW.A, D.part = ZW.D)
Gammas	A list of matrices for weighting SNPs (Gamma; $k \times k$ matrix). This forms linear kernel $ZKZ' = ZW\Gamma(ZW)'$ . For example, if there is no weighting, Gammas = lapply(Ws, function(x) diag(ncol(x)))
gammas.diag	If each Gamma is the diagonal matrix, please set this argument TRUE. The calculation time can be saved.
Gu	A $n \times n$ matrix. You should assign $ZKZ'$ , where K is covariance (relationship) matrix and Z is its design matrix.
Ge	A $n \times n$ matrix. You should assign identity matrix I (diag(n)).
P0	A $n \times n$ matrix. The Moore-Penrose generalized inverse of $SV0S$ , where $S = X(X'X)^{-1}X'$ and $V0 = \sigma_u^2Gu + \sigma_e^2Ge$ . $\sigma_u^2$ and $\sigma_e^2$ are estimators of the null model.
chi0.mixture	RAINBOW assumes the statistic $l1'F/l1$ follows the mixture of $\chi_0^2$ and $\chi_r^2$ , where l1 is the first derivative of the log-likelihood and F is the Fisher information. And r is the degree of freedom. chi0.mixture determines the proportion of $\chi_0^2$

**Value**

$-\log_{10}(p)$  calculated by score test

---

See

*Function to view the first part of data (like head(), tail())*

---

**Description**

Function to view the first part of data (like head(), tail())

**Usage**

```
See(data, fh = TRUE, fl = TRUE, rown = 6, coln = 6, rowst = 1,
     colst = 1, narray = 2, drop = FALSE, save.variable = FALSE,
     verbose = TRUE)
```

**Arguments**

data	Your data. 'vector', 'matrix', 'array' (whose dimensions $\leq 4$ ), 'data.frame' are supported format. If other formatted data is assigned, str(data) will be returned.
fh	From head. If this argument is TRUE, first part (row) of data will be shown (like head() function). If FALSE, last part (row) of your data will be shown (like tail() function).
fl	From left. If this argument is TRUE, first part (column) of data will be shown (like head() function). If FALSE, last part (column) of your data will be shown (like tail() function).
rown	The number of rows shown in console.
coln	The number of columns shown in console.
rowst	The start point for the direction of row.
colst	The start point for the direction of column.
narray	The number of dimensions other than row and column shown in console. This argument is effective only your data is array (whose dimensions $\geq 3$ ).
drop	When rown = 1 or coln = 1, the dimension will be reduced if this argument is TRUE.
save.variable	If you want to assign the result to a variable, please set this argument TRUE.
verbose	If TRUE, print the first part of data.

**Value**

If save.variable is FALSE, NULL. If TRUE, the first part of your data will be returned.

spectralG.cpp

*Perform spectral decomposition (implemented by Rcpp)***Description**

Perform spectral decomposition for  $G = ZKZ'$  or  $SGS$  where  $S = I - X(X'X)^{-1}X$ .

**Usage**

```
spectralG.cpp(ZETA, Zws = NULL, X = NULL, weights = 1,
  return.G = TRUE, return.SGS = FALSE, spectral.method = NULL,
  tol = NULL, df.H = NULL)
```

**Arguments**

ZETA	A list of variance (relationship) matrix ( $K$ ; $m \times m$ ) and its design matrix ( $Z$ ; $n \times m$ ) of random effects. You can use only one kernel matrix. For example, <code>ZETA = list(A = list(Z = Z, K = K))</code> Please set names of list "Z" and "K"!
Zws	A list of additional linear kernels other than genetic relationship matrix. We utilize this argument in <code>RGWAS.multisnp</code> function, so you can ignore this.
X	$n \times p$ matrix. You should assign mean vector ( <code>rep(1, n)</code> ) and covariates. NA is not allowed.
weights	If the length of ZETA $\geq 2$ , you should assign the ratio of variance components to this argument.
return.G	If this argument is TRUE, spectral decomposition results of G will be returned. ( $G = ZKZ'$ )
return.SGS	If this argument is TRUE, spectral decomposition results of SGS will be returned. ( $S = I - X(X'X)^{-1}X$ , $G = ZKZ'$ )
spectral.method	The method of spectral decomposition. In this function, "eigen" : eigen decomposition and "cholesky" : cholesky and singular value decomposition are offered. If this argument is NULL, either method will be chosen according to the dimension of Z and X.
tol	The tolerance for detecting linear dependencies in the columns of $G = ZKZ'$ . Eigen vectors whose eigen values are less than "tol" argument will be omitted from results. If tol is NULL, top 'n' eigen values will be effective.
df.H	The degree of freedom of K matrix. If this argument is NULL, <code>min(n, sum(nrow(K1), nrow(K2), ...))</code> will be assigned.

**Value**

**\$spectral.G** The spectral decomposition results of G.

**\$U** Eigen vectors of G.

**\$delta** Eigen values of G.

**\$spectral.SGS** Estimator for  $\sigma_e^2$

**\$Q** Eigen vectors of SGS.

**\$theta** Eigen values of SGS.

SS\_gwas

---

*Calculate some summary statistics of GWAS (genome-wide association studies) for simulation study*

---

## Description

Calculate some summary statistics of GWAS (genome-wide association studies) for simulation study

## Usage

```
SS_gwas(res, x, map.x, qtn.candidate, gene.set = NULL,
        n.top.false.block = 10, sig.level = c(0.05, 0.01),
        method.thres = "BH", inflator.plus = 2, LD_length = 150000,
        cor.thres = 0.35, window.size = 0, saveName = NULL,
        plot.ROC = TRUE)
```

## Arguments

res	Data frame of GWAS results where the first column is the marker names, the second and third column is the chromosome and map position, and the forth column is $-\log_{10}(p)$ for each marker.
x	A N (lines) x M (markers) marker genotype data (matrix), coded as -1, 0, 1 = aa, Aa, AA.
map.x	Data frame with the marker names in the first column. The second and third columns contain the chromosome and map position.
qtn.candidate	A vector of causal markers. You should assign where those causal markers are positioned in our marker genotype, rather than physical position of those causal markers.
gene.set	If you have information of gene (or haplotype block), and if you used it to perform kernel-based GWAS, you should assign your gene information to gene.set in the form of a "data.frame" (whose dimension is (the number of gene) x 2). In the first column, you should assign the gene name. And in the second column, you should assign the names of each marker, which correspond to the marker names of "x" argument.
n.top.false.block	We will calculate the mean of $-\log_{10}(p)$ values of top 'n.top.false.block' blocks to evaluate the inflation level of results. The default is 10.
sig.level	Significance level for the threshold. The default is 0.05.
method.thres	Method for determining threshold of significance. "BH" and "Bonferroni" are offered.
inflator.plus	If 'the $-\log_{10}(p)$ value for each marker' exceeds ('the inflation level' + 'inflator.plus'), that marker is regarded as significant.
LD_length	SNPs within the extent of LD are regarded as one set. This LD_length determines the size of LD block, and 2 x LD_length (b.p.) will be the size of LD block.

<code>cor.thres</code>	SNPs within the extent of LD are regarded as one set. This <code>cor.thres</code> also determines the size of LD block, and the region with square of correlation coefficients $\geq \text{cor.thres}$ is regarded as one LD block. More precisely, the regions which satisfies both <code>LD_length</code> and <code>cor.thres</code> condition is regarded as one LD block.
<code>window.size</code>	If you perform SNP-set analysis with sliding window, we can consider the effect of window size by this argument.
<code>saveName</code>	When drawing any plot, you can save plots in png format. In <code>saveName</code> , you should substitute the name you want to save. When <code>saveName = NULL</code> , the plot is not saved.
<code>plot.ROC</code>	If this argument is TRUE, ROC (Receiver Operating Characteristic) curve will be drawn with AUC (Area Under the Curve).

### Value

**\$log.p**  $-\log_{10}(p)$  values of the causals.

**\$qtn.logp.order** The rank of  $-\log_{10}(p)$  of causals.

**\$thres** A vector which contains the information of threshold.

**\$overthres** The number of markers which exceed the threshold.

**\$AUC** Area under the curve.

**\$AUC.relax** Area under the curve calculated with LD block units.

**\$FDR** False discovery rate.  $1 - \text{Precision}$ .

**\$FPR** False positive rate.

**\$FNR** False negative rate.  $1 - \text{Recall}$ .

**\$Recall** The proportion of the number of causals detected by GWAS to the number of causals you set.

**\$Precision** The proportion of the number of causals detected by GWAS to the number of markers detected by GWAS.

**\$Accuracy** The accuracy of GWAS results.

**\$Hm** Harmonic mean of Recall and Precision.

**\$haplo.name** The haplotype block name which correspond to causals.

**\$mean.false** The mean of  $-\log_{10}(p)$  values of top 'n.top.false.block' blocks.

**\$max.trues** Maximum of the  $-\log_{10}(p)$  values of the region near causals.

---

welcome\_to\_RGWAS

*Function to greet to users*

---

### Description

Function to greet to users

### Usage

```
welcome_to_RGWAS()
```

### Value

Show welcome messages

# Index

## \*Topic **datasets**

Rice\_Zhao\_etal, [51](#)

CalcThreshold, [2](#)

cumsumPos, [3](#)

design.Z, [4](#)

EM3.cpp, [4](#)

EM3.linker.cpp, [7](#)

EMM.cpp, [10](#)

EMM1.cpp, [14](#)

EMM2.cpp, [16](#)

genesetmap, [17](#)

genetrait, [18](#)

MAF.cut, [20](#)

make.full, [20](#)

manhattan, [21](#)

manhattan.plus, [22](#)

manhattan2, [22](#)

manhattan3, [23](#)

modify.data, [24](#)

qq, [25](#)

RAINBOW, [25](#)

RAINBOW-package (RAINBOW), [25](#)

RGWAS.epistasis, [25](#)

RGWAS.menu, [29](#)

RGWAS.multisnp, [29](#)

RGWAS.normal, [35](#)

RGWAS.twostep, [39](#)

RGWAS.twostep.epi, [44](#)

Rice\_geno\_map, [49](#), [51](#)

Rice\_geno\_score, [50](#), [51](#)

Rice\_pheno, [50](#), [51](#)

Rice\_Zhao\_etal, [51](#)

score.calc, [52](#)

score.calc.epistasis.LR, [53](#)

score.calc.epistasis.score, [55](#)

score.calc.LR, [56](#)

score.calc.LR.MC, [59](#)

score.calc.MC, [61](#)

score.calc.score, [62](#)

score.calc.score.MC, [64](#)

score.cpp, [66](#)

score.linker.cpp, [67](#)

See, [68](#)

spectralG.cpp, [69](#)

SS\_gwas, [70](#)

welcome\_to\_RGWAS, [71](#)