Лабораторная работа №2

Задание 1

1. Вывести на экран время работы каждого сотрудника.

	BusinessEntit	JobTitle	Na	StartTime	EndTime
1	1	Chief Executive Officer	Day	07:00:00.0000000	15:00:00.0000000
2	2	Vice President of Engineering	Day	07:00:00.0000000	15:00:00.0000000
3	3	Engineering Manager	Day	07:00:00.0000000	15:00:00.0000000
4	4	Senior Tool Designer	Day	07:00:00.0000000	15:00:00.0000000
5	4	Senior Tool Designer	Day	07:00:00.0000000	15:00:00.0000000
6	5	Design Engineer	Day	07:00:00.0000000	15:00:00.0000000
7	6	Design Engineer	Day	07:00:00.0000000	15:00:00.0000000
8	7	Research and Development Manager	Day	07:00:00.0000000	15:00:00.0000000
9	8	Research and Development Engineer	Day	07:00:00.0000000	15:00:00.0000000
10	9	Research and Development Engineer	Day	07:00:00.0000000	15:00:00.0000000
11	10	Research and Development Manager	Day	07:00:00.0000000	15:00:00.0000000
12	11	Senior Tool Designer	Day	07:00:00.0000000	15:00:00.0000000
13	12	Tool Designer	Day	07:00:00.0000000	15:00:00.0000000
14	13	Tool Designer	Day	07:00:00.0000000	15:00:00.0000000
15	14	Senior Design Engineer	Day	07:00:00.0000000	15:00:00.0000000
16	15	Design Engineer	Day	07:00:00.0000000	15:00:00.0000000
17	16	Marketing Manager	Day	07:00:00.0000000	15:00:00.0000000

2. Вывести на экран количество сотрудников в каждой группе отделов.

	GroupName	EmpCount
1	Executive General and Administration	35
2	Inventory Management	18
3	Manufacturing	185
4	Quality Assurance	11
5	Research and Development	14
6	Sales and Marketing	27

3. Вывести на экран почасовые ставки сотрудников, с указанием максимальной ставки для каждого отдела в столбце [MaxInDepartment]. В рамках каждого отдела разбейте все ставки на группы, таким образом, чтобы ставки с одинаковыми значениями входили в состав одной группы.

```
select Name, DepHist.BusinessEntityID, Rate, MaxInDepartment,
      dense rank() over(partition by Dep.DepartmentID order by Rate) RateGroup
from HumanResources.EmployeeDepartmentHistory as DepHist
inner join HumanResources.Department as Dep
      on DepHist.DepartmentID = Dep.DepartmentID
inner join HumanResources. EmployeePayHistory as PayHist
      on DepHist.BusinessEntityID = PayHist.BusinessEntityID
inner join (/*Calculating MaxInDepartment value for each Dep*/
      select DepartmentID, MAX(Rate) as MaxInDepartment
      from HumanResources.EmployeeDepartmentHistory as DepHist
      inner join HumanResources. EmployeePayHistory as PayHist
              on DepHist.BusinessEntityID = PayHist.BusinessEntityID
      where DepHist.EndDate is null
      group by DepartmentID
) MaxInDeps
on Dep.DepartmentID = MaxInDeps.DepartmentID
where DepHist.EndDate is null
order by Name, Rate;
go
```

	Name	BusinessEntityID	Rate	MaxInDepartment	RateGroup
1	Document Control	219	10,25	17,7885	1
2	Document Control	220	10,25	17,7885	1
3	Document Control	221	16,8269	17,7885	2
4	Document Control	218	16,8269	17,7885	2
5	Document Control	217	17,7885	17,7885	3
6	Engineering	5	32,6923	63,4615	1
7	Engineering	6	32,6923	63,4615	1
8	Engineering	15	32,6923	63,4615	1
9	Engineering	14	36,0577	63,4615	2
10	Engineering	3	43,2692	63,4615	3
11	Engineering	2	63,4615	63,4615	4
12	Executive	234	39,06	125,50	1
13	Executive	234	48,5577	125,50	2
14	Executive	234	60,0962	125,50	3
15	Executive	1	125,50	125,50	4
16	Facilities and Maintenance	229	9,25	24,0385	1
17	Facilities and Maintenance	230	9,25	24,0385	1
18	Facilities and Maintenance	231	9,25	24,0385	1
19	Facilities and Maintenance	232	9,25	24,0385	1
20	Facilities and Maintenance	233	9,75	24,0385	2
21	Facilities and Maintenance	228	20,4327	24,0385	3
22	Facilities and Maintenance	227	24,0385	24,0385	4
23	Finance	262	13,4615	43,2692	1
24	Finance	246	19,00	43,2692	2
25	Finance	247	19,00	43,2692	2

Задание 2

a) Создайте таблицу dbo.Employee с такой же структурой как HumanResources.Employee, кроме полей OrganizationLevel, SalariedFlag, CurrentFlag, а также кроме полей с типом hierarchyid, uniqueidentifier, не включая индексы, ограничения и триггеры.

```
create table dbo.Employee(
    BusinessEntityID int NOT NULL,
    NationalIDNumber nvarchar(15) NOT NULL,
    LoginID nvarchar(256) NOT NULL,
    JobTitle nvarchar(50) NOT NULL,
    BirthDate date NOT NULL,
    MaritalStatus nchar(1) NOT NULL,
    Gender nchar(1) NOT NULL,
    HireDate date NOT NULL,
    VacationHours smallint NOT NULL,
    SickLeaveHours smallint NOT NULL DEFAULT ((0)),
    ModifiedDate datetime NOT NULL DEFAULT (getdate()));
go
```

```
■ KOTPC\SQLEXPRESS (SQL Server 11.0.5058 - KOTPC\
 ■ Databases
  ■ System Databases
  ■ AdventureWorks 2012
   Database Diagrams
   ■ Tables
    ■ System Tables
     ■ FileTables
     ■ dbo.AWBuildVersion
     ■ dbo.DatabaseLog
     ■ dbo.Employee
      ■ Columns
         ■ BusinessEntityID (int, not null)
         NationalIDNumber (nvarchar(15), not null)
         LoginID (nvarchar(256), not null)
         JobTitle (nvarchar(50), not null)
         BirthDate (date, not null)
         MaritalStatus (nchar(1), not null)
        Gender (nchar(1), not null)
         HireDate (date, not null)
         VacationHours (smallint, not null)
         SickLeaveHours (smallint, not null)
         ModifiedDate (datetime, not null)
      Keys
      Constraints
      Triggers
      Indexes
      Statistics
```

b) Используя инструкцию ALTER TABLE, создайте для таблицы dbo. Employee ограничение UNIQUE для поля NationalIDNumber.

```
■ KOTPC\SQLEXPRESS (SQL Server 11.0.5058 - KOTPC\HP)
 ■ Databases
  ■ System Databases
  ■ AdventureWorks2012
   ■ Database Diagrams
   ■ Tables
    ■ System Tables
    ● FileTables
    ■ dbo.AWBuildVersion
    ■ dbo.DatabaseLog
    ■■dbo.Employee
     ■ Columns
     . ■ Keys
     Constraints
     ■ Triggers
     ■ Indexes
        UC_Employee_NationalIDNumber (Unique, Non-Clustered)
```

c) Используя инструкцию ALTER TABLE, создайте для таблицы dbo. Employee ограничение для поля VacationHours, запрещающее заполнение этого поля значениями меньшими или равными 0.

```
alter table dbo.Employee
        add constraint CHECK_Employee_VacationHours
        check (VacationHours > 0);
go
```

```
■ 6 KOTPC\SQLEXPRESS (SQL Server 11.0.5058 - KOTPC\HP)
 ■ Databases
  ■■ System Databases
  ■ AdventureWorks2012
   ■ Database Diagrams
   ■ Tables
    System Tables
    ■ FileTables
    ■ dbo.AWBuildVersion
    ■ dbo.DatabaseLog
    ■ ■ dbo.Employee
     ■ Columns
     ■ Keys
     ■ Constraints
        CHECK_Employee_VacationHours
        DF_Employee_Modifi_269AB60B
        DF_Employee_SickLe_25A691D2
     ■ Triggers
     ■ Indexes
     Statistics
```

d) Используя инструкцию ALTER TABLE, создайте для таблицы dbo. Employee ограничение DEFAULT для поля VacationHours, задайте значение по умолчанию 144.

```
alter table dbo.Employee
        add constraint DEFAULT_Employee_VacationHours
        default '144' for VacationHours;
go
```

```
■ KOTPC\SQLEXPRESS (SQL Server 11.0.5058 - KOTPC\HP)
 ■ Databases
  ■ System Databases
  ■ AdventureWorks2012
   ■■ Database Diagrams
   ■ Tables
     ■ System Tables
     ... FileTables
     ■ dbo.AWBuildVersion
     ■ dbo.DatabaseLog
     ■ dbo.Employee
      ■ Columns

■ Keys

      ■ Constraints
         {}^{\tiny{$\square$}} \, CHECK\_Employee\_VacationHours
         DEFAULT_Employee_VacationHours
         DF_Employee_Modifi_269AB60B
         DF_Employee_SickLe_25A691D2
      ■ Triggers
      ■ Indexes
      ■ Statistics
```

e) Заполните новую таблицу данными из HumanResources. Employee о сотрудниках на позиции 'Buyer'. Не указывайте для выборки поле VacationHours, чтобы оно заполнилось значениями по умолчанию.

```
insert into dbo.Employee (
       BusinessEntityID,
       NationalIDNumber,
       LoginID,
       JobTitle,
       BirthDate,
       MaritalStatus,
       Gender,
       HireDate,
       SickLeaveHours,
       ModifiedDate)
select
       BusinessEntityID,
       NationalIDNumber,
       LoginID,
       JobTitle,
       BirthDate,
       MaritalStatus,
       Gender,
       HireDate,
       SickLeaveHours,
       ModifiedDate
from HumanResources.Employee
       where JobTitle = 'Buyer';
go
```

	BusinessEntit	NationallDNum	LoginID	JobTi	BirthDate
1	251	603686790	adventure-works\mikael0	Buyer	1984-08-17
2	252	792847334	adventure-works\arvind0	Buyer	1974-08-21
3	253	407505660	adventure-works\linda2	Buyer	1970-11-30
4	254	482810518	adventure-works\fukiko0	Buyer	1970-11-24
5	255	466142721	adventure-works\gordon0	Buyer	1966-11-29
6	256	367453993	adventure-works\frank2	Buyer	1952-05-12
7	257	381073001	adventure-works\eric2	Buyer	1972-09-17
8	258	785853949	adventure-works\erin0	Buyer	1971-01-04
9	259	20269531	adventure-works\ben0	Buyer	1973-06-03

MaritalStat	Gen	HireDate	VacationHo	SickLeaveHo	ModifiedDate
S	M	2009-02-10	144	49	2014-06-30 00:00:00.000
M	М	2009-02-28	144	50	2014-06-30 00:00:00.000
M	F	2009-12-17	144	48	2014-06-30 00:00:00.000
M	М	2010-01-04	144	48	2014-06-30 00:00:00.000
М	М	2010-01-11	144	46	2014-06-30 00:00:00.000
M	М	2010-01-23	144	49	2014-06-30 00:00:00.000
S	М	2010-01-27	144	47	2014-06-30 00:00:00.000
S	F	2010-01-31	144	46	2014-06-30 00:00:00.000
M	M	2010-03-09	144	47	2014-06-30 00:00:00.000

f) Измените тип поля ModifiedDate на DATE и разрешите добавление null значений для него.

```
■ 6 KOTPC\SQLEXPRESS (SQL Server 11.0.5058 - KOTPC\HP)
 ■ Databases
  ■■ System Databases
  ■ AdventureWorks2012
   ■ Database Diagrams
   ■ ■ Tables
      ■ System Tables
     ■ FileTables
     ■ dbo.AWBuildVersion
     ■ dbo.DatabaseLog
     ■ ■ dbo.Employee
      ■ Columns
         BusinessEntityID (int, not null)
         NationalIDNumber (nvarchar(15), not null)
         LoginID (nvarchar(256), not null)
         JobTitle (nvarchar(50), not null)
         ■ BirthDate (date, not null)
         MaritalStatus (nchar(1), not null)
         Gender (nchar(1), not null)
         HireDate (date, not null)
         VacationHours (smallint, not null)
         SickLeaveHours (smallint, not null)
         ModifiedDate (date, null)
      ■ Keys
      ■ Constraints
         ☐ CHECK_Employee_VacationHours
         DEFAULT_Employee_ModifiedDate
         DEFAULT_Employee_VacationHours
         DF_Employee_SickLe_25A691D2
      ■ Triggers
      ■ Indexes
      Statistics
```