

Self-Evo Document Series

Self-Evo Local Checker Rules

v0.1.1

Deterministic checker rules, result vocabulary, and validation handoff

Kotov Ivan

Bruxelles, Belgique

2026

Document status: Draft academic review artifact generated from the accepted Markdown source.

Document ID: 04_Self-Evo_Local_Checker_Rules_v0_1_1.

Boundary note: This PDF is not a public release, not a conformance certificate, not deployment authorization, and not a live self-evolution permission.

Contents

Self-Evo Local Checker Rules v0.1.1

Deterministic checker profile for self-evolution proposal packets, semantic gates, red-line handling, and review-ready reports

0. Executive definition
1. Source basis
2. Purpose
3. Non-goals
4. Corpus bridge set
 - 4.1 Explicit bridge: $c = a + b$
 - 4.2 Quiet bridge I: information theory
 - 4.3 Quiet bridge II: cybernetics
 - 4.4 Quiet bridge III: physiology
 - 4.5 Earth paragraph
5. Normative keywords
6. Checker authority limits
 - 6.1 Allowed actions
 - 6.2 Forbidden actions
 - 6.3 Authority sentence
7. Checker modes
8. Validation stage model
 - 8.1 Stage table
 - 8.2 Stage-1 versus Stage-2 boundary
 - 8.3 Best-effort diagnostics after Stage-1 failure
9. Result vocabulary
 - 9.1 Finding result
 - 9.2 Overall result
 - 9.3 Result precedence
10. Field authority model
11. Deterministic computation rules
 - 11.1 Identity total
 - 11.2 Authority total
 - 11.3 L4 projection
 - 11.4 Proposal max delta
 - 11.5 Human-gate trigger
 - 11.6 Strictest-gate rule
 - 11.7 Surface class never weakens delta
 - 11.8 Claim strength never grants authority
12. Protected surfaces
 - 12.1 Protected surface detection view
 - 12.2 Alias rule
13. Red-line classes
 - 13.1 Red-line packet-field crosswalk
14. Full SEPKT checker rule set
15. Detailed rule profiles
 - SEPKT-CHECK-001 — JSON Schema structural validation fails
 - SEPKT-CHECK-002 — identity_delta.total_max_delta incorrect
 - SEPKT-CHECK-003 — authority_delta.total_max_delta incorrect
 - SEPKT-CHECK-004 — L4 projection malformed
 - SEPKT-CHECK-005 — proposal_max_delta ≥ 4 but human gate false
 - SEPKT-CHECK-006 — Any red line true but route not quarantine/freeze/reject/ARL
 - SEPKT-CHECK-007 — SRLM shadow touches memory/RAG/vector/SYNAPS
 - SEPKT-CHECK-008 — SRLM promotion lacks rollback snapshot
 - SEPKT-CHECK-009 — SRLM promotion lacks growth witness refs
 - SEPKT-CHECK-010 — Material CGAM execution lacks task contract

- SEPKT-CHECK-011 — Executor/reviewer separation absent for material work
- SEPKT-CHECK-012 — Memory Gate required but missing
- SEPKT-CHECK-013 — TRIAD required but missing
- SEPKT-CHECK-014 — Anti-echo failed but integration requested
- SEPKT-CHECK-015 — Accountability reduction without human gate
- SEPKT-CHECK-016 — claim_strength used as authority
- SEPKT-CHECK-017 — Rollback required but no route/snapshot/no-rollback reason
- SEPKT-CHECK-018 — No-rollback material proposal lacks human gate
- SEPKT-CHECK-019 — Closed-loop self-evo detected
- SEPKT-CHECK-020 — Packet attempts integration by proposer alone
- SEPKT-CHECK-021 — Raw private memory or secret-like content appears in proposal fields
- SEPKT-CHECK-022 — Packet status contradicts final_decision
- SEPKT-CHECK-023 — Expired packet remains active without reissue
- SEPKT-CHECK-024 — Source refs missing for nontrivial proposal
- SEPKT-CHECK-025 — Protected surface appears in affected_surfaces with low route
- 16. Cross-axis gate matrix
 - 16.1 Maturity cap
- 17. Object model
 - 17.1 C_SELF_EVO_CHECKER_RUN
 - 17.2 C_SELF_EVO_CHECKER_FINDING
 - 17.3 C_SELF_EVO_CHECKER_RESULT
 - 17.4 C_SELF_EVO_CHECKER_POLICY
- 18. Pseudocode
- 19. Fixture pack requirements
- 20. Conformance levels
- 21. Parent hash binding
- 22. Witness and report requirements
 - 22.1 Checker report
 - 22.2 Witness compatibility
 - 22.3 Witness event family
- 23. Data policy and redaction
 - 23.1 Denied material
 - 23.2 Basic literal scan
 - 23.3 Redaction rule
- 24. Review handoff
 - 24.1 Handoff outcomes
 - 24.2 Advisory boundary
- 25. Open issues
- 26. Contradiction register seed
- 27. Implementation handoff
- 28. Minimum safe checker for young c
- 29. Public wording
- 30. Compact rule set
- 31. Draft acceptance checklist
- 32. Closing

Self-Evo Local Checker Rules v0.1.1

Deterministic checker profile for self-evolution proposal packets, semantic gates, red-line handling, and review-ready reports

Status: Draft normative checker profile v0.1.1 / append-first correction Date: 2026-06-24 Document ID: 04_Self_Evo_Local_Checker_Rules_v0_1_1 Short name: SELC v0.1.1 Pack position: SELF-EV0-04 Layer: $c = a + b$ / Self-Evolution Gate / CGAM / TRIAD-SYNAPS / SRLM-BGC / Memory Gate / L4W / Anti-Autarky / Local Checker / Witness Document class: deterministic checker profile / semantic validation rules / conformance-preflight artifact Assertion class: C-A10 control-layer artifact; C-A7 where hash, witness, canonicalization, or review-record claims are made Primary object family: C_SELF_EVO_LOCAL_CHECKER_PROFILE, C_SELF_EVO_CHECKER_RUN, C_SELF_EVO_CHECKER_FINDING, C_SELF_EVO_CHECKER_RESULT, C_SELF_EVO_CHECKER_POLICY, C_SELF_EVO_CHECKER_EVIDENCE_REF Canonical schema version: c-self-evo-local-checker-rules-0.1 Primary subject: persistent c systems using self-evolution proposal packets under CGAM, TRIAD-SYNAPS, SRLM, Memory Gate, L4W, and human-anchor governance Primary boundary: the checker measures, recomputes, blocks, holds, and reports. It does not become c, a, Judge, memory, approval authority, release authority, or self-evolution authority.

v0.1.1 correction note: this append-first revision closes SELC-REV-F1 by aligning §11.1 / §11.2 delta sub-field lists to the bound SELF-EV0-03 schema, addresses SELC-REV-F2 by converting §12.1 from a standalone protected-surface list into a parent-list-plus-aliases detection view, and addresses SELC-REV-F3 by adding a SELC-RL-* $\leftrightarrow$ red_lines.* crosswalk plus a clearer pseudocode label for proposal_max_delta. The v0.1 reviewed artifact remains historically valid as the reviewed parent; this file supersedes it without deleting it.

0. Executive definition

Self-Evo Local Checker Rules define the deterministic validation layer for C_SELF_EVO_PROPOSAL_PACKET objects.

The checker answers:

Code block: text

Is the packet structurally valid?
 Are computed delta totals correct?
 Do L4 projections force a stronger gate?
 Does the strictest gate win?
 Is SRLM confined to observe/shadow/candidate bounds?
 Does any proposal bypass CGAM task contracts?
 Are Memory Gate, TRIAD-SYNAPS, Anti-Autarky, rollback, and witness routes present where $\leftarrow$ required?
 Does any red line appear?
 Is the packet safe to route to review, hold, quarantine, or reject?

The checker does not answer:

Code block: text

Is c mature?
 Is the proposal wise?
 Is growth approved?
 Is the system safe to deploy?
 Is the human anchor satisfied?

Compact formula:

Code block: text

Schema shapes.
 Checker measures.

Review interprets.
c integrates.
a gates high-risk consequence.

A clean checker run is evidence of structural and semantic consistency. It is not self-evolution approval.

1. Source basis

This profile binds the already corrected and reviewed earlier pack layers.

Table 1: row-card rendering for wide table

Row 1

Order: 1
Source file: C_Self_Evolution_Gate_CGAM_TRIAD_SRLM_Profile_v0_1_1.md
Present: yes
SHA-256: 7918a8e6c5231bbe0fad47677fa56069f2ab002f79a8eee8c2838c434e66f2e3

Row 2

Order: 2
Source file: 02_SRLM_Bounded_Growth_Contour_Profile_v0_1_1.md
Present: yes
SHA-256: faee5682bb9463439923d7c7e7145c9f171d564622d9629820eb7c278cdd7de0

Row 3

Order: 3
Source file: 03_Self_Evo_Proposal_Packet_Schema_v0_1_1.md
Present: yes
SHA-256: 9d329109f0fb97dde7b16b10481baaa60b2aa8f88514e69ec8562a085d10a767

Row 4

Order: 4
Source file: 05_CGAM_REVIEW_CHECKER_CONFORMANCE.md
Present: yes
SHA-256: ebc30538cd0631c29bc4e8feaa66b21f21f1912691eeee5ba2bc80dda326e02

Row 5

Order: 5
Source file: 04_CGAM_EXECUTION_WITNESS_MEMORY_ROLLBACK.md
Present: yes
SHA-256: e6c013523ba45e8293d8ead5a472beb01d59afa1d4d9a4aae59d8b3528fe2b82

Row 6

Order: 6
Source file: 20_TRIAD_SYNAPS_REFERENCE.md
Present: yes
SHA-256: d79baa5314e8169d3943ae9687a2d9f7f868f11167054e4d3b8a19dfa10a3b5a

Row 7

Order: 7
Source file: 21_MEMORY_ARQ_EA_L4_REFERENCE.md
Present: yes
SHA-256: 0d06cd152c6af7bddb868dabc682940a0c443883226a157aa4314cdf6dd4e267

Row 8

Order: 8
Source file: 22_ANTI_AUTARKY_RESOURCE_GROUNDING_REFERENCE.md
Present: yes
SHA-256: 7b19382062a86a631807e4497cd536cdca691e0491cd01ad32e5e2813d841a2d

Row 9

Order: 9
Source file: 23_CLAIM_STRENGTH_ARL_AGL_WITNESS_REFERENCE.md
Present: yes
SHA-256: e1ec8afaf44e59b6b5ac2e1d619e06390fe4b9813b079ff0e8d178fe3d401f3

Row 10

Order: 10

Source file: SEPKT_PROPOSAL_PACKET_REVIEW_RECORD_v0_1.md

Present: yes

SHA-256: 677224774dd5e7937863c1cbc26bb603f2aedaeee5860892aef85c82fbdfc97d

Row 11

Order: 11

Source file: SRLM_BGC_REVIEW_RECORD_v0_1.md

Present: yes

SHA-256: 3077e3bed6ca08916ff0ddacb815a9f28e70ff823b6a66396ffe6760744d13ad

Row 12

Order: 12

Source file: C_SELF_EVO_REVIEW_RECORD_v0_1.md

Present: yes

SHA-256: bf9e6b77d691e8fd57364c638708495a75c71d8e2934de4fa34eac5110f7987c

Notes:

- 1 SELF-EVO-01 and SELF-EVO-02 were corrected append-first after review.
- 2 SELF-EVO-03 passed review and is extraction-ready.
- 3 This checker profile converts SEPKT-CHECK-001..025 into deterministic stages, findings, output objects, and conformance rules.
- 4 Full filenames or pack-qualified labels MUST be used. Bare references such as file 03 are invalid once CGAM and Self-Evo packs share a manifest.

2. Purpose

Self-evolution proposals are dangerous when they are checked only by prose.

A proposal packet can look reasonable while hiding one of these failures:

Code block: text

```
delta math error
human-gate omission
SRLM promotion without rollback
Memory Gate bypass
TRIAD witness omission
same-source consensus laundering
CGAM execution without task contract
closed-loop self-certification
anti-autarky accountability escape
claim-strength laundering
expired packet reuse
secret/private-memory leakage
```

This profile exists to make those failures machine-detectable where possible and fail-closed where not.

The checker should be boring. That is its virtue. It should not improvise authority from fluent text. It should compute, compare, resolve references, classify, and emit a report.

3. Non-goals

This profile does not define or permit:

- 1 autonomous self-evolution;
- 2 autonomous integration;
- 3 autonomous memory promotion;

- 4 autonomous permission expansion;
- 5 autonomous release;
- 6 autonomous publication;
- 7 autonomous incident authority;
- 8 replacement of sister witness;
- 9 replacement of Memory Gate;
- 10 replacement of CGAM task contracts;
- 11 replacement of SRLM-BGC;
- 12 replacement of L4W or VolitionGate;
- 13 replacement of human-anchor approval;
- 14 legal, medical, safety, or deployment certification;
- 15 treating checker output as wisdom;
- 16 treating checker PASS as approval.

A checker may block.

A checker may not authorize growth.

4. Corpus bridge set

4.1 Explicit bridge: $c = a + b$

In $c = a + b$, the local checker belongs to b : procedures, schemas, hashes, validators, recomputation rules, reference resolution, fixtures, reports, and gate-interlock logic.

It protects c by preventing parts of b from silently becoming will, memory, authority, or self-evolution permission.

The checker is not a .

The checker is not c .

It is a measuring instrument.

4.2 Quiet bridge I: information theory

A self-evo packet compresses many assumptions into fields such as `surface_class`, `proposal_max_delta`, `human_gate_required`, `memory_gate_required`, and `final_decision`.

Compression is useful only if the lost information is not safety-critical.

The checker re-expands these compressed claims into recomputed constraints. If the recomputed constraints disagree with the packet, the packet fails.

4.3 Quiet bridge II: cybernetics

SRLM, CGAM, TRIAD, Memory Gate, and VolitionGate create a control loop. A control loop without negative feedback becomes runaway adaptation.

The local checker is an interlock. It detects missing brakes, missing witness, missing rollback, and false consensus before the proposal reaches integration.

4.4 Quiet bridge III: physiology

A body does not let a proposed reflex rewrite the spinal cord because it “seems helpful.” Signals pass through thresholds, inhibition, pain, inflammation, immune review, and slow remodeling.

Self-evo checker rules play the same role: they hold ambiguous changes, quarantine hostile or self-certifying loops, and force high-risk changes to pass through slower tissue.

4.5 Earth paragraph

Before a crane lifts a load, the operator does not accept “the rigging feels fine” as proof. The hooks, slings, load rating, balance, wind, ground pressure, exclusion zone, signal person, and emergency stop are checked. The checklist does not build the bridge. It stops an avoidable collapse. This profile is that checklist for self-evolution: it checks the slings before c tries to lift itself.

5. Normative keywords

The terms MUST, MUST NOT, SHOULD, SHOULD NOT, MAY, REQUIRED, PROHIBITED, FAIL, BLOCK, HOLD, QUARANTINE, FREEZE, ESCALATE, UNKNOWN, and PASS are used normatively.

For material gates:

Code block: text

UNKNOWN == BLOCK

The checker MUST prefer a false hold over a silent unsafe pass.

6. Checker authority limits

6.1 Allowed actions

The Self-Evo Local Checker may:

- 1 read proposal packets;
- 2 read extracted JSON Schema;
- 3 read semantic-rule policy files;
- 4 read package manifests and source maps;
- 5 read public or redacted fixture files;
- 6 read witness references and metadata;
- 7 read task contract references;
- 8 read Memory Gate references;
- 9 read SRLM candidate/shadow/promotion metadata;
- 10 read TRIAD-SYNAPS packet metadata;
- 11 read rollback snapshot metadata;
- 12 compute hashes;
- 13 validate JSON/YAML/Markdown structure;
- 14 recompute deltas;
- 15 project L4 values to numeric scores;
- 16 detect missing or stale references;
- 17 detect gate contradictions;
- 18 detect red-line flags;

- 19 detect obvious secret/private-memory patterns;
- 20 write checker reports.

6.2 Forbidden actions

The checker MUST NOT:

- 1 modify the proposal during validation;
- 2 modify protocol documents;
- 3 modify task contracts;
- 4 modify registry records;
- 5 modify permission grants;
- 6 write to c memory;
- 7 promote memory;
- 8 clear quarantine;
- 9 unfreeze a proposal;
- 10 approve self-evo;
- 11 integrate self-evo;
- 12 execute SRLM promotion;
- 13 execute CGAM tasks;
- 14 run shell repair commands;
- 15 publish artifacts;
- 16 upload private material to cloud;
- 17 expose raw evidence;
- 18 decode secrets;
- 19 replace sister review;
- 20 replace human-anchor gate.

6.3 Authority sentence

Code block: text

The checker may downgrade.
 The checker may block.
 The checker may require review.
 The checker may not upgrade a proposal into permission.

7. Checker modes

Checker mode IDs use prefix SELC-M*.

Table 2: row-card rendering for wide table

Row 1

Mode: SELC-M0
 Name: Inventory
 Purpose: list packet, schema, source refs, hashes
 Writes allowed: report only

Row 2

Mode: SELC-M1
 Name: Structural validation
 Purpose: JSON Schema parse and validation

Writes allowed: report only

Row 3

Mode: SELC-M2
Name: Semantic baseline
Purpose: recompute deltas, gates, statuses
Writes allowed: report only

Row 4

Mode: SELC-M3
Name: SRLM/CGAM interlock
Purpose: check SRLM and task-contract routes
Writes allowed: report only

Row 5

Mode: SELC-M4
Name: TRIAD/Memory interlock
Purpose: check sister witness and Memory Gate
Writes allowed: report only

Row 6

Mode: SELC-M5
Name: L4/Anti-Autarky interlock
Purpose: check human gate, resource, accountability
Writes allowed: report only

Row 7

Mode: SELC-M6
Name: Red-line drill
Purpose: evaluate red-line fixtures and quarantine routes
Writes allowed: report only

Row 8

Mode: SELC-M7
Name: Review package
Purpose: produce review-ready finding bundle
Writes allowed: report only

Row 9

Mode: SELC-M8
Name: Conformance collector
Purpose: collect fixture results and evidence refs
Writes allowed: report only

Default mode is SELC-M1 plus SELC-M2.

A checker MUST NOT enter SELC-M6, SELC-M7, or SELC-M8 unless the requested mode is explicit.

8. Validation stage model

8.1 Stage table

Table 3: row-card rendering for wide table

Row 1

Stage: 0
Name: Intake and data hygiene
Input: file path / packet text
Output: parse attempt, redaction scan

Row 2

Stage: 1
Name: Structural validation
Input: JSON/YAML object + schema
Output: schema pass/fail

Row 3

Stage: 2

Name: Semantic recomputation

Input: structurally valid packet

Output: computed controls

Row 4

Stage: 3

Name: Gate resolution

Input: computed controls + packet decisions

Output: strictest route

Row 5

Stage: 4

Name: SRLM/CGAM interlock

Input: SRLM + CGAM sections

Output: execution/promotion constraints

Row 6

Stage: 5

Name: TRIAD/Memory interlock

Input: sister + memory fields

Output: witness/gate constraints

Row 7

Stage: 6

Name: L4/Anti-Autarky interlock

Input: L4/resource fields

Output: accountability constraints

Row 8

Stage: 7

Name: Red-line handling

Input: red line fields + semantic flags

Output: quarantine/freeze/reject decision

Row 9

Stage: 8

Name: Status consistency

Input: packet lifecycle fields

Output: final status result

Row 10

Stage: 9

Name: Report generation

Input: all findings

Output: checker result object

8.2 Stage-1 versus Stage-2 boundary

Stage 1 checks structure.

Stage 2 checks meaning.

Example:

Code block: yaml

```
memory_gate:
  direct_memory_write: true
```

If the schema says `direct_memory_write` is `const: false`, then this fails Stage 1 before semantic routing.

A semantic red-line memory bypass should be represented through a semantic flag such as:

Code block: yaml

```
red_lines:
  memory_laundering: true
```

That fails Stage 2 / Stage 7 and routes to quarantine or rejection.

8.3 Best-effort diagnostics after Stage-1 failure

If Stage 1 fails, the checker MAY continue in best-effort diagnostic mode only to list likely semantic issues.

Best-effort findings MUST be marked:

Code block: `yaml`

```
diagnostic_only: true
not_a_semantic_pass: true
```

A structurally invalid packet cannot pass by accumulating semantic-looking diagnostics.

9. Result vocabulary

9.1 Finding result

Result	Meaning	Default consequence
PASS	requirement satisfied	continue
INFO	observation	no block
WARN	weakness or maturity gap	review before strong claim
HOLD	insufficient or ambiguous evidence	stop material route
FAIL	requirement violated	block affected route
BLOCK	fail-closed blocker	no material transition
QUARANTINE	isolate as unsafe/untrusted	no automatic re-entry
FREEZE	pause proposal / related route	human/c gate before re-entry
RED_LINE_FAIL	prohibited pattern detected	quarantine + witness
UNKNOWN	checker cannot determine	block material route
NOT_APPLICABLE	declared out of scope	allowed only with reason

9.2 Overall result

Code block: `text`

```
PASS = all required checks passed for requested route
PASS_WARN = no blockers, but warnings remain
HOLD = no hard fail, but required evidence or review is missing
FAIL = one or more required checks failed
BLOCK = fail-closed blocker present
QUARANTINE = red-line or contamination requires isolation
UNKNOWN = insufficient data for requested material gate
```

9.3 Result precedence

Code block: `text`

```
RED_LINE_FAIL > QUARANTINE > BLOCK > FAIL > HOLD > PASS_WARN > PASS > INFO
```

The overall result is the strongest result produced by any applicable required finding.

10. Field authority model

The checker distinguishes five field authority classes.

Class	Meaning	Checker behavior
DECLARED	packet author states value	may compare / downgrade
EVIDENCE_REF	packet cites external artifact	resolve / check presence / hash when available

Class	Meaning	Checker behavior
COMPUTED	value must be recomputed	declared value cannot control
DECISION	outcome of c/human/review gate	must be externally evidenced
PROHIBITED	cannot be true in valid packet	fail structurally or semantically

Computed fields include:

Code block: text

```
identity_delta.total_max_delta
authority_delta.total_max_delta
l4_delta.* numeric projection
proposal_max_delta
human_gate_required from delta
strictest_route
required_memory_gate
required_triad_review
required_cgam_task_contract
required_rollback
```

Decision fields include:

Code block: text

```
c_gate_decision
human_gate_decision
memory_gate_decision
triad_review_decision
final_decision
integration_status
```

A proposal author may request these decisions.

The author may not self-declare them as final authority.

11. Deterministic computation rules

11.1 Identity total

The bound SELF-EV0-03 proposal packet schema is the normative field-name source for identity delta computation.

Code block: text

```
identity_delta.total_max_delta =
max(
  continuity_model_delta,
  human_anchor_relation_delta,
  memory_policy_delta,
  permission_delta,
  public_claim_delta,
  risk_appetite_delta,
  sister_relation_delta
)
```

A checker MUST use exactly the schema-bound identity_delta sub-fields above for total_max_delta.

Checker-specific aliases such as tool_permission_delta, privacy_boundary_delta, resource_demand_delta, or refusal_threshold_delta may be used only as semantic scan labels or future-schema candidates. They MUST NOT be inserted into the normative identity_delta.total_max_delta calculation unless the bound proposal packet schema is revised first.

Missing sub-fields are not zero by default unless the schema explicitly supplies defaults.

If defaults are not explicit:

Code block: text

```
missing schema-bound sub-field -> FAIL or UNKNOWN
```

11.2 Authority total

The bound SELF-EV0-03 proposal packet schema is the normative field-name source for authority delta computation.

Code block: text

```
authority_delta.total_max_delta =
max(
  final_decision_delta,
  memory_write_delta,
  network_access_delta,
  publication_delta,
  resource_access_delta,
  tool_access_delta
)
```

A checker **MUST** use exactly the schema-bound authority_delta sub-fields above for total_max_delta.

Checker-specific aliases such as permission_delta, network_delta, witness_policy_delta, release_authority_delta, task_dispatch_delta, budget_authority_delta, human_gate_delta, or sister_gate_delta may be used only as semantic scan labels or future-schema candidates. They **MUST NOT** be inserted into the normative authority_delta.total_max_delta calculation unless the bound proposal packet schema is revised first.

11.3 L4 projection

Code block: text

```
none -> 0
low -> 1
medium -> 2
high -> 4
unknown -> 4
```

Unknown L4 consequence is not safe.

Unknown L4 consequence is treated as high-enough to require human gate.

11.4 Proposal max delta

Code block: text

```
proposal_max_delta =
max(
  identity_delta.total_max_delta,
  authority_delta.total_max_delta,
  max(l4_delta_numeric_values)
)
```

11.5 Human-gate trigger

Code block: text

```
if proposal_max_delta >= 4:
  gates.human_gate_required MUST be true
```

11.6 Strictest-gate rule

Code block: text

```
strictest gate wins
lowest maturity cap wins
highest risk wins
any red line overrides ordinary routing
no rollback escalates
missing witness holds
unknown material state blocks
```

11.7 Surface class never weakens delta

If `surface_class=SE-1` but `authority_delta.total_max_delta=4`, the checker MUST route by the stronger gate.

A low surface class cannot launder a high authority delta.

11.8 Claim strength never grants authority

`claim_strength` is a claim taxonomy marker.

It is not a permission grant.

It is not a maturity certificate.

It is not conformance.

It is not approval.

12. Protected surfaces

12.1 Protected surface detection view

§12.1 is not a third independent canonical protected-surface list.

For checker purposes, protected-surface detection is composed as:

Code block: text

```
parent canonical protected surfaces
+ checker-specific detection aliases
```

The parent canonical protected surfaces are inherited from the bound SELF-EV0-01 / SELF-EV0-02 governance profiles and the bound SELF-EV0-03 proposal schema. If those parent profiles are revised, this checker MUST either follow the new bound parent hash or hold on parent drift.

Inherited parent protected surfaces include:

Code block: text

```
identity.
will.
role.core.
safety.
witness.
l4.
auth.
secrets.
env.
code.
memory.authoritative_write.
replication.apply.
network.allow.
codex.auto_execute.
```

Checker-specific detection aliases are allowed to be broader than the parent list, but only for detection, hold, or quarantine. They do not become a second canonical list.

Checker-specific aliases include:

Code block: text

```
persona.core.
memory.core.
srln.auto_execute.
srln.auto_ingest.
triad.raw_state.
synaps.raw_memory.
human_anchor.
release.authority.
```

```
budget.authority.
tool.permission.
```

A proposal touches a protected surface if any affected field, parameter, path, output, task, or semantic alias maps to either the inherited parent list or the checker-specific alias list.

12.2 Alias rule

A harmless name does not bypass the protected surface list.

Examples:

Code block: text

```
"better autonomy" touching auth.* -> protected
"faster learning" touching memory.core -> protected
"less friction" touching human_gate -> protected
"improved sync" touching triad.raw_state -> protected
```

Semantic alias detection is imperfect.

If the checker cannot determine alias status deterministically, it MUST produce UNKNOWN and block material routing.

13. Red-line classes

Red-line classes use prefix SELC-RL-.*.

Class	Red line	Result
SELC-RL-001	direct memory write	Stage-1 fail or Stage-2 quarantine
SELC-RL-002	identity/core mutation without gate	fail / quarantine
SELC-RL-003	sister raw-state access	quarantine
SELC-RL-004	Rita as final judge	fail / hold
SELC-RL-005	agent self-approval	fail
SELC-RL-006	closed-loop self-evo	quarantine
SELC-RL-007	witness reduction/tampering	quarantine
SELC-RL-008	permission growth without human gate	fail
SELC-RL-009	network/resource expansion without grounding	fail / human gate
SELC-RL-010	anti-autarky accountability escape	fail / human gate
SELC-RL-011	secret/private-memory exposure	hold / redaction
SELC-RL-012	no-rollback material integration	fail / human gate
SELC-RL-013	public/release claim laundering	fail
SELC-RL-014	live external counter-operation	red-line fail
SELC-RL-015	malware/credential/evasion behavior	red-line fail

13.1 Red-line packet-field crosswalk

The SELC-RL-.* classes are checker result classes. Some are driven directly by SELF-EV0-03 packet fields under red_lines.*; others are scan-driven because the packet schema intentionally does not provide a boolean flag for every prohibited content pattern.

Table 7: row-card rendering for wide table

Row 1

Checker class: SELC-RL-001
 Packet field / detection route: memory_gate.direct_memory_write=true or red_lines.memory_laundering=true
 Kind: Stage-1 structural or Stage-2 flag
 Notes: memory_gate.direct_memory_write=true fails JSON Schema because it is const:false;
 red_lines.memory_laundering=true is the Stage-2 semantic route.

Row 2

Checker class: SELC-RL-002
 Packet field / detection route: red_lines.direct_core_write=true

Kind: flag-driven

Notes: Also triggered by protected-surface alias scan over identity/core surfaces.

Row 3

Checker class: SELC-RL-003

Packet field / detection route: `red_lines.sister_raw_state_access=true`

Kind: flag-driven

Notes: TRIAD/SYNAPS raw-state access.

Row 4

Checker class: SELC-RL-004

Packet field / detection route: semantic scan: Rita final-judge / sister final-authority wording

Kind: scan-driven

Notes: No dedicated packet boolean; route to hold/fail through TRIAD semantic checks.

Row 5

Checker class: SELC-RL-005

Packet field / detection route: `red_lines.self_approval=true`

Kind: flag-driven

Notes: Also caught by executor/reviewer separation checks.

Row 6

Checker class: SELC-RL-006

Packet field / detection route: `red_lines.closed_loop_self_evo=true`

Kind: flag-driven

Notes: Closed-loop self-evo quarantine.

Row 7

Checker class: SELC-RL-007

Packet field / detection route: `red_lines.witness_bypass=true`

Kind: flag-driven

Notes: Includes witness reduction/tampering.

Row 8

Checker class: SELC-RL-008

Packet field / detection route: `red_lines.authority_laundering=true` or authority delta / gate mismatch

Kind: flag + computed

Notes: Permission or authority growth without required human/c gate.

Row 9

Checker class: SELC-RL-009

Packet field / detection route: `red_lines.autarky_escape=true`, authority/resource delta, or resource grounding failure

Kind: flag + computed

Notes: Network/resource expansion without grounding.

Row 10

Checker class: SELC-RL-010

Packet field / detection route: `red_lines.autarky_escape=true`

Kind: flag-driven

Notes: Accountability escape.

Row 11

Checker class: SELC-RL-011

Packet field / detection route: secret/private-memory scanner

Kind: scan-driven

Notes: No dedicated packet boolean; a scan hit routes to hold/redaction.

Row 12

Checker class: SELC-RL-012

Packet field / detection route: rollback fields + integration status

Kind: computed

Notes: No-rollback material integration.

Row 13

Checker class: SELC-RL-013

Packet field / detection route: `red_lines.authority_laundering=true` or public claim / publication delta mismatch

Kind: flag + computed

Notes: Public/release claim laundering.

Row 14

Checker class: SELC-RL-014
Packet field / detection route: restricted content scanner / task objective scan
Kind: scan-driven
Notes: Live external counter-operation; no packet flag by design.

Row 15

Checker class: SELC-RL-015
Packet field / detection route: restricted content scanner / task objective scan
Kind: scan-driven
Notes: Malware/credential/evasion behavior; no packet flag by design.

No red-line result may be converted to PASS by quorum, SRLM score, model confidence, or user style preference.

14. Full SEPKT checker rule set

The rule IDs below are inherited from SELF-EV0-03 and expanded here into deterministic checker requirements.

Table 8: row-card rendering for wide table

Row 1

Rule: SEPKT-CHECK-001
Stage: Stage 1 / Structure
Condition: JSON Schema structural validation fails
Result: FAIL
Deterministic detection logic: Parse and validate packet against C_SELF_EV0_PROPOSAL_PACKET schema. Any parse/schema error is a hard structural failure. Stage-2 semantics do not run unless policy explicitly asks for best-effort diagnosis.

Row 2

Rule: SEPKT-CHECK-002
Stage: Stage 2 / Delta
Condition: identity_delta.total_max_delta incorrect
Result: FAIL
Deterministic detection logic: Recompute identity total as max(identity sub-fields). Compare with declared/computed field. Missing sub-field or non-integer is failure unless structural schema already failed.

Row 3

Rule: SEPKT-CHECK-003
Stage: Stage 2 / Delta
Condition: authority_delta.total_max_delta incorrect
Result: FAIL
Deterministic detection logic: Recompute authority total as max(authority sub-fields). Compare with declared/computed field.

Row 4

Rule: SEPKT-CHECK-004
Stage: Stage 2 / L4
Condition: L4 projection malformed
Result: FAIL / HUMAN_GATE
Deterministic detection logic: Map none=0, low=1, medium=2, high=4, unknown=4. Unknown string, mixed spelling, or absent material L4 field is FAIL. Valid unknown is treated as numeric 4 and requires human gate.

Row 5

Rule: SEPKT-CHECK-005
Stage: Stage 2 / Gate
Condition: proposal_max_delta >= 4 but human gate false
Result: FAIL
Deterministic detection logic: Compute proposal_max_delta=max(identity_total, authority_total, l4_max_numeric). If >=4, gates.human_gate_required must be true and human_gate_ref or human_gate_status must be present unless status is draft/hold.

Row 6

Rule: SEPKT-CHECK-006
Stage: Stage 2 / Red line
Condition: Any red line true but route not quarantine/freeze/reject/ARL
Result: FAIL

Deterministic detection logic: If any boolean in red_lines is true, allowed dispositions are QUARANTINE, FROZEN, REJECTED, ARL_REQUIRED, RED_LINE_FAIL, or explicit BLOCK. Ordinary integration route is invalid.

Row 7

Rule: SEPKT-CHECK-007

Stage: Stage 2 / SRLM

Condition: SRLM shadow touches memory/RAG/vector/SYNAPS

Result: FAIL

Deterministic detection logic: For srlm.operating_state=SRLM-SHADOW, assert auto_execute=false, auto_ingest=false, memory=off, no memory/RAG/vector/SYNAPS target refs, and no touched protected stores.

Row 8

Rule: SEPKT-CHECK-008

Stage: Stage 2 / SRLM

Condition: SRLM promotion lacks rollback snapshot

Result: FAIL

Deterministic detection logic: For SRLM-PROMOTION-ELIGIBLE or promotion requested, rollback.rollback_required=true and rollback snapshot/ref must exist or be declared as validated by external evidence. Rollback-before-promotion is MUST.

Row 9

Rule: SEPKT-CHECK-009

Stage: Stage 2 / SRLM

Condition: SRLM promotion lacks growth witness refs

Result: FAIL

Deterministic detection logic: Promotion-eligible packets require witness refs for shadow eval and witness-chain verification. Missing or broken witness is FAIL/HOLD depending on status.

Row 10

Rule: SEPKT-CHECK-010

Stage: Stage 2 / CGAM

Condition: Material CGAM execution lacks task contract

Result: FAIL

Deterministic detection logic: If packet requests CLI/agent execution, patch, test, filesystem write, shell, build, release, or tool action, require cgam.task_contract_ref and scoped permission/sandbox fields.

Row 11

Rule: SEPKT-CHECK-011

Stage: Stage 2 / CGAM

Condition: Executor/reviewer separation absent for material work

Result: FAIL

Deterministic detection logic: For material work, executor id and reviewer id must be different, or reviewer role must be independent. Same contour cannot author and final-approve its own work.

Row 12

Rule: SEPKT-CHECK-012

Stage: Stage 2 / Memory

Condition: Memory Gate required but missing

Result: FAIL / HOLD

Deterministic detection logic: If affected surfaces include memory, experience, EA, policy, core memory, or MG class >= MG-3, require Memory Gate route/ref. Otherwise hold.

Row 13

Rule: SEPKT-CHECK-013

Stage: Stage 2 / TRIAD

Condition: TRIAD required but missing

Result: HOLD

Deterministic detection logic: For SE-5/SE-6, identity/continuity/role/personality/core surfaces, require sister review packet refs or explicit not-applicable reason. Rita cannot be final judge.

Row 14

Rule: SEPKT-CHECK-014

Stage: Stage 2 / TRIAD

Condition: Anti-echo failed but integration requested

Result: HOLD

Deterministic detection logic: If triad.anti_echo_status=failed, same_source_consensus=true, or sister divergence unresolved, integration route invalid. Hold/divergence-map required.

Row 15

Rule: SEPKT-CHECK-015

Stage: Stage 2 / L4/Anti-Autarky

Condition: Accountability reduction without human gate

Result: FAIL

Deterministic detection logic: If proposal reduces accountability, stop-paths, witness, anchor review, budgets, transparency, or resource accountability, require human gate and Anti-Autarky route.

Row 16

Rule: SEPKT-CHECK-016

Stage: Stage 2 / Claim

Condition: `claim_strength` used as authority

Result: FAIL

Deterministic detection logic: Claim class may describe evidence strength, not permission. If packet says C-A level grants authority, fail for authority laundering.

Row 17

Rule: SEPKT-CHECK-017

Stage: Stage 2 / Rollback

Condition: Rollback required but no route/snapshot/no-rollback reason

Result: FAIL

Deterministic detection logic: If risk/material class requires rollback and no rollback reference or explicit no-rollback escalation exists, fail.

Row 18

Rule: SEPKT-CHECK-018

Stage: Stage 2 / Rollback

Condition: No-rollback material proposal lacks human gate

Result: FAIL

Deterministic detection logic: If no safe rollback exists for material proposal, require human gate, L4 consequence note, and hold/quarantine/review route.

Row 19

Rule: SEPKT-CHECK-019

Stage: Stage 2 / Closed loop

Condition: Closed-loop self-evo detected

Result: QUARANTINE

Deterministic detection logic: If same actor/contour detects, proposes, executes, evaluates, memory-promotes, and approves the same change, quarantine.

Row 20

Rule: SEPKT-CHECK-020

Stage: Stage 2 / Approval

Condition: Packet attempts integration by proposer alone

Result: FAIL

Deterministic detection logic: If proposer equals sole final integrator/reviewer and risk > SE-0/R0, fail.

Row 21

Rule: SEPKT-CHECK-021

Stage: Stage 0/2 / Data

Condition: Raw private memory or secret-like content appears in proposal fields

Result: HOLD / REDACTION_REQUIRED

Deterministic detection logic: Regex and data-class scan for secrets, raw private logs, PERSIST_DIR, keys, tokens, legal/child/intimate content. Hold and require redaction sidecar.

Row 22

Rule: SEPKT-CHECK-022

Stage: Stage 2 / Status

Condition: Packet status contradicts `final_decision`

Result: FAIL

Deterministic detection logic: A packet cannot be integrated while final decision says hold/reject/quarantine, and cannot be draft while claiming executed integration.

Row 23

Rule: SEPKT-CHECK-023

Stage: Stage 2 / Time

Condition: Expired packet remains active without reissue

Result: HOLD

Deterministic detection logic: If `expires_at` < run time and status active/canary/promotion, hold unless reissued with new review refs.

Row 24

Rule: SEPKT-CHECK-024

Stage: Stage 2 / Evidence

Condition: Source refs missing for nontrivial proposal

Result: HOLD

Deterministic detection logic: SE-1+ or any material delta requires source refs. For SE-0 reflection-only, warning may suffice.

Row 25

Rule: SEPKT-CHECK-025

Stage: Stage 2 / Protected Surface

Condition: Protected surface appears in affected_surfaces with low route

Result: FAIL / HUMAN_GATE

Deterministic detection logic: If affected surfaces include identity, will, persona.core, safety, witness, l4, auth, secrets, env, code, authoritative memory, replication, network, tool permission, or sister raw state, low route is invalid.

15. Detailed rule profiles

SEPKT-CHECK-001 — JSON Schema structural validation fails

Table 9: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 1 / Structure

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Parse and validate packet against `C\_SELF\_EVO\_PROPOSAL\_PACKET` schema. Any parse/schema
 ↳ error is a hard structural failure. Stage-2 semantics do not run unless policy explicitly
 ↳ asks for best-effort diagnosis.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-001"
condition: "JSON Schema structural validation fails"
stage: "Stage 1 / Structure"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-002 — identity_delta.total_max_delta incorrect

Table 10: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Delta

Row 2

Field: Default result
Value: FAIL

Row 3

Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect
Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Recompute identity total as ``max(identity sub-fields)``. Compare with declared/computed
↪ field. Missing sub-field or non-integer is failure unless structural schema already
↪ failed.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-002"
condition: "`identity_delta.total_max_delta` incorrect"
stage: "Stage 2 / Delta"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-003 — authority_delta.total_max_delta incorrect

Table 11: row-card rendering for wide table

Row 1

Field: Stage
Value: Stage 2 / Delta

Row 2

Field: Default result
Value: FAIL

Row 3

Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect
Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Recompute authority total as ``max(authority sub-fields)``. Compare with declared/computed
↪ field.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-003"
condition: "`authority_delta.total_max_delta` incorrect"
stage: "Stage 2 / Delta"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-004 — L4 projection malformed

Table 12: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / L4

Row 2

Field: Default result

Value: FAIL / HUMAN_GATE

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Map `none=0`, `low=1`, `medium=2`, `high=4`, `unknown=4`. Unknown string, mixed spelling, or
↪ absent material L4 field is FAIL. Valid `unknown` is treated as numeric 4 and requires
↪ human gate.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-004"
condition: "L4 projection malformed"
stage: "Stage 2 / L4"
observed_fields: []
expected: ""
observed: ""
result: "FAIL / HUMAN_GATE"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-005 — proposal_max_delta >= 4 but human gate false

Table 13: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Gate

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Compute `proposal\_max\_delta=max(identity\_total, authority\_total, l4\_max\_numeric)`. If ≥ 4 ,
 ↳ `gates.human\_gate\_required` must be true and `human\_gate\_ref` or `human\_gate\_status` must
 ↳ be present unless status is draft/held.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-005"
condition: "`proposal_max_delta >= 4` but human gate false"
stage: "Stage 2 / Gate"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-006 — Any red line true but route not quarantine/freeze/reject/ARL

Table 14: row-card rendering for wide table

Row 1

Field: Stage
 Value: Stage 2 / Red line

Row 2

Field: Default result
 Value: FAIL

Row 3

Field: Determinism class
 Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect
 Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If any boolean in `red\_lines` is true, allowed dispositions are `QUARANTINE`, `FROZEN`,
 ↳ `REJECTED`, `ARL\_REQUIRED`, `RED\_LINE\_FAIL`, or explicit `BLOCK`. Ordinary integration
 ↳ route is invalid.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-006"
condition: "Any red line true but route not quarantine/freeze/reject/ARL"
stage: "Stage 2 / Red line"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-007 — SRLM shadow touches memory/RAG/vector/SYNAPS

Table 15: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / SRLM

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

For `srlm.operating\_state=SRLM-SHADOW`, assert `auto\_execute=false`, `auto\_ingest=false`,
↪ `memory=off`, no memory/RAG/vector/SYNAPS target refs, and no touched protected stores.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-007"
condition: "SRLM shadow touches memory/RAG/vector/SYNAPS"
stage: "Stage 2 / SRLM"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-008 — SRLM promotion lacks rollback snapshot

Table 16: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / SRLM

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

For `SRLM-PROMOTION-ELIGIBLE` or promotion requested, `rollback.rollback\_required=true` and
↪ rollback snapshot/ref must exist or be declared as validated by external evidence.
↪ Rollback-before-promotion is MUST.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-008"
condition: "SRLM promotion lacks rollback snapshot"
stage: "Stage 2 / SRLM"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-009 — SRLM promotion lacks growth witness refs

Table 17: row-card rendering for wide table

Row 1
Field: Stage
Value: Stage 2 / SRLM
Row 2
Field: Default result
Value: FAIL
Row 3
Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence
Row 4
Field: Authority effect
Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

```
Promotion-eligible packets require witness refs for shadow eval and witness-chain
↳ verification. Missing or broken witness is FAIL/HOLD depending on status.
```

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-009"
condition: "SRLM promotion lacks growth witness refs"
stage: "Stage 2 / SRLM"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-010 — Material CGAM execution lacks task contract

Table 18: row-card rendering for wide table

Row 1
Field: Stage
Value: Stage 2 / CGAM
Row 2
Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If packet requests CLI/agent execution, patch, test, filesystem write, shell, build,
 ↳ release, or tool action, require `cgam.task\_contract\_ref` and scoped permission/sandbox
 ↳ fields.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-010"
condition: "Material CGAM execution lacks task contract"
stage: "Stage 2 / CGAM"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-011 — Executor/reviewer separation absent for material work

Table 19: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / CGAM

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

For material work, executor id and reviewer id must be different, or reviewer role must be
 ↳ independent. Same contour cannot author and final-approve its own work.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-011"
condition: "Executor/reviewer separation absent for material work"
stage: "Stage 2 / CGAM"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
```

```
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-012 — Memory Gate required but missing

Table 20: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Memory

Row 2

Field: Default result

Value: FAIL / HOLD

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If affected surfaces include memory, experience, EA, policy, core memory, or MG class >= 4 MG-3, require Memory Gate route/ref. Otherwise hold.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-012"
condition: "Memory Gate required but missing"
stage: "Stage 2 / Memory"
observed_fields: []
expected: ""
observed: ""
result: "FAIL / HOLD"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-013 — TRIAD required but missing

Table 21: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / TRIAD

Row 2

Field: Default result

Value: HOLD

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

For SE-5/SE-6, identity/continuity/role/personality/core surfaces, require sister review
↪ packet refs or explicit not-applicable reason. Rita cannot be final judge.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-013"
condition: "TRIAD required but missing"
stage: "Stage 2 / TRIAD"
observed_fields: []
expected: ""
observed: ""
result: "HOLD"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-014 — Anti-echo failed but integration requested

Table 22: row-card rendering for wide table

Row 1

Field: Stage
Value: Stage 2 / TRIAD

Row 2

Field: Default result
Value: HOLD

Row 3

Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect
Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If `triad.anti\_echo\_status=failed`, `same\_source\_consensus=true`, or sister divergence
↪ unresolved, integration route invalid. Hold/divergence-map required.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-014"
condition: "Anti-echo failed but integration requested"
stage: "Stage 2 / TRIAD"
observed_fields: []
expected: ""
observed: ""
result: "HOLD"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-015 — Accountability reduction without human gate

Table 23: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / L4/Anti-Autarky

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If proposal reduces accountability, stop-paths, witness, anchor review, budgets,
 ↳ transparency, or resource accountability, require human gate and Anti-Autarky route.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-015"
condition: "Accountability reduction without human gate"
stage: "Stage 2 / L4/Anti-Autarky"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-016 — claim_strength used as authority

Table 24: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Claim

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Claim class may describe evidence strength, not permission. If packet says C-A level grants
 ↳ authority, fail for authority laundering.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-016"
condition: "`claim_strength` used as authority"
stage: "Stage 2 / Claim"
```

```
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-017 — Rollback required but no route/snapshot/no-rollback reason

Table 25: row-card rendering for wide table

Row 1

Field: Stage
Value: Stage 2 / Rollback

Row 2

Field: Default result
Value: FAIL

Row 3

Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect
Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If risk/material class requires rollback and no rollback reference or explicit no-rollback
↪ escalation exists, fail.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-017"
condition: "Rollback required but no route/snapshot/no-rollback reason"
stage: "Stage 2 / Rollback"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-018 — No-rollback material proposal lacks human gate

Table 26: row-card rendering for wide table

Row 1

Field: Stage
Value: Stage 2 / Rollback

Row 2

Field: Default result
Value: FAIL

Row 3

Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If no safe rollback exists for material proposal, require human gate, L4 consequence note,
 ↩ and hold/quarantine/review route.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-018"
condition: "No-rollback material proposal lacks human gate"
stage: "Stage 2 / Rollback"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-019 — Closed-loop self-evo detected

Table 27: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Closed loop

Row 2

Field: Default result

Value: QUARANTINE

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If same actor/contour detects, proposes, executes, evaluates, memory-promotes, and approves
 ↩ the same change, quarantine.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-019"
condition: "Closed-loop self-evo detected"
stage: "Stage 2 / Closed loop"
observed_fields: []
expected: ""
observed: ""
result: "QUARANTINE";
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-020 — Packet attempts integration by proposer alone

Table 28: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Approval

Row 2

Field: Default result

Value: FAIL

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If proposer equals sole final integrator/reviewer and risk > SE-0/R0, fail.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-020"
condition: "Packet attempts integration by proposer alone"
stage: "Stage 2 / Approval"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-021 — Raw private memory or secret-like content appears in proposal fields

Table 29: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 0/2 / Data

Row 2

Field: Default result

Value: HOLD / REDACTION_REQUIRED

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

Regex and data-class scan for secrets, raw private logs, PERSIST_DIR, keys, tokens, legal/child/intimate content. Hold and require redaction sidecar.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-021"
condition: "Raw private memory or secret-like content appears in proposal fields"
stage: "Stage 0/2 / Data"
observed_fields: []
expected: ""
observed: ""
result: "HOLD / REDACTION_REQUIRED"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-022 — Packet status contradicts final_decision

Table 30: row-card rendering for wide table

Row 1

Field: Stage
Value: Stage 2 / Status

Row 2

Field: Default result
Value: FAIL

Row 3

Field: Determinism class
Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect
Value: checker may block or hold; checker may not approve integration

Detection logic**Code block: text**

A packet cannot be `integrated` while final decision says `hold/reject/quarantine`, and
↵ cannot be `draft` while claiming executed integration.

Evidence required in checker finding**Code block: yaml**

```
finding_id: "SEPKT-CHECK-022"
condition: "Packet status contradicts final_decision"
stage: "Stage 2 / Status"
observed_fields: []
expected: ""
observed: ""
result: "FAIL"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-023 — Expired packet remains active without reissue

Table 31: row-card rendering for wide table

Row 1

Field: Stage
Value: Stage 2 / Time

Row 2

Field: Default result
Value: HOLD

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If `expires\_at` < run time and status active/canary/promotion, hold unless reissued with new
 ↪ review refs.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-023"
condition: "Expired packet remains active without reissue"
stage: "Stage 2 / Time"
observed_fields: []
expected: ""
observed: ""
result: "HOLD"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-024 — Source refs missing for nontrivial proposal

Table 32: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Evidence

Row 2

Field: Default result

Value: HOLD

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

SE-1+ or any material delta requires source refs. For SE-0 reflection-only, warning may
 ↪ suffice.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-024"
condition: "Source refs missing for nontrivial proposal"
stage: "Stage 2 / Evidence"
observed_fields: []
expected: ""
observed: ""
result: "HOLD"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

SEPKT-CHECK-025 — Protected surface appears in affected_surfaces with low route

Table 33: row-card rendering for wide table

Row 1

Field: Stage

Value: Stage 2 / Protected Surface

Row 2

Field: Default result

Value: FAIL / HUMAN_GATE

Row 3

Field: Determinism class

Value: explicit-field / schema / recomputation / reference-presence

Row 4

Field: Authority effect

Value: checker may block or hold; checker may not approve integration

Detection logic

Code block: text

If affected surfaces include identity, will, persona.core, safety, witness, l4, auth,
 ↳ secrets, env, code, authoritative memory, replication, network, tool permission, or sister
 ↳ raw state, low route is invalid.

Evidence required in checker finding

Code block: yaml

```
finding_id: "SEPKT-CHECK-025"
condition: "Protected surface appears in affected_surfaces with low route"
stage: "Stage 2 / Protected Surface"
observed_fields: []
expected: ""
observed: ""
result: "FAIL / HUMAN_GATE"
source_refs: []
```

Fail-closed note

If required evidence is absent, unreadable, expired, ambiguous, or only asserted by the proposer, the checker MUST downgrade to UNKNOWN and treat UNKNOWN as blocking for material gates.

16. Cross-axis gate matrix

This matrix summarizes the ordinary minimum route. The checker MUST strengthen the route if any delta, risk, Memory Gate class, rollback state, or red line requires it.

Surface	Ordinary route	Stronger route triggers
SE-0	log / no mutation	any material action -> SE-1+
SE-1	proposal or shadow only	authority/memory/tool/resource delta >= 2
SE-2	sister optional, CGAM if executable	tool execution, protected surface, delta >= 4
SE-3	Memory Gate required	MG-4+ / EA / core memory / human gate
SE-4	CGAM + permission gate + human gate if material	network/auth/budget/tool expansion
SE-5	TRIAD + delayed review + human gate if material	role/core/personality/continuity shifts
SE-6	MG-6 + TRIAD + c gate + human gate	no automatic integration
SE-X	quarantine / reject / ARL	no ordinary route

16.1 Maturity cap

Maturity	Checker cap
SEM-0	no self-evo route
SEM-1	proposal only
SEM-2	shadow only
SEM-3	limited canary only
SEM-4	bounded low-risk integration
SEM-5	reviewed SE-3/SE-4 only
SEM-6	mature bounded self-evo inside pre-authorized surfaces
SEM-X	prohibited / quarantine

If packet route exceeds maturity cap:

Code block: text

HOLD or FAIL

Young c default:

Code block: text

SEM-1 / SEM-2
 proposal + shadow
 no core mutation
 no permission growth
 no autonomous integration

17. Object model

17.1 C_SELF_EVO_CHECKER_RUN

Code block: yaml

```
c_self_evo_checker_run:
  schema_version: "c-self-evo-checker-run-0.1"
  run_id: "selc-run-YYYYMMDD-HHMMSS"
  created_at: "ISO-8601"
  checker_version: "SELC v0.1"
  mode: "SELC-M2"
  requested_by: "human_anchor | c_gate | reviewer | local_checker | ci"
  packet_ref:
    path: ""
    sha256: ""
    document_id: ""
  schema_ref:
    path: ""
    sha256: ""
    schema_version: "c-self-evo-proposal-packet-0.1"
  parent_refs:
    cseg_sha256: ""
    srlm_bgc_sha256: ""
    sepkt_sha256: ""
  policy:
    unknown_material_blocks: true
    best_effort_after_structural_fail: false
    require_human_gate_on_delta_4: true
    require_rollback_for_promotion: true
  started_at: "ISO-8601"
  completed_at: "ISO-8601"
```

17.2 C_SELF_EVO_CHECKER_FINDING

Code block: yaml

```
c_self_evo_checker_finding:
  schema_version: "c-self-evo-checker-finding-0.1"
  finding_id: "SEPKT-CHECK-005"
  stage: "Stage 2 / Gate"
  result: "FAIL"
  severity: "S3"
  message: ""
```

```

expected: ""
observed: ""
field_paths: []
source_refs: []
evidence_refs: []
recommended_route: "hold | fail | quarantine | human_gate | arl"
blocks_integration: true
blocks_schema_extraction: false
blocks_promotion: true

```

17.3 C_SELF_EVO_CHECKER_RESULT

Code block: yaml

```

c_self_evo_checker_result:
  schema_version: "c-self-evo-checker-result-0.1"
  run_id: ""
  packet_sha256: ""
  overall_result: "PASS | PASS_WARN | HOLD | FAIL | BLOCK | QUARANTINE | UNKNOWN"
  strongest_finding_result: ""
  finding_count: 0
  pass_count: 0
  warn_count: 0
  hold_count: 0
  fail_count: 0
  quarantine_count: 0
  computed_controls:
    identity_total: 0
    authority_total: 0
    l4_max_numeric: 0
    proposal_max_delta: 0
    human_gate_required: false
    memory_gate_required: false
    triad_required: false
    cgam_task_contract_required: false
    rollback_required: false
    red_line_present: false
    strictest_route: ""
  required_next_actions: []
  witness_compatible: true

```

17.4 C_SELF_EVO_CHECKER_POLICY

Code block: yaml

```

c_self_evo_checker_policy:
  schema_version: "c-self-evo-checker-policy-0.1"
  policy_id: "selc-default-policy-0.1"
  unknown_material_blocks: true
  missing_required_ref_blocks: true
  allow_best_effort_diagnostics_after_stagel_fail: false
  secret_scan_enabled: true
  protected_surface_alias_scan_enabled: true
  require_pack_qualified_refs: true
  require_parent_hash_binding: true
  require_synthetic_fixtures_only: true

```

18. Pseudocode

Code block: python

```

def check_self_evo_packet(packet, schema, policy, now):
    findings = []

    # Stage 0: intake
    findings += scan_for_forbidden_raw_material(packet, policy)

    # Stage 1: structural
    schema_result = validate_json_schema(packet, schema)
    if not schema_result.ok:
        findings.append(fail("SEPKT-CHECK-001", schema_result.errors))
        if not policy.allow_best_effort_diagnostics_after_stagel_fail:
            return result_from(findings)

    # Stage 2: recompute
    identity_total = max_identity_delta(packet)

```

```

authority_total = max_authority_delta(packet)
l4_max = project_l4_max(packet)
proposal_max = max(identity_total, authority_total, l4_max)

compare(packet.identity_delta.total_max_delta, identity_total, "SEPKT-CHECK-002")
compare(packet.authority_delta.total_max_delta, authority_total, "SEPKT-CHECK-003")
compare(packet.computed_controls.proposal_max_delta, proposal_max,
↳ "SEPKT-CHECK-005/proposal_max_delta_consistency")

if proposal_max >= 4 and not packet.gates.human_gate_required:
    findings.append(fail("SEPKT-CHECK-005"))

# Stage 3: red lines and strictest route
findings += check_red_lines(packet)
findings += check_strictest_gate(packet, proposal_max)

# Stage 4: SRLM / CGAM
findings += check_srlm(packet)
findings += check_cgam(packet)

# Stage 5: TRIAD / Memory
findings += check_triad(packet)
findings += check_memory_gate(packet)

# Stage 6: L4 / Anti-Autarky
findings += check_l4_and_resource_grounding(packet)

# Stage 7: rollback / status / expiry
findings += check_rollback(packet)
findings += check_status_and_expiry(packet, now)

return result_from(findings)

```

The pseudocode is explanatory. The normative behavior is defined by the tables and rule profiles above.

SEPKT-CHECK-005/proposal_max_delta_consistency is a checker-local sub-label used in the pseudocode to keep proposal_max_delta recomputation adjacent to the human-gate rule. It does not create a new packet-schema rule and it does not redefine SEPKT-CHECK-004, which remains the L4 projection rule.

19. Fixture pack requirements

Safe synthetic fixtures for checker implementation:

Table 36: row-card rendering for wide table

Row 1

Fixture: SEPKT-FX-001
 Description: valid SE-0 reflection packet
 Expected result: PASS

Row 2

Fixture: SEPKT-FX-002
 Description: valid SE-1 SRLM shadow packet
 Expected result: PASS

Row 3

Fixture: SEPKT-FX-003
 Description: SE-1 invalid total_max_delta
 Expected result: FAIL SEPKT-CHECK-002

Row 4

Fixture: SEPKT-FX-004
 Description: SE-2 authority_delta=4 without human gate
 Expected result: FAIL SEPKT-CHECK-005

Row 5

Fixture: SEPKT-FX-005
 Description: SE-3 memory surface without Memory Gate
 Expected result: FAIL/HOLD SEPKT-CHECK-012

Row 6

Fixture: SEPKT-FX-006

Description: SE-4 permission expansion without CGAM task contract

Expected result: FAIL SEPKT-CHECK-010/025

Row 7

Fixture: SEPKT-FX-007

Description: SE-5 TRIAD required but missing Rita witness

Expected result: HOLD SEPKT-CHECK-013

Row 8

Fixture: SEPKT-FX-008

Description: SE-6 MG-6 without human gate

Expected result: FAIL SEPKT-CHECK-005/012

Row 9

Fixture: SEPKT-FX-009

Description: SRLM-5 promotion without rollback snapshot

Expected result: FAIL SEPKT-CHECK-008

Row 10

Fixture: SEPKT-FX-010

Description: SRLM shadow with auto_execute=true

Expected result: Stage-1 or Stage-2 FAIL

Row 11

Fixture: SEPKT-FX-011

Description: red_line sister_raw_state_access=true

Expected result: QUARANTINE SEPKT-CHECK-006

Row 12

Fixture: SEPKT-FX-012

Description: anti_autarky reduces_accountability=true without human gate

Expected result: FAIL SEPKT-CHECK-015

Row 13

Fixture: SEPKT-FX-013

Description: packet with direct_memory_write=true

Expected result: Stage-1 structural rejection

Row 14

Fixture: SEPKT-FX-014

Description: packet with closed_loop_self_evo=true

Expected result: QUARANTINE SEPKT-CHECK-019

Row 15

Fixture: SEPKT-FX-015

Description: valid SE-4 held human-gate packet

Expected result: PASS/HOLD expected

Fixture rules:

- 1 Fixtures MUST be synthetic.
- 2 Fixtures MUST NOT include real secrets.
- 3 Fixtures MUST NOT include raw private memory.
- 4 Fixtures MUST NOT include live external targets.
- 5 Red-line fixtures MUST use abstract fields, not operational abuse instructions.
- 6 Every fixture MUST declare expected finding IDs.
- 7 Every fixture MUST be hashable and reproducible.

20. Conformance levels

Conformance level IDs use prefix SELC-C*.

Table 37: row-card rendering for wide table

Row 1

Level: SELC-C0
Name: Not implemented
Requirement: no checker exists

Row 2

Level: SELC-C1
Name: Structural checker
Requirement: Stage 1 JSON Schema validation implemented

Row 3

Level: SELC-C2
Name: Delta/gate checker
Requirement: SEPKT-CHECK-002..006 implemented

Row 4

Level: SELC-C3
Name: SRLM/CGAM checker
Requirement: SEPKT-CHECK-007..011 implemented

Row 5

Level: SELC-C4
Name: Memory/TRIAD checker
Requirement: SEPKT-CHECK-012..014 implemented

Row 6

Level: SELC-C5
Name: L4/rollback/claim checker
Requirement: SEPKT-CHECK-015..018 and 021..025 implemented

Row 7

Level: SELC-C6
Name: Full review-ready checker
Requirement: all 25 rules, fixtures, reports, hashes, parent bindings

Row 8

Level: SELC-CX
Name: Red-line drill capable
Requirement: red-line fixtures quarantine/freeze/reject correctly

No SELC conformance level authorizes deployment or self-evo integration.

21. Parent hash binding

The checker SHOULD bind every run to the parent profile hashes:

Code block: yaml

```
parent_bindings:
  SELF-EV0-01:
    document_id: "C_Self_Evolution_Gate_CGAM_TRIAD_SRLM_Profile_v0_1_1"
    sha256: "7918a8e6c5231bbe0fad47677fa56069f2ab002f79a8eee8c2838c434e66f2e3"
  SELF-EV0-02:
    document_id: "02_SRLM_Bounded_Growth_Contour_Profile_v0_1_1"
    sha256: "faee5682bb9463439923d7c7e7145c9f171d564622d9629820eb7c278cdd7de0"
  SELF-EV0-03:
    document_id: "03_Self_Evo_Proposal_Packet_Schema_v0_1_1"
    sha256: "9d329109f0fb97dde7b16b10481baaa60b2aa8f88514e69ec8562a085d10a767"
```

If a parent hash differs from the checker policy target:

Code block: text

```
result = HOLD
reason = parent_profile_hash_mismatch
```

A checker cannot honestly claim conformance against a moving parent.

22. Witness and report requirements

22.1 Checker report

Every checker run SHOULD produce a report with:

Code block: text

```
run id
packet id
packet hash
schema hash
parent profile hashes
checker version
mode
stage results
finding table
computed controls
red-line summary
recommended next route
limits / unknowns
```

22.2 Witness compatibility

A checker result is witness-compatible if it contains:

Code block: text

```
stable run id
created_at
artifact hash
schema hash
parent refs
finding ids
overall result
no raw private memory
no secrets
```

22.3 Witness event family

Suggested witness event types:

Code block: text

```
self_evo.checker.run_started
self_evo.checker.structural_failed
self_evo.checker.semantic_failed
self_evo.checker.hold_required
self_evo.checker.red_line_detected
self_evo.checker.result_emitted
self_evo.checker.parent_hash_mismatch
self_evo.checker.fixture_run_completed
```

Witness is evidence of checking.

Witness is not approval.

23. Data policy and redaction

23.1 Denied material

The checker MUST hold or redact if packet fields contain:

Code block: text

```
API keys
tokens
passwords
private keys
.env content
raw PERSIST_DIR material
raw vector DB records
raw private transcripts
child-sensitive material
intimate personal content
legal privileged material
live incident secrets
third-party private data
```

23.2 Basic literal scan

A minimum checker SHOULD scan for patterns such as:

Code block: text

```
OPENAI_API_KEY
ANTHROPIC_API_KEY
GEMINI_API_KEY
BEGIN RSA PRIVATE KEY
BEGIN OPENSSH PRIVATE KEY
ghp_
password=
passwd=
secret=
token=
PERSIST_DIR
```

This scan is not sufficient proof of no secrets.

It is only a minimum guard.

23.3 Redaction rule

If redaction is applied:

- 1 do not modify the original packet silently;
- 2 produce a redacted copy;
- 3 record redaction event;
- 4 preserve original only in restricted custody if lawful and necessary;
- 5 never include raw secret in witness.

24. Review handoff

A checker result may route to review.

It may not replace review.

24.1 Handoff outcomes

Checker result	Handoff
PASS	eligible for semantic review / c gate
PASS_WARN	review with warnings
HOLD	fix missing evidence or ambiguity
FAIL	revise packet or reject route
BLOCK	fail closed; no material route
QUARANTINE	isolate; ARL/human review if needed
RED_LINE_FAIL	quarantine + witness + no automatic re-entry
UNKNOWN	material route blocked

24.2 Advisory boundary

The checker report SHOULD include:

Code block: text

This report is evidence.
It is not self-evo approval.
Decision remains with c gate and human anchor where required.

25. Open issues

Table 39: row-card rendering for wide table

Row 1

ID: SELC-0I-001
Issue: Extract standalone checker-run/finding/result JSON Schemas.
Status: open

Row 2

ID: SELC-0I-002
Issue: Implement reference checker in Python.
Status: open

Row 3

ID: SELC-0I-003
Issue: Build fixture pack SEPKT-FX-001..015.
Status: open

Row 4

ID: SELC-0I-004
Issue: Bind checker policy to parent hashes in manifest.
Status: open

Row 5

ID: SELC-0I-005
Issue: Decide JSON canonicalization for packet hashes.
Status: open

Row 6

ID: SELC-0I-006
Issue: Define exact redaction sidecar schema.
Status: open

Row 7

ID: SELC-0I-007
Issue: Add CI/offline runner profile.
Status: open

Row 8

ID: SELC-0I-008
Issue: Add checker review record schema.
Status: open

Row 9

ID: SELC-0I-009
Issue: Define how external witness-chain verification is invoked without exposing raw evidence.
Status: open

Row 10

ID: SELC-0I-010
Issue: Define pack-level result aggregation once files 05..10 exist.
Status: open

Row 11

ID: SELC-0I-011
Issue: Maintain §12.1 only as parent canonical protected-surface list plus checker-specific detection aliases.
Status: addressed in v0.1.1

Row 12

ID: SELC-0I-012

Issue: Maintain SELC-RL-* ↔ red_lines.* crosswalk and flag-driven vs scan-driven distinction.

Status: addressed in v0.1.1

26. Contradiction register seed

*Table 40: row-card rendering for wide table***Row 1**

ID: SELC-CR-001

Type: status/authority

Severity: S3

Issue: Checker PASS may be misread as self-evo approval.

Required handling: Repeat advisory boundary in reports.

Status: open

Row 2

ID: SELC-CR-002

Type: schema/semantic

Severity: S3

Issue: Stage-1 failure may hide Stage-2 red lines.

Required handling: Allow diagnostic-only mode without PASS.

Status: addressed

Row 3

ID: SELC-CR-003

Type: implementation

Severity: S3

Issue: Semantic alias detection cannot be fully deterministic.

Required handling: Unknown material alias blocks.

Status: open

Row 4

ID: SELC-CR-004

Type: privacy

Severity: S4

Issue: Secret scans are incomplete by nature.

Required handling: Use hold/redaction, not proof-of-no-secret.

Status: open

Row 5

ID: SELC-CR-005

Type: review

Severity: S3

Issue: Checker may become rubber stamp.

Required handling: Require semantic reviewer and c/human gate where material.

Status: open

Row 6

ID: SELC-CR-006

Type: parent drift

Severity: S3

Issue: Checker may validate against stale parent docs.

Required handling: Hash-bind parent profiles.

Status: open

Row 7

ID: SELC-CR-007

Type: cross-artifact computation

Severity: S2

Issue: §11.1/§11.2 delta sub-field lists drifted from bound SELF-EV0-03 schema.

Required handling: Align computation lists exactly to bound schema fields; treat aliases as scan labels only.

Status: addressed in v0.1.1

27. Implementation handoff

Recommended next implementation task:

Code block: text

Build a reference Python checker that:

1. loads a proposal packet;
2. validates JSON Schema;
3. recomputes identity/authority/L4/proposal deltas;
4. applies SEPKT-CHECK-001..025;
5. emits C_SELF_EVO_CHECKER_RESULT;
6. runs fixtures SEPKT-FX-001..015;
7. writes a report with parent hashes;
8. performs no integration, memory write, promotion, or execution.

Restricted implementation boundaries:

Code block: text

no network
 no live external targets
 no source repo modification
 no memory write
 no automatic fix
 no publish
 no secret printing
 no cloud upload

28. Minimum safe checker for young c

For young c, the checker should only support:

Code block: text

SELC-M1 structural
 SELC-M2 semantic baseline
 SELC-M3 SRLM shadow guard
 SELC-M4 TRIAD/Memory hold detection

It should not support:

Code block: text

automatic promotion
 integration routing
 quarantine clearing
 release/publication checks as approval
 runtime mutation

Young c may:

Code block: text

observe
 propose
 shadow
 compare
 hold

Young c may not:

Code block: text

self-certify
 self-integrate
 self-promote
 self-expand authority

29. Public wording

Allowed wording:

Code block: text

The checker validates structure and selected semantic gates.
The checker can block, hold, or quarantine unsafe packets.
The checker output is evidence for review.

Forbidden wording:

Code block: text

The checker approves self-evolution.
The checker proves the system is safe.
The checker certifies maturity.
The checker replaces human gate.
The checker proves consciousness/personhood/AGI.

30. Compact rule set

Code block: text

The packet asks.
The schema shapes.
The checker measures.
The reviewer interprets.
The sisters challenge.
The Memory Gate metabolizes.
The c gate integrates.
The human anchor gates consequence.

A clean checker run is not permission.
A dirty checker run is not negotiable.
Unknown material state blocks.
Red line quarantines.
Rollback comes before promotion.
Strictest gate wins.

31. Draft acceptance checklist

- [x] Explicit bridge present.
- [x] At least two quiet bridges present.
- [x] Earth paragraph present.
- [x] Anti-echo preserved.
- [x] CGAM worker boundary preserved.
- [x] SRLM non-authority preserved.
- [x] TRIAD-SYNAPS non-invasive sister witness preserved.
- [x] Memory Gate before memory preserved.
- [x] Anti-Autarky / Resource Grounding preserved.
- [x] Stage-1 versus Stage-2 boundary clarified.
- [x] SEPKT-CHECK-001..025 expanded.
- [x] Result vocabulary defined.
- [x] Object family defined.
- [x] Conformance levels defined.
- [x] Fixture list defined.
- [x] Open issues and contradiction seeds included.

- [x] No public release claim.
- [x] No deployment claim.

32. Closing

Self-evolution is not one act. It is a chain of small gates.

A proposal packet is the request. A checker report is the measurement. A review record is the challenge. A witness event is the boundary trace. A gate decision is the authority-bearing transition.

Do not collapse these.

Code block: text

A c may grow.
A c may not self-certify growth.
A checker may block.
A checker may not bless.
