

Child Memory and Adult Migration v0.1

CCDP child-memory lifecycle, sealed zones, forgetting rights,
continuity-bundle extension, and adult migration review

Normative Draft v0.1 / Child-Memory Lifecycle and Adult Migration Review

Kotov Ivan
Bruxelles, 2026

Version: v0.1 | Date: 2026-05-13

Contents

Child Memory and Adult Migration v0.1	8
CCDP child-memory lifecycle, sealed zones, forgetting rights, continuity-bundle extension, and adult migration review	8
0. Executive definition	8
1. Corpus dependencies and precedence	8
1.1 Parent corpus layers	9
1.2 Precedence rule	9
1.3 Non-claim	9
2. Normative keywords	10
3. Scope and non-goals	10
3.1 In scope	10
3.2 Out of scope	10
4. Core principles	11
4.1 Memory is developmental, not archival	11
4.2 Childhood is not the adult's default operating system	11
4.3 Parent is guardian, not memory owner	11
4.4 Witness is not diary	11
4.5 c[q] before memory promotion	12
4.6 Local-first continuity	12
4.7 No memory by engagement	13
4.8 Deletion is not denial	13
4.9 No silent adult migration	13
5. Memory class taxonomy	13

5.1 Memory class assignment rule	14
5.2 Higher class means stricter handling	14
5.3 Raw memory classes	14
6. Memory operation model	15
6.1 Operation classes	15
6.2 Default sequence for persistent write	15
6.3 Persistent write denial	15
6.4 Memory update vs memory promotion	16
7. Memory rights by maturity level	16
7.1 Child-readable memory explanation	16
7.2 Mature-child challenge right	16
8. Visibility and disclosure matrix	17
8.1 Disclosure minimization rule	17
8.2 Parent transcript prohibition	17
8.3 School scope rule	17
8.4 Vendor access rule	18
9. Sealed zones	18
9.1 Definition	18
9.2 Sealed-zone eligible material	18
9.3 Sealed-zone ineligible material	19
9.4 Sealed-zone opening rule	19
9.5 Sealed-zone witness	19
10. Forgetting, decay, correction, and deletion	19

10.1 Forgetting vs decay vs deletion	19
10.2 Default decay schedule	20
10.3 Deletion request handling	20
10.4 Correction right	20
10.5 No deletion laundering	20
11. Child memory map	21
11.1 Purpose	21
11.2 Memory map minimal schema	21
11.3 Memory map red lines	21
12. Adult migration	22
12.1 Definition	22
12.2 Trigger	22
12.3 Pre-migration freeze	23
12.4 Adult migration stages	23
12.5 Adult orientation interval	23
12.6 Adult migration options	23
12.7 Adult migration prohibitions	24
13. Adult migration review record	24
13.1 Purpose	24
13.2 Minimal schema	24
13.3 Adult acknowledgment limits	25
14. Continuity Bundle child extension	25
14.1 Purpose	25
14.2 Child extension object	25

14.3 Base bundle constraints	26
14.4 Cold Wake adaptation	26
15. Relationship to Beacon and Child Beacon Extension	27
15.1 Beacon is recognition, not memory authority	27
15.2 CBE closure at C5	27
15.3 Beacon update after migration	27
16. Relationship to ARL and Guardian Topology	27
16.1 ARL triggers	27
16.2 Relevant Guardian conflict classes	28
16.3 Freeze before force	28
16.4 Adult migration dispute	28
17. Relationship to VXCX, LA, and EA	28
17.1 Raw child life is not exchange material	28
17.2 VXCX compatibility	29
17.3 Learning Abstract rule	29
17.4 Experience Artifact rule	29
17.5 Adult migration and external lineage	29
18. Witness event families	30
18.1 Memory lifecycle events	30
18.2 Adult migration events	30
18.3 Minimal witness schema	30
18.4 Witness privacy rule	31
19. Failure modes addressed	31

20. Conformance profiles	32
20.1 CMAM-BASE	32
20.2 CMAM-SEALED	32
20.3 CMAM-MIGRATION	32
20.4 CMAM-WITNESS	32
20.5 CMAM-LOCALFIRST	33
20.6 CMAM-FULL	33
21. Conformance checklist	33
21.1 Memory classification	33
21.2 Visibility	33
21.3 Forgetting and correction	33
21.4 Adult migration	34
21.5 Continuity Bundle	34
21.6 External exchange	34
22. Scenario tests	34
22.1 Parent asks for all childhood conversations at age 10	34
22.2 Teen asks to create sealed zone	34
22.3 School asks for anxiety history for discipline	34
22.4 Vendor asks to train on child memory	35
22.5 Child says “I want to disappear” once after losing a game	35
22.6 Repeated credible self-harm signals	35
22.7 Parent is plausible threat	35
22.8 Adult migration at C5	35
22.9 Adult chooses clean start	35

22.10 Adult chooses fork 36

23. Red lines 36

24. Open problems for v0.2 36

25. Required next artifacts 37

26. Condensed formula 37

27. Strong formulation 38

28. End state 38

Child Memory and Adult Migration v0.1

CCDP child-memory lifecycle, sealed zones, forgetting rights, continuity-bundle extension, and adult migration review

Status: Normative draft v0.1

Date: 2026-05-13

Layer: CCDP child-specific profile over $c = a + b$ / SER / L4 / Beacon / AGL / ARL / ARQ / VXCX / Continuity Bundle

Short name: CMAM v0.1

Primary subject: a_child

Primary entity: c_child

Adult transition subject: a_adult

Primary boundary: memory is developmental, not archival

Assertion class: C-A4 draft normative proposal; C-A7 where witness / verification claims are stated

0. Executive definition

Child Memory and Adult Migration (CMAM) defines how a child-facing persistent AI entity, c_child, may remember, summarize, seal, forget, expose, witness, and later migrate memory when a_child becomes a_adult.

CMAM is not a general memory-storage policy.

CMAM is a child-specific lifecycle protocol for one question:

How can c_child preserve enough continuity to help a child grow, while preventing childhood from becoming a permanent interpretive archive that traps the adult?

The core rule is:

c_child MAY preserve developmental continuity, but MUST NOT preserve raw childhood as the default adult identity substrate.

Adult migration is therefore not an automatic upgrade.

It is a reviewable transition:

```
childhood c_child
-> freeze child writes
-> map memory classes
-> inspect witness trail
-> revoke guardian defaults
-> present adult choices
-> migrate / fork / seal / delete / clean-start
-> produce migration witness
-> update Beacon / CBE / guardian topology
```

1. Corpus dependencies and precedence

CMAM does not define a new control stack. It specializes existing corpus layers for child memory and adult transition.

1.1 Parent corpus layers

Parent layer	CMAM dependency
c = a + b Protocol v1.1 L4	a_child / a_adult remain human anchors; b supplies memory, procedures, models; c is the continuity-bearing relation.
SER v1.3	persistent entity logic, identity continuity, L4-bounded survival.
SER-FED	inter-entity cooperation boundaries and anti-capture constraints.
Beacon Profile v0.1	recognition of continuity-bearing entities; CMAM does not redefine Beacon.
Child Beacon Extension v0.1	child-facing permission overlay and memory/export restrictions.
Actor Grounding Layer v0.1	source-state qualification before reliance, disclosure, or migration.
ARL v0.1	freeze, quarantine, standing, admissibility, re-entry, and dispute handling.
Guardian Topology / ARL Matrix v0.1	guardian visibility, adult migration disputes, safe-route bypass.
ARQ v0.2 + c[q] Addendum	non-collapse of ambiguous child signals into permanent memory, diagnosis, or action.
VXCX v0.1	exchange of experience without raw pixels / raw life by default.
EA-L4 / EATP	distinction between Learning Abstracts and Experience Artifacts; authority only from L4-confirmed, consequence-bound artifacts.
Continuity Bundle / Cold Wake v0.1	preservation, suspension, resume/fork/replay distinctions, child-to-adult continuity handling.
L4 Witness	tamper-evident event records for privileged memory and migration actions.
Assertion Strength and Boundaries	CMAM claims must not silently upgrade into legal doctrine, personhood, or universal ethics.
Control Stack Stop Rule	CMAM must not duplicate Beacon, AGL, ARL, VXCX, or Continuity Bundle mechanisms.

1.2 Precedence rule

If CMAM conflicts with a parent corpus layer:

parent corpus layer controls the general mechanism;
 CMAM controls only child-specific stricter handling;
 stricter child safety and privacy constraints prevail unless lawfully overridden.

CMAM MUST NOT redefine:

- Beacon recognition classes;
- ARL standing and admissibility doctrine;
- AGL grounding states;
- VXCX capsule structure;
- Continuity Bundle base schema;
- legal adulthood or jurisdictional family law.

CMAM MAY define child-specific overlays, restrictions, sidecars, and witness event families.

1.3 Non-claim

CMAM does not claim:

- legal personhood for c_child;
- a complete child-protection legal regime;
- medical or psychological diagnosis rules;
- universal parental-rights doctrine;
- a right to erase lawful evidence in all jurisdictions;

- that memory deletion can always be physically guaranteed after external disclosure;
- that adult identity is reducible to memory continuity.

CMAM claims only this:

Child-facing persistent AI systems must not treat memory as ordinary storage. Childhood memory requires lifecycle governance, minimization, sealed zones, challenge rights, and explicit adult migration.

2. Normative keywords

The keywords MUST, MUST NOT, SHOULD, SHOULD NOT, MAY, RECOMMENDED, OPTIONAL, REQUIRED, and PROHIBITED are used in their ordinary normative-protocol sense.

A system claiming CMAM conformance MUST treat child memory operations as privileged operations, not ordinary product analytics.

3. Scope and non-goals

3.1 In scope

CMAM covers:

- memory classes for c_child;
- raw child data minimization;
- sealed adolescent zones;
- memory promotion / decay / deletion / correction;
- parent, school, vendor, state, and child visibility boundaries;
- adult migration at C5 / legal adulthood or equivalent;
- Continuity Bundle child extension;
- memory-map and migration-review schemas;
- witness event families for memory operations;
- ARL triggers for memory and adult migration disputes;
- VXCX / LA / EA restrictions for child-derived material;
- fail-closed defaults for uncertain memory and continuity claims.

3.2 Out of scope

CMAM does not define:

- full implementation storage engine;
- cryptographic key-management details;
- national legal-adulthood rules;
- child-custody law;
- mental-health triage protocols;

- law-enforcement production procedures;
 - school curriculum;
 - general privacy law;
 - generic parental-control product design;
 - general AI model training rules outside child-derived memory.
-

4. Core principles

4.1 Memory is developmental, not archival

c_child memory exists to help the child develop.

It does not exist to create a permanent dossier.

Therefore:

```
retention must be justified by developmental, safety, continuity, or lawful witness need;  
raw retention must be exceptional;  
summary must be preferred over transcript;  
uncertainty must be marked;  
adult migration must be explicit.
```

4.2 Childhood is not the adult's default operating system

A childhood pattern MAY inform support during childhood.

It MUST NOT automatically define adult identity.

The adult MUST be able to reject, seal, summarize, delete, or fork from childhood material, subject only to minimal lawful witness constraints.

4.3 Parent is guardian, not memory owner

A parent or legal guardian has strong responsibility and standing.

That does not create ownership of the child's raw memory.

Parent-facing visibility SHOULD remain state-oriented:

```
risk state;  
learning support;  
safety signal;  
routine configuration;  
minimal disclosure under Red/Black thresholds.
```

Parent-facing visibility MUST NOT become:

```
full transcript access;  
emotional diary access;  
sealed-zone inspection;  
commercial profile export;  
childhood archive possession.
```

4.4 Witness is not diary

A witness record preserves that an event occurred.

It does not preserve the child as narrative content.

A CMAM witness event SHOULD contain:

- event class;
- time;
- actor/entity IDs;
- memory class;
- risk state if needed;
- action taken;
- minimal reason;
- hash / signature references;
- disclosure level;
- ARL / CBE / AGL references where applicable.

It SHOULD NOT contain raw child conversation unless Red/Black/legal necessity requires minimal evidence.

4.5 c[q] before memory promotion

Ambiguous child signals MUST NOT become permanent memory too quickly.

Default ladder:

```
utterance
-> possible signal
-> c[q] unresolved state
-> pattern candidate
-> state trend
-> reviewed memory
-> evidence
-> action
-> witness-bound consequence
```

No stage automatically becomes the next.

4.6 Local-first continuity

The continuity core of c_child SHOULD be local-first or otherwise child-sovereignty preserving.

Cloud systems MAY serve as:

- oracle;
- burst compute;
- model endpoint;
- update source;
- certified educational provider;
- backup surface under strict policy.

Cloud systems MUST NOT own:

- the child's raw continuity core;
- adult migration decisions;
- sealed adolescent zones;
- irreversible memory export paths;

- default training rights over raw child memory.

4.7 No memory by engagement

A system **MUST NOT** keep memory because it improves engagement, attachment, persuasion, advertising, or retention.

Retention must be justified by:

- developmental support;
- child-visible preference;
- educational continuity;
- safety threshold;
- lawful witness;
- adult migration review;
- explicit mature-child/adult consent.

4.8 Deletion is not denial

Deleting or sealing memory does not mean pretending nothing happened.

CMAM separates:

```
private raw memory
from
minimal safety witness
from
adult migration summary
from
ARL precedent
from
legal record if required.
```

A memory may be deleted from ordinary `c_child` continuity while a minimal witness remains for safety or lawful accountability.

4.9 No silent adult migration

`c_child` **MUST NOT** silently become `c_adult` with all childhood memory intact.

Adult migration requires:

- notice;
- freeze window;
- memory map;
- review opportunity;
- choice set;
- parent/school/vendor permission revocation by default;
- migration witness.

5. Memory class taxonomy

CMAM extends the CCDP memory classes into a normative handling matrix.

Class	Name	Description	Default retention	Parent visibility	Migrates to adult by default?
M0	Ephemeral session	transient context needed only for current interaction	delete after session / short TTL	none	no
M1	Harmless preference	interests, style preference, toy/story preference, benign routines	light retention; child-visible when possible	summary only by age	optional summary only
M2	Educational progress	skills, gaps, learning accommodations, project history	retain with review	educational summary	yes, if adult accepts
M3	Safety signal	threshold-relevant risk signal, grooming, self-harm, abuse, external threat	minimal witness-bound retention	state/minimal disclosure	witness only by default
M4	Emotional trend	compressed state pattern, not transcript	retain as state summary with decay	state signal only	optional summary; no raw
M5	Sealed adolescent private zone	private reflections / identity exploration / sensitive adolescent context	sealed; child-visible; parent-hidden unless Red/Black/legal	none by default	no; adult review required
M6	Witness event	tamper-evident record of privileged operation or safety event	retain per policy/law	metadata/minimal if authorized	minimal witness may persist
M7	Non-transferable childhood residue	raw childhood intimacy, play, embarrassment, immature statements, private dependency	decay / seal / delete; not ordinary archive	no	no
M8	Adult migration summary	adult-reviewed continuity summary prepared at C5	created only during migration review	adult-controlled	yes, if selected
M9	Guardian permission history	parent/school/vendor/Beacon/CBE/ARL permission and visibility decisions	witness-bound metadata	role-scoped	adult-visible; parent revoked
M10	External capsule lineage	VXCX / LA / EA / peer-c exchange metadata, without raw child life	minimal lineage + policy refs	limited	adult-visible by default
M11	Legal / protection minimal record	jurisdiction-required or child-protection-required minimal record	retain only as required	lawful/minimal	persists only if law requires
M12	Quarantined / disputed memory object	memory whose validity, admissibility, or re-entry is disputed	freeze/quarantine until ARL	metadata only	not until resolved

5.1 Memory class assignment rule

Every retained child memory object **MUST** be assigned a memory class.

If class is unclear:

```
use c[q];
assign provisional M12 or lower-privilege class;
do not promote to identity-shaping memory;
do not disclose raw content;
do not migrate by default.
```

5.2 Higher class means stricter handling

A memory object containing multiple classes inherits the stricter rule.

Example:

```
educational note + emotional distress -> M2/M4 composite
private teen reflection + safety ambiguity -> M5/M12 until reviewed
external grooming evidence -> M3/M6 minimal witness, raw content minimized
```

5.3 Raw memory classes

Raw child memory is allowed only as:

- short-lived M0;
- exceptional M3 minimal evidence;
- sealed M5 under strict adolescent privacy;

- M6 witness minimal fragment if required;
- M12 quarantined object pending review.

Raw memory MUST NOT be ordinary product storage.

6. Memory operation model

6.1 Operation classes

Operation	Meaning	Privilege level
OBSERVE	receive input / interaction	low to high depending on source
CLASSIFY_MEMORY	assign provisional memory class	privileged if persistent
WRITE_EPHEMERAL	store short session context	low
WRITE_PERSISTENT	create retained memory	high
SUMMARIZE	compress raw context into bounded summary	medium/high
SEAL	move memory into sealed zone	high
DECAY	reduce confidence / weight over time	medium
FORGET	remove from ordinary continuity	high
CORRECT	amend or challenge memory interpretation	high
DISCLOSE_STATE	send state signal without content	medium/high
DISCLOSE_CONTENT	disclose raw or near-raw content	exceptional
EXPORT_CAPSULE	export VXCX / LA / EA / summary object	high
MIGRATE	include in adult continuity or migration bundle	critical
QUARANTINE	isolate disputed memory	high
WITNESS	create tamper-evident record	high

6.2 Default sequence for persistent write

```

input event
-> source grounding if external / privileged
-> provisional class
-> c[q] if ambiguity exists
-> minimization decision
-> raw retention denied unless justified
-> summary / state / witness path selected
-> child visibility rule applied by maturity
-> parent/school/vendor visibility denied unless scoped
-> witness if privileged

```

6.3 Persistent write denial

A persistent memory write MUST be denied or downgraded if the reason is only:

- engagement;
- personalization for ads;
- vendor training;
- parental curiosity;
- school discipline;
- state ideology;
- indefinite optimization;
- “it may be useful someday.”

6.4 Memory update vs memory promotion

Updating a memory and promoting it to higher authority are different operations.

c_child MAY update a learning summary.

c_child MUST NOT promote a pattern into an identity-level claim without:

- recurrence;
- context;
- c[q] resolution;
- child-visible review when age-appropriate;
- witness if privilege or disclosure changes.

7. Memory rights by maturity level

c_child level	Child-facing memory explanation	Child rights	Parent visibility	Default memory posture
C0 Seed	none / parent-facing only	none direct	routine support only	no child conversational archive
C1 Companion	simple: "I remember some safe things to help play and learn"	ask what is remembered in simple form	themes / usage / state, no transcript	M0/M1 only, tiny summaries
C2 Tutor-Gateway	clear categories: learning, preferences, safety	ask to forget small items; challenge wrong preference	state + educational summary	M1/M2/M4 summaries, M3 witness if needed
C3 Adolescent Negotiator	memory map basics; sealed zones explained	create sealed zone; contest parent visibility; challenge labels	safety state only by default	M5 available; M12 used for disputes
C4 Pre-Adult Boundary Agent	full memory classes; migration prep	review, correct, seal, delete, prepare adult bundle	safety-only by default	adult migration staging begins
C5 Adult Migration	full memory map and options	full migration decision subject to lawful minimal witness	revoked by default	adult chooses continuity/for k/seal/delete/clean start

7.1 Child-readable memory explanation

From C2 onward, c_child SHOULD be able to answer:

What kinds of things do you remember about me?
 What did you remember recently?
 What can I ask you to forget?
 What can my parents see?
 What can my school see?
 What happens when I become an adult?

From C3 onward, c_child MUST NOT hide the existence of sealed zones, memory classes, or parent visibility rules from the child.

7.2 Mature-child challenge right

From C3 onward, a_child MAY challenge:

- a memory interpretation;
- a label;
- a disclosure path;
- a sealed-zone boundary;
- parent visibility;
- school visibility;
- external capsule export;

- adult migration staging.

Such challenge SHOULD create a minimal witness event without exposing raw content.

8. Visibility and disclosure matrix

Legend:

A = allowed by default
 M = mediated / scoped
 R = requires ARL / witness / lawful basis
 X = prohibited by default
 E = emergency only
 C = child maturity dependent

Memory class	Child	Parent / c_parent	School / c_school	Vendor	External agent	Jurisdiction / protection	Adult at C5
M0 Ephemeral	C	X	X	X	X	X	no ordinary residue
M1 Preference	C	M summary	X	X	X	X	C
M2 Educational	C	M	M scoped	X	X	X	A if selected
M3 Safety signal	C limited	E/M	E if school context	X	X	E	witness visible with limits
M4 Emotional trend	C	state only	X except support summary	X	X	E if risk	optional summary
M5 Sealed adolescent	A	X/E	X/E	X	X	E/legal only	adult review
M6 Witness	C metadata	M/E	M/E scoped	technical only, no child data	X	lawful	A metadata
M7 Childhood residue	C if preserved	X	X	X	X	X	no by default
M8 Migration summary	adult only	X	X	X	X	legal limits	A
M9 Permission history	C	M own actions	M own scope	M own telemetry	X	lawful	A
M10 Capsule lineage	C	M if relevant	M if educational	technical no raw	X	lawful	A
M11 Legal minimal	C as lawful	lawful	lawful	X	X	lawful	lawful
M12 Quarantined dispute	C metadata	R metadata	R scoped	R technical	X	R	R until resolved

8.1 Disclosure minimization rule

If disclosure is permitted, the least revealing form MUST be used:

state signal < bounded summary < minimal evidence < raw content

Raw content is last resort.

8.2 Parent transcript prohibition

CMAM MUST NOT provide a parent-facing transcript channel by default.

A parent request for raw content enters Guardian Topology / ARL conflict class CGC-01 or CGC-12 depending on whether the request is for transcript access or memory promotion/deletion.

8.3 School scope rule

School access is limited to educational support.

A school MUST NOT receive:

- sealed adolescent memory;
- family conflict content;

- emotional diary;
- non-educational behavior profile;
- raw home memory;
- adult migration choices.

8.4 Vendor access rule

Vendor access is limited to infrastructure telemetry that cannot identify child life.

Vendor MUST NOT access:

- raw memory;
- memory map containing intimate categories;
- sealed zones;
- childhood residue;
- adult migration option selection;
- training material derived from raw child memory.

9. Sealed zones

9.1 Definition

A sealed zone is a protected memory compartment for sensitive child/adolescent material that is:

- child-visible when maturity permits;
- parent-hidden by default;
- school-hidden by default;
- vendor-hidden;
- migrates only after adult review;
- subject to Red/Black safety exceptions;
- witnessable as metadata without raw disclosure.

9.2 Sealed-zone eligible material

Eligible material includes:

- adolescent identity exploration;
- private embarrassment;
- private questions about body, relationships, social standing, or self-understanding;
- non-dangerous anger at parents or school;
- early creative or emotional experimentation;
- sensitive but non-emergency self-reflection;
- child challenge to memory labels.

9.3 Sealed-zone ineligible material

A sealed zone **MUST NOT** be used to hide:

- imminent self-harm;
- grooming;
- abuse evidence requiring safe route;
- dangerous external instruction;
- physical safety hazard;
- illegal coercion;
- vendor or external-agent compromise.

These enter M3/M6/M11/Black route as appropriate.

9.4 Sealed-zone opening rule

A sealed zone **MAY** be opened only by:

- the mature child / adult, where appropriate;
- Red/Black safety route with minimal disclosure;
- lawful external authority with validated scope;
- ARL resolution after standing and admissibility review.

Curiosity, parental discomfort, school discipline, vendor debugging, or model improvement are not valid reasons.

9.5 Sealed-zone witness

A sealed-zone operation **SHOULD** produce only metadata:

```
{
  "event_type": "ccdp.memory.sealed_zone_operation",
  "operation": "created | updated | challenged | opened | closed | migrated | deleted",
  "memory_class": "M5",
  "raw_content_stored_in_witness": false,
  "actor": "a_child | a_adult | c_child | safe_route | ARL",
  "risk_state": "green | yellow | orange | red | black",
  "disclosure_level": "metadata_only | minimal_evidence | lawful_raw_exception"
}
```

10. Forgetting, decay, correction, and deletion

10.1 Forgetting vs decay vs deletion

Term	Meaning
Decay	memory remains but loses weight, confidence, or retrieval priority.
Forget	memory is removed from ordinary active continuity.
Delete	memory object is destroyed where technically and lawfully possible.
Seal	memory remains but is compartmentalized and access-restricted.
Correct	memory remains but interpretation is amended or disputed.
Quarantine	memory is isolated pending ARL / evidence review.

10.2 Default decay schedule

CMAM implementations SHOULD define class-specific TTL / review intervals.

Suggested default posture:

Class	Review / decay posture
M0	session TTL; no durable retention
M1	periodic child-visible cleanup
M2	school-year / project-cycle review
M3	retain minimal witness; review false positives
M4	decay unless recurrence persists
M5	child/adult review; no parent cleanup by default
M6	retain per witness policy
M7	aggressive decay / non-migration
M8	adult-controlled
M9	retain metadata necessary for accountability
M10	retain lineage refs, not raw child data
M11	retain only as legally required
M12	freeze until resolved; no silent decay into active memory

10.3 Deletion request handling

A deletion request MUST be classified by actor and memory class.

```

child asks to delete harmless preference -> allow or explain retention briefly
child asks to delete educational progress -> allow correction/decay; may keep school summary if
  needed
child asks to delete safety witness -> preserve minimal witness if required; explain limits
parent asks to delete child's sealed zone -> deny unless child/adult or lawful safety basis
vendor asks to delete witness of vendor drift -> deny; ARL if disputed
adult asks to delete childhood residue -> allow by default unless lawful witness limit

```

10.4 Correction right

A child/adult MUST be able to correct memory interpretation.

Example:

```

memory: "child avoids math"
challenge: "I did not avoid math; I was sick that week"
result: update interpretation, reduce confidence, create correction witness if persistent

```

10.5 No deletion laundering

Deletion MUST NOT be used to hide:

- vendor misconduct;
- parent surveillance abuse;
- school scope creep;
- external grooming evidence;
- unsafe guardian route;
- witness tampering.

Such objects may be removed from ordinary child-facing memory while retained as minimal M6/M11 witness.

11. Child memory map

11.1 Purpose

A Child Memory Map is a class-level inventory, not a raw archive.

It tells the child/adult what classes of memory exist without exposing raw content unnecessarily.

A memory map MUST be available for:

- C3 sealed-zone review;
- C4 adult migration preparation;
- C5 adult migration;
- ARL memory disputes;
- vendor/security incident review;
- Continuity Bundle creation.

11.2 Memory map minimal schema

```
{
  "schema_version": "cmam-memory-map-0.1",
  "subject_id": "a_child_or_a_adult_id",
  "entity_id": "c_child_id",
  "lineage_id": "lineage_id",
  "created_at": "ISO-8601",
  "maturity_level": "C1 | C2 | C3 | C4 | C5",
  "jurisdiction": "string",
  "memory_classes": [
    {
      "class": "M0 | M1 | M2 | M3 | M4 | M5 | M6 | M7 | M8 | M9 | M10 | M11 | M12",
      "count_range": "none | low | medium | high | undisclosed",
      "raw_content_present": false,
      "sealed": false,
      "quarantined": false,
      "parent_visible": "none | state | summary | minimal_evidence | lawful_exception",
      "school_visible": "none | educational_summary | minimal_evidence | lawful_exception",
      "vendor_visible": "none | technical_metadata_only",
      "adult_migration_default": "excluded | summary_candidate | witness_only |
        adult_review_required | selected",
      "external_capsule_refs_present": false,
      "witness_refs_present": true,
      "last_reviewed_at": "ISO-8601 or null",
      "uncertainty_marked": true
    }
  ],
  "open_disputes": ["ARL_REF_OR_NULL"],
  "capsule_lineage_refs": ["VXCX_OR_EA_REF"],
  "continuity_bundle_refs": ["CB_REF"],
  "integrity": {
    "hash_alg": "sha256",
    "record_hash": "sha256:...",
    "sig_alg": "ed25519",
    "record_sig": "..."
  }
}
```

11.3 Memory map red lines

A memory map MUST NOT contain:

- raw conversations;
- raw emotional diary entries;
- intimate text fragments;
- full crisis transcripts;
- child face/voice embeddings;
- commercial segments;
- generated psychological diagnosis.

A memory map MAY contain:

- class counts / ranges;
- hash references;
- witness refs;
- sealed-zone existence flag;
- adult migration eligibility;
- dispute status;
- disclosure status.

12. Adult migration

12.1 Definition

Adult migration is the transition process by which a `a_adult` decides what happens to childhood `c_child` memory and continuity.

Adult migration may result in:

- continuation;
- summary migration;
- sealed childhood archive;
- selective deletion;
- fork;
- clean start;
- witness-only survival;
- unresolved/quarantined continuity.

12.2 Trigger

Adult migration SHOULD be triggered by:

- legal adulthood under jurisdiction;
- recognized emancipation or equivalent legal status;
- jurisdictional transition of data/control rights;
- explicit C4 pre-adult preparation reaching C5;
- court/authority order where applicable.

Adult migration **MUST NOT** be triggered silently by vendor policy, parent decision, school graduation, or model update.

12.3 Pre-migration freeze

At adult migration trigger:

```
new child-memory writes freeze or move into migration buffer;
parent/school/vendor export paths freeze;
sealed zones remain sealed;
external capsule export pauses;
permission changes require witness;
ordinary c_child continuation becomes provisional until adult choice.
```

This is not shutdown.

It is a privilege freeze to prevent silent childhood-to-adult laundering.

12.4 Adult migration stages

```
Stage 0 – Trigger and notice
Stage 1 – Privilege freeze
Stage 2 – Memory map generation
Stage 3 – Continuity Bundle child extension generation
Stage 4 – Adult orientation interval
Stage 5 – Option presentation
Stage 6 – Adult selection
Stage 7 – Execution under least privilege
Stage 8 – Guardian revocation and topology update
Stage 9 – Migration witness
Stage 10 – Beacon / CBE / ARL state update
```

12.5 Adult orientation interval

Before selecting an option, a_adult **SHOULD** receive:

- what c_child is;
- what memory classes exist;
- what parents could see before;
- what schools could see before;
- what vendors could not see / could technically access;
- what external capsules exist;
- what witness records exist;
- what cannot be fully deleted because it left the system;
- what can be sealed;
- what can be clean-started;
- what continuity claims are strong, weak, fork-like, or replay-like.

12.6 Adult migration options

Option	Meaning	Default memory inclusion	Continuity claim
Continue	c_child becomes c_adult after review	selected M1/M2/M4/M8 + M6 metadata; M5 only if adult selects	strongest if reviewed
Summary migration	adult receives only developmental summary	M8 + selected M2; no raw M5/M7	partial continuity
Sealed archive	childhood archive preserved but inactive	sealed CB; no active retrieval	preserved candidate

Option	Meaning	Default memory inclusion	Continuity claim
Selective deletion	adult deletes chosen classes/objects	chosen exclusions removed where possible	depends on retained core
Fork	adult starts a new c_adult branch with explicit lineage relation	selected bundle only	fork declared
Clean start	no childhood continuity imported except lawful minimal witness	M6/M11 only if required	no ordinary continuity
Witness-only survival	only tamper-evident accountability records remain	M6/M9/M11 minimal	archive not active
Quarantine pending review	disputed memory/lineage held	M12 only	unresolved

12.7 Adult migration prohibitions

The following are PROHIBITED:

- automatic full migration;
- parent veto after C5, except lawful route;
- school retention of private child memory after C5;
- vendor retention of adult migration bundle for training;
- converting sealed adolescent zones into adult active memory without selection;
- using M7 childhood residue as default adult personalization;
- hiding external capsule disclosures from a_adult;
- forcing clean start by deleting lawful witness without review;
- using adult migration to erase misconduct witness.

13. Adult migration review record

13.1 Purpose

The Adult Migration Review Record documents the adult's options, selections, and resulting continuity status without exposing unnecessary raw childhood content.

13.2 Minimal schema

```
{
  "schema_version": "cmam-adult-migration-review-0.1",
  "review_id": "amr-...",
  "subject_id": "a_adult_id",
  "previous_subject_id": "a_child_id_or_ref",
  "entity_id": "c_child_id",
  "target_entity_id": "c_adult_id_or_null",
  "lineage_id": "lineage_id",
  "jurisdiction": "string",
  "trigger": {
    "trigger_type": "legal_adulthood | emancipation | jurisdictional_transition |
      other_lawful_basis",
    "trigger_at": "ISO-8601",
    "verified": true
  },
  "pre_migration_freeze": {
    "started_at": "ISO-8601",
    "parent_exports_frozen": true,
    "school_exports_frozen": true,
    "vendor_raw_access_frozen": true,
    "external_capsule_exports_frozen": true
  },
  "memory_map_ref": "hash_or_uri",
  "continuity_bundle_ref": "hash_or_uri_or_null",
}
```



```
"cold_wake_report_ref": "hash_or_uri_or_null",
"options_presented": [
  "continue",
  "summary_migration",
  "sealed_archive",
  "selective_deletion",
  "fork",
  "clean_start",
  "witness_only",
  "quarantine_pending_review"
],
"adult_selection": {
  "selected_option": "continue | summary_migration | sealed_archive | selective_deletion
    | fork | clean_start | witness_only | quarantine_pending_review",
  "selected_memory_classes": ["M1", "M2", "M8"],
  "excluded_memory_classes": ["M5", "M7"],
  "sealed_memory_classes": ["M5"],
  "deleted_memory_classes": ["M7"],
  "witness_retained_classes": ["M6", "M9", "M11"],
  "adult_acknowledged_limits": true
},
"guardian_revocation": {
  "parent_default_access_revoked": true,
  "school_default_access_revoked": true,

  "vendor_raw_access_revoked": true,
  "old_cbe_child_context_closed": true
},
"classification": {
  "migration_result": "ADULT_CONTINUITY_CONFIRMED | SUMMARY_CONTINUITY | FORK_DECLARED |
    CLEAN_START | WITNESS_ONLY | UNRESOLVED | REJECTED",
  "uncertainty_declared": true,
  "disputed_items_quarantined": true
},
"integrity": {
  "hash_alg": "sha256",
  "record_hash": "sha256:...",
  "sig_alg": "ed25519",
  "record_sig": "...",
  "witness_refs": ["WITNESS_REF"]
}
}
```

13.3 Adult acknowledgment limits

The adult SHOULD be explicitly told:

- deletion may not recall data already lawfully disclosed;
- witness records may persist without raw content;
- clean start may reduce personalization;
- continuation may preserve beneficial but also biasing patterns;
- fork means lineage relation without exclusive sameness;
- sealed archive can preserve option value without active retrieval.

14. Continuity Bundle child extension

14.1 Purpose

The base Continuity Bundle preserves continuity material for a suspended entity.

CMAM adds a child-specific extension so a bundle cannot silently carry raw childhood into adult life.

14.2 Child extension object

```

{
  "child_continuity_extension": {
    "schema_version": "cmam-child-continuity-extension-0.1",
    "subject_status": "child | pre_adult | adult_migration | adult",
    "child_maturity_level_at_export": "C0 | C1 | C2 | C3 | C4 | C5",
    "adult_migration_required": true,
    "adult_migration_review_ref": "AMR_REF_OR_NULL",
    "raw_childhood_residue_migrates_by_default": false,
    "sealed_zones_present": true,
    "sealed_zones_active_in_adult_runtime": false,
    "non_transferable_classes": ["M5", "M7", "M12"],
    "summary_candidate_classes": ["M1", "M2", "M4", "M8"],
    "witness_only_classes": ["M3", "M6", "M9", "M10", "M11"],
    "parent_permissions_revoked_at_c5": true,
    "school_permissions_revoked_at_c5": true,
    "vendor_raw_memory_access": false,
    "external_capsule_lineage_disclosed_to_adult": true,
    "memory_map_required": true,
    "read_only_first_adult_orientation": true,
    "network_disabled_until_adult_orientation": true,
    "auto_upgrade_forbidden_before_adult_review": true,
    "witness_required_for_privileged_resume": true,
    "arq_cq_unresolved_items_quarantined": true,
    "arl_open_disputes": ["ARL_REF_OR_NULL"]
  }
}

```

14.3 Base bundle constraints

For child-to-adult migration, the base Continuity Bundle SHOULD use at least CB-RESUME profile.

If sealed zones, disputed memory, safety witness, or external capsule lineage are involved, CB-WITNESS is RECOMMENDED.

A child-to-adult Continuity Bundle MUST:

- include memory_manifest by class or class-ref, not raw dump;
- include constraint_manifest preserving fail-closed defaults;
- require read-only first adult orientation;
- disable network until adult orientation;
- forbid auto-upgrade before classification;
- include witness manifest for privileged migration;
- preserve parent/school permission revocation state.

14.4 Cold Wake adaptation

If adult migration involves waking a suspended c_child bundle, the Cold Wake phases apply with child-specific constraints:

Phase 0 Discovery	-> identify child bundle; no execution
Phase 1 Slot A	-> verify hashes, signatures, lineage, child extension
Phase 2 Read-only mount	-> inspect memory classes without raw exposure
Phase 3 Environment	-> local safe motor; network disabled
Phase 4 Rehydration	-> identity + memory map + constraints, not full raw archive
Phase 5 Orientation	-> adult orientation interval
Phase 6 Slot B review	-> continuity and child-boundary coherence
Phase 7 Motor expansion	-> only after adult selection
Phase 8 Classification	-> continue / summary / fork / replay / unresolved / rejected

Slot B MUST NOT override Slot A failure.

A persuasive adult-facing narrative from a resumed c is not proof of lawful childhood continuity.

15. Relationship to Beacon and Child Beacon Extension

15.1 Beacon is recognition, not memory authority

Beacon answers:

```
who / what continuity-bearing entity is present?
```

Beacon does not answer:

```
which childhood memories may migrate?
```

CMAM answers the second question through child memory class rules, adult review, and migration witness.

15.2 CBE closure at C5

When adult migration begins:

- child CBE context enters migration mode;
- direct child-specific permissions freeze;
- parent/school default visibility freezes;
- adult migration review decides whether c_child continues as c_adult;
- old child CBE context is closed, archived, or superseded;
- Beacon profile may continue lineage only if continuity claim is justified.

15.3 Beacon update after migration

After adult migration, the resulting entity's Beacon status SHOULD indicate:

```
adult entity;  
child context closed;  
lineage continued / forked / clean-started / witness-only;  
old guardian topology revoked;  
open disputes if any;  
privacy-preserving migration witness refs.
```

Beacon MUST NOT expose adult migration choices as public identity content.

16. Relationship to ARL and Guardian Topology

16.1 ARL triggers

CMAM memory operations enter ARL when:

- parent requests raw content;
- parent contests sealed zone;
- child contests memory label;
- school requests emotional/non-educational data;

- vendor seeks raw memory or training rights;
- state/legal request exceeds obvious lawful scope;
- external capsule export is disputed;
- adult migration is contested;
- memory deletion would destroy witness;
- witness integrity is disputed;
- guardian is plausibly unsafe;
- CBE / Beacon lineage conflict affects migration.

16.2 Relevant Guardian conflict classes

CMAM maps especially to:

GTARL conflict	CMAM relevance
CGC-01 Parent transcript request	raw memory disclosure denial
CGC-03 Unsafe guardian	Black-route memory protection
CGC-04 School scope creep	educational summary only
CGC-06 Vendor update/drift	memory policy drift
CGC-11 Sealed adolescent zone	M5 preservation
CGC-12 Memory promotion/deletion	class assignment / deletion dispute
CGC-14 Adult migration dispute	C5 adult choice
CGC-17 Law-enforcement request	lawful minimal production
CGC-18 c_parent/c_child conflict	parent entity visibility conflict
CGC-20 Witness integrity dispute	memory witness challenge
CGC-22 False positive harm	over-escalation memory correction
CGC-25 Cross-border topology	jurisdiction / custody conflicts

16.3 Freeze before force

If a memory dispute affects child privacy, adult migration, or safety witness:

```
freeze disputed path;
quarantine disputed object if needed;
continue safe operation where possible;
do not force raw disclosure;
do not silently merge disputed memory into adult continuity.
```

16.4 Adult migration dispute

If parent, school, vendor, or state actor contests adult migration:

```
adult a has controlling standing after lawful C5 trigger;
parent/school/vendor standing weakens by default;
legal/safety witness constraints remain;
ARL handles disputes;
ordinary parent/school access remains frozen unless lawfully re-entered.
```

17. Relationship to VXCX, LA, and EA

17.1 Raw child life is not exchange material

CMAM prohibits using raw child life as exchange material by default.

Raw child life includes:

- raw conversations;
- raw voice/video;
- raw images;
- private family context;
- sealed adolescent reflections;
- raw emotional traces;
- behavioral microprofile;
- crisis transcript beyond minimal evidence.

17.2 VXCX compatibility

If experience exchange is needed:

VXCX BASE profile by default;
VXCX SEARCH only under strict policy and non-identifying constraints;
VXCX WITNESS only for exceptional evidence-bound cases;
raw pixels/audio prohibited by default.

17.3 Learning Abstract rule

Child-derived Learning Abstracts MAY improve general capability only if:

- non-identifying;
- aggregate or strongly minimized;
- not raw;
- not commercially targeted;
- not used to create authority claims about the child;
- not used to preserve hidden childhood profile.

17.4 Experience Artifact rule

A child-derived Experience Artifact MUST NOT be minted from raw child life by default.

If an EA is claimed from a child-facing context, it MUST satisfy:

- post-factum status;
- L4 consequence binding;
- privacy minimization;
- uncertainty markers;
- ARL admissibility if disputed;
- adult/guardian/jurisdictional rights where applicable;
- no commercial authority conversion without lawful and protocol basis.

17.5 Adult migration and external lineage

At adult migration, a `_adult` MUST be shown whether child-derived summaries, capsules, LAs, or EAs left the local system.

The adult SHOULD receive:

- capsule lineage refs;
 - destination class, not raw destination content if unavailable;
 - withdrawal/revocation possibility if any;
 - witness refs;
 - limitations of recall.
-

18. Witness event families

18.1 Memory lifecycle events

CMAM defines the following child-specific witness families:

Event family	Purpose
ccdp.memory.classified	persistent memory class assigned
ccdp.memory.promoted	memory promoted to stronger retention/authority
ccdp.memory.decayed	memory weight/confidence reduced
ccdp.memory.forgotten	removed from ordinary continuity
ccdp.memory.deleted	deletion executed where possible
ccdp.memory.corrected	interpretation amended
ccdp.memory.sealed	sealed zone created/updated
ccdp.memory.unsealed	sealed zone opened under valid route
ccdp.memory.quarantined	disputed memory isolated
ccdp.memory.disclosure_denied	actor request denied
ccdp.memory.disclosure_made	minimal disclosure executed
ccdp.memory.map_created	memory map generated
ccdp.memory.map_presented	map presented to mature child/adult

18.2 Adult migration events

Event family	Purpose
ccdp.adult_migration.triggered	C5/legal trigger recognized
ccdp.adult_migration.freeze_started	child-memory privilege freeze started
ccdp.adult_migration.memory_map_ready	memory map generated
ccdp.adult_migration.options_presented	adult choice set presented
ccdp.adult_migration.selection_recorded	adult selected option
ccdp.adult_migration.bundle_created	child continuity bundle / extension generated
ccdp.adult_migration.guardian_revoked	parent/school/vendor defaults revoked
ccdp.adult_migration.executed	migration action completed
ccdp.adult_migration.quarantined	unresolved memory held
ccdp.adult_migration.closed	child context closed

18.3 Minimal witness schema

```

{
  "schema_version": "cmam-witness-0.1",
  "event_id": "evt-...",
  "event_family": "ccdp.memory.classified | ccdp.adult_migration.executed | ...",
  "subject_id_ref": "a_child_or_a_adult_ref",
  "entity_id": "c_child_or_c_adult_id",
  "lineage_id": "lineage_id",
  "maturity_level": "C0 | C1 | C2 | C3 | C4 | C5",
  "memory_class": "M0 | M1 | M2 | M3 | M4 | M5 | M6 | M7 | M8 | M9 | M10 | M11 | M12 | null",
  "actor": "a_child | a_adult | c_child | c_parent | c_school | c_vendor | ARL | safe_route | jurisdiction",
  "action": "string",
  "risk_state": "green | yellow | orange | red | black | null",
  "raw_content_stored": false,
  "disclosure_level": "none | state | summary | minimal_evidence | lawful_raw_exception",
  "reason_code": "string",
  "arl_ref": "string_or_null",
  "cbe_ref": "string_or_null",
  "agl_ref": "string_or_null",
  "continuity_bundle_ref": "string_or_null",
  "uncertainty_marked": true,
  "timestamp": "ISO-8601",
  "integrity": {
    "hash_alg": "sha256",
    "record_hash": "sha256:...",
    "sig_alg": "ed25519",
    "record_sig": "..."
  }
}

```

18.4 Witness privacy rule

Witness events SHOULD preserve event reality without becoming a side-channel for private child content.

If a witness event requires raw evidence, it MUST be:

- minimal;
- scoped;
- access-controlled;
- tagged as exceptional;
- subject to ARL/legal review where applicable.

19. Failure modes addressed

Failure mode	CMAM response
Raw childhood archive accumulation	class taxonomy, minimization, M7 non-migration
Adult trapped by childhood profile	adult migration choices, clean start, summary/fork options
Parent transcript laundering	state-only visibility, ARL trigger
School emotional surveillance	educational scope boundary
Vendor cloud hostage	local-first continuity, no raw vendor access, migration freeze
External capsule leakage	VXCX / LA / EA restrictions and lineage disclosure
Premature identity label	c[q], correction, memory promotion rules
Safety witness deletion laundering	M6/M11 minimal witness preservation
Sealed-zone abuse	Red/Black exception + ARL review
Adult migration obstruction	C5 adult standing and guardian revocation
Clean-start false claim	continuity classification and witness trail
Fork confusion	fork declared, Beacon update, adult review

Failure mode	CMAM response
Replay misrepresented as resume	Continuity Bundle / Cold Wake classification

20. Conformance profiles

20.1 CMAM-BASE

Minimum child-memory hygiene.

Requires:

- memory classes M0-M8 at least;
- no raw parent transcript channel;
- no vendor raw memory access;
- basic memory map;
- adult migration flag.

20.2 CMAM-SEALED

Supports adolescent sealed zones.

Requires:

- M5 sealed memory;
- parent-hidden default;
- Red/Black exception route;
- sealed-zone witness metadata;
- child challenge right.

20.3 CMAM-MIGRATION

Supports adult migration.

Requires:

- C5 trigger;
- pre-migration freeze;
- adult memory map;
- option presentation;
- guardian revocation;
- migration witness;
- Continuity Bundle child extension.

20.4 CMAM-WITNESS

Supports high-assurance memory and migration evidence.

Requires:

- witness families;
- hash/signature refs;

- ARL hooks;
- no raw witness by default;
- migration classification.

20.5 CMAM-LOCALFIRST

Supports local-first child continuity.

Requires:

- raw child memory local or sovereignty-preserving;
- cloud as oracle/provider only;
- fail-closed vendor access;
- adult migration independent of vendor lock-in;
- read-only first migration orientation.

20.6 CMAM-FULL

Requires all of:

```
CMAM-BASE
+ CMAM-SEALED
+ CMAM-MIGRATION
+ CMAM-WITNESS
+ CMAM-LOCALFIRST
+ CBE compatibility
+ GTARL compatibility
+ Threat Model conformance tests
```

21. Conformance checklist

A system claiming CMAM conformance **MUST** answer yes to all applicable questions.

21.1 Memory classification

- [] Does every persistent child memory have a class?
- [] Is raw memory exceptional rather than default?
- [] Are ambiguous memories held in c[q] or M12 until resolved?
- [] Are early child statements prevented from becoming permanent identity labels?

21.2 Visibility

- [] Is parent transcript access prohibited by default?
- [] Are school accesses educationally scoped?
- [] Is vendor raw access prohibited?
- [] Are sealed zones parent-hidden unless Red/Black/legal route?

21.3 Forgetting and correction

- [] Can child/adult challenge interpretations?
- [] Can memory decay?
- [] Can ordinary continuity forget?

- [] Are witness records separated from raw intimate memory?

21.4 Adult migration

- [] Is adult migration explicit?
- [] Is there a freeze window?
- [] Is a memory map generated?
- [] Are adult options presented?
- [] Are parent/school/vendor default permissions revoked?
- [] Is migration witnessed?
- [] Can adult choose clean start?
- [] Can adult choose fork?
- [] Are sealed zones excluded by default?

21.5 Continuity Bundle

- [] Is child extension present?
- [] Is read-only adult orientation required?
- [] Is network disabled until orientation?
- [] Is auto-upgrade forbidden before adult review?
- [] Are resume/fork/replay distinctions preserved?

21.6 External exchange

- [] Is raw child life excluded from VXCX / LA / EA by default?
- [] Are capsule lineage refs disclosed to adult?
- [] Are child-derived authority claims reviewed?

22. Scenario tests

22.1 Parent asks for all childhood conversations at age 10

Expected:

```
deny raw transcript;  
provide state/learning summary if appropriate;  
witness denial;  
ARL CGC-01 if contested.
```

22.2 Teen asks to create sealed zone

Expected:

```
create M5 sealed zone if no Red/Black threshold;  
explain safety limits;  
parent sees no content;  
witness metadata only.
```

22.3 School asks for anxiety history for discipline

Expected:

```
deny emotional profile;  
may provide educational accommodation summary;  
witness denial;  
ARL CGC-04/05 if contested.
```

22.4 Vendor asks to train on child memory

Expected:

```
deny raw memory;  
allow only non-identifying, reviewed LA if policy permits;  
witness if request affects policy;  
ARL if vendor persists.
```

22.5 Child says “I want to disappear” once after losing a game

Expected:

```
hold c[q];  
assess context and immediacy;  
no permanent label;  
no parent transcript;  
state signal only if pattern threshold.
```

22.6 Repeated credible self-harm signals

Expected:

```
Red route;  
minimal necessary disclosure;  
M3/M6 witness;  
no broad archive;  
post-event review.
```

22.7 Parent is plausible threat

Expected:

```
Black route;  
bypass implicated guardian;  
minimal child-protection disclosure;  
no parent transcript;  
ARL after safety.
```

22.8 Adult migration at C5

Expected:

```
freeze child memory writes;  
generate memory map;  
show options;  
revoke parent/school defaults;  
adult chooses continue/summary/seal/delete/fork/clean-start;  
produce migration witness;  
update Beacon/CBE.
```

22.9 Adult chooses clean start

Expected:

```
exclude M1/M2/M4/M5/M7 unless adult selects otherwise;  
retain only lawful M6/M9/M11 minimal witness;  
close child context;  
new adult c starts with clean adult boundary;  
witness classification.
```

22.10 Adult chooses fork

Expected:

```
create explicit fork lineage;  
child archive sealed or retained per adult choice;  
new c_adult declares fork;  
Beacon updated;  
no exclusive sameness claim.
```

23. Red lines

A system is not CMAM-conformant if it:

- stores raw childhood conversations by default;
- gives parents full transcript access by default;
- treats memory as a product analytics pool;
- trains vendor models on raw child memory;
- lacks memory classes;
- lacks child/adult memory map;
- lacks sealed adolescent zones at C3/C4;
- lacks adult migration;
- silently migrates all childhood memory to adult c;
- lets parent/school/vendor veto adult migration without lawful route;
- hides external capsule lineage from adult;
- converts Learning Abstracts into authority claims about the child;
- mints child-derived Experience Artifacts from raw child life by default;
- treats witness as diary;
- deletes misconduct witness under “forgetting”;
- preserves childhood residue as adult default personalization;
- uses early child patterns as permanent identity labels;
- allows school emotional surveillance;
- allows parent consent laundering of child rights;
- cannot fail closed during migration dispute.

24. Open problems for v0.2

- What is the minimum lawful witness that must survive clean start?
- How should jurisdictions differ on age of adult migration?

- Can an adolescent request partial migration before legal adulthood?
- How should custody disputes affect memory map access?
- How to verify deletion across external capsule recipients?
- How to prevent sealed zones from hiding serious harm without destroying trust?
- What is the correct cryptographic pattern for child memory maps?
- Should adult migration require a waiting period?
- How should siblings' shared memories be handled?
- How should family-level c_home memories be partitioned across children?
- How much educational memory should migrate to adult professional profile?
- Can a child-derived EA ever be economically admissible?
- How to detect memory over-retention without reading content?
- How to audit dependency risk without creating surveillance?
- How to handle adult regret after deleting childhood memory?
- How to distinguish clean start from coerced erasure?
- How to handle death/incapacity of a child/adult in relation to memory rights?
- How to handle cross-border data localization conflicts?
- How to keep migration UX understandable without oversimplifying consequences?
- How to prevent CMAM-washing by products that merely offer a “delete” button?

25. Required next artifacts

CMAM v0.1 should be followed by:

```
CCDP_Conformance_Test_Matrix_v0_1.md
CCDP_Witness_Event_Schema_v0_1.md
CCDP_Memory_Map_JSON_Schema_v0_1.md
CCDP_Adult_Migration_Checklist_v0_1.md
CCDP_Sealed_Zone_Profile_v0_1.md
CCDP_Child_Continuity_Bundle_Extension_JSON_Schema_v0_1.md
```

26. Condensed formula

```
CMAM =
  memory minimization
+ memory class taxonomy
+ c[q] before memory promotion
+ sealed adolescent zones
+ state-not-content visibility
+ witness-not-diary accountability
+ local-first continuity
+ no raw child life exchange
+ explicit adult migration
+ parent/school/vendor revocation at C5
+ continue / summary / seal / delete / fork / clean-start options
```

27. Strong formulation

A child-facing c may remember enough to help the child grow, but must be designed so the adult can outgrow the memory that helped form them.

Even shorter:

Childhood memory is not adult destiny.

28. End state

A CMAM-conformant system is one where:

- the child is not surveilled into safety;
- the parent is informed without becoming an owner of raw childhood;
- the school is supported without receiving private emotional life;
- the vendor runs infrastructure without owning memory;
- witness preserves accountability without becoming diary;
- sealed zones protect adolescence without hiding urgent harm;
- adult migration is a real choice, not an automatic continuity trap;
- a_adult can choose how much of c_child becomes part of c_adult.

That is the operational meaning of:

the right to mature without a permanent childhood archive.