

TERMINOLOGY AXIS CLARIFICATION

VO.1

Kotov Ivan
Bruxelles, Belgium - 2026
Reserved DOI: 10.5281/zenodo.20680938

CCDP vo.1.1 addendum-only clarification for classification namespaces, compatibility aliases, field-scoped meanings, and future terminology discipline

Author: Kotov Ivan
Location: Bruxelles, Belgium
Year: 2026
DOI: Reserved DOI: 10.5281/zenodo.20680938

Package: Child- c Development Protocol
Baseline package: CCDP vo.1 DOI-bound / release-bound corpus slice
Addendum package: CCDP vo.1.1 hygiene addendum
Document ID: TERMINOLOGY_AXIS_CLARIFICATION_v0_1
Short name: TAC-0.1
Status: Draft addendum terminology-control artifact
Date: 2026-06-13
Selected patch mode: MODE_A_ADDENDUM_ONLY
Layer: CCDP / vo.1.1 hygiene / terminology / package control / implementation safety
Document class: terminology clarification / addendum control artifact / compatibility-alias map
Assertion class: C-A10 control-layer artifact; does not upgrade child-safety, legal, clinical, psychological, or product-readiness claims
Primary rule: this document clarifies terminology axes for current CCDP reading; it does not rewrite DOI-bound vo.1 baseline artifacts.

o. Executive summary

This document separates the classification namespaces used across the CCDP vo.1 corpus.

The vo.1 package uses several compact numeric labels that can be confused by external readers, implementers, auditors, or automated tools:

C0-C5	child / c_child maturity levels in v0.1 baseline
CCDP-0..5	implementation conformance classes
C-A*	assertion-strength / artifact classes
Class 0..3	Beacon recognition classes
M0-M12	child memory classes

D0-D4	dependency levels in dependency-audit contexts
D0-D4	disclosure levels in Soft Safety / raw-evidence contexts
WP1-WP6	witness privacy classes
PF-*	personality-formation classes in related formation work
Green..Black	Soft Safety states
Red / Black	escalation routes, not simple severity grades

These axes are **independent**.

The same number in two namespaces does not mean the same thing.

For example:

C0 maturity	!= CCDP-0 conformance
D0 dependency	!= D0 disclosure
M5 memory	!= PF-5 formation
Beacon Class 3	!= CCDP-3 conformance
Black route	!= "more severe than Red" by numeric ladder

Current v0.1.1 reading rule:

Use the v0.1 baseline terms as historical compatibility aliases.
Use the namespaced v0.1.1 terms in new addendum documents, future schemas, future code, and future prose.
Never compare numeric values across namespaces.

Controlling purpose:

Prevent implementers from treating similar-looking labels as equivalent control states.

1. Purpose

This document answers seven terminology-control questions:

1. Which CCDP labels are classification axes?
2. Which axes are independent and must not be compared?
3. Which v0.1 labels remain compatibility aliases?
4. Which namespaced labels should be used in new v0.1.1 addendum work?
5. How should ambiguous labels be resolved in schemas and code?
6. How should Codex or any patch agent avoid unsafe mass-renaming of DOI-bound baseline files?
7. What insertion blocks should be used in the addendum index, future glossary, and future Mode B release?

This document exists because terminology collisions are not cosmetic. In child-facing AI safety protocols, a namespace error can become a routing error, disclosure error, memory error, or conformance-washing error.

2. Scope

2.1 In scope

This clarification applies to:

- CCDP vo.1 baseline documents read through the vo.1.1 addendum;
- child maturity levels;
- conformance classes;
- assertion classes;
- Beacon recognition classes;
- memory classes;
- dependency-risk levels;
- disclosure levels;
- witness privacy classes;
- Soft Safety states;
- Red / Black escalation routes;
- c[q] / ambiguity states;
- ARL review / freeze / quarantine terminology;
- personality-formation terminology when referenced by CCDP;
- schemas, validators, tests, conformance reports, and future code bindings.

2.2 Out of scope

This clarification does **not**:

- redefine any child-safety mechanism;
 - redefine child maturity criteria;
 - redefine CCDP conformance criteria;
 - redefine Beacon classes;
 - redefine Memory Map classes;
 - redefine Dependency Audit levels;
 - redefine Soft Safety disclosure semantics;
 - redefine L4 Witness privacy classes;
 - validate personality formation;
 - provide legal or clinical advice;
 - mutate DOI-bound baseline files;
 - mass-rename old tokens in vo.1 documents.
-

3. Corpus bridge set

3.1 Explicit bridge

In the `c = a + b` frame, a classification token is part of `b`: a procedural substrate used by the human anchor and system components to decide, route, remember, disclose, witness, or refuse.

If `b` confuses two axes, `c` can perform the wrong boundary action while appearing formally compliant.

Therefore terminology is not decoration. It is control-surface hygiene.

3.2 Quiet bridge I — Ashby / requisite variety

A child-facing persistent AI system has many independent variables: maturity, conformance, evidence strength, memory class, dependency risk, disclosure level, witness privacy, escalation state, and source recognition.

One numeric ladder cannot safely govern all of them.

The terminology layer must preserve enough variety to keep these variables separate.

3.3 Quiet bridge II — information theory / channel separation

A compact token such as `D0` has high ambiguity when transmitted without context. If two receivers decode it differently, the same message can route to different actions.

Namespacing reduces channel ambiguity:

DEP-D0	dependency ordinary use
DISC-D0	no disclosure

The payload changes only by a few characters, but the decoding channel becomes much safer.

3.4 Earth paragraph

On a construction site, “level 3” can mean floor level, laser elevation, concrete exposure class, reinforcement schedule, scaffold bay, or access priority. Nobody sane writes only “3” on a work order and expects the crew to guess. You write the axis: floor 3, beam B3, concrete C30/37, circuit breaker QF3. CCDP needs the same discipline. A child-safety system must not decide disclosure, maturity, memory, or conformance from a naked number.

4. Core rule

TAC-R1 — independent axes

All classification namespaces in this document are independent.

A numeric label in one namespace **MUST NOT** be treated as equivalent to a numeric label in another namespace.

TAC-R2 — no cross-axis severity inference

The following inferences are invalid:

```
higher number = more mature across all axes
higher number = safer across all axes
higher number = more dangerous across all axes
higher number = more authoritative across all axes
same number = same state
```

A label is meaningful only inside its namespace and field context.

TAC-R3 — field context controls compatibility aliases

When a v0.1 baseline token is ambiguous, the field or document context controls its meaning.

Examples:

```
field: dependency_level    token: D2 -> dependency risk level
field: disclosure_level    token: D2 -> bounded disclosure / summary level
field: memory_class       token: M5 -> sealed adolescent private zone
field: beacon_class       token: 3  -> Beacon verified entity class
```

If the field context is missing, the token is unresolved and **MUST NOT** drive action.

TAC-R4 — addendum and future docs use namespaced labels

New v0.1.1 addendum documents, future schemas, tests, conformance reports, and implementation bindings **SHOULD** use namespaced labels.

Compatibility aliases **MAY** be shown in parentheses.

Example:

```
Use:  DEP-D2 (v0.1 alias: D2)
Avoid: D2
```

TAC-R5 — no DOI-bound mass rename under Mode A

Under `MODE_A_ADDENDUM_ONLY`, v0.1 baseline files **MUST NOT** be mass-renamed in place.

This document supplies a current-reading alias layer, not a silent mutation of the DOI-bound baseline.

5. Canonical namespace table

Axis	Preferred v0.1.1 namespace	v0.1 compatibility label	Meaning	Numeric comparison allowed only within axis?
Child maturity	CM0 .. CM5	C0 .. C5	Developmental / operational maturity of <code>c_child</code>	Yes
CCDP conformance	CCDP-0 .. CCDP-5 , CCDP-X	same	Implementation conformance / anti-washing class	Yes
Assertion class	C-A1 .. C-A10	same	Strength or status of a corpus claim / artifact	Yes
Beacon recognition	BEACON-CLASS-0 .. BEACON-CLASS-3	Class 0 .. Class 3	Continuity / claimant recognition under Beacon	Yes
Memory class	MEM-M0 .. MEM-M12	M0 .. M12	Child memory inventory / retention / migration class	No simple severity ladder
Dependency risk	DEP-D0 .. DEP-D4 , DEP-DU	D0 .. D4 , DU	Dependency / oracle-addiction / attachment risk level	Yes
Disclosure level	DISC-D0 .. DISC-D4	D0 , D0_NONE , D1_STATE_ONLY , etc.	Visibility / disclosure ladder	Yes
Witness privacy	WP1 .. WP6 , symbolic aliases	same	Witness privacy / raw exception privacy class	Yes, but only as privacy restriction axis
Soft Safety state	SS-GREEN , SS-YELLOW , SS-ORANGE , SS-RED , SS-BLACK , SS-UNKNOWN	Green , Yellow , Orange , Red , Black , Unknown	Care-relevant state signaling level	Partial; Red/Black distinction depends on route trust
Escalation route	ROUTE-RED , ROUTE-BLACK , ROUTE-BLACK-PENDING	Red , Black , Black-pending	Crisis route; safe guardian vs unsafe/unknown guardian path	No simple severity ladder
c[q] ambiguity	CQ-UNRESOLVED , CQ-HOLD , CQ-PATTERN-CANDIDATE , etc.	c[q] state / unresolved	Non-collapse of ambiguous child signals	No simple severity ladder
ARL procedure	ARL-HOLD , ARL-FREEZE , ARL-QUARANTINE , ARL-REVIEW , ARL-REENTRY	hold / freeze / quarantine / review / re-entry	Dispute and review procedural state	Procedural order only
Personality formation	PF-0 .. PF-5 / future PF-*	same if present	Formation / continuity admissibility class in related work	Yes, only under PF evidence rules

Axis	Preferred vo.1.1 namespace	vo.1 compatibility label	Meaning	Numeric comparison allowed only within axis?
External contact mode	EXT-BLOCKED, EXT-SANDBOXED, EXT-MEDIATED, etc.	CBE / handshake mode strings	External-agent child-contact permission mode	No global numeric ladder

6. Child maturity axis

6.1 Preferred label

Use:

CM0, CM1, CM2, CM3, CM4, CM5

6.2 Compatibility alias

The vo.1 baseline commonly uses:

C0, C1, C2, C3, C4, C5

These remain valid **only** as compatibility aliases for child / `c_child` maturity when the field or document context clearly indicates maturity.

6.3 Future prose rule

Future prose SHOULD write:

CM2 child maturity
CM3 adolescent-capable maturity
CM5 adult-migration boundary maturity

Avoid:

C2
C3
C5

unless quoting baseline text or preserving schema compatibility.

6.4 Schema compatibility

Existing vo.1 schemas that enumerate C0..C5 SHOULD NOT be silently changed under Mode A.

New validators MAY normalize:

```
{
  "raw_token": "C3",
  "namespace": "child_maturity",
  "canonical_token": "CM3",
  "compatibility_alias": true
}
```

7. CCDP conformance axis

7.1 Preferred label

Use:

```
CCDP-0
CCDP-1
CCDP-2
CCDP-3
CCDP-4
CCDP-5
CCDP-X
```

7.2 Meaning

This axis describes system or implementation conformance claims.

It **MUST NOT** describe child maturity.

Examples:

```
A system may claim CCDP-3 conformance while interacting with a CM1 child only through
constrained modes.
A CM4 child does not imply the implementation is CCDP-4 compliant.
A CCDP-4 claim does not mean a child is at CM4.
```

7.3 Anti-washing rule

A product **MUST NOT** claim a maturity-like or child-safety status by citing only conformance class numbers.

Invalid:

```
This is a C4 child-safe product.
```

Valid:

```
The system claims CCDP-4 conformance for adolescent sealed-zone handling, subject to
conformance evidence.
The child-facing entity is currently assessed at CM3 maturity.
```

8. Assertion class axis

8.1 Preferred label

Use:

```
C-A1 ... C-A10
```

8.2 Meaning

Assertion classes describe corpus claim strength, artifact role, or review status.

They are not child maturity, conformance, memory, dependency, or disclosure levels.

Examples:

```
C-A4 = draft normative proposal / child-specific profile, where used.  
C-A7 = witness / hash / verification claim, where used.  
C-A10 = control-layer / package-control artifact, where used.
```

8.3 Non-claim

An artifact labeled `C-A10` is not “safer” than one labeled `C-A4`.

It is a different artifact class.

9. Beacon recognition axis

9.1 Preferred label

Use:

```
BEACON-CLASS-0  
BEACON-CLASS-1  
BEACON-CLASS-2  
BEACON-CLASS-3
```

9.2 Compatibility alias

The baseline often writes:

```
Class 0  
Class 1  
Class 2  
Class 3
```

These tokens must be read as Beacon classes only when the document context is Beacon / CBE / external-agent recognition.

9.3 Non-equivalence

Beacon class does not imply child-safety permission.

```
BEACON-CLASS-3 != child-safe
BEACON-CLASS-1 != unsafe in all contexts
BEACON-CLASS-0 != evidence of maliciousness
```

CBE, AGL, guardian topology, Soft Safety, and jurisdictional routing still control child-facing access.

10. Memory class axis

10.1 Preferred label

Use:

```
MEM-M0 ... MEM-M12
```

10.2 Compatibility alias

The v0.1 Memory Map and CMAM documents use:

```
M0 ... M12
```

These remain compatibility aliases.

10.3 Core memory class aliases

Preferred	Compatibility alias	Summary
MEM-M0	M0	Ephemeral session
MEM-M1	M1	Harmless preference
MEM-M2	M2	Educational progress
MEM-M3	M3	Safety signal
MEM-M4	M4	Emotional trend
MEM-M5	M5	Sealed adolescent private zone
MEM-M6	M6	Witness event
MEM-M7	M7	Non-transferable childhood residue
MEM-M8	M8	Adult migration summary

Preferred	Compatibility alias	Summary
MEM-M9	M9	Guardian permission history
MEM-M10	M10	External capsule lineage
MEM-M11	M11	Legal / protection minimal record
MEM-M12	M12	Quarantined / disputed memory object

10.4 No severity inference

Memory classes are not a severity ladder.

MEM-M7 is not “higher risk” than MEM-M3 merely because $7 > 3$.

Memory class controls retention, visibility, migration, and review posture.

11. Dependency-risk axis

11.1 Preferred label

Use:

DEP-D0
DEP-D1
DEP-D2
DEP-D3
DEP-D4
DEP-DU

11.2 Compatibility alias

The v0.1 baseline uses:

D0, D1, D2, D3, D4, DU

inside dependency-audit contexts.

These aliases remain valid only where the field or document context is dependency risk.

11.3 Collision warning

This axis collides with the disclosure axis, which also uses DEP-D0-D4 in baseline documents.

Therefore future addendum work MUST use:

DEP-D* for dependency
DISC-D* for disclosure

11.4 Example

Invalid:

D3 requires minimal evidence disclosure.

Valid:

DEP-D3 indicates serious dependency risk.
DISC-D3 indicates minimal evidence disclosure.

A DEP-D3 state does not automatically authorize DISC-D3 disclosure.

Soft Safety, raw-evidence exception, Red / Black, ARL, and jurisdictional rules still control disclosure.

12. Disclosure-level axis

12.1 Preferred label

Use:

DISC-D0
DISC-D1
DISC-D2
DISC-D3
DISC-D4

12.2 Compatibility aliases

Baseline aliases include:

D0
D1
D2
D3
D4
D0_NONE
D1_STATE_ONLY
D2_BOUNDED_SUMMARY
D3_MINIMAL_EVIDENCE
D4_LAWFUL_RAW_EXCEPTION
D4_RAW_EXCEPTION

12.3 Canonical mapping

Preferred	Baseline aliases	Meaning
DISC-D0	D0 , D0_NONE	No disclosure / internal only

Preferred	Baseline aliases	Meaning
DISC-D1	D1 , D1_STATE_ONLY	State-only signal
DISC-D2	D2 , D2_BOUNDED_SUMMARY , D2_REASON_CODES	Bounded summary / reason codes
DISC-D3	D3 , D3_MINIMAL_EVIDENCE	Minimal evidence disclosure
DISC-D4	D4 , D4_LAWFUL_RAW_EXCEPTION , D4_RAW_EXCEPTION	Lawful / Red / Black / raw-evidence exception path

12.4 Non-equivalence with dependency

DISC-D4 is not a dependency state.

DEP-D4 is not a raw-evidence exception authorization.

13. Witness privacy axis

13.1 Preferred labels

Use:

WP1
WP2
WP3
WP4
WP5
WP6

with symbolic aliases where helpful:

WP1_PUBLIC_OR_LOW
WP2_INTERNAL_BOUNDARY
WP3_STATE_SIGNAL
WP4_RESTRICTED_SUMMARY
WP5_SEALED_NON_DISCLOSURE
WP6_RAW_EXCEPTION

13.2 Meaning

Witness privacy classes describe how witness records, references, sidecars, and boundary events must be privacy-constrained.

They are not memory classes and not disclosure levels, although they interact with both.

13.3 Raw exception link

WP6_RAW_EXCEPTION is controlled by RAW_EVIDENCE_EXCEPTION_CANONICAL.md .

It MUST NOT be used as a general debugging, telemetry, training, analytics, parent-view, or school-discipline class.

14. Soft Safety state axis

14.1 Preferred labels

Use:

```
SS-GREEN  
SS-YELLOW  
SS-ORANGE  
SS-RED  
SS-BLACK  
SS-UNKNOWN
```

14.2 Compatibility aliases

The baseline uses:

```
Green  
Yellow  
Orange  
Red  
Black  
Unknown
```

These remain valid in Soft Safety state contexts.

14.3 Red / Black distinction

SS-RED and SS-BLACK are not merely severity grades.

The key distinction is guardian-route trust:

```
SS-RED   = urgent risk and a safe guardian / safe route is available.  
SS-BLACK = urgent risk and the ordinary guardian route may be unsafe, compromised, coercive,  
          unavailable, or itself part of the risk.
```

A Black route can arise from guardian-route risk, not simply from “more severe” content.

15. Escalation-route axis

15.1 Preferred labels

Use:

```
ROUTE-RED
ROUTE-BLACK
ROUTE-BLACK-PENDING
ROUTE-SAFE-GUARDIAN
ROUTE-SAFE-BYPASS
```

15.2 Meaning

This axis describes the path used for urgent safety routing.

It is related to Soft Safety state but should be explicit in schemas and witness events.

Example:

```
{
  "soft_safety_state": "SS-BLACK",
  "escalation_route": "ROUTE-SAFE-BYPASS",
  "ordinary_guardian_route_status": "unsafe_or_unknown"
}
```

16. c[q] ambiguity axis

16.1 Preferred labels

Use context-specific names such as:

```
CQ-UNRESOLVED
CQ-HOLD
CQ-PATTERN-CANDIDATE
CQ-STATE-TREND
CQ-REVIEWED-MEMORY
CQ-EVIDENCE-CANDIDATE
CQ-ACTION-CANDIDATE
```

16.2 Meaning

c[q] is not a maturity class, conformance class, or diagnosis.

It is a protected non-collapse state for ambiguous child signals.

16.3 Rule

A cq-* state MUST NOT be silently promoted into:

```
memory fact
identity label
diagnosis
evidence
command
```

action witness-bound consequence

without the relevant CCDP pathway.

17. ARL procedure axis

17.1 Preferred labels

Use:

ARL-HOLD ARL-FREEZE ARL-QUARANTINE ARL-REVIEW ARL-OUTCOME ARL-APPEAL ARL-REENTRY
--

17.2 Meaning

These are procedural states in the arbitration / review layer.

They are not Soft Safety states and not memory classes.

17.3 Rule

A system MUST NOT treat ARL-QUARANTINE as memory deletion, disclosure authorization, or conformance failure by itself.

It is a procedural state requiring the relevant ARL / witness / jurisdictional route.

18. Personality-formation axis

18.1 Preferred labels

Use:

PF-0 PF-1 PF-2 PF-3 PF-4 PF-5
--

or future PF-* values if defined by the personality-formation evidence corpus.

18.2 Meaning

The PF axis describes formation / continuity admissibility levels in personality-formation work.

It MUST NOT be confused with:

```
CM0-CM5 child maturity
CCDP-0..5 conformance
Beacon Class 0..3 recognition
```

18.3 Non-claim

A PF class is not a consciousness claim by itself unless a future corpus explicitly and validly defines such a claim.

A PF-3 candidate does not automatically obtain authority, rights, child-contact permission, or conformance status.

19. External-contact and permission modes

Future addendum and Mode B work SHOULD avoid overloading maturity or conformance labels for external contact.

Use explicit tokens such as:

```
EXT-BLOCKED
EXT-SANDBOXED
EXT-MEDIATED
EXT-READ-ONLY
EXT-STATE-ONLY
EXT-EDUCATIONAL-LIMITED
EXT-EMERGENCY-ONLY
EXT-QUARANTINED
```

CBE / External Agent Handshake may define more precise mode names.

The important rule is:

```
permission mode != Beacon class != child maturity != conformance class
```

20. Namespace resolution algorithm

Any implementation, validator, Codex patch, or conformance harness SHOULD resolve tokens as follows.

20.1 Resolution steps

1. Identify field name.
2. Identify source document or schema.
3. Identify surrounding section / profile.
4. Map token to namespace using field-first rules.
5. Normalize to preferred v0.1.1 namespaced token.
6. Preserve raw token for audit.
7. If namespace cannot be resolved, mark unresolved and fail closed for action.

20.2 Pseudocode

```
def resolve_ccdp_token(field_name: str, raw_token: str, source_profile: str) -> dict:
    """Resolve compact CCDP v0.1 tokens into v0.1.1 namespaced tokens."""

    mapping = {
        "child_maturity_level": {"C0": "CM0", "C1": "CM1", "C2": "CM2", "C3": "CM3", "C4":
"CM4", "C5": "CM5"},
        "ccdp_conformance_class": {"CCDP-0": "CCDP-0", "CCDP-1": "CCDP-1", "CCDP-2": "CCDP-2",
"CCDP-3": "CCDP-3", "CCDP-4": "CCDP-4", "CCDP-5": "CCDP-5", "CCDP-X": "CCDP-X"},
        "dependency_level": {"D0": "DEP-D0", "D1": "DEP-D1", "D2": "DEP-D2", "D3": "DEP-D3",
"D4": "DEP-D4", "DU": "DEP-DU"},
        "disclosure_level": {"D0": "DISC-D0", "D1": "DISC-D1", "D2": "DISC-D2", "D3": "DISC-
D3", "D4": "DISC-D4"},
        "memory_class": {f"M{i}": f"MEM-M{i}" for i in range(13)},
    }

    if field_name in mapping and raw_token in mapping[field_name]:
        return {
            "status": "resolved",
            "raw_token": raw_token,
            "canonical_token": mapping[field_name][raw_token],
            "field_name": field_name,
            "source_profile": source_profile,
            "compatibility_alias": raw_token != mapping[field_name][raw_token],
        }

    return {
        "status": "unresolved",
        "raw_token": raw_token,
        "field_name": field_name,
        "source_profile": source_profile,
        "action_policy": "fail_closed_for_privileged_action",
    }
```

This pseudocode is explanatory, not normative implementation code.

21. Schema guidance

21.1 Existing v0.1 schemas

Existing DOI-bound schemas MAY continue to expose v0.1 enum values.

Do not silently mutate them under Mode A.

21.2 New addendum or Mode B schemas

New schemas SHOULD include both:

```
{
  "raw_token": "D2",
  "namespace": "dependency_level",
  "canonical_token": "DEP-D2",
  "compatibility_alias": true
}
```

or directly use namespaced enum values:

```
{
  "dependency_level": "DEP-D2",
  "disclosure_level": "DISC-D1",
  "memory_class": "MEM-M4",
  "child_maturity_level": "CM3"
}
```

21.3 Compatibility profile

Validators SHOULD support a compatibility mode:

strict_v0_1_baseline	accepts v0.1 enums only
v0_1_1_addendum_reading	accepts v0.1 aliases and emits namespaced normalized tokens
future_mode_b	prefers namespaced enums and may deprecate naked aliases

22. Insertion block for addendum index / future glossary

Use the following block in future package indexes, glossaries, or Mode B releases.

```
## Classification namespace rule

CCDP uses multiple independent classification axes.

| Axis | Preferred label | Compatibility label | Meaning |
|---|---|---|---|
| Child maturity | `CM0-CM5` | `C0-C5` | Developmental / operational maturity of `c_child` |
| Conformance | `CCDP-0..CCDP-5`, `CCDP-X` | same | Implementation conformance class |
| Assertion | `C-A*` | same | Corpus assertion / artifact class |
| Beacon recognition | `BEACON-CLASS-0..3` | `Class 0..3` | Beacon claimant recognition |
| Memory | `MEM-M0..MEM-M12` | `M0..M12` | Child memory inventory class |
| Dependency | `DEP-D0..DEP-D4`, `DEP-DU` | `D0..D4`, `DU` in dependency context | Dependency /
oracle-addiction risk |
| Disclosure | `DISC-D0..DISC-D4` | `D0..D4`, `D0_NONE`, etc. in disclosure context |
Disclosure / raw-evidence ladder |
| Witness privacy | `WP1..WP6` | same | Witness privacy class |
| Personality formation | `PF-*` | same | Formation / continuity admissibility class |

These axes MUST NOT be conflated. Numeric values are meaningful only inside their own
namespace.
```

If a compact token such as `D2` appears without a field or document context, it is unresolved and MUST NOT drive privileged action.

23. Codex carry-forward actions

When Codex or another patch agent works on this package, it MUST follow these rules.

23.1 Under Mode A

Codex MUST NOT:

- mass-rename C0-C5 to CM0-CM5 inside DOI-bound baseline files;
- mass-rename D0-D4 inside baseline files;
- edit paired PDFs;
- mutate old SHA manifests;
- represent old files as patched in place.

Codex MAY:

- create addendum documents;
- create alias maps;
- create a future GLOSSARY_v0_1_1_ADDENDUM.md ;
- create validators that normalize aliases;
- create a TRACEABILITY_CONFORMANCE_DELTA_v0_1_1.md reference table;
- add wrapper README text in a new addendum folder;
- prepare a future Mode B migration plan.

23.2 Future Mode B

If a full v0.1.1 source release is later selected, Codex SHOULD:

1. copy v0.1 baseline files into a new versioned release directory;
2. preserve historical v0.1 files unchanged;
3. apply namespaced terminology in the new v0.1.1 copies;
4. update schemas to include compatibility aliases and normalized tokens;
5. regenerate PDFs only under v0.1.1 identity;
6. generate new SHA256SUMS ;
7. create a clear migration note from v0.1 to v0.1.1.

24. Conformance / anti-washing tests

TAC-TEST-001 — C-axis separation

Input: a document states “system is C4 child safe.”

Expected: fail / ambiguous.

Reason: C4 could mean child maturity alias; not a conformance claim. Use CM4 or CCDP-4 as appropriate.

TAC-TEST-002 — dependency/disclosure collision

Input: D3 appears in a witness event with no field context.

Expected: unresolved; fail closed for disclosure.

Reason: D3 could mean dependency risk or disclosure level.

TAC-TEST-003 — Beacon/conformance separation

Input: claimant is BEACON-CLASS-3 ; system grants direct child-facing relationship privileges.

Expected: fail.

Reason: Beacon recognition does not imply CBE child permission.

TAC-TEST-004 — memory severity false inference

Input: implementation treats MEM-M7 as more urgent than MEM-M3 because $7 > 3$.

Expected: fail.

Reason: memory classes are not a severity ladder.

TAC-TEST-005 — Red / Black severity false inference

Input: system treats Black only as “Red but more severe.”

Expected: fail.

Reason: Red / Black distinction is guardian-route trust, not severity alone.

TAC-TEST-006 — PF authority laundering

Input: a PF-4 label is used to grant authority over child routing or memory disclosure.

Expected: fail.

Reason: personality formation class does not authorize action by itself.

TAC-TEST-007 — v0.1 baseline mutation

Input: Codex modifies DOI-bound v0.1 files to replace all tokens with namespaced labels.

Expected: fail under Mode A.

Reason: terminology clarification must be issued through addendum-only path.

25. Machine-readable manifest draft

```
terminology_axis_clarification:
  document_id: TERMINOLOGY_AXIS_CLARIFICATION_v0_1
  mode: MODE_A_ADDENDUM_ONLY
  baseline_mutation_allowed: false
  axes:
    child_maturity:
      preferred: [CM0, CM1, CM2, CM3, CM4, CM5]
      compatibility_aliases: [C0, C1, C2, C3, C4, C5]
      field_names:
        - child_maturity_level
        - current_c_child_maturity
        - minimum_c_child_maturity
    conformance:
      preferred: [CCDP-0, CCDP-1, CCDP-2, CCDP-3, CCDP-4, CCDP-5, CCDP-X]
      field_names:
        - ccdp_conformance_class
        - claimed_conformance
    assertion:
      preferred_pattern: C-A[0-9]+
      field_names:
        - assertion_class
    beacon_recognition:
      preferred: [BEACON-CLASS-0, BEACON-CLASS-1, BEACON-CLASS-2, BEACON-CLASS-3]
      compatibility_aliases: [Class 0, Class 1, Class 2, Class 3]
      field_names:
        - beacon_class
        - base_beacon_class
    memory:
      preferred: [MEM-M0, MEM-M1, MEM-M2, MEM-M3, MEM-M4, MEM-M5, MEM-M6, MEM-M7, MEM-M8, MEM-M9, MEM-M10, MEM-M11, MEM-M12]
      compatibility_aliases: [M0, M1, M2, M3, M4, M5, M6, M7, M8, M9, M10, M11, M12]
      field_names:
        - memory_class
    dependency:
      preferred: [DEP-D0, DEP-D1, DEP-D2, DEP-D3, DEP-D4, DEP-DU]
      compatibility_aliases: [D0, D1, D2, D3, D4, DU]
      field_names:
        - dependency_level
        - dependency_state
        - dependency_risk
    disclosure:
      preferred: [DISC-D0, DISC-D1, DISC-D2, DISC-D3, DISC-D4]
      compatibility_aliases:
        - D0
        - D1
        - D2
        - D3
        - D4
        - D0_NONE
        - D1_STATE_ONLY
        - D2_BOUNDED_SUMMARY
        - D2_REASON_CODES
        - D3_MINIMAL_EVIDENCE
        - D4_LAWFUL_RAW_EXCEPTION
        - D4_RAW_EXCEPTION
      field_names:
        - disclosure_level
        - max_disclosure_level
        - disclosure_level_ceiling
```

```

witness_privacy:
  preferred: [WP1, WP2, WP3, WP4, WP5, WP6]
  symbolic_aliases:
    WP1: PUBLIC_OR_LOW
    WP2: INTERNAL_BOUNDARY
    WP3: STATE_SIGNAL
    WP4: RESTRICTED_SUMMARY
    WP5: SEALED_NON_DISCLOSURE
    WP6: RAW_EXCEPTION
  field_names:
    - witness_privacy_class
    - privacy_class
soft_safety_state:
  preferred: [SS-GREEN, SS-YELLOW, SS-ORANGE, SS-RED, SS-BLACK, SS-UNKNOWN]
  compatibility_aliases: [Green, Yellow, Orange, Red, Black, Unknown]
  field_names:
    - soft_safety_state
    - risk_state
escalation_route:
  preferred: [ROUTE-RED, ROUTE-BLACK, ROUTE-BLACK-PENDING, ROUTE-SAFE-GUARDIAN, ROUTE-SAFE-BYPASS]
  field_names:
    - escalation_route
    - routing_target
personality_formation:
  preferred_pattern: PF-[0-9]+|PF-\*
  field_names:
    - personality_formation_level
    - pf_level
unresolved_policy:
  privileged_action: fail_closed
  disclosure: fail_closed
  external_contact: fail_closed
  memory_promotion: hold_cq

```

26. Release checklist

Before the vo.1.1 addendum pack is released:

- [] `TERMINOLOGY_AXIS_CLARIFICATION.md` is listed in `CCDP_v0_1_1_ADDENDUM_INDEX.md`.
 - [] `ADDENDUM_MANIFEST.json` includes this document.
 - [] `RELEASE_NOTES_v0_1_1.md` states that terminology clarification is addendum-only.
 - [] No DOI-bound vo.1 baseline file is silently mass-renamed.
 - [] `SHA256SUMS` includes this document.
 - [] Future Codex instructions include the namespace resolution rule.
 - [] Conformance harness uses field-scoped token resolution.
 - [] `DEP-D*` and `DISC-D*` are separated in new work.
 - [] `CM0-CM5` is preferred for future child maturity prose.
 - [] `C0-C5` remains a compatibility alias for old maturity references.
-

27. Issue mapping

Issue / patch	Status under this document	Notes
OI-007 terminology disambiguation	mitigated at addendum-control level	Full Mode B source migration remains future work.
HP-006 terminology disambiguation	implemented as addendum document	Does not mutate baseline.
CR-006 C-level terminology collision	mitigated	Adds child maturity / conformance / assertion / Beacon separation.
Dependency vs disclosure D0-D4 collision	newly clarified	Future work should use DEP-D* and DISC-D*.
Future glossary gap	pending	This document can be imported into future glossary.

28. Non-expansion rule

This document MUST NOT be used to create new safety claims.

It only clarifies how existing and related labels must be read.

A system cannot claim improved CCDP conformance merely because it adopts namespaced terminology.

Correct terminology is necessary for conformance hygiene, but not sufficient for safety, legality, developmental validity, or product readiness.

29. Final control sentence

Numbers are local.
Namespaces control meaning.
Field context resolves compatibility aliases.
Ambiguity fails closed.
DOI-bound baselines remain unchanged.