BASIC SALES SUMMARY

Sample Superstore Dataset

TASK 14 | DATA ANALYTICS INTERNSHIP

Task	Task 14 — Basic Sales Summary
Organization	Veda Technologies
Dataset	Sample Superstore
Tool	Microsoft Excel
Deliverables	Summary sheet and three KPI indicators

This report describes the process for calculating total sales, average sales, and transaction count from the Sample Superstore dataset in Microsoft Excel.

Results note: The dataset was not attached to this request, so actual KPI values are not invented. Fill the results table using your Excel workbook before submitting.

1. Objective

Build a basic business summary using three key performance indicators (KPIs): total sales, average sales, and transaction count. Present them clearly in a dedicated Excel summary sheet.

2. Dataset Overview

Sample Superstore commonly includes order, date, customer, product, sales, quantity, discount, and profit fields. Exact columns and row counts vary by dataset version. The Sales column is used to calculate total and average sales.

3. Tools Used

Microsoft Excel is used to inspect the dataset, apply formulas, format KPI indicators, and prepare the summary sheet. Formatting the data as an Excel Table makes structured formulas easier to maintain.

4. KPI Definitions and Formulas

KPI	Definition	Example formula
Total Sales	Sum of all Sales values	=SUM(Superstore[Sales])
Average Sales	Average Sales value per row	=AVERAGE(Superstore[Sales])
Transaction Count	Count of nonblank Order ID entries	=COUNTA(Superstore[Order ID])

If the dataset is not an Excel Table named Superstore, use actual cell ranges, such as =SUM(H2:H9995), adjusting the column and last row to fit your workbook.

Counting note: COUNTA counts nonblank Order ID rows, not unique orders. One order can contain several product rows. If unique orders are required and your Excel version supports UNIQUE, use =COUNTA(UNIQUE(Superstore[Order ID])).

5. Workflow

Step	Action
1	Import the Sample Superstore dataset into Excel.
2	Inspect column names and check for blank or invalid Sales values.
3	Format the dataset as an Excel Table named Superstore.
4	Calculate total sales, average sales, and transaction count.
5	Create a separate summary sheet with three labeled KPI cells.
6	Format sales as currency and transaction count as a whole number.
7	Verify results against the source data or Excel status bar.

6. Results Summary

KPI	Calculated value
Total Sales	_____
Average Sales	_____
Transaction Count (rows with Order ID)	_____

Unique Order Count (if required)	_____

Complete this table using the actual figures from your Excel summary sheet. Values are intentionally blank until the dataset is calculated.

7. Summary Sheet Design and Optional Visualizations

Arrange the three KPIs in separate, consistently formatted areas. Use currency formatting for sales values and a whole-number format for counts. Optional charts include a monthly sales trend line chart or a sales-by-category bar chart; charts are not required by the task brief.

8. Key Learnings

This task reinforces Excel formula usage, KPI interpretation, basic data validation, and clear business reporting. It also highlights the difference between counting transaction rows and counting unique orders.

9. Conclusion

The Basic Sales Summary presents a concise view of the Sample Superstore dataset through total sales, average sales, and transaction count. Clear definitions, accurate formulas, and verification help ensure reliable results.