# Aim:

# **Source Code:**

#### BSTmain2.c

```
#include<stdio.h>
#include<stdlib.h>
#include "BSTDeleteAndPreOrder.c"
void main() {
   int x, op;
   BSTNODE root = NULL;
   while(1)
   {
      printf("1.Insert 2.Delete 3.Preorder Traversal 4.Exit\n");
      printf("Enter your option : ");
      scanf("%d", &op);
      switch(op) {
         case 1: printf("Enter an element to be inserted : ");
               scanf("%d", &x);
               root = insertNodeInBST(root,x);
               break;
         case 2: printf("Enter an element to be deleted : ");
               scanf("%d", &x);
               root = deleteNodeInBST(root,x);
               break;
         case 3:
               if(root == NULL) {
                  printf("Binary Search Tree is empty.\n");
               }
               else {
                  printf("Elements of the BST (pre-order traversal): ");
                  preorderInBST(root);
                  printf("\n");
               }
               break;
         case 4: exit(0);
      }
   }
}
```

Exp. Name: Implementation of BST Operations - Deletion and Pre-order traversal

# BSTDeleteAndPreOrder.c

```
struct node {
   int data;
   struct node *left, *right;
};
typedef struct node * BSTNODE;
BSTNODE newNodeInBST(int item) {
```

```
BSTNODE temp = (BSTNODE)malloc(sizeof(struct node));
   temp->data = item;
   temp->left = temp->right = NULL;
   return temp;
}
void preorderInBST(BSTNODE root) {
   if(root!=NULL)
{
printf("%d ",root->data);
preorderInBST(root->left);
preorderInBST(root->right);
}
}
BSTNODE insertNodeInBST(BSTNODE node, int ele) {
   if (node == NULL) {
      printf("Successfully inserted.\n");
      return newNodeInBST(ele);
   }
   if (ele < node->data)
      node->left = insertNodeInBST(node->left,ele);
   else if (ele > node->data)
      node->right = insertNodeInBST(node->right,ele);
   else
      printf("Element already exists in BST.\n");
   return node;
}
BSTNODE minValueNode(BSTNODE node) {
BSTNODE curr=node;
while(curr&&curr->left!=NULL)
   curr=curr->left;
}
}
BSTNODE deleteNodeInBST(BSTNODE root, int ele) {
if(root==NULL)
   printf("Cannot find %d in the binary search tree.\n");
   return root;
}
if(ele<root->data)
root->left=deleteNodeInBST(root->left,ele);
else if(ele>root->data)
root->right=deleteNodeInBST(root->right,ele);
else
   if(root->left==NULL)
   BSTNODE temp=root->right;
   printf("Deleted %d from binary search tree.\n",root->data);
free(root);
return temp;
else if(root->right==NULL)
```

```
BSTNODE temp=root->left;
   printf("Deleted %d from binary tree.\n",root->data);
}
else
{
   BSTNODE temp=minValueNode(root);
   root->data=temp->data;
   root->right=deleteNodeInBST(root->right,ele);
}
}
}
```

# Execution Results - All test cases have succeeded!

```
Test Case - 1
User Output
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 1
Enter your option : 1
Enter an element to be inserted : 56
Successfully inserted. 2
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 2
Enter your option : 2
Enter an element to be deleted :
Cannot find 35 in the binary search tree. 3
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 3
Enter your option : 3
Elements of the BST (pre-order traversal): 56 4
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 4
Enter your option : 4
```

```
Test Case - 2
User Output
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 1
Enter your option : 1
Enter an element to be inserted : 25
Successfully inserted. 1
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 1
Enter your option : 1
Enter an element to be inserted : 65
Successfully inserted. 2
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 2
Enter your option : 2
Enter an element to be deleted : 65
Deleted 65 from binary search tree. 3
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 3
Enter your option : 3
Elements of the BST (pre-order traversal): 25 4
1.Insert 2.Delete 3.Preorder Traversal 4.Exit 4
Enter your option : 4
```