

pEngine

Generated by Doxygen 1.8.17

1 Hierarchical Index	1
1.1 Class Hierarchy	1
2 Class Index	2
2.1 Class List	2
3 File Index	3
3.1 File List	3
4 Class Documentation	4
4.1 Behavior Class Reference	4
4.1.1 Detailed Description	6
4.1.2 Constructor & Destructor Documentation	6
4.1.3 Member Function Documentation	7
4.2 Camera Class Reference	13
4.2.1 Detailed Description	15
4.2.2 Constructor & Destructor Documentation	15
4.2.3 Member Function Documentation	16
4.3 Component Class Reference	23
4.3.1 Detailed Description	24
4.3.2 Member Enumeration Documentation	24
4.3.3 Constructor & Destructor Documentation	25
4.3.4 Member Function Documentation	25
4.4 Editor Class Reference	26
4.4.1 Detailed Description	27
4.4.2 Member Function Documentation	28
4.5 Engine Class Reference	42
4.5.1 Detailed Description	43
4.5.2 Member Function Documentation	43
4.6 File_Reader Class Reference	50
4.6.1 Detailed Description	51
4.6.2 Member Function Documentation	51
4.7 File_Writer Class Reference	58
4.7.1 Detailed Description	59
4.7.2 Constructor & Destructor Documentation	59
4.7.3 Member Function Documentation	59
4.8 Graphics Class Reference	63
4.8.1 Detailed Description	64
4.8.2 Constructor & Destructor Documentation	64
4.8.3 Member Function Documentation	64

4.9 Model Class Reference	70
4.9.1 Detailed Description	72
4.9.2 Constructor & Destructor Documentation	72
4.9.3 Member Function Documentation	73
4.10 Model_Data Class Reference	77
4.10.1 Detailed Description	78
4.10.2 Constructor & Destructor Documentation	78
4.10.3 Member Function Documentation	79
4.11 Model_Data_Manager Class Reference	84
4.11.1 Detailed Description	85
4.11.2 Member Function Documentation	85
4.12 Object Class Reference	87
4.12.1 Detailed Description	89
4.12.2 Constructor & Destructor Documentation	89
4.12.3 Member Function Documentation	90
4.13 Object_Manager Class Reference	98
4.13.1 Detailed Description	99
4.13.2 Member Function Documentation	99
4.14 Physics Class Reference	106
4.14.1 Detailed Description	108
4.14.2 Constructor & Destructor Documentation	108
4.14.3 Member Function Documentation	109
4.15 Random Class Reference	118
4.15.1 Detailed Description	118
4.15.2 Member Function Documentation	118
4.16 Shader Class Reference	121
4.16.1 Detailed Description	122
4.16.2 Member Function Documentation	122
4.17 Texture Class Reference	127
4.17.1 Detailed Description	128
4.17.2 Constructor & Destructor Documentation	128
4.17.3 Member Function Documentation	129
4.18 Texture_Manager Class Reference	132
4.18.1 Detailed Description	132
4.18.2 Member Function Documentation	132
4.19 Trace Class Reference	135
4.19.1 Detailed Description	135
4.19.2 Member Function Documentation	136
4.20 Transform Class Reference	137

4.20.1 Detailed Description	139
4.20.2 Constructor & Destructor Documentation	139
4.20.3 Member Function Documentation	140
4.21 Vector3_Func Class Reference	146
4.21.1 Detailed Description	147
4.21.2 Member Function Documentation	147
5 File Documentation	151
5.1 behavior.cpp File Reference	151
5.1.1 Detailed Description	151
5.2 behavior.hpp File Reference	151
5.2.1 Detailed Description	152
5.3 camera.cpp File Reference	152
5.3.1 Detailed Description	152
5.4 camera.hpp File Reference	153
5.4.1 Detailed Description	153
5.5 component.cpp File Reference	153
5.5.1 Detailed Description	153
5.6 component.hpp File Reference	154
5.6.1 Detailed Description	154
5.7 editor.cpp File Reference	154
5.7.1 Detailed Description	155
5.8 editor.hpp File Reference	155
5.8.1 Detailed Description	155
5.9 engine.cpp File Reference	156
5.9.1 Detailed Description	156
5.10 engine.hpp File Reference	156
5.10.1 Detailed Description	157
5.11 file_reader.cpp File Reference	157
5.11.1 Detailed Description	157
5.12 file_reader.hpp File Reference	158
5.12.1 Detailed Description	158
5.13 file_writer.cpp File Reference	158
5.13.1 Detailed Description	158
5.14 file_writer.hpp File Reference	159
5.14.1 Detailed Description	159
5.15 graphics.cpp File Reference	159
5.15.1 Detailed Description	160
5.16 graphics.hpp File Reference	160

5.16.1 Detailed Description	160
5.17 main.cpp File Reference	161
5.17.1 Detailed Description	161
5.17.2 Function Documentation	161
5.18 model.cpp File Reference	162
5.18.1 Detailed Description	162
5.19 model.hpp File Reference	162
5.19.1 Detailed Description	163
5.20 model_data.cpp File Reference	163
5.20.1 Detailed Description	163
5.21 model_data.hpp File Reference	164
5.21.1 Detailed Description	164
5.22 model_data_manager.cpp File Reference	164
5.22.1 Detailed Description	165
5.23 model_data_manager.hpp File Reference	165
5.23.1 Detailed Description	165
5.24 object.cpp File Reference	166
5.24.1 Detailed Description	166
5.25 object.hpp File Reference	166
5.25.1 Detailed Description	167
5.26 object_manager.cpp File Reference	167
5.26.1 Detailed Description	167
5.27 object_manager.hpp File Reference	168
5.27.1 Detailed Description	168
5.28 physics.cpp File Reference	168
5.28.1 Detailed Description	169
5.29 physics.hpp File Reference	169
5.29.1 Detailed Description	169
5.30 random.cpp File Reference	170
5.30.1 Detailed Description	170
5.31 random.hpp File Reference	170
5.31.1 Detailed Description	171
5.32 shader.cpp File Reference	171
5.32.1 Detailed Description	171
5.33 shader.hpp File Reference	172
5.33.1 Detailed Description	172
5.34 texture.cpp File Reference	172
5.34.1 Detailed Description	173
5.35 texture.hpp File Reference	173

5.35.1 Detailed Description	173
5.36 texture_manager.cpp File Reference	174
5.36.1 Detailed Description	174
5.37 texture_manager.hpp File Reference	174
5.37.1 Detailed Description	175
5.38 trace.cpp File Reference	175
5.38.1 Detailed Description	175
5.39 trace.hpp File Reference	176
5.39.1 Detailed Description	176
5.40 transform.cpp File Reference	176
5.40.1 Detailed Description	176
5.41 transform.hpp File Reference	177
5.41.1 Detailed Description	177
5.42 vector3_func.cpp File Reference	177
5.42.1 Detailed Description	177
5.43 vector3_func.hpp File Reference	178
5.43.1 Detailed Description	178

Index	179
--------------	------------

1 Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Camera	13
Component	23
Behavior	4
Model	70
Physics	106
Transform	137
Editor	26
Engine	42
File_Reader	50
File_Writer	58

Graphics	63
Model_Data	77
Model_Data_Manager	84
Object	87
Object_Manager	98
Random	118
Shader	121
Texture	127
Texture_Manager	132
Trace	135
Vector3_Func	146

2 Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Behavior	4
Camera	13
Component	23
Editor	26
Engine	42
File_Reader	50
File_Writer	58
Graphics	63
Model	70
Model_Data	77
Model_Data_Manager	84
Object	87
Object_Manager	98
Physics	106

Random	118
Shader	121
Texture	127
Texture_Manager	132
Trace	135
Transform	137
Vector3_Func	146

3 File Index

3.1 File List

Here is a list of all documented files with brief descriptions:

behavior.cpp	151
behavior.hpp	151
camera.cpp	152
camera.hpp	153
component.cpp	153
component.hpp	154
editor.cpp	154
editor.hpp	155
engine.cpp	156
engine.hpp	156
file_reader.cpp	157
file_reader.hpp	158
file_writer.cpp	158
file_writer.hpp	159
graphics.cpp	159
graphics.hpp	160
main.cpp	161
model.cpp	162


model.hpp	162
model_data.cpp	163
model_data.hpp	164
model_data_manager.cpp	164
model_data_manager.hpp	165
object.cpp	166
object.hpp	166
object_manager.cpp	167
object_manager.hpp	168
physics.cpp	168
physics.hpp	169
random.cpp	170
random.hpp	170
shader.cpp	171
shader.hpp	172
texture.cpp	172
texture.hpp	173
texture_manager.cpp	174
texture_manager.hpp	174
trace.cpp	175
trace.hpp	176
transform.cpp	176
transform.hpp	177
vector3_func.cpp	177
vector3_func.hpp	178

4 Class Documentation

4.1 Behavior Class Reference

```
#include <behavior.hpp>
```

Inheritance diagram for Behavior:



Public Member Functions

- [Behavior](#) ()
Creates an empty [Behavior](#) object.
- [Behavior](#) (const [Behavior](#) &other)
Copy constructor.
- [Behavior](#) ([File_Reader](#) &reader)
Creates [Behavior](#) object using file.
- [Behavior](#) * [Clone](#) () const
Clones current [Behavior](#) object.
- [~Behavior](#) ()
Deletes all of the lua states.
- void [Update](#) ()
Update for [Behavior](#) object. Calls [Behavior](#) manager giving list of its behaviors.
- void [Read](#) ([File_Reader](#) &reader)
Reads in the behaviors to be used.
- void [Write](#) ([File_Writer](#) &writer)
Gives the names of each lua file to the writer.
- void [SetupClassesForLua](#) ()
Setups up the interface between the engine and the lua files.
- std::vector< std::string > & [GetScripts](#) ()
Returns list of lua filenames.
- void [ClassSetup](#) (sol::state *state)
Sends engine variables and functions to lua.
- bool [SwitchScript](#) (unsigned scriptNum, std::string newScriptName)
Switches one script to another (replace)
- bool [AddScript](#) (std::string newScriptName)
Attaching new script to the object.
- bool [CheckIfCopy](#) (std::string newScriptName)
Checks if the script is already attached to the object.
- void [Clear](#) ()
Clears states and state filenames from object.

Static Public Member Functions

- static [CType](#) [GetCType](#) ()
Gets the CType of [Behavior](#) (used in [Object::GetComponent<>\(\)](#))

Private Attributes

- `std::vector< std::string > scripts`
Names of the lua scripts being used.
- `std::vector< sol::state * > states`
States of each lua script.

Additional Inherited Members

4.1.1 Detailed Description

[Behavior](#) class

Definition at line 30 of file `behavior.hpp`.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 [Behavior\(\)](#) [1/3] `Behavior::Behavior ()`

Creates an empty [Behavior](#) object.

Definition at line 29 of file `behavior.cpp`.

```
29 : Component(CType::CBehavior) {}
```

Referenced by `Clone()`.

4.1.2.2 [Behavior\(\)](#) [2/3] `Behavior::Behavior (` `const Behavior & other)`

Copy constructor.

Parameters

<i>other</i>	Behavior object to copy
--------------	---

Definition at line 36 of file `behavior.cpp`.

```
36                                     : Component(CType::CBehavior) {  
37     *this = other;  
38 }
```

4.1.2.3 Behavior() [3/3] Behavior::Behavior (File_Reader & reader)

Creates Behavior object using file.

Parameters

<i>reader</i>	Data from file
---------------	----------------

Definition at line 45 of file behavior.cpp.

```
45                                     : Component(CType::CBehavior) {
46     Read(reader);
47 }
```

References Read().

4.1.2.4 ~Behavior() Behavior::~~Behavior ()

Deletes all of the lua states.

Definition at line 62 of file behavior.cpp.

```
62     {
63     Clear();
64 }
```

References Clear().

4.1.3 Member Function Documentation

4.1.3.1 AddScript() bool Behavior::AddScript (std::string newScriptName)

Attaching new script to the object.

Parameters

<i>newScriptName</i>	
----------------------	--

Returns

true

false

Definition at line 233 of file behavior.cpp.

```

233                                     {
234     // Checking if this script is already attached
235     if (newScriptName.find(".lua") == std::string::npos) return false;
236     if (CheckIfCopy(newScriptName)) return false;
237     // Setting up new lua state
238     sol::state* state = new sol::state;
239     state->open_libraries(sol::lib::base, sol::lib::math, sol::lib::io, sol::lib::string);
240     states.emplace_back(state);
241     // Adding new script filename to list
242     scripts.emplace_back(newScriptName);
243     ClassSetup(state);
244     // Setting up lua script to run
245     states.back()->script_file(scripts.back());
246     (*states.back())["Start"]();
247
248     return true;
249 }

```

References CheckIfCopy(), ClassSetup(), scripts, and states.

Referenced by Editor::Display_Scripts().

4.1.3.2 CheckIfCopy() bool Behavior::CheckIfCopy (
std::string newScriptName)

Checks if the script is already attached to the object.

Parameters

<i>newScriptName</i>	Name of script being checked
----------------------	------------------------------

Returns

true

false

Definition at line 258 of file behavior.cpp.

```

258                                     {
259     // Checking if script is the same as an existing one
260     for (std::string scriptName : scripts) {
261         if (scriptName.compare(newScriptName) == 0) return true;
262     }
263
264     // Script is not a copy
265     return false;
266 }

```

References scripts.

Referenced by AddScript(), and SwitchScript().

4.1.3.3 ClassSetup() void Behavior::ClassSetup (
sol::state * state)

Sends engine variables and functions to lua.

Parameters

state

Definition at line 149 of file behavior.cpp.

```

149 {
150     // Giving lua random functions
151     state->set_function("random_vec3", Random::random_vec3);
152     state->set_function("random_float", Random::random_float);
153
154     // Giving lua glm::vec3 wrapper class
155     sol::usertype<glm::vec3> vec3_type = state->new_usertype<glm::vec3>("vec3",
156         sol::constructors<glm::vec3>(float, float, float), glm::vec3(float)>());
157     // Giving lua glm::vec3 wrapper class variables
158     vec3_type.set("x", &glm::vec3::x);
159     vec3_type.set("y", &glm::vec3::y);
160     vec3_type.set("z", &glm::vec3::z);
161     // Giving lua glm::vec3 wrapper class functions
162     state->set_function("normalize", Vector3_Func::normalize);
163     state->set_function("distance", Vector3_Func::distance);
164     state->set_function("get_direction", Vector3_Func::get_direction);
165     state->set_function("zero_vec3", Vector3_Func::zero_vec3);
166     state->set_function("length", Vector3_Func::length);
167     state->set_function("add_float", Vector3_Func::add_float);
168     state->set_function("add_vec3", Vector3_Func::add_vec3);
169
170     state->set_function("FindObject", sol::overload(sol::resolve<Object*>(int)>(&Object_Manager::FindObject),
171         sol::resolve<Object*>(std::string)>(&Object_Manager::FindObject)));
172
173     // Giving lua physics class
174     sol::usertype<Physics> physics_type = state->new_usertype<Physics>("Physics",
175         sol::constructors<Physics>(), Physics(const Physics)>());
176     // Giving lua physics class variables
177     physics_type.set("acceleration", sol::property(Physics::GetAccelerationRef, &Physics::SetAcceleration));
178     physics_type.set("forces", sol::property(Physics::GetForcesRef, &Physics::SetForces));
179     physics_type.set("velocity", sol::property(Physics::GetVelocityRef, &Physics::SetVelocity));
180     // Giving lua physics class functions
181     physics_type.set_function("ApplyForce", &Physics::ApplyForce);
182     physics_type.set_function("UpdateGravity", &Physics::UpdateGravity);
183
184     // Giving lua transform class
185     sol::usertype<Transform> transform_type = state->new_usertype<Transform>("Transform",
186         sol::constructors<Transform>(), Transform(const Transform)>());
187     // Giving lua transform class variables
188     transform_type.set("position", sol::property(Transform::GetPositionRef,
189         &Transform::SetPosition));
189     transform_type.set("rotation", sol::property(Transform::GetRotationRef,
190         &Transform::SetRotation));
190     transform_type.set("scale", sol::property(Transform::GetScaleRef,
191         &Transform::SetScale));
191     transform_type.set("startPosition", sol::property(Transform::GetStartPositionRef,
192         &Transform::SetStartPosition));
192
193     // Giving lua object class
194     state->set("object", GetParent());
195     sol::usertype<Object> object_type = state->new_usertype<Object>("Object",
196         sol::constructors<Object>(), Object(const Object)>());
197     // Giving lua object class variables
198     object_type.set("name", sol::property(Object::GetNameRef, &Object::SetName));
199     object_type.set("id", sol::readonly_property(Object::GetId));
200     object_type.set_function("GetPhysics", &Object::GetComponent<Physics>);
201     object_type.set_function("GetTransform", &Object::GetComponent<Transform>);
202 }

```

References [Vector3_Func::add_float\(\)](#), [Vector3_Func::add_vec3\(\)](#), [Physics::ApplyForce\(\)](#), [Vector3_Func::distance\(\)](#), [Object_Manager::FindObject\(\)](#), [Vector3_Func::get_direction\(\)](#), [Physics::GetAccelerationRef\(\)](#), [Physics::GetForcesRef\(\)](#), [Object::GetId\(\)](#), [Object::GetNameRef\(\)](#), [Component::GetParent\(\)](#), [Transform::GetPositionRef\(\)](#), [Transform::GetRotationRef\(\)](#), [Transform::GetScaleRef\(\)](#), [Transform::GetStartPositionRef\(\)](#), [Physics::GetVelocityRef\(\)](#), [Vector3_Func::length\(\)](#), [Vector3_Func::normalize\(\)](#), [Random::random_float\(\)](#), [Random::random_vec3\(\)](#), [Physics::SetAcceleration\(\)](#), [Physics::SetForces\(\)](#), [Object::SetName\(\)](#), [Transform::SetPosition\(\)](#), [Transform::SetRotation\(\)](#), [Transform::SetScale\(\)](#), [Transform::SetStartPosition\(\)](#), [Physics::SetVelocity\(\)](#), [Physics::UpdateGravity\(\)](#), and [Vector3_Func::zero_vec3\(\)](#).

Referenced by `AddScript()`, and `SetupClassesForLua()`.

4.1.3.4 `Clear()` `void Behavior::Clear ()`

Clears states and state filenames from object.

Definition at line 272 of file `behavior.cpp`.

```
272         {
273     for (sol::state* state : states) {
274         if (!state) continue;
275         delete state;
276         state = nullptr;
277     }
278
279     states.clear();
280     scripts.clear();
281 }
```

References `scripts`, and `states`.

Referenced by `Object::ReRead()`, and `~Behavior()`.

4.1.3.5 `Clone()` `Behavior * Behavior::Clone () const`

Clones current `Behavior` object.

Returns

`Behavior*`

Definition at line 54 of file `behavior.cpp`.

```
54     {
55     return new Behavior(*this);
56 }
```

References `Behavior()`.

4.1.3.6 `GetType()` `CType Behavior::GetType () [static]`

Gets the `CType` of `Behavior` (used in `Object::GetComponent<>()`)

Returns

`CType`

Definition at line 118 of file `behavior.cpp`.

```
118     {
119     return CType::CBehavior;
120 }
```

4.1.3.7 GetScripts() `std::vector< std::string > & Behavior::GetScripts ()`

Returns list of lua filenames.

Returns

`std::vector<std::string>&`

Definition at line 142 of file behavior.cpp.

```
142 { return scripts; }
```

References scripts.

Referenced by Editor::Display_Scripts().

4.1.3.8 Read() `void Behavior::Read (
File_Reader & reader)`

Reads in the behaviors to be used.

Parameters

<i>reader</i>	Data from file
---------------	----------------

Definition at line 83 of file behavior.cpp.

```
83                                     {
84     unsigned behavior_num = 0;
85
86     // Reads the name of the lua files
87     while (true) {
88         // Getting the name of the next lua file
89         std::string behavior_name = reader.Read_Behavior_Name("behavior_" + std::to_string(behavior_num));
90         if (behavior_name.compare("") == 0) break;
91         if (behavior_name.find(".lua") == std::string::npos) continue;
92         // Adding lua filename to list
93         scripts.emplace_back(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/scripts/" +
94             behavior_name);
95         ++behavior_num;
96     }
97     // Creating lua state for each of the scripts that were read in
98     for (unsigned i = 0; i < scripts.size(); ++i) {
99         sol::state* state = new sol::state;
100         state->open_libraries(sol::lib::base, sol::lib::math, sol::lib::io, sol::lib::string);
101         states.emplace_back(state);
102     }
```

References File_Reader::Read_Behavior_Name(), scripts, and states.

Referenced by Behavior(), and Object::ReRead().

4.1.3.9 SetupClassesForLua() void Behavior::SetupClassesForLua ()

Setups up the interface between the engine and the lua files.

Definition at line 126 of file behavior.cpp.

```

126     {
127         for (sol::state* state : states) {
128             ClassSetup(state);
129         }
130     }
131     for (unsigned i = 0; i < states.size(); ++i) {
132         states[i]->script_file(scripts[i]);
133         (*states[i])["Start"]();
134     }
135 }
```

References ClassSetup(), scripts, and states.

Referenced by Object_Manager::ReadList(), and Object::ReRead().

4.1.3.10 SwitchScript() bool Behavior::SwitchScript (unsigned scriptNum, std::string newScriptName)

Switches one script to another (replace)

Parameters

<i>scriptNum</i>	
<i>newScriptName</i>	

Returns

true
false

Definition at line 212 of file behavior.cpp.

```

212     {
213         // Checking if this script is already attached
214         if (CheckIfCopy(newScriptName)) return false;
215         if (newScriptName.compare(".lua") == 0) return false;
216         if (newScriptName.find(".lua") == std::string::npos) return false;
217         sol::state* state = states[scriptNum];
218         scripts[scriptNum] = newScriptName;
219         // Setting up new lua script
220         state->script_file(scripts[scriptNum]);
221         (*state)["Start"]();
222     }
223     return true;
224 }
```

References CheckIfCopy(), scripts, and states.

Referenced by Editor::Display_Scripts().

4.1.3.11 Update() void Behavior::Update ()

Update for [Behavior](#) object. Calls [Behavior](#) manager giving list of its behaviors.

Definition at line 71 of file behavior.cpp.

```

71         {
72     for (sol::state* state : states) {
73         if (!state) continue;
74         (*state)["FixedUpdate"] (Engine::GetDt());
75     }
76 }
```

References Engine::GetDt(), and states.

Referenced by Object::Update().

4.1.3.12 Write() void Behavior::Write (
File_Writer & writer)

Gives the names of each lua file to the writer.

Parameters

<i>writer</i>	
---------------	--

Definition at line 109 of file behavior.cpp.

```

109     {
110         writer.Write_Behavior_Name(scripts);
111     }
```

References scripts, and File_Writer::Write_Behavior_Name().

Referenced by Object::Write().

The documentation for this class was generated from the following files:

- [behavior.hpp](#)
- [behavior.cpp](#)

4.2 Camera Class Reference

```
#include <camera.hpp>
```

Public Member Functions

- [Camera](#) (int width, int height)
Creates a new camera with default values.

Static Public Member Functions

- static bool [Initialize](#) ([File_Reader](#) &settings)
Initializes the camera.
- static bool [Initialize](#) ()
Initialize the camera with default values.
- static void [Update](#) ()
Moves the camera and checks for some other inputs.
- static void [MouseUpdate](#) (GLFWwindow *, double xpos, double ypos)
Moves the camera using the mouse.
- static void [Shutdown](#) ()
Deletes the camera object if it exists.
- static glm::vec3 & [GetPosition](#) ()
Returns the position of the camera.
- static glm::vec3 & [GetFront](#) ()
Returns the direction of the camera.
- static glm::vec3 & [GetUp](#) ()
Returns the upward direction of the camera.
- static float [GetFov](#) ()
Returns the field of view of the camera.
- static float [GetNear](#) ()
Returns the near view distance of the camera.
- static float [GetFar](#) ()
Returns the far view distance of the camera.
- static float [GetYaw](#) ()
Returns the x rotation of the camera.
- static float [GetPitch](#) ()
Returns the y rotation of the camera.
- static float & [GetOriginalMoveSpeed](#) ()
Returns reference to originalMoveSpeed.
- static float & [GetOriginalSprintSpeed](#) ()
Returns reference to originalSprintSpeed.
- static float & [GetOriginalSensitivity](#) ()
Returns reference to originalSensitivity.

Private Attributes

- glm::vec3 [position](#)
Position of camera.
- glm::vec3 [front](#)
Direction of camera.
- glm::vec3 [up](#)
90 degree upwards direction of camera
- float [yaw](#)
x rotation
- float [pitch](#)
y rotation

- `std::pair< float, float > last`
Last position of mouse on screen.
- `float fov`
Field of view.
- `float speed`
Move speed.
- `float nearV`
Near view distance.
- `float farV`
Far view distance.
- `float sensitivity`
Mouse sensitivity.
- `float originalMoveSpeed`
Initial move speed (speed gets change by delta time)
- `float originalSprintSpeed`
Initial sprint speed.
- `float originalSensitivity`
Original mouse sensitivity.
- `bool canMoveMouse`
Whether the user can move the camera using the mouse.

4.2.1 Detailed Description

[Camera](#) class ?

Definition at line 26 of file camera.hpp.

4.2.2 Constructor & Destructor Documentation

4.2.2.1 Camera() `Camera::Camera (`
 `int width,`
 `int height)`

Creates a new camera with default values.

Parameters

<i>width</i>	Width of screen
<i>height</i>	Height of screen

Definition at line 33 of file camera.cpp.

```
33         : position(0.f, 0.f, 0.f), front(0.f, 0.f, -1.f),
34         up(0.f, 1.f, 0.f), yaw(-90.f), pitch(0.f), last({ width / 2.f, height / 2.f }),
```

```
35     fov(45.f), speed(1), nearV(0.1f), farV(10000.f), sensitivity(1), canMoveMouse(true) {}
```

Referenced by Initialize().

4.2.3 Member Function Documentation

4.2.3.1 GetFar() `float Camera::GetFar () [static]`

Returns the far view distance of the camera.

Returns

float

Definition at line 243 of file camera.cpp.

```
243 { return camera->farV; }
```

References camera, and farV.

Referenced by Graphics::Render().

4.2.3.2 GetFov() `float Camera::GetFov () [static]`

Returns the field of view of the camera.

Returns

float

Definition at line 229 of file camera.cpp.

```
229 { return camera->fov; }
```

References camera, and fov.

Referenced by Graphics::Render().

4.2.3.3 GetFront() `glm::vec3 & Camera::GetFront () [static]`

Returns the direction of the camera.

Returns

`vec3&`

Definition at line 215 of file camera.cpp.

```
215 { return camera->front; }
```

References camera, and front.

Referenced by Graphics::Render().

4.2.3.4 GetNear() `float Camera::GetNear () [static]`

Returns the near view distance of the camera.

Returns

`float`

Definition at line 236 of file camera.cpp.

```
236 { return camera->nearV; }
```

References camera, and nearV.

Referenced by Graphics::Render().

4.2.3.5 GetOriginalMoveSpeed() `float & Camera::GetOriginalMoveSpeed () [static]`

Returns reference to originalMoveSpeed.

Returns

`float&`

Definition at line 264 of file camera.cpp.

```
264 { return camera->originalMoveSpeed; }
```

References camera, and originalMoveSpeed.

Referenced by Editor::Display_Camera_Settings().

4.2.3.6 GetOriginalSensitivity() `float & Camera::GetOriginalSensitivity () [static]`

Returns reference to originalSensitivity.

Returns

`float&`

Definition at line 278 of file camera.cpp.

```
278 { return camera->originalSensitivity; }
```

References camera, and originalSensitivity.

Referenced by Editor::Display_Camera_Settings().

4.2.3.7 GetOriginalSprintSpeed() `float & Camera::GetOriginalSprintSpeed () [static]`

Returns reference to originalSprintSpeed.

Returns

`float&`

Definition at line 271 of file camera.cpp.

```
271 { return camera->originalSprintSpeed; }
```

References camera, and originalSprintSpeed.

Referenced by Editor::Display_Camera_Settings().

4.2.3.8 GetPitch() `float Camera::GetPitch () [static]`

Returns the y rotation of the camera.

Returns

`float`

Definition at line 257 of file camera.cpp.

```
257 { return camera->pitch; }
```

References camera, and pitch.

4.2.3.9 GetPosition() `glm::vec3 & Camera::GetPosition () [static]`

Returns the position of the camera.

Returns

`vec3&`

Definition at line 208 of file camera.cpp.

```
208 { return camera->position; }
```

References camera, and position.

Referenced by Graphics::Render().

4.2.3.10 GetUp() `glm::vec3 & Camera::GetUp () [static]`

Returns the upward direction of the camera.

Returns

`vec3&`

Definition at line 222 of file camera.cpp.

```
222 { return camera->up; }
```

References camera, and up.

Referenced by Graphics::Render().

4.2.3.11 GetYaw() `float Camera::GetYaw () [static]`

Returns the x rotation of the camera.

Returns

`float`

Definition at line 250 of file camera.cpp.

```
250 { return camera->yaw; }
```

References camera, and yaw.

4.2.3.12 Initialize() [1/2] `bool Camera::Initialize () [static]`

Initialize the camera with default values.

Returns

true
false

Definition at line 66 of file camera.cpp.

```

66     {
67         // Initializing the camera
68         camera = new Camera(1920, 1080);
69         if (!camera) {
70             Trace::Message("Camera was not initialized.");
71             return false;
72         }
73
74         // Getting data from settings file
75         camera->originalMoveSpeed = 10.f;
76         camera->originalSprintSpeed = 30.f;
77         camera->originalSensitivity = 150.f;
78
79         return true;
80     }

```

References camera, Camera(), Trace::Message(), originalMoveSpeed, originalSensitivity, and originalSprintSpeed.

Referenced by Engine::Initialize().

4.2.3.13 Initialize() [2/2] `bool Camera::Initialize (File_Reader & settings) [static]`

Initializes the camera.

Parameters

<i>settings</i>	File that contains settings for the camera
-----------------	--

Returns

true
false

Definition at line 44 of file camera.cpp.

```

44     {
45         // Initializing the camera
46         camera = new Camera(settings.Read_Int("windowWidth"), settings.Read_Int("windowHeight"));
47         if (!camera) {
48             Trace::Message("Camera was not initialized.");
49             return false;
50         }
51
52         // Getting data from settings file
53         camera->originalMoveSpeed = settings.Read_Float("moveSpeed");
54         camera->originalSprintSpeed = settings.Read_Float("sprintSpeed");

```

```

55     camera->originalSensitivity = settings.Read_Float("sensitivity");
56
57     return true;
58 }

```

References camera, Camera(), Trace::Message(), originalMoveSpeed, originalSensitivity, originalSprintSpeed, File_Reader::Read_Float(), and File_Reader::Read_Int().

4.2.3.14 MouseUpdate() void Camera::MouseUpdate (

```

    GLFWwindow * ,
    double xpos,
    double ypos ) [static]

```

Moves the camera using the mouse.

Parameters

<i>xpos</i>	x position of the mouse
<i>ypos</i>	y position of the mouse

Returns

void

Definition at line 138 of file camera.cpp.

```

138
139     if (!camera->canMoveMouse) {
140         camera->last = { xpos, ypos };
141         return;
142     }
143     // Setting up variables
144     static bool firstMouse = true;
145     std::pair<double, double> mousePos = { xpos, ypos };
146
147     // Setting the camera sens using delta time
148     camera->sensitivity = camera->originalSensitivity * Engine::GetDeltaTime();
149
150     // Checking if this is the first time the function was called
151     if (firstMouse) {
152         camera->last = { mousePos.first, mousePos.second };
153         firstMouse = false;
154     }
155
156     // Finding how far the mouse is from its last position
157     std::pair<float, float> offset = {
158         mousePos.first - camera->last.first,
159         camera->last.second - mousePos.second
160     };
161     // Setting new last position
162     camera->last = { mousePos.first, mousePos.second };
163
164     // Updating offsets to use the sensitivity of the camera
165     offset.first *= camera->sensitivity;
166     offset.second *= camera->sensitivity;
167
168     // Applying the offset to the camera's direction
169     camera->yaw += offset.first;
170     camera->pitch += offset.second;
171
172     // Stops the camera from circling completely in the y direction
173     if (camera->pitch > 89.f) camera->pitch = 89.f;
174     if (camera->pitch < -89.f) camera->pitch = -89.f;

```

```
175
176 // Finding the direction of the camera
177 glm::vec3 tempFront = {
178     std::cos(glm::radians(camera->yaw)) * std::cos(glm::radians(camera->pitch)),
179     std::sin(glm::radians(camera->pitch)),
180     std::sin(glm::radians(camera->yaw)) * std::cos(glm::radians(camera->pitch))
181 };
182 camera->front = glm::normalize(tempFront);
183
184 // Finding the upward direction of the camera
185 glm::vec3 tempUp = { 0.f, 1.f, 0.f };
186 glm::vec3 right = glm::normalize(glm::cross(tempUp, camera->front));
187 glm::vec3 up = glm::cross(camera->front, right);
188 camera->up = up;
189 }
```

References camera, canMoveMouse, front, Engine::GetDeltaTime(), last, originalSensitivity, pitch, sensitivity, up, and yaw.

Referenced by Graphics::Initialize().

4.2.3.15 Shutdown() void Camera::Shutdown () [static]

Deletes the camera object if it exists.

Returns

void

Definition at line 196 of file camera.cpp.

```
196 {
197     if (camera) {
198         delete camera;
199         camera = nullptr;
200     }
201 }
```

References camera.

Referenced by Engine::Shutdown().

4.2.3.16 Update() void Camera::Update () [static]

Moves the camera and checks for some other inputs.

Returns

void

Definition at line 87 of file camera.cpp.

```

87         {
88             // Checking if the engine should be closed
89             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_ESCAPE) == GLFW_PRESS) {
90                 if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_ESCAPE) == GLFW_RELEASE) {
91                     glfwSetWindowShouldClose(Graphics::GetWindow(), true);
92                 }
93             }
94
95             // Checking if sprint is being used
96             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_LEFT_SHIFT) == GLFW_PRESS &&
97                 Editor::GetTakeKeyboardInput()) {
98                 camera->speed = camera->originalSprintSpeed * Engine::GetDeltaTime();
99             }
100             else {
101                 camera->speed = camera->originalMoveSpeed * Engine::GetDeltaTime();
102             }
103
104             // Checking for movement using W, A, S, D, SPACE, and CTRL
105             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_W) == GLFW_PRESS && Editor::GetTakeKeyboardInput()) {
106                 camera->position += camera->speed * camera->front;
107             }
108             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_S) == GLFW_PRESS && Editor::GetTakeKeyboardInput()) {
109                 camera->position -= camera->speed * camera->front;
110             }
111             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_A) == GLFW_PRESS && Editor::GetTakeKeyboardInput()) {
112                 camera->position -= glm::normalize(glm::cross(camera->front, camera->up)) * camera->speed;
113             }
114             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_D) == GLFW_PRESS && Editor::GetTakeKeyboardInput()) {
115                 camera->position += glm::normalize(glm::cross(camera->front, camera->up)) * camera->speed;
116             }
117             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_SPACE) == GLFW_PRESS && Editor::GetTakeKeyboardInput()) {
118                 camera->position += camera->speed * camera->up;
119             }
120             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_LEFT_CONTROL) == GLFW_PRESS &&
121                 Editor::GetTakeKeyboardInput()) {
122                 camera->position -= camera->speed * camera->up;
123             }
124
125             if (glfwGetMouseButton(Graphics::GetWindow(), GLFW_MOUSE_BUTTON_RIGHT) == GLFW_PRESS &&
126                 Editor::GetTakeKeyboardInput()) {
127                 camera->canMoveMouse = true;
128             }
129             if (glfwGetMouseButton(Graphics::GetWindow(), GLFW_MOUSE_BUTTON_RIGHT) == GLFW_RELEASE) {
130                 camera->canMoveMouse = false;
131             }
132         }

```

References camera, canMoveMouse, front, Engine::GetDeltaTime(), Editor::GetTakeKeyboardInput(), Graphics::GetWindow(), originalMoveSpeed, originalSprintSpeed, position, speed, and up.

Referenced by Engine::Update().


The documentation for this class was generated from the following files:

- [camera.hpp](#)
- [camera.cpp](#)

4.3 Component Class Reference

```
#include <component.hpp>
```

Inheritance diagram for Component:



Public Types

- enum `CType` { `CBehavior`, `CModel`, `CPhysics`, `CTransform` }

Public Member Functions

- `Component (CType type_)`
Creates a new component of given type.
- `void SetParent (Object *object)`
Sets the parent of the component.
- `Object * GetParent () const`
Gets the parent of the component.
- `CType GetType () const`
Gets the type of the component.

Private Attributes

- `CType type`
Type of component.
- `Object * parent`
Object that this component is attached to.

4.3.1 Detailed Description

`Component` class

Definition at line 20 of file `component.hpp`.

4.3.2 Member Enumeration Documentation

4.3.2.1 `CType` enum `Component::CType`

Types of components

Definition at line 23 of file `component.hpp`.

```
23     {
24         CBehavior,
25         CModel,
26         CPhysics,
27         CTransform,
28     };
```

4.3.3 Constructor & Destructor Documentation

4.3.3.1 Component() `Component::Component (CType type_)`

Creates a new component of given type.

Parameters

<code>type_</code>	Type of component
—	

Definition at line 20 of file component.cpp.

```
20 : type(type_) {}
```

4.3.4 Member Function Documentation

4.3.4.1 GetCType() `CType Component::GetCType () const`

Gets the type of the component.

Returns

CType Type of the component

Definition at line 41 of file component.cpp.

```
41 { return type; }
```

References type.

Referenced by `Object::AddComponent()`.

4.3.4.2 GetParent() `Object * Component::GetParent () const`

Gets the parent of the component.

Returns

Object* The parent

Definition at line 34 of file component.cpp.

```
34 { return parent; }
```

References parent.

Referenced by `Behavior::ClassSetup()`, `Editor::Display_Model()`, `Editor::Display_Physics()`, `Editor::Display_Scripts()`, `Model::Draw()`, `Physics::Update()`, and `Physics::UpdateGravity()`.

4.3.4.3 SetParent() `void Component::SetParent (`
`Object * object)`

Sets the parent of the component.

Parameters

<i>object</i>	The object that is the parent
---------------	-------------------------------

Definition at line 27 of file component.cpp.

```
27 { parent = object; }
```

References parent.

Referenced by Object::AddComponent().

The documentation for this class was generated from the following files:

- [component.hpp](#)
- [component.cpp](#)

4.4 Editor Class Reference

```
#include <editor.hpp>
```

Static Public Member Functions

- static bool [Initialize](#) ()
Sets up the config and style of the editor.
- static void [Update](#) ()
Updates the editor content and calls display functions.
- static void [Render](#) ()
Render the editor.
- static void [Shutdown](#) ()
Destroy editor windows and systems.
- static void [Reset](#) ()
Sets selected object to invalid value.
- static bool [GetTakeKeyboardInput](#) ()
Returns whether the program should ignore keyboard input.

Private Member Functions

- void [Display_Dockspace](#) ()
Setup and display the editor's dockspace.
- void [Display_Scene](#) ()
Display the scene window.
- void [Display_Components](#) ()
Display all of the components of the current selected_object.
- void [Display_World_Settings](#) ()
Shows all of the settings of the engine itself.
- void [Display_Camera_Settings](#) ()
Displays the different camera settings, allows user to change them as needed.
- void [Display_Scripts](#) ([Behavior](#) *behavior)
Displays the different lua scripts attached to the selected object.
- void [Display_Model](#) ([Model](#) *model)
Displays the data of the model being used.
- void [Display_Physics](#) ([Physics](#) *physics)
Shows the [Physics](#) component.
- void [Display_Transform](#) ([Transform](#) *transform)
Display transform data, users can change any of it.
- void [Display_Menu_Bar](#) ()
Displays menu bar that can be used to save the scene.

Static Private Member Functions

- static std::string [Make_Display_String](#) (std::string inputString)
Removes the filepath from a filename.

Private Attributes

- bool [isOpen](#)
Whether the editor window is open or not.
- int [selected_object](#)
Current object selected in the scene window.
- int [selected_component](#)
Current component selected.
- bool [takeKeyboardInput](#)
Whether the program should take keyboard input.
- int [object_to_copy](#)
[Object](#) that will be copied if paste is used (doesn't need to be the same as selected_object)

4.4.1 Detailed Description

[Editor](#) class

Definition at line 25 of file editor.hpp.

4.4.2 Member Function Documentation

4.4.2.1 Display_Camera_Settings() void Editor::Display_Camera_Settings () [private]

Displays the different camera settings, allows user to change them as needed.

Definition at line 431 of file editor.cpp.

```

431     {
432         ImGui::Begin("Camera Settings");
433
434         ImGui::PushItemWidth(137);
435
436         // Default move speed
437         ImGui::Text("Move Speed");
438         ImGui::SameLine(100); ImGui::InputFloat("##2", &Camera::GetOriginalMoveSpeed());
439
440         // Move speed when holding shift
441         ImGui::Text("Sprint Speed");
442         ImGui::SameLine(100); ImGui::InputFloat("##3", &Camera::GetOriginalSprintSpeed());
443
444         // Mouse sensitivity when looking around
445         ImGui::Text("Sensitivity");
446         ImGui::SameLine(100); ImGui::InputFloat("##4", &Camera::GetOriginalSensitivity());
447
448         ImGui::PopItemWidth();
449
450         ImGui::End();
451     }
```

References `Camera::GetOriginalMoveSpeed()`, `Camera::GetOriginalSensitivity()`, and `Camera::GetOriginalSprintSpeed()`.

Referenced by `Update()`.

4.4.2.2 Display_Components() void Editor::Display_Components () [private]

Display all of the components of the current selected_object.

Definition at line 271 of file editor.cpp.

```

271     {
272         ImGui::Begin("Components##1");
273
274         if (selected_object == -1) { ImGui::End(); return; }
275         Object* object = Object_Manager::FindObject(selected_object);
276         std::string objectName = object->GetName();
277
278         ImGui::Text("Id: %d", object->GetId());
279
280         // Display name box (allows changing the name of an object)
281         static char nameBuf[128] = "";
282         sprintf(nameBuf, objectName.c_str());
283
284         if (ImGui::InputText("Name", nameBuf, 128, ImGuiInputTextFlags_EnterReturnsTrue)) {
285             object->SetName(std::string(nameBuf));
286         }
287
288         if (ImGui::IsItemDeactivatedAfterEdit()) {
289             object->SetName(std::string(nameBuf));
290         }
291
292         // Template used by the selected object
293         ImGui::Text("Template:");
```

```

294     ImGui::SameLine(100);
295     std::string templateName = object->GetTemplateName();
296     if (templateName.empty()) templateName = "No template##1";
297     else templateName = Editor::Make_Display_String(templateName);
298
299     if (ImGui::Button(templateName.c_str())) {
300         ImGuiFileDialog::Instance()->OpenDialog("ChooseTemplate##1", "Choose File", ".json",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/objects/");
301     }
302
303     ImGui::SameLine();
304     if (ImGui::Button("New Template")) {
305         ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDlgKey##6", "Choose File", ".json",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/objects/");
306     }
307
308
309     if (ImGuiFileDialog::Instance()->Display("ChooseFileDlgKey##6")) {
310         if (ImGuiFileDialog::Instance()->IsOk()) {
311             std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
312             object->Write(filePath);
313         }
314
315         ImGuiFileDialog::Instance()->Close();
316     }
317
318     if (ImGuiFileDialog::Instance()->Display("ChooseTemplate##1")) {
319         if (ImGuiFileDialog::Instance()->IsOk()) {
320             std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
321             filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName();
322             object->ReRead(filePath);
323         }
324
325         ImGuiFileDialog::Instance()->Close();
326     }
327
328     // Getting all of the components
329     Behavior* behavior = object->GetComponent<Behavior>();
330     Model* model = object->GetComponent<Model>();
331     Physics* physics = object->GetComponent<Physics>();
332     Transform* transform = object->GetComponent<Transform>();
333
334     // Display all of the components of the selected_object
335     Display_Transform(transform);
336     Display_Physics(physics);
337     Display_Model(model);
338     Display_Scripts(behavior);
339
340     ImGui::Separator();
341
342     // Button to add new components to the selected_object
343     if (ImGui::Button("Add Component##1")) {
344         ImGui::OpenPopup("New Component##1");
345     }
346
347     // Add new components to object (only ones that the object doesn't already have)
348     if (ImGui::BeginPopup("New Component##1")) {
349         if (!physics) {
350             if (ImGui::Selectable("Physics##1")) {
351                 physics = new Physics;
352                 object->AddComponent(physics);
353             }
354         }
355         if (!model) {
356             if (ImGui::Selectable("Model##1")) {
357                 model = new Model;
358                 object->AddComponent(model);
359             }
360         }
361         if (!behavior) {
362             if (ImGui::Selectable("Scripts##1")) {
363                 behavior = new Behavior;
364                 object->AddComponent(behavior);
365             }
366         }
367         ImGui::EndPopup();
368     }
369
370     ImGui::End();
371 }

```

References `Display_Model()`, `Display_Physics()`, `Display_Scripts()`, `Display_Transform()`, `Object_Manager::FindObject()`, `Object::GetId()`, `Make_Display_String()`, and `selected_object`.

Referenced by `Update()`.

4.4.2.3 `Display_Dockspace()` `void Editor::Display_Dockspace () [private]`

Setup and display the editor's dockspace.

Definition at line 155 of file `editor.cpp`.

```

155     {
156         // Setting up viewport
157         ImGuiViewport* viewport = ImGui::GetMainViewport();
158         ImGui::SetNextWindowPos(viewport->Pos);
159         ImGui::SetNextWindowSize(viewport->Size);
160         ImGui::SetNextWindowViewport(viewport->ID);
161         ImGui::SetNextWindowBgAlpha(0.0f);
162
163         // Setting up window flags
164         ImGuiWindowFlags window_flags = ImGuiWindowFlags_MenuBar | ImGuiWindowFlags_NoDocking;
165         window_flags |= ImGuiWindowFlags_NoTitleBar | ImGuiWindowFlags_NoCollapse | ImGuiWindowFlags_NoResize |
        ImGuiWindowFlags_NoMove;
166         window_flags |= ImGuiWindowFlags_NoBringToFrontOnFocus | ImGuiWindowFlags_NoNavFocus;
167
168         // Setting up window style
169         ImGui::PushStyleVar(ImGuiStyleVar_WindowRounding, 0.0f);
170         ImGui::PushStyleVar(ImGuiStyleVar_WindowBorderSize, 0.0f);
171         ImGui::PushStyleVar(ImGuiStyleVar_WindowPadding, ImVec2(0.0f, 0.0f));
172
173         // Making the window
174         ImGui::SetNextWindowBgAlpha(0.0f);
175         ImGui::Begin("Editor Window", &editor->isOpen, window_flags);
176         ImGui::PopStyleVar(3);
177
178         // Setting up window settings
179         ImGuiID dockspace_id = ImGui::GetID("Editor");
180         ImGuiDockNodeFlags dockspace_flags = ImGuiDockNodeFlags_PassthruCentralNode |
        ImGuiDockNodeFlags_NoDockingInCentralNode;
181         ImGui::DockSpace(dockspace_id, ImVec2(0.0f, 0.0f), dockspace_flags);
182         editor->Display_Menu_Bar();
183         ImGui::End();
184     }

```

References `Display_Menu_Bar()`, `editor`, and `isOpen`.

Referenced by `Update()`.

4.4.2.4 `Display_Menu_Bar()` `void Editor::Display_Menu_Bar () [private]`

Displays menu bar that can be used to save the scene.

Definition at line 717 of file `editor.cpp`.

```

717     {
718         if (ImGui::BeginMenuBar()) {
719             if (ImGui::BeginMenu("File##1")) {
720                 if (ImGui::MenuItem("Save##1")) {
721                     Engine::Write();
722                 }
723                 if (ImGui::MenuItem("Save As...##1")) {
724                     ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDialogKey##7", "Choose File", ".json",
        std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/preset");
725                 }

```

```

726
727     ImGui::EndMenu();
728 }
729
730 if (ImGuiFileDialog::Instance()->Display("ChooseFileDlgKey##7")) {
731     if (ImGuiFileDialog::Instance()->IsOk()) {
732         std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
733         filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName() + ".json";
734         Engine::SetPresetName(std::string(filePath));
735         Engine::Write();
736     }
737     ImGuiFileDialog::Instance()->Close();
738 }
739
740 ImGui::EndMenuBar();
741 }
742 }

```

References `Engine::SetPresetName()`, and `Engine::Write()`.

Referenced by `Display_Dockspace()`.

4.4.2.5 Display_Model() `void Editor::Display_Model (`
`Model * model) [private]`

Displays the data of the model being used.

Parameters

<i>model</i>	
--------------	--

Definition at line 537 of file `editor.cpp`.

```

537
538     if (!model) return;
539
540     std::string modelName = Editor::Make_Display_String(model->GetModelName());
541     std::string textureName = Editor::Make_Display_String(model->GetTextureName());
542
543     if (modelName.compare("") == 0) modelName = "no model";
544     if (textureName.compare("") == 0) textureName = "no texture";
545
546     // Setting up tree flags
547     ImGuiTreeNodeFlags node_flags = ImGuiTreeNodeFlags_SpanAvailWidth | ImGuiTreeNodeFlags_OpenOnDoubleClick
| ImGuiTreeNodeFlags_OpenOnArrow;
548     if (selected_component == CType::CModel) node_flags |= ImGuiTreeNodeFlags_Selected;
549
550     const bool model_open = ImGui::TreeNodeEx((void*)(intptr_t)CType::CModel, node_flags, "Model");
551     if (ImGui::IsItemClicked()) selected_component = CType::CModel;
552
553     // Right click behavior to delete model component from selected object
554     if (ImGui::IsItemClicked(ImGuiMouseButton_Right)) {
555         selected_component = CType::CModel;
556         ImGui::OpenPopup("DeleteModel##1");
557     }
558
559     if (ImGui::BeginPopup("DeleteModel##1")) {
560         if (ImGui::Selectable("Delete##3")) {
561             model->GetParent()->RemoveComponent<Model>();
562             selected_component = -1;
563         }
564         ImGui::EndPopup();
565     }
566
567     if (model_open) {
568         // Model that is being used
569         ImGui::Text("Model"); ImGui::SameLine(100);

```

```

570         if (ImGui::Button(modelName.c_str())) {
571             ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDlgKey##1", "Choose File", ".obj",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/models/");
572         }
573
574         if (ImGuiFileDialog::Instance()->Display("ChooseFileDlgKey##1")) {
575             if (ImGuiFileDialog::Instance()->IsOk()) {
576                 std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
577                 filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName();
578                 model->SwitchModel(filePath);
579             }
580
581             ImGuiFileDialog::Instance()->Close();
582         }
583
584         // Texture that is being used
585         ImGui::Text("Texture"); ImGui::SameLine(100);
586         if (ImGui::Button(textureName.c_str())) {
587             ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDlgKey##2", "Choose File", ".dds, .DDS",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/textures/");
588         }
589
590         if (ImGuiFileDialog::Instance()->Display("ChooseFileDlgKey##2")) {
591             if (ImGuiFileDialog::Instance()->IsOk()) {
592                 std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
593                 filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName();
594                 model->SwitchTexture(filePath);
595             }
596
597             ImGuiFileDialog::Instance()->Close();
598         }
599
600         ImGui::TreePop();
601     }
602 }

```

References `Model::GetModelName()`, `Component::GetParent()`, `Model::GetTextureName()`, `Make_Display_String()`, `Object::RemoveComponent()`, `selected_component`, `Model::SwitchModel()`, and `Model::SwitchTexture()`.

Referenced by `Display_Components()`.

4.4.2.6 Display_Physics() `void Editor::Display_Physics (`
`Physics * physics) [private]`

Shows the `Physics` component.

Parameters

<i>physics</i>	
----------------	--

Definition at line 609 of file editor.cpp.

```

609                                     {
610         if (!physics) return;
611
612         glm::vec3& velocity = physics->GetVelocityRef();
613         glm::vec3& rotVel = physics->GetRotationalVelocityRef();
614
615         ImGuiTreeNodeFlags node_flags = ImGuiTreeNodeFlags_SpanAvailWidth | ImGuiTreeNodeFlags_OpenOnDoubleClick
| ImGuiTreeNodeFlags_OpenOnArrow;
616         if (selected_component == CType::CPhysics) node_flags |= ImGuiTreeNodeFlags_Selected;
617
618         const bool physics_open = ImGui::TreeNodeEx((void*)(intptr_t)CType::CPhysics, node_flags, "Physics");
619         if (ImGui::IsItemClicked()) selected_component = CType::CPhysics;
620
621         if (ImGui::IsItemClicked(ImGuiMouseButton_Right)) {
622             selected_component = CType::CPhysics;

```

```

623     ImGui::OpenPopup("DeletePhysics##1");
624 }
625
626 if (ImGui::BeginPopup("DeletePhysics##1")) {
627     if (ImGui::Selectable("Delete##4")) {
628         physics->GetParent()->RemoveComponent<Physics>();
629         selected_component = -1;
630     }
631     ImGui::EndPopup();
632 }
633
634 if (physics_open) {
635     ImGui::Text("Velocity");
636
637     ImGui::PushItemWidth(65);
638     ImGui::SameLine(100); ImGui::InputFloat("x##1", &velocity.x);
639     ImGui::SameLine(185); ImGui::InputFloat("y##1", &velocity.y);
640     ImGui::SameLine(270); ImGui::InputFloat("z##1", &velocity.z);
641
642     ImGui::Text("RotVel");
643
644     ImGui::PushItemWidth(65);
645     ImGui::SameLine(100); ImGui::InputFloat("x##6", &rotVel.x);
646     ImGui::SameLine(185); ImGui::InputFloat("y##6", &rotVel.y);
647     ImGui::SameLine(270); ImGui::InputFloat("z##6", &rotVel.z);
648
649     ImGui::Text("Mass");
650     ImGui::SameLine(100); ImGui::InputFloat("##6", &physics->GetMassRef());
651     ImGui::PopItemWidth();
652
653     ImGui::TreePop();
654 }
655 }

```

References `Physics::GetMassRef()`, `Component::GetParent()`, `Physics::GetRotationalVelocityRef()`, `Physics::GetVelocityRef()`, `Object::RemoveComponent()`, and `selected_component`.

Referenced by `Display_Components()`.

4.4.2.7 Display_Scene() void Editor::Display_Scene () [private]

Display the scene window.

Definition at line 190 of file editor.cpp.

```

190     {
191     ImGui::Begin("Scene");
192
193     if (!takeKeyboardInput && ImGui::IsWindowFocused()) {
194         if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_LEFT_CONTROL) == GLFW_PRESS) {
195             // Copy current selected object
196             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_C) == GLFW_PRESS) {
197                 if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_C) == GLFW_RELEASE) {
198                     editor->object_to_copy = editor->selected_object;
199                 }
200             }
201             // Paste current selected object
202             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_V) == GLFW_PRESS) {
203                 if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_V) == GLFW_RELEASE) {
204                     if (editor->object_to_copy != -1) {
205                         Object* object = new Object(*Object_Manager::FindObject(editor->selected_object));
206                         Object_Manager::AddObject(object);
207                     }
208                 }
209             }
210         }
211     }
212
213     // Display all objects
214     for (int i = 0; i < (int)Object_Manager::GetSize(); ++i) {
215         if (ImGui::Selectable(Object_Manager::FindObject(i)->GetName().c_str(), selected_object == i,
216             ImGuiSelectableFlags_AllowDoubleClick)) {

```

```

216         if (selected_object != i) editor->selected_component = -1;
217         selected_object = i;
218         selected_component = -1;
219     }
220
221     // Checking for right click behavior
222     if (ImGui::IsItemClicked(ImGuiMouseButton_Right)) {
223         if (selected_object != i) editor->selected_component = -1;
224         selected_object = i;
225         selected_component = -1;
226         ImGui::OpenPopup("ObjectSettings##1");
227     }
228 }
229
230 if (ImGui::BeginPopup("ObjectSettings##1")) {
231     // Removes selected object from scene
232     if (ImGui::Selectable("Delete##1")) {
233         Object_Manager::RemoveObject(selected_object);
234         selected_object = -1;
235         selected_component = -1;
236     }
237     // Copies selected object
238     if (ImGui::Selectable("Copy##1")) {
239         editor->object_to_copy = editor->selected_object;
240     }
241     // Pastes copied object into scene
242     if (ImGui::Selectable("Paste##1")) {
243         if (editor->object_to_copy != -1) {
244             Object* object = new Object(*Object_Manager::FindObject(editor->selected_object));
245             Object_Manager::AddObject(object);
246         }
247     }
248     ImGui::EndPopup();
249 }
250
251 ImGui::Separator();
252
253 // Button to add new object to the scene
254 if (ImGui::Button("Add Object")) {
255     Object* newObject = new Object;
256     Transform* transform = new Transform;
257     transform->SetStartPosition(glm::vec3(0.f));
258     newObject->SetName("New_Object");
259     newObject->AddComponent(transform);
260
261     Object_Manager::AddObject(newObject);
262 }
263
264 ImGui::End();
265 }

```

References `Object::AddComponent()`, `Object_Manager::AddObject()`, `editor`, `Object_Manager::FindObject()`, `Object_Manager::GetSize()`, `Graphics::GetWindow()`, `object_to_copy`, `Object_Manager::RemoveObject()`, `selected_component`, `selected_object`, `Object::SetName()`, `Transform::SetStartPosition()`, and `takeKeyboardInput`.

Referenced by `Update()`.

4.4.2.8 Display_Scripts() `void Editor::Display_Scripts (Behavior * behavior) [private]`

Displays the different lua scripts attached to the selected object.

Parameters

<i>behavior</i>	Contains the script data
-----------------	--------------------------

Definition at line 458 of file editor.cpp.

```

458                                     {
459     if (!behavior) return;
460
461     // Setting up tree flags
462     ImGuiTreeNodeFlags node_flags = ImGuiTreeNodeFlags_SpanAvailWidth | ImGuiTreeNodeFlags_OpenOnDoubleClick
| ImGuiTreeNodeFlags_OpenOnArrow;
463     if (selected_component == CType::CBehavior) node_flags |= ImGuiTreeNodeFlags_Selected;
464
465     const bool scripts_open = ImGui::TreeNodeEx((void*)(intptr_t)CType::CBehavior, node_flags, "Scripts");
466     if (ImGui::IsItemClicked()) selected_component = CType::CBehavior;
467
468     // Right click behavior to delete script component from object
469     if (ImGui::IsItemClicked(ImGuiMouseButton_Right)) {
470         selected_component = CType::CBehavior;
471         ImGui::OpenPopup("DeleteScripts##1");
472     }
473
474     if (ImGui::BeginPopup("DeleteScripts##1")) {
475         if (ImGui::Selectable("Delete##2")) {
476             behavior->GetParent()->RemoveComponent<Behavior>();
477             selected_component = -1;
478         }
479         ImGui::EndPopup();
480     }
481
482     // Displays the currently attached scripts
483     if (scripts_open) {
484         std::vector<std::string>& scripts = behavior->GetScripts();
485         unsigned scriptNum = 1;
486         for (std::string& script : scripts) {
487             ImGui::Text(std::string("Script " + std::to_string(scriptNum) + ":").c_str());
488             ImGui::SameLine(100);
489             if (ImGui::Button(Editor::Make_Display_String(script).c_str())) {
490                 ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDialogKey##3", "Choose File", ".lua",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/scripts/");
491             }
492
493             if (ImGuiFileDialog::Instance()->Display("ChooseFileDialogKey##3")) {
494                 if (ImGuiFileDialog::Instance()->IsOk()) {
495                     std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
496                     filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName();
497                     behavior->SwitchScript(scriptNum - 1, filePath);
498                 }
499
500                 ImGuiFileDialog::Instance()->Close();
501             }
502             ++scriptNum;
503         }
504
505         // Add new script to the object
506         ImGui::Indent(71);
507         if (ImGui::Button("New Script##1")) {
508             ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDialogKey##4", "Choose File", ".lua",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/scripts/");
509         }
510
511         if (ImGuiFileDialog::Instance()->Display("ChooseFileDialogKey##4")) {
512             if (ImGuiFileDialog::Instance()->IsOk()) {
513                 std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
514                 filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName();
515                 behavior->AddScript(filePath);
516             }
517
518             ImGuiFileDialog::Instance()->Close();
519         }
520
521         // Popup to say that the selected script to add is already attached to the object
522         if (ImGui::BeginPopup("ExistingScript##1")) {
523             ImGui::Text(std::string("Script already being used or doesn't exist").c_str(),
ImGui::GetFontSize() * 2);
524             ImGui::EndPopup();
525         }
526
527         ImGui::TreePop();
528     }
529 }
530 }

```

References Behavior::AddScript(), Component::GetParent(), Behavior::GetScripts(), Make_Display_String(), Object::↵ RemoveComponent(), selected_component, and Behavior::SwitchScript().

Referenced by `Display_Components()`.

4.4.2.9 `Display_Transform()` `void Editor::Display_Transform (Transform * transform) [private]`

Display transform data, users can change any of it.

Parameters

<i>transform</i>	
------------------	--

Definition at line 662 of file `editor.cpp`.

```

662                                     {
663     if (!transform) return;
664
665     glm::vec3& position = transform->GetPositionRef();
666     glm::vec3& scale = transform->GetScaleRef();
667     glm::vec3& rotation = transform->GetRotationRef();
668     glm::vec3& startPos = transform->GetStartPositionRef();
669
670     ImGuiTreeNodeFlags node_flags = ImGuiTreeNodeFlags_SpanAvailWidth | ImGuiTreeNodeFlags_OpenOnDoubleClick
| ImGuiTreeNodeFlags_OpenOnArrow;
671     if (selected_component == CType::CTransform) node_flags |= ImGuiTreeNodeFlags_Selected;
672
673     const bool transform_open = ImGui::TreeNodeEx((void*)(intptr_t)CType::CTransform, node_flags,
"Transform");
674     if (ImGui::IsItemClicked()) selected_component = CType::CTransform;
675
676     if (transform_open) {
677         ImGui::Text("Position");
678
679         ImGui::PushItemWidth(65);
680         ImGui::SameLine(100); ImGui::InputFloat("x##1", &position.x);
681         ImGui::SameLine(185); ImGui::InputFloat("y##1", &position.y);
682         ImGui::SameLine(270); ImGui::InputFloat("z##1", &position.z);
683         ImGui::PopItemWidth();
684
685         ImGui::Text("Scale");
686
687         ImGui::PushItemWidth(65);
688         ImGui::SameLine(100); ImGui::InputFloat("x##2", &scale.x);
689         ImGui::SameLine(185); ImGui::InputFloat("y##2", &scale.y);
690         ImGui::SameLine(270); ImGui::InputFloat("z##2", &scale.z);
691         ImGui::PopItemWidth();
692
693         ImGui::Text("Rotation");
694
695         ImGui::PushItemWidth(65);
696         ImGui::SameLine(100); ImGui::InputFloat("x##3", &rotation.x);
697         ImGui::SameLine(185); ImGui::InputFloat("y##3", &rotation.y);
698         ImGui::SameLine(270); ImGui::InputFloat("z##3", &rotation.z);
699         ImGui::PopItemWidth();
700
701         ImGui::Text("Start Pos");
702
703         ImGui::PushItemWidth(65);
704         ImGui::SameLine(100); ImGui::InputFloat("x##5", &startPos.x);
705         ImGui::SameLine(185); ImGui::InputFloat("y##5", &startPos.y);
706         ImGui::SameLine(270); ImGui::InputFloat("z##5", &startPos.z);
707         ImGui::PopItemWidth();
708
709         ImGui::TreePop();
710     }
711 }
```

References `Transform::GetPositionRef()`, `Transform::GetRotationRef()`, `Transform::GetScaleRef()`, `Transform::GetStartPositionRef()`, and `selected_component`.

Referenced by `Display_Components()`.

4.4.2.10 `Display_World_Settings()` `void Editor::Display_World_Settings () [private]`

Shows all of the settings of the engine itself.

Definition at line 377 of file `editor.cpp`.

```

377 {
378     ImGui::Begin("World Settings");
379     std::string presetName = Engine::GetPresetName();
380     if (presetName.compare("no preset") != 0)
381         presetName = Editor::Make_Display_String(presetName);
382
383     // Allows user to change the preset that is loaded
384     ImGui::Text("Presets"); ImGui::SameLine(120);
385     if (ImGui::Button(presetName.c_str())) {
386         ImGuiFileDialog::Instance()->OpenDialog("ChooseFileDlgKey##5", "Choose File", ".json",
std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/preset/");
387     }
388
389     if (ImGuiFileDialog::Instance()->Display("ChooseFileDlgKey##5")) {
390         if (ImGuiFileDialog::Instance()->IsOk()) {
391             std::string filePath = ImGuiFileDialog::Instance()->GetCurrentPath();
392             filePath += "/" + ImGuiFileDialog::Instance()->GetCurrentFileName();
393
394             if (Engine::Restart(filePath)) {
395                 selected_object = -1;
396                 selected_component = -1;
397                 object_to_copy = -1;
398             }
399         }
400
401         ImGuiFileDialog::Instance()->Close();
402     }
403
404     ImGui::PushItemWidth(141);
405
406     // Strength of the light being used
407     ImGui::Text("Light Power");
408     ImGui::SameLine(120); ImGui::InputFloat("##1", &Engine::GetLightPower());
409
410     // Position of the light being used
411     ImGui::Text("Light Position");
412     ImGui::PushItemWidth(65);
413     ImGui::SameLine(120); ImGui::InputFloat("x##4", &Engine::GetLightPos().x);
414     ImGui::SameLine(205); ImGui::InputFloat("y##4", &Engine::GetLightPos().y);
415     ImGui::SameLine(290); ImGui::InputFloat("z##4", &Engine::GetLightPos().z);
416     ImGui::PopItemWidth();
417
418     // Grav const of the engine
419     ImGui::Text("Grav Const");
420     ImGui::SameLine(120); ImGui::InputDouble("##5", &Engine::GetGravConst());
421
422     ImGui::PopItemWidth();
423
424     ImGui::End();
425 }
```

References `Engine::GetGravConst()`, `Engine::GetLightPos()`, `Engine::GetLightPower()`, `Engine::GetPresetName()`, `Make_Display_String()`, `object_to_copy`, `Engine::Restart()`, `selected_component`, and `selected_object`.

Referenced by `Update()`.

4.4.2.11 GetTakeKeyboardInput() `bool Editor::GetTakeKeyboardInput () [static]`

Returns whether the program should ignore keyboard input.

Returns

true
false

Definition at line 750 of file editor.cpp.

```
750 { return editor->takeKeyboardInput; }
```

References editor, and takeKeyboardInput.

Referenced by Camera::Update(), and Graphics::Update().

4.4.2.12 Initialize() `bool Editor::Initialize () [static]`

Sets up the config and style of the editor.

Returns

true
false

Definition at line 35 of file editor.cpp.

```
35 {
36     // Initializing the editor
37     editor = new Editor;
38     if (!editor) {
39         Trace::Message("Editor failed to initialize.\n");
40         return false;
41     }
42     editor->selected_object = -1;
43     editor->selected_component = -1;
44     editor->object_to_copy = -1;
45
46     ImGui::CHECKVERSION();
47     ImGui::CreateContext();
48
49     // Setting up ImGui flags
50     ImGui::GetIO().ConfigFlags |= ImGuiConfigFlags_NavEnableKeyboard;
51     ImGui::GetIO().ConfigFlags |= ImGuiConfigFlags_DockingEnable;
52     ImGui::GetIO().ConfigFlags |= ImGuiConfigFlags_ViewportsEnable;
53
54     // Setting style for ImGui
55     ImGui::StyleColorsDark();
56     if (ImGui::GetIO().ConfigFlags & ImGuiConfigFlags_ViewportsEnable) {
57         ImGui::GetStyle().WindowRounding = 0.f;
58         ImGui::GetStyle().Colors[ImGuiCol_WindowBg].w = 1.f;
59     }
60
61     // Setting up ImGui
62     ImGui_ImplGlfw_InitForOpenGL(Graphics::GetWindow(), true);
63     ImGui_ImplOpenGL3_Init("#version 330");
64
65     return true;
66 }
```

References editor, Graphics::GetWindow(), Trace::Message(), object_to_copy, selected_component, and selected_↵ object.

Referenced by Engine::Initialize().

4.4.2.13 Make_Display_String() `std::string Editor::Make_Display_String (`
`std::string inputString) [static], [private]`

Removes the filepath from a filename.

Parameters

<i>inputString</i>	Original filename (with filepath)
--------------------	-----------------------------------

Returns

std::string

Definition at line 758 of file editor.cpp.

```

758                                     {
759     size_t slashLoc = inputString.find_last_of("/");
760     size_t dotLoc = inputString.find_last_of(".");
761
762     if (slashLoc == std::string::npos || dotLoc == std::string::npos)
763         return inputString;
764
765     std::string newString = inputString.substr(slashLoc + 1, dotLoc);
766
767     return newString;
768 }
```

Referenced by Display_Components(), Display_Model(), Display_Scripts(), and Display_World_Settings().

4.4.2.14 Render() void Editor::Render () [static]

Render the editor.

Returns

void

Definition at line 114 of file editor.cpp.

```

114     {
115     ImGui::Render();
116     ImGui_ImplOpenGL3_RenderDrawData(ImGui::GetDrawData());
117
118     if (ImGui::GetIO().ConfigFlags & ImGuiConfigFlags_ViewportsEnable) {
119         GLFWwindow* backup_current_context = glfwGetCurrentContext();
120         ImGui::UpdatePlatformWindows();
121         ImGui::RenderPlatformWindowsDefault();
122         glfwMakeContextCurrent(backup_current_context);
123     }
124 }
```

Referenced by Graphics::Render().

4.4.2.15 Reset() void Editor::Reset () [static]

Sets selected object to invalid value.

Returns

void

Definition at line 147 of file editor.cpp.

```

147     {
148         editor->selected_object = -1;
149     }
```

References editor, and selected_object.

Referenced by Engine::Restart().

4.4.2.16 Shutdown() void Editor::Shutdown () [static]

Destroy editor windows and systems.

Returns

void

Definition at line 131 of file editor.cpp.

```

131     {
132         if (!editor) return;
133
134         ImGui_ImplOpenGL3_Shutdown();
135         ImGui_ImplGlfw_Shutdown();
136         ImGui::DestroyContext();
137
138         delete editor;
139         editor = nullptr;
140     }
```

References editor.

Referenced by Engine::Shutdown().

4.4.2.17 Update() void Editor::Update () [static]

Updates the editor content and calls display functions.

Returns

void

Definition at line 73 of file editor.cpp.

```

73     {
74         // ImGui update functions
75         ImGui_ImplOpenGL3_NewFrame();
76         ImGui_ImplGlfw_NewFrame();
77         ImGui::NewFrame();
78
79         //ImGui::ShowDemoWindow();
80
81         // Updating whether program should ignore keyboard input
82         if (!ImGui::GetIO().WantCaptureKeyboard) {
83             editor->takeKeyboardInput = true;
84         }
85         else {
86             editor->takeKeyboardInput = false;
87         }
88
89         // Keyboard shortcuts
90         if (!editor->takeKeyboardInput) {
91             // Save current settings as preset
92             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_LEFT_CONTROL) == GLFW_PRESS) {
93                 if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_S) == GLFW_PRESS) {
94                     if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_S) == GLFW_RELEASE) {
95                         Engine::Write();
96                     }
97                 }
98             }
99         }
100
101         // Display the different windows
102         editor->Display_Dockspace();
```

```
103     editor->Display_Scene();
104     editor->Display_Components();
105     editor->Display_World_Settings();
106     editor->Display_Camera_Settings();
107 }
```

References `Display_Camera_Settings()`, `Display_Components()`, `Display_Dockspace()`, `Display_Scene()`, `Display_World_Settings()`, `editor`, `Graphics::GetWindow()`, `takeKeyboardInput`, and `Engine::Write()`.

Referenced by `Engine::Update()`.

The documentation for this class was generated from the following files:

- [editor.hpp](#)
- [editor.cpp](#)

4.5 Engine Class Reference

```
#include <engine.hpp>
```

Static Public Member Functions

- static bool [Initialize](#) ()
Initializes the engine and the systems in the engine.
- static void [Update](#) ()
Updates object and camera. [Object](#) updates have a fixed time step, camera updates have variable time step.
- static void [Shutdown](#) ()
Shutdown systems and then engine.
- static bool [Restart](#) ()
Resets the objects in the engine.
- static bool [Restart](#) (std::string [presetName](#))
Resets the engine to the given preset.
- static float [GetDeltaTime](#) ()
Returns delta time (variable)
- static float [GetDt](#) ()
Returns delta time (fixed)
- static double & [GetGravConst](#) ()
Returns gravitational constant.
- static std::string [GetPresetName](#) ()
Returns the name of the current preset.
- static float & [GetLightPower](#) ()
Returns reference to power of the light in the scene.
- static glm::vec3 & [GetLightPos](#) ()
Returns reference to the position of the light in the scene.
- static void [Write](#) ()
Writes the engine data to a preset file (creates new one if it doesn't already exist)
- static void [SetPresetName](#) (std::string [presetName_](#))
Sets the name of the preset file.

Private Attributes

- bool `isRunning`
state of the main loop
- float `deltaTime`
time between frames
- float `accumulator`
amount of unused time for physics updates
- float `time`
total time
- const float `dt` = 0.01f
fixed delta time for physics updates
- std::chrono::steady_clock::time_point `currentTime`
current read time
- std::chrono::steady_clock::time_point `newTime`
newest read time
- std::chrono::steady_clock::duration `timeTaken`
time between frames
- double `gravConst`
gravitational constant (used in physics)
- std::string `presetName`
name of the preset being used
- float `lightPower`
Power of the light in the scene.
- glm::vec3 `lightPos`
Position of the light in the scene.

4.5.1 Detailed Description

`Engine` class

Definition at line 24 of file engine.hpp.

4.5.2 Member Function Documentation**4.5.2.1 GetDeltaTime()** `float Engine::GetDeltaTime () [static]`

Returns delta time (variable)

Returns

float Variable delta time

Definition at line 214 of file engine.cpp.

```
214 { return engine->deltaTime; }
```

References `deltaTime`, and `engine`.

Referenced by `Camera::MouseUpdate()`, and `Camera::Update()`.

4.5.2.2 GetDt() `float Engine::GetDt () [static]`

Returns delta time (fixed)

Returns

float Fixed delta time

Definition at line 221 of file engine.cpp.

```
221 { return engine->dt; }
```

References dt, and engine.

Referenced by Behavior::Update(), and Physics::Update().

4.5.2.3 GetGravConst() `double & Engine::GetGravConst () [static]`

Returns gravitational constant.

Returns

double Gravitational constant

Definition at line 228 of file engine.cpp.

```
228 { return engine->gravConst; }
```

References engine, and gravConst.

Referenced by Editor::Display_World_Settings(), and Physics::UpdateGravity().

4.5.2.4 GetLightPos() `glm::vec3 & Engine::GetLightPos () [static]`

Returns reference to the position of the light in the scene.

Returns

glm::vec3&

Definition at line 249 of file engine.cpp.

```
249 { return engine->lightPos; }
```

References engine, and lightPos.

Referenced by Editor::Display_World_Settings(), and Model_Data::Draw().

4.5.2.5 GetLightPower() `float & Engine::GetLightPower () [static]`

Returns reference to power of the light in the scene.

Returns

`float&`

Definition at line 242 of file engine.cpp.

```
242 { return engine->lightPower; }
```

References engine, and lightPower.

Referenced by Editor::Display_World_Settings(), and Model_Data::Draw().

4.5.2.6 GetPresetName() `std::string Engine::GetPresetName () [static]`

Returns the name of the current preset.

Returns

`std::string`

Definition at line 235 of file engine.cpp.

```
235 { return engine->presetName; }
```

References engine, and presetName.

Referenced by Editor::Display_World_Settings().

4.5.2.7 Initialize() `bool Engine::Initialize () [static]`

Initializes the engine and the systems in the engine.

Returns

true

false

Definition at line 42 of file engine.cpp.

```

42     {
43         // Initializing engine
44         engine = new Engine;
45         if (!engine) {
46             Trace::Message("Engine was not initialized.\n");
47             return false;
48         }
49
50         // Initializing random
51         if (!Random::Initialize()) return false;
52
53         // Reading settings from json
54         File_Reader settings;
55         if (settings.Read_File(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/settings.json")) {
56             // Setting up sub systems
57             if (!Camera::Initialize(settings)) return false;
58             if (!Graphics::Initialize(settings)) return false;
59             if (!Model_Data_Manager::Initialize()) return false;
60             if (!Texture_Manager::Initialize()) return false;
61
62             File_Reader preset;
63
64             engine->presetName = std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/preset/" +
settings.Read_String("preset");
65             if (preset.Read_File(engine->presetName)) {
66                 engine->gravConst = preset.Read_Double("gravConst");
67                 engine->lightPos = preset.Read_Vec3("lightPos");
68                 if (engine->lightPos == glm::vec3(0.f)) {
69                     engine->lightPos = glm::vec3(4, 4, 0);
70                 }
71                 if (!Object_Manager::Initialize(preset)) return false;
72             }
73             else {
74                 engine->presetName = "no preset";
75                 if (!Object_Manager::Initialize()) return false;
76             }
77
78             engine->gravConst = 0.0;
79
80             engine->lightPower = 1000.f;
81         }
82         else {
83             engine->presetName = "no preset";
84             engine->gravConst = 0.0;
85
86             engine->lightPower = 1000.f;
87             engine->lightPos = glm::vec3(4, 4, 0);
88
89             // Setting up sub systems
90             if (!Camera::Initialize()) return false;
91             if (!Graphics::Initialize()) return false;
92             if (!Model_Data_Manager::Initialize()) return false;
93             if (!Texture_Manager::Initialize()) return false;
94             if (!Object_Manager::Initialize()) return false;
95         }
96
97         // Initializing the editor
98         if (!Editor::Initialize()) return false;
99
100        // Setting up variables used for dt
101        engine->currentTime = std::chrono::steady_clock::now();
102        engine->accumulator = 0.f;
103        engine->time = 0.f;
104        engine->isRunning = true;
105
106        return true;
107    }

```

References accumulator, currentTime, engine, gravConst, Random::Initialize(), Editor::Initialize(), Texture_Manager::Initialize(), Model_Data_Manager::Initialize(), Object_Manager::Initialize(), Camera::Initialize(), Graphics::Initialize(),

isRunning, lightPos, lightPower, Trace::Message(), presetName, File_Reader::Read_Double(), File_Reader::Read_File(), File_Reader::Read_String(), File_Reader::Read_Vec3(), and time.

Referenced by main().

4.5.2.8 Restart() [1/2] `bool Engine::Restart () [static]`

Resets the objects in the engine.

Returns

true
false

Definition at line 164 of file engine.cpp.

```

164     {
165         // Initializing object manager
166         File_Reader settings;
167         if (! settings.Read_File(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/settings.json"))
168             return false;
169         File_Reader preset;
170         if (!preset.Read_File(engine->presetName)) return false;
171
172         // Removing all current objects
173         Object_Manager::Shutdown();
174         Editor::Reset();
175
176         engine->presetName = settings.Read_String("preset");
177         engine->gravConst = preset.Read_Double("gravConst");
178         if (!Object_Manager::Initialize(preset)) return false;
179
180         return true;
181     }

```

References engine, gravConst, Object_Manager::Initialize(), presetName, File_Reader::Read_Double(), File_Reader::Read_File(), File_Reader::Read_String(), Editor::Reset(), and Object_Manager::Shutdown().

Referenced by Editor::Display_World_Settings(), and Graphics::Update().

4.5.2.9 Restart() [2/2] `bool Engine::Restart (std::string presetName) [static]`

Resets the engine to the given preset.

Parameters

<i>presetName</i>	Given preset
-------------------	--------------

Returns

true
false

Definition at line 190 of file engine.cpp.

```

190                                     {
191     // Initializing object manager
192     File_Reader settings;
193     settings.Read_File(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/settings.json");
194     Trace::Message(presetName + "\n");
195     File_Reader preset;
196     if (!preset.Read_File(presetName)) return false;
197
198     // Removing all current objects
199     Object_Manager::Shutdown();
200     Editor::Reset();
201
202     engine->presetName = presetName;
203     engine->gravConst = preset.Read_Double("gravConst");
204     if (!Object_Manager::Initialize(preset)) return false;
205
206     return true;
207 }
```

References engine, gravConst, Object_Manager::Initialize(), Trace::Message(), presetName, File_Reader::Read_↵
Double(), File_Reader::Read_File(), Editor::Reset(), and Object_Manager::Shutdown().

4.5.2.10 SetPresetName() void Engine::SetPresetName (
std::string presetName_) [static]

Sets the name of the preset file.

Parameters

<i>preset</i> ↵ Name_	
--------------------------	--

Returns

void

Definition at line 273 of file engine.cpp.

```

273                                     {
274     engine->presetName = presetName_;
275 }
```

References engine, and presetName.

Referenced by Editor::Display_Menu_Bar().

4.5.2.11 Shutdown() void Engine::Shutdown () [static]

Shutdown systems and then engine.

Returns

void

Definition at line 141 of file engine.cpp.

```

141         {
142             if (!engine) return;
143
144             // Shutdown sub systems
145             Editor::Shutdown();
146             Random::Shutdown();
147             Object_Manager::Shutdown();
148             Graphics::Shutdown();
149             Camera::Shutdown();
150             Texture_Manager::Shutdown();
151             Model_Data_Manager::Shutdown();
152
153             // Delete engine object
154             delete engine;
155             engine = nullptr;
156     }
```

References engine, Random::Shutdown(), Editor::Shutdown(), Model_Data_Manager::Shutdown(), Texture_Manager::Shutdown(), Camera::Shutdown(), Object_Manager::Shutdown(), and Graphics::Shutdown().

Referenced by main().

4.5.2.12 Update() void Engine::Update () [static]

Updates object and camera. **Object** updates have a fixed time step, camera updates have variable time step.

Returns

void

Definition at line 115 of file engine.cpp.

```

115         {
116             // Calculating dt
117             engine->newTime = std::chrono::steady_clock::now();
118             engine->timeTaken = engine->newTime - engine->currentTime;
119             engine->deltaTime = float(engine->timeTaken.count()) *
120                 std::chrono::steady_clock::period::num / std::chrono::steady_clock::period::den;
121             engine->currentTime = engine->newTime;
122             engine->accumulator += engine->deltaTime;
123
124             Editor::Update();
125             Camera::Update();
126             // Only called when it is time (fixed time step)
127             while (engine->accumulator >= engine->dt) {
128                 // Update objects
129                 Object_Manager::Update();
130                 // Update dt related variables
131                 engine->accumulator -= engine->dt;
132                 engine->time += engine->dt;
133             }
134     }
```

References accumulator, currentTime, deltaTime, dt, engine, newTime, time, timeTaken, Editor::Update(), Camera::Update(), and Object_Manager::Update().

Referenced by Graphics::Update().

4.5.2.13 Write() `void Engine::Write () [static]`

Writes the engine data to a preset file (creates new one if it doesn't already exist)

Returns

void

Definition at line 257 of file engine.cpp.

```
257     {
258         File_Writer writer;
259
260         writer.Write_Value("gravConst", engine->gravConst);
261         writer.Write_Vec3("lightPos", engine->lightPos);
262         Object_Manager::Write(writer);
263
264         writer.Write_File(engine->presetName);
265     }
```

References engine, gravConst, lightPos, presetName, Object_Manager::Write(), File_Writer::Write_File(), File_Writer::Write_Value(), and File_Writer::Write_Vec3().

Referenced by Editor::Display_Menu_Bar(), and Editor::Update().

The documentation for this class was generated from the following files:

- [engine.hpp](#)
- [engine.cpp](#)

4.6 File_Reader Class Reference

```
#include <file_reader.hpp>
```

Public Member Functions

- bool [Read_File](#) (std::string filename)
Reads the json file data into the root variable.
- int [Read_Int](#) (std::string valueName)
Reads int from the json file stored in root.
- std::string [Read_String](#) (std::string valueName)
Reads std::string from the json file stored in root.
- glm::vec3 [Read_Vec3](#) (std::string valueName)
Reads glm::vec3 from the json file stored in root. glm::vec3 is constructed from an array.
- bool [Read_Bool](#) (std::string valueName)
Reads bool from the json file stored in root.
- float [Read_Float](#) (std::string valueName)
Reads float from the json stored in root.
- double [Read_Double](#) (std::string valueName)
Reads double from the json stored in root.
- std::string [Read_Object_Name](#) (std::string valueName)
Reads the name of an object from an object list (preset folder)
- std::string [Read_Object_Template_Name](#) (std::string valueName)
Reads the name of the template file for object.
- glm::vec3 [Read_Object_Position](#) (std::string valueName)
Reads the position of an object from an object list (preset folder)
- glm::vec3 [Read_Object_Scale](#) (std::string valueName)
Reads the scale of an object.
- std::string [Read_Behavior_Name](#) (std::string valueName)
Reads the name of the behavior.

Private Attributes

- rapidjson::Document [root](#)
Holds the data of the json file.

4.6.1 Detailed Description

[File_Reader](#) class

Definition at line 24 of file file_reader.hpp.

4.6.2 Member Function Documentation

4.6.2.1 Read_Behavior_Name() `std::string File_Reader::Read_Behavior_Name (std::string valueName)`

Reads the name of the behavior.

Parameters

<i>valueName</i>	Behavior to read
------------------	----------------------------------

Returns

std::string Name of the behavior

Definition at line 205 of file file_reader.cpp.

```

205                                     {
206     // Checking if value exists
207     if (!root["behaviors"].HasMember(valueName.c_str())) {
208         return std::string("");
209     }
210
211     return root["behaviors"][valueName.c_str()].GetString();
212 }
```

Referenced by Behavior::Read().

4.6.2.2 Read_Bool() `bool File_Reader::Read_Bool (std::string valueName)`

Reads bool from the json file stored in root.

Parameters

<i>valueName</i>	Name of the bool in the json file
------------------	-----------------------------------

Returns

true
false

Definition at line 96 of file file_reader.cpp.

```
96                                     {
97     // Checking if the value is a bool
98     if (!root.HasMember(valueName.c_str())) {
99         return false;
100    }
101    return root[valueName.c_str()].GetBool();
102 }
```

4.6.2.3 Read_Double()

```
double File_Reader::Read_Double (
    std::string valueName )
```

Reads double from the json stored in root.

Parameters

<i>valueName</i>	Name of the double in the json file
------------------	-------------------------------------

Returns

double Value that was read

Definition at line 124 of file file_reader.cpp.

```
124                                     {
125     // Checking if the value is a double (has decimal)
126     if (!root.HasMember(valueName.c_str())) {
127         return false;
128    }
129    return root[valueName.c_str()].GetDouble();
130 }
```

Referenced by Engine::Initialize(), and Engine::Restart().

4.6.2.4 Read_File()

```
bool File_Reader::Read_File (
    std::string filename )
```

Reads the json file data into the root variable.

Parameters

<i>filename</i>	Name of the file to be read
-----------------	-----------------------------

Returns

true
false

Definition at line 32 of file file_reader.cpp.

```

32                                     {
33     // Opening the json file
34     std::string fileToOpen = filename;
35     FILE* file = fopen(fileToOpen.c_str(), "r");
36     if (!file) return false;
37
38     char buffer[65536];
39     FileReadStream stream(file, buffer, sizeof(buffer));
40     root.ParseStream<0, UTF8<>, FileReadStream>(stream);
41
42     fclose(file);
43     return true;
44 }
```

Referenced by Engine::Initialize(), Object::Read(), Object::ReRead(), and Engine::Restart().

4.6.2.5 Read_Float() float File_Reader::Read_Float (
std::string valueName)

Reads float from the json stored in root.

Parameters

<i>valueName</i>	Name of the float in the json file
------------------	------------------------------------

Returns

float Value that was read

Definition at line 110 of file file_reader.cpp.

```

110                                     {
111     // Checking if the value is a double (has decimal)
112     if (!root.HasMember(valueName.c_str())) {
113         return 0.f;
114     }
115     return root[valueName.c_str()].GetFloat();
116 }
```

Referenced by Camera::Initialize(), and Physics::Read().

4.6.2.6 Read_Int() `int File_Reader::Read_Int (`
`std::string valueName)`

Reads int from the json file stored in root.

Parameters

<i>valueName</i>	Name of the int in the json file
------------------	----------------------------------

Returns

int Value that was read

Definition at line 52 of file file_reader.cpp.

```

52                                     {
53     // Checking if the value is an int
54     if (!root.HasMember(valueName.c_str())) {
55         return 0;
56     }
57     return root[valueName.c_str()].GetInt();
58 }
```

Referenced by Camera::Initialize(), and Graphics::Initialize().

4.6.2.7 Read_Object_Name() `std::string File_Reader::Read_Object_Name (std::string valueName)`

Reads the name of an object from an object list (preset folder)

Parameters

<i>valueName</i>	Specifies which object
------------------	------------------------

Returns

std::string Name of the object

Definition at line 138 of file file_reader.cpp.

```

138                                     {
139     // Checking if the value exists
140     if (!root.HasMember(valueName.c_str())) {
141         return std::string("");
142     }
143     if (!root[valueName.c_str()].HasMember("objectName")) {
144         return std::string("");
145     }
146
147     return root[valueName.c_str()]["objectName"].GetString();
148 }
```

Referenced by Object_Manager::ReadList().

4.6.2.8 Read_Object_Position() `glm::vec3 File_Reader::Read_Object_Position (std::string valueName)`

Reads the position of an object from an object list (preset folder)

Parameters

<i>valueName</i>	Specifies which object
------------------	------------------------

Returns

glm::vec3 Position of object

Definition at line 174 of file file_reader.cpp.

```
174                                     {
175     if (!root[valueName.c_str()].HasMember("position")) {
176         return glm::vec3(0.f, 0.f, 0.f);
177     }
178
179     Value& array = root[valueName.c_str()]["position"];
180     return glm::vec3(array[0].GetFloat(), array[1].GetFloat(), array[2].GetFloat());
181 }
```

Referenced by Object_Manager::ReadList().

4.6.2.9 Read_Object_Scale() glm::vec3 File_Reader::Read_Object_Scale (
std::string valueName)

Reads the scale of an object.

Parameters

<i>valueName</i>	
------------------	--

Returns

glm::vec3

Definition at line 189 of file file_reader.cpp.

```
189                                     {
190     // Checking if value exists
191     if (!root[valueName.c_str()].HasMember("scale")) {
192         return glm::vec3(0.f, 0.f, 0.f);
193     }
194
195     Value& array = root[valueName.c_str()]["scale"];
196     return glm::vec3(array[0].GetFloat(), array[1].GetFloat(), array[2].GetFloat());
197 }
```

Referenced by Object_Manager::ReadList().

4.6.2.10 Read_Object_Template_Name() std::string File_Reader::Read_Object_Template_Name (
std::string valueName)

Reads the name of the template file for object.

Parameters

<i>valueName</i>	
------------------	--

Returns

std::string

Definition at line 156 of file file_reader.cpp.

```

156
157     // Checking if the value exists
158     if (!root.HasMember(valueName.c_str())) {
159         return std::string("");
160     }
161     if (!root[valueName.c_str()].HasMember("templateName")) {
162         return std::string("");
163     }
164
165     return root[valueName.c_str()]["templateName"].GetString();
166 }
```

Referenced by Object_Manager::ReadList().

4.6.2.11 Read_String() std::string File_Reader::Read_String (std::string valueName)

Reads std::string from the json file stored in root.

Parameters

<i>valueName</i>	Name of the std::string in the json file
------------------	--

Returns

std::string Value that was read

Definition at line 66 of file file_reader.cpp.

```

66
67     // Checking if the value is a std::string
68     if (!root.HasMember(valueName.c_str())) {
69         return std::string("");
70     }
71     return root[valueName.c_str()].GetString();
72 }
```

Referenced by Model_Data_Manager::Get(), Texture_Manager::Get(), Engine::Initialize(), Shader::Initialize(), Model_Data::Load(), Object::ReRead(), and Engine::Restart().

4.6.2.12 Read_Vec3() glm::vec3 File_Reader::Read_Vec3 (std::string valueName)

Reads glm::vec3 from the json file stored in root. glm::vec3 is constructed from an array.

Parameters

<i>valueName</i>	Name of the glm::vec3 in the json file
------------------	--

Returns

glm::vec3 Value that was read

Definition at line 81 of file file_reader.cpp.

```

81                                     {
82     // Checking if the value is an array
83     if (!root.HasMember(valueName.c_str())) {
84         return glm::vec3(0.f, 0.f, 0.f);
85     }
86     return glm::vec3(root[valueName.c_str()][0].GetFloat(), root[valueName.c_str()][1].GetFloat(),
87                     root[valueName.c_str()][2].GetFloat());

```

Referenced by Engine::Initialize(), and Physics::Read().

The documentation for this class was generated from the following files:

- [file_reader.hpp](#)
- [file_reader.cpp](#)

4.7 File_Writer Class Reference

```
#include <file_writer.hpp>
```

Public Member Functions

- [File_Writer](#) ()
Creates root object to write data into.
- void [Write_File](#) (std::string filename)
Writes all the data stored in root to the given filename.
- void [Write_Vec3](#) (std::string valueName, glm::vec3 value)
Write a glm::vec3 into root.
- void [Write_String](#) (std::string valueName, std::string value)
Write a std::string into root.
- template<typename T >
void [Write_Value](#) (std::string valueName, T value)
Writes most values to root (can't do strings)
- void [Write_Behavior_Name](#) (std::vector< std::string > &behaviorNames)
Writing behaviorNames into nested object and then into root.
- void [Write_Object_Data](#) (Object *object)
Writing data of an object into root.

Private Attributes

- rapidjson::Document [root](#)
Holds the data for the json file.

4.7.1 Detailed Description

[File_Writer](#) class

Definition at line 30 of file file_writer.hpp.

4.7.2 Constructor & Destructor Documentation

4.7.2.1 File_Writer() File_Writer::File_Writer ()

Creates root object to write data into.

Definition at line 27 of file file_writer.cpp.

```
27     {
28         root.SetObject();
29     }
```

4.7.3 Member Function Documentation

4.7.3.1 Write_Behavior_Name() void File_Writer::Write_Behavior_Name (std::vector< std::string > & behaviorNames)

Writing behaviorNames into nested object and then into root.

Parameters

<i>behaviorNames</i>	
----------------------	--

Definition at line 88 of file file_writer.cpp.

```
88     {
89         Value behaviors(kObjectType);
90
91         // Filling object
92         for (unsigned i = 0; i < behaviorNames.size(); ++i) {
93             std::string behaviorName = std::string("behavior_" + std::to_string(i));
94             Value name(behaviorName.c_str(), SizeType(behaviorName.size()), root.GetAllocator());
95
96             behaviors.AddMember(name, StringRef(behaviorNames[i].c_str()), root.GetAllocator());
97         }
```



```

98
99     // Nesting object into root
100     root.AddMember("behaviors", behaviors, root.GetAllocator());
101 }

```

Referenced by Behavior::Write().

4.7.3.2 Write_File() void File_Writer::Write_File (
 std::string filename)

Writes all the data stored in root to the given filename.

Parameters

<i>filename</i>	
-----------------	--

Definition at line 36 of file file_writer.cpp.

```

36                                     {
37     std::string fileToOpen = filename;
38     FILE* file = fopen(fileToOpen.c_str(), "w");
39
40     char buffer[65536];
41     FileWriteStream stream(file, buffer, sizeof(buffer));
42
43     PrettyWriter<FileWriteStream> writer(stream);
44     writer.SetMaxDecimalPlaces(3);
45     writer.SetFormatOptions(kFormatSingleLineArray);
46     root.Accept(writer);
47
48     fclose(file);
49 }

```

Referenced by Engine::Write(), and Object::Write().

4.7.3.3 Write_Object_Data() void File_Writer::Write_Object_Data (
 Object * object)

Writing data of an object into root.

Parameters

<i>object</i>	
---------------	--

Definition at line 108 of file file_writer.cpp.

```

108                                     {
109     if (!object) return;
110
111     // Getting transform data from object
112     Transform* transform = object->GetComponent<Transform>();
113     glm::vec3 startPos = { 0.f, 0.f, 0.f };
114     glm::vec3 startScale = { 1.f, 1.f, 1.f };
115     if (transform) startPos = transform->GetStartPosition();
116     if (transform) startScale = transform->GetScale();

```

```

117
118 // Putting position into value rapidjson can use
119 Value pos(kArrayType);
120 pos.PushBack(startPos.x, root.GetAllocator());
121 pos.PushBack(startPos.y, root.GetAllocator());
122 pos.PushBack(startPos.z, root.GetAllocator());
123
124 // Putting scale into value rapidjson can use
125 Value scale(kArrayType);
126 scale.PushBack(startScale.x, root.GetAllocator());
127 scale.PushBack(startScale.y, root.GetAllocator());
128 scale.PushBack(startScale.z, root.GetAllocator());
129
130 // Creating and filling object
131 Value objectData(kObjectType);
132
133 Value objectName(object->GetName().c_str(), SizeType(object->GetName().size()), root.GetAllocator());
134 objectData.AddMember(StringRef("objectName"), objectName, root.GetAllocator());
135 Value templateName(object->GetTemplateName().c_str(), SizeType(object->GetTemplateName().size()),
136 root.GetAllocator());
137 objectData.AddMember(StringRef("templateName"), templateName, root.GetAllocator());
138 objectData.AddMember(StringRef("position"), pos, root.GetAllocator());
139 objectData.AddMember(StringRef("scale"), scale, root.GetAllocator());
140
141 // Nesting object into root
142 std::string objectIdName = "object_" + std::to_string(object->GetId());
143 Value name(objectIdName.c_str(), SizeType(objectIdName.size()), root.GetAllocator());
144 root.AddMember(name, objectData, root.GetAllocator());
145 }

```

References `Object::GetId()`, `Object::GetName()`, `Transform::GetScale()`, `Transform::GetStartPosition()`, and `Object::GetTemplateName()`.

Referenced by `Object_Manager::Write()`.

4.7.3.4 Write_String() `void File_Writer::Write_String (`
`std::string valueName,`
`std::string value)`

Write a `std::string` into root.

Parameters

<i>valueName</i>	
<i>value</i>	

Definition at line 75 of file `file_writer.cpp`.

```

75
76 // Storing std::string in variable rapidjson can write
77 Value name(valueName.c_str(), SizeType(valueName.size()), root.GetAllocator());
78 Value newValue(value.c_str(), SizeType(value.size()), root.GetAllocator());
79
80 root.AddMember(name, newValue, root.GetAllocator());
81 }

```

Referenced by `Model::Write()`, and `Object::Write()`.

4.7.3.5 Write_Value() `template<typename T >`

```
void File_Writer::Write_Value (
    std::string valueName,
    T value ) [inline]
```

Writes most values to root (can't do strings)

Template Parameters

<i>T</i>	
----------	--

Parameters

<i>valueName</i>	Name of value being written to root
<i>value</i>	Value being written to root

Definition at line 46 of file file_writer.hpp.

```
46                                     {
47     rapidjson::Value name(valueName.c_str(), rapidjson::SizeType(valueName.size()),
48         root.GetAllocator());
49     root.AddMember(name, value, root.GetAllocator());
49 }
```

References root.

Referenced by Engine::Write(), and Physics::Write().

4.7.3.6 Write_Vec3() `void File_Writer::Write_Vec3 (`

```
    std::string valueName,
    glm::vec3 value )
```

Write a glm::vec3 into root.

Parameters

<i>valueName</i>	Name of glm::vec3
<i>value</i>	glm::vec3 to write

Definition at line 57 of file file_writer.cpp.

```
57                                     {
58     // Storing glm::vec3 in array that rapidjson can write
59     Value vector3(kArrayType);
60     vector3.PushBack(value.x, root.GetAllocator());
61     vector3.PushBack(value.y, root.GetAllocator());
62     vector3.PushBack(value.z, root.GetAllocator());
63
64     // Writing vector3 into root
65     Value name(valueName.c_str(), SizeType(valueName.size()), root.GetAllocator());
66     root.AddMember(name, vector3, root.GetAllocator());
67 }
```

Referenced by Engine::Write(), Transform::Write(), and Physics::Write().

The documentation for this class was generated from the following files:

- [file_writer.hpp](#)
- [file_writer.cpp](#)

4.8 Graphics Class Reference

```
#include <graphics.hpp>
```

Public Member Functions

- [Graphics](#) (int width, int height)
Creates [Graphics](#) object with given window size.

Static Public Member Functions

- static bool [Initialize](#) ([File_Reader](#) &settings)
Initializes the [Graphics](#) system using the settings in the given data.
- static bool [Initialize](#) ()
Initializes the [Graphics](#) system using default values.
- static bool [InitializeGL](#) ()
Initializes the settings of the graphics system.
- static void [Update](#) ()
[Graphics](#) update loop. Calls other update functions for the engine, input, and rendering. This is the main update function for the engine.
- static void [Render](#) ()
Renders all of the objects in the object_manager.
- static void [Shutdown](#) ()
Shutdown the graphics system.
- static bool [ErrorCheck](#) (GLenum error)
Checking for error in given enum.
- static void [ErrorCallback](#) (int error, const char *description)
Error callback for when the graphics system has an issue.
- static std::pair< int, int > [GetWindowSize](#) ()
Returns window size.
- static GLFWwindow * [GetWindow](#) ()
Return the graphics window.

Private Attributes

- std::pair< int, int > [windowSize](#)
Size of the window.
- GLFWwindow * [window](#)
Window for application.
- GLuint [vertexArrayId](#)
Id of the VAO.

4.8.1 Detailed Description

[Graphics](#) class

Definition at line 28 of file graphics.hpp.

4.8.2 Constructor & Destructor Documentation

4.8.2.1 Graphics() `Graphics::Graphics (`
 `int width,`
 `int height)`

Creates [Graphics](#) object with given window size.

Parameters

<i>width</i>	
<i>height</i>	

Definition at line 51 of file graphics.cpp.

```
51 {  
52     windowSize.first = width;  
53     windowSize.second = height;  
54 }
```

4.8.3 Member Function Documentation

4.8.3.1 errorCallback() `void Graphics::ErrorCallback (`
 `int error,`
 `const char * description) [static]`

Error callback for when the graphics system has an issue.

Parameters

<i>error</i>	Error that occurred
<i>description</i>	Description of error

Returns

void

Definition at line 275 of file graphics.cpp.

```
275     {
276     Trace::Message("Error: " + std::string(description) + ": " + std::to_string(error) + "\n");
277 }
```

References `Trace::Message()`.

4.8.3.2 ErrorCheck() `bool Graphics::ErrorCheck (`
`GLenum error) [static]`

Checking for error in given enum.

Parameters

<i>error</i>	Possible error
--------------	----------------

Returns

true

false

Definition at line 286 of file graphics.cpp.

```
286     {
287     error = glGetError();
288     if (error != GL_NO_ERROR) {
289     Trace::Message("Error initializing OpenGL. \n");
290     return false;
291     }
292
293     return true;
294 }
```

References `Trace::Message()`.

Referenced by `InitializeGL()`.

4.8.3.3 GetWindow() `GLFWwindow * Graphics::GetWindow () [static]`

Return the graphics window.

Returns

GLFWwindow*

Definition at line 310 of file graphics.cpp.

```
310     {
311     return graphics->window;
312 }
```

References `graphics`, and `window`.

Referenced by `Editor::Display_Scene()`, `Editor::Initialize()`, `Editor::Update()`, `Camera::Update()`, and `Update()`.

4.8.3.4 GetWindowSize() `std::pair< int, int > Graphics::GetWindowSize () [static]`

Returns window size.

Returns

`std::pair<int, int>`

Definition at line 301 of file `graphics.cpp`.

```
301 {
302     return graphics->windowSize;
303 }
```

References `graphics`, and `windowSize`.

4.8.3.5 Initialize() [1/2] `bool Graphics::Initialize () [static]`

Initializes the [Graphics](#) system using default values.

Returns

`true`

`false`

Definition at line 115 of file `graphics.cpp`.

```
115 {
116     // Initializing graphics
117     graphics = new Graphics(1920, 1080);
118     if (!graphics) {
119         Trace::Message("Graphics was not initialized.");
120         return false;
121     }
122
123     // Setting up error recording with graphics
124     glfwSetErrorCallback(ErrorCallback);
125
126     if (!glfwInit()) {
127         Trace::Message("Could not initialize GLFW.\n");
128         return false;
129     }
130
131     // Setting up the graphics window
132     graphics->window = glfwCreateWindow(graphics->windowSize.first, graphics->windowSize.second,
133         "pEngine", nullptr, nullptr);
134     if (!graphics->window) {
135         Trace::Message("Error creating window.\n");
136         return false;
137     }
138
139     // Setting up callback functions
140     glfwSetCursorPosCallback(graphics->window, Camera::MouseUpdate);
141
142     glfwMakeContextCurrent(graphics->window);
143     //glfwSwapInterval(1);
144     InitializeGL();
145
146     glewExperimental = GL_TRUE;
147     glewInit();
148
149     // Setting up input for keyboard and mouse using glfw library
150     glfwSetInputMode(graphics->window, GLFW_STICKY_KEYS, GL_TRUE);
151     glfwSetInputMode(graphics->window, GLFW_CURSOR, GLFW_CURSOR_HIDDEN);
152 }
```

```

153     glGenVertexArrays(1, &graphics->vertexArrayId);
154     glBindVertexArray(graphics->vertexArrayId);
155
156     if (!Shader::Initialize()) return false;
157
158     return true;
159 }

```

References `graphics`, `Shader::Initialize()`, `Trace::Message()`, `Camera::MouseUpdate()`, `vertexArrayId`, `window`, and `windowSize`.

Referenced by `Engine::Initialize()`.

4.8.3.6 Initialize() [2/2] `bool Graphics::Initialize (`
 `File_Reader & settings) [static]`

Initializes the `Graphics` system using the settings in the given data.

Parameters

<i>settings</i>	Settings information
-----------------	----------------------

Returns

`true`

`false`

Definition at line 63 of file `graphics.cpp`.

```

63                                     {
64     // Initializing graphics
65     graphics = new Graphics(settings.Read_Int("windowWidth"), settings.Read_Int("windowHeight"));
66     if (!graphics) {
67         Trace::Message("Graphics was not initialized.");
68         return false;
69     }
70
71     // Setting up error recording with graphics
72     glfwSetErrorCallback(ErrorCallback);
73
74     if (!glfwInit()) {
75         Trace::Message("Could not initialize GLFW.\n");
76         return false;
77     }
78
79     // Setting up the graphics window
80     graphics->window = glfwCreateWindow(graphics->windowSize.first, graphics->windowSize.second,
81         "pEngine", nullptr, nullptr);
82     if (!graphics->window) {
83         Trace::Message("Error creating window.\n");
84         return false;
85     }
86
87     // Setting up callback functions
88     glfwSetCursorPosCallback(graphics->window, Camera::MouseUpdate);
89
90     glfwMakeContextCurrent(graphics->window);
91     //glfwSwapInterval(1);
92     InitializeGL();
93
94     glewExperimental = GL_TRUE;
95     glewInit();
96

```



```

97     // Setting up input for keyboard and mouse using glfw library
98     glfwSetInputMode(graphics->window, GLFW_STICKY_KEYS, GL_TRUE);
99     glfwSetInputMode(graphics->window, GLFW_CURSOR, GLFW_CURSOR_HIDDEN);
100
101     glGenVertexArrays(1, &graphics->vertexArrayId);
102     glBindVertexArray(graphics->vertexArrayId);
103
104     if (!Shader::Initialize(settings)) return false;
105
106     return true;
107 }

```

References `graphics`, `Shader::Initialize()`, `Trace::Message()`, `Camera::MouseUpdate()`, `File_Reader::Read_Int()`, `vertexArrayId`, `window`, and `windowSize`.

4.8.3.7 InitializeGL() `bool Graphics::InitializeGL () [static]`

Initializes the settings of the graphics system.

Returns

`true`

`false`

Definition at line 167 of file `graphics.cpp`.

```

167     {
168         GLenum error = GL_NO_ERROR;
169
170         glClearColor(0.f, 0.f, 0.f, 1.f);
171         if (!Graphics::ErrorCheck(error)) return false;
172
173         glClearDepth(1.f);
174         if (!Graphics::ErrorCheck(error)) return false;
175
176         glEnable(GL_DEPTH_TEST);
177         if (!Graphics::ErrorCheck(error)) return false;
178
179         glDepthFunc(GL_LEQUAL);
180         if (!Graphics::ErrorCheck(error)) return false;
181
182         glShadeModel(GL_SMOOTH);
183         if (!Graphics::ErrorCheck(error)) return false;
184
185         glHint(GL_PERSPECTIVE_CORRECTION_HINT, GL_NICEST);
186         if (!Graphics::ErrorCheck(error)) return false;
187
188         glEnable(GL_CULL_FACE);
189         if (!Graphics::ErrorCheck(error)) return false;
190
191         return true;
192     }

```

References `ErrorCheck()`.

4.8.3.8 Render() void Graphics::Render () [static]

Renders all of the objects in the object_manager.

Returns

void

Definition at line 221 of file graphics.cpp.

```

221     {
222         // Setting up graphics system for rendering
223         glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
224         Shader::Update();
225
226         glm::mat4 projection = perspective(radians(Camera::GetFov()), (float)graphics->windowSize.first /
227             (float)graphics->windowSize.second, Camera::GetNear(), Camera::GetFar());
228
229         // Getting the view matrix of the camera
230         glm::mat4 view = lookAt(
231             Camera::GetPosition(),
232             Camera::GetPosition() + Camera::GetFront(),
233             Camera::GetUp());
234
235         // Rendering all of the objects
236         for (unsigned i = 0; i < Object_Manager::GetSize(); ++i) {
237             Object* object = Object_Manager::FindObject(i);
238
239             Model* model = object->GetComponent<Model>();
240             if (!model) continue;
241
242             model->Draw(projection, view);
243         }
244
245         Editor::Render();
246
247         glfwSwapBuffers(graphics->window);
248     }

```

References Model::Draw(), Object_Manager::FindObject(), Camera::GetFar(), Camera::GetFov(), Camera::GetFront(), Camera::GetNear(), Camera::GetPosition(), Object_Manager::GetSize(), Camera::GetUp(), graphics, Editor::Render(), Shader::Update(), window, and windowSize.

4.8.3.9 Shutdown() void Graphics::Shutdown () [static]

Shutdown the graphics system.

Returns

void

Definition at line 255 of file graphics.cpp.

```

255     {
256         if (!graphics) return;
257
258         Shader::Shutdown();
259         glDeleteVertexArrays(1, &graphics->vertexArrayId);
260         // Shutting down opengl
261         glfwDestroyWindow(graphics->window);
262         glfwTerminate();
263         // Deleting graphics object
264         delete graphics;
265         graphics = nullptr;
266     }

```

References graphics, Shader::Shutdown(), vertexArrayId, and window.

Referenced by Engine::Shutdown().

4.8.3.10 Update() `void Graphics::Update () [static]`

Graphics update loop. Calls other update functions for the engine, input, and rendering. This is the main update function for the engine.

Returns

void

Definition at line 200 of file `graphics.cpp`.

```

200     {
201         while(!glfwWindowShouldClose(graphics->window)) {
202             // Run updates
203             Engine::Update();
204             Render();
205             glfwPollEvents();
206
207             // Check for restart
208             if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_R) == GLFW_PRESS && Editor::GetTakeKeyboardInput()) {
209                 if (glfwGetKey(Graphics::GetWindow(), GLFW_KEY_R) == GLFW_RELEASE) {
210                     Engine::Restart();
211                 }
212             }
213         }
214     }
```

References `Editor::GetTakeKeyboardInput()`, `GetWindow()`, `graphics`, `Engine::Restart()`, `Engine::Update()`, and `window`.

Referenced by `main()`.


The documentation for this class was generated from the following files:

- [graphics.hpp](#)
- [graphics.cpp](#)

4.9 Model Class Reference

```
#include <model.hpp>
```

Inheritance diagram for Model:



Public Member Functions

- [Model](#) (GLenum mode_=GL_TRIANGLES)
Creates a [Model](#) object with default values.
- [Model](#) (const [Model](#) &other)
Copy constructor.
- [Model](#) ([File_Reader](#) &reader, GLenum mode_=GL_TRIANGLES)
Creates a [Model](#) object using the data from a file.
- [Model](#) * [Clone](#) () const
Clones this [Model](#) object.
- void [Load](#) ([File_Reader](#) &reader)
Load in the model data from a file (use model manager to not have multiple versions of the same model)
- void [Draw](#) (glm::mat4 projection, glm::mat4 view)
Draw the model.
- void [Read](#) ([File_Reader](#) &reader)
Reads name of model file and passes it to the Load function.
- void [Write](#) ([File_Writer](#) &writer)
Gives name of model and texture to writer.
- void [SwitchModel](#) (std::string modelName)
Switches the current model to that of the filename provided.
- void [SwitchTexture](#) (std::string textureName)
Switches the current texture to that of the filename provided.
- std::string [GetModelName](#) () const
Returns the filename of the current model.
- std::string [GetTextureName](#) () const
Returns the filename of the current texture.
- [Texture](#) * [GetTexture](#) () const
Returns pointer to texture object.

Static Public Member Functions

- static [CType](#) [GetCType](#) ()
Gets the CType of [Model](#) (used in [Object::GetComponent<>\(\)](#))

Private Attributes

- GLenum [mode](#)
Draw mode (Default is GL_TRIANGLES)
- [Model_Data](#) * [data](#)
Data about the faces of the model.
- [Texture](#) * [texture](#)
[Texture](#) object of model.

Additional Inherited Members

4.9.1 Detailed Description

[Model](#) class

Definition at line 32 of file model.hpp.

4.9.2 Constructor & Destructor Documentation

4.9.2.1 Model() [1/3] `Model::Model (`
`GLenum mode_ = GL_TRIANGLES)`

Creates a [Model](#) object with default values.

Parameters

<i>mode_</i>	Draw mode for opengl
—	

Definition at line 32 of file model.cpp.

```
32 : Component(CType::CModel), mode(mode_), data(nullptr), texture(nullptr) {}
```

Referenced by Clone().

4.9.2.2 Model() [2/3] `Model::Model (`
`const Model & other)`

Copy constructor.

Parameters

<i>other</i>	
--------------	--

Definition at line 39 of file model.cpp.

```
39 : Component(CType::CModel) { *this = other; }
```

4.9.2.3 Model() [3/3] `Model::Model (`
`File_Reader & reader,`
`GLenum mode_ = GL_TRIANGLES)`

Creates a [Model](#) object using the data from a file.

Parameters

<i>reader</i>	File with Model data
<i>mode</i> ↔	Draw mode for opengl
—	

Definition at line 47 of file model.cpp.

```
47         texture(nullptr) {
48             Read(reader);
49         }
: Component(CType::CModel), mode(mode_), data(nullptr),
```

References [Read\(\)](#).

4.9.3 Member Function Documentation

4.9.3.1 Clone() [Model](#) * [Model](#)::Clone () const

Clones this [Model](#) object.

Returns

[Model](#)* Cloned [Model](#)

Definition at line 56 of file model.cpp.

```
56 { return new Model(*this); }
```

References [Model\(\)](#).

4.9.3.2 Draw() void [Model](#)::Draw (glm::mat4 *projection*, glm::mat4 *view*)

Draw the model.

Parameters

<i>projection</i>	Projection matrix of the scene
<i>view</i>	View matrix of the scene

Definition at line 75 of file model.cpp.

```
75                                     {
76     Transform* transform = GetParent()->GetComponent<Transform>();
77     if (!data) return;
78
79     data->Draw(this, transform, projection, view);
80 }
```

References data, Model_Data::Draw(), Object::GetComponent(), and Component::GetParent().

Referenced by Graphics::Render().

4.9.3.3 GetCType() CType Model::GetCType () [static]

Gets the CType of Model (used in Object::GetComponent<>())

Returns

CType

Definition at line 158 of file model.cpp.

```
158     {
159     return CType::CModel;
160 }
```

4.9.3.4 GetModelName() std::string Model::GetModelName () const

Returns the filename of the current model.

Returns

std::string

Definition at line 131 of file model.cpp.

```
131     {
132     if (!data) return "no model";
133     return data->GetModelName();
134 }
```

References data, and Model_Data::GetModelName().

Referenced by Editor::Display_Model().

4.9.3.5 GetTexture() `Texture * Model::GetTexture () const`

Returns pointer to texture object.

Returns

`Texture*`

Definition at line 151 of file model.cpp.

```
151 { return texture; }
```

References texture.

Referenced by `Model_Data::Draw()`.

4.9.3.6 GetTextureName() `std::string Model::GetTextureName () const`

Returns the filename of the current texture.

Returns

`std::string`

Definition at line 141 of file model.cpp.

```
141 {
142     if (!texture) return "no texture";
143     return texture->GetTextureName();
144 }
```

References `Texture::GetTextureName()`, and texture.

Referenced by `Editor::Display_Model()`.

4.9.3.7 Load() `void Model::Load (File_Reader & reader)`

Load in the model data from a file (use model manager to not have multiple versions of the same model)

Parameters

<code>reader</code>	File_reader object that contains Model info
---------------------	---

Definition at line 64 of file model.cpp.

```
64 {
65     data = Model_Data_Manager::Get(reader);
66     texture = Texture_Manager::Get(reader);
67 }
```


References data, Texture_Manager::Get(), Model_Data_Manager::Get(), and texture.

Referenced by Read().

4.9.3.8 Read() `void Model::Read (`
`File_Reader & reader)`

Reads name of model file and passes it to the Load function.

Parameters

<i>reader</i>	File that contains the name of the model's file
---------------	---

Definition at line 87 of file model.cpp.

```
87 { Load(reader); }
```

References Load().

Referenced by Model(), and Object::ReRead().

4.9.3.9 SwitchModel() `void Model::SwitchModel (`
`std::string modelName)`

Switches the current model to that of the filename provided.

Parameters

<i>modelName</i>	
------------------	--

Definition at line 107 of file model.cpp.

```
107                                     {
108     Model_Data* proxy = Model_Data_Manager::Get (modelName);
109     if (!proxy) return;
110
111     data = proxy;
112 }
```

References data, and Model_Data_Manager::Get().

Referenced by Editor::Display_Model().

4.9.3.10 SwitchTexture() `void Model::SwitchTexture (`
`std::string textureName)`

Switches the current texture to that of the filename provided.

Parameters

<i>textureName</i>	
--------------------	--

Definition at line 119 of file model.cpp.

```

119     {
120         Texture* proxy = Texture_Manager::Get(textureName);
121         if (!proxy) return;
122     }
123     texture = proxy;
124 }
```

References Texture_Manager::Get(), and texture.

Referenced by Editor::Display_Model().

4.9.3.11 Write() void Model::Write (
File_Writer & writer)

Gives name of model and texture to writer.

Parameters

<i>writer</i>	
---------------	--

Definition at line 94 of file model.cpp.

```

94     {
95         std::string modelName = data->GetModelName();
96         std::string textureName = texture->GetTextureName();
97     }
98     writer.Write_String("modelToLoad", modelName.c_str());
99     writer.Write_String("textureToLoad", textureName.c_str());
100 }
```

References data, Model_Data::GetModelName(), Texture::GetTextureName(), texture, and File_Writer::Write_String().

Referenced by Object::Write().

The documentation for this class was generated from the following files:

- [model.hpp](#)
- [model.cpp](#)

4.10 Model_Data Class Reference

```
#include <model_data.hpp>
```

Public Member Functions

- [Model_Data](#) ()
Default constructor.
- [Model_Data](#) (const [Model_Data](#) &other)
Copy constructor.
- [~Model_Data](#) ()
Deletes all buffers of the model.
- bool [Load](#) ([File_Reader](#) &reader)
Loads data of a model from given file.
- bool [Load](#) (std::string modelName_)
Loads in model using given filename.
- bool [Read](#) (std::string modelName_)
Reads model data from file.
- void [Draw](#) ([Model](#) *parent, [Transform](#) *transform, glm::mat4 projection, glm::mat4 view)
Draws the models.
- std::string [GetModelName](#) () const
Returns the filename that the models data was gotten from.

Private Attributes

- std::vector< float > [vertices](#)
Contains vertices of model.
- std::vector< float > [normals](#)
Contains normals of model.
- std::vector< float > [uvs](#)
Contains uv data of model.
- std::string [modelName](#)
Name of the file for the model.
- GLuint [vertexbuffer](#)
Vertex buffer of model.
- GLuint [normalbuffer](#)
Normal buffer of model.
- GLuint [uvbuffer](#)
UV buffer of model.

4.10.1 Detailed Description

[Model_Data](#) class

Definition at line 33 of file [model_data.hpp](#).

4.10.2 Constructor & Destructor Documentation

4.10.2.1 Model_Data() [1/2] `Model_Data::Model_Data ()`

Default constructor.

Definition at line 33 of file `model_data.cpp`.

```
33 {}
```

4.10.2.2 Model_Data() [2/2] `Model_Data::Model_Data (const Model_Data & other)`

Copy constructor.

Parameters

<i>other</i>	
--------------	--

Definition at line 40 of file `model_data.cpp`.

```
40                                     {
41     for (float vert : other.vertices) {
42         vertices.emplace_back(vert);
43     }
44     for (float norm : other.normals) {
45         normals.emplace_back(norm);
46     }
47     for (float uv : other.uvs) {
48         uvs.emplace_back(uv);
49     }
50
51     vertexbuffer = other.vertexbuffer;
52     normalbuffer = other.normalbuffer;
53     uvbuffer = other.uvbuffer;
54 }
```

References `normalbuffer`, `normals`, `uvbuffer`, `uvs`, `vertexbuffer`, and `vertices`.

4.10.2.3 ~Model_Data() `Model_Data::~~Model_Data ()`

Deletes all buffers of the model.

Definition at line 60 of file `model_data.cpp`.

```
60     {
61         glDeleteBuffers(1, &vertexbuffer);
62         glDeleteBuffers(1, &uvbuffer);
63         glDeleteBuffers(1, &normalbuffer);
64     }
```

References `normalbuffer`, `uvbuffer`, and `vertexbuffer`.

4.10.3 Member Function Documentation

4.10.3.1 Draw() void Model_Data::Draw (

```

    Model * parent,
    Transform * transform,
    glm::mat4 projection,
    glm::mat4 view )

```

Draws the models.

Parameters

<i>parent</i>	Model component
<i>transform</i>	Transform component
<i>projection</i>	Projection matrix of the scene
<i>view</i>	View matrix of the scene

Definition at line 224 of file model_data.cpp.

```

224
225     // Creating the MVP (Model * View * Projection) matrix
226     glm::mat4 model = glm::mat4(1.f);
227     model = glm::translate(model, transform->GetPosition());
228     model = glm::rotate(model, (transform->GetRotation().x / 180.f) * glm::pi<float>(), glm::vec3(1, 0, 0));
229     model = glm::rotate(model, (transform->GetRotation().y / 180.f) * glm::pi<float>(), glm::vec3(0, 1, 0));
230     model = glm::rotate(model, (transform->GetRotation().z / 180.f) * glm::pi<float>(), glm::vec3(0, 0, 1));
231     model = glm::scale(model, transform->GetScale());
232
233     // Sending data to the shaders
234     glm::mat4 MVP = projection * view * model;
235     glUniformMatrix4fv(Shader::GetMatrixId(), 1, GL_FALSE, &MVP[0][0]);
236     glUniformMatrix4fv(Shader::GetModelMatrixId(), 1, GL_FALSE, &model[0][0]);
237     glUniformMatrix4fv(Shader::GetViewMatrixId(), 1, GL_FALSE, &view[0][0]);
238
239     // Sending light data to the shaders
240     glm::vec3 lightPos = Engine::GetLightPos();
241     glUniform3f(Shader::GetLightId(), lightPos.x, lightPos.y, lightPos.z);
242     glUniform1f(Shader::GetLightPowerId(), Engine::GetLightPower());
243
244     // Setup texture for drawing if it exists
245     if (parent->GetTexture())
246         parent->GetTexture()->Display();
247
248     // Setup the model vertices
249     glEnableVertexAttribArray(0);
250     glBindBuffer(GL_ARRAY_BUFFER, vertexbuffer);
251     glVertexAttribPointer(
252         0,
253         3,
254         GL_FLOAT,
255         GL_FALSE,
256         0,
257         (void*)0
258     );
259
260     // Setup the model uv
261     glEnableVertexAttribArray(1);
262     glBindBuffer(GL_ARRAY_BUFFER, uvbuffer);
263     glVertexAttribPointer(
264         1,
265         2,
266         GL_FLOAT,
267         GL_FALSE,
268         0,
269         (void*)0
270     );
271
272     // Setup the model normals
273     glEnableVertexAttribArray(2);
274     glBindBuffer(GL_ARRAY_BUFFER, normalbuffer);
275     glVertexAttribPointer(
276         2,
277         3,
278         GL_FLOAT,

```

```

279         GL_FALSE,
280         0,
281         (void*)0
282     );
283
284     // Draw the object
285     glDrawArrays(GL_TRIANGLES, 0, vertices.size());
286
287     // Disable data sent to shaders
288     glDisableVertexAttribArray(0);
289     glDisableVertexAttribArray(1);
290     glDisableVertexAttribArray(2);
291
292 }

```

References Texture::Display(), Shader::GetLightId(), Engine::GetLightPos(), Engine::GetLightPower(), Shader::GetLightPowerId(), Shader::GetMatrixId(), Shader::GetModelMatrixId(), Transform::GetPosition(), Transform::GetRotation(), Transform::GetScale(), Model::GetTexture(), Shader::GetViewMatrixId(), normalbuffer, uvbuffer, vertexbuffer, and vertices.

Referenced by Model::Draw().

4.10.3.2 GetModelName() `std::string Model_Data::GetModelName () const`

Returns the filename that the models data was gotten from.

Returns

string Name of the file that contains model data

Definition at line 299 of file model_data.cpp.

```
299 { return modelName; }
```

References modelName.

Referenced by Model_Data_Manager::Get(), Model::GetModelName(), and Model::Write().

4.10.3.3 Load() [1/2] `bool Model_Data::Load (File_Reader & reader)`

Loads data of a model from given file.

Parameters

<i>reader</i>	<code>File_Reader</code> object containing the model data
---------------	---

Returns

true
false

Definition at line 73 of file model_data.cpp.

```
73 {  
74     std::string modelName_ = reader.Read_String("modelToLoad");  
75  
76     return Read(modelName_);  
77 }
```

References Read(), and File_Reader::Read_String().

Referenced by Model_Data_Manager::Get().

4.10.3.4 Load() [2/2] `bool Model_Data::Load (`
`std::string modelName_)`

Loads in model using given filename.

Parameters

<i>modelName_</i>	Model's filename
-------------------	------------------

Returns

true
false

Definition at line 86 of file model_data.cpp.

```
86 { return Read(modelName_); }
```

References Read().

4.10.3.5 Read() `bool Model_Data::Read (`
`std::string modelName_)`

Reads model data from file.

Parameters

<i>modelName_</i>	Model's filename
-------------------	------------------

Returns

true
false

Definition at line 95 of file model_data.cpp.

```

95                                     {
96     // Opening the file
97     std::string fileToOpen = std::string(getenv("USERPROFILE")) + "/Documents/pEngine/models/" + modelName_;
98     // Setting the name of the file (used in model_data_manager)
99     modelName = fileToOpen;
100
101     FILE* file = fopen(fileToOpen.c_str(), "r");
102     if (!file) {
103         file = fopen(modelName_.c_str(), "r");
104         if (!file) {
105             return false;
106         }
107     }
108     else {
109         modelName = modelName_;
110     }
111 }
112
113 // Creating variables for reading
114 std::vector<unsigned> vertex_indices, uv_indices, normal_indices;
115 std::vector<glm::vec3> temp_vertices;
116 std::vector<glm::vec2> temp_uvs;
117 std::vector<glm::vec3> temp_normals;
118
119 // Until the whole file is read
120 while (true) {
121     char line_header[256];
122
123     // Getting next line of the file
124     int res = fscanf(file, "%s", line_header);
125     if (res == EOF) break;
126
127     // Checking for which data needs to be read in
128     if (strcmp(line_header, "v") == 0) {
129         glm::vec3 vertex;
130         fscanf(file, "%f %f %f\n", &vertex.x, &vertex.y, &vertex.z);
131         temp_vertices.emplace_back(vertex);
132         continue;
133     }
134
135     if (strcmp(line_header, "vt") == 0) {
136         glm::vec2 uv;
137         fscanf(file, "%f %f\n", &uv.x, &uv.y);
138         temp_uvs.emplace_back(uv);
139         continue;
140     }
141
142     if (strcmp(line_header, "vn") == 0) {
143         glm::vec3 normal;
144         fscanf(file, "%f %f %f\n", &normal.x, &normal.y, &normal.z);
145         temp_normals.emplace_back(normal);
146         continue;
147     }
148
149     if (strcmp(line_header, "f") == 0) {
150         // Connecting face to previous read vertices, uvs, and normals
151         unsigned vertex_index[3], uv_index[3], normal_index[3];
152         int matches = fscanf(file, "%d/%d/%d %d/%d/%d %d/%d/%d\n", &vertex_index[0], &uv_index[0],
153             &normal_index[0],
154             &vertex_index[1], &uv_index[1], &normal_index[1], &vertex_index[2], &uv_index[2],
155             &normal_index[2]);
156
157         // Expects models split into triangles
158         if (matches != 9) {
159             Trace::Message("File is incompatible with this parser. Export using different settings.");
160             return false;
161         }
162
163         // Setting vertices for current face
164         vertices.emplace_back((temp_vertices[vertex_index[0] - 1]).x);
165         vertices.emplace_back((temp_vertices[vertex_index[0] - 1]).y);
166         vertices.emplace_back((temp_vertices[vertex_index[0] - 1]).z);
167
168         vertices.emplace_back((temp_vertices[vertex_index[1] - 1]).x);
169         vertices.emplace_back((temp_vertices[vertex_index[1] - 1]).y);
170         vertices.emplace_back((temp_vertices[vertex_index[1] - 1]).z);
171
172         vertices.emplace_back((temp_vertices[vertex_index[2] - 1]).x);
173         vertices.emplace_back((temp_vertices[vertex_index[2] - 1]).y);
174         vertices.emplace_back((temp_vertices[vertex_index[2] - 1]).z);
175     }
176 }

```



```

173         // Setting uvs for current face
174         uvs.emplace_back((temp_uvs[uv_index[0] - 1]).x);
175         uvs.emplace_back((temp_uvs[uv_index[0] - 1]).y);
176
177         uvs.emplace_back((temp_uvs[uv_index[1] - 1]).x);
178         uvs.emplace_back((temp_uvs[uv_index[1] - 1]).y);
179
180         uvs.emplace_back((temp_uvs[uv_index[2] - 1]).x);
181         uvs.emplace_back((temp_uvs[uv_index[2] - 1]).y);
182
183         // Setting normals for current face
184         normals.emplace_back((temp_normals[normal_index[0] - 1]).x);
185         normals.emplace_back((temp_normals[normal_index[0] - 1]).y);
186         normals.emplace_back((temp_normals[normal_index[0] - 1]).z);
187
188         normals.emplace_back((temp_normals[normal_index[1] - 1]).x);
189         normals.emplace_back((temp_normals[normal_index[1] - 1]).y);
190         normals.emplace_back((temp_normals[normal_index[1] - 1]).z);
191
192         normals.emplace_back((temp_normals[normal_index[2] - 1]).x);
193         normals.emplace_back((temp_normals[normal_index[2] - 1]).y);
194         normals.emplace_back((temp_normals[normal_index[2] - 1]).z);
195     }
196 }
197
198 // Bind vertex data to buffers
199 glGenBuffers(1, &vertexbuffer);
200 glBindBuffer(GL_ARRAY_BUFFER, vertexbuffer);
201 glBufferData(GL_ARRAY_BUFFER, vertices.size() * sizeof(float), &vertices[0], GL_STATIC_DRAW);
202
203 // Bind uv data to buffers
204 glGenBuffers(1, &uvbuffer);
205 glBindBuffer(GL_ARRAY_BUFFER, uvbuffer);
206 glBufferData(GL_ARRAY_BUFFER, uvs.size() * sizeof(float), &uvs[0], GL_STATIC_DRAW);
207
208 // Bind normals data to buffers
209 glGenBuffers(1, &normalbuffer);
210 glBindBuffer(GL_ARRAY_BUFFER, normalbuffer);
211 glBufferData(GL_ARRAY_BUFFER, normals.size() * sizeof(float), &normals[0], GL_STATIC_DRAW);
212
213 return true;
214 }

```

References `Trace::Message()`, `modelName`, `normalbuffer`, `normals`, `uvbuffer`, `uvs`, `vertexbuffer`, and `vertices`.

Referenced by `Load()`.

The documentation for this class was generated from the following files:

- [model_data.hpp](#)
- [model_data.cpp](#)

4.11 Model_Data_Manager Class Reference

```
#include <model_data_manager.hpp>
```

Static Public Member Functions

- static bool [Initialize](#) ()
Initializes the model_data_manager.
- static [Model_Data](#) * [Get](#) ([File_Reader](#) &reader)
Checks if model data has already been read in. If yes then it returns a pointer to that data. If no it reads it in and adds it to the model list.
- static [Model_Data](#) * [Get](#) (std::string modelName)
Checks if model data has already been read in. If yes then it returns a pointer to that data. If no it reads it in and adds it to the model list.
- static void [Shutdown](#) ()
Deletes all of the [Model_Data](#) objects in the models list then deletes model_data_manager.

Private Attributes

- `std::vector< Model_Data * > models`
List of the different [Model_Data](#) objects.

4.11.1 Detailed Description

[Model_Data_Manager](#) class

Definition at line 25 of file `model_data_manager.hpp`.

4.11.2 Member Function Documentation

4.11.2.1 `Get()` [1/2] [Model_Data](#) * `Model_Data_Manager::Get` ([File_Reader](#) & `reader`) [static]

Checks if model data has already been read in. If yes then it returns a pointer to that data. If no it reads it in and adds it to the model list.

Parameters

<code>reader</code>	File_Reader object containing model data
---------------------	--

Returns

[Model_Data](#)* [Model](#) data either read or gotten from list

Definition at line 44 of file `model_data_manager.cpp`.

```

44         {
45             std::string filename = reader.Read_String("modelToLoad");
46             // Checks name of file against other model data objects
47             for (Model\_Data* model_data : model_data_manager->models) {
48                 if (model_data->GetModelName().compare(filename) == 0) {
49                     return model_data;
50                 }
51             }
52
53             // Creates new Model\_Data object, then adds it to list
54             Model\_Data* data = new Model\_Data;
55             data->Load(reader);
56             model_data_manager->models.emplace_back(data);
57
58             return data;
59     }
```

References [Model_Data::GetModelName\(\)](#), [Model_Data::Load\(\)](#), [model_data_manager](#), [models](#), and [File_Reader::Read_String\(\)](#).

Referenced by [Model::Load\(\)](#), and [Model::SwitchModel\(\)](#).

4.11.2.2 Get() [2/2] `Model_Data * Model_Data_Manager::Get (`
`std::string modelName) [static]`

Checks if model data has already been read in. If yes then it returns a pointer to that data. If no it reads it in and adds it to the model list.

Parameters

<i>modelName</i>	Filename of the model to get
------------------	------------------------------

Returns

`Model_Data*` `Model` data either read or gotten from list

Definition at line 69 of file `model_data_manager.cpp`.

```

69         {
70         // Checks name of file against other model data objects
71         for (Model_Data* model_data : model_data_manager->models) {
72             if (model_data->GetModelName().compare(modelName) == 0) {
73                 return model_data;
74             }
75         }
76
77         // Creates new Model_Data object, then adds it to list
78         Model_Data* data = new Model_Data;
79         if (!data->Load(modelName)) {
80             delete data;
81             return nullptr;
82         }
83         model_data_manager->models.emplace_back(data);
84
85         return data;
86     }

```

References `Model_Data::GetModelName()`, `Model_Data::Load()`, `model_data_manager`, and `models`.

4.11.2.3 Initialize() `bool Model_Data_Manager::Initialize () [static]`

Initializes the `model_data_manager`.

Returns

true
false

Definition at line 24 of file `model_data_manager.cpp`.

```

24         {
25         // Initializing model_data_manager
26         model_data_manager = new Model_Data_Manager;
27         if (!model_data_manager) {
28             Trace::Message("Model Data Manager was not initialized.\n");
29             return false;
30         }
31
32         model_data_manager->models.reserve(10);
33         return true;
34     }

```

References `Trace::Message()`, `model_data_manager`, and `models`.

Referenced by `Engine::Initialize()`.

4.11.2.4 Shutdown() `void Model_Data_Manager::Shutdown () [static]`

Deletes all of the [Model_Data](#) objects in the models list then deletes model_data_manager.

Returns

void

Definition at line 94 of file model_data_manager.cpp.

```

94     {
95         if (!model_data_manager) return;
96
97         // Deleting all of the Model_Data objects
98         for (Model_Data* model_data : model_data_manager->models) {
99             if (!model_data) continue;
100
101             delete model_data;
102             model_data = nullptr;
103         }
104
105         delete model_data_manager;
106         model_data_manager = nullptr;
107     }

```

References model_data_manager, and models.

Referenced by Engine::Shutdown().

The documentation for this class was generated from the following files:

- [model_data_manager.hpp](#)
- [model_data_manager.cpp](#)

4.12 Object Class Reference

```
#include <object.hpp>
```

Public Member Functions

- [Object](#) ()
Default constructor.
- [Object](#) (const [Object](#) &other)
Copy constructor.
- [Object](#) * [Clone](#) () const
Clones this object.
- void [Update](#) ()
Updates object (only physics for now)
- void [AddComponent](#) ([Component](#) *component)
Adds component to object. Only one of each type of component.
- template<typename T >
T * [GetComponent](#) ()
Get a component of the object.

- `template<typename T >`
`void RemoveComponent ()`
Removes component from object.
- `void SetId (int id_)`
Sets the id of object.
- `int GetId () const`
Returns the id of object.
- `void SetName (std::string name_)`
Sets name of object.
- `std::string GetName () const`
Returns name of object.
- `std::string & GetNameRef ()`
Returns reference to the name.
- `void SetTemplateName (std::string templateName_)`
Sets the name of the template file.
- `std::string GetTemplateName () const`
Returns the name of the template file.
- `bool Read (std::string objectFilename)`
Reads object from file. This includes the components of an object.
- `bool ReRead (std::string objectFilename)`
Reading data into object that already exists.
- `void Write (std::string filePath)`
Writes the data of the object to a template file.
- `std::unordered_map< CType, Component * > GetComponentList ()`
Returns the list of components.
- `void Clear ()`
Clears the components from the object.

Private Member Functions

- `template<typename T >`
`T * GetComponentConst () const`
Get a component of the object (const)

Private Attributes

- `std::unordered_map< CType, Component * > components`
List of components.
- `std::string name`
Name of the object.
- `std::string templateName`
Name of the template file used.
- `int id`
Location of object in object_manager.

4.12.1 Detailed Description

[Object](#) class

Definition at line 25 of file `object.hpp`.

4.12.2 Constructor & Destructor Documentation

4.12.2.1 `Object()` [1/2] `Object::Object ()`

Default constructor.

Definition at line 28 of file `object.cpp`.

```
28 : id(-1) {}
```

Referenced by `Clone()`.

4.12.2.2 `Object()` [2/2] `Object::Object (` `const Object & other)`

Copy constructor.

Parameters

<i>other</i>	Object to be copied
--------------	-------------------------------------

Definition at line 35 of file `object.cpp`.

```
35 {
36     SetName(other.GetName());
37     SetTemplateName(other.GetTemplateName());
38
39     // Copying Behavior component
40     Behavior* behavior = other.GetComponentConst<Behavior>();
41     if (behavior) {
42         Behavior* newBehavior = new Behavior(*behavior);
43         AddComponent(newBehavior);
44     }
45
46     // Copying Model component
47     Model* model = other.GetComponentConst<Model>();
48     if (model) {
49         Model* newModel = new Model(*model);
50         AddComponent(newModel);
51     }
52
53     // Copying Physics component
54     Physics* physics = other.GetComponentConst<Physics>();
55     if (physics) {
56         Physics* newPhysics = new Physics(*physics);
57         AddComponent(newPhysics);
58     }
59 }
```

```

60     // Copying transform component
61     Transform* transform = other.GetComponentConst<Transform>();
62     if (transform) {
63         Transform* newTransform = new Transform(*transform);
64         AddComponent(newTransform);
65     }
66 }

```

References AddComponent(), GetComponentConst(), GetName(), GetTemplateName(), SetName(), and SetTemplateName().

4.12.3 Member Function Documentation

4.12.3.1 AddComponent() void Object::AddComponent (Component * component)

Adds component to object. Only one of each type of component.

Parameters

<i>component</i>	Component to be added
------------------	-----------------------

Definition at line 95 of file object.cpp.

```

95     {
96         component->SetParent(this);
97         components.emplace(component->GetCType(), component);
98     }

```

References components, Component::GetCType(), and Component::SetParent().

Referenced by Editor::Display_Scene(), Object(), Read(), and ReRead().

4.12.3.2 Clear() void Object::Clear ()

Clears the components from the object.

Definition at line 275 of file object.cpp.

```

275     {
276         Behavior* behavior = GetComponent<Behavior>();
277         Model* model = GetComponent<Model>();
278         Physics* physics = GetComponent<Physics>();
279
280         if (behavior) {
281             delete behavior;
282             behavior = nullptr;
283         }
284         if (model) {
285             delete model;
286             model = nullptr;
287         }
288         if (physics) {
289             delete physics;
290             physics = nullptr;
291         }
292     }

```

4.12.3.3 Clone() `Object * Object::Clone () const`

Clones this object.

Returns

Object*

Definition at line 73 of file object.cpp.

```
73     {
74         return new Object(*this);
75     }
```

References Object().

4.12.3.4 GetComponent() `template<typename T >`

`T* Object::GetComponent () [inline]`

Get a component of the object.

Template Parameters

<i>T</i>	Component class to return
----------	---------------------------

Parameters

<i>type</i>	Type of component
-------------	-------------------

Returns

T* Pointer to the component

Definition at line 44 of file object.hpp.

```
44     {
45         // Searching for component using the type (enum as int)
46         auto found = components.find(T::GetCType());
47         if (found == components.end()) {
48             return nullptr;
49         }
50         // Cast found component into correct type
51         return (T*) found->second;
52     }
```

References components.

Referenced by Model::Draw(), Physics::Update(), and Physics::UpdateGravity().

4.12.3.5 GetComponentConst() `template<typename T >`

`T* Object::GetComponentConst () const [inline], [private]`

Get a component of the object (const)

Template Parameters

<i>T</i>	<code>Component</code> class to return
----------	--

Parameters

<i>type</i>	Type of component
-------------	-------------------

Returns

`T*` Pointer to the component

Definition at line 96 of file `object.hpp`.

```
96         {
97             // Searching for component using the type (enum as int)
98             auto found = components.find(T::GetCType());
99             if (found == components.end()) {
100                 return nullptr;
101             }
102             // Cast found component into correct type
103             return (T*)found->second;
104         }
```

References `components`.

Referenced by `Object()`.

4.12.3.6 GetComponentList() `std::unordered_map< CType, Component * > Object::GetComponentList ()`

Returns the list of components.

Returns

`std::unordered_map<CType, Component*>`

Definition at line 267 of file `object.cpp`.

```
267         {
268             return components;
269         }
```

References `components`.

4.12.3.7 GetId() `int Object::GetId () const`

Returns the id of object.

Returns

unsigned Position in [Object_Manager](#)

Definition at line 112 of file object.cpp.

```
112 { return id; }
```

References id.

Referenced by [Object_Manager::CheckName\(\)](#), [Behavior::ClassSetup\(\)](#), [Editor::Display_Components\(\)](#), and [File_Writer::Write_Object_Data\(\)](#).

4.12.3.8 GetName() `std::string Object::GetName () const`

Returns name of object.

Returns

string Name of object

Definition at line 128 of file object.cpp.

```
128 { return name; }
```

References name.

Referenced by [Object_Manager::CheckName\(\)](#), [Object_Manager::FindObject\(\)](#), [Object\(\)](#), and [File_Writer::Write_Object_Data\(\)](#).

4.12.3.9 GetNameRef() `std::string & Object::GetNameRef ()`

Returns reference to the name.

Returns

std::string&

Definition at line 135 of file object.cpp.

```
135 { return name; }
```

References name.

Referenced by [Behavior::ClassSetup\(\)](#).

4.12.3.10 GetTemplateName() `std::string Object::GetTemplateName () const`

Returns the name of the template file.

Returns

`std::string`

Definition at line 149 of file `object.cpp`.

```
149 { return templateName; }
```

References `templateName`.

Referenced by `Object()`, and `File_Writer::Write_Object_Data()`.

4.12.3.11 Read() `bool Object::Read (std::string objectFilename)`

Reads object from file. This includes the components of an object.

Parameters

<code>objectFilename</code>

Returns

`true`

`false`

Definition at line 158 of file `object.cpp`.

```
158                                     {
159     // Getting data from file
160     File_Reader object_reader;
161     if (!object_reader.Read_File(objectFilename)) return false;
162
163     // Reading Behavior component form file
164     Behavior* object_behavior = new Behavior(object_reader);
165     AddComponent(object_behavior);
166
167     // Reading Model component from file
168     Model* object_model = new Model(object_reader);
169     AddComponent(object_model);
170
171     // Reading Physics component from file
172     Physics* object_physics = new Physics(object_reader);
173     AddComponent(object_physics);
174
175     // Reading Transform component from file
176     Transform* object_transform = new Transform(object_reader);
177     AddComponent(object_transform);
178
179     return true;
180 }
```

References `AddComponent()`, and `File_Reader::Read_File()`.

Referenced by `Object_Manager::ReadList()`.

4.12.3.12 RemoveComponent() `template<typename T >`

```
void Object::RemoveComponent ( ) [inline]
```

Removes component from object.

Template Parameters

<i>T</i>	
----------	--

Definition at line 60 of file object.hpp.

```

60     {
61         // Searching for component using the type (enum as int)
62         auto found = components.find(T::GetType());
63         if (found == components.end()) return;
64         // Delete component
65         delete found->second;
66         found->second = nullptr;
67         // Remove pointer from map
68         components.erase(found->first);
69     }
```

References components.

Referenced by Editor::Display_Model(), Editor::Display_Physics(), and Editor::Display_Scripts().

4.12.3.13 ReRead() `bool Object::ReRead (`
`std::string objectFilename)`

Reading data into object that already exists.

Parameters

<i>objectFilename</i>	Name of template file
-----------------------	-----------------------

Returns

true

false

Definition at line 189 of file object.cpp.

```

189     {
190         // Getting data from file
191         File_Reader object_reader;
192         if (!object_reader.Read_File(objectFilename)) return false;
193
194         if (name.compare("") == 0)
195             SetName(object_reader.Read_String("name"));
196
197         templateName = objectFilename;
198
199         // Reading Model component from file
200         Model* object_model = GetComponent<Model>();
201         if (!object_model) {
202             object_model = new Model;
203             AddComponent(object_model);
204         }
```

```

204     }
205     object_model->Read(object_reader);
206
207     // Reading Physics component from file
208     Physics* object_physics = GetComponent<Physics>();
209     if (!object_physics) {
210         object_physics = new Physics;
211         AddComponent(object_physics);
212     }
213     object_physics->Read(object_reader);
214
215     // Reading Transform component from file
216     Transform* object_transform = GetComponent<Transform>();
217     if (!object_transform) {
218         object_transform = new Transform;
219         AddComponent(object_transform);
220     }
221     object_transform->Read(object_reader);
222
223     // Reading Behavior component form file
224     Behavior* object_behavior = GetComponent<Behavior>();
225     if (object_behavior) object_behavior->Clear();
226     if (!object_behavior) {
227         object_behavior = new Behavior;
228         AddComponent(object_behavior);
229     }
230     object_behavior->Read(object_reader);
231     object_behavior->SetupClassesForLua();
232
233     return true;
234 }

```

References AddComponent(), Behavior::Clear(), name, Behavior::Read(), Model::Read(), Transform::Read(), Physics::Read(), File_Reader::Read_File(), File_Reader::Read_String(), SetName(), Behavior::SetupClassesForLua(), and templateName.

4.12.3.14 SetId() void Object::SetId (
 int id_)

Sets the id of object.

Parameters

$id \leftrightarrow$	Position in Object_Manager
$_ \leftrightarrow$	

Definition at line 105 of file object.cpp.

```
105 { id = id_; }
```

Referenced by Object_Manager::RemoveObject().

4.12.3.15 SetName() void Object::SetName (
 std::string name_)

Sets name of object.

Parameters

<i>name</i> ↔	Name of object
—	

Definition at line 119 of file object.cpp.

```
119 {
120     name = Object_Manager::CheckName(name_, id);
121 }
```

References Object_Manager::CheckName(), and name.

Referenced by Behavior::ClassSetup(), Editor::Display_Scene(), Object(), Object_Manager::ReadList(), and ReRead().

4.12.3.16 SetTemplateName() void Object::SetTemplateName (
std::string *templateName_*)

Sets the name of the template file.

Parameters

<i>template</i> ↔ <i>Name_</i>	Name of the template file
-----------------------------------	---------------------------

Definition at line 142 of file object.cpp.

```
142 { templateName = templateName_; }
```

References templateName.

Referenced by Object().

4.12.3.17 Update() void Object::Update ()

Updates object (only physics for now)

Definition at line 81 of file object.cpp.

```
81 {
82     Behavior* behavior = GetComponent<Behavior>();
83     if (behavior)
84         behavior->Update();
85     Physics* physics = GetComponent<Physics>();
86     if (physics)
87         physics->Update();
88 }
```

References Behavior::Update(), and Physics::Update().

Referenced by Object_Manager::Update().

4.12.3.18 Write() void Object::Write (
std::string *filePath*)

Writes the data of the object to a template file.

Parameters

<i>filePath</i>	Filepath for the object being written
-----------------	---------------------------------------

Definition at line 241 of file object.cpp.

```

241     {
242         File_Writer object_writer;
243         object_writer.Write_String("name", name);
244         templateName = filePath + "/" + name + ".json";
245         Trace::Message(templateName + "\n");
246
247         Model* object_model = GetComponent<Model>();
248         if (object_model) object_model->Write(object_writer);
249
250         Transform* object_transform = GetComponent<Transform>();
251         if (object_transform) object_transform->Write(object_writer);
252
253         Physics* object_physics = GetComponent<Physics>();
254         if (object_physics) object_physics->Write(object_writer);
255
256         Behavior* object_behavior = GetComponent<Behavior>();
257         if (object_behavior) object_behavior->Write(object_writer);
258
259         object_writer.Write_File(templateName);
260     }

```

References `Trace::Message()`, `name`, `templateName`, `Behavior::Write()`, `Model::Write()`, `Transform::Write()`, `Physics::Write()`, `File_Writer::Write_File()`, and `File_Writer::Write_String()`.

The documentation for this class was generated from the following files:

- [object.hpp](#)
- [object.cpp](#)

4.13 Object_Manager Class Reference

```
#include <object_manager.hpp>
```

Public Member Functions

- void [ReadList](#) ([File_Reader](#) &preset)
Reads in objects from a preset list that is given.

Static Public Member Functions

- static bool [Initialize](#) ([File_Reader](#) &preset)
Initializes the object_manager object. Reads in objects for the given preset.
- static bool [Initialize](#) ()
Initialize object manager with default values.
- static void [AddObject](#) ([Object](#) *object)
Adds object to object_manager.
- static [Object](#) * [FindObject](#) (int id)
Finds a object using its id (location in object list) giving instant access.

- static [Object](#) * [FindObject](#) (std::string objectName)
Finds object with the matching name.
- static unsigned [GetSize](#) ()
Gets the size of the object_manager object list.
- static void [Update](#) ()
Calls the update function for each object in the object list.
- static void [Shutdown](#) ()
Deletes all objects in the manager and then the object manager.
- static std::string [CheckName](#) (std::string objectName, int id)
Checks if the name of the given object is already being used. If it is being used it applies a number to the back.
- static void [RemoveObject](#) (int id)
Removes an object from the object_manager.
- static void [Write](#) ([File_Writer](#) &writer)
Gives all of the object data to writer for output to file.

Private Attributes

- std::vector< [Object](#) * > [objects](#)
Current objects being tracked by the engine.

4.13.1 Detailed Description

[Object_Manager](#) class

Definition at line 25 of file object_manager.hpp.

4.13.2 Member Function Documentation

4.13.2.1 AddObject() void [Object_Manager::AddObject](#) (
 [Object](#) * *object*) [static]

Adds object to object_manager.

Parameters

<i>object</i>	Object to be added
---------------	------------------------------------

Returns

void

Definition at line 72 of file object_manager.cpp.


```

72                                     {
73     // Tells object its location in object_manager object list
74     object->SetId(object_manager->objects.size());
75     object_manager->objects.emplace_back(object);
76 }

```

References `object_manager`, and `objects`.

Referenced by `Editor::Display_Scene()`, and `ReadList()`.

4.13.2.2 CheckName() `std::string Object_Manager::CheckName (`
`std::string objectName,`
`int id) [static]`

Checks if the name of the given object is already being used. If it is being used it applies a number to the back.

Parameters

<i>objectName</i>	
<i>id</i>	

Returns

`std::string`

Definition at line 192 of file `object_manager.cpp`.

```

192                                     {
193     // Checking if the name matches any other objects
194     int objWithName = 0;
195     for (Object* objToCheck : object_manager->objects) {
196         if (id != -1 && objToCheck->GetId() == id) continue;
197         if (objToCheck->GetName().find(objectName) != std::string::npos)
198             ++objWithName;
199     }
200
201     // Updating the name
202     if (objWithName > 0)
203         return objectName + "_" + std::to_string(objWithName);
204
205     return objectName;
206 }

```

References `Object::GetId()`, `Object::GetName()`, `object_manager`, and `objects`.

Referenced by `Object::SetName()`.

4.13.2.3 FindObject() `[1/2] Object * Object_Manager::FindObject (`
`int id) [static]`

Finds a object using its id (location in object list) giving instant access.

Parameters

<i>id</i>	Location of object in object_manager object list
-----------	--

Returns

Object*

Definition at line 84 of file object_manager.cpp.

```

84     {
85         if (id >= (int)object_manager->objects.size()) return nullptr;
86         return object_manager->objects[id];
87     }

```

References object_manager, and objects.

Referenced by Behavior::ClassSetup(), Editor::Display_Components(), Editor::Display_Scene(), Graphics::Render(), Shutdown(), Update(), and Physics::UpdateGravity().

4.13.2.4 FindObject() [2/2] Object * Object_Manager::FindObject (std::string objectName) [static]

Finds object with the matching name.

Parameters

<i>objectName</i>	Name to look for
-------------------	------------------

Returns

Object*

Definition at line 95 of file object_manager.cpp.

```

95     {
96         for (Object* object : object_manager->objects) {
97             if (objectName.compare(object->GetName()) == 0)
98                 return object;
99         }
100         return nullptr;
101     }
102 }

```

References Object::GetName(), object_manager, and objects.

4.13.2.5 GetSize() unsigned Object_Manager::GetSize () [static]

Gets the size of the object_manager object list.

Returns

unsigned Size of object list

Definition at line 109 of file object_manager.cpp.

```
109 { return object_manager->objects.size(); }
```

References object_manager, and objects.

Referenced by Editor::Display_Scene(), Graphics::Render(), and Physics::UpdateGravity().

4.13.2.6 Initialize() [1/2] `bool Object_Manager::Initialize () [static]`

Initialize object manager with default values.

Returns

true

false

Definition at line 52 of file object_manager.cpp.

```
52 {
53     // Initializing object_manager
54     object_manager = new Object_Manager;
55     if (!object_manager) {
56         Trace::Message("Object Manager was not initialized.");
57         return false; // Failed to initialize
58     }
59
60     // Adding objects from preset into engine
61     object_manager->objects.reserve(10);
62
63     return true; // Successful initialization
64 }
```

References Trace::Message(), object_manager, and objects.

Referenced by Engine::Initialize(), and Engine::Restart().

4.13.2.7 Initialize() [2/2] `bool Object_Manager::Initialize (
 File_Reader & preset) [static]`

Initializes the object_manager object. Reads in objects for the given preset.

Parameters

<i>preset</i>	List of objects for this preset
---------------	---------------------------------

Returns

true
false

Definition at line 31 of file object_manager.cpp.

```

31                                     {
32     // Initializing object_manager
33     object_manager = new Object_Manager;
34     if (!object_manager) {
35         Trace::Message("Object Manager was not initialized.");
36         return false; // Failed to initialize
37     }
38
39     // Adding objects from preset into engine
40     object_manager->objects.reserve(10);
41     object_manager->ReadList(preset);
42
43     return true; // Successful initialization
44 }
```

References `Trace::Message()`, `object_manager`, `objects`, and `ReadList()`.

4.13.2.8 ReadList() void Object_Manager::ReadList (
File_Reader & preset)

Reads in objects from a preset list that is given.

Parameters

<i>preset</i>	List of objects to be added
---------------	-----------------------------

Definition at line 147 of file object_manager.cpp.

```

147                                     {
148     // Track which object we are on
149     unsigned object_num = 0;
150
151     // Reads objects until there is a failed read
152     while (true) {
153         // Getting the name of the objects file
154         std::string object_name = preset.Read_Object_Name("object_" + std::to_string(object_num));
155         std::string template_name = preset.Read_Object_Template_Name("object_" +
156         std::to_string(object_num));
157         if (template_name.compare("") == 0) break;
158
159         // Constructing the object
160         Object* object = new Object;
161         if (!object->Read(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/objects/" +
162         template_name)) {
163             delete object;
164             continue;
165         }
166         object->SetName(object_name);
167         object->SetTemplateName(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/json/objects/" +
168         template_name);
169         // Reading in the objects position
170         glm::vec3 position = preset.Read_Object_Position("object_" + std::to_string(object_num));
171         glm::vec3 scale = preset.Read_Object_Scale("object_" + std::to_string(object_num));
172         Transform* transform = object->GetComponent<Transform>();
173         transform->SetPosition(position);
174         transform->SetStartPosition(position);
175         transform->SetScale(scale);
176         Behavior* behavior = object->GetComponent<Behavior>();
```

```
175         behavior->SetupClassesForLua();
176
177         // Adding the object to the manager
178         AddObject(object);
179
180         ++object_num;
181     }
182 }
```

References AddObject(), Object::Read(), File_Reader::Read_Object_Name(), File_Reader::Read_Object_Position(), File_Reader::Read_Object_Scale(), File_Reader::Read_Object_Template_Name(), Object::SetName(), Transform::← SetPosition(), Transform::SetScale(), Transform::SetStartPosition(), and Behavior::SetupClassesForLua().

Referenced by Initialize().

4.13.2.9 RemoveObject() void Object_Manager::RemoveObject (
int id) [static]

Removes an object from the object_manager.

Parameters

<i>id</i>	id of object to remove
-----------	------------------------

Returns

void

Definition at line 214 of file object_manager.cpp.

```
214     {
215         if (id >= (int)object_manager->objects.size()) return;
216         Object* objectToDelete = object_manager->objects[id];
217
218         // Moves all the objects to the right of one being deleted to the left
219         unsigned offset = 0;
220         for (unsigned objectNum = id + 1; objectNum < object_manager->objects.size(); ++objectNum) {
221             Object* objectToSwitch = object_manager->objects[objectNum];
222             object_manager->objects[id + offset] = objectToSwitch;
223             objectToSwitch->SetId(id + offset++);
224         }
225
226         // Deleting the object
227         delete objectToDelete;
228         objectToDelete = nullptr;
229         object_manager->objects.pop_back();
230     }
```

References object_manager, objects, and Object::SetId().

Referenced by Editor::Display_Scene().

4.13.2.10 Shutdown() void Object_Manager::Shutdown () [static]

Deletes all objects in the manager and then the object manager.

Returns

void

Definition at line 127 of file object_manager.cpp.

```
127     {
128         if (!object_manager) return; // If the object_manager doesn't exist
129
130         // Deleting each object in the manager
131         for (unsigned i = 0; i < object_manager->objects.size(); ++i) {
132             Object* object = object_manager->FindObject(i);
133             if (object)
134                 delete object;
135         }
136
137         // Deleting the manager
138         delete object_manager;
139         object_manager = nullptr;
140     }
```

References FindObject(), object_manager, and objects.

Referenced by Engine::Restart(), and Engine::Shutdown().

4.13.2.11 Update() void Object_Manager::Update () [static]

Calls the update function for each object in the object list.

Returns

void

Definition at line 116 of file object_manager.cpp.

```
116     {
117         for (unsigned i = 0; i < object_manager->objects.size(); ++i) {
118             object_manager->FindObject(i)->Update();
119         }
120     }
```

References FindObject(), object_manager, objects, and Object::Update().

Referenced by Engine::Update().

4.13.2.12 Write() void Object_Manager::Write (
File_Writer & writer) [static]

Gives all of the object data to writer for output to file.

Parameters

<i>writer</i>	
---------------	--

Returns

void

Definition at line 238 of file object_manager.cpp.

```
238 {
239     for (Object* object : object_manager->objects) {
240         writer.Write_Object_Data(object);
241     }
242 }
```

References object_manager, objects, and File_Writer::Write_Object_Data().

Referenced by Engine::Write().


The documentation for this class was generated from the following files:

- [object_manager.hpp](#)
- [object_manager.cpp](#)

4.14 Physics Class Reference

#include <physics.hpp>

Inheritance diagram for Physics:

**Public Member Functions**

- [Physics](#) ()
Creates [Physics](#) object with default values.
- [Physics](#) (const [Physics](#) &other)
Copy constructor.
- [Physics](#) ([File_Reader](#) &reader)
Creates [Physics](#) object using file.
- [Physics](#) * [Clone](#) () const
Clone [Physics](#) object.
- void [SetAcceleration](#) (glm::vec3 accel)
Sets acceleration of object.

- glm::vec3 [GetAcceleration](#) () const
Returns acceleration of object.
- glm::vec3 & [GetAccelerationRef](#) ()
Returns reference to the acceleration of the object.
- void [SetForces](#) (glm::vec3 force)
Sets forces acting on object.
- void [AddForce](#) (glm::vec3 force)
Adds a force to the current forces acting on the object.
- glm::vec3 [GetForces](#) () const
Returns the forces acting on the object.
- glm::vec3 & [GetForcesRef](#) ()
Returns reference to the forces acting on the object.
- void [ApplyForce](#) (glm::vec3 direction, float power)
Applies force in the given direction using the given power.
- void [SetVelocity](#) (glm::vec3 vel)
Sets the velocity of the object.
- glm::vec3 [GetVelocity](#) () const
Returns the current velocity of the object.
- glm::vec3 & [GetVelocityRef](#) ()
Returns reference to velocity of the object.
- void [SetRotationalVelocity](#) (glm::vec3 rotVel)
Sets rotational velocity.
- glm::vec3 [GetRotationalVelocity](#) () const
Returns rotational velocity.
- glm::vec3 & [GetRotationalVelocityRef](#) ()
Returns reference to rotational velocity.
- void [SetMass](#) (float ma)
Sets the mass of the object.
- float [GetMass](#) () const
Returns the mass of the object.
- float & [GetMassRef](#) ()
Returns reference to mass of the object.
- void [Update](#) ()
Updates the physics of the object.
- void [UpdateGravity](#) ()
Calculates the gravitational pull each object has on each other.
- void [Read](#) (File_Reader &reader)
Reads data for [Physics](#) object from file.
- void [Write](#) (File_Writer &writer)
Gives physics data to the writer object.

Static Public Member Functions

- static [CType](#) [GetCType](#) ()
Gets the CType of [Physics](#) (used in [Object::GetComponent<>\(\)](#))

Private Attributes

- glm::vec3 [acceleration](#)
Acceleration of object.
- glm::vec3 [forces](#)
Forces acting on object (reset at end of each update)
- glm::vec3 [velocity](#)
Velocity of object.
- glm::vec3 [initialVelocity](#)
Starting velocity.
- glm::vec3 [initialAcceleration](#)
Starting acceleration.
- glm::vec3 [rotationalVelocity](#)
How fast is the object rotating.
- float [mass](#)
Mass of object.

Additional Inherited Members

4.14.1 Detailed Description

[Physics](#) class

Definition at line 25 of file physics.hpp.

4.14.2 Constructor & Destructor Documentation

4.14.2.1 [Physics\(\)](#) [1/3] `Physics::Physics ()`

Creates [Physics](#) object with default values.

Definition at line 32 of file physics.cpp.

```
32         : Component(CType::CPhysics),  
33   acceleration(glm::vec3(0.f, 0.f, 0.f)), forces(glm::vec3(0.f, 0.f, 0.f)),  
34   velocity(glm::vec3(0.f, 0.f, 0.f)), rotationalVelocity(glm::vec3(0.f, 0.f, 0.f)), mass(1.f) {}
```

Referenced by [Clone\(\)](#).

4.14.2.2 [Physics\(\)](#) [2/3] `Physics::Physics (` `const Physics & other)`

Copy constructor.

Parameters

<i>other</i>	Physics object to be copied
--------------	-----------------------------

Definition at line 41 of file physics.cpp.

```

41                                     : Component(CType::CPhysics) {
42     *this = other;
43 }
```

4.14.2.3 Physics() [3/3] Physics::Physics (File_Reader & reader)

Creates Physics object using file.

Parameters

<i>reader</i>	File to use for making physics object
---------------	---------------------------------------

Definition at line 50 of file physics.cpp.

```

50                                     : Component(CType::CPhysics),
51     acceleration(glm::vec3(0.f, 0.f, 0.f)), forces(glm::vec3(0.f, 0.f, 0.f)),
52     velocity(glm::vec3(0.f, 0.f, 0.f)), rotationalVelocity(glm::vec3(0.f, 0.f, 0.f)), mass(1.f) {
53     Read(reader);
54 }
```

References Read().

4.14.3 Member Function Documentation

4.14.3.1 AddForce() void Physics::AddForce (glm::vec3 force)

Adds a force to the current forces acting on the object.

Parameters

<i>force</i>	
--------------	--

Definition at line 98 of file physics.cpp.

```
98 { forces += force; }
```

References forces.

Referenced by ApplyForce().

4.14.3.2 ApplyForce() `void Physics::ApplyForce (`
 `glm::vec3 direction,`
 `float power)`

Applies force in the given direction using the given power.

Parameters

<i>direction</i>	
<i>power</i>	

Definition at line 120 of file physics.cpp.

```
120                                     {
121     direction = glm::normalize(direction);
122     direction *= power;
123
124     AddForce(direction);
125 }
```

References AddForce().

Referenced by Behavior::ClassSetup().

4.14.3.3 Clone() `Physics * Physics::Clone () const`

Clone [Physics](#) object.

Returns

Physics* Cloned [Physics](#) object

Definition at line 61 of file physics.cpp.

```
61     {
62     return new Physics(*this);
63 }
```

References Physics().

4.14.3.4 GetAcceleration() `glm::vec3 Physics::GetAcceleration () const`

Returns acceleration of object.

Returns

glm::vec3

Definition at line 77 of file physics.cpp.

```
77 { return acceleration; }
```

References acceleration.

4.14.3.5 GetAccelerationRef() `glm::vec3 & Physics::GetAccelerationRef ()`

Returns reference to the acceleration of the object.

Returns

`glm::vec3&`

Definition at line 84 of file `physics.cpp`.

```
84 { return acceleration; }
```

References acceleration.

Referenced by `Behavior::ClassSetup()`.

4.14.3.6 GetCType() `CType Physics::GetCType () [static]`

Gets the CType of `Physics` (used in `Object::GetComponent<>()`)

Returns

`CType`

Definition at line 281 of file `physics.cpp`.

```
281 {  
282     return CType::CPhysics;  
283 }
```

4.14.3.7 GetForces() `glm::vec3 Physics::GetForces () const`

Returns the forces acting on the object.

Returns

`glm::vec3`

Definition at line 105 of file `physics.cpp`.

```
105 { return forces; }
```

References forces.

4.14.3.8 GetForcesRef() `glm::vec3 & Physics::GetForcesRef ()`

Returns reference to the forces acting on the object.

Returns

`glm::vec3&`

Definition at line 112 of file physics.cpp.

```
112 { return forces; }
```

References forces.

Referenced by Behavior::ClassSetup().

4.14.3.9 GetMass() `float Physics::GetMass () const`

Returns the mass of the object.

Returns

`float`

Definition at line 160 of file physics.cpp.

```
160 { return mass; }
```

References mass.

4.14.3.10 GetMassRef() `float & Physics::GetMassRef ()`

Returns reference to mass of the object.

Returns

`float&`

Definition at line 167 of file physics.cpp.

```
167 { return mass; }
```

References mass.

Referenced by Editor::Display_Physics().

4.14.3.11 GetRotationalVelocity() `glm::vec3 Physics::GetRotationalVelocity () const`

Returns rotational velocity.

Returns

`glm::vec3`

Definition at line 181 of file physics.cpp.

```
181 { return rotationalVelocity; }
```

References rotationalVelocity.

4.14.3.12 GetRotationalVelocityRef() `glm::vec3 & Physics::GetRotationalVelocityRef ()`

Returns reference to rotational velocity.

Returns

`glm::vec3&`

Definition at line 188 of file physics.cpp.

```
188 { return rotationalVelocity; }
```

References rotationalVelocity.

Referenced by Editor::Display_Physics().

4.14.3.13 GetVelocity() `glm::vec3 Physics::GetVelocity () const`

Returns the current velocity of the object.

Returns

`glm::vec3`

Definition at line 139 of file physics.cpp.

```
139 { return velocity; }
```

References velocity.

4.14.3.14 GetVelocityRef() `glm::vec3 & Physics::GetVelocityRef ()`

Returns reference to velocity of the object.

Returns

`glm::vec3&`

Definition at line 146 of file physics.cpp.

```
146 { return velocity; }
```

References velocity.

Referenced by Behavior::ClassSetup(), and Editor::Display_Physics().

4.14.3.15 Read() `void Physics::Read (
 File_Reader & reader)`

Reads data for [Physics](#) object from file.

Parameters

<i>reader</i>	File to be read from
---------------	----------------------

Definition at line 257 of file physics.cpp.

```
257     {  
258         initialAcceleration = reader.Read_Vec3("acceleration");  
259         initialVelocity = reader.Read_Vec3("velocity");  
260         SetAcceleration(initialAcceleration);  
261         SetVelocity(initialVelocity);  
262         SetMass(reader.Read_Float("mass"));  
263     }
```

References initialAcceleration, initialVelocity, File_Reader::Read_Float(), File_Reader::Read_Vec3(), SetAcceleration(), SetMass(), and SetVelocity().

Referenced by Physics(), and Object::ReRead().

4.14.3.16 SetAcceleration() `void Physics::SetAcceleration (
 glm::vec3 accel)`

Sets acceleration of object.

Parameters

<i>accel</i>	
--------------	--

Definition at line 70 of file physics.cpp.

```
70 { acceleration = accel; }
```

References acceleration.

Referenced by Behavior::ClassSetup(), and Read().

4.14.3.17 SetForces() void Physics::SetForces (
glm::vec3 *force*)

Sets forces acting on object.

Parameters

<i>force</i>	
--------------	--

Definition at line 91 of file physics.cpp.

```
91 { forces = force; }
```

References forces.

Referenced by Behavior::ClassSetup().

4.14.3.18 SetMass() void Physics::SetMass (
float *ma*)

Sets the mass of the object.

Parameters

<i>ma</i>	
-----------	--

Definition at line 153 of file physics.cpp.

```
153 { mass = ma; }
```

References mass.

Referenced by Read().

4.14.3.19 SetRotationalVelocity() void Physics::SetRotationalVelocity (
glm::vec3 *rotVel*)

Sets rotational velocity.

Parameters

<i>rotVel</i>	New rotational velocity
---------------	-------------------------

Definition at line 174 of file physics.cpp.

```
174 { rotationalVelocity = rotVel; }
```

References rotationalVelocity.

4.14.3.20 SetVelocity() void Physics::SetVelocity (
 glm::vec3 vel)

Sets the velocity of the object.

Parameters

<i>vel</i>	
------------	--

Definition at line 132 of file physics.cpp.

```
132 { velocity = vel; }
```

References velocity.

Referenced by Behavior::ClassSetup(), and Read().

4.14.3.21 Update() void Physics::Update ()

Updates the physics of the object.

Definition at line 194 of file physics.cpp.

```
194 {
195     // Finding the acceleration of the object using F=ma
196     acceleration = forces / mass;
197
198     // Updating velocity
199     velocity += (acceleration * Engine::GetDt());
200
201     // Updating position
202     Transform* transform = GetParent()->GetComponent<Transform>();
203     glm::vec3 position = transform->GetPosition();
204     transform->SetOldPosition(position);
205     position = (velocity * Engine::GetDt()) + position;
206     transform->SetPosition(position);
207
208     // Updating rotation
209     glm::vec3 rotation = transform->GetRotation();
210     rotation = (rotationalVelocity * Engine::GetDt()) + rotation;
211     transform->SetRotation(rotation);
212
213     // Resetting the forces acting on the object
214     forces = glm::vec3(0.f, 0.f, 0.f);
215 }
```

References acceleration, forces, Object::GetComponent(), Engine::GetDt(), Component::GetParent(), Transform::GetPosition(), Transform::GetRotation(), mass, rotationalVelocity, Transform::SetOldPosition(), Transform::SetPosition(), Transform::SetRotation(), and velocity.

Referenced by Object::Update().

4.14.3.22 UpdateGravity() void Physics::UpdateGravity ()

Calculates the gravitational pull each object has on each other.

Definition at line 221 of file physics.cpp.

```

221         {
222             // Gets the needed components for the current object
223             Object* object = GetParent();
224             Transform* transform = object->GetComponent<Transform>();
225             Physics* physics = object->GetComponent<Physics>();
226             glm::vec3 position = transform->GetPosition();
227
228             // For each object
229             for (unsigned i = 0; i < Object_Manager::GetSize(); ++i) {
230                 if ((int)i == object->GetId()) continue;
231                 // Gets needed components for the object being checked
232                 Object* other = Object_Manager::FindObject(i);
233                 Physics* otherPhysics = other->GetComponent<Physics>();
234                 Transform* otherTransform = other->GetComponent<Transform>();
235                 glm::vec3 otherPosition = otherTransform->GetPosition();
236                 // Finding the distance between the objects
237                 double distance = sqrt(pow(double(otherPosition.x - position.x), 2.0) +
238                                     pow(double(otherPosition.y - position.y), 2.0) +
239                                     pow(double(otherPosition.z - position.z), 2.0));
240                 // Calculating the force the objects apply on each other
241                 double magnitude = Engine::GetGravConst() * ((physics->mass * otherPhysics->mass)) / pow(distance,
242                 2.0);
243                 // Getting the direction (normalized)
244                 glm::vec3 direction = otherPosition - position;
245                 glm::vec3 normDirection = glm::normalize(direction);
246                 // Applying gravitational force to normalized direction
247                 glm::vec3 force = normDirection * float(magnitude);
248                 // Adding the gravitational force to the forces on object
249                 physics->AddForce(force);
250             }
251         }

```

References Object_Manager::FindObject(), Object::GetComponent(), Engine::GetGravConst(), Component::GetParent(), Transform::GetPosition(), Object_Manager::GetSize(), and mass.

Referenced by Behavior::ClassSetup().

4.14.3.23 Write() void Physics::Write (File_Writer & writer)

Gives physics data to the writer object.

Parameters

<i>writer</i>	
---------------	--

Definition at line 270 of file physics.cpp.

```
270     {
271     writer.Write_Vec3("acceleration", initialAcceleration);
272     writer.Write_Vec3("velocity", initialVelocity);
273     writer.Write_Value("mass", mass);
274 }
```

References `initialAcceleration`, `initialVelocity`, `mass`, `File_Writer::Write_Value()`, and `File_Writer::Write_Vec3()`.

Referenced by `Object::Write()`.

The documentation for this class was generated from the following files:

- [physics.hpp](#)
- [physics.cpp](#)

4.15 Random Class Reference

```
#include <random.hpp>
```

Static Public Member Functions

- static bool [Initialize](#) ()
Initializes the random system.
- static void [Shutdown](#) ()
Delete the random object.
- static glm::vec3 [random_vec3](#) (float low, float high)
Creates a random vec3.
- static float [random_float](#) (float low, float high)
Creates random float.

Private Attributes

- std::random_device [rd](#)
Random device.

4.15.1 Detailed Description

[Random](#) class

Definition at line 23 of file random.hpp.

4.15.2 Member Function Documentation

4.15.2.1 Initialize() `bool Random::Initialize () [static]`

Initializes the random system.

Returns

true

false

Definition at line 24 of file random.cpp.

```

24         {
25         // Initializing random
26         random = new Random;
27         if (!random) {
28             Trace::Message("Random failed to initialize.");
29             return false;
30         }
31
32         return true;
33     }
```

References Trace::Message(), and random.

Referenced by Engine::Initialize().

4.15.2.2 random_float() `float Random::random_float (float low, float high) [static]`

Creates random float.

Parameters

<i>low</i>	Lower boundary in random gen
<i>high</i>	Upper boundary in random gen

Returns

float

Definition at line 70 of file random.cpp.

```

70         {
71         // Setup random gen
72         std::mt19937 gen(random->rd());
73         std::uniform_real_distribution<> dist(low, high);
74         // Gen random float
75         return dist(gen);
76     }
```

References random, and rd.

Referenced by Behavior::ClassSetup().

4.15.2.3 random_vec3() glm::vec3 Random::random_vec3 (
float low,
float high) [static]

Creates a random vec3.

Parameters

<i>low</i>	Lower boundary in random gen
<i>high</i>	Upper boundary in random gen

Returns

vec3

Definition at line 54 of file random.cpp.

```
54                                     {  
55     // Setup random gen  
56     std::mt19937 gen(random->rd());  
57     std::uniform_real_distribution<> dist(low, high);  
58     // Gen random vec3  
59     glm::vec3 result_vec3 = { dist(gen), dist(gen), dist(gen) };  
60     return result_vec3;  
61 }
```

References random, and rd.

Referenced by Behavior::ClassSetup().

4.15.2.4 Shutdown() void Random::Shutdown () [static]

Delete the random object.

Returns

void

Definition at line 40 of file random.cpp.

```
40     {  
41     if (!random) return;  
42  
43     delete random;  
44     random = nullptr;  
45 }
```

References random.

Referenced by Engine::Shutdown().

The documentation for this class was generated from the following files:

- [random.hpp](#)
- [random.cpp](#)

4.16 Shader Class Reference

```
#include <shader.hpp>
```

Static Public Member Functions

- static bool [Initialize](#) ([File_Reader](#) &settings)
Initializes the shader object.
- static bool [Initialize](#) ()
Initialize shader with default values.
- static void [Update](#) ()
Tells program to use shader.
- static void [Shutdown](#) ()
Shutdown shader.
- static std::string [ReadFile](#) (std::string filename)
Reads shader file into std::string.
- static void [LoadShader](#) (std::string vertexPath, std::string fragmentPath)
Loads the vertex and fragment shader using given filepaths.
- static GLuint [GetProgram](#) ()
Returns the program id.
- static GLuint [GetMatrixId](#) ()
Returns the mvp buffer id.
- static GLuint [GetViewMatrixId](#) ()
Returns the view matrix buffer id.
- static GLuint [GetModelMatrixId](#) ()
Returns the model matrix buffer id.
- static GLuint [GetLightId](#) ()
Returns the light pos buffer id.
- static GLuint [GetLightPowerId](#) ()
Returns the light power buffer id.

Private Attributes

- GLuint [program](#)
Program id for the engine.
- GLuint [matrixId](#)
MVP matrix id.
- GLuint [viewMatrixId](#)
View matrix id.
- GLuint [modelMatrixId](#)
Model matrix id.
- GLuint [lightId](#)
Light id for world.
- GLuint [lightPowerId](#)
Id for light power buffer.

4.16.1 Detailed Description

[Shader](#) class

Definition at line 26 of file shader.hpp.

4.16.2 Member Function Documentation

4.16.2.1 `GetLightId()` `GLuint Shader::GetLightId () [static]`

Returns the light pos buffer id.

Returns

GLuint

Definition at line 192 of file shader.cpp.

```
192 { return shader->lightId; }
```

References `lightId`, and `shader`.

Referenced by `Model_Data::Draw()`.

4.16.2.2 `GetLightPowerId()` `GLuint Shader::GetLightPowerId () [static]`

Returns the light power buffer id.

Returns

GLuint

Definition at line 199 of file shader.cpp.

```
199 { return shader->lightPowerId; }
```

References `lightPowerId`, and `shader`.

Referenced by `Model_Data::Draw()`.

4.16.2.3 GetMatrixId() GLuint Shader::GetMatrixId () [static]

Returns the mvp buffer id.

Returns

GLuint

Definition at line 171 of file shader.cpp.

```
171 { return shader->matrixId; }
```

References matrixId, and shader.

Referenced by Model_Data::Draw().

4.16.2.4 GetModelMatrixId() GLuint Shader::GetModelMatrixId () [static]

Returns the model matrix buffer id.

Returns

GLuint

Definition at line 185 of file shader.cpp.

```
185 { return shader->modelMatrixId; }
```

References modelMatrixId, and shader.

Referenced by Model_Data::Draw().

4.16.2.5 GetProgram() GLuint Shader::GetProgram () [static]

Returns the program id.

Returns

GLuint

Definition at line 164 of file shader.cpp.

```
164 { return shader->program; }
```

References program, and shader.

Referenced by Texture::Load().

4.16.2.6 GetViewMatrixId() `GLuint Shader::GetViewMatrixId () [static]`

Returns the view matrix buffer id.

Returns

GLuint

Definition at line 178 of file shader.cpp.

```
178 { return shader->viewMatrixId; }
```

References shader, and viewMatrixId.

Referenced by Model_Data::Draw().

4.16.2.7 Initialize() [1/2] `bool Shader::Initialize () [static]`

Initialize shader with default values.

Returns

true

false

Definition at line 50 of file shader.cpp.

```
50 {
51     shader = new Shader;
52     if (!shader) {
53         Trace::Message("Shader failed to initialize.\n");
54         return false;
55     }
56
57     //LoadShader("src/shaders/vertex.glsl", "src/shaders/fragment.glsl");
58     LoadShader(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/shaders/vertex.glsl",
59               std::string(getenv("USERPROFILE")) + "/Documents/pEngine/shaders/fragment.glsl");
60     return true;
61 }
```

References LoadShader(), Trace::Message(), and shader.

Referenced by Graphics::Initialize().

4.16.2.8 Initialize() [2/2] `bool Shader::Initialize (File_Reader & settings) [static]`

Initializes the shader object.

Parameters

<i>settings</i>	<code>File_Reader</code> object that contains name of shaders to use
-----------------	--

Returns

true
false

Definition at line 31 of file shader.cpp.

```

31                                     {
32     shader = new Shader;
33     if (!shader) {
34         Trace::Message("Shader failed to initialize.\n");
35         return false;
36     }
37
38     //LoadShader("src/shaders/vertex.glsl", "src/shaders/fragment.glsl");
39     LoadShader(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/shaders/" +
settings.Read_String("vertexShader") + ".glsl",
40               std::string(getenv("USERPROFILE")) + "/Documents/pEngine/shaders/" +
settings.Read_String("fragShader") + ".glsl");
41     return true;
42 }
```

References LoadShader(), Trace::Message(), File_Reader::Read_String(), and shader.

4.16.2.9 LoadShader() void Shader::LoadShader (
std::string vertexPath,
std::string fragmentPath) [static]

Loads the vertex and fragment shader using given filepaths.

Parameters

<i>vertexPath</i>	// Vertex shader filepath
<i>fragmentPath</i>	// Fragment shader filepath

Returns

void

Definition at line 121 of file shader.cpp.

```

121                                     {
122     // Creating shaders
123     GLuint vertShader = glCreateShader(GL_VERTEX_SHADER);
124     GLuint fragShader = glCreateShader(GL_FRAGMENT_SHADER);
125
126     // Reading shaders
127     std::string vertShaderStr = ReadFile(vertexPath);
128     std::string fragShaderStr = ReadFile(fragmentPath);
129     const char *vertShaderSrc = vertShaderStr.c_str();
130     const char *fragShaderSrc = fragShaderStr.c_str();
131
132     // Compiling shaders
133     glShaderSource(vertShader, 1, &vertShaderSrc, nullptr);
134     glCompileShader(vertShader);
135
136     glShaderSource(fragShader, 1, &fragShaderSrc, nullptr);
137     glCompileShader(fragShader);
138
139     // Attaching shaders to engine
140     shader->program = glCreateProgram();
141     glAttachShader(shader->program, vertShader);
```

```

142     glAttachShader(shader->program, fragShader);
143
144     // Cleanup
145     glDeleteShader.vertShader);
146     glDeleteShader(fragShader);
147
148     // Setting up program
149     glLinkProgram(shader->program);
150     glUseProgram(shader->program);
151
152     shader->matrixId = glGetUniformLocation(shader->program, "MVP");
153     shader->viewMatrixId = glGetUniformLocation(shader->program, "V");
154     shader->modelMatrixId = glGetUniformLocation(shader->program, "M");
155     shader->lightId = glGetUniformLocation(shader->program, "LightPosition_worldspace");
156     shader->lightPowerId = glGetUniformLocation(shader->program, "LightPower");
157 }

```

References lightId, lightPowerId, matrixId, modelMatrixId, program, ReadFile(), shader, and viewMatrixId.

Referenced by Initialize().

4.16.2.10 ReadFile() `std::string Shader::ReadFile (`
`std::string filepath) [static]`

Reads shader file into std::string.

Parameters

<i>filepath</i>	Shader file
-----------------	-----------------------------

Returns

std::string

Definition at line 92 of file shader.cpp.

```

92     {
93         std::string content;
94
95         // Opening the shader file
96         std::ifstream file(filepath.c_str(), std::ios::in);
97         if (!file.is_open()) {
98             Trace::Message("Failed to read file: " + filepath + "\n");
99             return "";
100         }
101
102         // Saving shader file into std::string
103         std::string line = "";
104         while (!file.eof()) {
105             getline(file, line);
106             content.append(line + "\n");
107         }
108
109         // Closing file and returning std::string
110         file.close();
111         return content;
112     }

```

References Trace::Message().

Referenced by LoadShader().

4.16.2.11 Shutdown() `void Shader::Shutdown () [static]`

Shutdown shader.

Returns

void

Definition at line 77 of file shader.cpp.

```
77     {  
78     if (!shader) return;  
79  
80     glDeleteProgram(shader->program);  
81  
82     delete shader;  
83     shader = nullptr;  
84 }
```

References program, and shader.

Referenced by Graphics::Shutdown().

4.16.2.12 Update() `void Shader::Update () [static]`

Tells program to use shader.

Returns

void

Definition at line 68 of file shader.cpp.

```
68     {  
69     glUseProgram(shader->program);  
70 }
```

References program, and shader.

Referenced by Graphics::Render().

The documentation for this class was generated from the following files:

- [shader.hpp](#)
- [shader.cpp](#)

4.17 Texture Class Reference

```
#include <texture.hpp>
```

Public Member Functions

- [~Texture](#) ()
Deletes texture data.
- bool [Load](#) (std::string textureName_)
Loads in texture with given filename.
- void [Display](#) ()
Setup texture for drawing.
- std::string [GetTextureName](#) () const
Returns texture name.
- GLuint [GetTextureNum](#) () const
Returns texture data id.

Static Private Member Functions

- static GLuint [LoadDDS](#) (FILE *fp)
Loads in the given dds file.

Private Attributes

- std::string [textureName](#)
Name of texture.
- GLuint [textureNum](#)
Loaded texture data id.
- GLuint [textureId](#)
Textures buffer id.
- bool [hasBeenSet](#)
Whether there is a texture or not.

4.17.1 Detailed Description

[Texture](#) class

Definition at line 23 of file texture.hpp.

4.17.2 Constructor & Destructor Documentation

4.17.2.1 [~Texture\(\)](#) `Texture::~~Texture ()`

Deletes texture data.

Definition at line 24 of file texture.cpp.

```
24     {  
25         glDeleteTextures(1, &textureNum);  
26     }
```

References [textureNum](#).

4.17.3 Member Function Documentation

4.17.3.1 Display() `void Texture::Display ()`

Setup texture for drawing.

Definition at line 63 of file texture.cpp.

```
63     {  
64         if (!hasBeenSet) return;  
65     }  
66     glActiveTexture(GL_TEXTURE0);  
67     glBindTexture(GL_TEXTURE_2D, textureNum);  
68     glUniform1i(textureId, 0);  
69 }
```

References `hasBeenSet`, `textureId`, and `textureNum`.

Referenced by `Model_Data::Draw()`.

4.17.3.2 GetTextureName() `std::string Texture::GetTextureName () const`

Returns texture name.

Returns

`std::string`

Definition at line 76 of file texture.cpp.

```
76 { return textureName; }
```

References `textureName`.

Referenced by `Texture_Manager::Get()`, `Model::GetTextureName()`, and `Model::Write()`.

4.17.3.3 GetTextureNum() `GLuint Texture::GetTextureNum () const`

Returns texture data id.

Returns

`GLuint`

Definition at line 83 of file texture.cpp.

```
83 { return textureNum; }
```

References `textureNum`.

4.17.3.4 Load() `bool Texture::Load (std::string textureName_)`

Loads in texture with given filename.

Parameters

<i>textureName_</i>	Filename of texture
---------------------	---------------------

Returns

true
false

Definition at line 35 of file texture.cpp.

```

35                                     {
36     FILE *fp;
37     std::string filename = std::string(getenv("USERPROFILE")) + "/Documents/pEngine/textures/" +
    textureName_;
38     textureName = filename ;
39
40     // Opening the file
41     fp = fopen(filename.c_str(), "rb");
42     if (!fp) {
43         fp = fopen(textureName_.c_str(), "rb");
44         if (!fp) {
45             return false;
46         }
47         else {
48             textureName = textureName_;
49         }
50     }
51
52     textureNum = Texture::LoadDDS(fp);
53     textureId = glGetUniformLocation(Shader::GetProgram(), "myTextureSampler");
54     hasBeenSet = true;
55
56     return true;
57 }
```

References Shader::GetProgram(), hasBeenSet, LoadDDS(), textureId, textureName, and textureNum.

Referenced by Texture_Manager::Get().

4.17.3.5 LoadDDS() GLuint Texture::LoadDDS (
 FILE * *fp*) [static], [private]

Loads in the given dds file.

Parameters

<i>fp</i>	The file stream
-----------	-----------------

Returns

GLuint

Definition at line 94 of file texture.cpp.

```

94         {
95     unsigned char header[124];
96
97     // Making sure it is a dds
98     char filecode[4];
99     fread(filecode, 1, 4, fp);
100     if (strncmp(filecode, "DDS ", 4) != 0) {
101         fclose(fp);
102         return 0;
103     }
104
105     // Getting the surface description
106     fread(&header, 124, 1, fp);
107
108     unsigned int height      = *(unsigned int*)&(header[8]);
109     unsigned int width       = *(unsigned int*)&(header[12]);
110     unsigned int linearSize  = *(unsigned int*)&(header[16]);
111     unsigned int mipMapCount = *(unsigned int*)&(header[24]);
112     unsigned int fourCC      = *(unsigned int*)&(header[80]);
113
114     unsigned char * buffer;
115     unsigned int bufsize;
116
117     bufsize = mipMapCount > 1 ? linearSize * 2 : linearSize;
118     buffer = (unsigned char*)malloc(bufsize * sizeof(unsigned char));
119     fread(buffer, 1, bufsize, fp);
120
121     // Close the file
122     fclose(fp);
123
124     unsigned int format;
125     switch(fourCC) {
126     case FOURCC_DXT1:
127         format = GL_COMPRESSED_RGBA_S3TC_DXT1_EXT;
128         break;
129     case FOURCC_DXT3:
130         format = GL_COMPRESSED_RGBA_S3TC_DXT3_EXT;
131         break;
132     case FOURCC_DXT5:
133         format = GL_COMPRESSED_RGBA_S3TC_DXT5_EXT;
134         break;
135     default:
136         free(buffer);
137         return 0;
138     }
139
140     GLuint textureID;
141     glGenTextures(1, &textureID);
142
143     glBindTexture(GL_TEXTURE_2D, textureID);
144     glPixelStorei(GL_UNPACK_ALIGNMENT,1);
145
146     unsigned int blockSize = (format == GL_COMPRESSED_RGBA_S3TC_DXT1_EXT) ? 8 : 16;
147     unsigned int offset = 0;
148
149     for (unsigned int level = 0; level < mipMapCount && (width || height); ++level) {
150         unsigned int size = ((width+3)/4)*((height+3)/4)*blockSize;
151         glCompressedTexImage2D(GL_TEXTURE_2D, level, format, width, height,
152             0, size, buffer + offset);
153
154         offset += size;
155         width  /= 2;
156         height /= 2;
157
158         if(width < 1) width = 1;
159         if(height < 1) height = 1;
160     }
161
162     free(buffer);
163
164     return textureID;
165 }
166 }

```

References `FOURCC_DXT1`, `FOURCC_DXT3`, and `FOURCC_DXT5`.

Referenced by `Load()`.

The documentation for this class was generated from the following files:

- [texture.hpp](#)
- [texture.cpp](#)

4.18 Texture_Manager Class Reference

```
#include <texture_manager.hpp>
```

Static Public Member Functions

- static bool [Initialize](#) ()
Initializes the texture_manager.
- static [Texture](#) * [Get](#) ([File_Reader](#) &reader)
Looks for texture in list of loaded textures. If found it returns a pointer. If not found it creates texture, adds it to the list of textures and returns a pointer to it.
- static [Texture](#) * [Get](#) (std::string textureName)
Looks for texture in list of loaded textures. If found it returns a pointer. If not found it creates texture, adds it to the list of textures and returns a pointer to it.
- static void [Shutdown](#) ()
Deletes all texture object and then the manager.

Private Attributes

- std::vector< [Texture](#) * > [textures](#)
List of loaded textures.

4.18.1 Detailed Description

[Texture_Manager](#) class

Definition at line 25 of file texture_manager.hpp.

4.18.2 Member Function Documentation

4.18.2.1 [Get\(\)](#) [1/2] [Texture](#) * [Texture_Manager::Get](#) ([File_Reader](#) & reader) [static]

Looks for texture in list of loaded textures. If found it returns a pointer. If not found it creates texture, adds it to the list of textures and returns a pointer to it.

Parameters

<i>reader</i>	File_Reader object that contains name of texture
---------------	--

Returns

Texture*

Definition at line 45 of file texture_manager.cpp.

```

45     {
46         // Getting texture's filename
47         std::string filename = reader.Read_String("textureToLoad");
48         // Looking for texture in list of loaded textures
49         for (Texture* texture : texture_manager->textures) {
50             if (texture->GetTextureName().compare(filename) == 0) {
51                 return texture;
52             }
53         }
54
55         // Creating new texture
56         Texture* texture = new Texture;
57         texture->Load(filename);
58         texture_manager->textures.emplace_back(texture);
59
60         return texture;
61     }

```

References [Texture::GetTextureName\(\)](#), [Texture::Load\(\)](#), [File_Reader::Read_String\(\)](#), [texture_manager](#), and [textures](#).Referenced by [Model::Load\(\)](#), and [Model::SwitchTexture\(\)](#).

4.18.2.2 Get() [2/2] [Texture](#) * [Texture_Manager::Get](#) (
 std::string textureName) [static]

Looks for texture in list of loaded textures. If found it returns a pointer. If not found it creates texture, adds it to the list of textures and returns a pointer to it.

Parameters

<i>textureName</i>	Name of texture
--------------------	-----------------

Returns

Texture*

Definition at line 71 of file texture_manager.cpp.

```

71     {
72         // Looking for texture in list of loaded textures
73         for (Texture* texture : texture_manager->textures) {
74             if (texture->GetTextureName().compare(textureName) == 0) {
75                 return texture;
76             }
77         }
78
79         // Creating new texture

```

```
80     Texture* texture = new Texture;
81     if (!texture->Load(textureName)) {
82         delete texture;
83         return nullptr;
84     }
85     texture_manager->textures.emplace_back(texture);
86
87     return texture;
88 }
```

References Texture::GetTextureName(), Texture::Load(), texture_manager, and textures.

4.18.2.3 Initialize() `bool Texture_Manager::Initialize () [static]`

Initializes the texture_manager.

Returns

true

false

Definition at line 24 of file texture_manager.cpp.

```
24     {
25         // Initializing texture_manager
26         texture_manager = new Texture_Manager;
27         if (!texture_manager) {
28             Trace::Message("Texture Manager was not initialized.\n");
29             return false;
30         }
31
32         // Reserving space in the texture_manager
33         texture_manager->textures.reserve(10);
34         return true;
35 }
```

References Trace::Message(), texture_manager, and textures.

Referenced by Engine::Initialize().

4.18.2.4 Shutdown() `void Texture_Manager::Shutdown () [static]`

Deletes all texture object and then the manager.

Returns

void

Definition at line 95 of file texture_manager.cpp.

```
95     {  
96         if (!texture_manager) return;  
97  
98         for (Texture* texture : texture_manager->textures) {  
99             if (!texture) continue;  
100  
101             delete texture;  
102             texture = nullptr;  
103         }  
104  
105         delete texture_manager;  
106         texture_manager = nullptr;  
107     }
```

References texture_manager, and textures.

Referenced by Engine::Shutdown().

The documentation for this class was generated from the following files:

- [texture_manager.hpp](#)
- [texture_manager.cpp](#)

4.19 Trace Class Reference

```
#include <trace.hpp>
```

Static Public Member Functions

- static void [Initialize](#) ()
Initializes the trace system.
- static void [Message](#) (std::string message)
Prints a message into the output file.
- static void [Shutdown](#) ()
Closes output file and deletes trace object.

Private Attributes

- std::fstream [trace_stream](#)
Output file.

4.19.1 Detailed Description

[Trace](#) class

Definition at line 21 of file trace.hpp.

4.19.2 Member Function Documentation

4.19.2.1 Initialize() `void Trace::Initialize () [static]`

Initializes the trace system.

Returns

`void`

Definition at line 26 of file trace.cpp.

```
26     {  
27         trace = new Trace;  
28  
29         // Opens output file  
30         trace->trace_stream.open(std::string(getenv("USERPROFILE")) + "/Documents/pEngine/trace.log",  
std::ofstream::out);  
31         if (!trace->trace_stream) std::cout << "Trace file wasn't opened successfully.\n";  
32     }
```

References trace, and trace_stream.

Referenced by main().

4.19.2.2 Message() `void Trace::Message (std::string message) [static]`

Prints a message into the output file.

Parameters

<i>message</i>	Message to be printed
----------------	-----------------------

Returns

`void`

Definition at line 40 of file trace.cpp.

```
40     {  
41         if (!trace->trace_stream) return;  
42  
43         trace->trace_stream << message;  
44         std::cout << message;  
45     }
```

References trace, and trace_stream.

Referenced by Graphics::ErrorCallback(), Graphics::ErrorCheck(), Random::Initialize(), Engine::Initialize(), Model←_Data_Manager::Initialize(), Object_Manager::Initialize(), Texture_Manager::Initialize(), Editor::Initialize(), Shader::←Initialize(), Camera::Initialize(), Graphics::Initialize(), Model_Data::Read(), Shader::ReadFile(), Engine::Restart(), and Object::Write().

4.19.2.3 Shutdown() `void Trace::Shutdown () [static]`

Closes output file and deletes trace object.

Returns

`void`

Definition at line 52 of file trace.cpp.

```
52     {
53         // Closing output file
54         if (trace->trace_stream) trace->trace_stream.close();
55
56         delete trace;
57         trace = nullptr;
58     }
```

References trace, and trace_stream.

Referenced by main().


The documentation for this class was generated from the following files:

- [trace.hpp](#)
- [trace.cpp](#)

4.20 Transform Class Reference

```
#include <transform.hpp>
```

Inheritance diagram for Transform:



Public Member Functions

- [Transform](#) ()
Creates [Transform](#) object with default values.
- [Transform](#) (const [Transform](#) &other)
Copy constructor.
- [Transform](#) ([File_Reader](#) &reader)
Creates [Transform](#) object using file.
- [Transform](#) * [Clone](#) () const
Clones current [Transform](#) object.
- void [SetPosition](#) (glm::vec3 pos)
Sets position of object.
- glm::vec3 [GetPosition](#) () const
Returns position of object.
- glm::vec3 & [GetPositionRef](#) ()
Returns position reference of object.
- void [SetOldPosition](#) (glm::vec3 oldPos)
Sets old position of object.
- glm::vec3 [GetOldPosition](#) () const
Returns old position of object.
- void [SetScale](#) (glm::vec3 sca)
Sets scale of object.
- glm::vec3 [GetScale](#) () const
Returns scale of object.
- glm::vec3 & [GetScaleRef](#) ()
Returns scale reference of object.
- void [SetRotation](#) (glm::vec3 rot)
Sets rotation of object.
- glm::vec3 [GetRotation](#) () const
Returns rotation of object.
- glm::vec3 & [GetRotationRef](#) ()
Returns rotation reference of object.
- void [SetStartPosition](#) (glm::vec3 startPosition_)
Sets the start position of the object.
- glm::vec3 [GetStartPosition](#) () const
Returns the saved start position of the object.
- glm::vec3 & [GetStartPositionRef](#) ()
Returns a reference to the start position of the object.
- void [Read](#) ([File_Reader](#) &reader)
Reads data for [Transform](#) object from file.
- void [Write](#) ([File_Writer](#) &writer)
Gives transform data to writer object.

Static Public Member Functions

- static [CType](#) [GetCType](#) ()
Gets the CType of [Transform](#) (used in [Object::GetComponent<>\(\)](#))

Private Attributes

- glm::vec3 [position](#)
Position of object.
- glm::vec3 [oldPosition](#)
Previous position of object.
- glm::vec3 [scale](#)
Scale of object.
- glm::vec3 [rotation](#)
Rotation of object.
- glm::vec3 [startPosition](#)
Starting position of the object.

Additional Inherited Members**4.20.1 Detailed Description**

[Transform](#) class

Definition at line 25 of file transform.hpp.

4.20.2 Constructor & Destructor Documentation**4.20.2.1 Transform() [1/3]** `Transform::Transform ()`

Creates [Transform](#) object with default values.

Definition at line 19 of file transform.cpp.

```
19         : Component(CType::CTransform),
20     position(glm::vec3(0.f, 0.f, 0.f)), scale(glm::vec3(1.f, 1.f, 1.f)), rotation(glm::vec3(0.f, 0.f, 0.f))
    {}
```

Referenced by `Clone()`.

4.20.2.2 Transform() [2/3] `Transform::Transform (const Transform & other)`

Copy constructor.

Parameters

<i>other</i>	
--------------	--

Definition at line 27 of file transform.cpp.

```
27                                     : Component(CType::CTransform) {
28     *this = other;
29 }
```

4.20.2.3 [Transform\(\)](#) [3/3] `Transform::Transform (File_Reader & reader)`

Creates [Transform](#) object using file.

Parameters

<code>reader</code>	File to use for making Transform object
---------------------	---

Definition at line 36 of file transform.cpp.

```
36                                     : Component(CType::CTransform),
37     position(glm::vec3(0.f, 0.f, 0.f)), scale(glm::vec3(1.f, 1.f, 1.f)), rotation(glm::vec3(0.f, 0.f, 0.f)) {
38     Read(reader);
39 }
```

References [Read\(\)](#).

4.20.3 Member Function Documentation

4.20.3.1 [Clone\(\)](#) `Transform * Transform::Clone () const`

Clones current [Transform](#) object.

Returns

`Transform*` Cloned [Transform](#)

Definition at line 46 of file transform.cpp.

```
46     {
47     return new Transform(*this);
48 }
```

References [Transform\(\)](#).

4.20.3.2 GetCType() `CType Transform::GetCType () [static]`

Gets the CType of [Transform](#) (used in [Object::GetComponent<>\(\)](#))

Returns

CType

Definition at line 171 of file transform.cpp.

```
171 {  
172     return CType::CTransform;  
173 }
```

4.20.3.3 GetOldPosition() `glm::vec3 Transform::GetOldPosition () const`

Returns old position of object.

Returns

glm::vec3

Definition at line 83 of file transform.cpp.

```
83 { return oldPosition; }
```

References oldPosition.

4.20.3.4 GetPosition() `glm::vec3 Transform::GetPosition () const`

Returns position of object.

Returns

glm::vec3

Definition at line 62 of file transform.cpp.

```
62 { return position; }
```

References position.

Referenced by [Model_Data::Draw\(\)](#), [Physics::Update\(\)](#), and [Physics::UpdateGravity\(\)](#).

4.20.3.5 GetPositionRef() `glm::vec3 & Transform::GetPositionRef ()`

Returns position reference of object.

Returns

`glm::vec3&`

Definition at line 69 of file transform.cpp.

```
69 { return position; }
```

References position.

Referenced by Behavior::ClassSetup(), and Editor::Display_Transform().

4.20.3.6 GetRotation() `glm::vec3 Transform::GetRotation () const`

Returns rotation of object.

Returns

`float`

Definition at line 118 of file transform.cpp.

```
118 { return rotation; }
```

References rotation.

Referenced by Model_Data::Draw(), and Physics::Update().

4.20.3.7 GetRotationRef() `glm::vec3 & Transform::GetRotationRef ()`

Returns rotation reference of object.

Returns

`glm::vec3&`

Definition at line 125 of file transform.cpp.

```
125 { return rotation; }
```

References rotation.

Referenced by Behavior::ClassSetup(), and Editor::Display_Transform().

4.20.3.8 GetScale() `glm::vec3 Transform::GetScale () const`

Returns scale of object.

Returns

`glm::vec3`

Definition at line 97 of file transform.cpp.

```
97 { return scale; }
```

References scale.

Referenced by `Model_Data::Draw()`, and `File_Writer::Write_Object_Data()`.

4.20.3.9 GetScaleRef() `glm::vec3 & Transform::GetScaleRef ()`

Returns scale reference of object.

Returns

`glm::vec3&`

Definition at line 104 of file transform.cpp.

```
104 { return scale; }
```

References scale.

Referenced by `Behavior::ClassSetup()`, and `Editor::Display_Transform()`.

4.20.3.10 GetStartPosition() `glm::vec3 Transform::GetStartPosition () const`

Returns the saved start position of the object.

Returns

`glm::vec3`

Definition at line 139 of file transform.cpp.

```
139 { return startPosition; }
```

References startPosition.

Referenced by `File_Writer::Write_Object_Data()`.

4.20.3.11 GetStartPositionRef() `glm::vec3 & Transform::GetStartPositionRef ()`

Returns a reference to the start position of the object.

Returns

`glm::vec3&`

Definition at line 146 of file transform.cpp.

```
146 { return startPosition; }
```

References startPosition.

Referenced by Behavior::ClassSetup(), and Editor::Display_Transform().

4.20.3.12 Read() `void Transform::Read (
File_Reader & reader)`

Reads data for [Transform](#) object from file.

Parameters

<i>reader</i>	File to read from
---------------	-------------------

Definition at line 153 of file transform.cpp.

```
153 {  
154     //SetRotation(reader.Read_Float("rotation"));  
155 }
```

Referenced by Object::ReRead(), and Transform().

4.20.3.13 SetOldPosition() `void Transform::SetOldPosition (
glm::vec3 oldPos)`

Sets old position of object.

Parameters

<i>oldPos</i>	
---------------	--

Definition at line 76 of file transform.cpp.

```
76 { oldPosition = oldPos; }
```

References oldPosition.

Referenced by Physics::Update().

4.20.3.14 SetPosition() `void Transform::SetPosition (glm::vec3 pos)`

Sets position of object.

Parameters

<i>pos</i>	
------------	--

Definition at line 55 of file transform.cpp.

```
55 { position = pos; }
```

References position.

Referenced by Behavior::ClassSetup(), Object_Manager::ReadList(), and Physics::Update().

4.20.3.15 SetRotation() `void Transform::SetRotation (glm::vec3 rot)`

Sets rotation of object.

Parameters

<i>rot</i>	
------------	--

Definition at line 111 of file transform.cpp.

```
111 { rotation = rot; }
```

References rotation.

Referenced by Behavior::ClassSetup(), and Physics::Update().

4.20.3.16 SetScale() `void Transform::SetScale (glm::vec3 sca)`

Sets scale of object.

Parameters

<i>sca</i>	
------------	--

Definition at line 90 of file transform.cpp.

```
90 { scale = sca; }
```

References scale.

Referenced by Behavior::ClassSetup(), and Object_Manager::ReadList().

4.20.3.17 SetStartPosition() `void Transform::SetStartPosition (glm::vec3 startPosition_)`

Sets the start position of the object.

Parameters

<i>start</i> ↔ <i>Position_</i>	
------------------------------------	--

Definition at line 132 of file transform.cpp.

```
132 { startPosition = startPosition_; }
```

References startPosition.

Referenced by Behavior::ClassSetup(), Editor::Display_Scene(), and Object_Manager::ReadList().

4.20.3.18 Write() `void Transform::Write (File_Writer & writer)`

Gives transform data to writer object.

Parameters

<i>writer</i>	
---------------	--

Definition at line 162 of file transform.cpp.

```
162 {  
163     writer.Write_Vec3("rotation", rotation);  
164 }
```

References rotation, and File_Writer::Write_Vec3().

Referenced by Object::Write().

The documentation for this class was generated from the following files:

- [transform.hpp](#)
- [transform.cpp](#)

4.21 Vector3_Func Class Reference

```
#include <vector3_func.hpp>
```

Static Public Member Functions

- static glm::vec3 [normalize](#) (const glm::vec3 vec)
Wrapper for the glm normalize function.
- static float [distance](#) (const glm::vec3 vec1, const glm::vec3 vec2)
Wrapper for the glm distance function.
- static glm::vec3 [get_direction](#) (const glm::vec3 vec1, const glm::vec3 vec2)
Wrapper for subtracting two glm vectors to make a new vector.
- static glm::vec3 [zero_vec3](#) ()
Creates a glm::vec3 filled with zeroes.
- static float [length](#) (const glm::vec3 vec3)
Wrapper for the glm length function.
- static glm::vec3 [add_float](#) (const glm::vec3 vec, float num)
Adds float to each part of a glm::vec3.
- static glm::vec3 [add_vec3](#) (const glm::vec3 vec1, const glm::vec3 vec2)
Add two glm::vec3 together.

4.21.1 Detailed Description

[Vector3_Func](#) class

Definition at line 21 of file vector3_func.hpp.

4.21.2 Member Function Documentation

4.21.2.1 add_float() glm::vec3 Vector3_Func::add_float (const glm::vec3 vec, float num) [static]

Adds float to each part of a glm::vec3.

Parameters

<i>vec</i>	
<i>num</i>	

Returns

glm::vec3

Definition at line 73 of file vector3_func.cpp.

```

73
74     glm::vec3 returnVec3;
    {
```



```
75
76     returnVec3.x = vec.x + num;
77     returnVec3.y = vec.y + num;
78     returnVec3.z = vec.z + num;
79
80     return vec;
81 }
```

Referenced by Behavior::ClassSetup().

4.21.2.2 add_vec3() glm::vec3 Vector3_Func::add_vec3 (
const glm::vec3 vec1,
const glm::vec3 vec2) [static]

Add two glm::vec3 together.

Parameters

<i>vec1</i>	
<i>vec2</i>	

Returns

glm::vec3

Definition at line 90 of file vector3_func.cpp.

```
90
91     glm::vec3 returnVec3;
92
93     returnVec3.x = vec1.x + vec2.x;
94     returnVec3.y = vec1.y + vec2.y;
95     returnVec3.z = vec1.z + vec2.z;
96
97     return vec1;
98 }
```

Referenced by Behavior::ClassSetup().

4.21.2.3 distance() float Vector3_Func::distance (
const glm::vec3 vec1,
const glm::vec3 vec2) [static]

Wrapper for the glm distance function.

Parameters

<i>vec1</i>	First input vec3
<i>vec2</i>	Second input vec3

Returns

float

Definition at line 32 of file vector3_func.cpp.

```
32                                     {  
33     return glm::distance(vec1, vec2);  
34 }
```

Referenced by Behavior::ClassSetup().

4.21.2.4 get_direction() glm::vec3 Vector3_Func::get_direction (
const glm::vec3 vec1,
const glm::vec3 vec2) [static]

Wrapper for subtracting two glm vectors to make a new vector.

Parameters

<i>vec1</i>	First input vec3
<i>vec2</i>	Second input vec3

Returns

glm::vec3

Definition at line 43 of file vector3_func.cpp.

```
43                                     {  
44     return vec1 - vec2;  
45 }
```

Referenced by Behavior::ClassSetup().

4.21.2.5 length() float Vector3_Func::length (
const glm::vec3 vec) [static]

Wrapper for the glm length function.

Parameters

<i>vec</i>	Input vec3
------------	------------

Returns

float

Definition at line 62 of file vector3_func.cpp.

```
62                                     {  
63     return glm::length(vec);  
64 }
```

Referenced by Behavior::ClassSetup().

4.21.2.6 normalize() glm::vec3 Vector3_Func::normalize (
const glm::vec3 vec) [static]

Wrapper for the glm normalize function.

Parameters

vec	Input vec3
-----	------------

Returns

glm::vec3

Definition at line 21 of file vector3_func.cpp.

```
21                                     {  
22     return glm::normalize(vec);  
23 }
```

Referenced by Behavior::ClassSetup().

4.21.2.7 zero_vec3() glm::vec3 Vector3_Func::zero_vec3 () [static]

Creates a glm::vec3 filled with zeroes.

Returns

glm::vec3

Definition at line 52 of file vector3_func.cpp.

```
52                                     {  
53     return glm::vec3(0.f, 0.f, 0.f);  
54 }
```

Referenced by Behavior::ClassSetup().

The documentation for this class was generated from the following files:

- [vector3_func.hpp](#)
- [vector3_func.cpp](#)

5 File Documentation

5.1 behavior.cpp File Reference

```
#include <glm.hpp>
#include "behavior.hpp"
#include "engine.hpp"
#include "object.hpp"
#include "object_manager.hpp"
#include "physics.hpp"
#include "random.hpp"
#include "transform.hpp"
#include "vector3_func.hpp"
```

5.1.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-22

Copyright

Copyright (c) 2021

5.2 behavior.hpp File Reference

```
#include <vector>
#include <vec3.hpp>
#include <lua.hpp>
#include <sol/sol.hpp>
#include "component.hpp"
#include "file_reader.hpp"
#include "file_writer.hpp"
```

Classes

- class [Behavior](#)

5.2.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-22

Copyright

Copyright (c) 2021

5.3 camera.cpp File Reference

```
#include <glfw3.h>
#include <glm.hpp>
#include "editor.hpp"
#include "engine.hpp"
#include "graphics.hpp"
#include "camera.hpp"
#include "trace.hpp"
```

Variables

- static [Camera](#) * [camera](#) = nullptr
[Camera](#) object.

5.3.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.4 camera.hpp File Reference

```
#include <utility>
#include <vec3.hpp>
#include "file_reader.hpp"
```

Classes

- class [Camera](#)

5.4.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.5 component.cpp File Reference

```
#include "component.hpp"
```

5.5.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.6 component.hpp File Reference

Classes

- class [Component](#)

Typedefs

- typedef [Component::CType](#) CType
Typedef for CType (used in other files)

5.6.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.7 editor.cpp File Reference

```
#include <imgui.h>
#include "imgui_impl_glfw.h"
#include "imgui_impl_opengl3.h"
#include "imgui_internal.h"
#include "ImGuiFileDialog.h"
#include <vec3.hpp>
#include "camera.hpp"
#include "editor.hpp"
#include "engine.hpp"
#include "graphics.hpp"
#include "object_manager.hpp"
```

Variables

- static `Editor * editor` = nullptr
Editor object.

5.7.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-14

Copyright

Copyright (c) 2021

5.8 editor.hpp File Reference

```
#include "behavior.hpp"
#include "object.hpp"
#include "model.hpp"
#include "physics.hpp"
#include "trace.hpp"
#include "transform.hpp"
```

Classes

- class `Editor`

5.8.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-14

Copyright

Copyright (c) 2021

5.9 engine.cpp File Reference

```
#include <cmath>
#include <string>
#include "engine.hpp"
#include "graphics.hpp"
#include "object_manager.hpp"
#include "object.hpp"
#include "component.hpp"
#include "model_data_manager.hpp"
#include "physics.hpp"
#include "camera.hpp"
#include "editor.hpp"
#include "file_reader.hpp"
#include "random.hpp"
#include "texture_manager.hpp"
```

Variables

- static `Engine * engine` = nullptr
Engine object.

5.9.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-04

Copyright

Copyright (c) 2021

5.10 engine.hpp File Reference

```
#include <chrono>
#include <string>
#include <vec3.hpp>
```

Classes

- class [Engine](#)

5.10.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-04

Copyright

Copyright (c) 2021

5.11 file_reader.cpp File Reference

```
#include <fstream>
#include <iostream>
#include <filereadstream.h>
#include "file_reader.hpp"
#include "trace.hpp"
```

5.11.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-04

Copyright

Copyright (c) 2021

5.12 file_reader.hpp File Reference

```
#include <string>
#include <document.h>
#include <vec3.hpp>
```

Classes

- class [File_Reader](#)

5.12.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-04

Copyright

Copyright (c) 2021

5.13 file_writer.cpp File Reference

```
#include <fstream>
#include <iostream>
#include "file_writer.hpp"
#include "trace.hpp"
#include "transform.hpp"
```

5.13.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-27

Copyright

Copyright (c) 2021

5.14 file_writer.hpp File Reference

```
#include <string>
#include <vector>
#include <document.h>
#include <filewritestream.h>
#include <prettywriter.h>
#include <vec3.hpp>
#include "object.hpp"
```

Classes

- class [File_Writer](#)

5.14.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-27

Copyright

Copyright (c) 2021

5.15 graphics.cpp File Reference

```
#include <string>
#include <vector>
#include <cmath>
#include <glew.h>
#include <vec3.hpp>
#include <vec2.hpp>
#include <mat4x4.hpp>
#include <glm.hpp>
#include <gtc/matrix_transform.hpp>
#include <gtx/transform.hpp>
#include "engine.hpp"
#include "graphics.hpp"
#include "object_manager.hpp"
#include "model.hpp"
#include "transform.hpp"
#include "camera.hpp"
#include "editor.hpp"
#include "trace.hpp"
#include "shader.hpp"
```

Variables

- static [Graphics](#) * [graphics](#) = nullptr
[Graphics](#) object.

5.15.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.16 [graphics.hpp](#) File Reference

```
#include <utility>
#include <GL/gl.h>
#include <glfw3.h>
#include "file_reader.hpp"
```

Classes

- class [Graphics](#)

5.16.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.17 main.cpp File Reference

```
#include "trace.hpp"
#include "engine.hpp"
#include "graphics.hpp"
```

Functions

- `int main (int, char *[])`
Main function.

5.17.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-05-06

Copyright

Copyright (c) 2021

5.17.2 Function Documentation

5.17.2.1 main() `int main (`
 `int ,`
 `char * [])`

Main function.

Returns

`int`

Definition at line 22 of file main.cpp.

```
22     {
23         // Initializing systems
24         Trace::Initialize();
25         if (!Engine::Initialize()) return -1;
26         // Engine update loop
27         Graphics::Update();
28
29         // Shutting down systems
30         Engine::Shutdown();
31         Trace::Shutdown();
32
33         return 0;
34 }
```

References `Trace::Initialize()`, `Engine::Initialize()`, `Trace::Shutdown()`, `Engine::Shutdown()`, and `Graphics::Update()`.

5.18 model.cpp File Reference

```
#include <cstdio>
#include "object.hpp"
#include "model.hpp"
#include "model_data_manager.hpp"
#include "transform.hpp"
#include "texture.hpp"
#include "texture_manager.hpp"
#include "trace.hpp"
```

5.18.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-06

Copyright

Copyright (c) 2021

5.19 model.hpp File Reference

```
#include <vector>
#include <array>
#include <string>
#include <GL/gl.h>
#include "component.hpp"
#include "file_reader.hpp"
#include "file_writer.hpp"
#include "model_data.hpp"
#include "texture.hpp"
```

Classes

- class [Model](#)

5.19.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-06

Copyright

Copyright (c) 2021

5.20 model_data.cpp File Reference

```
#include <cstdio>
#include <cstring>
#include <glew.h>
#include <glm.hpp>
#include <gtc/matrix_transform.hpp>
#include <gtx/transform.hpp>
#include "engine.hpp"
#include "model.hpp"
#include "model_data.hpp"
#include "trace.hpp"
#include "shader.hpp"
```

5.20.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-06

Copyright

Copyright (c) 2021

5.21 model_data.hpp File Reference

```
#include <vector>
#include <array>
#include <string>
#include <vec3.hpp>
#include <vec2.hpp>
#include <mat4x4.hpp>
#include <GL/gl.h>
#include "transform.hpp"
```

Classes

- class [Model_Data](#)

5.21.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-06

Copyright

Copyright (c) 2021

5.22 model_data_manager.cpp File Reference

```
#include "model_data_manager.hpp"
#include "trace.hpp"
```

Variables

- static [Model_Data_Manager](#) * [model_data_manager](#) = nullptr
Model_Data_Manager object.

5.22.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-06

Copyright

Copyright (c) 2021

5.23 model_data_manager.hpp File Reference

```
#include <vector>
#include <string>
#include "model_data.hpp"
#include "file_reader.hpp"
```

Classes

- class [Model_Data_Manager](#)

5.23.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-06

Copyright

Copyright (c) 2021

5.24 object.cpp File Reference

```
#include "object.hpp"
#include "behavior.hpp"
#include "model.hpp"
#include "object_manager.hpp"
#include "physics.hpp"
#include "transform.hpp"
#include "file_reader.hpp"
```

5.24.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.25 object.hpp File Reference

```
#include <unordered_map>
#include <string>
#include "component.hpp"
#include "trace.hpp"
```

Classes

- class [Object](#)

5.25.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.26 object_manager.cpp File Reference

```
#include <string>
#include "behavior.hpp"
#include "object_manager.hpp"
#include "trace.hpp"
#include "transform.hpp"
```

Variables

- static [Object_Manager](#) * [object_manager](#) = nullptr
[Object_Manager](#) object.

5.26.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.27 object_manager.hpp File Reference

```
#include <vector>
#include "object.hpp"
#include "file_reader.hpp"
#include "file_writer.hpp"
```

Classes

- class [Object_Manager](#)

5.27.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.28 physics.cpp File Reference

```
#include <cmath>
#include <glm.hpp>
#include "engine.hpp"
#include "object_manager.hpp"
#include "object.hpp"
#include "physics.hpp"
#include "transform.hpp"
```

5.28.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.29 physics.hpp File Reference

```
#include <vec3.hpp>
#include "component.hpp"
#include "file_reader.hpp"
#include "file_writer.hpp"
```

Classes

- class [Physics](#)

5.29.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.30 random.cpp File Reference

```
#include "random.hpp"  
#include "trace.hpp"
```

Variables

- static [Random](#) * [random](#) = nullptr
[Random](#) object.

5.30.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-13

Copyright

Copyright (c) 2021

5.31 random.hpp File Reference

```
#include <random>  
#include <vec3.hpp>
```

Classes

- class [Random](#)

5.31.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-13

Copyright

Copyright (c) 2021

5.32 shader.cpp File Reference

```
#include <fstream>
#include <glew.h>
#include "shader.hpp"
#include "trace.hpp"
```

Variables

- static [Shader](#) * [shader](#) = nullptr
[Shader](#) object.

5.32.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-19

Copyright

Copyright (c) 2021

5.33 shader.hpp File Reference

```
#include <string>
#include <GL/gl.h>
#include "file_reader.hpp"
```

Classes

- class [Shader](#)

5.33.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-19

Copyright

Copyright (c) 2021

5.34 texture.cpp File Reference

```
#include <glew.h>
#include "shader.hpp"
#include "texture.hpp"
#include "trace.hpp"
```

Macros

- #define [FOURCC_DXT1](#) 0x31545844
Equivalent to "DXT1" in ASCII.
- #define [FOURCC_DXT3](#) 0x33545844
Equivalent to "DXT3" in ASCII.
- #define [FOURCC_DXT5](#) 0x35545844
Equivalent to "DXT5" in ASCII.

5.34.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-14

Copyright

Copyright (c) 2021

5.35 texture.hpp File Reference

```
#include <string>
#include <GL/gl.h>
```

Classes

- class [Texture](#)

5.35.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-14

Copyright

Copyright (c) 2021

5.36 texture_manager.cpp File Reference

```
#include "texture_manager.hpp"
#include "trace.hpp"
```

Variables

- static [Texture_Manager](#) * `texture_manager` = nullptr
Texture_Manager object.

5.36.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-14

Copyright

Copyright (c) 2021

5.37 texture_manager.hpp File Reference

```
#include <string>
#include <vector>
#include "file_reader.hpp"
#include "texture.hpp"
```

Classes

- class [Texture_Manager](#)

5.37.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-14

Copyright

Copyright (c) 2021

5.38 trace.cpp File Reference

```
#include <iostream>
#include <cstdint>
#include "trace.hpp"
```

Variables

- static [Trace](#) * [trace](#) = nullptr
Trace object.

5.38.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.39 trace.hpp File Reference

```
#include <string>
#include <fstream>
```

Classes

- class [Trace](#)

5.39.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.40 transform.cpp File Reference

```
#include "transform.hpp"
```

5.40.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.41 transform.hpp File Reference

```
#include <vec3.hpp>
#include "component.hpp"
#include "file_reader.hpp"
#include "file_writer.hpp"
```

Classes

- class [Transform](#)

5.41.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-06-05

Copyright

Copyright (c) 2021

5.42 vector3_func.cpp File Reference

```
#include "vector3_func.hpp"
```

5.42.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-26

Copyright

Copyright (c) 2021

5.43 vector3_func.hpp File Reference

```
#include <glm.hpp>
#include <vec3.hpp>
```

Classes

- class [Vector3_Func](#)

5.43.1 Detailed Description

Author

Kelson Wysocki (kelson.wysocki@gmail.com)

Version

0.1

Date

2021-07-26

Copyright

Copyright (c) 2021

Index

- ~Behavior
 - Behavior, [7](#)
- ~Model_Data
 - Model_Data, [79](#)
- ~Texture
 - Texture, [128](#)
- add_float
 - Vector3_Func, [147](#)
- add_vec3
 - Vector3_Func, [148](#)
- AddComponent
 - Object, [90](#)
- AddForce
 - Physics, [109](#)
- AddObject
 - Object_Manager, [99](#)
- AddScript
 - Behavior, [7](#)
- ApplyForce
 - Physics, [109](#)
- Behavior, [4](#)
 - ~Behavior, [7](#)
 - AddScript, [7](#)
 - Behavior, [6](#)
 - CheckIfCopy, [8](#)
 - ClassSetup, [8](#)
 - Clear, [10](#)
 - Clone, [10](#)
 - GetCType, [10](#)
 - GetScripts, [10](#)
 - Read, [11](#)
 - SetupClassesForLua, [11](#)
 - SwitchScript, [12](#)
 - Update, [12](#)
 - Write, [13](#)
- behavior.cpp, [151](#)
- behavior.hpp, [151](#)
- Camera, [13](#)
 - Camera, [15](#)
 - GetFar, [16](#)
 - GetFov, [16](#)
 - GetFront, [16](#)
 - GetNear, [17](#)
 - GetOriginalMoveSpeed, [17](#)
 - GetOriginalSensitivity, [17](#)
 - GetOriginalSprintSpeed, [18](#)
 - GetPitch, [18](#)
 - GetPosition, [18](#)
 - GetUp, [19](#)
 - GetYaw, [19](#)
 - Initialize, [19](#), [20](#)
 - MouseUpdate, [21](#)
 - Shutdown, [22](#)
 - Update, [22](#)
- camera.cpp, [152](#)
- camera.hpp, [153](#)
- CheckIfCopy
 - Behavior, [8](#)
- CheckName
 - Object_Manager, [100](#)
- ClassSetup
 - Behavior, [8](#)
- Clear
 - Behavior, [10](#)
 - Object, [90](#)
- Clone
 - Behavior, [10](#)
 - Model, [73](#)
 - Object, [90](#)
 - Physics, [110](#)
 - Transform, [140](#)
- Component, [23](#)
 - Component, [25](#)
 - CType, [24](#)
 - GetCType, [25](#)
 - GetParent, [25](#)
 - SetParent, [25](#)
- component.cpp, [153](#)
- component.hpp, [154](#)
- CType
 - Component, [24](#)
- Display
 - Texture, [129](#)
- Display_Camera_Settings
 - Editor, [28](#)
- Display_Components
 - Editor, [28](#)
- Display_Dockspace
 - Editor, [30](#)
- Display_Menu_Bar
 - Editor, [30](#)
- Display_Model
 - Editor, [31](#)
- Display_Physics
 - Editor, [32](#)
- Display_Scene
 - Editor, [33](#)
- Display_Scripts
 - Editor, [34](#)

- Display_Transform
 - Editor, [36](#)
- Display_World_Settings
 - Editor, [37](#)
- distance
 - Vector3_Func, [148](#)
- Draw
 - Model, [73](#)
 - Model_Data, [79](#)
- Editor, [26](#)
 - Display_Camera_Settings, [28](#)
 - Display_Components, [28](#)
 - Display_Dockspace, [30](#)
 - Display_Menu_Bar, [30](#)
 - Display_Model, [31](#)
 - Display_Physics, [32](#)
 - Display_Scene, [33](#)
 - Display_Scripts, [34](#)
 - Display_Transform, [36](#)
 - Display_World_Settings, [37](#)
 - GetTakeKeyboardInput, [37](#)
 - Initialize, [38](#)
 - Make_Display_String, [38](#)
 - Render, [40](#)
 - Reset, [40](#)
 - Shutdown, [40](#)
 - Update, [41](#)
- editor.cpp, [154](#)
- editor.hpp, [155](#)
- Engine, [42](#)
 - GetDeltaTime, [43](#)
 - GetDt, [43](#)
 - GetGravConst, [44](#)
 - GetLightPos, [44](#)
 - GetLightPower, [44](#)
 - GetPresetName, [45](#)
 - Initialize, [45](#)
 - Restart, [47](#)
 - SetPresetName, [48](#)
 - Shutdown, [48](#)
 - Update, [49](#)
 - Write, [49](#)
- engine.cpp, [156](#)
- engine.hpp, [156](#)
- ErrorCallback
 - Graphics, [64](#)
- ErrorCheck
 - Graphics, [65](#)
- File_Reader, [50](#)
 - Read_Behavior_Name, [51](#)
 - Read_Bool, [51](#)
 - Read_Double, [52](#)
 - Read_File, [52](#)
 - Read_Float, [53](#)
 - Read_Int, [53](#)
 - Read_Object_Name, [55](#)
 - Read_Object_Position, [55](#)
 - Read_Object_Scale, [56](#)
 - Read_Object_Template_Name, [56](#)
 - Read_String, [57](#)
 - Read_Vec3, [57](#)
- file_reader.cpp, [157](#)
- file_reader.hpp, [158](#)
- File_Writer, [58](#)
 - File_Writer, [59](#)
 - Write_Behavior_Name, [59](#)
 - Write_File, [60](#)
 - Write_Object_Data, [60](#)
 - Write_String, [61](#)
 - Write_Value, [61](#)
 - Write_Vec3, [62](#)
- file_writer.cpp, [158](#)
- file_writer.hpp, [159](#)
- FindObject
 - Object_Manager, [100](#), [101](#)
- Get
 - Model_Data_Manager, [85](#)
 - Texture_Manager, [132](#), [133](#)
- get_direction
 - Vector3_Func, [149](#)
- GetAcceleration
 - Physics, [110](#)
- GetAccelerationRef
 - Physics, [110](#)
- GetComponent
 - Object, [91](#)
- GetComponentConst
 - Object, [91](#)
- GetComponentList
 - Object, [92](#)
- GetCType
 - Behavior, [10](#)
 - Component, [25](#)
 - Model, [74](#)
 - Physics, [111](#)
 - Transform, [140](#)
- GetDeltaTime
 - Engine, [43](#)
- GetDt
 - Engine, [43](#)
- GetFar
 - Camera, [16](#)
- GetForces
 - Physics, [111](#)
- GetForcesRef
 - Physics, [111](#)

GetFov
 Camera, [16](#)
GetFront
 Camera, [16](#)
GetGravConst
 Engine, [44](#)
GetId
 Object, [92](#)
GetLightId
 Shader, [122](#)
GetLightPos
 Engine, [44](#)
GetLightPower
 Engine, [44](#)
GetLightPowerId
 Shader, [122](#)
GetMass
 Physics, [112](#)
GetMassRef
 Physics, [112](#)
GetMatrixId
 Shader, [122](#)
GetModelMatrixId
 Shader, [123](#)
GetModelName
 Model, [74](#)
 Model_Data, [81](#)
GetName
 Object, [93](#)
GetNameRef
 Object, [93](#)
GetNear
 Camera, [17](#)
GetOldPosition
 Transform, [141](#)
GetOriginalMoveSpeed
 Camera, [17](#)
GetOriginalSensitivity
 Camera, [17](#)
GetOriginalSprintSpeed
 Camera, [18](#)
GetParent
 Component, [25](#)
GetPitch
 Camera, [18](#)
GetPosition
 Camera, [18](#)
 Transform, [141](#)
GetPositionRef
 Transform, [141](#)
GetPresetName
 Engine, [45](#)
GetProgram
 Shader, [123](#)
GetRotation
 Transform, [142](#)
GetRotationalVelocity
 Physics, [112](#)
GetRotationalVelocityRef
 Physics, [113](#)
GetRotationRef
 Transform, [142](#)
GetScale
 Transform, [142](#)
GetScaleRef
 Transform, [143](#)
GetScripts
 Behavior, [10](#)
GetSize
 Object_Manager, [101](#)
GetStartPosition
 Transform, [143](#)
GetStartPositionRef
 Transform, [143](#)
GetTakeKeyboardInput
 Editor, [37](#)
GetTemplateName
 Object, [93](#)
GetTexture
 Model, [74](#)
GetTextureName
 Model, [75](#)
 Texture, [129](#)
GetTextureNum
 Texture, [129](#)
GetUp
 Camera, [19](#)
GetVelocity
 Physics, [113](#)
GetVelocityRef
 Physics, [113](#)
GetViewMatrixId
 Shader, [123](#)
GetWindow
 Graphics, [65](#)
GetWindowSize
 Graphics, [65](#)
GetYaw
 Camera, [19](#)
Graphics, [63](#)
 ErrorCallback, [64](#)
 ErrorCheck, [65](#)
 GetWindow, [65](#)
 GetWindowSize, [65](#)
 Graphics, [64](#)
 Initialize, [66](#), [67](#)
 InitializeGL, [68](#)
 Render, [68](#)

- Shutdown, 69
- Update, 69
- graphics.cpp, 159
- graphics.hpp, 160
- Initialize
 - Camera, 19, 20
 - Editor, 38
 - Engine, 45
 - Graphics, 66, 67
 - Model_Data_Manager, 86
 - Object_Manager, 102
 - Random, 118
 - Shader, 124
 - Texture_Manager, 134
 - Trace, 136
- InitializeGL
 - Graphics, 68
- length
 - Vector3_Func, 149
- Load
 - Model, 75
 - Model_Data, 81, 82
 - Texture, 129
- LoadDDS
 - Texture, 130
- LoadShader
 - Shader, 125
- main
 - main.cpp, 161
- main.cpp, 161
 - main, 161
- Make_Display_String
 - Editor, 38
- Message
 - Trace, 136
- Model, 70
 - Clone, 73
 - Draw, 73
 - GetType, 74
 - GetModelName, 74
 - GetTexture, 74
 - GetTextureName, 75
 - Load, 75
 - Model, 72
 - Read, 76
 - SwitchModel, 76
 - SwitchTexture, 76
 - Write, 77
- model.cpp, 162
- model.hpp, 162
- Model_Data, 77
 - ~Model_Data, 79
- Draw, 79
- GetModelName, 81
- Load, 81, 82
- Model_Data, 78, 79
- Read, 82
- model_data.cpp, 163
- model_data.hpp, 164
- Model_Data_Manager, 84
 - Get, 85
 - Initialize, 86
 - Shutdown, 86
- model_data_manager.cpp, 164
- model_data_manager.hpp, 165
- MouseUpdate
 - Camera, 21
- normalize
 - Vector3_Func, 150
- Object, 87
 - AddComponent, 90
 - Clear, 90
 - Clone, 90
 - GetComponent, 91
 - GetComponentConst, 91
 - GetComponentList, 92
 - GetId, 92
 - GetName, 93
 - GetNameRef, 93
 - GetTemplateName, 93
 - Object, 89
 - Read, 94
 - RemoveComponent, 94
 - ReRead, 95
 - SetId, 96
 - SetName, 96
 - SetTemplateName, 97
 - Update, 97
 - Write, 97
- object.cpp, 166
- object.hpp, 166
- Object_Manager, 98
 - AddObject, 99
 - CheckName, 100
 - FindObject, 100, 101
 - GetSize, 101
 - Initialize, 102
 - ReadList, 103
 - RemoveObject, 104
 - Shutdown, 104
 - Update, 105
 - Write, 105
- object_manager.cpp, 167
- object_manager.hpp, 168

- Physics, [106](#)
 - AddForce, [109](#)
 - ApplyForce, [109](#)
 - Clone, [110](#)
 - GetAcceleration, [110](#)
 - GetAccelerationRef, [110](#)
 - GetCType, [111](#)
 - GetForces, [111](#)
 - GetForcesRef, [111](#)
 - GetMass, [112](#)
 - GetMassRef, [112](#)
 - GetRotationalVelocity, [112](#)
 - GetRotationalVelocityRef, [113](#)
 - GetVelocity, [113](#)
 - GetVelocityRef, [113](#)
 - Physics, [108](#), [109](#)
 - Read, [114](#)
 - SetAcceleration, [114](#)
 - SetForces, [115](#)
 - SetMass, [115](#)
 - SetRotationalVelocity, [115](#)
 - SetVelocity, [116](#)
 - Update, [116](#)
 - UpdateGravity, [117](#)
 - Write, [117](#)
- physics.cpp, [168](#)
- physics.hpp, [169](#)
- Random, [118](#)
 - Initialize, [118](#)
 - random_float, [119](#)
 - random_vec3, [119](#)
 - Shutdown, [120](#)
- random.cpp, [170](#)
- random.hpp, [170](#)
- random_float
 - Random, [119](#)
- random_vec3
 - Random, [119](#)
- Read
 - Behavior, [11](#)
 - Model, [76](#)
 - Model_Data, [82](#)
 - Object, [94](#)
 - Physics, [114](#)
 - Transform, [144](#)
- Read_Behavior_Name
 - File_Reader, [51](#)
- Read_Bool
 - File_Reader, [51](#)
- Read_Double
 - File_Reader, [52](#)
- Read_File
 - File_Reader, [52](#)
- Read_Float
 - File_Reader, [53](#)
- Read_Int
 - File_Reader, [53](#)
- Read_Object_Name
 - File_Reader, [55](#)
- Read_Object_Position
 - File_Reader, [55](#)
- Read_Object_Scale
 - File_Reader, [56](#)
- Read_Object_Template_Name
 - File_Reader, [56](#)
- Read_String
 - File_Reader, [57](#)
- Read_Vec3
 - File_Reader, [57](#)
- ReadFile
 - Shader, [126](#)
- ReadList
 - Object_Manager, [103](#)
- RemoveComponent
 - Object, [94](#)
- RemoveObject
 - Object_Manager, [104](#)
- Render
 - Editor, [40](#)
 - Graphics, [68](#)
- ReRead
 - Object, [95](#)
- Reset
 - Editor, [40](#)
- Restart
 - Engine, [47](#)
- SetAcceleration
 - Physics, [114](#)
- SetForces
 - Physics, [115](#)
- SetId
 - Object, [96](#)
- SetMass
 - Physics, [115](#)
- SetName
 - Object, [96](#)
- SetOldPosition
 - Transform, [144](#)
- SetParent
 - Component, [25](#)
- SetPosition
 - Transform, [144](#)
- SetPresetName
 - Engine, [48](#)
- SetRotation
 - Transform, [145](#)

- SetRotationalVelocity
 - Physics, 115
- SetScale
 - Transform, 145
- SetStartPosition
 - Transform, 146
- SetTemplateName
 - Object, 97
- SetupClassesForLua
 - Behavior, 11
- SetVelocity
 - Physics, 116
- Shader, 121
 - GetLightId, 122
 - GetLightPowerId, 122
 - GetMatrixId, 122
 - GetModelMatrixId, 123
 - GetProgram, 123
 - GetViewMatrixId, 123
 - Initialize, 124
 - LoadShader, 125
 - ReadFile, 126
 - Shutdown, 126
 - Update, 127
- shader.cpp, 171
- shader.hpp, 172
- Shutdown
 - Camera, 22
 - Editor, 40
 - Engine, 48
 - Graphics, 69
 - Model_Data_Manager, 86
 - Object_Manager, 104
 - Random, 120
 - Shader, 126
 - Texture_Manager, 134
 - Trace, 137
- SwitchModel
 - Model, 76
- SwitchScript
 - Behavior, 12
- SwitchTexture
 - Model, 76
- Texture, 127
 - ~Texture, 128
 - Display, 129
 - GetTextureName, 129
 - GetTextureNum, 129
 - Load, 129
 - LoadDDS, 130
- texture.cpp, 172
- texture.hpp, 173
- Texture_Manager, 132
 - Get, 132, 133
 - Initialize, 134
 - Shutdown, 134
- texture_manager.cpp, 174
- texture_manager.hpp, 174
- Trace, 135
 - Initialize, 136
 - Message, 136
 - Shutdown, 137
- trace.cpp, 175
- trace.hpp, 176
- Transform, 137
 - Clone, 140
 - GetCType, 140
 - GetOldPosition, 141
 - GetPosition, 141
 - GetPositionRef, 141
 - GetRotation, 142
 - GetRotationRef, 142
 - GetScale, 142
 - GetScaleRef, 143
 - GetStartPosition, 143
 - GetStartPositionRef, 143
 - Read, 144
 - SetOldPosition, 144
 - SetPosition, 144
 - SetRotation, 145
 - SetScale, 145
 - SetStartPosition, 146
 - Transform, 139, 140
 - Write, 146
- transform.cpp, 176
- transform.hpp, 177
- Update
 - Behavior, 12
 - Camera, 22
 - Editor, 41
 - Engine, 49
 - Graphics, 69
 - Object, 97
 - Object_Manager, 105
 - Physics, 116
 - Shader, 127
- UpdateGravity
 - Physics, 117
- Vector3_Func, 146
 - add_float, 147
 - add_vec3, 148
 - distance, 148
 - get_direction, 149
 - length, 149
 - normalize, 150
 - zero_vec3, 150

vector3_func.cpp, [177](#)

vector3_func.hpp, [178](#)

Write

Behavior, [13](#)

Engine, [49](#)

Model, [77](#)

Object, [97](#)

Object_Manager, [105](#)

Physics, [117](#)

Transform, [146](#)

Write_Behavior_Name

File_Writer, [59](#)

Write_File

File_Writer, [60](#)

Write_Object_Data

File_Writer, [60](#)

Write_String

File_Writer, [61](#)

Write_Value

File_Writer, [61](#)

Write_Vec3

File_Writer, [62](#)

zero_vec3

Vector3_Func, [150](#)