

Vulnerability Assessment Tool : Vulas

SAP Security Research

Serena Elisa Ponta

October 17th, 2018

PUBLIC

SAP Run Simple

Motivation

Motivation
Vulnerable OSS components

- 80% to 90% of software products on the market include OSS component
- Number of vulnerabilities disclosed for OSS libraries steadily increasing since 2009



("The State of Open Source Security", Snyk, 2017)

Motivation

Using components with known vulnerabilities:

- Included in **OWASP Top 10** (2013-2017): A9
- Root cause of 12 of the top 50 data breaches in 2016
  - Mossack Fonseca (***Panama Pa***
  - ***Equifax*** breach

Consequences can be:

- Financial
- Loss of customers' trust
- Loss of image/reputation

Just Update?

Perhaps during development, but **transitive** dependenci sidered and may be **unknown** or **not understood**



Unrealistic for **live** applications

Impact analysis is difficult

Vulnerability description (in natural language) often not useful

CVE-2012-5633: *"The URIMappingInterceptor in Apache CXF before 2.5.8, 2.6.x before 2.6.5, and 2.7.x before 2.7.2, when using the WSS4JInInterceptor, bypasses WS-Security processing, which allows remote attackers to obtain access to SOAP services via an HTTP GET request."*

Impact analysis is difficult

Vulnerabilities are assigned to entire projects (e.g., Apache POI, Tomcat), sub-components (e.g. Jar archives) are used separately



Existing approaches
based on meta-data

- Most tools “somehow” map finer-grained OSS components (e.g., JAR archives) to vulnerabilities using the project metadata
- **Actual code is ignored**

Limitations:

- False-positives (e.g., multi-module projects)
- False-negatives (e.g., re-bundling)
- Focus only on detection (no app-specific analysis)

Contributions

- From vulnerability to **vulnerable constructs** (actual code)
- Code-centric **detection** of known vulnerabilities
- Static and Dynamic **assessment** of vulnerable code
- Metrics to support selection of non-vulnerable libraries (**mitigation**)

Approach

Vulnerable Constructs



Vulnerability advisory

(CVE, GitHub issue)

Repository:
https://github.com/some/project

Commits: 236AF0619, 1234E4D5C1A, ….

Patch Information

Method x.y.z *ADDED*

Method a.b.c *MODIFIED*

Constructor i.j.k *DELETED*

……

Vulnerable Constructs

Vulnerable Constructs (CVE-2014-3574)



org.apache.poi.util.SAXHelper.getSAXReader()

Feedbac

Change	Entity Type	Changed Entity	New Entity
Insert			xmlReader.setValidation(false);
Insert			trySetSAXFeature(xmlReader, XMLConstants.FEATURE_SECURE_PR...
Insert			trySetXercesSecurityManager(xmlReader);

Vulnerable to Fixed

Vulnerable Collapse all Expand all

AST Code Representation
SAXReader xmlReader = new SAXReader();

xmlReader.setEntityResolver(new EntityResolver() {
public InputSource resolveEntity(String publicId, String systemId) throws
return new InputSource(new StringReader(""));
}
});

RETURN xmlReader;

Fixed Collapse all Expand all

AST Code Representation
SAXReader xmlReader = new SAXReader();
xmlReader.setValidation(false);

xmlReader.setEntityResolver(new EntityResolver() {
public InputSource resolveEntity(String publicId, String systemId) throws
return new InputSource(new StringReader(""));
}
});

trySetSAXFeature(xmlReader, XMLConstants.FEATURE_SECURE_PRO(
trySetXercesSecurityManager(xmlReader);
RETURN xmlReader;

Approach

Assumption: If an application contains and executes vulnerable constructs, then there is a significant risk that the vulnerability can be exploited in the application context



- Dynamic analysis
- Static reachability analysis
- Combination of static and dynamic analysis

Ponta, Plate, Sabetta,
"Beyond Metadata: Code-centric and Usage-based Analysis of Known Vulnerabilities in Open-source Software"
34th IEEE Int Conf on Software Maintenance and Evolution (ICSME), 2018

Demo

Vulnerability Overview



Ass…	Dependenc… (Direct / Trans…	Archive Filename (Digest)	Vulnerability (CVSS Score*)	Inclusion of vulnerable code	Static Analysi… execution of v…	Dynamic Anal… execution of v…
	SYSTEM direct	**cf1.2.2-cc1.4-xz1.0.jar** 7F7798C34114BF620EFA99DFF6770C458234FDBC	**CVE-2012-2098** 5.0 (v2.0)	!	🐾	🐾
	SYSTEM direct	**cf1.2.2-cc1.4-xz1.0.jar** 7F7798C34114BF620EFA99DFF6770C458234FDBC	**CVE-2013-2186** 7.5 (v2.0)	!	🐾	🐾
	SYSTEM direct	**cf1.2.2-cc1.4-xz1.0.jar** 7F7798C34114BF620EFA99DFF6770C458234FDBC	**CVE-2014-0050** 7.5 (v2.0)	!	🐾	🐾
	SYSTEM direct	**cf1.2.2-cc1.4-xz1.0.jar** 7F7798C34114BF620EFA99DFF6770C458234FDBC	**CVE-2016-3092-FU** 7.8 (v2.0)	!	🐾	🐾
📋	**COMPILE** direct	**commons-collections-3.2.1.jar** 761EA405B9B37CED573D2DF0D1E3A4E0F9EDC668	**COLLECTIONS-580** n/a	!		
	COMPILE direct	**commons-fileupload-1.2.1.jar** 384FAA82E193D4E4B0546059CA09572654BC3970	**CVE-2013-0248** 3.3 (v2.0)	!	🐾	
	COMPILE direct	**commons-fileupload-1.2.1.jar** 384FAA82E193D4E4B0546059CA09572654BC3970	**CVE-2013-2186** 7.5 (v2.0)	!	🐾	
	COMPILE direct	**commons-fileupload-1.2.1.jar** 384FAA82E193D4E4B0546059CA09572654BC3970	**CVE-2014-0050** 7.5 (v2.0)	!	🐾	

Vulnerability Details



CVE-2014-3574 NVD Exploit DB

Vulnerability Id: CVE-2014-3574

Description:

Apache POI before 3.10.1 and 3.11.x before 3.11-beta2 allows remote attackers to cause a denial of service (CPU consumption and crash) via a crafted OOXML file, aka an XML Entity Expansion (XEE) attack.

References:

CVSS Score: 4.3 (v2.0)

Published at: 2014-09-04T00:00:00.000Z

Modified at: 2017-08-28T00:00:00.000Z

Covered by Vulas since: 2016-12-16T15:43:01.891+0000

Filename: poi-ooxml-3.11-beta1.jar

Archive ID: org.apache.poi : poi-ooxml : 3.11-beta1

Programming constructs of the change list of the OSS patch

Repository:http://svn.apache.org/repos/asf/poi

Revisions fixing the vulnerability:1615720,1615731,1615781,1616509

Change	Revision	Type	Qualified Construct Name (Path)	Contained	Reacha…	Traced
MOD	1615720	PACK	**org.apache.poi.util** /poi/trunk/src/ooxml/java/org/apache/poi/util/SAXHelper.java	true		
MOD	1615720	Class	**org.apache.poi.util.SAXHelper** /poi/trunk/src/ooxml/java/org/apache/poi/util/SAXHelper.java	true	N/a	N/a
MOD	1615720	Method	**org.apache.poi.util.SAXHelper.getSAXReader()** /poi/trunk/src/ooxml/java/org/apache/poi/util/SAXHelper.java	true		
ADD	1615720	Method	**org.apache.poi.util.SAXHelper.trySetSAXFeature(SAXReader,String,boolean)** /poi/trunk/src/ooxml/java/org/apache/poi/util/SAXHelper.java	false		
ADD	1615720	Method	**org.apache.poi.util.SAXHelper.trySetXercesSecurityManager(SAXReader)** /poi/trunk/src/ooxml/java/org/apache/poi/util/SAXHelper.java	false		
MOD	1615720	PACK	**org.apache.poi.xssf.usermodel** /poi/trunk/src/ooxml/testcases/org/apache/poi/xssf/usermodel/TestXSSFBugs.java	true		

Vulnerability Details



Mitigation Overview



Mitigation Details





Experience Report

Evaluation

- No downtime since Dec 2016
- 250,000 scans of 500 applications
- Under-development/legacy applications



arison with existing (open/commercial) tools



Beyond Metadata!

- NVD reported that “Eclipse Mojarra before 2.3.5 is affected by CVE-2018-14371”
- Vulas found that Eclipse Mojarra 2.3.5 includes vulnerable code
- C

CVE Modified by MITRE - 8/27/2018 9:29:00 AM

Action	Type	Old Value	New Value
Changed	Description	The getLocalePrefix function in ResourceManager.java in Eclipse Mojarra before 2.3.5 is affected by Directory Traversal via the loc parameter. A remote attacker can download configuration files or Java bytecodes from applications.	The getLocalePrefix function in ResourceManager.java in Eclipse Mojarra before 2.3.7 is affected by Directory Traversal via the loc parameter. A remote attacker can download configuration files or Java bytecodes from applications.

Vulas Summary

Client-side tools

- Plugins for Maven and Gradle (Java) and setuptools (Python)
- Command Line Interface (CLI) for everything else

Two server-side microservices

- Tenants and workspaces to separate scans
- RESTful interfaces

Enterprise-ready

- Usable in CI/CD pipelines, but also for legacy software
- Aggregated reports and audit of findings
- New vulnerabilities are detected without needing to re-scan
- Support of CERT: Which of our apps are impacted by vulnerability X?
- Non-disclosed (internal) vulnerabilities can also be added to knowledge base

Vulas is Open-source

Vulas is Open-source

Goal: Establish a collaboration among enterprises, universities and Open Source foundations to reduce the risk coming from the use of vulnerable OSS components, e.g.,

- Contributions to the vulnerability knowledge base
- New analysis techniques
- New languages

Already available

- Core components (client-side tools and server-side components)
- Docker files

Coming Soon

- Knowledge base with 780+ public vulnerabilities
- Other features: Gradle plugin, Python setuptools plugin, etc.

Subscribe to the newsletter! vulas-news-request@listserv.sap.com (“subscribe” in the body)

Try it out!

https://github.com/SAP/vulnerability-assessment-tool

Docker to

- build project
- facilitate operation of server-side components

- Interested in an introductory session?
  Contact: henrik.plate@sap.com



Newsletter: vulas-news-request@listserv.sap.com (“subscribe” in the body)

Thank you.
Questions?

Subscribe to receive news on **Vulas**: vulas-news@listserv.sap.com (“subscribe” in the body)
Request for participating to introductory session: henrik.plate@sap.com
https://github.com/SAP/vulnerability-assessment-tool