AD 2. AERODROMES

VIAG AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIAG - AGRA AIRPORT, AGRA [INDIAN AIR FORCE]

NOTE: Aeronautical Data and Aeronautical Information published as here under is provided by Indian Air Force

VIAG AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	270933N 0775738E 160M North of runway intersection	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	260 DEG, 10 Km West of Agra city.	
3	Aerodrome elevation and reference temperature	550 FT / 41.6 DEG C	
4	Magnetic variation, date of information and annual change	0.25 DEG W (1995) /0.016 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station Agra Uttar Pradesh - 282008,	
		Telephone:	(91) 562 2400067 (91) 8171625081
		Fax:	(91) 562 2400067
		AFS:	VIAGYFYX
		Email:	Guard-ian365@gov.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Joint User Aerodrome (Defence & Civil Ops)	

VIAG AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	H24
2	Custom and immigration	H24
3	Health and sanitation	H24
4	AIS briefing office	H24
5	ATS reporting office (ARO)	H24
6	MET Briefing office	H24
7	Air Traffic Service	H24
8	Fuelling	NIL
9	Handling	H24
10	Security	H24
11	De-icing	NIL
12	Remarks	Airfield will be available for civil movements from local Sunrise to 2000IST only.

VIAG AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Not Available
2	Fuel and Oil types	Fuel: ATF (K-50) Oil: Not Available
3	Fuelling facilities and capacity	Operators to coordinate with Airports Authority of India
4	De-icing facilities	NIL

5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VIAG AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the City.
2	Restaurant(s) at or in the vicinity of aerodrome	In the City.
3	Transportation possibilities	Buses, Taxies in the City
4	Medical Facilities	First Aid at AD, Hospitals in City
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the City. Post office: In the City
6	Tourist office	Office in the Civil terminal/City
7	Remarks	NIL

VIAG AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	As per aerodrome category
3	Capability for removal of disabled aircraft	With Local Airlines (Operators to make own arrangements).
4	Remarks	NIL

VIAG AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Not Available
2	Clearance priorities	Not Available
3	Remarks	NIL

VIAG AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Civil dispersal Surface: Rigid Strength:Not Available
2	Designation, width, surface and strength of taxiways	Designator: LINK TWY C Width: 15 M Surface: Concrete Strength: PCN 62/R/C/X/T
3	Location and elevation of altimeter checkpoints	NIL
4	Location of VOR checkpoints	Available at TWY C.
5	Position of INS checkpoints	NIL
6	Remarks	NIL

VIAG AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Ground markings for stand identification available and also taxi guidance provided on R/T.

2	Runway and taxiway markings and lights	RWY05/23: Markings: Designation, THR, TDZ, Centreline, Side strip, Aiming point. Lights: THR, TDZ, Edge, RWY End, RWY Centreline, CAT II Approach for RWY 05 and Simple Approach Lights available for RWY 23. RWY 12/30: Markings: Designation, THR, TDZ, Centreline, Side strip, Aiming point. Lights: THR, Edge, RWY End, Lead in lights for RWY 12. TWY: Markings: Centreline, Taxi holding position at all TWY/RWY Intersection. Lights: TWY Edge light
3	Stop bars (if any)	At link C1 and C2.
4	Remarks	Side strip marking of RWY 12/30 have been dispensed with at the intersection with primary RWY 05/23.

VIAG AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
23/TKOF 05/APCH	OTHER	270915.0N 0775845.0E	716 FT	LGTD	MAST
23/APCH 05/TKOF	TOWER	271158.0N 0780300.0E	1020 FT	LGTD	MICROWAVE
30/APCH 12/TKOF	TOWER	270750.0N 0780300.0E	1044 FT	LGTD	TV TOWER

VIAG AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

Note: Resolution of obstacles coordinates is up to Second only

1	Name of the associated meteorological office	MET Section AF STN Agra
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	MET Section AF STN Agra 12 HR
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend 30 MIN
5	Information on how briefing and/or consultation is provided	Telephone
6	Types of flight documentation supplied and language(s) used in flight documentation	Chart And Pictorial Form, English
7	Charts and other information displayed or available for briefing or consultation	Surface, Upper Air Chart, TAFOR, Satellite Image

8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	DMDD. MOL, Internet
9	The air traffic services unit(s) provided with meteorological information	Agra ATC
10	Additional information, e.g. concerning any limitation of service.	NIL

VIAG AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
05	46.00 DEG	2866 x 46 M	37/F/C/X/T Asphalt	THR: 270855.00N 0775702.00E RWY END: 271000.00N 0775816.00E
23	226.00 DEG	2866 x 46 M	37/F/C/X/T Asphalt	THR: 271000.00N 0775816.00E RWY END: 270855.00N 0775702.00E
12	116.00 DEG	1829 x 46 M	50/F/C/X/T Asphalt	THR: 270940.00N 0775709.00E RWY END: 270914.00N 0775808.00E
30	296.00 DEG	1829 x 46 M	50/F/C/X/T Asphalt	THR: 270914.00N 0775808.00E RWY END: 270940.00N 0775709.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 550.2FT TDZ: 550.3FT		234 x 46 M	234 x 46	3334 x 300 M
THR: 550.3FT TDZ: 551.0FT		100 x 46 M	100 x 46	3334 x 300 M
THR: 550.7FT TDZ: 550.3FT				1949 x 300 M
THR: 548.3FT TDZ: 550.2FT				1949 x 300 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
			1.PCN of first 391M and last 269M is 71/R/C/X/T. Surface: Rigid 2.Resolution of THR and RWY END Coordinates is up to Second. 3.Elevation of THR and TDZ is up to nearest feet
			1. PCN of first 269M and last 391M is 71/R/C/X/T. Surface: Rigid. 2.Resolution of THR and RWY END Coordinates is up to Second. 3.Elevation of THR and TDZ is up to nearest feet
			1.PCN of first 305M and last 305M is 71/R/C/X/T. Surface: Rigid. 2.Resolution of THR and RWY END Coordinates is up to Second. 3.Elevation of THR and TDZ is up to nearest feet 4. Secondary RWY AVBL BTN HJ. 5. Turn PAD measuring 164FT by 82FT AVBL at dumbell 12 and dumbell 30.
			1.PCN of first 305M and last 305M is 71/R/C/X/T. Surface: Rigid. 2.Resolution of THR and RWY END Coordinates is up to Second. 3.Elevation of THR and TDZ is up to nearest feet 4.Secondary RWY AVBL BTN HJ. 5. Turn PAD measuring 164FT by 82FT AVBL at dumbell 12 and dumbell 30.

VIAG AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
05	2866	3100	3100	2866	
23	2866	2966	2966	2866	
12	1829	1829	1829	1649	RWY12 threshold displaced by 180 M
30	1829	1829	1829	1829	NIL

VIAG AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
05	CAT II 900 M LIH	Green	PAPI RIGHT/3.00 DEG	900 M
23	SALS 420 M LIH	Green	PAPI RIGHT/3.00 DEG	
12	180 M NALS LIL	Green	NIL	
30	SALS 240 M LIH	Green	NIL	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2866 M 15 M LIH WHITE AND RED	2866 M 60 M WHITE/AMBER LIH	Red	Red 240 M	1. RWY centreline lights from THR to 1966M-white, from 1966M to 2566M - alternate red and white from 2566M to end light-red. 2. RWY Edge lights from THR to 2266M-white and from 2266M to end – yellow
2866 M 15 M LIH WHITE AND RED	2866 M 60 M WHITE/ AMBER LIH	Red	Red 106 M	1. RWY centreline lights from THR to 1966M-white, from 1966M to 2566M - alternate red and white from 2566M to end light-red. 2. RWY Edge lights from THR to 2266M-white and from 2266M to end - yellow
	1829 M 60 M WHITE/AMBER LIH	Red		1. RWY Edge Lights from THR to 1229M- white and from 1229M to end – yellow. 2. RWY lights, omni lights, lead in lights AVBL for both RWY not meeting ICAO specification.

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	1829 M 60 M WHITE/AMBER LIH	Red		1. RWY Edge Lights from THR to 1229M- white and from 1229M to end – yellow. 2. RWY lights, omni lights, lead in lights AVBL for both RWY not meeting ICAO specification.

VIAG AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At ATC Tower building, FLG W&G 22/MIN, As per requirement.
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	In front of ATC/Lighted
		Anemometer	Near both THR of RWY 05/23
3	Taxiway edge and taxiway centre line lights;	Edge	ALL TWY
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary Power supply available, Switch over time for RWY 12/30: 15 sec Switch over time for RWY 05/23: 1 Sec: RWY edge lights. 8-15 Sec: for inner 300 m of approach lighting system, RWY threshold, RWY end, RWY centre line, RWY touchdown zone, all stop bars other parts of approach lighting system, and TWY edge lights	
5	Remarks	1. UPS available for runway 05/23 edge lights for a power back up of 15 minutes. 2. UPS available for runway 12/30 edge lights for a power back up of 30 minutes.	

VIAG AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	Not established

VIAG AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: Area bounded by lines joining points 271222N 0771852E then along the clockwise arc of a circle of 35NM radius centred on 270901N 0775755E to 274501N 0775255E; 273301N 0782655E; 272801N 0782955E; 273501N 0780855E; 264201N 0781355E; 263801N 0775355E; 271301N 0772955E to point of origin.
2	Vertical limits	FL 150
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Agra Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	H24
7	Remarks	1. Communication Frequency: Agra Tower: 125.000 MHz 2. Controlling Unit: IAF AGRA TEL: +91-562-2400067 FAX: +91-562-2400067 Email: udan.4vayu@gov.in

VIAG AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Agra Approach	129.500 MHZ	
TWR	Agra Tower	125.000 MHZ	
ATIS	Agra Information	112.000 MHZ	
ALRS	Emergency Frequency	121.500 MHZ	
ALRS	Emergency Frequency	243.000 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	AS ATS	NIL
	AS ATS	NIL
	AS ATS	NIL
	AS ATS	VHF
	AS ATS	UHF

VIAG AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 05	IARA	110.700 MHz	As Required
GP 05	GP	330.200 MHz	As Required
DME ILS 05	IARA	CH44X	As Required
VOR/DME	AGG	112.000 MHz CH57X	As Required

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
271008.0N 0775826.0E			
270859.0N 0775713.0E			Glide Path Angel 3 DEG
270859.0N 0775713.0E			Co-located with GP IARA
270926.2N 0775723.6E	570 FT		1. Controlling Authority: Indian Air Force 2. Coverage 150 NM.

VIAG AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VIAG AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIAG AD 2.22 FLIGHT PROCEDURES

1. Surveillance Radar Approach:

SRA Procedure for RWY 05, RWY 23, RWY 30.

i. Radar frequency: 127.900 MHz.

ii. Minimum vectoring Altitude: 2500ft.

iii. OCA:

(a) RWY 05: 970ft

(b) RWY 23: 1270ft

(c) RWY 30: 1290ft

iv. Glide Slope: 3 DEG .

v. Termination: 1NM from touch down.

vi. Missed Approach Procedure: Climb 3600ft on last assigned heading, turn left join VOR hold or as directed by radar controller .

vii. Caution for VI (P) 90, VI (D) 104, VI (D) 166. Aircraft not to fly below 3600ft AMSL within 2 Km over Tajmahal.

viii. For any query contact +91- 562-2400067

VIAG AD 2.23 ADDITIONAL INFORMATION

1. All sked and non-sked operators to ensure no aerial photography by passengers is carried upon arrival and during departure. No passenger or crew to carry-out photography during taxi. Provisions on this subject applies as Aircraft Act and Indian Official Secret Act. For strict compliance.
2. VIR142 is Agra LFA. All aircraft maintaining FL150 and below to establish two way communication with Agra on 127.9 MHz (Approach Frequency) or 125.0 MHz (Tower Frequency) before entering VIR 142 and CTR of Agra.
3. Airfield lighting system will be kept 'switched off' 01 Hr before and after sunset until emergency or low visibility operations for Military aircraft only. All civil sked/non sked and military aircraft to report 10 miles AGG during approach for 'switching on' of airfield Lighting system. This is to reduced bird hits during approach due insect activity. For departure section wise light will be 'switched on' as per ground position of aircraft.
4. TORA information for intersection departures:
   i. RWY 23 DEP B3 TORA 2205M/7235FT
   ii. RWY 23 DEP C2 TORA 2865M/9400FT
   iii. RWY 05 DEP A4 TORA 1992M/6535FT
   iv. RWY 05 DEP A3/G3 TORA 2483M/8146FT
   v. RWY 05 DEP A2/G2 TORA 2741M/8992FT
5. All code D aircraft to carry out minimum power during taxi unless requested by ATC to avoid grass and foreign object damage (FOD) on all Manoeuvring surface.
6. Surveillance radar equipment shall operate as follows.
   i. For day/night when specially requested.
   ii. For fighter flying.
   iii. For VIP/VVIP movement.
   iv. During marginal weather when visibility less than 3000 m.
   v. Cloud below circuit altitude.

In case radar is completely shut down, 01 hr 30 min during morning hr and 03 hr notice during non-working hour required for operation of radar due manning constraints.

7. Two helipad marked.

   Helipad-1 Coordinates: 270941.3N 0775808.8E, location on Taxi track south of RWY 05/23 abeam civil dispersal,

   Helipad-2 Coordinates: 270912N 0775713.4e, location on taxi track North of RWY 05/23.
8. All pilots to exercise caution for increase of blue bull, deer, jackal or any other wild animal activity at airfield in and around manoeuvring area during day and night. Pilot to expect low overshoot to scare blue bull, deer, jackal or any other wild animal in order to prevent collision with it especially at night.
9. Flying restriction during training para sorties. Location dropping zone active during day and night. Hours of operations as per requirements training. Drop zone location bearing 218 DEG distance 4.4NM from ARP.
   a) For static jump, operating height band from GND up to 3500ft. No landing/take-off permitted during static line drop.
   b) For free fall jump, operating height band as per requirements. No arrival/departure and no traffic permitted within 25NM of drop zone below operating height. Aircraft may be subj to delays.

10. Smart fence erected in flight strip to contain wild animals in airfield area.
    a) Northern shoulder of main runway from 05 DB to intersection at a distance of 80m from runway centreline, from 23 DB to intersection at a distance of 90m from runway centreline.
    b) Southern shoulder of main runway from 05DB up to 1700ft at a distance of 220m from runway centreline, from 1700 ft to 23 DB at a distance of 75 m from runway centreline.
    c) On 05 approach at the distance of 175m from 05 DB, on 23 approach at the distance of 140m from 23 DB.
    d) The height of fencing is 1.3m. All operators to exercise caution.
11. All civil operators to Agra are to submit FPL and obtain destination acceptance on tele/fax 0562-2400067 prior to planned operations. Flight without prior submission of FPL shall not be accepted. All civil operators to coordinate with AAI for parking.
    Ensure strict adherence to FPL timing to avoid delays in departures.
12. All non-sked operators desiring to conduct operations outside ATS routes to and from VIR 142 to submit their flight details 24 Hr in advance to Agra ATC for approval.
    Tele/FAX Number of Agra ATC 0562-2400067. Non-compliance shall be deemed violation of airspace and dealt accordingly.
13. Following HF Frequencies are manned by Agra ATC:
    i. From 0130 to 0359 Hrs and 1100 to 1329 Hrs: 5795 KHz
    ii. From 0400 to 1059 Hrs 7310 KHz
    iii. From 1330 to 0129 Hrs 3660 KHz
14. ATC Agra Watch Supervisor Officer (WSO) Contact Nr. +91-8171625081. Communication on number only limited to level coordination, flight clearance and traffic information in case no contact on landline 0562-2400067 tele-fax. All ATS units and aircrew to note.
15. Obstructions in flight strip RWY05.
    i. RWY controller hut south side, distance from RWY edge 179 FT, from RWY 05 THR 1500 FT, height 25 FT. WDI for RWY 05, distance 197 FT from RWY edge, height 30 FT.
    ii. RWY controller hut north side, distance 175 FT from RWY edge, from RWY 23 displaced threshold 200 FT, height 25 FT. WDI for RWY 23, distance 296 FT from dumbbell 23, height 30 FT AGL.
    iii. Traffic crossing hut on both sides of RWY, distance 3000 FT from RWY 05 threshold. North side distance from RWY edge 150 FT, height 10 FT, south side distance from RWY Edge 254 FT, height 10 FT.
    iv. Blast pens north side, distance from RWY edge 183 FT, distance from RWY 05 threshold 750 FT and height 22 FT.
    v. Barbed wire fence running parallel to RWY on both sides from intersection up to distance of 2000 Ft towards threshold RWY 05, distance 400 FTfrom RWY edge.
    vi. Total 22 monsoon drain recharge well covered with load bearing Capacity 20 tons.
    vii. Saucer monsoon drain along RWY at a minimum distance of 100 FT.
16. Obstructions in flight strip RWY 12/30.
    i. High tension railway traction electric cable on approach RWY 12, distance 1200 FT from threshold RWY 12, height 30 FT.
    ii. Tree line distance 1500 FT from threshold RWY 12, 75 FT AGL.
    iii. High mast Apron light, distance 2000 FT from threshold RWY 12, 130 FT from RWY edge, height 66 FT AGL.
    iv. RWY controller hut RWY 12 east side, distance from RWY edge 150 FT, abeam RWY 12 threshold, height 15 FT. RWY controller hut for RWY 30.

17.Obstructions, High TV Transmitter On Radial 110DEG 5.0 NM FM Agra VOR, HGT 500 FT AGL, Concrete RWY Controller Huts to left Of APCH path for RWY 30, 300 FT FM beginning of RWY and 150 FT FM RWY edge, for RWY 12 right of APCH, 300 FT FM beginning of RWY and 150 FT FM RWY Edge, High Tension Railway Track at 900 FT FM Dumbell 12, Tree Line Running Across APCH Path Of RWY 12, DIST 1500 FT FM Dumbell 12

18. RWY 12/30 has standard shoulders, but standard cleared zones not AVBL for 12/30

19. All OPR to COOR mandatorily with VIAG atleast 24 HR prior to
intended FLT FM RWY 12/30.

VIAG AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aircraft Parking/Docking Chart(02 October 2025)
2 Instrument Approach Chart - ILS CAT I Procedure RWY 05 (08 August 2024)
3 Instrument Approach Chart – CAT II ILS RWY 05(12 June 2025)
4 Instrument Approach Chart - VOR (Z) Procedure RWY 05 (08 August 2024)
5 Instrument Approach Chart - VOR (Y) Procedure RWY 05 (08 August 2024)
6 Instrument Approach Chart - VOR Procedure RWY 12 (08 August 2024)
7 Instrument Approach Chart - VOR Procedure RWY 30 (08 August 2024)

VIAG AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3