AD 2. AERODROMES

VAAM AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VAAM - AMRAVATI AIRPORT, AMRAVATI

VAAM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	204853N 0774304E On Northern side of RWY near Apron R	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	Airport is located 15KM South-West of Amravati Town.	
3	Aerodrome elevation and reference temperature	1137 FT / 39.7 DEG C	
4	Magnetic variation, date of information and annual change	0.50 DEG W (2010) /0.0167 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director Amravati Airport, At Belora Taluka- Nandgaon Khandeshwar, Post Office: Dabha, District- Amravati-444701 ,	
		Telephone:	07221-221001
		Fax:	
		AFS:	
		Email:	apd.amravati@madcindia.org
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	AD Reference Code: 3C Geoid Model: EGM08	

VAAM AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-SUN 0430-1230 UTC (1000-1800 IST)
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As ATS
5	ATS reporting office (ARO)	As ATS
6	MET Briefing office	As ATS
7	Air Traffic Service	Refer Current NOTAM for ATS HR
8	Fuelling	NIL
9	Handling	As ATS
10	Security	As ATS
11	De-icing	NIL
12	Remarks	1. Security by State Police/MSSC H24 2. All non-Schedule aircraft to take positive Clearance/Permission at least 24 HR prior to planned arrival at Amravati.

VAAM AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	No exclusive facilities. Belly Cargo to be handled by the concerned operator. Limited cargo operations carried out through terminal building
2	Fuel and Oil types	
3	Fuelling facilities and capacity	NIL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	Nil

VAAM AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in city within 10Kms
2	Restaurant(s) at or in the vicinity of aerodrome	Snacks counter available at AD and restaurants available in the city within 10Kms.
3	Transportation possibilities	NIL
4	Medical Facilities	First Aid at AD. For Serious & critical cases District Hospital /other Private Hospitals located in Amravati City about 15 kms away.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Bank & Post office in the city within 6 KMs.
6	Tourist office	Available in city within 6 KMs
7	Remarks	Bank ATM facility provided at PTB

VAAM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-5
2	Rescue equipment	Ambulance 01 CFT 01
3	Capability for removal of disabled aircraft	1) The critical aircraft for the airport is ATR72. 2) Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3) The airlines may contact ‘Airport Director for Disabled Aircraft Removal Operations’ for coordinating with the agencies (Air India) having Disabled Aircraft Recovery Kit. 4) Contact Details: Airport Director, Tel/Mob. +91 9766168198 Email: apd.amravati@madcindia.org
4	Remarks	MADC has received assurance letter from Air India for provision of the recovery kit

VAAM AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VAAM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	Location- On Apron T Stand No 1 & 2 Elevation- 1124 FT & 1124.7 FT
4	Location of VOR checkpoints	
5	Position of INS checkpoints	
6	Remarks	1) Dimension of Apron: Apron T: 120 M X 114M Apron R: 60 x 44.5 M Location: North of RWY 08/26 2) Apron-T is restricted to accommodate 02 Nos. of ATR-72 or similar type of Aircraft. 3) Apron-R is restricted to accommodate 01 (one) CRJ-200 or similar type of aircraft up to the wingspan of 21 meters 4) All Stands are Power-in / Power-out and Remote Stands. 5) Apron Slope a) Apron-T: 0.5% b) Apron-R: 1.5% 6) Isolation Bay: Dimension: 58.8M X 54M PCN: 16/F/B/W/T Location: On LHS Perpendicular to THR of RWY 08 Parking Facing North-West Suitable for: ATR 72 or similar type of aircraft Connecting Taxiway: TWY-Z 7) Vertical Datum: EGM 08

VAAM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxing guidance signs at intersection with TWY and RWY and at holding position, Gridlines at apron. Taxiing guidance provided on R/T also.
2	Runway and taxiway markings and lights	RWY Markings Designation, Centreline, THR, TDZ, RWY Side Strip, Aiming Point, Turn pad Lights NIL TWY Marking Centreline, Holding Position, Edge, Mandatory Instructions. Lights NIL
3	Stop bars (if any)	NIL
4	Remarks	NIL

VAAM AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	OTHER	205438.6N 0774952.7E	1806 FT	NIL	Cell Phone Mast on Hill Top
In circling area and at AD	OTHER	205526.0N 0774828.7E	1693 FT	NIL	Microwave Tower on Hill Top
In circling area and at AD	OTHER	205116.6N 0774357.6E	1391 FT	NIL	Cell Phone Mast

See AD 2.23

VAAM AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	AMO NAGPUR
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	09 HRS Prior to ATC Watch HRS
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	AMO Nagpur, AMO Nagpur, Validity Period of TAF is 9 Hrs. and TAF Issuance interval is 3 Hrs.
4	Availability of the trend forecast for the aerodrome and interval of issuance	NIL
5	Information on how briefing and/or consultation is provided	Online Briefing System (OLBS) and Automated Transmission to ATC
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form (English)
7	Charts and other information displayed or available for briefing or consultation	OLBS
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	DWR NAGPUR, INSAT-3DR & 3DS Images.
9	The air traffic services unit(s) provided with meteorological information	Amravati Airport ATC
10	Additional information, e.g. concerning any limitation of service.	NIL

VAAM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
08	75.20 DEG	1850 x 45 M	16/F/B/W/T Asphalt	THR: 204843.38N 0774245.86E RWY END: 204858.75N 0774347.71E
26	255.20 DEG	1850 x 45 M	16/F/B/W/T Asphalt	THR: 204858.75N 0774347.71E RWY END: 204843.38N 0774245.86E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 1126.6FT TDZ:	0.17%			1970 x 280 M
THR: 1131.6FT TDZ:	0.17%			1970 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M	NIL		Geoid Model: EGM08
240M x 90M	NIL		NIL

VAAM AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
08	1785	1785	1850	1850	TORA & TODA RWY 08 restricted to 1785M.
26	1850	1850	1850	1850	

VAAM AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
08			PAPI LEFT/3.00 DEG MEHT (12.93M)	
26			PAPI LEFT/3.00 DEG MEHT (12.93M)	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
				NIL
				NIL

VAAM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Above the ATC Tower Building, FLG W & G with a frequency of 26 flashes per minute
		IBN	
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	North of RWY 08 Lat: 204851.35N Long: 0774250.43N Elevation: 344.12 M LIGHTED
		Anemometer	Available. North of RWY 26 near ATC Building
3	Taxiway edge and taxiway centre line lights;	Edge	
		Centre Line	
4	Secondary power supply including switch-over time;	DG set available for all Lights at Aerodrome; Secondary Power supply switchover time is within 15 Seconds. (Back up with UPS system for AGL lights).	
5	Remarks	ABN operational during ATS hours	

VAAM AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VAAM AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 204853N 0774304E within a 15NM radius.
2	Vertical limits	FL 75
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	AMRAVATI TWR, English
5	Transition altitude	4000 FT
6	Hours of applicability	HO
7	Remarks	1) Airspace classified as Class D 2) Beyond operational hours the airspace classification is Class G. 3)Amravati Approach Control Unit is combined with Amravati Aerodrome Control Tower.

VAAM AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	AMRAVATI TOWER	118.650 MHZ	
APP	AMRAVATI TOWER	124.475 MHZ	
TWR	AMRAVATI TWR	118.650 MHZ	
TWR	AMRAVATI TWR	124.475 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	1. Backup Frequency 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1. Main Frequency 2. Functions of Approach Control Service provided by Aerodrome Control Tower.

Logon address, as appropriate	Hours of operation	Remarks
	HO	BACK UP
	HO	MAIN

VAAM AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	BEL	115.600 MHz CH103X	HO

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
204851.9N 0774349.6E	1162 FT		I) DME Co-located with DVOR. II) Top ELEV in EGM-08.

VAAM AD 2.20 LOCAL AERODROME REGULATIONS

1) TAXI PROCEDURE:
i). All the aircraft stands are power in/ power out, precaution required during taxiing.
ii). Wing Tip Marsheller mandatory to be available during movement of aircraft on apron.
iii).No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage. Use turn pad for 180 deg turn, provided on END of RWY 08 & 26

VAAM AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VAAM AD 2.22 FLIGHT PROCEDURES

NIL

VAAM AD 2.23 ADDITIONAL INFORMATION

NIL

VAAM AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart(29 October 2026)
2. Aircraft Parking/Docking Chart(07 August 2025)
3. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 08/26(07 August 2025)
4. Aerodrome Obstacle Chart Type B(07 August 2025)

VAAM AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3