AD 2. AERODROMES

VEBD AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VEBD - BAGDOGRA AIRPORT, BAGDOGRANOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VEBD AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	264107N 0881938E In Front of ATC Tower near link 'A'	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	Approximately 11 Km SW of Siliguri town.	
3	Aerodrome elevation and reference temperature	414 FT / DEG C	
4	Magnetic variation, date of information and annual change		
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer AF Station Bagdogra Distt-Darjeeling West Bengal Pin-734421,	
		Telephone:	(91) 353 2698101 353 2698102 353 2698103 353 2698104 353 2698105 -7350 -7352 -7353 -7359 (91) 9474921397 (91) 8116167879
		Fax:	(91) 353 2698068 2698101
		AFS:	
		Email:	safe.hand@gov.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	NIL	

VEBD AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	Sunrise – 2200 HRS IST
2	Custom and immigration	MON, WED, THU: 0930-1800 IST TUE & FRI: 0600-1430 IST (However timings may change as per international scheduled flight operations)
3	Health and sanitation	NIL
4	AIS briefing office	Sunrise – 2200 HRS IST
5	ATS reporting office (ARO)	Sunrise – 2200 HRS IST
6	MET Briefing office	Sunrise – 2200 HRS IST
7	Air Traffic Service	Sunrise – 2200 HRS IST
8	Fuelling	0830 – 1700 IST (As per requirement)
9	Handling	1000-1900 IST (May vary as per civil scheduled movement)

10	Security	24 Hrs Apron security on shift basis and operational shift from 02 Hr before arrival to 02 hrs after last departure by CISF
11	De-icing	NIL
12	Remarks	NIL

VEBD AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	AAI
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	04 Bowser of 16 KL by IOC 01 Bowser of 9 KL by IOC 01 Bowser of 6 KL by IOC
4	De-icing facilities	Not Available
5	Hangar space for visiting aircraft	Not Available
6	Repair facilities for visiting aircraft	Not Available
7	Remarks	NIL

VEBD AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available at a distance of 03 Km.
2	Restaurant(s) at or in the vicinity of aerodrome	At AD and in the city
3	Transportation possibilities	Available at AD
4	Medical Facilities	Medical facility not available at AD. Hospitals in the city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: ICICI Bank at 01 Km, all banks in City Post office: Near AD
6	Tourist office	Available
7	Remarks	Matter for Provisioning of medical facility at AD is pending with APD.

VEBD AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per category.
3	Capability for removal of disabled aircraft	Towing tractor not available at AD.
4	Remarks	NIL

VEBD AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Mechanical runway sweeper
2	Clearance priorities	Operational area
3	Remarks	All Season

VEBD AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: CIVIL APRON Surface: Concrete Strength: PCN 62/R/C/X/T

<table>
<tr><td>2</td><td>Designation, width, surface and strength of taxiways</td><td>Designator: TWY A
Width: 23 M
Surface: Asphalt
Strength:

Designator: TWY B
Width: 23 M
Surface: Asphalt
Strength:

Designator: TWY C
Width: 23 M
Surface: Concrete
Strength: PCN 53/R/C/X/T

Designator: TWY D
Width: 23 M
Surface: Concrete
Strength: PCN 53/R/C/X/T

Designator: TWY E1
Width: 23 M
Surface: Concrete
Strength: PCN 75/R/C/X/T

Designator: TWY E2
Width: 15 M
Surface: Concrete
Strength: PCN 53/R/C/X/T

Designator: TWY G
Width: 15 M
Surface: Concrete
Strength: PCN 53/R/C/X/T

Designator: TWY M
Width: 15 M
Surface: Asphalt
Strength: PCN 53/R/C/X/T

Designator: TWY PTT
Width: 15 M
Surface: Concrete
Strength: PCN 53/R/C/X/T</td></tr>
<tr><td>3</td><td>Location and elevation of altimeter checkpoints</td><td>Not Established.</td></tr>
<tr><td>4</td><td>Location of VOR checkpoints</td><td>i. Link 'A'
ii. Link 'B'
iii. Link 'C'
iv. Link 'D'
v. Link 'E2'
vi. Link 'F'</td></tr>
<tr><td>5</td><td>Position of INS checkpoints</td><td></td></tr>
<tr><td>6</td><td>Remarks</td><td>1. Apron Dimensions: 369M X 86.5M
2. Stand Elevations
<table><tr><th>Stand</th><th>Elevation</th></tr><tr><td>Stand 1</td><td>414 ft</td></tr><tr><td>Stand 2</td><td>414 ft</td></tr><tr><td>Stand 3</td><td>414 ft</td></tr><tr><td>Stand 4</td><td>414 ft</td></tr><tr><td>Stand 5</td><td>414 ft</td></tr></table></td></tr>
</table>

VEBD AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxi Guidance provided on R/T.
2	Runway and taxiway markings and lights	RWY: Markings: Designation, THR, TDZ, Centre line, Aiming Point, Side Strip. Lights: Edge, Centre line, THR, RWY End, CAT-II approach light. TWY: Markings: Centre line, Holding Position at all TWY & FOD line. Lights: Edge (except A and B)
3	Stop bars (if any)	On Link A, B, C, D, E, F & G.
4	Remarks	NIL

VEBD AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
RWY 36/APCH RWY 18/TKOF	ANTENNA	262600.0N 0881600.0E	666 FT	LGTD	Mast Antenna
In circling area and at AD	OTHER	264134.0N 0881935.0E	502 FT	LGTD	Transmitter Aerial Masts
In circling area and at AD	OTHER	264234.0N 0881807.0E	551 FT	LGTD	Microwave Tower
In circling area and at AD	OTHER	264228.0N 0882048.0E	482 FT	LGTD	High Tension Cables-Running Parallel to the runway

VEBD AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Met Section, AF Station Bagdogra
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 HRS Observation, 18 HRS forecasting, Type ‘B’
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Bagdogra 12 HR Validity and 03 TAFORs in a day.
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend Trend type half an hourly
5	Information on how briefing and/or consultation is provided	Self-briefing displayProvided
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form / English
7	Charts and other information displayed or available for briefing or consultation	S, U85,U70,U50,U40,U30,U25,U20, Satellite Picture
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	AWS, DMDD, LDS, MWR, DDRWE, DSRRG
9	The air traffic services unit(s) provided with meteorological information	ATC Bagdogra

10	Additional information, e.g. concerning any limitation of service.	NIL

VEBD AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
RWY 18	182.00 DEG	2744 x 45 M	53/R/C/X/T Concrete	THR: 264137.00N 0881942.00E RWY END:
RWY 36	2.00 DEG	2744 x 45 M	53/R/C/X/T Concrete	THR: 264008.00N 0881939.00E RWY END:

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 423.2FT TDZ:		346 x 45 M	346 x 45	3295 x 229 M
THR: 389.3FT TDZ:		386 x 45 M	386 x 45	3295 x 229 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
	THR 36: ADRDE 20.4 Ton		Resolution of RWY THR Coordinates is up to Second.
	THR 18: ADRDE 20.4 Ton		Resolution of RWY THR Coordinates is up to Second.

VEBD AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
RWY 18	2744	3090	3090	2744	
RWY 36	2744	3130	3130	2744	

VEBD AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
RWY 18	SALS 420 M LIH	Green	PAPI RIGHT/3.00 DEG	
RWY 36	CAT II 900 M LIH	Green	PAPI LEFT/3.00 DEG	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2744 M 15 M LIH White	2744 M 60 M White LIH	Red	Red	Colour of runway edge lights - Initial 1800M white, then 600M amber and remaining 343 M red.
2744 M 15 M LIH White	2744 M 60 M White LIH	Red	Red	Colour of runway edge lights - Initial 1800M white, then 600M amber and remaining 343M red.

VEBD AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At ATC Tower Building, FLG W&G, AS ATS HR, 24 FPM
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	In Front of ATC Tower / Lighted
		Anemometer	Automated in Tower
3	Taxiway edge and taxiway centre line lights;	Edge	All TWY
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Available at AD / Switch over time Max 10 sec	
5	Remarks	NIL	

VEBD AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	Not established

VEBD AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: Area bounded by 262303N 0873449E; then eastward along the border of Nepal and India to a point on common border of Nepal, China and India, then along the border of India and China to a point on common border of Bhutan, China and India, then along the border of India and Bhutan to 265901.3N 0885549.8E; 262601.5N 0885549.8E then along India and Bangladesh border to 255512N 0880545E; 260605N 0875630E; 262303N 0873449E;
2	Vertical limits	FL 250
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Bagdogra Tower, English
5	Transition altitude	13000 FT
6	Hours of applicability	Sunrise to 1630 UTC
7	Remarks	Controlling Unit : IAF Bagdogra Mobile: +91-7407666672

VEBD AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Bagdogra Approach	131.200 MHZ	
TWR	Bagdogra Tower	122.300 MHZ	
RADAR	Bagdogra Approach	131.200 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	AS ATS	NIL
	AS ATS	NIL
	HO	MSSR/RSR

VEBD AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC RWY 36 CAT II	IBGD	108.100 MHz	
GP RWY 36		334.700 MHz	
DME ILS RWY 36	IBGD	CH18X	
DVOR/DME	BGD	115.200 MHz CH99X	HO

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
264151.0N 0881943.0E			
264017.0N 0881935.0E			
264017.0N 0881935.0E			Collocated with Glide Path
264118.0N 0881934.0E			1. Controlling Authority: Indian Air Force 2. Coverage: 150NM.

VEBD AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VEBD AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VEBD AD 2.22 FLIGHT PROCEDURES

i. The Low Visibility Procedures are in place during CAT II Operations for RWY 36.

VEBD AD 2.23 ADDITIONAL INFORMATION

i. All aircraft on Q-18, W-69,W-105 & G 348 to contact APP 131.2 MHz at least 10 min prior to OPIMO, KHR, MECHI & SUBSU due military operational flying.

ii. Taxiing procedure - all aircraft to use full length of runway after landing for taxiing.

iii. Radar approach for RWY 18 not possible due close proximity of hills.

iv. IAF installations located at 18.9M from the runway edge on the eastern shoulder at both the ends of the runway, height 28 FT. All aircraft to exercise caution.

v. Standard cleared zone width 83.82M commencing at a distance of 45.72M from runway edge not available on western side of runway.

vi. Army Helicopter at SEVOKE is Located at Distance of 09 NM ON BRG OF 052 DEG from VEBD. Helicopter TFC ZONE is 03 NM in RADIUS UPTO 2000 FT ON QNH. SEVOKE is AVBL ON MAIN FREQ 133.2 MHZ AND SDBY FREQ 134.2 MHZ. ALL ACFT to Exercise Caution.

VEBD AD 2.24 CHARTS RELATED TO AN AERODROME

1 ILS (Z) Procedure RWY 36
2 ILS Procedure CAT II RWY 36
3 VOR (Z) Procedure RWY 36
4 VOR (Y) Procedure RWY 36

VEBD AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3