AD 2. AERODROMES

VIBY AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIBY - BAREILLY AIRPORT, BAREILLY [INDIAN AIR FORCE]

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VIBY AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	282517N 0792657E North of PTT near Middle Marker, 37.5m from PTT edge	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	10 km North of Bareilly Railway Station	
3	Aerodrome elevation and reference temperature	571 FT / 33.0 DEG C	
4	Magnetic variation, date of information and annual change		
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station Bareilly Izzatnagar, Bareilly Uttar Pradesh -243002,	
		Telephone:	(91) 581 2315796
		Fax:	(91) 581 2315796
		AFS:	
		Email:	trishul.control@gov.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	1. Joint User Airfield (Defence & Civil Ops) 2. Annual Magnetic Variation Change not determined.	

VIBY AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON to SUN 0500 UTC to 0930 UTC
2	Custom and immigration	Not available
3	Health and sanitation	H24
4	AIS briefing office	HJ
5	ATS reporting office (ARO)	HJ
6	MET Briefing office	H24
7	Air Traffic Service	HJ
8	Fuelling	On prior co-ordination with IOCL
9	Handling	AVBL
10	Security	H24
11	De-icing	NIL
12	Remarks	Nil

VIBY AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	AVBL
2	Fuel and Oil types	JET A1 Oil: Not Available

3	Fuelling facilities and capacity	IOCL Refuellers with Capacity: 04 X 16KL Discharge Rate(L/Min): 700 LPM – 900LPM
4	De-icing facilities	Not available
5	Hangar space for visiting aircraft	Not available
6	Repair facilities for visiting aircraft	Not available
7	Remarks	Limited Parking facility available, prior coordination with AAI is mandatory.

VIBY AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Five star and budget hotels available near Bareilly AD.
2	Restaurant(s) at or in the vicinity of aerodrome	Available near AD and in Bareilly city
3	Transportation possibilities	State transport and taxi services available 24H outside AD premises
4	Medical Facilities	First aid at AD. Hospitals in the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available near AD and in Bareilly city. Post office: Available near AD and in Bareilly city.
6	Tourist office	Available in the City
7	Remarks	Nil

VIBY AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per AD category
3	Capability for removal of disabled aircraft	Disabled aircraft removal to be ensured by the operator in coordination with local authorities
4	Remarks	Nil

VIBY AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VIBY AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: Civil Enclave Apron Surface: Asphalt Strength: PCN 61/F/C/W/T Elevation: 571 FT
2	Designation, width, surface and strength of taxiways	Designator: TWY P Width: 76 FT Surface: Asphalt Strength: PCN 61/F/C/W/T
3	Location and elevation of altimeter checkpoints	Location: Dumbbell 29/11 Elevation: 569 FT (DB 29) 569 FT (DB 11)
4	Location of VOR checkpoints	Taxi holding point Link C: 306 DEG, 0.4 NM
5	Position of INS checkpoints	Not available

6	Remarks	TWY P connecting RWY to Civil apron is located 60M from dumbbell 29. Civil Apron available to accommodate 03 nos. of A-321 type a/c. Dimension of: **TWY P:** 819 M X 23 M with 5.5 M shoulder on both sides. **Civil Apron:** 151 M X 120 M with 5.5 M shoulders on all around.

VIBY AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Ground markings for stand identification available. Taxi guidance provided on R/T. VDGS Not Available.
2	Runway and taxiway markings and lights	RWY Markings: THR, Designation, Aiming point, Side Stripe, TDZ, Centreline Lights: Edge, Wing bar, THR, End, Centreline, Stopway for both runways, TDZ, SAPL for RWY 11, CAT II ALS for RWY 29 TWY Marking:Centreline and Holding positions on all taxiways Lights:Available at all TWYs except TWY P.
3	Stop bars (if any)	Available at link A, B, C, D, E, M, N & P
4	Remarks	NIL

VIBY AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
29/TKOF 11/APCH	OTHER	282554.0N 0792307.0E	715 FT	LGTD	Electric Pylon
29/TKOF 11/APCH	TOWER	282625.0N 0792644.0E	733 FT	LGTD	MWT at Didarpatti
29/APCH 11/TKOF	TOWER	282456.0N 0792647.0E	690 FT	LGTD	SUV Tower
29/APCH 11/TKOF	TOWER	282528.0N 0792733.0E	919 FT	LGTD	North WCDMA Tower
In circling area and at AD	TOWER	282509.0N 0792703.0E	656 FT	LGTD	ATC Tower
In circling area and at AD	TOWER	281830.0N 0792450.0E	1099 FT	LGTD	TV TWR Bareilly City
In circling area and at AD	TOWER	282245.0N 0792605.0E	899 FT	LGTD	BSNL Tower

VIBY AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Air Force, Met Watch Office

2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 Hours Observation, 18 hours forecasting
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Watch Office: 0000 to 1200 (UTC) 1200 to 2400 (UTC) 0600 to 1800 (UTC) 12 HRS
4	Availability of the trend forecast for the aerodrome and interval of issuance	Local Forecast 0730, 1330, 1830 (IST)
5	Information on how briefing and/or consultation is provided	Personal Consultation, T3, T4 briefing
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form English
7	Charts and other information displayed or available for briefing or consultation	Surface Charts, Upper Air Graph, Satellite picture, Radar report (Delhi, Lucknow)
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	AWS, Upper Air Sound System, LDS
9	The air traffic services unit(s) provided with meteorological information	Bareilly ATC
10	Additional information, e.g. concerning any limitation of service.	NIL

VIBY AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
11	112.00 DEG	2743 x 46 M	81/F/C/X/T Asphalt	THR: 282537.00N 0792613.00E RWY END: 282504.00N 0792746.00E
29	292.00 DEG	2743 x 46 M	81/F/C/X/T Asphalt	THR: 282504.00N 0792746.00E RWY END: 282537.00N 0792613.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 569.0FT TDZ: 571.0FT	1.00%	366 x 46 M	NIL	NIL
THR: 568.0FT TDZ: 569.0FT	1.00%	366 x 46 M	NIL	NIL

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
NIL	Not available for civil flights	Available	1. Dimensions of Strip: 3535 M X 150 M 2. Arrester barrier structure exists at both ends for RWY within the strip. 3. RESA not available due arrester barrier installed on both ends of RWY. 4. First and last 305m of RWY 11 surface is concrete PCN 62/R/C/X/T and remaining is asphalt. 5. Stopway for RWY 11 extends laterally from the extended centre line to 150m on the northern side up to 280m from threshold. The lateral distance of stopway reduces to 58 m on northern side beyond 280m till 366 m of stopway
NIL	Not available for civil flights	Available	1. Dimensions of Strip: 3475 M X 150 M 2. Arrester barrier structure exists at both ends for RWY within the strip. 3. RESA not available due arrester barrier installed on both ends of RWY. 4. First and last 305m of RWY 11 surface is concrete PCN 62/R/C/X/T and remaining is asphalt. 5. 60m area beyond the stopway is not available for RWY 29.

VIBY AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
11	2743	2743	3109	2743	
29	2743	2743	3109	2743	

VIBY AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
11	SALS 360 M LIH	Green	PAPI LEFT/3.00 DEG	NIL
29	CAT II 690 M LIH	Green	PAPI RIGHT/3.00 DEG	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2743 M 15 M LIH White	2743 M 60 M White LIH	Red	Red 366 M	1. Runway centreline lights from threshold to 1800m White, 1800 M to 2400M alternate Red and White, 2400M to 2743M Red. 2. Runway edge lights from threshold to 2100M White, 2100M to 2743 Red
2743 M 15 M LIH White	2743 M 60 M White LIH	Red	Red 366 M	1. Runway centreline lights from threshold to 1800m White, 1800 M to 2400M alternate Red and White, 2400M to 2743M Red. 2. Runway Edge lights from threshold to 2100M White, 2100M to 2743 Red.

VIBY AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On top of ATC Tower building, 24FPM, During night and low visibility conditions.
		IBN	Not available
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	East of ATC, Lighted
		Anemometer	AVBL at both ends of RWY North side
3	Taxiway edge and taxiway centre line lights;	Edge	All taxiways excpet TWY P
		Centre Line	Not available
4	Secondary power supply including switch-over time;	Secondary power supply available. Switch over time: 1 Sec: for inner 300m of approach lighting system, RWY threshold, RWY end, RWY centreline, RWY touchdown zone and all stop bars. 15 Sec: Other parts of approach lighting system, RWY edge, TWY lights	
5	Remarks	Nil	

VIBY AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Nil

VIBY AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: Area bounded by lines joining points 280039N 0793402E; 281932N 0785947E then along the clockwise arc of a circle of 25NM radius centred on 282502N 0792725E to 284000N 0794954E; 280948N 0794954E then along the clockwise arc of a circle of 25NM radius centred on 282502N 0792725E to point of origin.
2	Vertical limits	FL 145
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Bareilly Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	HJ
7	Remarks	All flying within control zone is to be carried out under positive control of approach/ aerodrome controller as applicable.

VIBY AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Bareilly Approach/ Radar	122.900 MHZ	
TWR	Bareilly Tower	125.525 MHZ	
ATIS	Bareilly Information	115.600 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HJ	NIL
	HJ	NIL
	HJ	NIL

VIBY AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 29 CAT I	IBLY	109.100 MHz	As per ATS
GP 29	GP29	331.400 MHz	As per ATS
DME ILS 29	IBLY	CH28X	As per ATS
DVOR/DME	BRL	115.600 MHz CH103X	As per ATS
NDB	BY	218 kHz	As per ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
282542.0N 0792600.0E			1. Controlling Authority: Indian Air Force 2. Resolution of Coordinates is up to Second.
282512.0N 0792736.0E			1. Controlling Authority: Indian Air Force 2. Resolution of Coordinates is up to Second.
282512.0N 0792736.0E	571 FT		1. Controlling Authority: Indian Air Force. 2. Co-located with GP. 3. Resolution of Coordinates is up to Second.
282501.0N 0792725.0E	571 FT		1. Controlling Authority: Indian Air Force. 2. DME collocated with DVOR. 3. Resolution of Coordinates is up to Second.
282427.0N 0792718.0E			1. Controlling Authority: Indian Air Force. 2. Resolution of Coordinates is up to Second.

VIBY AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VIBY AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIBY AD 2.22 FLIGHT PROCEDURES

NIL

VIBY AD 2.23 ADDITIONAL INFORMATION

1. Helicopter circuit south of airfield and fixed wing circuit north of airfield
2. Approach lights on RWY 29 extended up to 690M
3. Excessive bird activity below 4000Ft in circuit area during morning and dusk time.
4. No fixed wing aircraft to over fly between radial 180 DEG to 210 DEG BRL (DVOR), up to a distance of 25 km below 6000 Ft indicated.
5. All aircraft are to carry out 180 DEG turn only on concrete portion of Runway and exercise caution for arrester net in lowered position at stop end of runway.
6. Helicopters operations up to 3000 FT from Bareilly Cantonment (173 DEG/ 4.86 NM from Bareilly). Overfly Bareilly Cantonment 4000 FT and above.
7. Parking bay at Phase-I apron closed.

VIBY AD 2.24 CHARTS RELATED TO AN AERODROME

1. Instrument Approach Chart - CAT I ILS RWY 29 (12 JUN 2025
2. Instrument Approach Chart - CAT II ILS RWY 29 (CAT A/B/C)
3. Instrument Approach Chart - VOR Z RWY 11
4. Instrument Approach Chart - VOR Y RWY 11
5. Instrument Approach Chart - VOR Z RWY 29
6. Instrument Approach Chart - VOR Y RWY 29

VIBY AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3