AD 2. AERODROMES

VOBM AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOBM - BELAGAVI AIRPORT, BELAGAVI

VOBM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	155130N 0743704E 255.68 DEG/ 992 M from physical extremity of RWY 26	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	090 DEG/10KM from Belagavi city	
3	Aerodrome elevation and reference temperature	2489 FT / 36.0 DEG C	
4	Magnetic variation, date of information and annual change	1.41 DEG W (2010) /0.0333 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority of India, Civil Aerodrome Sambra, Belagavi Airport - 591124	
		Telephone:	(91) 8312562020
		Fax:	(91) 8312562030
		AFS:	VOBMYHYX VOBMYDYX
		Email:	apdvabm@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Gravity Model: EGM-08	

VOBM AD 2.3 OPERATIONAL HOURS

1.	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT, SUN + HOL: Nil
2.	Custom and immigration	NIL
3.	Health and sanitation	NIL
4.	AIS briefing office	NIL
5.	ATS reporting office (ARO)	As ATS
6.	MET Briefing office	As ATS (Available Class III)
7.	Air Traffic Service	Consult NOTAM for current ATS HR.
8.	Fuelling	As ATS
9.	Handling	In coordination with Airline Operator
10.	Security	AS ATS
11.	De-icing	NIL
12.	Remarks	1. Outside of ATS hours services are available on request with 48 HR prior notice to aerodrome. 2. The ATS approved hourly RWY traffic handling capacity as follows: Maximum number of arrivals and departures -10 Maximum number of arrivals only -06 Maximum number of departures only -06

VOBM AD 2.4 HANDLING SERVICES AND FACILITIES

1.	Cargo-handling facilities	In Coordination with Airline Operator
2.	Fuel/Oil types	JET A1 (Grade K-50) ATF Grade K-50 Jet A1
3.	Fuelling facilities/capacity	2 Bowser 9000 liters each
4.	De-icing facilities	NIL
5.	Hangar space for visiting aircraft	NIL
6.	Repair facilities for visiting aircraft	NIL
7.	Remarks	NIL

VOBM AD 2.5 PASSENGER FACILITIES

1.	Hotel(s) at or in the vicinity of aerodromes	In the city.
2.	Restaurant(s) at or in the vicinity of aerodromes	In the city.
3.	Transportation possibilities	Taxis in the City
4.	Medical Facilities	First aid at AD. Hospital in the city.
5.	Bank and post office at or in the vicinity of aerodromes	Banks: In the city. Post office: In the city.
6.	Tourist office	NIL
7.	Remarks	NIL

VOBM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1.	Aerodrome category for fire fighting	Within ATS HR: CAT-6
2.	Rescue equipment	Available as per category
3.	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is A320. 2. Primary responsibility for removal of disabled aircraft rests with the oncerned airline. 3. The airlines may contact ' Aerodrome coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: The Airport Director Office : 0831-2562020 ; Mobile: 9448477222 Email : apdvabm@AAI.AERO)
4.	Remarks	NIL

VOBM AD 2.7 SEASONAL AVAILABILITY CLEARING

1.	Types of clearing equipment	NIL
2.	Clearance priorities	NIL
3.	Remarks	NIL

VOBM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	Location: PARKING BAY 1 Elevation: 2466 FT
4	Location of VOR checkpoints	TWY C : 155133.20 N / 0743642.15E
5	Position of INS checkpoints	NIL
6	Remarks	1. New apron dimension: 158 M X 130 M 2. Isolated Aircraft Parking Position: 155121.435 N 0743658.918 E, ELEV: 2498 FT 3. Coordinates and elevations of Runway Holding Position: i. TWY A: 155132.833 N 0743646.894 E, ELEV: 2477 FT ii. TWY B: 155135.893 N 0743703.574 E, ELEV: 2485 FT iii. TWY C: 155132.004 N 0743642.375 E, ELEV: 2476 FT iv. TWY K: 155128.678 N 0743657.498 E, ELEV: 2491 FT v. TWY L 155127.239N 0743649.665 E, ELEV 2482 FT 4.Coordinates and elevations of Runway-Taxiway Intersection Point: i. TWY A: 155129.888 N 0743647.462 E, ELEV: 2481 FT ii. TWY B: 155132.955 N 0743704.173 E, ELEV: 2488 FT iii. TWY C: 155129.062 N 0743642.953 E, ELEV: 2479 FT iv. TWY K: 155131.624 N 0743656.922 E, ELEV: 2488 FT v. TWY L: 155130.189 N 0743649.093 E, ELEV: 2482 FT 5. Gravity Model: EGM-08

VOBM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1.	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Guidelines at Apron, Apron safety line and Aircraft stand markings, Apron Flood Lights available. Lighted Signage Boards: RWY 08/26, TWY A, B, C and K.
2.	RWY and TWY markings and LGT	RWY Markings: Designation, THR, Centerline, Edge, Touchdown zone and Aiming point RWY Lights: THR, Edge, Turning pad lights for RWY26 and RWY08 TWY Markings: Edge, Centerline & Holding Positions TWY Lights: Edge
3.	Stop bars	NIL
4.	Remarks	NIL

VOBM AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
26/TKOF 08/APCH	POLE	155101.2N 0743408.1E	2642 FT	NIL	Cellphone Mast

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
26/APCH 08/TKOF	POLE	155141.8N 0743737.6E	2453 FT	LGTD	Light Pole
26/APCH 08/TKOF	POLE	155142.6N 0743738.6E	2464 FT	LGTD	Light Pole
26/APCH 08/TKOF	POLE	155136.6N 0743738.7E	2455 FT	LGTD	Light Pole
26/APCH 08/TKOF	POLE	155142.9N 0743740.3E	2461 FT	LGTD	Light Pole
26/APCH 08/TKOF	TREE	155136.8N 0743807.7E	2522 FT	NIL	Group of Trees
26/APCH 08/TKOF	TREE	155147.1N 0743814.5E	2530 FT	NIL	Group of Trees
26/APCH 08/TKOF	TREE	155151.9N 0743816.5E	2550 FT	NIL	Group of Trees
26/APCH 08/TKOF	OTHER	155200.6N 0744141.5E	2998 FT	LGTD	Obstruction Light on Hill
26/APCH 08/TKOF	TREE	155140.0N 0743817.8E	2546 FT	NIL	Group Of Trees
26/APCH 08/TKOF	FENCE	155136.1N 0743738.9E	2454 FT	NIL	Airport Boundary Wall With Fencing On Top
26/APCH 08/TKOF	FENCE	155134.7N 0743738.9E	2454 FT	NIL	Airport Boundary Wall With Fencing On Top
In circling area and at AD	TREE	155126.9N 0743621.2E	2473 FT	NIL	Bushes
In circling area and at AD	TREE	155126.5N 0743620.1E	2474 FT	NIL	Bushes
In circling area and at AD	TREE	155127.2N 0743618.6E	2471 FT	NIL	Bushes
In circling area and at AD	TREE	155126.3N 0743618.3E	2474 FT	NIL	Bushes
In circling area and at AD	TREE	155120.8N 0743621.5E	2487 FT	NIL	Group of Trees
In circling area and at AD	OTHER	155128.0N 0743628.6E	2474 FT	LGTD	PAPI
In circling area and at AD	OTHER	155142.3N 0743737.2E	2456 FT	NIL	Airport Boundary Wall With Fencing On Top
In circling area and at AD	OTHER	155141.9N 0743737.3E	2465 FT	NIL	Mobile Road Traffic (Road Elev. 746.4 M+5.0 M Mobile Road Traffic)
In circling area and at AD	OTHER	155136.4N 0743738.4E	2464 FT	NIL	Mobile Road Traffic (Road Elev. 746.1 M+5.0 M Mobile Road Traffic)
In circling area and at AD	OTHER	155135.4N 0743727.8E	2463 FT	LGTD	PAPI
In circling area and at AD	POLE	155135.5N 0743733.4E	2465 FT	LGTD	Light Pole
In circling area and at AD	POLE	155142.7N 0743733.8E	2472 FT	LGTD	Light Pole
In circling area and at AD	POLE	155141.9N 0743734.4E	2459 FT	LGTD	Light Pole

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	POLE	155142.2N 0743735.3E	2472 FT	LGTD	Light Pole
In circling area and at AD	POLE	155136.0N 0743735.5E	2462 FT	LGTD	Light Pole
In circling area and at AD	POLE	155141.6N 0743736.0E	2458 FT	LGTD	Light Pole
In circling area and at AD	POLE	155142.3N 0743737.0E	2468 FT	LGTD	Light Pole
In circling area and at AD	POLE	155136.3N 0743737.1E	2458 FT	LGTD	Light Pole
In circling area and at AD	ANTENNA	155133.1N 0743726.9E	2496 FT	NIL	Met Antenna
In circling area and at AD	NAVAID	155133.6N 0743729.9E	2475 FT	LGTD	Glide Path Monitor Antenna
In circling area and at AD	NAVAID	155133.3N 0743728.2E	2506 FT	LGTD	Glide Path Main Antenna
In circling area and at AD	NAVAID	155133.2N 0743728.3E	2481 FT	LGTD	Glide Path DME
In circling area and at AD	BUILDING	155133.1N 0743728.2E	2471 FT	LGTD	Lighting Arrester on Glide Path Hut
In circling area and at AD	TREE	155131.7N 0743735.6E	2493 FT	NIL	Group Of Trees
In circling area and at AD	TREE	155043.5N 0743905.5E	2767 FT	NIL	Tree On Hill
In circling area and at AD	TREE	155109.2N 0743926.0E	2877 FT	NIL	Tree On Hill
In circling area and at AD	TREE	155046.0N 0743942.7E	2906 FT	NIL	Tree On Hill
In circling area and at AD	TREE	154957.7N 0743700.9E	2835 FT	NIL	Tree On Hill
In circling area and at AD	OTHER	155025.3N 0743557.8E	2640 FT	NIL	Cellphone Mast
In circling area and at AD	TREE	154950.1N 0743703.4E	2863 FT	NIL	Tree On Hill

VOBM AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1.	Name of the associated meteorological office	Bengaluru
2.	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3.	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Bengaluru 9 HR(00-09, 03-12, 06-15, 09-18, & 21-06)
4.	Availability of the trend forecast for the aerodrome and interval of issuance	NIL
5.	Information on how briefing and/or consultation is provided	Available
6.	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form (English)
7.	Charts and other information displayed or available for briefing or consultation	NIL
8.	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	NIL
9.	The air traffic services unit(s) provided with meteorological information	Belgavi ATC and ACS
10.	Additional information, e.g. concerning any limitation of service.	NIL.

VOBM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
08	79.27 DEG	2300 x 45 M	52/F/B/W/T Asphalt	THR: 155124.83N 0743619.90E RWY END: 155138.77N 0743735.85E
26	259.27 DEG	2300 x 45 M	52/F/B/W/T Asphalt	THR: 155138.77N 0743735.85E RWY END: 155124.83N 0743619.90E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 2467.0FT TDZ: 2483.0FT	-0.20%			2420 x 300 M
THR: 2452.0FT TDZ: 2487.0FT	0.20%			2420 x 300 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
90M x 90M			Gravity Model: EGM-08
90M x 90M			Gravity Model: EGM-08

VOBM AD 2.13 DECLARED DISTANCES

RWY Designation	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared) Remarks
1	2	3	4	5	6
08	2300	2300	2300	2300	Slope 1:50
26	2300	2300	2300	2300	Slope 1:50

VOBM AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
08	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG	NIL
26	180 M ABRIDGED APPROACH LIGHTING SYSTEM LIH	Green	PAPI LEFT/3.00 DEG	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2300 M 60 M White LIH	Red		NIL
	2300 M 60 M White LIH	Red		CAT1 Abridged 180 M

VOBM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On Tower Building, FLG W&G EV 2SEC As ATS HR
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	AVBL and lighted in signal area
		Anemometer	NIL
3	Taxiway edge and taxiway centre line lights;	Edge	Available
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary power supply to all lighting at AD. Switch-over time: 15 Sec.	
5	Remarks	NIL	

VOBM AD 2.16 HELICOPTER LANDING AREA

1.	Geographical coordinates of the geometric centre of touchdown and liftoff (TLOF) or of each threshold of final approach and take-off (FATO) area	--
2.	TLOF and/or FATO area elevation:	--
3.	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	--
4.	True bearings of FATO;	--
5.	Declared distances available	--
6.	Approach and FATO lighting;	--
7.	Remarks	Not Established

VOBM AD 2.17 ATS AIRSPACE

1.	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 152310N 0742631E; 153855N 0741620E; 161401N 0741630E then along the clockwise arc of a circle of 30NM radius centred on 155130N 0743704E to point of origin.
2.	Vertical limits	FL 85
3.	Airspace classification	D
4.	Call sign and language(s) of the air traffic services unit providing service;	Belagavi Tower, English
5.	Transition altitude	6000 FT
6.	Hours of applicability	HO
7.	Remarks	Belagavi Approach Control Unit is combined with Belagavi Aerodrome Control Tower.

VOBM AD 2.18 ATS COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	BELAGAVI TOWER	118.050 MHZ	
APP	BELAGAVI TOWER	119.200 MHZ	
TWR	Belagavi Tower	118.050 MHZ	
TWR	Belagavi Tower	119.200 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	AS ATS	1. Backup Frequency 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
		Functions of Approach Control Service provided by Aerodrome Control Tower.
	AS ATS	STANDBY
	As ATS	TWR & SMC Combined

VOBM AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic and type of supported operation for ILS/MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 26 CAT I	IBGM	111.300 MHz	HO
GP 26		332.300 MHz	HO
DME ILS 26	IBGM	CH50X	HO
DVOR/DME	BBM	112.100 MHz CH58X	H24

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
155123.0N 0743609.8E			
155133.3N 0743728.2E			Glide Angle 3 Deg
155133.2N 0743728.3E	2481 FT		
155125.7N 0743709.4E	2521 FT		Gravity Model: EGM-08

VOBM AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VOBM AD 2.21 NOISE ABATEMENT PROCEDURES

VOBM AD 2.22 FLIGHT PROCEDURES

1. Circling Approach is prohibited as the surrounding hills are not lighted

VOBM AD 2.23 ADDITIONAL INFORMATION

1. DGCA India has granted temporary exemption vide reference no. 2022/ASD/EXEMPTION/0000000318 dated 05-12-2022 for non-compliant width of runway strip for RWY 08/26 against provisions in CAR Section 4 Series B Part I Para 4.3.3 for the period up to 31.12.2025.

2. TWY L is exclusively for the use of FTO Trainer aircraft that are bearing AUW less than 5700 KG.

3. Intermediate Turn Pad lights not available.

4. Reduced declared distances intermediate/intersection departures:

RWY	TWY	TORA	TODA	ASDA	Remarks
08	A	1465M	1465M	1465M	
08	C	1602M	1602M	1602	Up to DH8D/ Q400
08	L	1416M	1416M	1416	
08	Intermediate Turnpad	1837	1837	1837	Day time only.

VOBM AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aerodrome Chart
2 Aircraft Parking/Docking Chart
3 Aerodrome Obstacle Chart – Type A (Obstacle Limitations) RWY 08
4 Aerodrome Obstacle Chart – Type A (Obstacle Limitations) RWY 26
5 Aerodrome Obstacle Chart - Type B
6 ILS (Z) Procedure RWY 26
7 ILS Y or LOC Y Procedure RWY 26 (27 November 2025)
8 Coding Table - ILS (Z) Procedure RWY 26
9 VOR Procedure RWY 08
10 Instrument Approach Chart - VOR Procedure RWY 26 (CAT A/B/C) (08 August 2024)
11 RNP Y Procedure RWY 08
12 Coding Table - RNP Y Procedure RWY 08
13 RNP Y Procedure RWY 26
14 Coding Table - RNP Y Procedure RWY 26
15 Instrument Approach Chart - RNP Z Procedure RWY 08 (CAT A/B/C) (LPV Only) (08 August 2024)
16 Tabular Description - RNP Z Procedure RWY 08 (08 August 2024)
17 FAS Data Block Table - RNP Z Procedure RWY 08 (08 August 2024)
18 Instrument Approach Chart - RNP Z Procedure RWY 26 (CAT A/B/C) (LPV Only) (08 August 2024)
19 Tabular Description - RNP Z Procedure RWY 26 (08 August 2024)
20 FAS Data Block Table - RNP Z Procedure RWY 26 (08 August 2024)

VOBM AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration

1	2	3