AD 2. AERODROMES

VOVI AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOVI - BHOGAPURAM INTERNATIONAL AIRPORT

VOVI AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	175826N 0833020E Abeam Apron between TWY B7 and TWY B8	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	Southeast of Vizianagaram, 25 km from Vizianagaram.	
3	Aerodrome elevation and reference temperature	188 FT / 33.7 DEG C	
4	Magnetic variation, date of information and annual change	1.00 DEG W (2010) /0.016 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	GMR Vishakhapatnam International Airport Ltd. 10-1-43, Flat No. 202, Second Floor, Siripuram Fort, Siripuram, Visakhapatnam – 530003, Andhra Pradesh.,	
		Telephone:	+91-856-2220506
		Fax:	NA
		AFS:	VOVIZTZX
		Email:	ceo.gvial@gmrgroup.in website: gmraero.com/GVIAL
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Aerodrome Reference Code: 4E Elevations in EGM-08	

VOVI AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON - SAT: 0400-1230 UTC (0930-1800 IST) (Except 2nd, 4th and 5th SAT)
2	Custom and immigration	H24
3	Health and sanitation	H24
4	AIS briefing office	H24
5	ATS reporting office (ARO)	H24
6	MET Briefing office	H24
7	Air Traffic Service	H24
8	Fuelling	H24
9	Handling	H24
10	Security	H24
11	De-icing	NIL
12	Remarks	NIL

VOVI AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Available Handling Capacity: 25,000 MT p.a. Managed by GMR Airports Limited

2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	Fuelling agency – HPCL Fuelling with Fuel bowsers & Hydrant Total Capacity: 8385 KL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VOVI AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city.
2	Restaurant(s) at or in the vicinity of aerodrome	At Airport and in the city.
3	Transportation possibilities	Taxis and Buses.
4	Medical Facilities	At Airport
5	Bank and post office at or in the vicinity of aerodrome	Banks: Banks ATM at Airport Post office: Post Office In the city
6	Tourist office	At Airport
7	Remarks	NIL

VOVI AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-9
2	Rescue equipment	Available as per category
3	Capability for removal of disabled aircraft	1. The critical aircraft for VOVI is Code E. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Aerodrome Coordinator: Head-ARFF Mob: 9538882047 Email: Ramesh.BabuR@gmrgroup.in
4	Remarks	NIL

VOVI AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VOVI AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking / Docking Charts
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking / Docking Charts
3	Location and elevation of altimeter checkpoints	All the aircraft stands
4	Location of VOR checkpoints	Taxi Holding position A3, A9 & A10
5	Position of INS checkpoints	NIL
6	Remarks	NIL

VOVI AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Illuminated stand identification boards displaying stand numbers and stand co-ordinates are available for stands 11-24 Taxiing guidance signs are provided on all TWY intersections and straight sections. Advanced Visual Docking Guidance System installed on stands 12L, 12, 12R, 13, 14, 20, 21 & 22 to follow AVDGS for parking. Marshalling guidance available for parking in assigned stands through Authorized Ground Handling Agents/Airlines.
2	Runway and taxiway markings and lights	RWY Markings Runway Transverse stripe, Runway Designation, Runway Threshold, Runway Touchdown zone, Runway Centre line, Runway Aiming Point, Runway Side stripe markings. Lights Runway Threshold, Runway Edge, Runway Centerline & Runway End lights. TWY Markings Taxiway Edge, Taxiway Centre line Runway Holding positions Enhanced Taxiway center line markings. Lights Taxiway edge Lights, Taxiway Centre lights, Runway Guard Lights, Intermediate Holding Point, No entry Bar lights.
3	Stop bars (if any)	Available at TWY A3, A9 & A10
4	Remarks	Mandatory & Information signs provided.

VOVI AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
28/TKOF 10/APCH	NATURAL HIGHPOINT	175936.7N 0832102.7E	843 FT	NIL	Hill Top
28/TKOF 10/APCH	TREE	175940.8N 0832054.7E	693 FT	NIL	Tree on Hill
28/TKOF 10/APCH	TREE	175944.2N 0832046.9E	645 FT	NIL	Tree on Hill
In circling area and at AD	POLE	175821.3N 0832915.7E	152 FT	LGTD	Windsock, Obstruction Light Top: 46.28 M, Windsock Top: 46.00 M.
In circling area and at AD	OTHER	175826.3N 0832916.6E	131 FT	NIL	PAPI

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	NAVAID	175802.2N 0833100.0E	196 FT	LGTD	GP Monitor Antenna: Lightning Arrester Top: 59.85 M, Obstruction Light Top: 59.66 M, Antenna Top: 59.27 M.
In circling area and at AD	SIGN	175806.3N 0833106.5E	186 FT	NIL	Sign Board
In circling area and at AD	SIGN	175824.4N 0832927.5E	136 FT	NIL	Sign Board
In circling area and at AD	NAVAID	175802.9N 0833056.2E	228 FT	LGTD	GP Antenna: Lightning Arrester Top: 69.58 M, Obstruction Light Top: 69.46 M, Antenna Top: 68.93 M.
In circling area and at AD	NAVAID	175802.8N 0833056.2E	202 FT	LGTD	GP DME Antenna: Lightning Arrester Top: 61.70 M, Obstruction Light Top: 61.37 M, Antenna Top: 61.24 M.
In circling area and at AD	BUILDING	175802.7N 0833055.9E	184 FT	NIL	Restroom
In circling area and at AD	BUILDING	175802.9N 0833055.9E	184 FT	NIL	GP Hut
In circling area and at AD	POLE	175803.4N 0833054.1E	197 FT	LGTD	Windsock, Obstruction Light Top: 60.13 M, Windsock Top: 59.86 M.
In circling area and at AD	OTHER	175806.4N 0833052.5E	175 FT	NIL	PAPI
In circling area and at AD	SIGN	175809.2N 0833050.5E	173 FT	NIL	Sign Board
In circling area and at AD	SIGN	175815.3N 0833017.1E	154 FT	NIL	Sign Board
In circling area and at AD	SIGN	175816.8N 0833008.7E	151 FT	NIL	Sign Board
In circling area and at AD	SIGN	175822.9N 0832935.6E	139 FT	NIL	Sign Board
In circling area and at AD	OTHER	175756.5N 0833107.4E	246 FT	NIL	Mobile Road Traffic (Road Elev: 69.90 M + 5 M Mobile Traffic)
In circling area and at AD	OTHER	175757.4N 0833104.4E	238 FT	NIL	Mobile Road Traffic (Road Elev:67.65 M + 5 M Mobile Traffic)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	POLE	175758.1N 0833102.5E	226 FT	NIL	Light Pole
In circling area and at AD	POLE	175758.3N 0833102.1E	225 FT	NIL	Light Pole
In circling area and at AD	POLE	175758.5N 0833101.6E	224 FT	NIL	Light Pole
In circling area and at AD	POLE	175758.6N 0833101.1E	222 FT	NIL	Light Pole
In circling area and at AD	POLE	175758.8N 0833100.6E	222 FT	NIL	Light Pole
In circling area and at AD	POLE	175804.9N 0833035.9E	179 FT	NIL	Light Pole
In circling area and at AD	POLE	175805.3N 0833033.4E	178 FT	NIL	Light Pole
In circling area and at AD	OTHER	175805.8N 0833030.1E	184 FT	NIL	Mobile Road Traffic (Road Elev: 51.00 M + 5 M Mobile Traffic)
In circling area and at AD	POLE	175806.0N 0833029.4E	176 FT	NIL	Light Pole
In circling area and at AD	POLE	175806.4N 0833026.8E	176 FT	NIL	Light Pole
In circling area and at AD	OTHER	175806.8N 0833022.6E	183 FT	NIL	Mobile Road Traffic (Road Elev: 50.81 M + 5 M Mobile Traffic)
In circling area and at AD	POLE	175811.1N 0833001.9E	165 FT	NIL	Camera Pole
In circling area and at AD	OTHER	175814.5N 0832944.1E	159 FT	NIL	Mobile Road Traffic (Road Elev: 43.57 M + 5 M Mobile Traffic)
In circling area and at AD	OTHER	175817.3N 0832925.9E	161 FT	NIL	Mobile Road Traffic (Road Elev: 43.99 M + 5 M Mobile Traffic)
In circling area and at AD	POLE	175818.0N 0832923.5E	152 FT	NIL	Light Pole
In circling area and at AD	POLE	175817.9N 0832922.3E	155 FT	NIL	Camera Pole
In circling area and at AD	TREE	175651.6N 0832906.0E	788 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175652.9N 0832855.4E	888 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175652.0N 0832843.9E	741 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175642.8N 0832846.8E	853 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175640.7N 0832822.5E	778 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175642.8N 0832815.3E	840 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175630.1N 0832809.7E	788 FT	NIL	Tree on Hill

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	TREE	175646.3N 0832754.6E	658 FT	NIL	Tree on Hill
In circling area and at AD	TREE	175653.4N 0832746.0E	534 FT	NIL	Tree on Hill
In circling area and at AD	BUILDING	175842.7N 0832958.9E	345 FT	NIL	ATC Tower (U/C), Antenna Top - 105.12 M, Antenna Top - 105.11 M, Antenna Top - 104.96 M, Antenna Top - 104.96 M, Airports Authority of India AIP Supplement 80/2026 Page 8 of 40 Antenna Top - 104.93 M, Antenna Top - 104.86 M, ATC Tower Top - 100.97 M.

VOVI AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	AMS, Bhogapuram
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	AMS, Bhogapuram AMO, RGIA, Shamshabad Long duration TAFs valid for 36 hours and issued every 12 hours Short duration TAFs valid for 24 hours and issued every 6 hours
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend Trend Forecast appended to METAR
5	Information on how briefing and/or consultation is provided	Round the clock through Online Briefing System (OLBS)
6	Types of flight documentation supplied and language(s) used in flight documentation	Wind/temperature charts of different flight levels and sig. Weather charts as available in OLBS. English.
7	Charts and other information displayed or available for briefing or consultation	Charts available in OLBS
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	MET Report displays installed at ATC tower, Met Briefing Room and Approach Radar.
9	The air traffic services unit(s) provided with meteorological information	ATC
10	Additional information, e.g. concerning any limitation of service.	Aviation Weather Observation Systems available for both Runways 10 & 28. Integrated panel available at Met Briefing Room and Control Tower. Instrumental RVR reading for Runway 10 & 28 available through Present Visibility Sensor.

VOVI AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
10	100.77 DEG	3800 x 45 M	820/F/C/W/T Asphalt	THR: 175827.41N 0832903.84E RWY END: 175804.32N 0833110.66E
28	280.77 DEG	3800 x 45 M	820/F/C/W/T Asphalt	THR: 175804.32N 0833110.66E RWY END: 175827.41N 0832903.84E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 120.4FT TDZ: 137.7FT	0.54%	NIL	Dimensions of clearway: Not AvailableNIL	3920 x 280 M
THR: 188.3FT TDZ: 188.3FT	0.54%	NIL	Dimensions of clearway: Not AvailableNIL	3920 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M	Not available	YES	1. RWY PCR: 0-250 M: 1220/R/C/W/T 250-3600M: 820/F/C/W/T 3600-3800 M: 1220/R/C/W/T 2. Gravity Model: EGM 08
240M x 90M	Not available	YES	1. RWY PCR: 0-200 M: 1220/R/C/W/T 200-3550M: 820/F/C/W/T 3550-3800 M: 1220/R/C/W/T 2. Gravity Model: EGM 08 3. Slope of runway and associated stop way: (-) 0.544 %

VOVI AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
10	3800	3800	3800	3800	NIL
28	3800	3800	3800	3800	NIL

VOVI AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
10	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (21.28M)	NIL
28	CAT I 900 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (21.28M)	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
3800 M 30 M LIH White	3800 M 60 M White LIH	Red	NIL	1. RCL – White from threshold to the point 900M from the RWY end, alternate Red and white from 900M to 300M from the RWY end and Red from 300M to the RWY end. 2. RWY Edge lights Last 600M Yellow.
3800 M 30 M LIH White	3800 M 60 M White LIH	Red	NIL	1. RCL – White from threshold to the point 900M from the RWY end, alternate Red & white from 900M to 300M from the RWY end and Red from 300M to the RWY end. 2. RWY edge lights last 600M Yellow.

VOVI AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Top of Control Tower Green and White Flashing FPM 24 / 12 RPM
		IBN	Not Available
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Available
		Anemometer	Anemometer Located at ATC Two Wind Direction Indicator are provided & are illuminated. Wind Direction Indicators are provided on southern side of runway close to Glide path hut RWY 28 and abeam PAPI RWY 10
3	Taxiway edge and taxiway centre line lights;	Edge	Taxiway edge Lights are provided at the taxiway turnings only. No Taxiway edge Lights are provided in the Straight Section of taxiways.
		Centre Line	Available
4	Secondary power supply including switch-over time;	UPS back up available. Switch over time less than Two Seconds	
5	Remarks	DG Yard back up available. 1800 KW X 04 numbers Change Over Time: 15 Seconds	

VOVI AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	Nil

VOVI AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 175501N 0830604E; 174909N 0833937E; 175647N 0840145E then along the counter clockwise arc of a circle of 30NM radius centred on 175826N 0833020E to 180529N 0825944E to point of origin.
2	Vertical limits	5500 FT AMSL
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Bhogapuram TWR / Bhogapuram Approach, English
5	Transition altitude	7000 FT
6	Hours of applicability	HO
7	Remarks	NIL

VOVI AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available	Logon address, as appropriate	Hours of operation	Remarks
1	2	3	4	5	6	7
APP	Bhogapuram Approach	120.050 MHZ			HO	1. Backup Frequency
APP	Bhogapuram Approach	124.400 MHZ			HO	1. Main Frequency
TWR	Bhogapuram TWR	118.325 MHZ			HO	1. Main Frequency
TWR	Bhogapuram TWR	119.025 MHZ			HO	1. Backup FREQ 2. Combined Backup Frequency for TWR/SMC
ATIS	Bhogapuram Information	126.275			HO	1. NIL
ALRS	Bhogapuram emergency	121.500 MHZ			HO	1. Emergency Frequency
SMC	Bhogapuram Ground	121.800 MHZ			HO	1. Main Frequency

VOVI AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 28 CAT I	IBGP	108.700 MHz	H24
GP 28		330.500 MHz	H24
DME ILS 28	IBGP	CH24X	H24
DVOR/DME	BHZ	115.350 MHz CH100Y	H24

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
175829.4N 0832853.2E			i) Outer coverage within plus minus 10 DEG FM course line- satisfactory up to 25 NM above 3000 FT height above threshold (HAT), satisfactory up to 23nm above 2500ft height above threshold (HAT), satisfactory up to 20nm above 2000ft height above threshold (HAT). ii) Inner coverage within plus minus 35 DEG FM course line- satisfactory up to 17 NM above 2000 FT height above threshold (HAT). iii) Reduced outer coverage within plus minus 10 DEG FM course line- satisfactory up to 18 NM above 2000 FT height above threshold (HAT). iv) Reduced inner coverage within plus minus 35 DEG FM course line- satisfactory up to 10 NM above 2000 FT height above threshold (HAT).
175802.9N 0833056.2E			1. Glide Angle 3 degree.
175802.8N 0833056.2E	201 FT		1. Co-located with GP and elevation in EGM-08
175803.6N 0833132.7E	194 FT		1. DME Collocated with DVOR 2. Gravity Model; EGM 08

VOVI AD 2.20 LOCAL AERODROME REGULATIONS

1) PUSHBACK AND START-UP PROCEDURES

i) Aircraft on all stands at Bhogapuram International Airport shall be pushed back from the stand towards the taxilane centreline, taking into account the taxi route to be followed.

ii) Bhogapuram Ground (frequency 121.800 MHz, or any alternate frequency) shall be contacted for pushback and start up permission only after the Pilot-In- Command has established that the aircraft is 'ready' for pushback/start up.
Note: For the purpose of clarity, 'ready' means all doors of the aircraft are closed, the Passenger Boarding Bridge (PBB) / Step Ladder (s) are disconnected / withdrawn, the tug is connected to the aircraft and the ground engineer is in position and in contact with the Pilot-In-Command (PIC).

iii) On receiving the above-mentioned information, ATC will allow pushback and start-up of the aircraft depending on the traffic.

iv) Simultaneous push back from adjacent stands is not permitted.
Note: Adjacent stands shall include associated 'L'(left) and 'R' (right) stands except wherever specified otherwise.

v) The pilot shall adhere strictly to SOP by aircraft manufacturer/ relevant operational manuals for starting up engine(s) at idle power or at breakaway locations.

vi) Ground crew must strictly follow the safety instructions at all times on hazard zones set out by aircraft manufacturer / relevant operational manuals.

vii) Deployment of wing walkers/wing guards by airline is mandatory for arrival of aircraft on to stand and prior to undertaking pushback from any stand at Bhogapuram International Airport.

viii) On receipt of the clearance, the PIC shall read back the pushback clearance given by ATC, then co-ordinate with the ground crew for the pushback and start-up of the aircraft. The ground crew must ensure that the area in the front, behind and around the aircraft is clear of personnel, vehicles, equipment and other obstructions before commencing pushback and start-up of the aircraft.

ix) No engine start-up is allowed on stands before pushback, unless technically essential and coordinated with ground crew. However, engine start is strictly prohibited on stands 11R, 12L, 12R, 13, 21, and 22 before pushback due to safety risks.

x) Single-engine start at idle power may be permitted on other stands with ground crew coordination and only after ensuring the hazard zone is clear.

xi) Cross-bleed start is not allowed during pushback or pull-ahead operations. Cross-bleed start may begin only after the aircraft is aligned with the TXL centreline and the ground crew has confirmed the area is hazard-free. Ground crew must always follow aircraft manufacturer's hazard zone instructions and applicable operational manuals.

xii) Ground crew of aircraft intending to do a cross-bleed start must assess the clearance behind and in-front of aircraft and in case they feel that there is insufficient clearance, they shall request SMC for repositioning the aircraft to a position from where cross bleed start can take place. As a broad guideline a separation distance equivalent to 3 (three) aircraft length should be clear behind the aircraft so that there is no jet blast impact behind the aircraft due to cross bleed start.

xiii) Vehicle or movement of personnel is NOT permitted behind the aircraft once the anti-collision beacons of the aircraft have been switched ON.
xiv) For aircraft stands without dedicated pushback lines, the stand lead-in line may be used for pushback guidance.
xv) Pilots shall adhere to the pushback and start-up procedures and will use minimum breakaway power.
xvi) Simultaneous pushback (Code C Aircraft only) can be permitted in alternate stands. All aircraft shall pull forward till abeam lead in line of respective stand.
xvii) Aircraft on Stands 11L, 11 & 11R shall pushback on TXL B7 facing east till pushback limit line and pull forward till abeam lead-in line of stand no. 11R for engine start up.
xviii) No aircraft on stand 11L, 11, 11R, 12L, 12, 12R, 13 & 14 shall start the aircraft engine while another aircraft is pushing back from these stands.
xix) Aircraft on stand no. 12L, 12, 12R, 13 & 14 shall pushback on TXL B7 facing east till abeam lead-in line of stand no. 11R for engine start up.
xx) No Simultaneous pushback is permitted on Stands 11L, 11R, 12L, 12R, 13 & 14.
xxi) When aircraft is parked on L or R stand of 11 & 12; centre stand of respective MARS configuration is not available or when aircraft parked on centre stand of 11 & 12; L or R stand of respective MARS configuration is not available.
xxii) Aircraft on stand no. 17, 18 & 19 shall pushback on to taxilane B8 facing south and pull abeam respective stand for engine start.
xxiii) All aircraft on stands 20, 21 & 22 shall deep pushback on taxilane B8 facing west till abeam lead-in line of stand no. 23 for engine start up.
xxiv) Aircraft on stand no. 20, 21 & 22 is not permitted to pushback if the aircraft on stand no. 19 is already pushed back.
xxv) Aircraft on stands 23 & 24 shall pushback on taxilane B8 facing west till pushback limit line and pull forward till abeam stand no. 23 for engine start up.
xxvi) Aircraft on stands 80 & 81 shall pushback on TXL C facing west till pushback limit line and pull forward abeam lead-in line of stand no. 80 for engine start up.

2) **OTHER RESTRICTIONS:**

i) Entry and exit for east apron stands (17 to 24) will be from TXL B8 only.
ii) Entry and exit for west apron stands (11 to 16) will be from TXL B7 only.
iii) Entry and exit for NSOP apron stands (80 & 81) will be from TXL B2 & C only.
iv) No tail of stand road is provided. No GSE/ vehicle belonging to other airline/ GHA is permitted to cross behind aircraft tail.
v) No GSE/ vehicle shall be left on the stand after completion of the turnaround activity/ departure of aircraft.
vi) GSE/ vehicles shall not stop/ park on the White hatch marking areas marked in between the stands.
vii) No GSE/ vehicle is allowed to operate beyond apron end safety line.
viii) No GSE/ vehicle is permitted to park on the MARS stands before the arrival of aircraft.
ix) No GSE/ Vehicle is permitted to park inside the ERA.
x) No vehicle with height of more than 4 mtrs is permitted to go below the FLB of PBB.
xi) In case aircraft overshoots TWY A3 while landing from RWY 28, the aircraft shall backtrack and vacate runway via TWY A3.

Note: TWY A1 & A2 are not provided in the first phase.

xii) All the aircraft requiring lineup for RWY 10 shall enter Runway via TWY A3 and back track if full length required for departure.
xiii) No dedicated engine ground run point is established at Bhogapuram International Airport. In case of exigency requiring high power engine ground run, the portion of Taxiway A between TWY A9 & A10 will be used for high power engine ground run.

VOVI AD 2.21 NOISE ABATEMENT PROCEDURES

1. GENERAL

Noise abatement procedures are implemented in accordance with ICAO Annex 16, Volume I and DGCA requirements to minimize the impact of aircraft noise on surrounding area without compromising safety. Safety of flight operations shall take precedence over noise abatement at all times.

2. RUNWAY USE

Our preferred runway is 28 based on wind, runway surface, and operational conditions permit, preferential runway use shall be applied to minimize overflight of noise-sensitive areas.

3. DEPARTURE PROCEDURES

i) Operators shall comply with ICAO PANS-OPS Doc 8168 Noise Abatement Departure Procedures (NADP 1 or NADP 2) as per aircraft type and Aerodrome SOPs.
ii) Use minimum thrust consistent with safe operation.
iii) Reverse thrust after landing shall be limited to idle or minimum practical setting, consistent with safety.

4. ARRIVAL PROCEDURES

i) Avoid level flight segments during approach unless required by ATC or safety considerations.

5. ENGINE GROUND OPERATIONS

i) APU usage shall be minimized; fixed ground power and pre-conditioned air should be used where available.
ii) High-power engine ground runs shall be carried out only in designated areas and during approved time slots.

6. RESTRICTIONS

i) No scheduled operations of Chapter 2 aircraft between 2200 IST and 0600 IST.
ii) Noise monitoring will be conducted to ensure compliance.

VOVI AD 2.22 FLIGHT PROCEDURES

I) LOW VISIBILITY PROCEDURES:

1. LOW VISIBILITY PROCEDURE RWY 28

i) Low Visibility Procedures have been developed for Bhogapuram International Airport, to accommodate/ permit low visibility CAT I operations for RWY 28 and LVTO (Low visibility Take Off) for RWY 10 and 28 in Visibility/ RVR less than 800m/ 550m respectively.
ii) As RCL lights are available at Bhogapuram International Airport, these procedures will be applicable for take-off in Visibility/RVR below 800m/550m respectively but not below 300m as ASMGCS is not available

2. GENERAL:

i) Bhogapuram International Airport is equipped with CAT 1 ILS system for RWY 28.
ii) Runway and Taxiway centerline lights are available which can be used during LVP.
iii) The following AGL shall be available to the required standard to support LVP operations:
a) Aeronautical ground lighting System consisting of Runway (RWY) edge lights, RWY centerline lights, RWY end lights, Taxiway (TWY) edge lights, Stop bar lights, Approach lights.
b) The critical lighting system RWY edge, RWY centerline and RWY end lights are supported by UPS for zero switch over time.
c) Real time RVR reporting System (available for both RWYs). In case RVR equipment is unserviceable, manual RVR will be made available.
d) In case of main power failure, Switchover time for standby power for Aeronautical ground lighting system excluding critical lighting system is a maximum of 15 seconds.

3. SAFEGUARDING PROCEDURES:

i) Duty Air Traffic Control Officer (DATCO) will initiate and co-ordinate with all the concerned agencies for completion of Safeguarding Procedures before implementation of LVPs.

The Safeguarding Procedures (SP) shall be initiated when: -

a) The visibility/ RVR is less than 1200m and visibility/ RVR is forecasted to deteriorate to 800m or less; and/or

b) The cloud ceiling is less than 400ft and forecast to fall to 200ft or less.

ii) Safeguarding Procedures include:

a) Stopping all maintenance works on the manoeuvring area and the associated runway/taxiway strips as well as removal of all men and mobile equipment from the said area.

b) Ensuring availability of secondary power supply (DG)

Note: The lights may continue to operate on main power supply during Safeguarding Procedures. Whenever LVP is to be implemented, all lights shall be put on Standby Power Supply (DG set/UPS). This operation needs to be completed before LVP is implemented.

c) Serviceability of Aeronautical Ground Lights

Note: The Aeronautical Ground Lights must have been inspected during the hour preceding implementation of LVP and thereafter once every two-hour period. The lighting inspections should be accorded priority.

d) Positioning of 1 CFT each at the two predetermined positions (in front of main fire station and in front of satellite fire station on fire access road);

e) Availability of Follow-Me services for all non-scheduled aircraft.

iii) Actions by various agencies during LVP:

a) The duty MET Officer shall keep the duty ATCO informed of any change in Visibility/RVR.

b) All the towing operations shall be suspended during low visibility procedures.

c) The number of vehicles operating on the manoeuvring area shall be restricted to bare minimum.

d) Only those vehicles capable of two-way communication with ATC (fitted R/T set) shall be operated on the manoeuvring area. In case of extreme emergency, a vehicle without two-way communication capability may be permitted provided it is escorted by “Follow-Me” vehicle with two-way communication capabilities.

e) Since ASMGCS is not available, aircraft movement shall be restricted to two aircraft at a time on the apron and one aircraft at a time in the manoeuvring area.

f) Once the “Low Visibility Procedures in force” the same shall be included in the DATIS.

g) DATCO shall stop all flight operations whenever RVR falls below 350m.

h) P&E team shall continuously monitor the main and standby power during LVP operations and report any unserviceability to ATC immediately.

4. TERMINATION OF LOW VISIBILITY PROCEDURES:

i) When visibility/ RVR improves to 800m/550m or more and the cloud ceiling is 200ft or higher and trend is for improvement, DATCO would terminate operations of LVP. DATCO may obtain advice from Duty Met Officer regarding improvement in weather conditions before the termination of LVP.

ii) The DATCO will intimate all concerned agencies regarding the termination of LVP operations.

iii) On cancelling LVP, following message shall be included in subsequent ATIS broadcasts, “Low Visibility Procedures cancelled”.

iv) If SPs are in force and LVP are terminated, and if the visibility/ RVR improves and is more than 1200m and/ or cloud ceiling is 400ft or higher and both are forecast to remain above the required SP criteria, DATCO may cancel the Safeguarding Procedures.

5. ACTIONS BY OTHER AGENCIES (AIRLINES, REFUELLING COMPANIES, ETC.):

i) All the agencies shall ensure that staff and drivers are suitably trained on Low Visibility Operations.

ii) A refresher program for ATCOs and personnel responsible for airside operations shall be conducted every year.

iii) All agencies operating in the operational area shall ensure that only those vehicles that are absolutely essential for aircraft operations operate in the operational area during the periods of low visibility. The drivers of these vehicles shall keep a look out for taxiing aircraft and other vehicles to prevent accidents.

iv) All vehicles must have their obstruction and hazard lights ‘ON’ during Low Visibility Procedures operations.

v) All instructions/ sign boards provided for vehicular movement area/ service roads, must be followed while operating in the operational area.

VOVI AD 2.23 ADDITIONAL INFORMATION

1) Preferred exit Taxiway is RET A5 for RWY 28 and RET A7 for RWY 10.

2) Both the RET A5 & A7 are compatible for Code-E aircraft.

3) The distance of RET A5 from threshold RWY 28 is 1923m.

4) The distance of RET A7 from threshold RWY 10 is 2248m.

VOVI AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart
2. Aerodrome Chart- Hot Spot
3. Aircraft Parking/Docking Chart – Main Apron
4. Aircraft Parking/Docking Chart – NSOP Apron
5. Aircraft Parking/Docking Chart – Isolated Aircraft Parking Position
6. Aerodrome Obstacle Chart Type- A (Operating Limitations), RWY 10
7. Aerodrome Obstacle Chart Type- A (Operating Limitations), RWY 28
8. Aerodrome Obstacle Chart - Type- B
9. LDA Chart – RWY 10
10. LDA Chart – RWY 28
11. Precision Approach Terrain Chart RWY 10
12. Precision Approach Terrain Chart RWY 28
13. Pushback Procedure Chart-Stand 11-12
14. Pushback Procedure Chart-Stand 11L-11R-12L-12R
15. Pushback Procedure Chart-Stand 13-16
16. Pushback Procedure Chart-Stand 17-19
17. Pushback Procedure Chart-Stand 20-24
18. Pushback Procedure Chart-Stand 80-81
19. Taxiway Compatibility Chart
20. TORA Chart – Departure RWY 10
21. TORA Chart – Departure RWY 28
22. Instrument Approach Chart – ILS Y OR LOC RWY 28
23. Instrument Approach procedure – VOR RWY 10
24. Instrument Approach procedure – VOR RWY 28
25. VOVI-ATC-SMAC (29 October 2026)

VOVI AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3