AD 2. AERODROMES

VOCL AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOCL - CALICUT AIRPORT, CALICUT

VOCL AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	110816N 0755702E MAG BRG 096.46 DEG/859M from physical extremity of RWY 10	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	127 DEG, 28KM from Calicut Railway Station	
3	Aerodrome elevation and reference temperature	343 FT / 31.0 DEG C	
4	Magnetic variation, date of information and annual change	2.11 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airport Director, Airports Authority of India, Calicut International Airport, Karipur-673647.,	
		Telephone:	(91) 4832719400 (91) 483 2719500 (91) 9562406400 (91) 9847245543
		Fax:	(91) 4832711406
		AFS:	VOCLYHYX
		Email:	apd_calicut@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Elevation in EGM 08	

VOCL AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT/SUN/HOLIDAY: NIL.
2	Custom and immigration	As ATS
3	Health and sanitation	H24
4	AIS briefing office	H24
5	ATS reporting office (ARO)	H24
6	MET Briefing office	H24
7	Air Traffic Service	H24
8	Fuelling	H24
9	Handling	H24
10	Security	H24
11	De-icing	NIL
12	Remarks	1. The ATS approved hourly RWY traffic handling capacity is as follows: Maximum number of arrivals and departures -08 Maximum number of arrivals only -06 Maximum number of departures only -06 2. Non SKED OPR to obtain positive CLR Atleast 24 HR in advance before operating FLT to Calicut AP due acute shortage of ACFT stands.REQ for permission to be sent thru email to: slots.calicut(a)aai.aero

VOCL AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Available
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	BPCL: 5 Bowsers (75 KL), 3 Storage Tanks outside AD(600KL). IOCL: 6 Bowsers (137 KL), Storage Tanks (740KL). HPCL: 6 Bowsers (130 KL), Storage Tanks (800KL). RELIANCE LTD: 6 Bowsers (108 KL), 2 Storage Tanks outside AD(860KL).
4	De-icing facilities	Not applicable
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	At Calicut International Airport, Calicut, Ground Handling Service provided by: 1. Air India Airport Services Limited, Email: ccj.nodalofficer@aiasl.in; ccj.gh@aiasl.in Contact No: 0483 2714000 2. Indothai Calicut Private Limited, E-mail: indothaiccj@indothai.in; sudhirshukla@indothai.in Contact Nos.: +91 8800317408, +91 9843488923

VOCL AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Near the AD and in the city.
2	Restaurant(s) at or in the vicinity of aerodrome	At AD, near the AD and in the city.
3	Transportation possibilities	Taxis from the AD and state transport buses.
4	Medical Facilities	Doctor on request & first aid at AD. Hospitals near AD & in the city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: At AD. Open from 1030 Hrs to 1500 Hrs Post office: open with AD Administration HR.
6	Tourist office	Tourist information counter at AD.
7	Remarks	NIL

VOCL AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-8 CAT VIII.
2	Rescue equipment	Available as per category
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is A321. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director, AAI Calicut International Airport Phone No: +914832719401 Mobile : +9195624 06400 Email: apd_calicut@aai.aero
4	Remarks	NIL

VOCL AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VOCL AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

<table>
<tr><td>1</td><td>Designation, surface and strength of aprons</td><td colspan="5">Refer Aircraft Parking/Docking Chart</td></tr>
<tr><td>2</td><td>Designation, width, surface and strength of taxiways</td><td colspan="5">Refer Aircraft Parking/Docking Chart</td></tr>
<tr><td>3</td><td>Location and elevation of altimeter checkpoints</td><td colspan="5">Location Apron Elevation 334FT</td></tr>
<tr><td>4</td><td>Location of VOR checkpoints</td><td colspan="5">TWY-A 110817.00N 0755659.19E / ELEV: 335 FT</td></tr>
<tr><td>5</td><td>Position of INS checkpoints</td><td colspan="5">NIL</td></tr>
<tr><td rowspan="6">6</td><td rowspan="6">Remarks</td><td colspan="5">1. Coordinates of Taxi Holding Position
i. TWY A: 110816.667N 0755659.125E / ELEV: 335FT
ii. TWY B: 110815.863N 0755703.318E / ELEV: 335FT
iii. TWY C: 110815.017N 0755707.777E / ELEV: 336FT
iv. TWY D: 110812.494N 0755648.889E / ELEV: 323FT
Geoid Model Used: EGM08
2. RWY/TAXIWAY INTERSECTION COORDINATES/ ELEV
TWY A: 110813.71N 0755658.55E/ ELEV: 336FT
TWY B: 110812.99N 0755702.74E/ ELEV: 338FT
TWY C: 110812.06N 0755707.20E/ ELEV: 341FT
TWY D: 110815.43N 0755649.46E/ ELEV: 328FT</td></tr>
<tr><td colspan="5">3. Location of TWY’s from RWY 28 THR/Additional information of TWY’s</td></tr>
<tr><td></td><td>TWY A</td><td>TWY B</td><td>TWY C</td><td>TWY D</td></tr>
<tr><td>Distance</td><td>2130M</td><td>1990M</td><td>1829M</td><td>2377M</td></tr>
<tr><td>Length</td><td>102M</td><td>102M</td><td>102M</td><td>175M</td></tr>
<tr><td>Shoulder on either side</td><td>10.5M</td><td>10.5M</td><td>10.5M</td><td>10.5M</td></tr>
<tr><td></td><td></td><td colspan="5">4. Additional Information : Code D and Code E aircraft operations remains suspended till such time all recommendations and additional recommendations made by the Committee along with mitigation measures for safe Code C aircraft operations are put in place</td></tr>
</table>

VOCL AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiing guidance signs provided at all intersections and taxi holding PSN. Aircraft stand markings, apron side strip marking and guidelines provided on the Apron & isolation parking stand. Visual Docking Guidance System – Available for all aircraft parking stands except stand 12A.
2	Runway and taxiway markings and lights	RWY Markings Designation, THR, TDZ, Aiming Point, Centreline, Transverse stripe & side stripe. Lighting THR, Centreline, TDZ, EDGE, and END TWY Marking Centreline, side strip, Holding PSN at All TWY/RWY intersection Lighted Edge, RWY Guard Lights on TWY's A, B, C

3	Stop bars (if any)	Not available.
4	Remarks	180 Degree turn permitted only on turning pad.

VOCL AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	110813.2N 0755639.9E	334 FT	LGTD	GP Monitor Antenna
In circling area and at AD	OTHER	110812.7N 0755642.5E	376 FT	LGTD	GP Antenna
In circling area and at AD	OTHER	110812.7N 0755642.5E	343 FT	NO	GP DME
In circling area and at AD	OTHER	110812.5N 0755642.8E	324 FT	LGTD	Bird Chaser Hut
In circling area and at AD	OTHER	110812.9N 0755642.9E	326 FT	LGTD	Bird Chaser Hut
In circling area and at AD	OTHER	110812.7N 0755642.7E	324 FT	LGTD	GP Hut
In circling area and at AD	ANTENNA	110818.4N 0755653.1E	333 FT	NO	MET Antenna
In circling area and at AD	TANK	110824.0N 0755652.5E	409 FT	LGTD	OHWT LC Rod (L)
In circling area and at AD	ANTENNA	110819.9N 0755644.4E	328 FT	NO	MET Antenna
In circling area and at AD	FENCE	110810.0N 0755650.7E	364 FT	LGTD	Obstruction Light on Boundary Wall
In circling area and at AD	OTHER	110818.6N 0755646.1E	344 FT	LGTD	WDI (L)
In circling area and at AD	OTHER	110821.1N 0755632.8E	319 FT	LGTD	Bird Chaser Hut
In circling area and at AD	TREE	110813.8N 0755635.0E	334 FT	NO	Group of Tree
In circling area and at AD	TREE	110813.2N 0755636.5E	343 FT	NO	Group of Tree
In circling area and at AD	OTHER	110813.4N 0755637.1E	328 FT	NO	Mobile Road Traffic (Road Elev.-95.1M+5M Mobile Road Traffic)
In circling area and at AD	FENCE	110813.3N 0755637.3E	322 FT	NO	Boundary Wall with Fencing on Top
In circling area and at AD	OTHER	111125.4N 0755624.5E	816 FT	LGTD	Olavator Hill (Solar Light)
In circling area and at AD	OTHER	110812.4N 0755646.1E	328 FT	LGTD	Bird Chaser Hut
In circling area and at AD	OTHER	110818.2N 0755649.2E	331 FT	LGTD	Bird Chaser Hut
In circling area and at AD	ANTENNA	110813.5N 0755642.9E	351 FT	NO	MET Antenna
In circling area and at AD	OTHER	110800.6N 0755807.4E	327 FT	LGTD	Approach Light
In circling area and at AD	OTHER	110805.1N 0755756.6E	337 FT	LGTD	GP DME (L)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	110801.6N 0755751.3E	343 FT	LGTD	WDI (L)
In circling area and at AD	OTHER	110726.2N 0755926.1E	523 FT	NO	Ground Elevation
In circling area and at AD	OTHER	110722.0N 0755928.3E	670 FT	NO	Ground Elevation
In circling area and at AD	ANTENNA	110805.5N 0755755.0E	341 FT	LGTD	MET Antenna (Lighted)
In circling area and at AD	OTHER	110805.1N 0755756.3E	336 FT	LGTD	GP Hut
In circling area and at AD	OTHER	110804.4N 0755759.2E	339 FT	LGTD	GP Monitor Antenna
In circling area and at AD	OTHER	110805.0N 0755756.5E	373 FT	LGTD	GP Antenna
In circling area and at AD	OTHER	110910.8N 0755841.5E	823 FT	LGTD	Cheppilla Kunnu Hill Solar Light
In circling area and at AD	OTHER	110719.1N 0755929.8E	823 FT	LGTD	Puttodimala Hill Solar Light
In circling area and at AD	OTHER	110630.3N 0760036.4E	1162 FT	LGTD	Arimbara Kunnu Hill Solar Light
In circling area and at AD	OTHER	110517.9N 0760035.1E	1576 FT	LGTD	Urugu / Urotmala Hill Solar Light
In circling area and at AD	OTHER	110643.7N 0755859.7E	794 FT	NO	Cherpaddimala Hill - II
In circling area and at AD	OTHER	110904.1N 0755916.3E	641 FT	LGTD	Cellphone Mast on Hill
In circling area and at AD	OTHER	110559.6N 0760014.7E	1157 FT	LGTD	Muchhu Kunnu Hill Tree Top (Solar Light Top-347.6M)
In circling area and at AD	OTHER	110727.6N 0755921.5E	505 FT	NO	Group Of Tree on Hill
In circling area and at AD	OTHER	110726.2N 0755929.1E	517 FT	NO	Group Of Tree on Hill
In circling area and at AD	OTHER	110725.0N 0755928.4E	572 FT	NO	Group Of Tree on Hill
In circling area and at AD	OTHER	110724.9N 0755927.7E	572 FT	NO	Ground Elevation
In circling area and at AD	OTHER	110724.8N 0755927.2E	585 FT	NO	Ground Elevation
In circling area and at AD	OTHER	110724.0N 0755927.9E	635 FT	NO	Group Of Tree on Hill
In circling area and at AD	OTHER	110726.3N 0755927.6E	495 FT	NO	Ground Elevation
In circling area and at AD	OTHER	110726.6N 0755926.7E	508 FT	NO	Ground Elevation
In circling area and at AD	OTHER	110805.4N 0755755.1E	340 FT	NO	LC ROD
In circling area and at AD	OTHER	110805.2N 0755755.7E	331 FT	LGTD	Bird Chaser Hut

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	110721.4N 0755906.3E	500 FT	LGTD	Cellphone Mast on Hill
In circling area and at AD	OTHER	110919.4N 0755909.7E	491 FT	LGTD	Cellphone Mast
In circling area and at AD	TREE	110727.3N 0755926.1E	519 FT	NO	Group of Tree
In circling area and at AD	TREE	110728.2N 0755926.4E	499 FT	NO	Group of Tree
In circling area and at AD	TREE	110726.7N 0755926.5E	547 FT	NO	Group of Tree
In circling area and at AD	TREE	110725.6N 0755926.9E	589 FT	NO	Group of Tree
In circling area and at AD	TREE	110726.9N 0755927.6E	517 FT	NO	Group of Tree
In circling area and at AD	TREE	110727.3N 0755928.1E	502 FT	NO	Group of Tree
In circling area and at AD	OTHER	110720.2N 0755928.2E	698 FT	NO	Ground Elevation
In circling area and at AD	TREE	110727.6N 0755928.3E	498 FT	NO	Group of Tree
In circling area and at AD	OTHER	110721.1N 0755931.5E	733 FT	LGTD	Obstruction Light on Hill
In circling area and at AD	OTHER	110722.7N 0755932.4E	608 FT	LGTD	Obstruction Light on Hill
In circling area and at AD	OTHER	110720.8N 0755932.8E	676 FT	NO	Group of Tree on Hill
In circling area and at AD	OTHER	110724.2N 0755933.2E	504 FT	NO	Group of Tree on Hill
In circling area and at AD	OTHER	110722.2N 0755933.5E	530 FT	NO	Ground Elevation
In circling area and at AD	OTHER	110722.9N 0755934.3E	530 FT	NO	Group of Tree on Hill
In circling area and at AD	OTHER	110727.8N 0755927.7E	499 FT	NO	Tree on Hill
In circling area and at AD	OTHER	110821.8N 0755656.9E	391 FT	NO	Flood Light Mast
In circling area and at AD	OTHER	110822.2N 0755658.2E	405 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110822.0N 0755659.3E	405 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110821.7N 0755701.0E	404 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110821.3N 0755703.1E	404 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110820.9N 0755705.4E	403 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110820.4N 0755707.9E	403 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110820.1N 0755709.5E	404 FT	LGTD	Flood Light Mast
In circling area and at AD	OTHER	110819.8N 0755711.1E	405 FT	LGTD	Flood Light Mast

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	110822.7N 0755656.0E	398 FT	NO	Antenna on Technical Block (Building Top - 116.4M)
In circling area and at AD	OTHER	110822.1N 0755655.6E	404 FT	NO	LC Rod on ATC (ATC Building Top - 114.0M)
In circling area and at AD	ANTENNA	110822.0N 0755655.7E	401 FT	NO	VHF Antenna on ATC
In circling area and at AD	OTHER	110822.0N 0755655.7E	395 FT	LGTD	ATC Beacon (L)
In circling area and at AD	OTHER	110811.0N 0755657.9E	351 FT	LGTD	WDI (L)
In circling area and at AD	TREE	110808.1N 0755651.8E	397 FT	NO	Group of Tree
In circling area and at AD	TREE	110807.6N 0755650.9E	404 FT	NO	Group of Tree
In circling area and at AD	TREE	110806.7N 0755649.9E	405 FT	NO	Group of Tree
In circling area and at AD	TREE	110806.9N 0755652.1E	405 FT	NO	Group of Tree
In circling area and at AD	TREE	110807.9N 0755658.7E	365 FT	NO	Group of Tree
In circling area and at AD	TREE	110807.0N 0755702.6E	369 FT	NO	Group of Tree
In circling area and at AD	TREE	110805.7N 0755649.8E	414 FT	NO	Group of Tree
In circling area and at AD	TREE	110808.1N 0755650.1E	392 FT	NO	Group of Tree
In circling area and at AD	TREE	110809.3N 0755650.5E	378 FT	NO	Group of Tree
In circling area and at AD	TREE	110820.2N 0755651.5E	341 FT	NO	Tree
In circling area and at AD	OTHER	110810.9N 0755654.7E	335 FT	LGTD	Security Hut
In circling area and at AD	ANTENNA	110822.4N 0755655.3E	401 FT	NO	VHF Antenna on ATC
In circling area and at AD	TREE	110806.5N 0755704.9E	369 FT	NO	Group of Tree
In circling area and at AD	OTHER	110814.4N 0755713.1E	350 FT	NO	Mobile Road Traffic (Road Elevation 101.8 M +5 M Traffic Height)
In circling area and at AD	OTHER	110814.1N 0755713.3E	344 FT	LGTD	Security Hut
In circling area and at AD	SIGN	110812.5N 0755713.4E	344 FT	NO	Sign Board
In circling area and at AD	BUILDING	110805.9N 0755718.1E	342 FT	NO	Old DVOR Building
In circling area and at AD	SIGN	110807.7N 0755722.0E	341 FT	NO	Sign Board
In circling area and at AD	OTHER	110803.1N 0755723.7E	355 FT	NO	LC Rod

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	110803.8N 0755734.5E	332 FT	LGTD	Bird Chaser Hut
In circling area and at AD	OTHER	110808.7N 0755710.5E	346 FT	LGTD	Bird Chaser Hut
In circling area and at AD	OTHER	110811.2N 0755724.4E	340 FT	LGTD	Bird Chaser Hut
In circling area and at AD	OTHER	110700.0N 0755803.8E	531 FT	NO	Cherpaddi Mala Hill
In circling area and at AD	OTHER	110517.7N 0760133.7E	1083 FT	NO	Hill Top
In circling area and at AD	OTHER	110504.5N 0760246.7E	1034 FT	NO	Hill Top

VOCL AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Calicut
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Trivandrum 9, 24HR
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend Trend Half Hourly
5	Information on how briefing and/or consultation is provided	Personal ConsultationOn request Personal Consultation
6	Types of flight documentation supplied and language(s) used in flight documentation	Chartsabbreviated plain language English
7	Charts and other information displayed or available for briefing or consultation	NIL
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Digital current WX INSTR System (DCWIS) installed for RWY 10 at 300M from RWY 10 THR and 95M south of RWY CL. Digital curren WX INSTR System (DCWIS) installed fo RWY 28 at 366M from RWY 28 THR and 75M north of RWY CL. Present weather detector having RVR installed for RWY 10 and RWY 28.
9	The air traffic services unit(s) provided with meteorological information	Calicut TWR/APP
10	Additional information, e.g. concerning any limitation of service.	Half hourly METAR at every hour (UTC) and hour + 30 minutes.

VOCL AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
10	100.90 DEG	2860 x 45 M	72/F/A/W/T Asphalt	THR: 110818.40N 0755633.84E RWY END: 110800.80N 0755806.41E
28	280.90 DEG	2860 x 45 M	72/F/A/W/T Asphalt	THR: 110800.80N 0755806.41E RWY END: 110818.40N 0755633.84E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 315.0FT TDZ: 339.0FT	0.30%	NIL	NIL	2980 x 150 M
THR: 326.0FT TDZ: 328.0FT	-0.30%	NIL	NIL	2980 x 150 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M	NIL	NIL	Vertical Datum: EGM08 Initial 150M of RESA for RWY10/28 is paved surface.
240M x 90M	NIL	NIL	Vertical Datum: EGM 08 Initial 150M of RESA for RWY10/28 is paved surface.

VOCL AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
10	2700	2700	2700	2700	Portion of RWY length beyond 2700 M available for Taxing and 180DEG at existing turn pad.

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
28	2700	2700	2700	2700	Portion of RWY length beyond 2700 M available for Taxing and 180DEG at existing turn pad.

VOCL AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
10	SALS 150 M Abridged LIH	Green	PAPI LEFT/3.00 DEG MEHT (65.06FT)	900 M
28	SALS 150 M Abridge LIH	Green	PAPI LEFT/3.20 DEG MEHT (70.47FT)	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2700 M 30 M LIH	2700 M 60 M White LIH	Red	NIL	1. RWY CL LGT WITH VRB WHITE, LAST 300M RED, BTN LAST 300M TO LAST 900M ALTN RED
2700 M 30 M LIH	2700 M 60 M White LIH	Red	NIL	1. RWY CL LGT WITH VRB WHITE, LAST 300M RED, BTN LAST 300M TO LAST 900M ALTN RED

VOCL AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building, FLG W&G26 flashes/min, AS ATS
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	LDI: (Outlined by white lights):225M NW of ARP Abeam (left side) RWY THR 10 & 28, & 2130M from RWY 28 THR.
		Anemometer	2320M from THR RWY 28 on northern side of RWY
3	Taxiway edge and taxiway centre line lights;	Edge	Lighted
		Centre Line	Not Lighted

4	Secondary power supply including switch-over time;	SECONDARY PWR SUPPLY TO ALL ESSENTIAL LGT AND OPR UNITS AT AD. MAX SWITCH OVER TIME:15 SEC. RWY EDGE LGT (PRI/SRY),TWY LGT,RWY GUARD LIGHT,PAPI,APP LGT,RCL, TDZ LGT AND OTHER MANDATORY INFO SIGN BOARDS SWITCH OVER TIME:01 SEC. ALL NAV/COM AIDS SWITCH OVER TIME:ZERO.
5	Remarks	RWY 28 Lead-in-lighting system: 4 Light units, each consisting of a group of 3 sequential flashing white lights in a linear configuration installed on the FINAL APP. TRACK, of RWY 28, at a distance of 6193M, 4721M, 3121M, and 1826Mrespectively from THR RWY 28. Light unit situated at 3121M from THR RWY 28 is offset by 16.5M towards right while approaching of extended RWY centreline. Intensity - 300cd/1500cd/15000cd.

VOCL AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VOCL AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 110816N 0755702E within a 12NM radius.
2	Vertical limits	5500 FT AMSL
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Calicut Approach, English
5	Transition altitude	10000 FT
6	Hours of applicability	H24
7	Remarks	1.Vertical Limit- 5500 FT AMSL. 2.Aerodrome Control & SMC services provided by Calicut Tower. Independent APP unit operational, Operational hrs as per NOTAM.

VOCL AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Calicut Approach	122.950 MHZ	
TWR	Calicut Tower	119.150 MHZ	
TWR	Calicut Tower	123.350 MHZ	
ATIS	Calicut Information	126.850 MHZ	
ALRS	Calicut Emergency	121.500 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	H24	1. Main Frequency 2. DLY BTN 0130-0730 and 1330-1630 independent APP UNIT
	H24	1. Backup frequency. 2. Combined Backup frequency for TWR/APP.
	H24	Main Frequency
	H24	--
	H24	EMERG FREQ

VOCL AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 28 CAT I	ICAC	109.500 MHz	H24
LOC 10 CAT I	ICLB	110.700 MHz	H24
GP 28	ICAC	332.600 MHz	H24
GP 10	ICLB	330.200 MHz	H24
DME ILS 28	ICAC	CH32X	H24
DME ILS 10	ICLB	CH44X	H24
DVOR/DME	CLC	116.500 MHz CH112X	H24

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
110819.3N 0755629.2E			
110759.9N 0755811.0E			
110805.0N 0755756.5E			Minor fluctuations of GP signal RWY 28 up to one dot in CDI is reported. EXER CTN.
110812.7N 0755642.5E			
110805.1N 0755756.6E	337 FT		1. Collocated with GP 28 2. Geoid Model Used: EGM08
110812.7N 0755642.5E	343 FT		1. Collocated with GP 10 2. Geoid Model Used: EGM08
110803.0N 0755723.7E	353 FT		1. Vertical datum: EGM08 2. DME Collocated with DVOR

VOCL AD 2.20 LOCAL AERODROME REGULATIONS

1. AIRCRAFT PARKING AND PUSH BACK PROCEDURES

i. All aircraft stands are power in/pushback

ii. Stand no.1, 2, 3, 7, 11, 12 and13 for code-C or lesser type of aircraft (wing span less than 36m and length less than 45m)

iii. Stand no.6 for code C or lesser type of aircraft wing span less than 36m and length less than 45m and shall be used as remote stand only

iv. Stand 4 and 8 are for A300-600 or lesser type of aircraft (wing span less than 45m and length less than 55m). A300-600 or other code-D aircraft to stand no.4 shall taxi in/taxi out via TWY A only and shall be pushed back to left side so as to take left turn into TWY A. A300-600 or other code-D aircraft to stand 8 shall taxi-in/taxi-out via TWY B only.

v. Stand 5 is for B757-300 or lesser type of aircraft (wing span less than 39m and length less than 55m) B757-300 or other code-D aircraft to stand no. 5 shall taxi-in/taxi-out via TWY A only and shall be pushed back to left side so as to take left turn into TWY A.

vi. Stand 10 for code-D or lesser type of aircraft (wing span less than 52m and length less than 62m). If stand 9 and 12A are occupied by code-E aircraft, then stand no.10 to be allotted to code-C aircraft only.

vii. Stand 5A is for code-E or lesser type of aircraft (wing span less than 65m and length less than 75.5m) and shall be allotted only when stand no. 4 and 5 are vacant. Aircraft to stand 5A shall taxi-in and pushback to runway via TWY A only.

viii. Stand 9 for code-E or lesser type of aircraft (wing span less than 65m and length less than 75.5m) and shall be allotted only when stand no. 7 and 8 are vacant. Aircraft to stand 9 shall taxi-in and pushback to runway via TWY B only.

ix. Stand 12A for code-E or lesser type of aircraft (wing span less than 65m and length less than 75.5m) and shall be allotted only when stand 11 and 12 are vacant and stand no.10 is occupied by code-C aircraft. Aircraft to stand 12A shall taxi-in and pushback to runway via TWY C only.

x. Aircraft from stand no. 1 shall pushback facing west to taxi-out via TWY A and aircraft from stand no.13 shall pushback facing east or as instructed by ATC.

2. Intersection Take-off from RWY 10/28 Not permitted.

3. All aircrafts to strictly follow Taxi guidelines for 180 DEG turn on RWY turn pads to avoid damages to the pavement.

4. No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

5. Hot Spot Identified. Location :Intersection of TWY C with RWY.

VOCL AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VOCL AD 2.22 FLIGHT PROCEDURES

I. ADS-B based ATS Surveillance services are provided to suitably equipped aircraft on opportunity basis within the coverage area of Calicut ADS-B sensors in the jurisdiction of Calicut Approach control.

ADS-B equipped aircraft flying within Calicut Approach Control to comply with relevant provisions.

Refer NOTAM for hours of services.

II. LOW VISIBILITY PROCEDURES

1. INTRODUCTION:

The Low Visibility Procedure (LVP) incorporates safeguarding measures to mitigate runway incursions and defines operational restrictions to ensure safe aircraft operations taking into account the available Aerodrome facilities. This LVP is applicable only for take- off operations at Calicut Airport during conditions of Visibility/ RVR less than 800M/550M but not less than 350M. (LVP procedures shall not be applied at Calicut airport if RVR is less than 350m). These procedures are required for compliance with DGCA Civil Aviation Requirements Series C Part I Section 8 Para 5.3.

2. DEFINITIONS & ABBREVIATIONS

2.1 Instrument approach operations: An approach and landing using instruments for navigation guidance based on an instrument approach procedure. There are two methods for executing instrument approach operations:

a) a two-dimensional (2D) instrument approach operation, using lateral navigation guidance only; and

b) a three-dimensional (3D) instrument approach operation, using both lateral and vertical navigation guidance

Note – Lateral and vertical navigation guidance refers to the guidance provided either by:

i) a ground-based radio navigation aid; or

ii) computer-generated navigation data from ground-based, space-based, self-contained navigation aids or a combination of these.

Instrument approach operations shall be classified based on the designed lowest operating minima below which an approach operation shall only be continued with the required visual reference as follows:

a) Type A: a minimum descent height or decision height at or above 75m(250ft); and

b) Type B: a decision height below 75 m (250 ft). Type B instrument approach operations are categorized as:

i) Category I (CAT I): a decision height not lower than 60 m (200 ft) and with either a visibility not less than 800 m or a runway visual range not less than 550m;

ii) Category II (CAT II): a decision height lower than 60 m (200 ft) but not lower than 30 m (100 ft) and a runway visual range not less than 300 m;

iii) Category III (CAT III): a decision height lower than 30 m (100 ft) or no decision height and a runway visual range less than 300 m or no runway visual range limitations.

2.2 Decision Altitude/Height: A specified altitude or height in a 3D instrument approach operation at which a missed approach must be initiated if the required visual reference to continue the approach has not been established.

Note. - Decision altitude (DA) is referenced to mean sea level and decision height (DH) is referenced to the threshold elevation.

2.3 ILS Critical Area: An area of defined dimensions about the localizer and glide path antennas where aircraft and vehicles are excluded during all ILS operations. The critical area is protected because the presence of vehicles / or aircraft inside its boundaries will cause unacceptable disturbance to the ILS signal-in-space.

2.4 ILS Sensitive Area: An area extending beyond the ILS critical area where the parking and/or movement of vehicles, including aircraft, are controlled to prevent the possibility of unacceptable interference to the ILS signal during ILS operations. The sensitive area is protected to provide protection against interferences cause by large moving

objects outside the critical area but still normally within the airfield boundary.

2.5 Low Visibility Procedures: Specific procedures applied at an aerodrome for the purpose of ensuring safe operations during Categories II/ III approaches and/or low visibility take-offs.

2.6 Low Visibility Take-Off (LVTO): A term used in relation to flight operations referring to a take-off on a Runway where the RVR is less than 400m.

2.7 Maneuvering Area: That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, excluding aprons.

2.8 Movement Area: That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, consisting of the maneuvering area and the apron(s).

2.9 Visibility: Visibility for aeronautical purposes is the greater of:

a) the greatest distance at which a black object of suitable dimensions, situated near the ground, can be seen and recognized when observed against a bright background;

b) the greatest distance at which lights in the vicinity of 1 000 candelas can be seen and identified against an unlit background.

Note 1. — The two distances have different values in air of a given extinction coefficient, and the latter b) varies with the background illumination. The former a) is represented by the meteorological optical range (MOR).

Note. 2. — The definition applies to the observations of visibility in local routine and special reports, to the observations of prevailing and minimum visibility reported in METAR and SPECI and to the observations of ground visibility.

2.10 Runway Visual Range: The range over which the pilot of an aircraft on the centerline of a runway can see the runway surface markings or the lights delineating the runway or identifying its center line.

2.11 Aerodrome Operating Minima: The limits of usability of an aerodrome for:

a) take off, expressed in terms of runway visual range and / or visibility and, if necessary, cloud conditions.

b) landing in 2D instrument approach operations, expressed in terms of visibility and/or runway visual range; minimum descent altitude/height (MDA/H) and, if necessary, cloud conditions; and

c) Landing in 3D Instrument Approach operations, expressed in terms of visibility and/or runway visual range and decision altitude/height (DA/H) appropriate to the type and/or category of the operation

3. ABBREVIATIONS

ADC	**Aerodrome Control**
ADP	**Airside Driver Permit**
AOCC	**Airport Operations Control Centre**
ARFFS	**Airport Rescue and Fire Fighting Service**
ATC	**Air Traffic Control**
ATIS	**Automatic Terminal Information Service**
ATM	**Air Traffic Management**
AVP	**Airside Vehicle Permit**
CAR	**Civil Aviation Requirements**
CAT	**Category**
CFT	**Crash Fire Tender**
CISF	**Central Industrial Security Force**
DG	**Diesel Generator**
DGCA	**Directorate general of Civil Aviation**
DG	**Decision Height**
ICAO	**International Civil Aviation Organization**
ILS	**Instrumental Landing System**
KSEB	**Kerala State Electrical Board**
LVP	**Low Visibility Procedures**
LVTO	**Low Visibility Take Off**
MDA	**Minimum Descent Altitude**
MEL	**Minimum Equipment Limit**
MET	**Meteorology**
PAPI	**Precision Approach Path Indicator**
PDP	**Pre-Determined Position**
PIC	**Pilot In Command**
RT	**Radio Telephony**
RVR	**Runway Visual Range**
RWY	**Runway**
SMC	**Surface Movement Control**
SOP	**Standard Operating Procedure**
SP	**Safeguarding Procedure**
TDZ	**Touchdown Zone**
TWR SUP	**Tower Supervisor**
TWY	**Taxiway**
WSO	**Watch Supervisory Officer**

4. MINIMUM FACILITIES REQUIRED TO SUPPORT LVP.

The following Aeronautical Ground lights/equipment shall be serviceable to the required standard to support Low Visibility Procedures. In the absence of any of the following facilities, the LVP operation shall be suspended.

a) Runway Edge Lights- Switch overtime: 1 sec

b) Runway End Lights- Switch over time: 1sec

c) Runway Centre line Lights- Switch over time: 1sec

d) TWY edge lights, Runway guard lights - Switch over time: 15sec,

e) Secondary/stand by power supply to meet above specified switch over time requirements

f) Real time TDZ RVR/Manual RVR

Note: Mid RVR and Roll- out RVR are not required for LVP as no operation is permitted below 350m RVR at Calicut International Airport

5. SERVICEABILITY REQUIREMENTS OF AERONAUTICAL GROUND LIGHTS BEFORE IMPLEMENTATION OF LVP (REF. DGCA CAR 4B-1 /ANNEX 14, CLAUSE 10.4.11)

Aeronautical Ground Lighting Facility	**Un-Serviceability**	**Restrictions**
Runway Edge/Centre line lights/ taxiway Lights	More than 5% of all lights are unserviceable.	LVP operations will be suspended.
	Any two consecutive lights or more are unserviceable.	
Runway threshold lights/ End Lights	More than 25% of all lights are unserviceable.	LVP operations will be suspended.
	Any two consecutive lights or more are unserviceable.	
UPS for AGL	Any UPS is unserviceable	LVP operations will be suspended. LVP may be resumed with DG Set as Primary Source of power supply.
DG Set for Power Supply to AGL in case of unserviceability of the Main power supply	Any DG Set supplying power to the essential	LVP operations will be suspended.
	AGL/equipment is unserviceable	
RVR System	Automated RVR System unserviceable	LVP operations will be continued if manual RVR can be provided

NOTE:

a) If the intensity of any lights has reduced more than 50 % of its minimum required level, the light shall be considered unserviceable.

b) Engg-E shall ensure the above serviceability requirements for runway lighting system before implementation of the LVP. Any non-compliance shall immediately be reported to ATC and Apron Control.

c) UPS can supply power for a period of maximum 30 minutes.

6. SAFEGUARDING PROCEDURES

Safeguarding Procedures (SP) are instructions for airport departments, Airline operators, ground handling agents and other agencies working in the airside to prepare ground services and facilities for low visibility operations in order that LVP are

implemented after all Safeguarding Procedures (SP) are completed.

Duty Officer Tower/Tower Supervisor will initiate and co-coordinate with all the concerned agencies for completion of safeguarding procedures before implementation of Low Visibility Procedures.

6.1 Safeguarding Procedures shall be initiated when:

The Visibility/RVR is less than 1200m and the forecast is to deteriorate to 800m or less.

6.2 Safeguarding procedures include:

a) Runway inspection shall be carried out by the Apron Controller on duty along with electrical engineering officials before implementation of LVP.

b) Positioning of one CFT each at the two predetermined positions (ATC approach road outside the Runway strip and near Fire Station).

c) Stopping of all maintenance works on the manoeuvring area as well as removal of all men and mobile equipment from the said area including RWY strip.

d) Safeguarding the Runway from incursion via various access road to the runway. This may be achieved by removing all non-essential vehicles from the operational area and/or by temporarily displaying “LVP – Low Visibility Procedure in operation” signs at roads leading to the Runways, essential Taxiways and apron.

e) The identified points for displaying the sign boards are;

i) On perimeter road holding position Hill road.

ii) On perimeter road holding position Isolation Bay/ TWY D

iii) On perimeter road holding position GP 10 (west side)

iv) On perimeter road holding position Fire station approach road.

v) On perimeter road holding position old Fire station/ ATC approach road.

vi) At least 4 sign boards in apron area on the aero-bridge pillars (Stands 4, 7. 11 and on stand identification pole for stand2)

vii) Near Gate No.1

f) Ensuring uninterrupted power supply for essential facilities. It is not necessary to switch over to secondary power supply (Generators) and keep main power supply as stand by. However, the electrical In-charge/ shift in- charge of the power house shall ensure that the Secondary Power Supply shall be available with change over time as mentioned in point No.5

7. LOW VISIBILITY PROCEDURES

7.1 Implementation of Low Visibility Procedures:

Tower Duty officer and Tower A shall monitor the deterioration of visibility to 800 Meters or below Tower Supervisor/ Tower A shall coordinate with all the agencies to confirm whether the Safeguarding procedures have been completed. When Visibility/RVR falls below 800M/550M and safeguarding procedures are completed, Tower supervisor will implement Low Visibility Procedures. Duty Officer Tower shall inform ARFF and Apron Control for the implementation of low visibility procedures.

7.2 Restriction on vehicular movements:

The number of vehicles on the manoeuvring area shall be restricted to one vehicle only during the period of LVP. All vehicles previously operating on the manoeuvring area shall be vacated and parked away from the RWY strip preferably on the perimeter road in the valley area. Apron control shall monitor and keep the record of all such vehicles.

8. ACTIONS BY VARIOUS AGENCIES DURING LVP

8.1 CONTROL TOWER

a) Duty Officer, TWR should ensure the appropriate Aeronautical ground lights must have been inspected during the hour

preceding implementation of LVP, and thereafter once every two-hour period to ensure the serviceability of all Aeronautical Ground Lights. These inspections of Aerodrome Ground Lights should be accorded priority and, if necessary, aircraft operations may be delayed. Necessary entries in respect of any unserviceability of AGLs shall be made in the LVP Register kept in Tower.

b) ATC Tower shall inform Apron Control, Fire Station, and AOCC about the implementation of low visibility operations.

c) Duty Officer Tower shall ensure the MET official is present in control Tower for real time update of Visibility/RVR.

d) Tower shall not permit any ground run of aircraft on the manoeuvring area

e) Number of Aircraft movement during LVP shall be restricted to one aircraft only.

f) Restrictions imposed by 9-member committee constituted to oversee the recommendations of AAIB regarding aircraft movement on aircraft stand taxi lane during landing and take- off shall be strictly followed. (No aircraft shall be on the aircraft stand taxi lane at apron during take-off).

g) The following may be included in ATIS broad cast.

“LOW VISIBILITY PROCEDURE IN FORCE”.

h) TWR shall permit departures only from the beginning of the Runway in use.

i) If the reported RVR id less than 400m, TWR shall obtain the approved LVTO minima from the pilot.

a) If RVR is obtained manually, ATC shall inform the Pilot that the observation is manual. PIC may make his own assessment of the RVR before departure to ensure that it is above 350M as update of Manual RVR may take time.

b) Duty Officer Tower shall stop all departures whenever RVR falls below 350 M.

8.2 APRON CONTROL

i) Inform all users of apron (airlines/ground handling agencies/stakeholders), Engg-Civil, Engg-Electrical, ARFF, CISF Control room, Equipment room and MT section regarding commencement of implementation of SGP.

ii) Restrict the movement of vehicular traffic on movement area by advising CISF Control Room to stop entry of vehicles through vehicle entry gate no. 01, 07 & 08 and CISF Barrack area. However, vehicles that are essential for airport operation /aircraft handling emergency vehicle shall be permitted through gate N0.1

iii) Apron control shall coordinate with airline operators and ground handling agencies and take necessary action to safe guard the Aircraft stand taxi lane on the apron during the implementation of LVP

iv) No men / vehicles / equipment are allowed to cross the apron safety lane.

v) The procedure of SG/LVP shall be included in the ADP/AVP training

vi) Temporary barriers/ LVP sign boards to stop the movement of vehicular traffic shall be provided at the following locations:

a) On perimeter road holding position Hill road.

b) On perimeter road holding position Isolation Bay/ Twy D

c) On perimeter road holding position GP 10 (west side)

d) On perimeter road holding position Fire station service road.

e) On perimeter road holding position old Fire station/ ATC approach road.

f) Near Gate No.1

vii) Inform Duty Officer Engg. (Elect) to check and confirm serviceability/ availability of generator for secondary power supply.

viii) Inform Civil/ Electrical Maintenance Division to suspend all works in progress in operational area and removal of men, machinery and material from the movement area.

ix) Inform all users of the Apron (airlines/other agencies) regarding enforcement of Low Visibility Procedure and confirm

its compliance to ATC Tower.

x) As and when ATC notify for withdrawal of Safe Guarding Procedure, all concerned shall be intimated.

xi) Ensure availability of 'Follow Me' service to aircraft as and when requested by ATC.

xii) No vehicle on Apron shall enter the manoeuvring area without permission from ATC tower.

xiii) No vehicle shall be permitted except Apron control vehicle fitted with Tower VHF R/T for RWY/electrical inspection. In case of any emergency requirement, Apron control jeep shall provide escort to other needy vehicles.

xiv) All Non-Sked aircraft shall be provided with Follow-Me service mandatorily and scheduled aircraft as and when requested.

xv) Ensure that bird scares are properly distributed and briefed accordingly.

xvi) Apron control shall inform ATC tower on completion of the all safe guarding procedures for the implementation of LVP.

8.3 ELECTRICAL ENGINEERING

a) Electrical In-charge shall ensure the availability/serviceability of Secondary Power Supply with change over as mentioned in point No.5

b) Inspection of AGL in co-ordination with Apron Control . Following visual aids associated with RWY 10/28 shall be serviceable as given in Para 5 & 5.1 above and can be operated at full intensity.

- Runway Edge lights
- Runway threshold and Runway end lights
- Taxiway edge lights
- Runway holding position lights & signs
- Runway guard lights
- Runway Center line lights
- Obstacle lights

Note: No adjustment of light intensities shall be made without permission from Control Tower.

c) Inform the serviceability of above visual lighting aids to ATC.

d) Ensure that Switch Room and New Power House is manned. If one second switch over time cannot be achieved due to any reasons, Switch on generator set so as to run parallel with the primary source (KSEB) to meet requirement of switch over time as specified in para 5. The generator may be switched off when advised by apron control/ ATC.

e) Inform the un-serviceability or any change in the status of any facility/systems to ATC and Apron Control immediately.

f) Maintain a constant listening watch on R/T.

g) Shift in- charge, Powerhouse shall continuously monitor the main and Standby Power supply to ensure change over time as mentioned in Para-5 and report any unserviceability to ATC immediately.

8.4 AIRPORT RESCUE & FIRE FIGHTING SERVICE (ARFFS)

a) On receipt of notification of implementation of Safe Guarding procedures/LVP, Airport Rescue and Fire Fighting Service (ARFFS) will remain in readiness at Fire Station and PDPs.

b) In the event of an incident when LVP is in force, positive clearance needs to be obtained by ARFFS from ATC prior for entering maneuvering area. ATC and Apron Control should provide the maximum assistance in directing ARFFS to required location.

c) The PDPs are in front of ATC Tower (old fire station road) & in front of Fire Station.

8.5 ENGG- CIVIL

On receipt of notification from ATC/Apron Control/AOCC that safeguarding procedure is being implemented, Engg-Civil shall confirm the following to Apron Control.

a) Stop the work in progress in the operational area.

b) Remove men, machinery and material from the work site and leave the operational area to the valley side.

c) Resuming of work shall only be initiated after obtaining positive clearance from ATC/Apron Control.

8.6 CISF

On receipt of notification from ATC/Apron Control/AOCC that safeguarding procedure is being implemented, CISF Control Room shall initiate the following actions:

a) Inform all access gates leading to operational area and CISF Posts in operational area to STOP entry of non-essential vehicles.

b) No vehicle from the CISF barrack shall enter the operational area without prior permission from ATC /coordination with Apron Control.

8.7 AIRLINE OPERATORS/GROUND HANDLING AGENCIES/OTHER AGENCIES

a) All the agencies shall ensure that staff and drivers/operators are suitably trained and aware about the importance and prevailing conditions of Low Visibility operations, aerodrome lay-out, markings and signs in the operational area.

b) All agencies operating in the operational area shall ensure that only those vehicles that are absolutely essential for aircraft operations operate in the operational area during periods of low visibility. The drivers/operators of these vehicles should keep a look out for taxiing aircraft and other vehicles to prevent accidents.

c) All the vehicles must have their obstruction lights "ON" during operation of low visibility procedures. No vehicle without serviceable obstruction light shall be permitted in the apron/ maneuvering area during LVP implementation.

d) All instructions/sign boards provided for vehicular movement area/service roads, must be followed while operating in the operational area. All vehicles shall operate at 10kmph or below during LVP on the apron.

e) No vehicle/equipment/ men shall cross the apron safety line demarcating the boundary of the aircraft stand taxi lane on the apron during LVP period.

f) Follow all instructions/sign boards provided for vehicular movement area/service roads.

g) No vehicle/equipment/personnel shall enter in and around the vicinity of the runways or taxi-ways without prior permission of ATC.

h) Airline operators shall ensure that the aircraft is suitably equipped and the pilots have necessary training and authorization to operate during LVP.

i) Every year before commencement of monsoon/winter season, a refresher/ sensitization program for personnel responsible for airside operations shall be conducted to create awareness and to ensure cooperation for safe airport operations during periods of low visibility.

8.8 PILOTS

a) Pilot in command shall not initiate Take off below 800m visibility / 550m RVR unless the LVP are enforced.

b) The pilot shall ensure that the aircraft is suitably equipped for the operation during LVP meeting the minimum requirements including MEL as specified in the DGCA CAR.

c) If any time the reported visibility is below 800m, then RVR criteria shall be applicable for aerodrome operating minima. The RVR may be derived from an automated RVR system/manual observation of RVR.

d) If RVR is obtained manually, ATC shall inform the Pilot that the observation is manual. PIC may make his own assessment of the RVR before departure to ensure that it is above 350M as update of Manual RVR may take time.

e) The airline operator/ pilot in command shall ensure that the flying crew shall be meeting the training requirement specified by the regulator for the operation during LVP. The training criteria for the pilot has been specified in DGCA CAR section 8C part 1 - All weather Since Calicut airport allows only departures during LVP, no cloud base minima is not considered for the implementation of LVP. Airline/ pilot in command has to follow their own minima based on cloud base if applicable.

f) For all departures during LVP, the pilot shall ensure that suitable alternate aerodrome/aerodromes are filed in their operational flight plan (Refer para 14.2 DGCA CAR- manual on of weather operations). Take off alternate shall be selected and specified in the OFP as per the criteria specified in para 14.2 (a) of DGCA CAR 8C part-1 (all weather operations).

g) Pilot in command shall ensure that they have the necessary approval for LVTO minima form DGCA/ regulatory authorities if the take-off is conducted below RVR 400M.

9. CONTINGENCY PROCEDURES

Degradation of RVR System

a) If automated RVR system is unserviceable, manual observation of RVR may be taken by MET department (IMD) if it is feasible, ATC may allow this and apron control shall make necessary arrangements for manual observation of RVR. If the manual RVR reported is 350m, the ATC may permit the departures.

b) The ATC while giving Manual RVR shall inform the pilot that the observation is manual. The time of observation shall also to be informed to the pilots.

Note: The requirement of Mid RVR / Roll out RVR is not required as the Take-off is not allowed below 350m RVR at Calicut.

10. SUSPENSION/ TERMINATION OF LOW VISIBILITY PROCEDURES

a) When Visibility/RVR improves to 800M/550 M and trend is for further improvement; Tower Supervisor/Duty Officer Tower would terminate operations of LVP. He must obtain advice from Duty Officer, Meteorological Office regarding improvement in weather conditions before the termination of LVP. However, the runway safe guarding procedures will be continued till the visibility improve to 1200m or more.

b) When the RVR falls below 350 meters the LVP will be suspended by Tower Supervisor/Duty Officer, Tower and no aircraft departures are allowed. However, runway safe guarding procedure will continue to be in force if the trend forecast indicates that the RVR is likely to be improved to 350 meters or above within a reasonable time.

c) The Aircraft Departures during LVP will be suspended by ATC in the following circumstances also.

i) If the automated RVR system becomes unserviceable.

ii) If the facilities essential for the implementation of LVP becomes unserviceable (Ref. Para5& 5.1)

iii) If the runway lighting system failed to meet the minimum switch over time as specified in this SOP.

iv) Failure/ non-availability of secondary power supply.

v) Failure of Runway lights monitoring system provided at control Tower

vi) Failure of two-way radio communication system (123.35 MHz) of vehicles/ CFTs Deployed in operational area during LVP.

vii) If unable to safe guard the runway and Maneuvering area. viii. During degrade mode of operation of Air Traffic services.

viii) On cancellation / Suspension of LVP, Duty officer Tower shall inform Apron Control, AOCC and Fire station.

ix) Apron Control/AOCC will inform all concerned agencies (Engg-Elect, Engg-Civil, Equipment room, MT section CISF and other stake holders. regarding the suspension/ termination of LVP operations.

x) On cancelling/suspending of LVP, following message shall be included in two subsequent ATS broadcasts “LOW VISIBILITY PROCEDURES CANCELLED/ SUSPENDED “.

xi) If Safeguarding Procedures are implemented and LVP are not subsequently implemented and the visibility/RVR improves to 1200 m and above, then the Tower Supervisor/Duty Officer Tower may cancel Safe guarding Procedures in coordination with apron control.

VOCL AD 2.23 ADDITIONAL INFORMATION

1. Details of aircraft stands available at Calicut International Airport:
   i. AVDGS available for Stands 1, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, and 13.
   ii. Passenger Boarding Bridge provided for Stands no. 4, 5, 5A, 7, 8, 9, 10, 11, 12, 12A and 13
2. Details of TWY C: Location: PARL to and to the eastern side of TWY 'B' connecting RWY and APN at an angle of 90 DEG.TWY 'C'AVBL for code 'E' ACFT and lesser type. H-24, trapezoidal turning pad on southern side of RWY28 beginning AVBL. PCN 55/F/A/X/T. shoulders 10.5M. Semicircular turning pad on the northern side of RWY28 beginning not usable.
3. RWY end light to indicate RWY 28 and RWY 10 end provided in the form of inset RWY end light.
4. Commissioning of ADS-B at Calicut Airport
   Facility: ADS-B
   Freq: 1090MHZ
   Coord: 110822N 755655E
   Site Elev: 122.5 AMSL
5. Intermediate turn pad provided to the north of RWY at 2250m from the beginning of Rwy10 for aircraft type upto code-C.
6. Fixed distance markers provided onthe left side of RWY in use.
7. All ACFT to strictly follow Taxi guide lines for 180 DEG Turn on RWY Turn pads to avoid damages to the pavment.
8. On recommendation of aircraft accident investigation bureau (AAIB), DGCA has imposed the following restrictions on aircraft operations :
   a) No aircraft on apron taxiway and no push back if runway is in use for take-off/landing.
   b) ACFT OPS not to be undertaken ABV cross wind of 15 KTS for dry RWY and 10 KTS for wet RWY
   c) Limit tail wind to 10 KTS (DRY RWY) and 5 KTS (WET RWY).
9. Bird activity in and around airfield. Pilots to excercise caution.

Exemption Granted by DGCA:
DGCA India has granted exemption vide letter dated 10.09.2025 for non-compliant width of runway strip against provisions in CAR Section 4, Series B, part I, Para 3.4.3 for the period up to 07.09.2027.

VOCL AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (08 August 2024)
2. Aircraft Parking/Docking Chart
3. Aerodrome Obstacle Chart - Type A (Operating Limitations), RWY 10 (08 August 2024)
4. Aerodrome Obstacle Chart - Type A (Operating Limitations), RWY 28 (08 August 2024)
5. Aerodrome Obstacle Chart - Type B

6. Instrument Approach Chart – ILS Z Procedure RWY 10 (13 June 2024)
7. Instrument Approach Chart – ILS or LOC Z Procedure RWY 28 (13 June 2024)
8. Instrument Approach Chart – VOR Procedure RWY 28 (17 April 2025)
9. Instrument Approach Chart – VOR Procedure RWY 10 (17 April 2025)
10. ATC Surveillance Minimum Altitude Chart
11. Instrument Approach Chart – RNP Y Procedure RWY 10
12. Coding Table - RNP Y Procedure RWY 10
13. Waypoints - RNP Y Procedure RWY 10
14. Instrument Approach Chart – RNP Y Procedure RWY 28
15. Coding Table - RNP Y Procedure RWY 28
16. Waypoints - RNP Y Procedure RWY 28

VOCL AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3