AD 2. AERODROMES

VADN AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VADN - DAMAN AIRPORT, DAMAN [COAST GUARD AIR STATION]

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Coast Guard

VADN AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	202602N 0725033E Location: In front of ATC Tower and Western side of main runway 03/21	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	4KM North of city Daman.	
3	Aerodrome elevation and reference temperature	42 FT / 31.0 DEG C	
4	Magnetic variation, date of information and annual change	0.06 DEG E (2015) /0.07 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Indian Coast Guard ICGAS Daman Airport Road Nani Daman Daman - 396 210,	
		Telephone:	912602261004
		Fax:	(91) 260 2405717 (91) 260 2405718
		AFS:	VADNZTZX
		Email:	notamdaman@gmail.com
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	AD Reference code-4C	

VADN AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	Indian Coast Guard
2	Custom and immigration	NIL
3	Health and sanitation	Service MI Room available within the airfield and Local government hospital available approximately 3 km from airport
4	AIS briefing office	Facilitated with Flight Planning Section
5	ATS reporting office (ARO)	ATC Tower, Operational Hours (0200 to 0800 UTC) except Saturday, Sunday and Holidays
6	MET Briefing office	Met Office, H24
7	Air Traffic Service	ATS Services as per Controlled Aerodrome, Operational Hours (0200 to 0800 UTC) except Saturday, Sunday and Holidays
8	Fuelling	ATF-K-50 (Through IOC), (0200 to 1200 UTC) except Saturday, Sunday and Holidays
9	Handling	Handling only for Military Aircraft
10	Security	Security only for Military Aircraft
11	De-icing	Not available
12	Remarks	NIL

VADN AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Not available

2	Fuel and Oil types	ATF-K-50 (Through IOC), Oil- Nil
3	Fuelling facilities and capacity	Two fuelling Bowser available with capacity of 06 & 09 KL. Total storage capacity 140 KL
4	De-icing facilities	Not available
5	Hangar space for visiting aircraft	Not available
6	Repair facilities for visiting aircraft	Not available
7	Remarks	NIL

VADN AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available within 3 to 4 km
2	Restaurant(s) at or in the vicinity of aerodrome	Available within 3 to 4 km
3	Transportation possibilities	Not available
4	Medical Facilities	Service MI Room available within the airfield and Local government hospital available approximately 3 km from airport
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available within 2 to 3 km Post office: Available within 2 to 3 km
6	Tourist office	Available within 2 to 3 km
7	Remarks	NIL

VADN AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-5
2	Rescue equipment	Available as per category
3	Capability for removal of disabled aircraft	Crane with 12.5 tons (Safe load 7.5 tons)
4	Remarks	NIL

VADN AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VADN AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: Two dispersals for operations of Military Aircraft Surface: Concrete Strength: PCN 9/R/C/X/T
2	Designation, width, surface and strength of taxiways	Designator: TWY A Width: 20 M Surface: Asphalt Strength: PCN 8/F/C/X/T Designator: TWY B Width: 18 M Surface: Concrete Strength: PCN 9/R/C/X/T Designator: TWY C Width: 18 M Surface: Concrete Strength: PCN 9/R/C/X/T
3	Location and elevation of altimeter checkpoints	Not available

4	Location of VOR checkpoints	202605.71N 0725042.80E (Near Dumbell 28)
5	Position of INS checkpoints	Not available
6	Remarks	NIL

VADN AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Marking available as per the service aircraft requirement
2	Runway and taxiway markings and lights	RWY Markings: Standard ICAO Marking RWY Threshold Marking, RWY Designation marking, Touch Down Zone Marking, Aiming Point Marking, RWY Centre line Marking, RWY Edge line Marking, Displaced Threshold Marking (for RWY 03 & RWY 28) RWY Lights: Runway edge lights, Threshold lights, Half way Lights, RWY end lights, PAPI for RWY 03 & RWY 21, APAPI for RWY 10 & RWY 28 TWY Markings: ICAO Standard Taxi way centre line marking and edge line marking from dispersal to RWY, Taxi link 'A' & 'B' TWY Lights: TWY edge blue lights
3	Stop bars (if any)	NIL
4	Remarks	NIL

VADN AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
21/TKOF 03/APCH	BUILDING	202501.0N 0725002.0E	95 FT	NIL	BUILDING RWY 03 threshold displaced by 200m as this building falls in the approach funnel and height of the building is more than the permissible height.
21/TKOF 03/APCH	BUILDING	202524.0N 0725009.0E	52 FT	LGTD	BUILDING
21/TKOF 03/APCH	BUILDING	202503.0N 0724948.0E	151 FT	LGTD	BUILDING
21/TKOF 03/APCH	BUILDING	202453.0N 0725002.0E	102 FT	LGTD	BUILDING
21/TKOF 03/APCH	OTHER	202425.0N 0724951.0E	144 FT	LGTD	LIGHT HOUSE
21/TKOF 03/APCH	BUILDING	202407.0N 0724951.0E	190 FT	LGTD	BUILDING
21/APCH 03/TKOF	NATURAL HIGHPOINT	202645.0N 0725102.0E	150 FT	NIL	HILL
21/APCH 03/TKOF	BUILDING	202728.0N 0725117.0E	128 FT	NIL	BUILDING
28/APCH 10/TKOF	OTHER	202655.0N 0725220.0E	151 FT	NIL	MAST

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
28/APCH 10/TKOF	OTHER	202545.0N 0725423.0E	253 FT	NIL	CHIMNEY
In circling area and at AD	TOWER	202722.0N 0725245.0E	177 FT	LGTD	TOWER
In circling area and at AD	OTHER	202743.0N 0725319.0E	249 FT	NIL	CHIMNEY
In circling area and at AD	TOWER	202659.0N 0725123.0E	167 FT	NIL	TOWER
In circling area and at AD	TOWER	202655.0N 0725220.0E	236 FT	LGTD	TOWER
In circling area and at AD	TOWER	202643.0N 0725115.0E	141 FT	LGTD	TOWER
In circling area and at AD	NATURAL HIGHPOINT	202622.0N 0725204.0E	381 FT	NIL	HILL
In circling area and at AD	BUILDING	202623.0N 0725103.0E	157 FT	NIL	BUILDING
In circling area and at AD	TANK	202614.0N 0725114.0E	177 FT	LGTD	WATER TANK
In circling area and at AD	BUILDING	202542.0N 0725044.0E	157 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	202537.0N 0725030.0E	56 FT	LGTD	BUILDING
In circling area and at AD	POLE	202529.0N 0725110.0E	118 FT	NIL	ELECTRIC POLE
In circling area and at AD	BUILDING	202527.0N 0725004.0E	118 FT	LGTD	BUILDING
In circling area and at AD	TOWER	203227.0N 0725458.0E	194 FT	LGTD	TOWER
In circling area and at AD	BUILDING	202520.0N 0725027.0E	131 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	202518.0N 0725019.0E	85 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	202512.0N 0725031.0E	128 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	202503.0N 0724950.0E	135 FT	LGTD	BUILDING
In circling area and at AD	NATURAL HIGHPOINT	201929.0N 0725059.0E	758 FT	NIL	HILL
In circling area and at AD	TOWER	202442.0N 0725150.0E	190 FT	LGTD	TOWER
In circling area and at AD	OTHER	202345.0N 0725331.0E	226 FT	LGTD	Building + Mast
In circling area and at AD	POLE	202229.0N 0725138.0E	295 FT	NIL	ELECTRIC POLE

VADN AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Met Office ICGAS Daman
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Office ICGAS Daman 0300 UTC-1200 UTC & 1200 UTC -2100 UTC
4	Availability of the trend forecast for the aerodrome and interval of issuance	0730 EF-1830 EF & 1830EF -2330 EF
5	Information on how briefing and/or consultation is provided	Met documentation provided to Aircrew in Met Office
6	Types of flight documentation supplied and language(s) used in flight documentation	Met T-3 (Within 500 NM), Met T-4 (Beyond 500 NM) & Met T-10 (as and when required) in English
7	Charts and other information displayed or available for briefing or consultation	W3 (Surface Chart for MSL pressure) W4 (Upper air Charts for all significant levels) W3 (C)- Change Chart for changing of current weather parameters T phigram-for Upper levels analysis of weather parameters
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Satellite image received from IMD website by Internet
9	The air traffic services unit(s) provided with meteorological information	Daman ATC
10	Additional information, e.g. concerning any limitation of service.	Not Available

VADN AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
03	26.00 DEG	1801 x 45 M	14/F/C/X/T Asphalt	THR: 202531.06N 0725019.91E RWY END: 202618.13N 0725043.45E
21	206.00 DEG	1801 x 45 M	14/F/C/X/T Asphalt	THR: 202618.13N 0725043.45E RWY END: 202525.18N 0725016.98E
10	95.00 DEG	1035 x 25 M	8/F/C/X/T Asphalt	THR: 202607.99N 0725009.81E RWY END: 202605.63N 0725008.54E
28	275.00 DEG	1035 x 25 M	8/F/C/X/T Asphalt	THR: 202606.00N 0725040.20E RWY END: 202608.08N 0725008.64E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 29.4FT TDZ: 28.4FT	0.02%			1921 x 140 M
THR: 41.8FT TDZ: 40.7FT	0.02%			1921 x 140 M
THR: 26.3FT TDZ:	0.97%			1155 x 55 M
THR: 36.4FT TDZ:	0.97%			1155 x 55 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
			True Bearing is provided up to nearest degree
			True Bearing is provided up to nearest degree
			1. RWY 10/28 available for helicopter operations only. 2. True Bearing is provided up to nearest degree
			1. RWY 10/28 available for helicopter operations only. 2. True Bearing is provided up to nearest degree

VADN AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
03	1801	1801	1801	1601	
21	1801	1801	1801	1801	
10	1035	1035	1035	1000	
28	1035	1035	1035	919	

VADN AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
03		Green Wing bar not available	PAPI	
21		Green Wing bar not available	PAPI	
10		Green Wing bar not available	APAPI	
28		Green Wing bar not available	APAPI	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	1801 M 60 M LIH	RED Wing bar not available		Five omnidirectional RWY middle marker white light installed on each side of RWY 03/21 to indicate half runway length.
	1801 M 60 M LIH	RED Wing bar not available		Five omnidirectional RWY middle marker white light installed on each side of RWY 03/21 to indicate half runway length.
	1035 M 60 M LIH	RED Wing bar not available		Nil
	1035 M 60 M LIH	RED Wing bar not available		Nil

VADN AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On the top of ATC Tower, 30 Flashes per minutes alternate White & Green, during night/low visibility operation.
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Available near Signal square
		Anemometer	On top of ATC tower
3	Taxiway edge and taxiway centre line lights;	Edge	Blue edge lights with 15 M intervals
		Centre Line	Not Available
4	Secondary power supply including switch-over time;	Stand by Generator available with 10 sec switch over time	
5	Remarks	ABN position: 202557N 0725042E, HGT: 27.3M AMSL	

VADN AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	NIL
2	TLOF and/or FATO area elevation:	NIL
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	NIL
4	True bearings of FATO;	NIL
5	Declared distances available	NIL
6	Approach and FATO lighting;	NIL
7	Remarks	All Helicopters landing and take-off from runways only

VADN AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 200303N 0724958E; 202003N 0722558E; 204103N 0722958E; 205103N 0724958E; 204203N 0730958E; 200703N 0730758E to point of origin.
2	Vertical limits	FL 60
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	DAMAN TOWER, English
5	Transition altitude	4000 FT
6	Hours of applicability	HO
7	Remarks	NIL

VADN AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
TWR	DAMAN TOWER	118.700 MHZ	
TWR	DAMAN TOWER	119.700 MHZ	
TWR	DAMAN TOWER	120.700 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	0200-0800 (UTC) except Sat/ Sun & holidays	MAIN
	0200-0800 (UTC) except Sat/ Sun & holidays	STANDBY
	0200-0800 (UTC) except Sat/ Sun & holidays	APP

VADN AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	DMN	113.300 MHz CH80X	0200-0800 (UTC) except Sat/ Sun & holidays

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
202632.5N 0725116.0E	139 FT		1.DMEcollocatedwithDVOR 2. Controlling Authority: Indian Navy

VADN AD 2.20 LOCAL AERODROME REGULATIONS

Bird activity in and around airfield. Pilots exercise caution while landing and takeoff.

VADN AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VADN AD 2.22 FLIGHT PROCEDURES

NIL

VADN AD 2.23 ADDITIONAL INFORMATION

i. Wednesday will be observed as maintenance/non flying day. Operational flying will only be permitted with 48 hrs prior notice.

ii. Operational/training sorties are undertaken including Saturdays, Sundays and holidays. Aircraft to contact positively on primary frequency 118.700 MHz (Secondary frequency 119.700 MHz prior to entering Daman local flying area VAR-47 and CTR. All aircraft transiting through Daman airspace to maintain minimum 10NM around VOR/DME demarcated as circuit for training purpose.

iii. All aircraft at FL060 and below must obtain positive clearance from Daman Control Frequency 118.700 MHz before entering Daman local flying area bounded by coordinates 2003N 07250E, 2010N 07150E, 2113N 07206E, 2120N 07237E, 2100N 07150E, 2049N 07257E.

iv. Watch Towers locations in no construction zone. Details are as follows:

S. No.	PSN	DIST FM RWY C/L	HGT	LGT
1	PORT SIDE DUMBELL 03	43.01M	06M	LGT
2	PORT SIDE RWY MM 21	61.33M	06M	LGT
3	PORT SIDE DUMBELL 21	61.81M	06M	LGT
4	PORT SIDE MM 10	39.15M	06M	LGT
5	RIGHTSIDE DUMBELL 28	37.59M	06M	LGT

v. PAPI installed and commissioned on RWY 03 and RWY 21. For RWY 21 at a distance of 291M from threshold and 15M from RWY edge for RWY 03 at a distance of 185M from displaced threshold and 15M from RWY edge. Approach angle: 03deg.

vi. Exercise caution for tall trees on approach path of RWY 10.

VADN AD 2.24 CHARTS RELATED TO AN AERODROME

1 VOR DME Procedure RWY 03
2 VOR DME Procedure RWY 21

VADN AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3