AD 2. AERODROMES

VEDO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VEDO - DEOGHAR AIRPORT, JHARKHAND

VEDO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	242645N 0864225E 263.16 DEG / 1056 M from physical beginning of RWY 27.	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	13 KM / 7NM, 132 DEG South East of Jasidih Railway Station.	
3	Aerodrome elevation and reference temperature	802 FT / 32.0 DEG C	
4	Magnetic variation, date of information and annual change	0.25 DEG W (2010) /0.0166 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority Of India, Airport Director, Deoghar Airport, Deoghar, P.O.- Gurukul, Via- Deosangh, District Deoghar-814114 Jharkhand.,	
		Telephone:	(91) 7520091198 06432-350111 06432-350104 06432-350100 06432-350135
		Fax:	
		AFS:	VEDOZTZX
		Email:	apd.deoghar@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	1. Aerodrome Reference Code: 4C 2. Vertical Datum: EGM 08	

VEDO AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI: 0400-1230 UTC (0930-1800 IST) SAT, SUN+HOL: NIL
2	Custom and immigration	NIL
3	Health and sanitation	Provided by municipal corporation and health department during watch hour.
4	AIS briefing office	AS ATS
5	ATS reporting office (ARO)	AS ATS
6	MET Briefing office	AS ATS
7	Air Traffic Service	Refer NOTAM
8	Fuelling	Provided by HPCL and IOCL
9	Handling	Provided by approved handler or AIASL
10	Security	Provided by Jharkhand police, H-24
11	De-icing	NIL

12	Remarks	ATS approved hourly RWY traffic handling capacity is as follows: MAX NR of ARR and DEP (PER HR)- 04 (MNM spacing between two successive ARR shall not be less than 10 MIN BTN similar PER ACFT) MAX NR of ARR ONLY(per hr)-02 MAX NR of DEP ONLY(per hr)-02

VEDO AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	IOCL: 01 Bowser- 16KL & 02 Bowsers- 11KL, Static storing capacity- 38KL Fuel Type: JET A1 BPCL: 02 Bowser- 15KL & 01 Bowsers- 11KL, Static storing capacity- 30KL Fuel Type: JET A1
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VEDO AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city within 8 km
2	Restaurant(s) at or in the vicinity of aerodrome	In the city within 5 km
3	Transportation possibilities	Available (Hired Car)
4	Medical Facilities	MI Room(First Aid facilities) Available in the terminal building. For serious & critical cases: Sadar Hospital is located in Deoghar City about 8km from the airport & AIIMS Deoghar is 20km from Deoghar Airport.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Located within 3km of Deoghar Airport ATM: Available at Deoghar Airport Post office: Located within 3km of Deoghar Airport.
6	Tourist office	Available within 8km in the city near Deoghar Bus Stand.
7	Remarks	NIL

VEDO AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Ambulance: 02 CFT: 02

3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is : A321. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Detail of Aerodrome coordinator : Airport Director Contact No. : 7520091198 /06432-350111 Email : apd.deoghar@aai.aero
4	Remarks	NIL

VEDO AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VEDO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	At TWY A, Elev. 771 FT. At TWY B, Elev. 796 FT. At TWY C, Elev. 789.6 FT.
4	Location of VOR checkpoints	AT RWY HOLDING POSITION OF TAXI 'A'.
5	Position of INS checkpoints	NIL
6	Remarks	1. Taxi Holding Point Coordinates/Elevation: TWY A: 242645.76962N 0864221.66180E/771 FT TWY B: 242645.79862N 0864247.71665E/796 FT TWY C: 242651.71780N 0864154.25398E/790 FT 2. RWY & TWY Intersection Coordinates/Elevation: TWY A: 242648.75918N 0864221.66032E/795 FT TWY B: 242648.78420N 0864247.71081E/798 FT TWY C: 242648.72454N 0864154.25968E/773 FT 3. Vertical Datum EGM 08

VEDO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft Stand Identification Sign – Illuminated signage & Marking Available at Parking stand. Taxiway Guidelines: Taxiing guidance signs available at all the intersection of TWY and RWY and at all holding position Guidelines at Apron. VDGS: Not Available

2	Runway and taxiway markings and lights	RWY: Markings: Designator, Aiming Point, Centreline, Touch Down Zone, Runway Edge, Runway Threshold marking, Turnpad Lights: RWY Edge Lights, RWY End Lights, Threshold Lights TWY: Marking: TWY Edge, Centreline, Rwy Holding Position at all taxiway, VOR Checkpoint at TWY A. Lights: TWY Edge Lights
3	Stop bars (if any)	NIL
4	Remarks	Apron Flood Light: 04 (Main Apron) & 03 (DRDO Apron) WDI: 02 nos. are Available (illuminated) Landing T: Available

VEDO AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
27/APCH 09/TKOF	NATURAL HIGHPOINT	242708.2N 0864501.9E	996 FT	NIL	HILL TOP
27/APCH 09/TKOF	NATURAL HIGHPOINT	242704.1N 0864501.9E	994 FT	NIL	HILL TOP
27/APCH 09/TKOF	NATURAL HIGHPOINT	242706.8N 0864503.2E	995 FT	NIL	HILL TOP
27/APCH 09/TKOF	NATURAL HIGHPOINT	242659.8N 0864504.1E	973 FT	NIL	HILL TOP
In circling area and at AD	OTHER	242645.8N 0864142.4E	782 FT	NIL	W.D.I
In circling area and at AD	OTHER	242651.4N 0864245.3E	815 FT	NIL	W.D.I
In circling area and at AD	ANTENNA	242638.9N 0864216.4E	865 FT	NIL	ANT.TOP ON ATC BUILDING (BLDG TOP 260.6M, BEACON TOP 261.7M)
In circling area and at AD	OTHER	242640.1N 0864243.2E	857 FT	NIL	FLOOD LIGHT MAST
In circling area and at AD	ANTENNA	242645.1N 0864250.8E	829 FT	NIL	MET ANTENNA
In circling area and at AD	NATURAL HIGHPOINT	243036.0N 0863539.0E	1708 FT	NIL	HILL TOP
In circling area and at AD	OTHER	242759.2N 0864058.5E	954 FT	NIL	CELL PHONE MAST
In circling area and at AD	OTHER	242835.1N 0864120.2E	957 FT	NIL	CELL PHONE MAST
In circling area and at AD	OTHER	242901.3N 0864128.2E	976 FT	NIL	CELL PHONE MAST

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	242846.0N 0864132.0E	965 FT	NIL	CELL PHONE MAST
In circling area and at AD	OTHER	242849.0N 0864216.8E	1000 FT	NIL	CELL PHONE MAST
In circling area and at AD	OTHER	242815.9N 0864220.9E	980 FT	NIL	CELL PHONE MAST
In circling area and at AD	TREE	242656.1N 0864230.2E	883 FT	NIL	GROUP OF TREE
In circling area and at AD	OTHER	242831.8N 0864244.2E	1011 FT	NIL	CELL PHONE MAST
In circling area and at AD	OTHER	242828.4N 0864300.2E	1036 FT	NIL	CELL PHONE MAST
In circling area and at AD	OTHER	242727.5N 0864308.0E	993 FT	NIL	CELL PHONE MAST
In circling area and at AD	NATURAL HIGHPOINT	242900.0N 0864951.0E	1422 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	242954.0N 0865015.1E	2377 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	242903.3N 0865048.3E	2334 FT	NIL	HILL
In circling area and at AD	OTHER	242859.1N 0865050.3E	2307 FT	NIL	ROPEWAY TOP ON HILL
In circling area and at AD	NATURAL HIGHPOINT	242839.0N 0865100.0E	2026 FT	NIL	HILL TOP
In circling area and at AD	NATURAL HIGHPOINT	242357.0N 0865300.1E	1298 FT	NIL	HILL TOP

VEDO AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Aerodrome Meteorological Station Deoghar
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As per ATS
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Patna
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend Half hourly METARs
5	Information on how briefing and/or consultation is provided	Available
6	Types of flight documentation supplied and language(s) used in flight documentation	English
7	Charts and other information displayed or available for briefing or consultation	Available

8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Radar: Not available. Radar information may be provided from IMD website/OLBS Satellite images available METAR DCWIS installed at RWY 27 with PWD sensor DIGITAL PORTABLE BAROMETER, PSYCHROMETER (as a backup to DCWIS) VIP TOOLKIT: containing hand held anemometer, hand held wind vand and portable pressure cum temperature sensor.
9	The air traffic services unit(s) provided with meteorological information	Deoghar ATS
10	Additional information, e.g. concerning any limitation of service.	NIL

VEDO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
09	89.93 DEG	2500 x 45 M	55/R/B/W/T Concrete	THR: 242648.70N 0864133.57E RWY END: 242648.80N 0864302.32E
27	269.93 DEG	2500 x 45 M	55/R/B/W/T Concrete	THR: 242648.80N 0864302.32E RWY END: 242648.70N 0864133.57E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 758.5FT TDZ: 769.8FT	0.53%	NIL	NIL	2620 x 280 M
THR: 802.2FT TDZ: 798.2FT	-0.53%	NIL	NIL	2620 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M			1. All elevations in EGM 08. 2. Slope of RWY 09: 0M-870M: 0.75% 870M-1440M: 0.63% 1440M-2500M: 0.30%

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M			1. All elevations in EGM 08. 2. Slope of RWY 27: 0M-1060M: -0.30% 1060M-1630M: -0.63% 1630M-2500M: -0.75%

VEDO AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
09	2500	2500	2500	2500	
27	2500	2500	2500	2500	

VEDO AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
09	CAT I 900 M	Green Wing bar not available	PAPI LEFT/3.00 DEG MEHT (16.30M)	
27	SALS 420 M LIH	Green Wing bar not available	PAPI LEFT/3.00 DEG MEHT (16.19M)	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2500 M 60 M White LIH	Red		Colour of last 600M of Edge light is Yellow
	2500 M 60 M White LIH	Red		Colour of last 600M of Edge light is Yellow

VEDO AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Top of ATC Tower 20-30 flashes per minute Alternate White & Green As ATS Hrs
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Provided near TWY-A
		Anemometer	NIL
3	Taxiway edge and taxiway centre line lights;	Edge	MIRL
		Centre Line	NIL
4	Secondary power supply including switch-over time;	DG Set & UPS Available with switchover time 01 sec	
5	Remarks	NIL	

VEDO AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	Not established

VEDO AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 242645N 0864225E within a 25NM radius.
2	Vertical limits	FL 105
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Deoghar Tower, English
5	Transition altitude	5000 FT
6	Hours of applicability	HO
7	Remarks	1. ATC Frequencies: i. Deoghar APP: 119.350 MHz 120.825 MHz ii. Deoghar TWR: 119.350 MHz 120.825 MHz 2. Deoghar Approach Control Unit is combined with Deoghar Aerodrome Control Tower.

VEDO AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Deoghar Tower	119.350 MHZ	
APP	Deoghar Tower	120.825 MHZ	
TWR	Deoghar Tower	119.350 MHZ	
TWR	Deoghar Tower	120.825 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HO	1.Main FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1.Backup FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	AS ATS	MAIN
	AS ATS	BACKUP

VEDO AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 09 CAT I	IDGR	108.500 MHz	HO
GP 09		329.900 MHz	HO
DME ILS 09	IDGR	CH22X	HO
DVOR/DME	DGH	117.200 MHz CH119X	AS ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
242648.8N 0864313.9E			
242652.7N 0864144.9E			GLIDE ANGLE 3 DEG
242652.8N 0864144.9E	781 FT		ELEVATION IN EGM-08
242645.3N 0864319.5E	822 FT		1. DME COLOCATED WITH DVOR 2. VERICAL DATUM: EGM 08

VEDO AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.
• 180 degree turn prohibited on RWY, aircraft advised to use turn pad for 180 degree turn.

VEDO AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VEDO AD 2.22 FLIGHT PROCEDURES

NIL

VEDO AD 2.23 ADDITIONAL INFORMATION

180 degree turn prohibitted on RWY, aircraft advised to use turn pad for 180 degree turn.

VEDO AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aerodrome Chart (13 June 2024)
2 Aircraft Parking/Docking Chart (13 June 2024)
3 Aerodrome Obstacle Chart Type-A (Operating Limitations) RWY 09/27 (13 June 2024)
4 Aerodrome Obstacle Chart Type B (13 June 2024)
5 Instrument Approach Chart - ILS or LOC Procedure RWY 09 (CAT A/B/C) (08 August 2024)
6 Instrument Approach Chart - VOR Procedure RWY 09 (CAT A/B/C) (08 August 2024)
7 Instrument Approach Chart - RNP Y Procedure RWY 09 (CAT A/B/C) (08 August 2024)
8 Coding Table - RNP Y Procedure RWY 09
9 Instrument Approach Chart - RNP Y Procedure RWY 27 (CAT A/B/C) (08 August 2024)
10 Coding Table - RNP Y Procedure RWY 27
11 Instrument Approach Chart - RNP Z Procedure RWY 27 (CAT A/B/C) (LPV Only) (08 August 2024)
12 Coding Table - RNP Z Procedure RWY 27 (08 August 2024)
13 Instrument Approach Chart - VOR Procedure RWY 27 (CAT A/B/C) (17 April 2025)

VEDO AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3