# AD 2. AERODROMES

## VEMN AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VEMN - DIBRUGARH AIRPORT, DIBRUGARH

## VEMN AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | | |
|---|---|---|---|
| 1 | Aerodrome reference point coordinates and its site | 272856N 0950101E<br>MAG BRG 48.5 DEG / 1256M From physical beginning of RWY 05 | |
| 2 | Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves | 090 DEG, 11KM from Dibrugarh | |
| 3 | Aerodrome elevation and reference temperature | 361 FT / 31.0 DEG C | |
| 4 | Magnetic variation, date of information and annual change | 0.50 DEG W (2010) /0.017 DEG W | |
| 5 | Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available) | Airports Authority of India,<br>Dibrugarh Airport<br>Dibugarh-786012, | |
| | | Telephone: | (91) 373 2382755 (91) 602617792 |
| | | Fax: | |
| | | AFS: | VEMNZTZX/VEMNYHYX |
| | | Email: | apddib@aai.aero |
| 6 | Types of traffic permitted (IFR/VFR) | IFR/VFR | |
| 7 | Remarks | Elevation in EGM08 | |

## VEMN AD 2.3 OPERATIONAL HOURS

| | | |
|---|---|---|
| 1 | Aerodrome Operator | 0330-1200 UTC (0900-1730 IST)<br>SAT, SUN + HOL: NIL |
| 2 | Custom and immigration | NIL |
| 3 | Health and sanitation | NIL |
| 4 | AIS briefing office | As ATS |
| 5 | ATS reporting office (ARO) | As ATS |
| 6 | MET Briefing office | As ATS |
| 7 | Air Traffic Service | Consult Current NOTAM for ATS HR |
| 8 | Fuelling | As ATS |
| 9 | Handling | As ATS |
| 10 | Security | H24 |
| 11 | De-icing | NIL |
| 12 | Remarks | 1.Outside of ATS hours, services are available O/R, with 24 HR PN to AD.<br>2.Night landing facility available. |

## VEMN AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|---|
| 1 | Cargo-handling facilities | Nil |
| 2 | Fuel and Oil types | ATF/JET A1 |
| 3 | Fuelling facilities and capacity | 4 BOWSERS,(ONE 9000 LITRES, TWO 12000 LITRES, ONE 16000 LITRES), 500 to 700 LITRES/ MIN. |
| 4 | De-icing facilities | NIL |
| 5 | Hangar space for visiting aircraft | Nil |

| | | |
|---|---|---|
| 6 | Repair facilities for visiting aircraft | Nil |
| 7 | Remarks | NIL |

**VEMN AD 2.5 PASSENGER FACILITIES**

| | | |
|---|---|---|
| 1 | Hotel(s) at or in the vicinity of aerodrome | In The City |
| 2 | Restaurant(s) at or in the vicinity of aerodrome | In The City |
| 3 | Transportation possibilities | Taxi In The City / Airport |
| 4 | Medical Facilities | First Aid At AD. Hospitals In The City |
| 5 | Bank and post office at or in the vicinity of aerodrome | Banks: Near Aerodrome<br>Post office: Near Aerodrome |
| 6 | Tourist office | Nil |
| 7 | Remarks | Holiday Travel- In The Airport |

**VEMN AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

| | | |
|---|---|---|
| 1 | Aerodrome category for fire fighting | Within ATS HR: CAT-7 |
| 2 | Rescue equipment | Available as per category. |
| 3 | Capability for removal of disabled aircraft | 1. The critical aircraft for the airport is A320.<br>2. Primary responsibility for removal of disabled aircraft rests with the concerned airline.<br>3.The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit.<br>4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations:<br>Aerodrome Coordinator: Airport Director<br>Contact: 0373-2382755<br>M-+916026177692<br>Email-apddib@aai.aero |
| 4 | Remarks | NIL |

**VEMN AD 2.7 SEASONAL AVAILABILITY CLEARING**

| | | |
|---|---|---|
| 1 | Type(s) of clearing equipment | NIL |
| 2 | Clearance priorities | NIL |
| 3 | Remarks | NIL |

**VEMN AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA**

| | | |
|---|---|---|
| 1 | Designation, surface and strength of aprons | Refer Aircraft Parking/Docking Chart |
| 2 | Designation, width, surface and strength of taxiways | Refer Aircraft Parking/Docking Chart |
| 3 | Location and elevation of altimeter checkpoints | NIL |
| 4 | Location of VOR checkpoints | i. At TWY D: 272900.30N 0950106.81E/ ELEV 358 FT<br>ii. At TWY E: 272904.55N 0950111.63E/ ELEV 357 FT<br>iii. At TWY G: 272909.62N 0950117.45E/ ELEV 356 FT |
| 5 | Position of INS checkpoints | TWY D & E |

| | | |
|---|---|---|
| 6 | Remarks | **1. Coordinates of Taxi Holding Position:**<br>i. TWY D: 272900.37316N 0950106.72363E / ELEV: 358FT<br>ii. TWY E: 272904.63016N 0950111.54518E / ELEV: 357FT<br>iii. TWY G: 272909.69941N 0950117.36059E / ELEV: 356FT<br>**2. Coordinates of RWY & Taxi Intersection:**<br>i. TWY D: 272902.45663N 0950104.43505E / ELEV: 358FT<br>ii. TWY E: 272906.70649N 0950109.25000E / ELEV: 358FT<br>iii. TWY G: 272911.79606N 0950115.01655E / ELEV: 358FT<br>**3. All elevations in EGM08** |

## VEMN AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

| | | |
|---|---|---|
| 1 | Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands | Taxiing guidance provided on R/T |
| 2 | Runway and taxiway markings and lights | RWY<br>Markings<br>Designation, THR, TDZ, Centerline, Edge, Fixed Distance, Side Strip.<br>Lights<br>EDGE/END/THR<br><br>TWY<br>Marking<br>Centerline, Holding Positions at all TWY/RWY intersection.<br>Lights<br>Edge |
| 3 | Stop bars (if any) | Nil |
| 4 | Remarks | NIL |

## VEMN AD 2.10 AERODROME OBSTACLES

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| 23/TKOF<br>05/APCH | TREE | 272756.8N<br>0950003.5E | 432 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | TREE | 272810.0N<br>0950009.2E | 408 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | WALL | 272824.3N<br>0950027.2E | 369 FT | NIL | Wall |
| 23/TKOF<br>05/APCH | TREE | 272808.6N<br>0950009.0E | 421 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | TREE | 272815.3N<br>0950014.6E | 409 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | TREE | 272818.8N<br>0950009.5E | 418 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | TREE | 272813.1N<br>0950017.4E | 422 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | TREE | 272819.5N<br>0950022.5E | 408 FT | NIL | Group of Tree |
| 23/TKOF<br>05/APCH | TREE | 272809.6N<br>0950010.9E | 450 FT | NIL | Group of Trees |
| 23/TKOF<br>05/APCH | OTHER | 272928.1N<br>0950133.4E | 373 FT | NIL | Mobile Road Traffic (Road Elev.108.8 M +Traffic Ht.5.0 M) |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| 23/TKOF 05/APCH | TREE | 272820.7N 0950005.7E | 406 FT | NIL | Group of Trees |
| 23/TKOF 05/APCH | OTHER | 272835.9N 0950039.3E | 360 FT | NIL | Gate |
| 23/TKOF 05/APCH | OTHER | 272840.8N 0950034.3E | 360 FT | NIL | Airport Boundary Wall with Fencing on Top |
| 23/TKOF 05/APCH | OTHER | 272836.3N 0950038.8E | 362 FT | NIL | Airport Boundary Wall with Fencing on Top |
| 23/TKOF 05/APCH | OTHER | 272835.1N 0950040.1E | 362 FT | NIL | Airport Boundary Wall with Fencing on Top |
| 23/TKOF 05/APCH | OTHER | 272837.6N 0950036.2E | 365 FT | NIL | Temporary Airport Boundary Wall with Fencing on Top |
| 23/TKOF 05/APCH | OTHER | 272840.5N 0950031.8E | 368 FT | NIL | Mobile Road Traffic (Road Elev.107.3 M +Traffic Ht.5.0 M) |
| 23/TKOF 05/APCH | TREE | 272806.4N 0950013.9E | 443 FT | NIL | Group of Tree |
| 23/TKOF 05/APCH | OTHER | 272841.6N 0950033.4E | 368 FT | NIL | Mobile Road Traffic (Road Elev.107.5 M +Traffic Ht.5.0 M) |
| 23/TKOF 05/APCH | TREE | 272820.9N 0950028.1E | 406 FT | NIL | Group of Tree |
| 23/TKOF 05/APCH | TREE | 272812.3N 0950020.9E | 431 FT | NIL | Group of Tree |
| 23/TKOF 05/APCH | OTHER | 272832.3N 0950036.3E | 386 FT | NIL | Arrester on Antenna |
| 23/TKOF 05/APCH | OTHER | 272924.8N 0950138.9E | 376 FT | NIL | Mobile Road Traffic (Road Elev.109.7 M +Traffic Ht.5.0 M) |
| 23/TKOF 05/APCH | OTHER | 272924.6N 0950138.5E | 375 FT | NIL | Mobile Road Traffic (Road Elev.109.4 M +Traffic Ht.5.0 M) |
| 23/TKOF 05/APCH | FENCE | 272928.5N 0950126.0E | 365 FT | NIL | Airport Boundary Wall With Fencing on Top |
| 23/APCH 05/TKOF | NAVAID | 272924.8N 0950129.7E | 366 FT | NIL | Localizer Antenna Centre |
| 23/APCH 05/TKOF | OTHER | 272924.8N 0950129.7E | 366 FT | NIL | Obstacle Light on Localizer |
| 23/APCH 05/TKOF | OTHER | 272924.6N 0950130.1E | 369 FT | LGTD | Arrester on Localizer |
| 23/APCH 05/TKOF | NAVAID | 272923.2N 0950127.9E | 364 FT | NIL | Localizer Monitor Antenna |
| 23/APCH 05/TKOF | OTHER | 272929.5N 0950126.9E | 372 FT | NIL | Mobile Road Traffic (Road Elev.108.4 M +Traffic Ht.5.0 M) |
| 23/APCH 05/TKOF | OTHER | 272928.1N 0950126.4E | 370 FT | NIL | Airport Boundary Wall With Fencing On Top |
| 23/APCH 05/TKOF | BUILDING | 272923.3N 0950131.6E | 370 FT | NIL | Localizer Hut |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| 23/APCH 05/TKOF | OTHER | 272923.3N 0950132.1E | 375 FT | NIL | Mobile Road Traffic (Road Elev. 109.3m+5m) |
| 23/APCH 05/TKOF | OTHER | 272928.8N 0950126.3E | 373 FT | NIL | Mobile Road Traffic (Road Elev.108.8 M +Traffic Ht.5.0 M) |
| 23/APCH 05/TKOF | OTHER | 272923.3N 0950131.6E | 374 FT | NIL | Arrester on Localizer Hut |
| 23/APCH 05/TKOF | TREE | 272928.7N 0950140.5E | 395 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | OTHER | 272920.9N 0950130.3E | 373 FT | NIL | Mobile Road Traffic (Road Elev.108.7 M +Traffic Ht.5.0 M) |
| 23/APCH 05/TKOF | OTHER | 272925.7N 0950125.1E | 375 FT | NIL | Mobile Road Traffic (Road Elev.109.3 M +Traffic Ht.5.0 M |
| 23/APCH 05/TKOF | TREE | 272927.8N 0950140.1E | 398 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272928.9N 0950140.3E | 404 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272927.2N 0950139.0E | 402 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272940.1N 0950146.4E | 408 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | OTHER | 272924.8N 0950129.7E | 366 FT | NIL | Obstacle Light on Localizer |
| 23/APCH 05/TKOF | TREE | 272941.3N 0950139.0E | 402 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272939.0N 0950140.8E | 404 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272940.6N 0950138.6E | 405 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272937.1N 0950138.2E | 399 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272939.6N 0950144.0E | 411 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272940.3N 0950142.6E | 411 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272937.9N 0950136.3E | 400 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272931.0N 0950141.2E | 397 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272937.9N 0950147.5E | 417 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272940.1N 0950138.6E | 409 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272942.0N 0950138.6E | 412 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272939.7N 0950142.9E | 414 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272950.8N 0950145.8E | 434 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272940.1N 0950144.8E | 422 FT | NIL | Group of Tree |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| 23/APCH 05/TKOF | TREE | 272947.8N 0950144.3E | 432 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272937.0N 0950133.5E | 404 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272936.4N 0950133.4E | 403 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272929.8N 0950143.9E | 408 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272939.2N 0950141.6E | 419 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272936.9N 0950136.5E | 410 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272937.0N 0950133.7E | 408 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272936.0N 0950138.7E | 419 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272943.7N 0950145.3E | 439 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272935.9N 0950136.1E | 417 FT | NIL | Group of Tree |
| 23/APCH 05/TKOF | TREE | 272945.3N 0950140.7E | 440 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272945.9N 0950140.9E | 443 FT | NIL | Group of Trees |
| 23/APCH 05/TKOF | TREE | 272937.5N 0950140.8E | 434 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272837.7N 0950047.2E | 389 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272837.2N 0950046.6E | 390 FT | NIL | Group of Trees |
| In circling area and at AD | OTHER | 272902.1N 0950119.7E | 436 FT | NIL | Arrester on Terminal Building |
| In circling area and at AD | OTHER | 272841.1N 0950032.7E | 360 FT | NIL | Fencing |
| In circling area and at AD | POLE | 272843.0N 0950051.9E | 381 FT | NIL | Electric Pole |
| In circling area and at AD | TREE | 272929.7N 0950123.0E | 407 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272930.9N 0950122.2E | 427 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272846.2N 0950056.7E | 393 FT | NIL | Group of Tree |
| In circling area and at AD | OTHER | 272858.3N 0950112.9E | 416 FT | NIL | Arrester on ATC Building |
| In circling area and at AD | TREE | 272836.0N 0950045.0E | 390 FT | NIL | Group of Tree |
| In circling area and at AD | OTHER | 272846.7N 0950054.1E | 366 FT | NIL | Cooling Pit Corner |
| In circling area and at AD | TREE | 272833.2N 0950018.9E | 408 FT | NIL | Group of Tree |
| In circling area and at AD | OTHER | 272825.5N 0950031.1E | 372 FT | NIL | Concrete Mixer Plant |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| In circling area and at AD | OTHER | 272850.9N 0950112.8E | 495 FT | NIL | Cell Phone Mast |
| In circling area and at AD | OTHER | 272924.2N 0950142.3E | 419 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272836.4N 0950046.2E | 401 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272908.3N 0950100.4E | 397 FT | NIL | Tree |
| In circling area and at AD | TREE | 272928.5N 0950122.3E | 406 FT | NIL | Group of Tree |
| In circling area and at AD | BUILDING | 272918.2N 0950114.6E | 370 FT | NIL | DVOR Hut |
| In circling area and at AD | OTHER | 272840.5N 0950031.8E | 368 FT | NIL | Mobile Road Traffic (Road Elev.107.3 M +Traffic Ht.5.0 M) |
| In circling area and at AD | TREE | 272923.3N 0950115.8E | 411 FT | NIL | Group of Trees |
| In circling area and at AD | BUILDING | 272845.0N 0950037.0E | 370 FT | NIL | Water Tank on Building |
| In circling area and at AD | TREE | 272845.5N 0950031.2E | 426 FT | NIL | Group of Trees |
| In circling area and at AD | OTHER | 272826.2N 0950031.2E | 368 FT | NIL | Shed |
| In circling area and at AD | TREE | 272818.3N 0950028.8E | 427 FT | NIL | Group of Tree |
| In circling area and at AD | OTHER | 272826.1N 0950031.8E | 377 FT | NIL | Concrete Mixer Plant |
| In circling area and at AD | TREE | 272841.9N 0950051.7E | 401 FT | NIL | Group of Trees |
| In circling area and at AD | OTHER | 272841.6N 0950033.4E | 369 FT | NIL | Mobile Road Traffic (Road Elev.107.5 M +Traffic Ht.5.0 M) |
| In circling area and at AD | TREE | 272840.4N 0950053.4E | 432 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272925.9N 0950118.8E | 416 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272820.7N 0950005.7E | 406 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272818.1N 0950000.1E | 430 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272818.4N 0950028.2E | 428 FT | NIL | Group of Trees |
| In circling area and at AD | NAVAID | 272918.2N 0950114.4E | 380 FT | NIL | DVOR Main Antenna Centre |
| In circling area and at AD | TREE | 272847.3N 0950034.4E | 425 FT | NIL | Group of Tree |
| In circling area and at AD | OTHER | 272922.5N 0950115.8E | 412 FT | NIL | Structure |
| In circling area and at AD | NAVAID | 272918.3N 0950114.2E | 385 FT | NIL | DVOR DME |
| In circling area and at AD | TREE | 272844.3N 0950032.0E | 415 FT | NIL | Group of Tree |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| In circling area and at AD | TREE | 272925.8N 0950119.3E | 417 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272847.6N 0950034.4E | 430 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272820.9N 0950028.1E | 406 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272843.1N 0950054.4E | 424 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272834.4N 0950040.5E | 384 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272821.7N 0950029.0E | 410 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272812.3N 0950020.9E | 431 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272819.4N 0950028.3E | 428 FT | NIL | Group of Trees |
| In circling area and at AD | OTHER | 272917.8N 0950114.3E | 386 FT | NIL | Arrester on DVOR |
| In circling area and at AD | TREE | 272843.0N 0950033.8E | 400 FT | NIL | Group of Trees |
| In circling area and at AD | TREE | 272806.4N 0950013.9E | 443 FT | NIL | Group of Trees |
| In circling area and at AD | OTHER | 272847.0N 0950104.2E | 531 FT | NIL | Crane |
| In circling area and at AD | OTHER | 272902.2N 0950057.9E | 361 FT | NIL | Light |
| In circling area and at AD | OTHER | 272857.0N 0950103.4E | 361 FT | NIL | LPG Bird Scare |
| In circling area and at AD | FENCE | 272901.8N 0950057.9E | 362 FT | NIL | LPG Bird Scare |
| In circling area and at AD | TREE | 272857.2N 0950105.7E | 361 FT | NIL | Aerodrome Marker |
| In circling area and at AD | OTHER | 272858.9N 0950053.7E | 363 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | OTHER | 272912.6N 0950109.2E | 360 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | OTHER | 272855.9N 0950101.9E | 364 FT | NIL | Sign Board |
| In circling area and at AD | OTHER | 272839.3N 0950043.4E | 360 FT | NIL | LPG Bird Scare |
| In circling area and at AD | OTHER | 272910.5N 0950118.6E | 361 FT | NIL | Sign Board |
| In circling area and at AD | OTHER | 272842.7N 0950047.2E | 362 FT | NIL | Sign Board |
| In circling area and at AD | OTHER | 272840.9N 0950046.1E | 361 FT | NIL | Dumped Soil |
| In circling area and at AD | BUILDING | 272849.7N 0950043.3E | 362 FT | NIL | Security Hut |
| In circling area and at AD | OTHER | 272846.0N 0950039.2E | 361 FT | NIL | Airport Boundary Wall With Fencing On Top |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| In circling area and at AD | BUILDING | 272853.6N 0950047.4E | 363 FT | NIL | Building |
| In circling area and at AD | BUILDING | 272900.3N 0950055.6E | 364 FT | NIL | Security Hut |
| In circling area and at AD | OTHER | 272843.4N 0950048.0E | 363 FT | NIL | LPG Bird Scare |
| In circling area and at AD | OTHER | 272902.6N 0950058.7E | 364 FT | NIL | Shed |
| In circling area and at AD | OTHER | 272902.9N 0950059.1E | 364 FT | NIL | Shed |
| In circling area and at AD | OTHER | 272840.8N 0950034.3E | 360 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | OTHER | 272835.9N 0950039.3E | 360 FT | NIL | Gate |
| In circling area and at AD | TREE | 272848.5N 0950054.2E | 364 FT | NIL | Dumped Soil |
| In circling area and at AD | OTHER | 272843.7N 0950036.5E | 363 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | OTHER | 272836.3N 0950038.8E | 362 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | OTHER | 272912.4N 0950110.1E | 364 FT | NIL | Security Hut |
| In circling area and at AD | OTHER | 272910.6N 0950119.2E | 364 FT | NIL | Shed |
| In circling area and at AD | OTHER | 272835.1N 0950040.1E | 362 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | POLE | 272900.0N 0950054.7E | 368 FT | NIL | Pole |
| In circling area and at AD | OTHER | 272837.5N 0950042.9E | 364 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | OTHER | 272837.6N 0950036.2E | 365 FT | NIL | Temporary Airport Boundary Wall with Fencing on Top |
| In circling area and at AD | BUILDING | 272844.1N 0950050.0E | 369 FT | NIL | Hut |
| In circling area and at AD | OTHER | 272926.0N 0950124.0E | 371 FT | NIL | Airport Boundary Wall With Fencing On Top |
| In circling area and at AD | BUILDING | 272904.0N 0950059.0E | 372 FT | NIL | Water Tank on Building |
| In circling area and at AD | BUILDING | 272843.3N 0950049.0E | 372 FT | NIL | GP Hut |
| In circling area and at AD | TREE | 272921.8N 0950119.6E | 374 FT | NIL | Tree |
| In circling area and at AD | TREE | 272902.3N 0950057.4E | 379 FT | NIL | Tree |
| In circling area and at AD | NAVAID | 272843.1N 0950049.0E | 378 FT | NIL | GP DME Antenna |
| In circling area and at AD | NAVAID | 272841.4N 0950046.9E | 378 FT | NIL | GP Monitor Antenna |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| In circling area and at AD | NAVAID | 272857.7N 0950105.1E | 380 FT | NIL | Windsock |
| In circling area and at AD | TREE | 272903.5N 0950058.6E | 380 FT | NIL | Tree |
| In circling area and at AD | NAVAID | 272855.5N 0950049.4E | 381 FT | NIL | Windsock |
| In circling area and at AD | OTHER | 272857.7N 0950105.1E | 381 FT | NIL | Obstacle Light on Windsock |
| In circling area and at AD | POLE | 272917.7N 0950114.5E | 388 FT | NIL | DVOR DME (NEW) |
| In circling area and at AD | OTHER | 272832.3N 0950036.3E | 386 FT | NIL | Arrester on Antenna |
| In circling area and at AD | NAVAID | 272843.2N 0950048.9E | 411 FT | NIL | GP Main Antenna |
| In circling area and at AD | TREE | 272816.5N 0950027.9E | 427 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272942.2N 0950135.4E | 418 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272941.0N 0950138.3E | 402 FT | NIL | Group of Tree |
| In circling area and at AD | OTHER | 272946.2N 0950138.3E | 440 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272927.7N 0950144.2E | 403 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 272926.3N 0950145.8E | 432 FT | NIL | Group of Tree |

## VEMN AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|---|---|---|
| 1 | Name of the associated meteorological office | AMO Mohanbari |
| 2 | Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours | H24 |
| 3 | Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts | AMO Mohanbari (During ATC Watch Hrs),<br>AMO Guwahati (Beyond ATC Watch Hours)<br>Valid for 09 Hrs issued at 03 Hours Intercal |
| 4 | Availability of the trend forecast for the aerodrome and interval of issuance | Trend<br>Half Hourly ( Valid for next 02 Hours)<br>During ATC Watch Hours and Hourly (Valid for next 02 Hours) Beyond ATC Watch Hours |
| 5 | Information on how briefing and/or consultation is provided | Physical and/or through online mode |
| 6 | Types of flight documentation supplied and language(s) used in flight documentation | Chart, Image, Text form and tabular form. |
| 7 | Charts and other information displayed or available for briefing or consultation | S,U85 ,U70,U50,U30,U25, U15, U10, P30,<br>P25, P20, SW [Upto FL 460] |
| 8 | Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images; | Radar and Satellite display work station |
| 9 | The air traffic services unit(s) provided with meteorological information | VEMN Dibrugarh ATC |

| | | |
|---|---|---|
| 10 | Additional information, e.g. concerning any limitation of service. | Integrated Aviation Meteorological System (DCWIS) at RWY 05. The System will provide following information on Digital Display:<br>1. Wind Direction- Instantaneous, 2 Minute Average and 10 Minute Average.<br>2. Wind Speed - Instantaneous, 2 Minute Average and 10 Minute Average.<br>3. Air Temperature: Actual Dry Bulb Temperature.<br>4. Humidity: Actual Humidity in Percent<br>5. DEW Point Temperature: In Degree Celsius.<br>6. Air Pressure: QNH & QFE in hPa.<br>7. The RVR system at RWY 05 will provide RVR and MOR data displayed on PC monitor. In case of unserviceability of DCWIS System Manual RVR is provided as requested by ATC.<br>8.The Display Location is the Met Officer Position at ATC Tower |

## VEMN AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| Designations | TRUE Bearings | Dimensions of RWY (M) | Strength of pavement (PCR) and associated data) and surface of runway and associated stopways | Geographical coordinates for threshold and runway end |
|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 |
| 05 | 45.27 DEG | 2291 x 45 M | 828/F/C/W/T<br>Asphalt | THR:<br>272829.39N<br>0950027.04E<br>RWY END:<br>272921.80N<br>0950126.30E |
| 23 | 225.27 DEG | 2291 x 45 M | 828/F/C/W/T<br>Asphalt | THR:<br>272917.65N<br>0950121.60E<br>RWY END:<br>272829.39N<br>0950027.04E |

| THR elevation and highest elevation of TDZ of precision APP RWY | Slope of runway and associated stopway | Dimensions of stopway (M) | Dimensions of clearway (M) | Dimensions of strips (M) |
|---|---|---|---|---|
| 6 | 7 | 8 | 9 | 10 |
| THR: 355.0FT<br>TDZ: 355.0FT | 0.05% | NIL | NIL | 2411 x 260 M |
| THR: 358.0FT<br>TDZ: 359.0FT | -0.05% | NIL | NIL | 2411 x 260 M |

| Dimensions of runway end safety areas | Location and description of arresting system (if any) | Existence of an obstacle-free zone | Remarks. |
|---|---|---|---|
| 11 | 12 | 13 | 14 |
| 180M x 90M | | NIL | 1. PCR RWY 05:<br>0-363M 745/R/B/W/T, Concrete<br>363-2291/F/C/W/T, Asphalt<br>2. From the beginning of Rwy 05, from Ch. 0 to to 461 M, a triangular portion of RWY on the left side of the centre line having a base of 0.90 M at Ch. 0 has a PCR value of 300/R/B/W/T.<br>3. Geoid Model: EGM 08 |
| 240M x 90M | | NIL | 1. PCR RWY 05:<br>0-363M 745/R/B/W/T, Concrete<br>363-2291/F/C/W/T, Asphalt<br>2. From the beginning of Rwy 05, from Ch. 0 to to 461 M, a triangular portion of RWY on the left side of the centre line having a base of 0.90 M at Ch. 0 has a PCR value of 300/R/B/W/T.<br>3. Geoid Model: EGM 08 |

**VEMN AD 2.13 DECLARED DISTANCES**

| RWY Designator | Take-off run available TORA (M) | Take-off distance available TODA (M) | Accelerate distance available ASDA (M) | Landing distance available LDA (M) | Remarks (including runway entry or start point where alternative reduced declared distances have been declared) |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 05 | 2291 | 2291 | 2291 | 2291 | |
| 23 | 2291 | 2291 | 2291 | NIL | |

**VEMN AD 2.14 APPROACH AND RUNWAY LIGHTING**

| Runway Designator | Type, length and intensity of approach lighting system | Runway threshold lights, colour and wing bars | Type of visual slope indicator system | Length of runway touchdown zone lights |
|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 |
| **05** | CAT I<br>900 M<br>LIH | Green | PAPI<br>LEFT/3.00 DEG<br>MEHT<br>(51.97FT) | |
| **23** | | Green | NIL | |

| Length, spacing, colour and intensity of runway centre line lights | Length, spacing, colour and intensity of runway edge lights | Colour of runway end lights and wing bars | Length and colour of stopway lights | Remarks |
|---|---|---|---|---|
| 6 | 7 | 8 | 9 | 10 |
| | 2291 M<br>60 M<br>White<br>LIH | Red | | LAST 600M OF RWY 05 RWY EDGE LIGHT AMBER |
| | 2291 M<br>60 M<br>White<br>LIH | Red | | NIL |

## VEMN AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

| | | | |
|---|---|---|---|
| 1 | Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any) | ABN | At Tower Building, Rotation Rate of ABN FLG W & G is 12 RPM. As ATS Hr |
| | | IBN | NIL |
| 2 | Location and lighting (if any) of anemometer/ landing direction indicator; | LDI | 215M west of control Tower |
| | | Anemometer | South of RWY 05<br>(Latitude 272832.34N,<br>Longitude 0950036.32E) |
| 3 | Taxiway edge and taxiway centre line lights; | Edge | Avbl. |
| | | Centre Line | ---------- |
| 4 | Secondary power supply including switch-over time; | Secondary Power supply to all lighting at AD. Switch-over time : Less than 1 SEC. | |
| 5 | Remarks | Runway Guard lights Available on Taxiway<br>D, E, and G | |

## VEMN AD 2.16 HELICOPTER LANDING AREA

| | | |
|---|---|---|
| 1 | Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area | |
| 2 | TLOF and/or FATO area elevation: | |
| 3 | TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking; | |
| 4 | True bearings of FATO; | |
| 5 | Declared distances available | |
| 6 | Approach and FATO lighting; | |
| 7 | Remarks | 1.For civil helicopter no helipad available, helicopter to land on runway.<br><br>2.For Defence, helipads are available on all taxiway, connecting to IAF Dispersal. |

## VEMN AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

| | | |
|---|---|---|
| 1 | Airspace designation, geographical coordinates and lateral limits | CTR: Area bounded by lines joining points 272902N 0941947E; 274402N 0943247E; 275302N 0945947E; 275102N 0952947E; 271702N 0955447E; 264702N 0945947E to point of origin. |
| 2 | Vertical limits | FL 200 |

| | | |
|---|---|---|
| 3 | Airspace classification | D |
| 4 | Call sign and language(s) of the air traffic services unit providing service; | Dibrugarh Tower, English |
| 5 | Transition altitude | 8000 FT |
| 6 | Hours of applicability | HO |
| 7 | Remarks | Dibrugarh Approach Control Unit is combined with Dibrugarh Aerodrome Control Tower. |

## VEMN AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

| Service Designation | Call sign | Channel(s) | SATVOICE Number(s), if available |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| APP | Dibrugarh Tower | 118.250 MHZ | |
| APP | Dibrugarh Tower | 124.000 MHZ | |
| TWR | Dibrugarh Tower | 118.250 MHZ | |
| TWR | Dibrugarh Tower | 124.000 MHZ | |
| ATIS | ---- | 127.650 MHZ | |

| Logon address, as appropriate | Hours of operation | Remarks |
|---|---|---|
| 5 | 6 | 7 |
| | As ATS | Functions of Approach Control Service provided by Aerodrome Control Tower. |
| | AS ATS | Functions of Approach Control Service provided by Aerodrome Control Tower. |
| | As ATS | Backup Frequency |
| | AS ATS | Main Frequency |
| | AS ATS | NIL |

## VEMN AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid | Identification | Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate | Hours of operation, as appropriate; |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| LOC 05<br>CAT I | IDIB | 109.500 MHz | As ATS |
| GP 05 | | 332.600 MHz | As ATS |
| DME ILS 05 | IDIB | CH32X | As ATS |
| DVOR/DME | DRG | 117.300 MHz<br>CH120X | As ATS |
| NDB | DBR | 265 kHz | As ATS |

| Geographical coordinates of the position of the transmitting antenna | Elevation of transmitting antenna of DME/ elevation of GBAS reference point | Service volume radius from the GBAS reference point | Remarks |
|---|---|---|---|
| 5 | 6 | 7 | 8 |
| 272924.8N<br>0950129.7E | | | |
| 272843.2N<br>0950048.9E | | | |
| 272843.1N<br>0950049.0E | 378 FT | | Elevation in EGM08 |
| 272920.3N<br>0950112.9E | 389 FT | | DMECollocatedwithDVOR.<br>Vertical datum: EGM-08 |
| 272804.1N<br>0950105.6E | | | Vertical datum: EGM08 |

## VEMN AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage. All fixed wing ACFT to make 180 deg turn only at designated RWY turnpad using turnpad marking.

## VEMN AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

## VEMN AD 2.22 FLIGHT PROCEDURES

## RADIO COMMUNICATION FAILURE PROCEDURES

### 1. INTRODUCTION:

The close proximity of Chabua (IAF) and Dibrugarh (AAI) airfields with similar runway orientations, complexity of airspace demarcation and ATS route structure requires close monitoring of air traffic in this area. The constant growth of air traffic in this sector, increased flying intensity at Chabua including future enhancement in operations and proximity of two airfields, necessitates provision of approach control services by single agency. The installation of new SRE ATCR 33S at AF Station Chabua (a combined primary and secondary radar) provides an opportunity to provide surveillance based services instead of procedural control. In this respect a coordination procedure & an MOU has been finalized between AAI & IAF for the provision of surveillance based approach control services by Chabua (IAF ATC) when Chabua local flying area (LFA) is active and Radar is available. Otherwise Dibrugarh (AAI ATC) would provide procedural approach control service in its designated airspace. The control of civil flights proceeding to Dibrugarh shall be transferred by Jorhat (IAF ATC) to appropriate ATC unit. The control of flights departing from Dibrugarh shall be transferred by Dibrugarh ATC to the appropriate ATC unit. Accordingly, the radio communication failures procedures to be followed by aircraft is as mentioned below.

### 2. RADIO COMMUNICATION FAILURE PROCEDURES

The Radio Communication Failure procedures established herein are based on the provisions of ICAO ANNEX 2 and DOC 4444 PANS ATM. The objective is to standardize the actions to be taken by the pilot of arriving and departing aircraft at Dibrugarh Airport experiencing radio communication failure while following bidirectional ATS route W51.

### 3. SCOPE:

The procedures in this document shall be applicable to the pilots of arriving and departing aircraft experiencing radio communication failure at Dibrugarh airport following bi-directional ATS route W51.

### 4. GENERAL:

**4.1** All Transponder equipped aircraft experiencing Radio Communication Failure shall set transponder to Mode A Code 7600 as soon as practicable to indicate that it has experienced air-ground communication failure. (Note: This Requirement of Setting transponder to Mode A Code 7600 in no way imposes any restriction on the pilot's decision to set transponder to Mode A Code 7500 or 7700, whenever required).

**4.2.** An aircraft equipped with other surveillance system transmitters, including ADS-B and ADS-C, might indicate the loss of air-ground communication by all of the available means.

**4.3** Aircraft should log on to Kolkata Data-link (ADS-CPDLC) VECF, if equipped, so that CPDLC connection may be established for communication.

**4.4** As soon as it is known that two-way communication has failed, action shall be taken by Dibrugarh/Chabua ATC to ascertain whether the aircraft is able to receive transmissions from the air traffic control unit by requesting it to execute a specified maneuver which can be observed by radar or ADS-B or to transmit, if possible, a specified signal in order to indicate acknowledgement.

**4.5** Immediately after detection of RCF, the aircraft shall attempt to establish communications with the appropriate air traffic control unit using all other available means. In addition, the aircraft, when forming part of the aerodrome traffic at Dibrugarh aerodrome, shall keep a watch for such instructions as may be issued by visual signals. The RCF aircraft shall also try to contact the appropriate HF frequencies to relay messages to the concerned ATS unit.

**4.6** Unless otherwise required, aircraft shall avoid all restricted areas, active danger areas and Bangladesh airspace if flight plan does not include Dhaka FIR. In case an aircraft is observed approaching any of such airspace, the concerned ATS unit shall inform the respective units accordingly.

**4.7** Pilot shall make blind transmission to ATC of all necessary reports and actions taken by the aircraft, e.g. descent, turn, proceeding to waypoint etc., irrespective of whether partial/ complete RCF has been established or not.

### 5. ASSIGNED RUNWAY AND ITS AVAILABILITY FOR RCF AIRCRAFT:

**5.1** In case of an arriving aircraft experiencing RCF, when Runway for landing has already been advised to the aircraft by ATC, such runway shall be considered as the assigned runway. If an arriving aircraft has not been advised of any runway, Runway 05 shall be considered as assigned runway for such arrival.

**5.2** In case of departures from Dibrugarh returning due to RCF, RWY 05 shall be considered as assigned runway for landing, irrespective of runway used for departure.

**5.3** Runway lights and Approach lights shall be in 'SWITCHED ON' position to indicate the availability of such Runway for aircraft experiencing RCF.

**5.4** Runway and Approach lights in 'SWITCHED OFF' position shall indicate nonavailability of such Runway for aircraft experiencing RCF.

5.5 In case strong tail wind conditions are encountered during approach for the assigned Runway, the aircraft experiencing RCF will carry out a missed approach on assigned runway and after following complete missed approach procedure for such approach, aircraft will carry out the either visual or circling approach procedure published for RWY 23.

**6. PROCEDURE FOR ARRIVALS:**

**6.1. GENERAL:**

a. In case radio communication failure takes place after establishing final approach track, aircraft may continue the approach and land if visual, or go around and carry out the missed approach procedure and join the VOR (117.3) DRG/NDB (265) DBR holding procedure climbing to and maintaining 3000ft.

**6.2 ARRIVING AIRCRAFT**

a. Except when descent clearance has already been received from ATC and acknowledged, pilot shall continue on ATS route W51 maintaining filed flight plan level and not commence descent before RUPAK.
b. After crossing RUPAK, pilot shall descend to Descend to FL110 or level cleared by Jorhat ATC to reach FL110 or level cleared by Jorhat ATC by VOR (117.3) DRG to join the hold over VOR (117.3) DRG.
c. Commence descent to 3000 feet in hold VOR (117.3) DRG at, or as close as possible to, the expected approach time (EAT) last received and acknowledged; or, if no expected approach time (EAT) has been received and acknowledged, at, or as close as possible to, the estimated time of arrival ETA) resulting from the current flight plan;
d. Leave VOR (117.3) DRG and carry out published ILS/VOR RWY 05 Procedure i.e. assigned runway.
e. Land, if possible, within 30 minutes after the estimated time of arrival (ETA) or the last acknowledged expected approach time (EAT), whichever is later.

**7. PROCEDURE FOR DEPARTURES:**

**7.1. DEPARTURE INTENDING TO CONTINUE TO DESTINATION**

A departing aircraft experiencing radio communication failure and intending to continue to its filed flight plan destination shall:

a. Maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 7 minutes following:

- the time the last assigned level or minimum flight altitude is reached; or
- the time the transponder is set to Code 7600; or
- the aircraft's failure to report its position over a compulsory reporting point;

Whichever is later, and thereafter adjust level and speed in accordance with the filed flight plan;
b. When being radar vectored without a specified limit, re-join the current flight plan route W51 no later than the next significant point, taking into consideration the applicable minimum flight altitude;
c. Continue ATS route W51, climbing to/maintaining cleared and acknowledged flight level or minimum flight altitude, whichever is higher until RUPAK.
d. After RUPAK, continue to ATS route W51 and climbing to flight plan level and continue as per the filed flight plan to destination.

**7.2 DEPARTURE INTENDING TO LAND BACK AT DIBRUGARH:**

A departing aircraft, experiencing radio communication failure and intending to land back at Dibrugarh Airport, shall:
a. Maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 7 minutes following:
- the time the last assigned level or minimum flight altitude is reached; or
- the time the transponder is set to Code 7600; or
- the aircraft's failure to report its position over a compulsory reporting point; whichever is later;

b. Thereafter turn towards VOR (117.3) DRG climbing to FL110 to join the hold. If required jettison fuel in VOR (117.3) DRG hold after taking all precautions.
c. Commence descent in the hold to 3000 feet. Leave VOR (117.3) DRG and carry out published ILS/VOR RWY 05 Procedure i.e. assigned runway.

## VEMN AD 2.23 ADDITIONAL INFORMATION

1.Location of ILS monitor Antenna frangible type Hgt. 1.4M at a distance of 60M away from THR RWY 23 and ILS LOC antenna of HGT. 2.8M at a distance 125M away from THR RWY23.OBS marked by day and night.

2.Out of 3 NDB mast light only one is glowing and rest are unserviceable. Height / Location 83FT 153 DEG and Dist. 0.8NM from RWY 05.

3.New air obstruction mast erected at Lepatketta (Dibrugarh) coordinates 2722N 09453E height 120 M distance approx 25 Km south-west of Dibrugarh airport. Mast printed white and orange. Obstruction light provided.

4.GP Mast HGT 50FT Provided with Obstruction Light

5. ADS-B Ground Equipment Commissioned and Operational.

6. PCN of LINK TAXIWAY: 63/R/C/W/T

7. PCN of OLD APRON: 52/R/C/W/T

8. Bird activity observed over and in the vicinity of airfield.Pilots to exercise caution while landing and takoff.

## VEMN AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart(16 APRIL 2026)
2. Aerodrome Parking & Docking Chart
3. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 05(16 APRIL 2026)
4. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 23(16 APRIL 2026)
5. Aerodrome Obstacle Chart Type B(16 APRIL 2026)
6. VOR Procedure RWY05(9 JULY 2026)

## VEMN AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

| Procedure | Procedure Minima | VSS Penetration |
|---|---|---|
| 1 | 2 | 3 |
| | | |