AD 2. AERODROMES

VAGD AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VAGD - GONDIA AIRPORT, GONDIA

VAGD AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	213125N 0801716E MAG. BRG. 50.09 DEG/488M from physical extremity of RWY04	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	16 KM North East Gondia Railway Station.	
3	Aerodrome elevation and reference temperature	994 FT / 46.0 DEG C	
4	Magnetic variation, date of information and annual change	0.50 DEG W (2010) /0.0166 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority Of India, Airport Director, Birsi Airport, Gondia - 441601,	
		Telephone:	(91) 07182 283187
		Fax:	(91) 07182283187
		AFS:	VAGDYFYX
		Email:	apcgondia@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	1. Vertical Datum: EGM 08	

VAGD AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	0930-1730 IST (MON TO FRIDAY) SAT, SUN, HOL - NIL
2	Custom and immigration	NIL
3	Health and sanitation	Provide by health department (State Govt.)
4	AIS briefing office	As per ATS
5	ATS reporting office (ARO)	As per ATS
6	MET Briefing office	As per ATS
7	Air Traffic Service	Refer NOTAM
8	Fuelling	Provided by IOCL
9	Handling	Not Available
10	Security	24 Hrs with state police.
11	De-icing	Not applicable

12	Remarks	1. ATC services not available. Access to airport available as uncontrolled airfield with prior approval of Airport Director, Gondia. 2. 24 HR prior notice for NON SKED OPS.
		1. The approved hourly RWY traffic handling capacity: (a) Maximum number of arrival and departures: 12 (The minimum spacing between two successive arrivals shall be more than five minutes) (b) Maximum number of arrivals: 06 (c) Maximum number of departures: 10

VAGD AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Not applicable
2	Fuel and Oil types	100LL AVGAS and ATF on request
3	Fuelling facilities and capacity	ATF shall be arranged by M/s Indian Oil through mobile van with adequate capacity during schedule commercial flight operation.
4	De-icing facilities	Not applicable
5	Hangar space for visiting aircraft	Not available
6	Repair facilities for visiting aircraft	Not available
7	Remarks	NIL

VAGD AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in city (within 10 km)
2	Restaurant(s) at or in the vicinity of aerodrome	Available in city (within 10 km)
3	Transportation possibilities	Private Taxi, State Transport
4	Medical Facilities	Primary Health Centre at Kamtha village, 02 Km away and Multi-speciality Hospital available in Gondia city 16 Km from Airport.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available in city (within 3 km) Post office: Available in city (within 3 km)
6	Tourist office	NIL
7	Remarks	NIL

VAGD AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-5
2	Rescue equipment	Available as per category.
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is ATR-72/600. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director Office: 0718-283187; Mobile: 7030230114 Email: apcgondia@aai.aero
4	Remarks	1. Rescue and fire fighting services category will be upgraded to CAT VI on 72 HR prior notice for operation of A320 type aircraft.

VAGD AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VAGD AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	At aircraft stands
4	Location of VOR checkpoints	TWY P3 (213127.24N 0801720.91E) TWY P2 (213124.90N 0801718.49E))
5	Position of INS checkpoints	NIL
6	Remarks	1. Coordinates of Runway Holding Positions: i. TWY P1: 213113.62095N 0801706.00198E, Elev 991 ft ii. TWY P2: 213125.29284N 0801718.06209E, Elev 994 ft iii. TWY P3: 213127.59111N 0801720.52292E, Elev 994 ft iv. TWY P4: 213138.12682N 0801731.36853E, Elev 995 ft v. TWY P5: 213152.34180N 0801746.09447E, Elev 986 ft vi. TWY P6: 213213.54250N 0801808.14957E, Elev 977 ft 2. Coordinates of RWY and TWY Intersection: i. TWY P1: 213115.62456N 0801703.76424E, Elev 992 ft ii. TWY P2: 213127.29702N 0801715.84589E, Elev 993 ft iii. TWY P3: 213129.63571N 0801718.25835E, Elev 993 ft iv. TWY P4: 213140.14150N 0801729.13813E, Elev 995 ft v. TWY P5: 213154.36073N 0801743.86183E, Elev 989 ft vi. TWY P6: 213215.60593N 0801805.86872E, Elev 979 ft 3. Geoid Model: EGM08

VAGD AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft stand ID markings available. Taxiing guidance provided on R/T Guidelines at Apron.
2	Runway and taxiway markings and lights	RWY RWY Markings: RCL,THR, RWY Designation, RWY Edge, Aiming Point, TDZ, RWY, TURNPAD RWY Lights: THR, RWY Edge ,RWY END TWY TWY Marking: Centreline, Side strip, TWY Holding position TWY Lights: Taxiway Edge Light
3	Stop bars (if any)	NIL
4	Remarks	NIL

VAGD AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
22/TKOF 04/APCH	TREE	213102.0N 0801658.3E	1027 FT	NIL	Group of Trees
22/TKOF 04/APCH	POLE	213104.8N 0801658.6E	1010 FT	NIL	Electric Pole
22/TKOF 04/APCH	TREE	213103.6N 0801658.1E	1032 FT	NIL	Group of Trees
22/TKOF 04/APCH	POLE	213106.1N 0801659.2E	1010 FT	NIL	Electric Pole
22/TKOF 04/APCH	TREE	213106.2N 0801659.6E	1039 FT	NIL	Group of Trees
22/TKOF 04/APCH	POLE	213107.0N 0801701.0E	1008 FT	NIL	Electric Pole
22/TKOF 04/APCH	TREE	213107.1N 0801702.0E	1037 FT	NIL	Group of Trees
22/TKOF 04/APCH	OTHER	213107.3N 0801700.1E	1004 FT	NIL	Mobile Road Traffic (Road Elev. 300.9m+ 5m Mobile Traffic)
22/TKOF 04/APCH	POLE	213108.3N 0801702.4E	1004 FT	NIL	Light Post
22/TKOF 04/APCH	BUILDING	213108.3N 0801702.9E	1003 FT	NIL	Anganwadi
22/TKOF 04/APCH	BUILDING	213108.8N 0801703.5E	1003 FT	NIL	Urmila Bai House
22/TKOF 04/APCH	BUILDING	213108.9N 0801703.5E	1001 FT	NIL	Ganpat House
22/TKOF 04/APCH	OTHER	213109.3N 0801703.8E	1007 FT	NIL	Mobile Road Traffic (Road Elev.301.9m + 5m Mobile Traffic)
22/TKOF 04/APCH	BUILDING	213109.6N 0801703.4E	997 FT	NIL	Shop
22/TKOF 04/APCH	TREE	213110.0N 0801703.9E	998 FT	NIL	Airport Fencing Top
22/APCH 04/TKOF	OTHER	213254.0N 0801905.5E	1117 FT	NIL	Cell Phone Mas
22/APCH 04/TKOF	TREE	213236.2N 0801817.0E	1023 FT	NIL	Group of Trees
22/APCH 04/TKOF	TREE	213228.0N 0801810.8E	1004 FT	NIL	Group of Trees
22/APCH 04/TKOF	TREE	213229.3N 0801813.9E	1009 FT	NIL	Group of Trees
22/APCH	TREE	213226.1N 0801823.2E	1020 FT	NIL	Group of Trees
22/APCH 04/TKOF	TREE	213220.0N 0801818.7E	1013 FT	NIL	Group of Trees
22/APCH 04/TKOF	TREE	213220.5N 0801816.8E	1006 FT	NIL	Group of Trees
In circling area and at AD	TREE	213104.0N 0801700.7E	1024 FT	NIL	Group of Trees

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	TREE	213100.8N 0801658.7E	1025 FT	NIL	Group of Trees
In circling area and at AD	BUILDING	213107.3N 0801702.8E	1007 FT	NIL	Hut Type Building
In circling area and at AD	BUILDING	213108.2N 0801703.9E	1006 FT	NIL	House
In circling area and at AD	BUILDING	213108.7N 0801704.3E	1005 FT	NIL	House
In circling area and at AD	BUILDING	213109.1N 0801704.9E	1021 FT	NIL	White Building
In circling area and at AD	BUILDING	213109.1N 0801704.2E	1003 FT	NIL	House
In circling area and at AD	OTHER	213109.2N 0801704.5E	1005 FT	NIL	Rod on House Top
In circling area and at AD	TREE	213109.3N 0801705.1E	1021 FT	NIL	Group of Trees
In circling area and at AD	OTHER	213109.4N 0801704.7E	1006 FT	NIL	Rod on Building Top (Building=306.0m)
In circling area and at AD	TREE	213109.4N 0801705.1E	1018 FT	NIL	Ashok Tree
In circling area and at AD	TANK	213109.7N 0801705.8E	1010 FT	NIL	Solar Water Tank (Water Tank=307.5m) Structure
In circling area and at AD	TREE	213109.8N 0801706.7E	1027 FT	NIL	Neem Tree
In circling area and at AD	TREE	213109.9N 0801706.9E	1027 FT	NIL	Group of Trees
In circling area and at AD	FENCE	213110.0N 0801705.3E	998 FT	NIL	Airport Shed with Fencing on Top
In circling area and at AD	TREE	213110.4N 0801706.2E	1031 FT	NIL	Tree
In circling area and at AD	OTHER	213200.9N 0801754.2E	1002 FT	NIL	Mobile Road Traffic (Road Elev.300.5m+ 5m Mobile Traffic)
In circling area and at AD	POLE	213144.1N 0801738.9E	1016 FT	LGTD	Windsock
In circling area and at AD	BUILDING	213200.1N 0801753.4E	996 FT	NIL	LLZ. Hut
In circling area and at AD	BUILDING	213202.5N 0801752.3E	993 FT	NIL	Airport Fencing Top
In circling area and at AD	OTHER	213202.7N 0801752.6E	1002 FT	NIL	Mobile Road Traffic (Road Elev.300.4m+ 5m Mobile Traffic)
In circling area and at AD	FENCE	213203.3N 0801751.5E	992 FT	NIL	Airport Fencing Top
In circling area and at AD	FENCE	213203.2N 0801749.1E	996 FT	NIL	Airport Fencing Top

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	213144.5N 0801735.4E	994 FT	LGTD	PAPI
In circling area and at AD	OTHER	213155.5N 0801736.3E	1011 FT	NIL	Lightning Arrester
In circling area and at AD	TREE	213203.7N 0801805.6E	1033 FT	NIL	Group of Trees
In circling area and at AD	TREE	213149.5N 0801727.8E	1038 FT	NIL	Mango Tree
In circling area and at AD	TREE	213151.9N 0801731.1E	1036 FT	NIL	Mango Tree
In circling area and at AD	OTHER	213205.0N 0801746.7E	1002 FT	NIL	Mobile Road Traffic (Road Elev.300.5m +5m Mobile Traffic)
In circling area and at AD	OTHER	213118.7N 0801710.3E	995 FT	NIL	Cable Box
In circling area and at AD	FENCE	213202.7N 0801752.2E	993 FT	NIL	Airport Boundary Wall with Fencing on Top
In circling area and at AD	POLE	213114.8N 0801708.7E	1012 FT	LGTD	Windsock
In circling area and at AD	BUILDING	213116.0N 0801658.4E	1001 FT	NIL	Glide Path Hut
In circling area and at AD	POLE	213121.4N 0801701.6E	1009 FT	NIL	Electric Pole
In circling area and at AD	TREE	213121.6N 0801659.2E	1035 FT	NIL	Group of Trees
In circling area and at AD	TREE	213122.3N 0801701.0E	1028 FT	NIL	Group of Trees
In circling area and at AD	TREE	213137.1N 0801716.0E	1035 FT	NIL	Group of Trees
In circling area and at AD	TREE	213149.5N 0801727.8E	1038 FT	NIL	Group of Trees
In circling area and at AD	OTHER	213115.7N 0801721.6E	1107 FT	LGTD	Lightning Arrester on ATC Tower
In circling area and at AD	FENCE	213120.7N 0801702.0E	996 FT	NIL	Airport Fencing Top
In circling area and at AD	TREE	213122.2N 0801702.8E	1018 FT	NIL	Group of Trees
In circling area and at AD	TREE	213122.3N 0801701.7E	1020 FT	NIL	Group of Trees
In circling area and at AD	TREE	213123.1N 0801701.3E	1032 FT	NIL	Group of Trees
In circling area and at AD	TREE	213125.5N 0801704.7E	1045 FT	NIL	Group of Trees
In circling area and at AD	TREE	213127.4N 0801706.2E	1030 FT	NIL	Group of Trees
In circling area and at AD	TREE	213122.0N 0801702.3E	1020 FT	NIL	Bamboo Tree
In circling area and at AD	TREE	213122.6N 0801701.3E	1031 FT	NIL	Group of Trees
In circling area and at AD	OTHER	213105.5N 0801701.3E	1008 FT	NIL	Pipe on Building Top

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM 08)	Marking/LGT	Remarks
In circling area and at AD	TREE	213104.4N 0801702.8E	1033 FT	NIL	Coconut Tree
In circling area and at AD	POLE	213105.0N 0801701.2E	1012 FT	NIL	Electric Pole
In circling area and at AD	OTHER	213121.8N 0801527.6E	1166 FT	LGTD	Cell Phone Mast
In circling area and at AD	OTHER	213114.5N 0801830.1E	1183 FT	LGTD	Cell Phone Mast
In circling area and at AD	OTHER	213055.5N 0801826.4E	1171 FT	LGTD	Cell Phone Mast
In circling area and at AD	NATURAL HIGHPOINT	213834.8N 0802525.8E	1649 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213939.2N 0802334.7E	1716 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	214004.6N 0802334.0E	1865 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213929.4N 0802446.7E	1772 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213900.5N 0802430.6E	1903 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213951.4N 0802823.2E	2165 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213854.8N 0802816.4E	1575 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213737.5N 0802811.8E	1903 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213716.0N 0802925.0E	1837 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213645.4N 0802827.1E	1968 FT	NIL	Hill Top
In circling area and at AD	NATURAL HIGHPOINT	213625.4N 0802903.4E	1772 FT	NIL	Hill Top

VAGD AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Meteorology office Gondia
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As per ATS Operations Hours
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Aerodrome Metrological Office Nagpur Airport Interval 3 Hours
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend Available AMO, Nagpur, when required
5	Information on how briefing and/or consultation is provided	Available at AMS, Gondia
6	Types of flight documentation supplied and language(s) used in flight documentation	METAR, SPECI Language: English
7	Charts and other information displayed or available for briefing or consultation	Available at AMS, Gondia on Request

8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Available at AMS, Gondia on Request
9	The air traffic services unit(s) provided with meteorological information	Gondia Tower
10	Additional information, e.g. concerning any limitation of service.	NIL

VAGD AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
04	44.07 DEG	2624 x 45 M	72/F/A/W/T Asphalt	THR: 213118.91N 0801707.18E RWY END: 213215.88N 0801806.15E
22	224.07 DEG	2624 x 45 M	72/F/A/W/T Asphalt	THR: 213215.88N 0801806.15E RWY END: 213114.58N 0801702.70E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 992.0FT TDZ: 994.0FT		NIL	NIL	2744 x 280 M
THR: 979.0FT TDZ: 988.0FT		NIL	NIL	2744 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
90M x 90M		NIL	1. PCN RWY 04 (0-1529M): 72/F/A/W/T (1529-2624M): 65/R/C/W/T 2. Vertical Datum: EGM 08
90M x 90M		NIL	1. Vertical Datum: EGM 08

VAGD AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
04	2624	2624	2624	2439	THR displacement: 185 M
22	2624	2624	2624	2624	

VAGD AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
04		Green	PAPI LEFT/3.00 DEG MEHT (17.15M)	
22	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (16.18M)	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2624 M 60 M White LIH	Red		NIL
	2624 M 60 M White LIH	Red		NIL

VAGD AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building FLG W & G EV 2SEC. As ATS HR.
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	300M from ARP, Lighted
		Anemometer	On Tower building, Non-Lighted
3	Taxiway edge and taxiway centre line lights;	Edge	ALL TWY
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary Power supply to all lighting at AD. Switch-over time< 15 SEC.	
5	Remarks	NIL	

VAGD AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VAGD AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 213125N 0801716E within a 12NM radius.
2	Vertical limits	FL 75
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Gondia Tower, English
5	Transition altitude	5000 FT
6	Hours of applicability	HO
7	Remarks	Gondia Approach Control Unit is combined with Gondia Aerodrome Control Tower.

VAGD AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Gondia Tower	118.350 MHZ	
APP	Gondia Tower	118.700 MHZ	
TWR	Gondia Tower	118.350 MHZ	
TWR	Gondia Tower	118.700 MHZ	
ALRS	--	121.500 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	1.Main FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1.Backup FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	AS ATS	NIL
	Standby Frequency	Standby Frequency
		Emergency Frequency

VAGD AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 04 CAT I	IGON	108.300 MHz	AS ATS
GP 04		334.100 MHz	AS ATS
DME ILS 04	IGON	CH20X	
DVOR/DME	GDA	114.200 MHz CH89X	As ATS
NDB	GN	230 kHz	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
213222.9N 0801813.4E			
213129.8N 0801712.6E			GP ANGLE 3 DEG.
213129.9N 0801712.5E	1006 FT		Elevation in EGM-08
213139.5N 0801742.8E	1023 FT		1. Vertical Datum: EGM 08
213114.5N 0801719.7E			

VAGD AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VAGD AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VAGD AD 2.22 FLIGHT PROCEDURES

RADIO COMMUNICATION FAILURE PROCEDURES

1. INTRODUCTION:

1.1 Radio communication failure procedures are prescribed in ICAO PANS-ATM Doc 4444. Based on these provisions, following radio communication failure procedures are established to standardize the actions taken by the pilot of arriving and departing aircraft experiencing radio communication failure at Gondia Airport, Gondia.

The purpose of this document is to establish the standard procedure to handle the event of a radio communication failure situation at Gondia Airport to ensure safe and efficient aircraft operation.

2. GENERAL

2.1 All Transponder equipped aircraft experiencing Radio Communication Failure shall set transponder to Mode A/C code 7600 as soon as practicable.

(Note: This requirement of setting transponder to Mode A/C code 7600 in no way imposes any restriction on the pilot's decision to set transponder to Mode A/C code 7500 or 7700, whenever required).

2.2 Immediately after the detection of RCF, the aircraft shall attempt to establish communications with the appropriate air traffic control unit using all other available means. In addition, the aircraft shall keep watch for any instructions that may be issued by visual signals.

2.3 The pilot shall make blind transmission to ATC of all necessary reports and actions taken by the aircraft, e.g. descent, turn, joining hold, leaving for approach, FAF etc., irrespective of whether partial/complete RCF has been experienced or not.

2.4 Aircraft experiencing radio communication failure shall be provided all required information necessary for the safe and efficient conduct of flight and landing clearance without expecting acknowledgment.

3. ASSIGNED RUNWAY AND ITS AVAILABILITY FOR RCF AIRCRAFT

3.1 In case of an arriving aircraft experiencing RCF, when the Runway for landing has already been advised to and acknowledged by the aircraft by GONDIA ATC via VHF, such runway shall be considered as the assigned runway. If an arriving aircraft has not been advised and acknowledged any runway, Runway 04 shall be considered as an assigned runway for such arrival.

3.2 In case of departures from Gondia airport is returning due to RCF, Runway 04 shall be considered as the assigned runway for landing, irrespective of the runway used for departure.

3.3 Runway lights and Approach lights shall be in the 'SWITCHED ON' position to indicate the availability of such Runway for aircraft experiencing RCF irrespective of visibility and Day or Night. Runway and Approach lights in the 'SWITCHED OFF' position shall Indicate the non-availability of such Runway for aircraft experiencing RCF.

3.4 In case strong tailwind conditions are encountered during approach for the Runway as mentioned in para 3.1 and 3.2, the aircraft experiencing RCF will carry out a missed approach on the runway as mentioned in para 3.1 and 3.2 and after following the complete missed approach procedure as Published for such approach, aircraft will carry out the published approach procedure for the opposite runway.

4. PROCEDURE FOR ARRIVALS

4.1 Arriving Aircraft – In VMC

4.1.1 continue to fly in Visual Meteorological Conditions;

4.1.2 land at the nearest suitable aerodrome;

4.1.3 report its arrival by the most expeditious means to the appropriate air traffic control unit.

4.2 Arriving Aircraft- in IMC

4.2.1 In case Radio Communication Failure takes place after establishing final approach track, aircraft may continue the approach and land if visual or go around and carry out the missed approach procedure and join the VOR (114.2) GDA holding procedure climbing to and maintaining 3900ft.

4.2.2 Except when descent clearance has already been received from ATC GONDIA and acknowledged, the pilot shall continue on the ATS route maintaining filed flight plan level or level cleared and acknowledged by adjacent area control unit i.e. VANP ACC/VECC ACC.

4.2.3 In airspace where procedural separation is being applied, maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 20 minutes following the aircraft's failure to report its position over a compulsory reporting point and thereafter adjust level and speed in accordance with the filed flight plan.

4.2.4 After 20 minutes, commence descent to MHA in published hold over VOR (114.2) GDA at, or as close as possible to, the expected approach time (EAT) last received and acknowledged; or, if no expected approach time (EAT) has been received and acknowledged, at, or as close as possible to, the estimated time of arrival (ETA) over GDA VOR.

4.2.5 Leave "GDA" and carry out the published ILS/VOR Procedure for the runway as mentioned in para 3.1.

4.2.6 Land, if possible, within 30 minutes after the estimated time of arrival (ETA) or the last acknowledged expected approach time (EAT), whichever is later.

5. PROCEDURE FOR DEPARTURES

5.1 DEPARTURE INTENDING TO CONTINUE TO DESTINATION

A departing aircraft experiencing radio communication failure and intending to continue to its filed flight plan destination shall:

a) Maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 20 minutes following the aircraft's failure to report its position over a compulsory reporting point and thereafter adjust level and speed in accordance with the filed flight plan.

b) when being cleared on radial by ATC without a specified limit, proceed in the most direct manner possible to re-join the current flight plan route no later than the next significant point, taking into consideration the applicable minimum flight altitude.

5.2 DEPARTURE INTENDING TO LAND BACK AT GONDIA

A departing aircraft, experiencing radio communication failure and intending to land back at Gondia Airport shall:
a) maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 20 minutes following the aircraft's failure to report its position over a compulsory reporting point.
b) thereafter turn towards VOR (114.2) GDA to join the hold.
c) Commence descent in the hold to 3900ft. Leave VOR (114.2) GDA and carry out published ILS/VOR RWY04 Procedure, i.e. assigned runway as mentioned in Para 3.
d) If required to jettison fuel, then Proceed towards 20-25 miles from GDA between 110-125 radial minimum flight level FL 065. After fuel jettisoning, proceed towards GDA (114.2) VOR for holding as published and thereafter descend to 3900 ft. Taking all precautions and holding altitude as per published chart to follow provisions mentioned in ICAO Doc 4444.
e) After landing, aircraft shall lookout for follow me jeep on taxiway holding point and after sighting the Follow Me jeep, aircraft shall follow the Follow Me jeep for parking to the allotted bay. Upon sighting the Marshaller, aircraft shall stop following "Follow Me jeep" and shall follow Marshaller for parking.

5.3 PROCEDURES FOR VFR TRAFFIC:

5.3.1 In case of a VFR flight experiencing RCF and does not intend to land at Gondia: It shall continue to fly in VMC, land at the nearest suitable aerodrome/ helipad, and report its arrival by the most expeditious means to the ATC, Gondia.
5.3.2 In case of a VFR flight experiencing RCF and intending to land at Gondia:
a) Proceed according to the current flight plan route in VMC and maintain the altitude/level last assigned and acknowledged.
b) Proceed towards 20-25 miles from GDA (114.2) VOR between 110-125 Radial minimum flight level FL 065 for fuel jettisoning.
c) Maintaining FL 065 proceed and join GDA VOR (114.2). Reaching GDA VOR descend to circuit altitude to establish left hand traffic circuit for runway 22 or righthand circuit for Runway 04 (if assigned and acknowledged).
d) Carry out a complete aerodrome traffic circuit and land on the last acknowledged Runway or the Runway as per para 3.1.

VAGD AD 2.23 ADDITIONAL INFORMATION

NIL

VAGD AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (07 August 2025)
2. Aircraft Parking/Docking Chart (07 August 2025)
3. Aerodrome Obstacle Chart (Operating Limitations), Type A RWY 04 (07 August 2025)
4. Aerodrome Obstacle Chart (Operating Limitations), Type A RWY 22 (07 August 2025)
5. Aerodrome Obstacle Chart (Operating Limitations), Type B (07 August 2025)
6. VOR Procedure RWY 04 (27 NOV 2025)
7. VOR Procedure RWY 22 (27 NOV 2025)
8. NDB Circling Procedure
9. ILS LOC Procedure RWY 04(27 NOV 2025)

VAGD AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3