AD 2. AERODROMES

VEGK AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VEGK - GORAKHPUR AIRPORT, GORAKHPUR [INDIAN AIR FORCE]

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VEGK AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	264429N 0832701E 50 FT East of the middle marker at a distance of 232 FT from northern edge of the runway	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	06 KM East of Gorakhpur City	
3	Aerodrome elevation and reference temperature	260 FT / 37.8 DEG C	
4	Magnetic variation, date of information and annual change	0.38 DEG E (2020) /0.01 DEG W	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station, Gorakhpur (UP) Pin-273002,	
		Telephone:	(91) 055 12745035
		Fax:	(91) 055 12745035
		AFS:	
		Email:	ats.17@nic.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Joint User Airfield (Defence & Civil Ops)	

VEGK AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON - FRI: 0200-0900 UTC SAT, SUN & HOL : NIL
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As per NOTAM
5	ATS reporting office (ARO)	HJ
6	MET Briefing office	HJ
7	Air Traffic Service	HJ
8	Fuelling	Mon-Fri : 0130 to 1630 UTC Sat, Sun & Holidays : As per civil flights
9	Handling	0700 to 1900 Hrs
10	Security	0700 to 1900 Hrs
11	De-icing	NIL
12	Remarks	Operational hours can be extended till 2100 IST for civil scheduled operations.

VEGK AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1

3	Fuelling facilities and capacity	Refueller Capacity: 16000 X 3 , 6000 X 1 Discharge Rate (L/Sec): 12 L/Sec Agency: IOC
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VEGK AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In Gorakhpur City Approx 06 Km
2	Restaurant(s) at or in the vicinity of aerodrome	In Gorakhpur City Approx 06 Km
3	Transportation possibilities	Taxis at civil terminal
4	Medical Facilities	Hospital in Gorakhpur city
5	Bank and post office at or in the vicinity of aerodrome	Banks: State bank of India ATM counters Post office: Available in the City
6	Tourist office	Not Available
7	Remarks	NIL

VEGK AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per AD Category
3	Capability for removal of disabled aircraft	A coordinated plan for removal of disabled aircraft exists. Disabled aircraft removal to be ensured by the operator in coordination with local authorities.
4	Remarks	NIL

VEGK AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VEGK AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Civil Apron Surface : Rigid Elevation : 255 FT Strength Stand No. Strength 1 PCN 57/R/C/X/T 2 PCN 57/R/C/X/T 3 PCN 57/R/C/X/T
2	Designation, width, surface and strength of taxiways	Designation Width Surface Strength PTT 75 FT Rigid PCN 71/R/C/XT Link B 50 FT Flexible PCN 73/F/C/X/T Link C 75 FT Rigid PCN 57/R/C/X/T Link D 75 FT Rigid PCN 57/R/C/X/T
3	Location and elevation of altimeter checkpoints	NIL
4	Location of VOR checkpoints	

5	Position of INS checkpoints	
6	Remarks	NIL

VEGK AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Ground markings for stand identification available and also taxi guidance provided on R/T
2	Runway and taxiway markings and lights	RWY Marking : RWY Designation, THR, Aiming point, TDZ, Centre Line, RWY Edge & RWY End RWY Lights : Standard CAT II Lights available for RWY 29 and simple approach lights available for RWY 11. TWY Marking : Centre line indicated by White broken lines, CAT II holding position marking, 04 Helipads marked on Parallel Taxiway TWY Lights: Taxiway Edge lights installed.
3	Stop bars (if any)	Available
4	Remarks	NIL

VEGK AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
29/APCH 11/TKOF	TREE	264452.0N 0832546.0E	348 FT	NIL	TREES
29/APCH 11/TKOF	TANK	264450.0N 0832522.0E	331 FT	LGTD	OVER HEAD TANK
29/TKOF 11/APCH	TREE	264351.0N 0832827.0E	328 FT	NIL	TREES
In circling area and at AD	ANTENNA	264439.0N 0832650.0E	335 FT	LGTD	ATC Tower
In circling area and at AD	ANTENNA	264433.0N 0832725.0E	352 FT	LGTD	SIGNAL TOWER
In circling area and at AD	ANTENNA	264444.0N 0832642.0E	354 FT	LGTD	SIGNAL TOWER
In circling area and at AD	TANK	264431.0N 0832626.0E	321 FT	LGTD	WATER TANK
In circling area and at AD	TREE	264414.0N 0832723.0E	380 FT	NIL	TREES
In circling area and at AD	TANK	264504.0N 0832638.0E	328 FT	LGTD	WATER TANK
In circling area and at AD	TANK	264459.0N 0832640.0E	335 FT	LGTD	WATER TANK
In circling area and at AD	ANTENNA	264417.0N 0832511.0E	410 FT	LGTD	MICROWAVE TOWER
In circling area and at AD	ANTENNA	263730.0N 0831741.0E	397 FT	LGTD	MICROWAVE TOWER

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	ANTENNA	265339.0N 0832909.0E	764 FT	LGTD	TV TOWER
In circling area and at AD	ANTENNA	265230.0N 0832753.0E	630 FT	LGTD	RADIO TOWER
In circling area and at AD	ANTENNA	264955.0N 0833919.0E	383 FT	LGTD	MICROWAVE TOWER
In circling area and at AD	OTHER	264108.0N 0832237.0E	558 FT	NIL	CHIMNEYS
In circling area and at AD	ANTENNA	264110.0N 0833919.0E	387 FT	LGTD	MICROWAVE TOWER
In circling area and at AD	ANTENNA	263841.0N 0833506.0E	479 FT	LGTD	MICROWAVE TOWER
In circling area and at AD	ANTENNA	264002.0N 0833519.0E	387 FT	LGTD	MICROWAVE TOWER
In circling area and at AD	ANTENNA	264110.0N 0832950.0E	407 FT	LGTD	MICROWAVE TOWER
In circling area and at AD	ANTENNA	264453.0N 0832201.0E	581 FT	LGTD	TOWER
In circling area and at AD	ANTENNA	264917.0N 0832133.0E	527 FT	NIL	Prilling tower of fertilizer Chimney

VEGK AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Met Office Air Force Station Gorakhpur
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 Hrs Observational and 18 Hrs Forecasting Watch
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Office, Air Force Station Gorakhpur 12 Hrs
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend At interval of 30 Min
5	Information on how briefing and/or consultation is provided	Verbal and telephonic briefing provided
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular form English
7	Charts and other information displayed or available for briefing or consultation	Surface Chart, Upper Air Chart, Satellite imagery and NWP products
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Automatic Weather Station(AWS), Laser Ceilometer, LDS, DDRWE, MWR and Civil Internet.
9	The air traffic services unit(s) provided with meteorological information	ATC Gorakhpur
10	Additional information, e.g. concerning any limitation of service.	NIL

VEGK AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
11	113.00 DEG	2777 x 45 M	91/F/C/X/T	THR: 264444.00N 0832614.00E RWY END: 264409.00N 0832746.00E
29	293.00 DEG	2777 x 45 M	91/F/C/X/T	THR: 264409.00N 0832746.00E RWY END: 264444.00N 0832614.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 259.0FT TDZ:		296 x 45 M	296 x 45	3496 x 300 M
THR: 260.0FT TDZ:		303 x 45 M	303 x 45	3496 x 300 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
	Arresting system not available for Civil flights		1. Arrester barrier structure exists on the edges of overrun, 150 FT from the stop end of RWY. 2. RHAG pendant cable (aircraft arresting gear) may be installed 1171 FT short of stop end of RWY during military operations. 3. PCN for first 314M and last 319M of RWY 11 is 71/R/C/X/T with rigid surface.
	Arresting system not available for Civil flights		1. Arrester barrier structure exists on the edges of overrun, 150 FT from the stop end of RWY. 2. RHAG pendant cable (aircraft arresting gear) may be installed 1171 FT short of stop end of RWY during military operations. 3. PCN for first 319M and last 314M of RWY 29 is 71/R/C/X/T with rigid surface.

VEGK AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
11	2777	3073	3073	2777	
29	2777	3080	3080	2777	

VEGK AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
11	SALS 300 M LIH	Green	PAPI LEFT/3.00 DEG	
29	CAT II 900 M LIH	Green	PAPI RIGHT/3.00 DEG	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2777 M 15 M LIH White	2777 M 60 M White LIH	Red Red	Red 60 M	1. RWY centreline from THR to 1877 M - white, from 1877 M to 2477M - ALTN red and white from 2477 M to end light-red. 2. RWY Edge Lights light THR to 2177 M- white and from 2177 M to end-yellow
2777 M 15 M LIH White	2777 M 60 M White LIH	Red Red	Red 60 M	1. RWY centreline from THR to 1877 M- white, from 1877 M to 2477M- ALTN red and white from 2477 M to end lightred. 2. RWY Edge Lights light THR to 2177 M- white and from 2177 M to end-yellow

VEGK AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On top of aerodrome control tower, FPM: 24, During Night and low visibility conditions.
		IBN	

2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Landing 'T' is placed between TWY C and D. A landing 'T' for night operations is placed between TWY B and C.
		Anemometer	Near both THR of RWY
3	Taxiway edge and taxiway centre line lights;	Edge	All Taxiways
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary Power supply available, Switch over time: 1 Sec: RWY edge lights. 8-15 Sec: for inner 300 m of approach lighting system, RWY threshold, RWY end, RWY centreline, RWY touchdown zone, All stop bars other parts of approach lighting system and TWY edge lights.	
5	Remarks	NIL	

VEGK AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	NIL

VEGK AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: GORAKHPUR MCTR - 1 Circular area centered on 264429N 0832701E within a 25NM radius. FL150/GND GORAKHPUR MCTR – 2 Circular area centered on 264622N0835343 within a 15NM radius. FL150/GND
2	Vertical limits	FL 150
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Gorakhpur Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	HJ
7	Remarks	1. Controlling Unit: IAF Gorakhpur TEL: +91-551-2745035 FAX: +91-5512745035 Email:ats.17@nic.in 2. Beyond Operational Hours of Gorakhpur ATC MCTR - 2 will be controlled as CTR by Kushinagar ATC. 3. ATC Frequencies: a) Gorakhpur TWR: 128.200 MHz b) Kushinagar TWR: 118.025 MHz 118.675 MHz

VEGK AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Gorakhpur Approach	131.000 MHZ	
TWR	Gorakhpur Tower	128.200 MHZ	
ATIS	Gorakhpur Information	116.200 MHZ	
ALRS	Emergency Frequency	121.500 MHZ	
ALRS	Emergency Frequency	243.000 MHZ	
RADAR	Gorakhpur Radar	131.000 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HJ	NIL
	HJ	NIL
	HJ	NIL
	HJ	VHF
	HJ	UHF
	HJ	NIL

VEGK AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 29 CAT I	IGOR	108.300 MHz	As per NOTAM
GP 29	IGOR	334.100 MHz	As per NOTAM
DME ILS 29	LP	CH20X	As per NOTAM
DVOR/DME	GKP	116.200 MHz CH109X	As per NOTAM
NDB	GH	278 kHz	As per NOTAM

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
264448.0N 0832603.0E			
264410.0N 0832734.0E			
264410.0N 0832734.0E	256 FT		Co-located with GP
264433.0N 0832622.0E	256 FT		Controlling Authority: Indian Air Force
264412.0N 0832646.0E			1. Controlling Authority: Indian Air Force

VEGK AD 2.20 LOCAL AERODROME REGULATIONS

1. Only one B737/A320 class of aircraft along with 01 ATR 72 class of aircraft or 02 ATR 72 class of aircraft can be accommodated on civil dispersal at same time.

VEGK AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VEGK AD 2.22 FLIGHT PROCEDURES

NIL

VEGK AD 2.23 ADDITIONAL INFORMATION

1. Link 'A' not available for taxing of aircraft with wingspan 80 FT or more due to presence of obstacles on shoulders.
2. Increased bird and animal activities observed all along runway. Extensive dense forest located south of runway. Measures have been undertaken to reduce threat of birds and animal hit with aircraft. All operators to exercise caution while arriving and departing from Gorakhpur airfield.
3. Refuelling facility for civil non-scheduled aircraft available subject to prior coordination by the operator with IOC Gorakhpur.
4. All non-scheduled operators intending to operate flight to/from Kushinagar Airfield (24 NM from Gorakhpur) to note that Kushinagar Airfield lies within CTR of Gorakhpur. Positive clearance must be obtained from Telefax: 0551-2745035, Mobile: 9984420506 before commencing such operations.
5. 180 DEG turn on runway to be performed only on concrete portion at both ends of Runway.
6. Tall trees 100 FT to 150 FT height present on the cleared zone from 29 dumbbell to DTGM 3 for RWY 29 at a distance of 230 FT from runway edge on the south side of Runway.
7. All aircraft routing via W45 between Lucknow and Patna G590 Varanasi to Kathmandu to establish positive R/T contact with Gorakhpur Tower 128.2 MHz before entering Gorakhpur Local Flying Area VER 75A and VER 75B.
8. Four helipads marked on Parallel Taxi Track (PTT), Helipad-1, 300m from RWY 11 Threshold, Helipad-2 abeam VIP dispersal, Helipad-3 abeam TWY N and Helipad-4 at 300m short.
9. SRE Available for RWY 11/29:
   i. OCA for SRA for RWY 11/29 at Gorakhpur: 640FT.
   ii. MHA: 1900 FT.
   iii. SRA will be terminated at 1 nm from touchdown.
   iv. Advisory altitude based on three DEG glide path will be passed each NM.
   v. Missed approach procedure for both RWY 11/29: Climb to 3000FT on QNH on last assigned heading and await further instructions from radar controller.
   vi. RCF Procedure: If unable to proceed visually climb 2500FT on track to Gorakhpur and contact TWR on TWR frequency 128.2 MHz
10. Non standard marking on parallel taxi track. 3M long broken white lines with 3M gap in between as centre line marking on the straight portion of parallel taxi track. Yellow triangles of sides 6 M in length marked at both ends of parallel taxi track. White transverse strips of 1.8M width at beginning of straight portion of parallel taxi track at both ends, broken white transverse strips at 300 m from the beginning of straight portion of parallel taxi track at both ends.
11. Hook and pendent arrester cable (RHAG) available for lay out on both ends of RWY 11/29 at distance of 357M from the stop end of RWY 11/29. Height: 0.21FT from RWY surface, Motor assembly hut (infrangible) abeam RHAG location on RWY shoulders at a dist of 1.6M. Max height of hut is 4.5ft. RHAG cable laid out only at one location ,stop end of RWY 11/29. Aircraft can roll down over the cable. Arrester barrier cable installed at 92m from THR, aircraft cannot roll down over arrester barrier cable. All operators to exercise caution.

VEGK AD 2.24 CHARTS RELATED TO AN AERODROME

1 Instrument Approach Chart – ILS (Z) RWY 29
2 Instrument Approach Chart – ILS (Y) RWY 29
3 Instrument Approach Chart – VOR (Z) RWY 29
4 Instrument Approach Chart – VOR (Y) RWY 29
5 Instrument Approach Chart – VOR (Z) RWY 11
6 Instrument Approach Chart – VOR (Y) RWY 11
7 Instrument Approach Chart – NDB RWY 11
8 Instrument Approach Chart – NDB RWY 29

VEGK AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3