AD 2. AERODROMES

VIHX AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIHX - HALWARA AIRPORT, HALWARA

VIHX AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	304457N 0753748E North of Runway, abeam Middle Marker Appx 30 M/100 FT from runway edge.	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	26 Km Southwest of Ludhiana Town	
3	Aerodrome elevation and reference temperature	790 FT / 40.0 DEG C	
4	Magnetic variation, date of information and annual change	1.90 DEG E (2022)/ NIL	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Indian Air Force SATCO Air Force Station Halwara Ludhiana (Punjab) PIN - 141106 Civil Terminal Airport Director Airports Authority of India Halwara Airport Ludhiana (Punjab) 141106,	
		Telephone:	IAF +91-1624-276947 Civil Terminal +91 9815555772
		Fax:	IAF +91-1624-276947
		AFS:	
		Email:	IAF happi-ness9@gov.in Civil Terminal ceolial@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Joint User Airfield (Defence & Civil Ops).	

VIHX AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	Indian Air Force (Air Traffic Services) HJ
2	Custom and immigration	Not Available
3	Health and sanitation	Health – Nil Sanitation - As per AD operator Hours
4	AIS briefing office	H24 (IAF)
5	ATS reporting office (ARO)	HJ (IAF)
6	MET Briefing office	H24 (IAF)
7	Air Traffic Service	HJ (IAF)

8	Fuelling	IOCL (During AD Hours)
9	Handling	Available by AIASL and Global Flight Handling Services on prior coordination with Authorised Ground Handling Agency
10	Security	Available, 24 Hrs
11	De-icing	Not Available
12	Remarks	Non-scheduled operator to take prior clearance from Airport Director for Parking and from ATC for operations

VIHX AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Not Available
2	Fuel and Oil types	JET A1 Fuel Type: Jet A-1 Oil Type: NIL
3	Fuelling facilities and capacity	IOCL, Mobile Refueller-16Kl Qty 02 Static – 200Kl Qty 02
4	De-icing facilities	Not Available
5	Hangar space for visiting aircraft	Not Available
6	Repair facilities for visiting aircraft	Not Available
7	Remarks	Contact No Aviation Fuel Station (IOCL): +91 9873104032

VIHX AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in nearby townships within 10-20 km
2	Restaurant(s) at or in the vicinity of aerodrome	Available in nearby townships within 05km
3	Transportation possibilities	Hired Cars
4	Medical Facilities	First Aid available at terminal. Hospitals are available within 05 km from airport
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available within 05 km from airport. Post office: Available within 05 km from airport.
6	Tourist office	Not available
7	Remarks	NIL

VIHX AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per category
3	Capability for removal of disabled aircraft	Disabled aircraft removal to be ensured by Aircraft operator in coordination with local authority before commencement of Operation.
4	Remarks	NIL

VIHX AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VIHX AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Civil Apron (67 M X 95 M) Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Designator: PTT Width: 23 M Surface: Asphalt Strength: Designator: TWY A Width: 23 M Surface: Asphalt Strength: Designator: TWY D Width: 23 M Surface: Asphalt Strength: Designator: TWY L Width: 23 M Surface: Asphalt Strength:
3	Location and elevation of altimeter checkpoints	Location: NIL Elevation: NIL
4	Location of VOR checkpoints	At RWY Holding position of TWY A and TWY L.
5	Position of INS checkpoints	NIL
6	Remarks	NIL

VIHX AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxi guidance signs at all intersections with taxiway and runway, at all holding positions, gridlines at Apron.
2	Runway and taxiway markings and lights	RWY Markings: Designation, Threshold, touchdown zone, aiming point, Centre line, Runway Edge. Lights: Threshold lights, Runway Edge lights, Runway end light, Runway Centre Line Light. TWY Markings: Centre line, Taxi holding Position at all taxi ways, intersection. Lights: Taxiway Edge light
3	Stop bars (if any)	At TWY A, TWY D and TWY L.
4	Remarks	NIL

VIHX AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
31/TKOF 13/APCH	OTHER	304741.0N 0753548.0E	909 FT	LGTD	MAST
31/TKOF 13/APCH	OTHER	304929.0N 0753418.0E	951 FT	LGTD	MWT
31/TKOF 13/APCH	OTHER	304746.0N 0753216.0E	928 FT	LGTD	MAST
31/TKOF 13/APCH	OTHER	304823.0N 0752924.0E	1010 FT	LGTD	MAST
31/TKOF 13/APCH	OTHER	304419.0N 0753744.0E	902 FT	LGTD	MAST
31/APCH 13/TKOF	OTHER	304401.0N 0753812.0E	896 FT	LGTD	MAST
31/APCH 13/TKOF	OTHER	304335.0N 0753829.0E	925 FT	LGTD	MAST
31/APCH 13/TKOF	OTHER	304332.0N 0753825.0E	935 FT	LGTD	MAST
31/APCH 13/TKOF	OTHER	304116.0N 0754008.0E	968 FT	LGTD	MAST
31/APCH 13/TKOF	OTHER	304229.0N 0754245.0E	991 FT	LGTD	MAST
31/APCH 13/TKOF	OTHER	304229.0N 0754026.0E	942 FT	NO	Thin Mast
In circling area and at AD	BUILDING	304458.0N 0753755.0E	856 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	304501.0N 0753804.0E	886 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	304458.0N 0753749.0E	807 FT	LGTD	BUILDING
In circling area and at AD	BUILDING	304415.0N 0753829.0E	814 FT	LGTD	BUILDING
In circling area and at AD	OTHER	304421.0N 0753747.0E	902 FT	LGTD	Mast (North)
In circling area and at AD	OTHER	305517.0N 0753711.0E	801 FT	LGTD	MAST
In circling area and at AD	OTHER	304436.0N 0753818.0E	801 FT	LGTD	MAST
In circling area and at AD	OTHER	304533.0N 0753827.0E	915 FT	LGTD	MAST
In circling area and at AD	POLE	304510.0N 0753616.0E	902 FT	NIL	POLE
In circling area and at AD	OTHER	304109.0N 0753844.0E	902 FT	LGTD	MAST
In circling area and at AD	OTHER	304305.0N 0753613.0E	919 FT	LGTD	MAST
In circling area and at AD	TOWER	305431.0N 0753337.0E	899 FT	LGTD	TOWER
In circling area and at AD	OTHER	305154.0N 0753457.0E	955 FT	LGTD	MAST
In circling area and at AD	OTHER	305008.0N 0755412.0E	1047 FT	LGTD	MAST

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	OTHER	305057.0N 0754059.0E	1086 FT	LGTD	MAST
In circling area and at AD	OTHER	305035.0N 0754022.0E	988 FT	LGTD	MAST
In circling area and at AD	POLE	304421.0N 0753747.0E	902 FT	LGTD	POLE
In circling area and at AD	OTHER	304832.0N 0752816.0E	961 FT	LGTD	MAST
In circling area and at AD	OTHER	304746.0N 0753216.0E	928 FT	LGTD	MAST
In circling area and at AD	OTHER	304741.0N 0753548.0E	958 FT	LGTD	MAST
In circling area and at AD	OTHER	304804.0N 0754126.0E	991 FT	LGTD	MAST
In circling area and at AD	OTHER	304802.0N 0753816.0E	919 FT	LGTD	MAST
In circling area and at AD	OTHER	304745.0N 0754506.0E	1007 FT	LGTD	MAST
In circling area and at AD	OTHER	304517.0N 0754203.0E	1010 FT	LGTD	MAST
In circling area and at AD	OTHER	304156.0N 0753644.0E	965 FT	LGTD	MAST
In circling area and at AD	OTHER	304109.0N 0754456.0E	968 FT	LGTD	MAST
In circling area and at AD	OTHER	304848.0N 0753906.0E	958 FT	LGTD	MAST
In circling area and at AD	OTHER	304037.0N 0754055.0E	961 FT	LGTD	MAST
In circling area and at AD	BUILDING	305149.0N 0754258.0E	1106 FT	LGTD	Building

VIHX AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	MET Section, Air Force Station Halwara
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 Hrs Observational watch 18 Hrs Forecasting watch (0000 UTC till 1800 UTC)
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Section, Air Force Station Halwara TOO: 0330 UTC Validity: 0600 UTC to 1800 UTC TOO: 0930 UTC Validity: 1800 UTC to 2400 UTC TOO: 1530 UTC Validity: 0000 UTC to 1200 UTC
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend TREND forecast is available with every half hourly METAR during the forecasting watch hours
5	Information on how briefing and/or consultation is provided	Briefing is conducted in MET section
6	Types of flight documentation supplied and language(s) used in flight documentation	T3 and T4 route forecast in English.
7	Charts and other information displayed or available for briefing or consultation	Surface charts, Upper Air charts, Satellite images, Radar images are available

8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Automatic Weather Station, Runway Visual Range, Digital Electronic Theodolite (for taking upper air ascent), Lightning Detection System, Radar and Satellite images are available
9	The air traffic services unit(s) provided with meteorological information	ATS, Air Force Station Halwara
10	Additional information, e.g. concerning any limitation of service.	Forecasting is limited to ATS watch hours only.

VIHX AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
13	131.00 DEG	3034 x 45 M	-	THR: 304527.00N 0753704.00E RWY END: 304422.00N 0753830.00E
31	311.00 DEG	3034 x 45 M	-	THR: 304425.00N 0753826.00E RWY END: 304527.00N 0753704.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 786.0FT TDZ:		310 x 45 M	310 x 45	3774 x 280 M
THR: 790.0FT TDZ:		312 x 45 M	312 x 45	3774 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
310M x 90M	Arresting system not available for civil flights	YES	NIL
312M x 90M	Arresting system not available for civil flights	YES	NIL

VIHX AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
13	3034	3344	3344	3034	NIL
31	3034	3346	3346	2881	NIL

VIHX AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
13	SALS 420 M LIH	Green	PAPI RIGHT/3.00 DEG	900 M
31	CAT II 900 M LIH	Green	PAPI RIGHT/3.00 DEG	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
3034 M 15 M LIH White	3034 M 60 M White LIH	Red	Red 310 M	1. Colour of last 300 M of runway centre line lights is Red, from 300M to 600M Alternate Red & Clear, Rest all in clear filter 2. Colour of last 900 M of runway edge lights is amber
3034 M 15 M LIH White	3034 M 60 M White LIH	Red	Red 312 M	1. Colour of last 300 M of runway centre line lights is Red, from 300M to 600M Alternate Red & Clear, Rest all in clear filter 2. Colour of last 900 M of runway edge lights is amber

VIHX AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building, Alternate White & Green, 24 Flashes /Min, During IMC & Night Ops
		IBN	Not Available

2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	In Front of ATC Building
		Anemometer	End of RWY 31 and RWY 13 along with AWS
3	Taxiway edge and taxiway centre line lights;	Edge	All Taxiway and Links, Distance 200 ft
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary Power Supply to all lighting System/ 08-10 sec	
5	Remarks	NIL	

VIHX AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	TWY A and TWY B on runway and Z helipad (on request from Pilot)

VIHX AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	Not established
2	Vertical limits	Not established
3	Airspace classification	G
4	Call sign and language(s) of the air traffic services unit providing service;	Halwara Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	HJ
7	Remarks	NIL

VIHX AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Halwara Approach	130.100 MHZ	
TWR	Halwara Tower	130.100 MHZ	
ATIS	Halwara Information	115.200 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HJ	NIL
	HJ	NIL
	HJ	NIL

VIHX AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 31 CAT II	IHLR	111.500 MHz	HJ
GP 31		332.900 MHz	HJ
DME ILS 31	IHLR		HJ
DVOR/DME	HLW	115.200 MHz	HJ

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
304533.0N 0753655.0E			1. Controlling Authority: Indian Air Force
304429.0N 0753812.0E			1. Controlling Authority: Indian Air Force 2. Oscillation observed between 1.4 NM to 0.156 NM from THR on GP
304429.0N 0753812.0E	784 FT		1. Controlling Authority: Indian Air Force
304437.0N 0753756.0E	817 FT		1. Controlling Authority: Indian Air Force 2. DME Collocated with DVOR

VIHX AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VIHX AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIHX AD 2.22 FLIGHT PROCEDURES

NIL

VIHX AD 2.23 ADDITIONAL INFORMATION

1. Open saucer drain on northern shoulder of runway having length 850 M, depth 0.5 M, width 02 M and distance from runway edge 83 M.
2. Open saucer drain on southern shoulder of parallel taxi track (PTT) having length 2000 M, width 03 M, depth 0.6 M and distance from edge of parallel taxi track 27 M.
3. Open unpaved saucer drain on northern shoulder of runway from Dumbell 31 to link R2 having length 900 M, depth 0.5 M, width 2 M and distance from runway edge 83 M.
4. Open box drain on south of runway between link R2 and link E having length 2100 M, width 1.6 M, depth 1 M and distance from runway edge 70 M.
5. Open unpaved saucer drain on southern shoulder of parallel taxi track (PTT) from link C to Dumbell 14 having length 2200 M, width 3 M, depth 0.6 M and distance from edge of PTT 27 M.
6. The following ground markings on the manoeuvring area at variance from ICAO Annex 14, Vol 1:
   i) Centre line on parallel taxiway is broken white.
   ii) White transverse strip painted across parallel taxiway at extremities.
   iii) Solid yellow triangles painted at beginning parallel taxi track on both ends.
   iv) Two helipads marked on parallel taxi track abeam link C and link D.
   v) Military aircraft parking bay markings on runway turn pads at both ends.
   vi) Non-Load Bearing (NLB) marking not available on link A, Link D and Parallel taxi track.

VIHX AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aircraft Parking/Docking Chart (11 JUNE 2026)

2 Instrument Approach Chart – CAT I ILS RWY 31 (11 JUNE 2026)

3 Instrument Approach Chart – CAT II ILS RWY 31 (11 JUNE 2026)

4 Instrument Approach Chart – VOR Z RWY 13 (11 JUNE 2026)

5 Instrument Approach Chart – VOR Y RWY 13 (11 JUNE 2026)

6 Instrument Approach Chart – VOR Z RWY 31 (11 JUNE 2026)

7 Instrument Approach Chart – VOR Y RWY 31 (11 JUNE 2026)

VIHX AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3