AD 2. AERODROMES

VIDX AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIDX - HINDAN AIRPORT, HINDAN [INDIAN AIR FORCE]

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VIDX AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	284224N 0772134E 94 M South of RWY 27/09 close to Middle Marker	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	300 DEG/08 KM from Ghaziabad City	
3	Aerodrome elevation and reference temperature	703 FT / 41.0 DEG C	
4	Magnetic variation, date of information and annual change	0.75 DEG E (2016)/ NIL	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Air Traffic Control Air Force Station, Hindan, Ghaziabad - 201004 (UP),	
		Telephone:	(91) 120-2656868
		Fax:	(91) 120 2656868
		AFS:	VIDXYFYX (AMSS)
		Email:	nadnih.sta@gov.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	1.Joint User Aerodrome	

VIDX AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	HJ
2	Custom and immigration	HO
3	Health and sanitation	HJ In coordination with APD, Civil Terminal
4	AIS briefing office	HJ
5	ATS reporting office (ARO)	HJ
6	MET Briefing office	H24
7	Air Traffic Service	HJ and O/R 02 Hrs
8	Fuelling	AVBL
9	Handling	HJ, (IOCL)
10	Security	CASO (CO, Sahibabad, UP Police)
11	De-icing	NIL
12	Remarks	Entry and Exit through civil terminal

VIDX AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Ground handling services by AIASL and Aviaxpert Private Limited AVBL.
2	Fuel and Oil types	ATF A-1(ATF)
3	Fuelling facilities and capacity	1 Bulk Petroleum Installation/ 1200 K Ltr (IOCL)

4	De-icing facilities	NA
5	Hangar space for visiting aircraft	NA
6	Repair facilities for visiting aircraft	NA
7	Remarks	NIL

VIDX AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available at a distance of 05 km
2	Restaurant(s) at or in the vicinity of aerodrome	Light refreshment
3	Transportation possibilities	APP basedTaxis are available
4	Medical Facilities	Hospital available at 03 km
5	Bank and post office at or in the vicinity of aerodrome	Banks: All nationalised banks available within 05 km radius. Post office: AVAILABLE
6	Tourist office	NA
7	Remarks	NIL

VIDX AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	CAT- VIII
2	Rescue equipment	Available as per category
3	Capability for removal of disabled aircraft	With respective operator
4	Remarks	NIL

VIDX AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VIDX AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: APRON Surface: Concrete Strength: PCN 54/R/C/W/T ELEVATION: 702 FT
2	Designation, width, surface and strength of taxiways	Designator: LINK Q Width: 28 M Surface: Concrete Strength: PCN 39/R/C/X/T
3	Location and elevation of altimeter checkpoints	NIL
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	Landing and parking facility with IAF for maximum 02 ATR 72/Q 400 type and 02 A-320/B-737 aircraft simultaneously.

VIDX AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxi guidance provided on R/T

2	Runway and taxiway markings and lights	RWY Markings : Designation, Threshold, touchdown zone, Centreline, RWY Edge & RWY End. RWY Lights : RWY 27 CAT-II Lighting system, RWY 09 – Simple App Lighting TWY Markings : Centre line, Taxi holding Position at all taxiways/ RWY intersection. TWY Lights : Edge of T/T
3	Stop bars (if any)	Available
4	Remarks	NIL

VIDX AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
27/TKOF 09/APCH	OTHER	284236.0N 0772652.0E	997 FT	LGTD	Microwave Tower
27/TKOF 09/APCH	BUILDING	284211.0N 0772500.0E	850 FT	LGTD	Group of Buildings Raj Nagar Extension
27/TKOF 09/APCH	OTHER	284216.0N 0772134.0E	774 FT	LGTD	Tower
27/TKOF 09/APCH	OTHER	284257.0N 0772122.0E	830 FT	LGTD	Overhead Water Tank
27/TKOF 09/APCH	OTHER	284245.0N 0772122.0E	797 FT	LGTD	Hangar
27/TKOF 09/APCH	OTHER	284254.0N 0772132.0E	823 FT	LGTD	Tower 2
27/TKOF 09/APCH	OTHER	284232.0N 0772216.0E	749 FT	LGTD	Tower 3
27/APCH 09/TKOF	OTHER	284216.0N 0772134.0E	774 FT	LGTD	ATC Tower
27/APCH 09/TKOF	BUILDING	284250.0N 0771945.0E	866 FT	LGTD	Buildings
In circling area and at AD	OTHER	284211.0N 0772137.0E	860 FT	LGTD	Mast
In circling area and at AD	BUILDING	284216.0N 0772124.0E	797 FT	LGTD	Building
In circling area and at AD	BUILDING	284323.0N 0772027.0E	830 FT	NO	Apartments
In circling area and at AD	BUILDING	284036.0N 0772348.0E	807 FT	LGTD	Group of Buildings
In circling area and at AD	OTHER	284019.0N 0772402.0E	846 FT	NO	Pylon
In circling area and at AD	OTHER	284048.0N 0772246.0E	843 FT	LGTD	Water Tank
In circling area and at AD	BUILDING	284146.0N 0772641.0E	850 FT	NO	Building
In circling area and at AD	OTHER	284150.0N 0770901.0E	1476 FT	LGTD	Pitampura TV Tower

VIDX AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Air Force Station, Hindan
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 Hrs Observation & Forecast
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	MET office, Air Force Station Hindan 12 Hrs
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend 30 Min
5	Information on how briefing and/or consultation is provided	Available
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form, English
7	Charts and other information displayed or available for briefing or consultation	Surface Chart, Upper Air chart, satellite imagery NWP Output, HRPT products, LDS image
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	AWS, AFNET and LAN
9	The air traffic services unit(s) provided with meteorological information	ATC Hindan
10	Additional information, e.g. concerning any limitation of service.	24 Hrs forecasting

VIDX AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
09	91.00 DEG	2743 x 45 M	71/R/C/X/T Concrete 80/F/C/X/T Flexible	THR: 284228.00N 0772041.00E RWY END: 284227.00N 0772222.00E
27	271.00 DEG	2743 x 45 M	71/R/C/X/T Concrete 80/F/C/X/T Flexible	THR: 284227.00N 0772222.00E RWY END: 284228.00N 0772041.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 700.0FT TDZ: 701.0FT	0.80%	398 x 45 M	398 x 45	3659 x 280 M
THR: 702.0FT TDZ: 703.0FT	0.80%	398 x 45 M	398 x 45	3659 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
NIL	Arresting system not available for civil flights	Obstacle free zone available	1. Slope RWY and associated SWY i.Transverse: 0.5 % ii. Longitudinal: 0.8% 2. Resolution of obstacles coordinates is up to Second only.
NIL	Arresting system not available for civil flights	Obstacle free zone available	1. Slope RWY and associated SWY i.Transverse: 0.5 % ii. Longitudinal: 0.8% 2. Resolution of obstacles coordinates is up to Second only.

VIDX AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
09	2743	3141	3141	2743	NIL
27	2743	3141	3141	2743	NIL

VIDX AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
09	SALS 270 M LIH	Green Available	PAPI RIGHT/3.00 DEG	NIL
27	CAT II 900 M LIH	Green Available	PAPI RIGHT/3.00 DEG	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2743 M 15 M White	2743 M 60 M White LIH	Red	Red 45 M	1. Runway centreline lights between last 300 M to 900 M are alternate RED & variable white and in last 300 M are RED and white light for remaining length of runway
2743 M 15 M White	2743 M 60 M White LIH	Red	Red 45 M	1. Runway centreline lights between last 300 M to 900 M are alternate RED & variable white and in last 300 M are RED and white light for remaining length of runway.

VIDX AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On top of ATC tower 24 FPM, operated during ATS hours at night and when visibility less than 3000 M.
		IBN	N/A
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	South of RWY adjacent to ATC tower/ Lighted
		Anemometer	NIL
3	Taxiway edge and taxiway centre line lights;	Edge	Single aspect blue light, Dist- 60 M at both Parallel Taxi Track (PTT) & North Taxi Track (NTT)
		Centre Line	Only on NTT
4	Secondary power supply including switch-over time;	Two 750 KVA DG Set/ 08-10 sec	
5	Remarks	NIL	

VIDX AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	On Parallel Taxi Track (PTT), south of RWY 27/09 near ARP
2	TLOF and/or FATO area elevation:	NIL
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	NIL
4	True bearings of FATO;	NIL
5	Declared distances available	NIL
6	Approach and FATO lighting;	NIL
7	Remarks	Only aircraft stands 1, 3, 5, 6 and 7 are earmarked for parking of Skid Landing Gear Helicopters

VIDX AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	Not established
2	Vertical limits	Not established
3	Airspace classification	G
4	Call sign and language(s) of the air traffic services unit providing service;	Hindan Tower, English
5	Transition altitude	5000 FT
6	Hours of applicability	Refer NOTAM
7	Remarks	Airspace utilised with Delhi under Flexi use of airspace

VIDX AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Hindan Approach	134.200 MHZ	
TWR	Hindan Tower	130.100 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	Refer NOTAM	NIL
	Refer NOTAM	NIL

VIDX AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	**2**	**3**	**4**
LOC 27	IHND	111.700 MHz	As ATS
GP 27		333.500 MHz	As ATS
DME ILS 27	IHND	CH54X	As ATS
DVOR/DME	HND	113.400 MHz CH81X	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
284228.0N 0772028.0E			1. Controlling Authority: Indian Air Force 2. Resolution of Coordinates is up to Second
284232.0N 0772216.0E			1. Controlling Authority: Indian Air Force 2. Resolution of Coordinates is up to Second
284232.0N 0772216.0E	622 FT		1. Controlling Authority: Indian Air Force 2.CollocatedwithGP27 3. Resolution of Coordinates is up to Second
284219.0N 0772151.0E	726 FT		1. Controlling Authority: Indian Air Force 2. Resolution of Coordinates is up to Second

VIDX AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VIDX AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIDX AD 2.22 FLIGHT PROCEDURES

NIL

VIDX AD 2.23 ADDITIONAL INFORMATION

1. (a) The facilities/ infrastructure at IAF aerodromes mainly cater for Air Force commitments, some of these (like Rescue and Crash Fire Fighting facilities, aerodrome markings, Nav-aids, ATC briefing section etc.) may not conform to ICAO standards. In this regard, IAF accepts no responsibility, whatsoever for the shortcomings/ variations if any.

(b) Landing and parking facility is available in IAF dispersal for ATR 72/Q 400 and A320/B-737class of aircraft. At any given time, maximum of four aircraft (Two of each type) will be permitted on the apron for boarding/ de-boarding.

(c) No Instrument approach is available for RWY 09

(d) Due to extensive bird activity around the airfield, flying is restricted plus minus one hour of sunrise and sunset.

(e) Due to proximity of VIP-89 (South-West of Hindan (236DEG/8NM)), all fixed wing aircraft to mandatory turn Right for a Northerly heading after departure RWY 27.

(f) All slow moving traffic incoming/ transiting via Delhi to mandatorily contact hindan Tower/ Approach open over point-N (360DEG/10NM from DPN) or continue on a northerly heading/maintaining 12 DME ARC HND till such time two way communication is established with hindan to avoid departing/arriving traffic at HINDAN.)

VIDX AD 2.24 CHARTS RELATED TO AN AERODROME

1. Instrument Approach Chart – CAT I ILS RWY 27(19 MAR 2026)
2. Instrument Approach Chart – CAT II ILS RWY 27 (19 MAR 2026)
3. Instrument Approach Chart - VOR RWY 27(12 June 2025)

VIDX AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3