AD 2. AERODROMES

VOHB AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOHB - HUBBALLI AIRPORT, HUBBALLI

VOHB AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	152143N 0750504E 328.067 DEG/ 54M from intersection of TWY C and RWY	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	270 DEG/ 08 KM from Hubballi Railway Station	
3	Aerodrome elevation and reference temperature	2195 FT / 31.0 DEG C	
4	Magnetic variation, date of information and annual change	1.50 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority of India, Hubballi Airport, Hubballi Karnatka-580030,	
		Telephone:	(91) 8362237921
		Fax:	(91) 8362237920
		AFS:	VOHBYHYX
		Email:	apchubli@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Elevation in EGM 08	

VOHB AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT, SUN+ HOL: NIL
2	Custom and immigration	As ATS
3	Health and sanitation	NIL
4	AIS briefing office	As ATS
5	ATS reporting office (ARO)	As ATS
6	MET Briefing office	As ATS
7	Air Traffic Service	Consult NOTAM for current ATS HR.
8	Fuelling	As ATS
9	Handling	As ATS
10	Security	As ATS
11	De-icing	NIL
12	Remarks	The ATS approved hourly RWY traffic handling capacity is as follows: Maximum number of arrivals and departures -07 Maximum number of arrivals only -06 Maximum number of departures only -09

VOHB AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Cargo terminal operator- AAICLAS One time cargo holding capacity-27 Metric tonnes Cold storage- Not available Strong room for valuables- Available Handling equipment- Hydraulic pallet truck, 04 wheel trolley

2	Fuel and Oil types	JET-A1
3	Fuelling facilities and capacity	HPCL-03 refuellers of capacity 15KL each and 01 refueller of capacity 11 KL BPCL-01 bunded tank of capacity 30 KL, 01 refueller of capacity 16 KL and 01 refueller of 06 KL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	NIL

VOHB AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city.
2	Restaurant(s) at or in the vicinity of aerodrome	In the city.
3	Transportation possibilities	Arranged Taxi/Auto
4	Medical Facilities	First aid at AD. Hospital in the city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the city. Post office: In the city
6	Tourist office	In the city.
7	Remarks	NIL

VOHB AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-6
2	Rescue equipment	Available as per category.
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is A320. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director, AAI, Hubballi Airport Phone (Office): 0836-2237921 Mobile: 9449827652 E-mail: apchubli@aai.aero
4	Remarks	NIL

VOHB AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VOHB AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/ Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	LOCATION – PARKING STAND NUMBER 6, 7, 8. ELEVATION – 2192 FT

4	Location of VOR checkpoints	HOLDING POINTS ON TWY-A, TWY-B AND TWY-C
5	Position of INS checkpoints	NIL
6	Remarks	i. Apron floodlights available. ii. Coordinates of Taxi Holding Position: TWY A: 152139.205N 0750513.316E/ 2176.9685 FT TWY B: 152138.810N 0750510.027E/ 2180.3674 FT TWY C: 152138.216N 0750505.051E/ 2181.4304 FT TWY D: 152131.957N 0750413.062E/ 2194.5538 FT All elevations in EGM08

VOHB AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiway guideline, Taxi holding position and aircraft stand markings are provided on the apron.
2	Runway and taxiway markings and lights	RWY Markings:Designation, THR, Aiming point, Centreline, Edge and RWY end, Touchdown. Lighting:THR, Edge, End. TWY Marking:Centreline, Holding Position, Edge. Lighting:Edge.
3	Stop bars (if any)	Nil
4	Remarks	

VOHB AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
26/TKOF 08/APCH	BUILDING	152132.1N 0750407.5E	2212 FT	NO	Temple
26/TKOF 08/APCH	TREE	152133.2N 0750353.0E	2237 FT	NO	Group of Trees
26/TKOF 08/APCH	TREE	152134.8N 0750353.3E	2235 FT	NO	Group of Trees
26/TKOF 08/APCH	TREE	152134.2N 0750358.6E	2234 FT	NO	Group of Trees
26/TKOF 08/APCH	TREE	152138.8N 0750402.6E	2235 FT	NO	Group of Trees
26/TKOF 08/APCH	TREE	152130.9N 0750405.1E	2227 FT	NO	Group of Trees
26/TKOF 08/APCH	TREE	152130.7N 0750407.4E	2243 FT	NO	Group of Trees
26/TKOF 08/APCH	TREE	152131.9N 0750407.5E	2239 FT	NO	Group of Trees
26/TKOF 08/APCH	OTHER	152140.5N 0750257.3E	2379 FT	NO	Mast
26/TKOF 08/APCH	OTHER	152131.7N 0750408.6E	2206 FT	NO	Spot Elev
26/TKOF 08/APCH	OTHER	152132.0N 0750408.8E	2203 FT	NO	Spot Elev
26/TKOF 08/APCH	OTHER	152131.8N 0750409.5E	2203 FT	NO	Spot Elev

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
26/TKOF 08/APCH	OTHER	152131.9N 0750410.3E	2201 FT	NO	Spot Elev
26/TKOF 08/APCH	OTHER	152123.0N 0750225.1E	2352 FT	NO	Pylon Mast
26/APCH 08/TKOF	BUILDING	152140.5N 0750750.4E	2506 FT	NO	KIMS Hospital Building
26/APCH 08/TKOF	TREE	152148.1N 0750541.2E	2172 FT	NO	Group of Trees
26/APCH 08/TKOF	TREE	152142.1N 0750542.1E	2170 FT	NO	Group of Trees
In circling area and at AD	OTHER	152139.0N 0750419.8E	2209 FT	LGTD	W.D.I.
In circling area and at AD	SIGN	152134.4N 0750418.8E	2195 FT	NO	Sign Board
In circling area and at AD	OTHER	152131.3N 0750415.3E	2197 FT	NO	Spot Elev
In circling area and at AD	OTHER	152131.9N 0750411.2E	2197 FT	NO	Spot Elev
In circling area and at AD	OTHER	152143.0N 0750530.2E	2159 FT	LGTD	PAPI
In circling area and at AD	OTHER	152140.2N 0750529.3E	2216 FT	LGTD	Glide Path Main Antenna
In circling area and at AD	OTHER	152140.4N 0750531.6E	2180 FT	LGTD	Glide Path Monitor Antenna
In circling area and at AD	OTHER	152139.9N 0750529.3E	2180 FT	LGTD	Glide Path DME
In circling area and at AD	OTHER	152140.1N 0750528.9E	2178 FT	LGTD	Lightning Arrestor on GP Hut
In circling area and at AD	OTHER	152140.1N 0750528.3E	2196 FT	LGTD	MET Antenna
In circling area and at AD	TREE	152128.6N 0750424.2E	2258 FT	NO	Group of Trees
In circling area and at AD	TREE	152140.3N 0750401.7E	2240 FT	NO	Group of Trees
In circling area and at AD	TREE	152140.1N 0750404.6E	2233 FT	NO	Group of Trees
In circling area and at AD	TREE	152140.1N 0750406.2E	2229 FT	NO	Group of Trees
In circling area and at AD	TREE	152129.6N 0750409.7E	2228 FT	NO	Group of Trees
In circling area and at AD	TREE	152141.2N 0750402.4E	2242 FT	NO	Group of Trees
In circling area and at AD	TREE	152127.6N 0750418.8E	2255 FT	NO	Group of Trees
In circling area and at AD	OTHER	152130.6N 0750415.8E	2201 FT	NO	Spot Elev
In circling area and at AD	OTHER	152130.1N 0750415.9E	2204 FT	NO	Spot Elev
In circling area and at AD	BUILDING	152207.2N 0750221.4E	2396 FT	NO	Temple on Hill (Hill Top - 723.1 M)
In circling area and at AD	OTHER	152157.4N 0750259.3E	2356 FT	NO	Pylon Mast

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	BUILDING	152200.2N 0750242.5E	2348 FT	NO	Building
In circling area and at AD	BUILDING	152205.7N 0750239.7E	2364 FT	NO	Building
In circling area and at AD	OTHER	152203.7N 0750247.5E	2344 FT	NO	Overhead Water Tank
In circling area and at AD	OTHER	152207.5N 0750246.4E	2367 FT	NO	Pylon Mast
In circling area and at AD	OTHER	152204.9N 0750238.7E	2406 FT	NO	Mast
In circling area and at AD	BUILDING	152159.0N 0750243.4E	2352 FT	NO	Building
In circling area and at AD	OTHER	152201.8N 0750241.6E	2383 FT	NO	Cellphone Mast
In circling area and at AD	OTHER	152157.2N 0750258.6E	2356 FT	NO	Pylon Mast
In circling area and at AD	ANTENNA	152143.8N 0750257.1E	2388 FT	NO	Antenna Near Building
In circling area and at AD	STACK	152153.8N 0750243.4E	2358 FT	NO	Chimney
In circling area and at AD	OTHER	152138.7N 0750527.6E	2178 FT	NO	Bird Chaser Hut
In circling area and at AD	TREE	152150.6N 0750536.3E	2170 FT	NO	Group of Trees
In circling area and at AD	TREE	152138.8N 0750537.4E	2206 FT	NO	Group of Trees
In circling area and at AD	TREE	152135.4N 0750533.2E	2223 FT	NO	Group of Trees
In circling area and at AD	TREE	152136.6N 0750532.3E	2218 FT	NO	Tree
In circling area and at AD	TREE	152150.5N 0750538.3E	2172 FT	NO	Group of Trees
In circling area and at AD	TREE	152140.9N 0750543.8E	2176 FT	NO	Tree
In circling area and at AD	TREE	152137.4N 0750538.7E	2202 FT	NO	Group of Trees
In circling area and at AD	TREE	152136.6N 0750540.3E	2219 FT	NO	Group of Trees
In circling area and at AD	OTHER	152239.4N 0750740.1E	2399 FT	NO	Shed on Hill
In circling area and at AD	OTHER	152131.3N 0750427.0E	2210 FT	NO	Bird Chaser Hut
In circling area and at AD	OTHER	152135.0N 0750458.7E	2205 FT	NO	Bird Chaser Hut
In circling area and at AD	OTHER	152137.2N 0750515.0E	2185 FT	NO	Bird Chaser Hut
In circling area and at AD	OTHER	152132.2N 0750432.6E	2206 FT	NO	Bird Chaser Hut
In circling area and at AD	TREE	152134.2N 0750448.4E	2207 FT	NO	Group of Trees
In circling area and at AD	OTHER	152147.5N 0750530.1E	2174 FT	LGTD	W.D.I.

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	152133.4N 0750512.4E	2246 FT	LGTD	Lightning Arrestor on Old ATC (ATC Top - 681.5 M.)
In circling area and at AD	OTHER	152200.5N 0750254.8E	2351 FT	NO	Pylon Mast
In circling area and at AD	BUILDING	152403.7N 0750408.9E	2400 FT	NO	Building
In circling area and at AD	OTHER	152309.5N 0750454.7E	2377 FT	NO	Cellphone Mast
In circling area and at AD	OTHER	152216.3N 0750225.9E	2406 FT	NO	Pylon Mast
In circling area and at AD	OTHER	152217.5N 0750234.4E	2407 FT	NO	Pylon Mast
In circling area and at AD	OTHER	152255.4N 0750257.9E	2353 FT	NO	Overhead Water Tank
In circling area and at AD	OTHER	152225.0N 0750308.3E	2349 FT	NO	Pylon Mast
In circling area and at AD	OTHER	152554.8N 0750029.0E	2738 FT	NO	Cellphone Mast
In circling area and at AD	OTHER	152449.8N 0750229.4E	2698 FT	NO	TV Tower
In circling area and at AD	TREE	152415.3N 0750348.3E	2511 FT	NO	Tree on Hill
In circling area and at AD	OTHER	152236.1N 0750744.3E	2472 FT	NO	Police Mast
In circling area and at AD	OTHER	152017.0N 0750619.7E	2363 FT	NO	Mast
In circling area and at AD	OTHER	152235.8N 0750744.6E	2465 FT	NO	Police Mast
In circling area and at AD	TREE	152235.0N 0750745.8E	2452 FT	NO	Group of Trees

VOHB AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	AMS HUBBALLI
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As ATS HR. AMO Bengaluru
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	AMO Bengaluru 1) 30 HOURS TAF issued every 6 hrs. interval 2) 09 HOURS TAF issued every 3 hrs. interval
4	Availability of the trend forecast for the aerodrome and interval of issuance	NOT AVBL
5	Information on how briefing and/or consultation is provided	Through OLBS
6	Types of flight documentation supplied and language(s) used in flight documentation	English
7	Charts and other information displayed or available for briefing or consultation	Charts and Documents available in OLBS will be provided to operators as per their requirement

8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Digital Current Weather Instrument System (DCWIS) installed at a distance of 115 M from the centre line of the RWY and 330 M from THR RWY 26. Present Weather Detector having RVR installed for RWY 26.
9	The air traffic services unit(s) provided with meteorological information	VOHB Hubballi TWR
10	Additional information, e.g. concerning any limitation of service.	Half hourly MET REPORT & SPECIAL REPORT during ATS HR.

VOHB AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
08	82.93 DEG	2600 x 45 M	58/F/C/W/T Macadam	THR: 152134.81N 0750412.31E RWY END: 152145.22N 0750538.78E
26	262.93 DEG	2600 x 45 M	58/F/C/W/T Macadam	THR: 152145.22N 0750538.78E RWY END: 152134.81N 0750412.31E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 2195.0FT TDZ: 2195.0FT	-0.50%	NIL	NIL	2720 x 300 M
THR: 2153.0FT TDZ: 2178.0FT	0.50%	NIL	NIL	2720 x 300 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M	NIL	Nil	Vertical Datum: EGM 08
240M x 90M	NIL	Nil	Vertical Datum: EGM 08

VOHB AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
08	2600	2600	2600	2600	
26	2600	2600	2600	2600	

VOHB AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
08	SALS 420 M LIH	Green NIL	PAPI LEFT/3.00 DEG	
26	CAT I 900 M LIH	Green NIL	PAPI RIGHT/3.00 DEG	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2600 M 60 M White LIH	Red		NIL
	2600 M 60 M White LIH	Red		NIL

VOHB AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building FLG W&G 20 to 30 flashes/min As ATS HR
		IBN	---
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Landing T Provided between Taxiway A and Taxiway B and illuminated.
		Anemometer	Anemometer is part of DCWIS and located South of RWY-26 TDZ, near to Glide path building.
3	Taxiway edge and taxiway centre line lights;	Edge	Lighted
		Centre Line	-----
4	Secondary power supply including switch-over time;	Available.Switch-over time: 15 Sec.	

5	Remarks	WDI provided at both ends of Runway north of runway threshold 08/26. All Wind Direction Indicator are illuminated.

VOHB AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	Not Established

VOHB AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 154641N 0750747E then along the clockwise arc of a circle of 25NM radius centred on 152143N 0750504E to 152127N 0743912E then along the counter clockwise arc of a circle of 30NM radius centred on 155130N 0743704E to point of origin.
2	Vertical limits	FL 95
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Hubballi Tower, English
5	Transition altitude	6000 FT
6	Hours of applicability	HO
7	Remarks	Hubballi Approach Control Unit is combined with Hubballi Aerodrome Control Tower.

VOHB AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Hubballi Tower	118.850 MHZ	
APP	Hubballi Tower	122.200 MHZ	
TWR	Hubballi Tower	118.850 MHZ	
TWR	Hubballi Tower	122.200 MHZ	
ATIS	Hubballi Information	127.400 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	1.Backup 2. Functions of Approach Control Service provided by Aerodrome Control Tower.

Logon address, as appropriate	Hours of operation	Remarks
	HO	1. Main 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
	AS ATS	SDBY FREQ
	As ATS	SMC and TWR combined
	As ATS	NIL

VOHB AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 26 CAT I	IHUB	109.100 MHz	
GP 26		331.400 MHz	As ATS
DME ILS 26	IHUB	CH28X	H24
DVOR/DME	HBL	113.400 MHz CH81X	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
152133.6N 0750402.2E			
152140.2N 0750529.3E			
152140.2N 0750529.3E	2180 FT		Elevation in EGM-08
152154.5N 0750547.7E	2176 FT		Vertical Datum: EGM 08, DME CO-LOCATED WITH DVOR

VOHB AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VOHB AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VOHB AD 2.22 FLIGHT PROCEDURES

1.INTRODUCTION

1.1 Radio communication failure (RCF) procedures are prescribed in ICAO PANS-ATM DOC 4444. The objective is to standardize the actions to be taken by the pilot of arriving and departing aircraft experiencing radio communication failure at Hubballi airport. Based on these provisions, following radio communication failure procedures are established, to standardize the actions to be taken by the pilot of arriving and departing aircraft at Hubballi airport.

2. GENERAL:

2.1 All Transponder equipped aircraft experiencing Radio Communication Failure shall set transponder to Mode A code 7600 as soon as practicable.
(Note: This Requirement of Setting transponder to Mode A code 7600 in no way imposes any restriction on the pilot's decision to set transponder to Mode A code 7500 or 7700, whenever required).

2.2 Immediately after the detection of RCF, the pilot shall try to communicate to Hubballi ATS unit through the standby frequency 118.850 MHZ.

2.3 If unable to contact on standby frequency also, pilot shall try to communicate through adjacent unit's/stations frequencies (VOBM 119.200 MHz, VOML 127.550MHz, VOGO 123.800 MHz), company frequency or by relay through other aircraft.

2.4 Unless otherwise required, the aircraft shall avoid all Restricted and Prohibited Areas.

2.5 The pilot shall make blind transmission to ATC of all necessary reports and actions taken by the aircraft, e.g. descent, turn, joining hold, leaving for approach, FAF etc., irrespective of whether partial/complete RCF has been experienced or not.

3. ASSIGNED RUNWAY AND AVAILABILITY FOR RCF AIRCRAFT:

3.1 ln case of arriving aircraft, when Runway for landing has already been advised to the aircraft by ATC, such runway shall be considered as assigned runway. If radio communication failure occurs after the receipt of final/procedural turn or approach clearance, the aircraft may continue its approach to land on such Runway and observe the ATC tower to follow the visual Signal for the control of aircraft shown from the aerodrome control Tower.

3.2 (a) In the event of arriving aircraft has not been advised of any runway for landing, Runway 26 shall be considered as assigned runway for such arrival, as ILS is available only for RWY 26.

(b) In strong tail wind conditions for Runway-26, aircraft will carry out a missed approach for Runway-26 and after following complete missed approach procedure for such approach, will carry out the published instrument approach procedure for Runway 08.

3.3 In the case of neighbouring adjacent ATC unit informs that the departing aircraft from Hubballi is returning on account of RCF and squawking 7600, the departure runway of such aircraft shall be considered as assigned runway for landing.

3.4 Hubballi ATC shall ensure PAPI, approach and runway lights of the assigned runway in 'SWITCHED ON' position for RCF aircraft irrespective of day/night/visibility/weather conditions.

3.5 PAPI and Approach lights in 'SWITCHED OFF' position shall indicate that the approach should be made from the opposite end of same runway.

3.6 PAPI, Runway and Approach lights on both sides in 'SWITCHED OFF' position shall indicate non- availability of Runway for aircraft experiencing RCF.

4. PROCEDURE FOR ARRIVALS:

4.1 ARRIVING AIRCRAFT - In VMC

4.1.1 Continue to fly in visual meteorological conditions

4.1.2 land at the nearest suitable aerodrome.

4.1.3 Report its arrival by the most expeditious means to the appropriate air traffic control unit.

4.1.4 If landing at Hubballi, Observe the ATC tower to follow Various Signals used by ATCO during communication failure.

4.2 ARRIVING AIRCRAFT - In IMC

4.2.1 Maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 20 minutes following the aircraft's failure to report its position over a compulsory reporting point and thereafter adjust level and speed in accordance with the filed flight plan; or

4.2.2 Proceed according to the current flight plan route to the appropriate designated navigation aid and hold over this aid until commencement of descent.

4.2.3 Commence descent at, or as close to, the expected approach time (EAT) last received and acknowledged; if no expected approach time has been received and acknowledged, at, or as close as possible to, the estimated time of arrival resulting from the current flight plan;

4.2.4 Complete a normal instrument approach procedure as specified for the designated navigation aid.

4.2.5 land, if possible, within 30 minutes of the estimated time of arrival (ETA) or the last acknowledged expected (EAT) approach time, whichever is later.

4.2.6 Observe the ATC tower to follow visual Signal for the control of aircraft shown from the aerodrome control Tower during communication failure.

4.2.7 After landing at Hubballi Airport, Aircraft shall lookout for follow me jeep on taxiway holding point and after sighting the Follow me Jeep, Aircraft shall follow the Follow Me Jeep for parking to the allotted bay. Upon sighting the Marshaller, aircraft shall stop following “Follow me Jeep” and shall follow marshaller for parking.

5. PROCEDURE FOR DEPARTURES:

5.1 DEPARTURE INTENDING TO CONTINUE TO DESTINATION: Departing aircraft experiencing RCF and intending to continue to its filed plan destination shall;

5.1.1 Continue on assigned route/Radial climbing to or maintaining cleared level as per the clearance given as far as practicable.

5.1.2 Three minutes after setting Mode A/C code 7600 or reaching cleared Flight level whichever is later; aircraft shall proceed directly to re-join the current flight plan route not later than the next significant point, maintaining cleared flight level. After joining ATS route, climb to filed Flight level and continue as per the filed fight plan. (Aircraft shall avoid all Prohibited and Restricted areas).

5.2 DEPARTURE INTENDING TO LAND BACK AT Hubballi: Departing aircraft experiencing RCF and intending to land back at Hubballi airport shall;

5.2.1 Continue as per ATC clearance, climbing to or maintaining the cleared Flight level.

5.2.2 Three minutes after setting Mode A/C code 7600 or reaching the cleared level, whichever is later; take a turn to proceed direct to 'HBL' maintaining the cleared level. The departure runway of such aircraft shall be considered as assigned runway for landing.

5.2.3 Descend to 4500 FT in HBL hold (If required to burn fuel, then remain in the hold.). Leave 'HBL' at 4500 FT to carry out any of the published instrument approach procedure for assigned runway.

5.2.4 Observe the ATC tower to follow visual Signal for the control of aircraft shown from the aerodrome control Tower during communication failure.

5.2.5 After landing at Hubballi Airport, Aircraft shall lookout for follow me jeep on taxiway holding point and after sighting the Follow me Jeep, Aircraft shall follow the Follow Me Jeep for parking to the allotted bay.

Upon sighting the Marshaller, aircraft shall stop following "Follow me Jeep" and shall follow marshaller for parking.

VOHB AD 2.23 ADDITIONAL INFORMATION

1.**Exemption Granted by DGCA:**

DGCA India has granted Permanent exemption vide letter dated 11.08.2015 for non-compliant location of runway exit sign against provisions in CAR Section 4 Series B Part I Para 5.4.3.17 .

2.Birds activities are in and around the airfield. Pilots to exercise caution while landing and taking off.

VOHB AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (23 January 2025)
2. Aircraft Parking/ Docking Chart (23 January 2025)
3. Aerodrome Obstacle Chart - Type A (Operating Limitations) RWY 08 (23 January 2025)
4. Aerodrome Obstacle Chart - Type A (Operating Limitations) RWY 26 (23 January 2025)
5. Aerodrome Obstacle Chart – Type B (23 January 2025)
6. ILS Procedure RWY 26
7. VOR Procedure RWY 08 (CAT A/B/C)
8. VOR Procedure RWY 26 (CAT A/B/C) (DME Required)
9. RNP Y Procedure RWY 08
10. Coding Table - RNP Y Procedure RWY 08
11. RNP Y Procedure RWY 26
12. Coding Table - RNP Y Procedure RWY 26

VOHB AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3