AD 2. AERODROMES

VAJB AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VAJB - JABALPUR AIRPORT, JABALPUR

VAJB AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	231100N 0800338E MAG BRG 245.50 DEG / 698.14 M from Physical Extremity of RWY 24	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	080 DEG, 15 Km from Jabalpur Railway Station	
3	Aerodrome elevation and reference temperature	1626 FT / 42.0 DEG C	
4	Magnetic variation, date of information and annual change	0.36 DEG W (2010) /0.016 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority of India, Jabalpur Airport, Jabalpur - 482005	
		Telephone:	+ 91 761-2601341 (O) + 91 75662 29006 (M)
		Fax:	
		AFS:	VAJBYDYX
		Email:	apd_vajb@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Elevation in EGM 08	

VAJB AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT, SUN+HOL: Nil
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As ATS
5	ATS reporting office (ARO)	As ATS
6	MET Briefing office	As ATS
7	Air Traffic Service	Consult NOTAM for current ATS HR
8	Fuelling	ATF Refueling available with Reliance AFS, IOCL AFS & BPCL AFS
9	Handling	As ATS
10	Security	As ATS
11	De-icing	NIL
12	Remarks	1. Outside of ATS hours services are available on request with 24-hour prior notice to aerodrome. 2. 48-hour prior notice required for night operations. 3. The ATS approved hourly runway traffic handling capacity is as follows: Maximum number of arrival and departure -12 (the minimum spacing between two successive arrivals and DEP shall be more than five minutes) Maximum number of arrivals only -6 Maximum number of departures only -10

VAJB AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	1) IOCL AFS Storage Capacity- 70 KL 2 Bowser- 16 KL (each) 2) BPCL AFS Storage Capacity- 30 KL 2 Bowser- 16 KL (each) 3) Reliance AFS Storage Capacity- 60 KL 3 Bowser- 6 KL (each) 1 Bowser- 11 KL 1 Bowser- 16 KL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VAJB AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city.
2	Restaurant(s) at or in the vicinity of aerodrome	In the city.
3	Transportation possibilities	Car rental service counter available in Arrival Hall.
4	Medical Facilities	First aid at AD. Hospital in the city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the city Post office: In the city
6	Tourist office	In the city.
7	Remarks	NIL

VAJB AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-6
2	Rescue equipment	AVBL as per category.
3	Capability for removal of disabled aircraft	1.The critical aircraft for the airport is A-320. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director Contact number :0761-2601341, Mob:- 7566229006 E-mail:- apd_vajb@aai.aero
4	Remarks	NIL

VAJB AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL

3	Remarks	NIL

VAJB AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking / Docking Chart for Details
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking / Docking Chart for Details
3	Location and elevation of altimeter checkpoints	Location: On all aircraft stands Elevation: Refer Aircraft Parking/Docking Chart
4	Location of VOR checkpoints	On TWY A and TWY C
5	Position of INS checkpoints	NIL
6	Remarks	1. Old Apron Dimension: 67 X 52 M PCR 400/R/C/W/T 2. New Apron Dimension: 206 X 117 M PCR 760/R/A/W/T 3. Isolated Aircraft Parking Position: i. Dimension: 108.5m X 68m ii. Shoulders 3.5M iii. Location: Southwest of Aerodrome near RWY 06 beginning. iv. Surface: Rigid pavement, Concrete Surface, PCR: 680/R/B/W/T v. Coordinate & Elevation: 2301015.53N 08000242.26E/477.765M vi. Lightings: Isolation Bay Flood Lights vii. Suitable for: A320 4. Taxiway Connecting Isolated Aircraft Parking Position: Designation: TWY B Dimension: 165 X18 M Shoulder: 3.5 M on both sides. Location: Southwest of Aerodrome near RWY 06 beginning. Surface: - Bitumen up to 58 M from Runway Edge - PCR 625/F/B/W/T Concrete up to 107.4 M from IPB Edge. - PCR 680/R/B/W/T 5. Coordinates of RWY Holding Position: TWY A: 231055.54N 0800329.68E ELEV: 1624 FT TWY C: 231055.64N 0800329.62E ELEV: 1624 FT 6. Coordinates of RWY & TWY A Intersection TWY A: 231053.45 N 0800331.05E ELEV: 1625 FT 7. Vertical Datum: EGM 08

VAJB AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft ID marking provided on ground. Taxiing guidance provided on RTF. Standard markings at Apron, Mandatory Information and Location signs provide Guidelines at apron. PBB and Visual docking/parking guidance system available for parking stand no. 1 to 3.
2	Runway and taxiway markings and lights	RWY Markings: Designation, THR, Centre line, Aiming Point, TDZ, Edge. RWY Lighting: Edge, End, Threshold TWY Markings: Centre line, Holding Positions, Edge TWY Lighting: Edge
3	Stop bars (if any)	NIL
4	Remarks	NIL

VAJB AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
24/TKOF 06/APCH	OTHER	231022.2N 0800235.4E	1576 FT	NIL	APPROACH LIGHT
24/TKOF 06/APCH	TREE	231025.5N 0800231.9E	1582 FT	NIL	GROUP OF TREES
In circling area and at AD	OTHER	231022.7N 0800236.4E	1576 FT	NIL	APPROACH LIGHT
In circling area and at AD	TREE	231026.5N 0800233.6E	1590 FT	NIL	GROUP OF TREES
In circling area and at AD	TREE	231024.9N 0800229.8E	1588 FT	NIL	GROUP OF TREES
In circling area and at AD	OTHER	231029.7N 0800241.9E	1586 FT	NO	SECURITY HUT
In circling area and at AD	TREE	231020.5N 0800239.9E	1577 FT	NO	TREE
In circling area and at AD	FENCE	231029.8N 0800241.5E	1586 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	OTHER	231025.9N 0800249.1E	1589 FT	NIL	SECURITY HUT
In circling area and at AD	FENCE	231031.1N 0800243.9E	1589 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	OTHER	231059.7N 0800328.3E	1690 FT	NIL	FLOOD LIGHT MAST
In circling area and at AD	OTHER	231058.6N 0800326.3E	1690 FT	NO	FLOOD LIGHT MAST
In circling area and at AD	BUILDING	231058.7N 0800324.9E	1666 FT	NO	ATC BUILDING TOP
In circling area and at AD	ANTENNA	231058.9N 0800324.9E	1681 FT	NO	ANTENNA ON ATC BLDG.
In circling area and at AD	BUILDING	231106.2N 0800341.5E	1650 FT	NIL	TEMPLE
In circling area and at AD	NATURAL HIGHPOINT	231101.2N 0800338.1E	1629 FT	NIL	SPOT LEVEL
In circling area and at AD	SIGN	231100.2N 0800337.6E	1634 FT	NIL	ARP SIGN BOARD
In circling area and at AD	FENCE	231052.6N 0800337.1E	1635 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	OTHER	231049.4N 0800331.1E	1634 FT	NIL	SECURITY HUT
In circling area and at AD	FENCE	231047.7N 0800328.2E	1628 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	OTHER	231051.6N 0800322.6E	1639 FT	NIL	WDI

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	OTHER	231050.9N 0800332.7E	1641 FT	NIL	MOBILE ROAD TRAFFIC (ROAD ELEV. 495.1 M. + 5.0 M TRAFFIC HT.)
In circling area and at AD	ANTENNA	231101.8N 0800336.4E	1641 FT	NIL	ANTENNA TOP
In circling area and at AD	ANTENNA	231101.0N 0800336.6E	1660 FT	LGTD	MET ANTENNA (L)
In circling area and at AD	TREE	231106.5N 0800337.4E	1691 FT	NIL	GROUP OF TREES
In circling area and at AD	FENCE	231104.3N 0800339.7E	1638 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	FENCE	231057.6N 0800345.0E	1629 FT	NIL	TEMPORARY AIRPORT BOUNDARY WALL WITH F/T
In circling area and at AD	FENCE	231101.5N 0800345.4E	1634 FT	NIL	TEMPORARY AIRPORT BOUNDARY WALL WITH F/T
In circling area and at AD	OTHER	231101.2N 0800352.8E	1626 FT	NIL	GP HUT
In circling area and at AD	OTHER	231036.4N 0800307.9E	1614 FT	NIL	SECURITY HUT
In circling area and at AD	TREE	231047.2N 0800310.5E	1632 FT	NIL	GROUP OF TREES
In circling area and at AD	FENCE	231047.6N 0800313.2E	1616 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	OTHER	231047.6N 0800313.5E	1619 FT	NIL	SECURITY HUT
In circling area and at AD	FENCE	231040.7N 0800301.0E	1609 FT	NIL	AIRPORT BOUNDARY WALL WITH FENCING TOP
In circling area and at AD	TREE	231038.9N 0800314.1E	1622 FT	NIL	GROUP OF TREES
In circling area and at AD	FENCE	231104.5N 0800343.4E	1624 FT	NIL	TEMPORARY AIRPORT BOUNDARY WALL WITH F/T
In circling area and at AD	TREE	231046.0N 0800307.3E	1628 FT	NIL	GROUP OF TREES
In circling area and at AD	BUILDING	231100.5N 0800353.3E	1622 FT	NIL	BUILDING
In circling area and at AD	TOWER	230955.1N 0800311.7E	1781 FT	LGTD	MOBILE TOWER

VAJB AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	AMS JABALPUR

2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	0200 UTC TO 1400 UTC (Changes as per ATC Watch). FOR OUTSIDE HOURS: MO JABALPUR
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	TAF ISSUED BY M O NAGPUR/BHOPAL 9 HOURS VALIDITY 3 HOURS INTERVAL
4	Availability of the trend forecast for the aerodrome and interval of issuance	NOT AVAILABLE
5	Information on how briefing and/or consultation is provided	COLLECTED BY CREW/OPERATORS FROM MET OFFICE OR ONLINE WHEN REQUIRED.
6	Types of flight documentation supplied and language(s) used in flight documentation	ROFOR, TAF, SAT PIC, METAR, MET-T3 FORM & CHARTS OBTAINED FROM OLBS. ENGLISH
7	Charts and other information displayed or available for briefing or consultation	RELEVANT CHARTS AVAILABLE ON OLBS LIKE UPPER AIR CHARTS, CROSS SECTION CHARTS, WX BULLETINS
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	NIL
9	The air traffic services unit(s) provided with meteorological information	ATC JABALPUR
10	Additional information, e.g. concerning any limitation of service.	NIL

VAJB AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCR) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
06	58.69 DEG	2750 x 45 M	625/F/B/W/T Asphalt	THR: 231023.20N 0800237.26E RWY END: 231109.67N 0800359.89E
24	238.69 DEG	2750 x 45 M	625/F/B/W/T Asphalt	THR: 231109.67N 0800359.89E RWY END: 231023.20N 0800237.26E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 1575.0FT TDZ: 1601.0FT	0.77%	NIL	NIL	2870 x 280 M
THR: 1611.0FT TDZ: 1626.0FT	-0.77%	NIL	NIL	2870 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M		NIL	i) PCR: 0 to 762 M: 685/F/C/W/T 762 to 2750 M: 625/F/B/W/T ii)Vertical Datum: EGM 08
240M x 90M		NIL	i) PCR: 0 to 1988 M: 625/F/C/W/T 1988 to 2750M: 685/F/B/W/T ii) Vertical Datum: EGM 08

VAJB AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
06	2750	2750	2750	2750	NIL
24	2750	2750	2750	2750	NIL

VAJB AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
06	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (16.25M)	NIL
24	CAT I 900 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (16.94M)	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2750 M 60 M White LIH	Red		i) Distance of PAPI from RWY 06 THR – 277.77 M ii) Runway edge lights variable white, Last 600m yellow towards the landing direction
	2750 M 60 M White LIH	Red	NIL	i) Distance of PAPI from RWY 24 THR – 300.35 M ii) Runway edge lights variable white, Last 600m yellow towards the landing direction

VAJB AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Top of ATC Tower Roof flashing White & Green alternately 30 FPM. Operational during ATC Watch Hours
		IBN	
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	0.6 NM North of ARP, Lighted
		Anemometer	NIL
3	Taxiway edge and taxiway centre line lights;	Edge	Available
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Switch-over time: 15 SEC.	
5	Remarks	Apron floodlight available. Lighted wind cone available	

VAJB AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	---
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	---
4	True bearings of FATO;	---
5	Declared distances available	---
6	Approach and FATO lighting;	---
7	Remarks	---

VAJB AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 231046N 0800335E within a 25NM radius.
2	Vertical limits	FL 105
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Jabalpur Tower, English
5	Transition altitude	5000 FT
6	Hours of applicability	HO
7	Remarks	Jabalpur Approach Control Unit is combined with Jabalpur Aerodrome Control Tower.

VAJB AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Jabalpur Tower	118.850 MHZ	
APP	Jabalpur Tower	122.300 MHZ	
TWR	Jabalpur Tower	118.850 MHZ	
TWR	Jabalpur Tower	122.300 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	1.Main FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1.Backup FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	Backup Frequency
	HO	NIL

VAJB AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 24 CAT I	IJBL	111.100 MHz	
GP 24		331.700 MHz	
DME ILS 24	IJBL	CH48X	As ATS
DVOR/DME	JJB	113.600 MHz CH83X	AS ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
231017.9N 0800227.9E			
231101.1N 0800353.0E			Glide Angle 3 DEG
231101.1N 0800353.1E	1634 FT		Gravity Model: EGM 08
231046.0N 0800334.7E	1649 FT		Vertical Datum: EGM 08

VAJB AD 2.20 LOCAL AERODROME REGULATIONS

1. PUSHBACK AND TAXI PROCEDURES: New Apron

a) STAND NUMBER 1 TO 3

- Arriving aircraft shall vacate the runway via TWY A and turn right for powered in taxi to stand number 1 to 3.
- Aircraft parked at Stand 2 and 3 shall pushback facing WEST and pull forward the aircraft behind Stand number 3 for Startup or as instructed by ATC.
- Aircraft parked at stand number 1 shall make deep pushback on extended portion of apron and then shall pull forward facing WEST behind stand number 3 for Startup, or as instructed by ATC.
- Simultaneous pushback from stands 1 to 3 not permitted.
- Startup will be approved only when the aircraft has reached behind Stand number 3 after pushback. Startup while pushing back not allowed.

b) STAND NUMBER 4 TO 8)

- Arriving aircraft shall vacate the runway via TWY A and turn left for powered in taxi to stands 4 to 8 and for taxi out aircraft will power taxi out and turn right for Taxiway A and further for RWY 06-24, or as instructed by ATC.
- When an aircraft is parked on Stand number 4, the other aircraft cannot taxi in to Stand number 5 to 8.
- Stand number 4 and 5 cannot be used simultaneously.
- If Stand number 6 and 7 are occupied, then aircraft on Stand number 4 cannot taxi out until Stand number 6 and 7 are vacant.

2. Take off Run Available for Departures from Intermediate Runway Position:

i) RWY 06:

a) From TWY A - 1088 M

b) From TWY C - 960M

ii) RWY 24:

a) From TWY A - 1662 M

b) From TWY C - 1790 M

iii) RWY 24:

a) From intermediate turn pad - 1988 M

3. Departures on RWY 24 from intermediate turn pad can be initiated by ATC with concurrence of pilot or as per request from pilots.

4. Aircraft landing on RWY 06 can use intermediate turn pad for making 180 degree turn for runway vacation. Critical aircraft A320.

5. No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

6.All ACFT after LDG RWY 24 and RWY 06 shall make 180 DEG turn using turn pad at the end of RWY for backtrack.

VAJB AD 2.21 NOISE ABATEMENT PROCEDURES

VAJB AD 2.22 FLIGHT PROCEDURES

VAJB AD 2.23 ADDITIONAL INFORMATION

VAJB AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aerodrome Chart (19 March 2026)
2 Aircraft Parking/Docking Chart (19 March 2026)
3 Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 06/24
4 Instrument Approach Chart - ILS or LOC RWY 24 (CAT A/B/C) (17 April 2025)
5 Instrument Approach Chart - VOR Procedure RWY 06 (17 April 2025)
6 Instrument Approach Chart - VOR Procedure RWY 24 (CAT A/B/C) (17 April 2025)
7 Instrument Approach Chart - RNP Y Procedure RWY 06 (17 April 2025)
8 Coding Table - RNP Y Procedure RWY 06
9 Instrument Approach Chart - RNP Z Procedure RWY 06 (17 April 2025)
10 Coding Table - RNP Z Procedure RWY 06 (11 JUNE 2026)
11 Coding Table - RNP Z Procedure RWY 06 (17 April 2025)

VAJB AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	**2**	**3**