AD 2. AERODROMES

VIJU AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIJU - JAMMU AIRPORT, JAMMU [INDIAN AIR FORCE]

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VIJU AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	324133N 0745022E East of runway, 170 DEG/1060 M from Dumbell 18.	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	Jammu Airfield is situated 224 DEG/08 KM from Jammu Tawi Railway Station	
3	Aerodrome elevation and reference temperature	965 FT / 36.0 DEG C	
4	Magnetic variation, date of information and annual change	2.30 DEG E (2020) /0.0167 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station Satwari, Jammu J &K -180003,	
		Telephone:	(91) 191-2437843
		Fax:	(91) 191-2454318 (91) 191-2453700
		AFS:	
		Email:	ats.viju@gov.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	NIL	

VIJU AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI: 0400 - 1230 UTC SAT, SUN and HOL: NIL
2	Custom and immigration	NIL
3	Health and sanitation	Available during AD Hours
4	AIS briefing office	NIL
5	ATS reporting office (ARO)	NIL
6	MET Briefing office	As per ATS
7	Air Traffic Service	SR to 1530 UTC
8	Fuelling	As per ATS
9	Handling	As per ATS with Prior coordination
10	Security	H24 (AAI/CISF)
11	De-icing	NIL
12	Remarks	NIL

VIJU AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Available
2	Fuel and Oil types	JET A1

3	Fuelling facilities and capacity	Static store 600KL (200KLX3), Bowser 3X16 KL & Bowser 1X11 KL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VIJU AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in the city
2	Restaurant(s) at or in the vicinity of aerodrome	At AD and in the city
3	Transportation possibilities	Taxis, Car hire service available at AD
4	Medical Facilities	First Aid at AD/Hospitals in the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: ATM Facility (J&K Bank) Post office: Available
6	Tourist office	Available at AD
7	Remarks	NIL

VIJU AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per AD Category
3	Capability for removal of disabled aircraft	By civil Operators
4	Remarks	ARFF by IAF

VIJU AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VIJU AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: Civil Apron Surface: Concrete Strength: PCN 64/R/B/W/T
2	Designation, width, surface and strength of taxiways	Designator: A Width: 23 M Surface: Asphalt Strength: PCN 61/F/C/W/T Designator: B Width: 23 M Surface: Asphalt Strength: PCN 70/F/C/W/T
3	Location and elevation of altimeter checkpoints	Not Available
4	Location of VOR checkpoints	Not Available
5	Position of INS checkpoints	Not Available
6	Remarks	1. Coordinates of suitability of aircraft stands: i. Stand Nr. 5: 324058.5N0745027.6E, A320 ii. Stand Nr. 6: 324100.9N0745028.7E, A320

VIJU AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	TWY & RWY marked and lighted
2	Runway and taxiway markings and lights	RWY Markings: Designation, THR, TDZ, Centre Line, RWY Edge and RWY End RWY Lights: THR, RWY Edge, RWY End, CAT I Approach lights for RWY 36 and Simple Approach Lights Runway 18 TWY Marking: Centre line, holding Positions, Edge. TWY Lights: Edge
3	Stop bars (if any)	Not available
4	Remarks	1. Steady green/red wing bar lights are provided on either side of threshold and runway end at a distance of not less than 1.5 M and 3 M between each light

VIJU AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
36/APCH 18/TKOF	TOWER	324216.7N 0745013.9E	960 FT	LGTD	TOWER
36/APCH 18/TKOF	TOWER	324439.0N 0745206.0E	1509 FT	LGTD	TOWER
36/APCH 18/TKOF	TOWER	324021.0N 0745026.0E	1086 FT	LGTD	TOWER
In circling area and at AD	BUILDING	324119.5N 0745030.0E	1065 FT	LGTD	BUILDING
In circling area and at AD	OTHER	324128.1N 0745022.7E	973 FT	LGTD	MAST
In circling area and at AD	BUILDING	324122.0N 0745022.6E	991 FT	LGTD	BUILDING
In circling area and at AD	ANTENNA	324118.5N 0745011.4E	968 FT	LGTD	Antenna
In circling area and at AD	OTHER	324114.4N 0745015.9E	976 FT	LGTD	Mast
In circling area and at AD	ANTENNA	324111.4N 0745041.5E	1036 FT	LGTD	Antenna
In circling area and at AD	ANTENNA	324108.1N 0745040.2E	959 FT	LGTD	Antenna
In circling area and at AD	ANTENNA	324101.5N 0745015.1E	966 FT	LGTD	Antenna
In circling area and at AD	ANTENNA	324142.5N 0745019.3E	972 FT	LGTD	Antenna
In circling area and at AD	ANTENNA	324059.2N 0745016.5E	966 FT	LGTD	Antenna
In circling area and at AD	BUILDING	324126.5N 0745011.4E	997 FT	LGTD	Building

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	ANTENNA	324058.1N 0745014.1E	997 FT	LGTD	Antenna Marked
In circling area and at AD	BUILDING	324119.7N 0745031.8E	994 FT	LGTD	Building
In circling area and at AD	TOWER	324135.0N 0745023.0E	1047 FT	LGTD	Tower
In circling area and at AD	TOWER	324104.0N 0745032.0E	1066 FT	LGTD	Tower
In circling area and at AD	OTHER	324053.0N 0745032.0E	1047 FT	LGTD	Mast
In circling area and at AD	TREE	324152.0N 0745012.0E	1053 FT	NO	Tree
In circling area and at AD	BUILDING	324111.0N 0745015.0E	1036 FT	NO	Building
In circling area and at AD	OTHER	324022.0N 0745019.0E	988 FT	LGTD	Overhead Tank
In circling area and at AD	OTHER	324145.0N 0745032.0E	1050 FT	LGTD	Overhead Tank
In circling area and at AD	OTHER	324131.0N 0745001.0E	1007 FT	LGTD	Overhead Tank
In circling area and at AD	OTHER	324118.0N 0745046.0E	1047 FT	LGTD	Overhead Tank
In circling area and at AD	ANTENNA	324119.0N 0745037.0E	1106 FT	LGTD	Antenna
In circling area and at AD	OTHER	324054.0N 0745036.0E	1056 FT	NO	Mast
In circling area and at AD	BUILDING	324120.0N 0745047.0E	1145 FT	LGTD	Building
In circling area and at AD	BUILDING	324109.0N 0745033.0E	1115 FT	NO	Building
In circling area and at AD	TOWER	324132.0N 0745031.0E	1073 FT	LGTD	Tower
In circling area and at AD	ANTENNA	324045.0N 0745037.0E	1047 FT	LGTD	Antenna
In circling area and at AD	ANTENNA	324147.0N 0745024.0E	1070 FT	LGTD	Antenna
In circling area and at AD	TOWER	324134.0N 0074534.0E	1099 FT	LGTD	Tower
In circling area and at AD	ANTENNA	324117.0N 0745014.0E	962 FT	LGTD	Antenna
In circling area and at AD	BUILDING	324125.0N 0745010.0E	994 FT	LGTD	Building
In circling area and at AD	BUILDING	324127.0N 0745013.0E	975 FT	NO	Building
In circling area and at AD	BUILDING	324130.0N 0745012.0E	982 FT	NO	Building
In circling area and at AD	BUILDING	324126.0N 0745010.0E	998 FT	LGTD	Building
In circling area and at AD	BUILDING	324130.8N 0745006.0E	1019 FT	NO	Building

VIJU AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Met Office, Air Force Station Jammu
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 Hrs Observation 12 Hrs Forecasting and as per requirement
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Office, Air Force Station Jammu 0600-1800 & 1800-1200 UTC
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend As per ICAO policy. Appended with METAR & SPECI
5	Information on how briefing and/or consultation is provided	Self-briefing display Available
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form/ English
7	Charts and other information displayed or available for briefing or consultation	Surface Charts, Upper Air Charts, Satellite Imagery, NWP products
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Automatic Weather Station
9	The air traffic services unit(s) provided with meteorological information	ATC Jammu (IAF)
10	Additional information, e.g. concerning any limitation of service.	RVR not available

VIJU AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
18	176.88 DEG	2438 x 45 M	80/F/C/W/T Asphalt	THR: 324207.00N 0745015.00E RWY END: 324047.77N 0745019.48E
36	356.88 DEG	2438 x 45 M	80/F/C/W/T Asphalt	THR: 324047.77N 0745019.48E RWY END: 324207.00N 0745015.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 957.0FT TDZ: 959.0FT		60 x 46 M	NIL	2558 x 135 M
THR: 950.0FT TDZ: 953.0FT		60 x 46 M	NIL	2558 x 135 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
61M x 90M		NIL	1. Surface of first 396 M of RWY 18 is Concrete. PCN: 80/R/B/W/T. 2. Runway strip of standard dimensions not available. 3. Turn pad of dimensions 135M X 45M available at dumbbell RWY 18 4.Resolution of RWY 18 THR coordinates is up to second
244M x 90M		NIL	1. Surface of turn pad RWY 36 is Concrete. PCN: 80/R/B/W/T. 2. Runway strip of standard dimensions not available. 3.Resolution of RWY 36 END coordinates is upto second

VIJU AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
18	2438	2438	2498	2438	
36	2438	2438	2498	2438	

VIJU AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
18	SALS 319 M LIH	Green AVBL	PAPI LEFT/3.00 DEG	
36	CAT I 840 M LIH	Green AVBL	PAPI LEFT/3.00 DEG	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	2438 M 60 M White LIH	Red	Red 60 M	NIL
NIL	2438 M 60 M White LIH	Red	Red 60 M	NIL

VIJU AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At ATC tower building EV 2.5 Sec W&G (24 FPM) As per ATS
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	58 M from eastern edge of RWY abeam ATC/Lighted
		Anemometer	Available, Unlighted
3	Taxiway edge and taxiway centre line lights;	Edge	Single aspect blue light/ 60M spacing.
		Centre Line	NIL
4	Secondary power supply including switch-over time;	DG Set/ 08-10 sec	
5	Remarks	NIL	

VIJU AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	NIL

VIJU AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: CTR - Area bounded by 324658.6N 0743956.5E along an arc of radius 10 NM centred at 324158.6N 0744956.5E to point where it meets international boundary.
2	Vertical limits	FL 120
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Jammu Tower, English
5	Transition altitude	11000 FT
6	Hours of applicability	As ATS

7	Remarks	NIL

VIJU AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
TWR	Jammu Tower	122.850 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	As ATS	NIL

VIJU AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	JJU	113.300 MHz CH80X	Refer NOTAM

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
324118.5N 0745011.3E	968 FT		1. Controlling Authority: AAI 2.. Collocated with DVOR

VIJU AD 2.20 LOCAL AERODROME REGULATIONS

1. All scheduled and non-scheduled operators to ensure strict compliance that no photography/videography is permitted of the airfield during enroute, landing, taxiing and take-off. Crew to make appropriate announcements before approach, landing as well as during boarding for passengers.
2. Airfield will not be available on 1st, 3rd and 5th Wednesday of every month for fixed wing aircraft operations from 0830 - 1530 UTC due planned maintenance activity.
3. Civil fixed wing operations are permitted only from 0300-1530 UTC on all days except above mentioned maintenance period.
4. First touchdown of civil flights at Jammu airfield shall be only at or after 0300 UTC.
5. All aircraft to line up following the turn pad taxi line marked by std yellow taxi line on Dumbbell 36 and carry out free 180 deg turn only.
6. No aircraft shall carry out pivotal turn or wheel locking turn on any part of runway or taxiway to avoid surface erosion.
7. All aircraft after landing will be backtracking on runway due to non-availability of parallel taxiway.
8. All turns at turn pad 36 and turn pad 18 shall be clockwise.

VIJU AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIJU AD 2.22 FLIGHT PROCEDURES

1. All arriving flights to descent with Northern Control up to altitude 12000 FT on regional QNH and report over JJU. Further descent/approach and landing with Jammu Tower.
2. All departing flights to climb overhead JJU to altitude 10000 FT on Jammu QNH and contact Northern Control for further climb

VIJU AD 2.23 ADDITIONAL INFORMATION

1. Taxiways on eastern side connecting to runway commencing from dumbbell 36 are designated as TWY A, TWY B, TWY C, TWY D, TWY E, TWY F. Taxiways on western side connecting runway is designated as TWY Z.
2. Link between TWY D and TWY F is designated as TWY P1.
3. Link between TWY F and TWY C is designated as TWY P2.
4. Link to the new dispersal on eastern side of runway is designated as TWY P3.
5. The taxiway from TWY C to intersection of TWY B/TWY C is designated as TWY P4
6. Pushback facility available for stand numbers 1, 2 and 3.
7. Markings of some obstructions in and around airfield may be non-standard.

8. Pilots to exercise caution for three antenna masts in NE direction, height 90 FT/90 FT/110 FT, distance 120 FT/295 FT/900 FT and bearing 008 DEG/015 DEG/099 DEG from ARP respectively.

9. All aircraft to avoid overflying the area bounded by 324002N 0745748E, 323947N 0745726E, 323920N 0745652E, 323935N 0745654E, location 105 DEG 10.5 KM from Jammu Airport. If overflying is unavoidable, no aircraft to overfly the explosive area at a height less than 900 M.

10. No aircraft to cross the sound barrier at an altitude/distance less than 900 M over/near explosive area.

11. Details of permanent obstructions around airfield:

i. Safety Bay: Distance from RWY edge 268 FT, Height 20 FT, Location near TWY E.

ii. Commutated Aerial Direction Finding (CADF) Hut on western side of runway:

Distance from RWY edge 180 FT, Height 25 FT, Location abeam DTGM 6 (Distance To Go Marker) for RWY 36

iii. CADF Antenna: Distance from RWY Edge 145 FT, Height 15 FT, Location abeam DTGM 6 for RWY36.

iv. DVOR: Distance from RWY Edge 450 FT, Height 30 FT, Location near DTGM 5 for RWY36.

v. Glide Path: Distance from RWY Edge 275 FT, Height 80 FT, Location near DTGM 7 for RWY36.

vi. Peer Baba Mazar: Location western side of runway at a distance of 155 FT from RWY Edge and distance from THR RWY 36 1700 FT. Height scaffolding 25 FT. Construction unmarked and unlighted. A road running along Peer Baba Mazar falling at a distance of 135 FT from RWY Edge. Pilots to exercise caution during landing and take-off and operating on runway.

vii. A permanent hanger in the cleared zone on eastern side of runway near MM. Distance from RWY Edge 260 FT and height 20.5 FT.

viii. Tawi Field Firing Range active throughout the year, during day and night.

Location 280 DEG, 2 NM from ARP. All pilots to exercise caution while landing and take-off.

ix. Pilots to exercise caution for communication towers of height 40 M erected at following locations:

a) 324017N 0744842E

b) 324016N 0745018E

c) 323958N 0744958E

d) 323958N 0745021E.

VIJU AD 2.24 CHARTS RELATED TO AN AERODROME

1. Instrument Approach Chart – CAT I ILS RWY 36 (29 October 2026)
2. VOR Procedure RWY 36 (29 October 2026)

VIJU AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3