AD 2. AERODROMES

VIJO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIJO - JODHPUR AIRPORT, JODHPUR [INDIAN AIR FORCE]

NOTE: AERONAUTICAL DATA AND AERONAUTICAL INFORMATION OF THIS AIP SUPPLEMENT IS PROVIDED BY INDIAN AIR FORCE.

VIJO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	261526N 0730306E ARP is located North of runway near TWY K.	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	5km South-East of Jodhpur railway Junction	
3	Aerodrome elevation and reference temperature	712 FT / 41.4 DEG C	
4	Magnetic variation, date of information and annual change	NIL	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station, Ratanada Jodhpur Rajasthan - 342011,	
		Telephone:	91 291 2514004
		Fax:	(91) 291 2512250
		AFS:	
		Email:	jjoats@nic.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Joint User Airfield (Defence & Civil Ops)	

VIJO AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	Indian Air Force (Air Traffic Services) Airport Authority of India (Civil terminal & Apron)
2	Custom and immigration	Not Available
3	Health and sanitation	Available during AD Hours
4	AIS briefing office	H24
5	ATS reporting office (ARO)	H24
6	MET Briefing office	H24
7	Air Traffic Service	HJ
8	Fuelling	During AD Hours
9	Handling	0330-1130 UTC (0900-1700 IST)
10	Security	CISF (H24) for guarding the terminal including one shift for flight operation.
11	De-icing	Not Available
12	Remarks	NIL

VIJO AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Available with Air India (Limited & Manual)
2	Fuel and Oil types	JET A1 (ATF) By IOC

3	Fuelling facilities and capacity	Total capacity (48000 ltrs) 03 Bowsers – 48000(16000 x 3)
4	De-icing facilities	Not Available
5	Hangar space for visiting aircraft	Not Available
6	Repair facilities for visiting aircraft	Not Available
7	Remarks	NIL

VIJO AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Taj Vivanta (+91-291-2439700) Park Plaza (+91-291-25105000) Chandra Inn (+91-291-2671997) Rajputana Palace (+91-291-2671672)
2	Restaurant(s) at or in the vicinity of aerodrome	Basic facilities at Terminal. (Snacks Bar available) Restaurants located in the vicinity.
3	Transportation possibilities	Taxi and Car hire services available at terminal
4	Medical Facilities	First Aid available at terminal. Hospitals available in the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available in the city Post office: Available in the city.
6	Tourist office	Available at Terminal
7	Remarks	NIL

VIJO AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	CAT 7 within AD HRS
2	Rescue equipment	Available as per category
3	Capability for removal of disabled aircraft	A coordinated plan for removal of disabled aircraft exists. Disabled aircraft removal to be ensured by Operator in coordination with local authorities.
4	Remarks	NIL

VIJO AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VIJO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart.

2	Designation, width, surface and strength of taxiways	Designator: PTT Width: 23 M Surface: Concrete Strength: Designator: TWY B1 Width: 23 M Surface: Concrete Strength: PCN 57/R/C/X/T Designator: TWY C1 Width: 23 M Surface: Concrete Strength: PCN 57/R/C/X/T Designator: TWY C2 Width: 23 M Surface: Asphalt Strength: PCN 91/F/C/X/T Designator: TWY E2 Width: 23 M Surface: Concrete Strength: Designator: TWY H Width: 15 Surface: Concrete Strength: Designator: TWY K Width: 23 M Surface: Asphalt Strength: PCN 91/F/C/X/T Designator: TWY K1 Width: 23 M Surface: Concrete Strength: PCN 57/R/C/X/T
3	Location and elevation of altimeter checkpoints	Not established
4	Location of VOR checkpoints	On TWY K1 and TWY C2
5	Position of INS checkpoints	Not Available
6	Remarks	Refer Aircraft Parking/Docking Chart.

VIJO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxing guidance signs at all Intersections with TWY and RWY and at all holding positions
2	Runway and taxiway markings and lights	RWY Markings : RWY Centreline, Sidestripe, RWY Designation,Threshold, Touch Down Zone, Aiming Point RWY Lights : Centreline, Touchdown Zone, Edge RWY Marking : Centreline, Edge on all taxiways except on parallel Taxitrack where the centreline is a broken line to meet operational requirement of IAF, Intermediate holding position TWY Lights : Edge Lights

3	Stop bars (if any)	Available on TWY K1, C2, B1, C and on PTT abeam GP antenna
4	Remarks	NIL

VIJO AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
23/APCH 05/TKOF	OTHER	261758.0N 0730454.0E	837 FT	LGTD	Wireless Mast in Jodhpur Cantonment
23/APCH 05/TKOF	TOWER	262306.0N 0730405.0E	853 FT	LGTD	Microwave Tower along road
23/APCH 05/TKOF	BUILDING	261608.0N 0730338.0E	774 FT	LGTD	Building
23/APCH 05/TKOF	TANK	261639.0N 0730423.0E	776 FT	NO	Tank
23/APCH 05/TKOF	TOWER	262016.0N 0730835.0E	1024 FT	LGTD	Microwave Tower
23/TKOF 05/APCH	OTHER	261419.0N 0730141.0E	794 FT	LGTD	South Mast
23/TKOF 05/APCH	TOWER	261117.0N 0725624.0E	853 FT	LGTD	Microwave Tower
23/TKOF 05/APCH	TOWER	261401.0N 0730042.0E	906 FT	LGTD	Microwave Tower
23/TKOF 05/APCH	TANK	261442.0N 0730159.0E	797 FT	LGTD	Tank
23/TKOF 05/APCH	TOWER	261312.0N 0725721.0E	892 FT	LGTD	Microwave Tower
23/TKOF 05/APCH	TANK	261501.0N 0730216.0E	787 FT	LGTD	Tank
23/TKOF 05/APCH	TOWER	261437.0N 0730053.0E	837 FT	LGTD	Microwave Tower near Bhagat ki Kothi
In circling area and at AD	TOWER	261241.0N 0730352.0E	837 FT	LGTD	Tower at Jhalamand
In circling area and at AD	OTHER	261510.0N 0730135.0E	827 FT	LGTD	Mast
In circling area and at AD	TOWER	261624.0N 0735956.0E	1542 FT	LGTD	TV Tower
In circling area and at AD	BUILDING	261533.0N 0730248.0E	794 FT	LGTD	Building
In circling area and at AD	TOWER	261752.0N 0730108.0E	1286 FT	LGTD	P & T Tower
In circling area and at AD	TOWER	261944.0N 0725933.0E	1099 FT	LGTD	Microwave Tower
In circling area and at AD	OTHER	261747.0N 0730101.0E	1283 FT	LGTD	Fort Temple
In circling area and at AD	TOWER	261819.0N 0730113.0E	1394 FT	LGTD	Microwave Tower
In circling area and at AD	TOWER	261729.0N 0725738.0E	1361 FT	LGTD	Tower
In circling area and at AD	ANTENNA	261547.0N 0730249.0E	798 FT	LGTD	Antenna
In circling area and at AD	ANTENNA	261548.0N 0730231.0E	817 FT	LGTD	Antenna

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	TOWER	261741.0N 0730221.0E	902 FT	LGTD	Microwave Tower
In circling area and at AD	OTHER	261721.0N 0730353.0E	915 FT	LGTD	Wireless Mast
In circling area and at AD	BUILDING	261652.0N 0730250.0E	1056 FT	LGTD	Building
In circling area and at AD	TOWER	262306.0N 0730405.0E	1017 FT	LGTD	Microwave Tower
In circling area and at AD	OTHER	264030.0N 0730357.0E	1713 FT	LGTD	Wind Mill Suzlon Near Basni
In circling area and at AD	TOWER	261624.0N 0725935.0E	1542 FT	LGTD	Microwave Tower (TV) on Hill Top

VIJO AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Met Office, Jodhpur
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Office, Jodhpur 12 Hrs
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend At interval of 1/2 Hr
5	Information on how briefing and/or consultation is provided	Verbal and telephonic briefings can be obtained on telephone No 7891695988
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular and chart Form English
7	Charts and other information displayed or available for briefing or consultation	Sea Level Charts, Upper Air Charts, Satellite cloud imagery, Doppler Weather Radar Imagery, NWP Product of CAT and Icing, Local Forecast, Current Weather, Astronomical and climatological Data
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Doppler Weather Radar , DSRRG, DDRWE, Automatic Weather Station & RVR is available
9	The air traffic services unit(s) provided with meteorological information	Jodhpur ATC
10	Additional information, e.g. concerning any limitation of service.	NIL

VIJO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
05	45.00 DEG	2744 x 45 M	81/F/C/X/T Asphalt	THR: 261433.00N 0730218.00E RWY END: 261536.00N 0730328.00E
23	225.00 DEG	2744 x 45 M	81/F/C/X/T Asphalt	THR: 261536.00N 0730328.00E RWY END: 261433.00N 0730218.00E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 707.0FT TDZ: 705.3FT	0.50%	196 x 45 M	NIL	3331 x 300 M
THR: 700.0FT TDZ: 700.2FT	0.50%	273 x 45 M	NIL	3331 x 300 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
NIL	Arresting system not available for civil aircraft operations		1. Strength and surface of First and Last 518M OF RWY 05/23 IS 62/R/C/X/T, CONCRETE 2. RESA not available due arrester barrier installed at both ends of RWY.
NIL	Arresting system not available for civil aircraft operations		1. Strength and surface of First and Last 518M OF RWY 05/23 IS 62/R/C/X/T, CONCRETE 2. RESA not available due arrester barrier installed at both ends of RWY.

VIJO AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
05	2744	2744	2940	2744	
23	2744	2744	3017	2744	

VIJO AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
05	CAT II 540 M LIH	Green	PAPI RIGHT/3.00 DEG	900 M
23	SALS 300 M LIH	Green	PAPI RIGHT/3.00 DEG	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2744 M 15 M LIH White	2744 M 60 M White LIH	Red	Red 195 M	1. RWY Centreline lights of variable white from the threshold to the point 900 m from the runway end; alternate red and variable white from 900 m to 300 m from the runway end; and red from 300 m to the runway end.
2744 M 15 M LIH White	2744 M 60 M White LIH	Red	Red 195	1. RWY Centreline lights of variable white from the threshold to the point 900 m from the runway end; alternate red and variable white from 900 m to 300 m from the runway end; and red from 300 m to the runway end.

VIJO AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At tower building, Alternate White & Green Flashes, 24 flashes/ min. During IMC & Night Ops
		IBN	Not Available
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Near Taxiway C2 (Lighted)
		Anemometer	In met observatory near main ATC building
3	Taxiway edge and taxiway centre line lights;	Edge	All TWY
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary power supply to all lighting at AD. Switch over time: 9 sec	
5	Remarks	NIL	

VIJO AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Helipad 1 261537N 0730300E	Helipad 2 261533N 0730304E
2	TLOF and/or FATO area elevation:	217 M	217 M
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	75 M X 30 M	75 M X 23M
4	True bearings of FATO;	045.00 DEG 225.00 DEG	045.00 DEG 225.00 DEG
5	Declared distances available	75M, 75M, 75M, 75M	75M, 75M, 75M, 75M
6	Approach and FATO lighting;	NIL	NIL
7	Remarks	NIL	NIL

VIJO AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: Circular area centered on 261501N 0730158E within a 25NM radius.
2	Vertical limits	FL 100
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Jodhpur Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	HJ
7	Remarks	Controlling Unit: IAF Jodhpur TEL: +91-291-2512250

VIJO AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
TWR	Jodhpur Tower	122.400 MHZ	
ATIS	Jodhpur Information	116.200 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
		NIL
	HJ	NIL

VIJO AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 05 CAT II	IJDH	108.900 MHz	HJ
GP 05	IJDH	329.300 MHz	HJ
DME ILS 05	IJDH	CH26X	
VOR/DME	JDP	116.200 MHz CH109X	HO

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
261541.0N 0730333.0E			1. Controlling Authority: Indian Air Force
261436.0N 0730229.0E			
261436.0N 0730230.0E			1. Controlling Authority: Indian Air Force 2. Collocated with GP RWY 05
261458.2N 0730235.7E	738 FT		1. Controlling Authority: Indian Air Force 2. Coverage 150 NM.

VIJO AD 2.20 LOCAL AERODROME REGULATIONS

Field Ammunition Depot (FAD) is located on a radial/distance of 040deg/14km from ARP. Overflying the FAD below 3800ft (3000ft AGL) is not permitted.

VIJO AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VIJO AD 2.22 FLIGHT PROCEDURES

NIL

VIJO AD 2.23 ADDITIONAL INFORMATION

1. Operation Readiness Platform is available at the beginning of the runway for parking of fighter aircraft prior to take off. All scheduled and non-scheduled aircraft toexercise caution while lining up to ensure jet wake is not directed towards fighter aircrafts to avoid any foreign object damage.

2. Non-scheduled operators to take prior clearance from Airport Director for parking and from ATC for Operations.

3. All scheduled and non-scheduled aircraft to carryout 180 DEG turn only on rigid portion of runway.

i. Ground markings on parallel taxitrack south of RWY do not conform to standard taxi markings as per Annex 14. TWY centreline marked with broken white stripes 3m long and 0.3m wide with the longitudinal gap of 3m between stripes.

VIJO AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aircraft Parking/Docking Chart
2. Instrument Approach Chart – CAT I ILS RWY 05(12 June 2025)
3. Instrument Approach Chart – VOR Z RWY 05 (12 June 2025)
4. Instrument Approach Chart – VOR Y RWY 05 (12 June 2025)
5. Instrument Approach Chart – VOR RWY 23 (19 Mar 2026)

VIJO AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3