AD 2. AERODROMES

VAKE AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VAKE - KANDLA AIRPORT, KANDLA

VAKE AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	230644N 0700602E MAG. BRG. 52.05 DEG / 762 M FROM PHYSICAL EXTREMITY OF RWY 05.	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	325 Degree, 10KM from Gandhidham Railway station	
3	Aerodrome elevation and reference temperature	97 FT / 39.0 DEG C	
4	Magnetic variation, date of information and annual change	0.00 DEG (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority of India, Kandla Airport, Anjar, Pin-370110 Kutch, Gujarat.,	
		Telephone:	(91) 2836269401 919825235079
		Fax:	(91) 2836269402
		AFS:	
		Email:	apd_vake@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Elevation in EGM08	

VAKE AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI : 0400-1230 UTC (0930-1800 IST) SAT, SUN+HOL: Nil
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	NIL
5	ATS reporting office (ARO)	NIL
6	MET Briefing office	As ATS
7	Air Traffic Service	Consult Current NOTAM for ATS HR.
8	Fuelling	AVBL
9	Handling	As ATS
10	Security	As ATS
11	De-icing	NIL
12	Remarks	1. 24 HR prior notice for non-scheduled flights. 2. The ATS APV hourly RWY TFC handling capacity is as FLW: MAX number of ARR and DEP -12 MAX number of ARR only -06 (The minimum spacing between two successive arrivals is 10 min) MAX number of DEP only-10(The minimum spacing between two successive DEP is 06 min)

VAKE AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	Capacity - 56 Kilo Litres along with allied facility using refueller R-241 (16KL) and R-06 (10KL) and storage tank KAN-01 (30KL)
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VAKE AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city
2	Restaurant(s) at or in the vicinity of aerodrome	In the city
3	Transportation possibilities	Taxis from city to AD.
4	Medical Facilities	First aid at AD. Hospital in city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the city. Post office: In the city
6	Tourist office	In the city.
7	Remarks	NIL

VAKE AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-6
2	Rescue equipment	Available as per category.
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is ATR-72. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director, Kandla Airport Office: 02836-269401, Mob - 9825235079 Email: apd_vake@aai.aero
4	Remarks	NIL

VAKE AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VAKE AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Designator: A Width: 15 M Surface: Asphalt Strength: PCN 18/F/C/W/T Length: 195M

3	Location and elevation of altimeter checkpoints	Location: At apron Elevation: 90FT
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	**1. Coordinates of RWY Holding Position:** TWY Coordinates Elevation (FT) TWY A 230647.49N 0700609.14E 95 **2. Coordinates of RWY & Taxi Intersection:** TWY Coordinates Elevation (FT) TWY A 230649.39N 0700607.43E 97 **3. All elevations in EGM08**

VAKE AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiing guidance provided on R/T. TWY guidelines AVBL at APRON.
2	Runway and taxiway markings and lights	RWY Markings: THR, Centreline, Designation, TDZ, Edge, Turnpad, END, RWY Lighting: RWY Edge, END, THR, Turnpad, TWY Markings: Centreline, Holding Positions, Edge, TWY Lighting: Edge.
3	Stop bars (if any)	NIL
4	Remarks	Night landing facility not available.

VAKE AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM08)	Marking/LGT	Remarks
23/TKOF 05/APCH	OTHER	230627.5N 0700539.2E	98 FT	NO	Approach Light
23/TKOF 05/APCH	OTHER	230630.7N 0700535.4E	113 FT	NO	Mobile Road Traffic (Road Elev. 29.3 M. + 5.0 M. Traffic Ht.)
23/TKOF 05/APCH	OTHER	230623.1N 0700541.5E	112 FT	NO	Mobile Road Traffic (Road Elev. 29.2 M. + 5.0 M. Traffic Ht.)
23/TKOF 05/APCH	FENCE	230629.5N 0700533.4E	107 FT	NO	Airport Boundary Wall With F/T
23/TKOF 05/APCH	FENCE	230621.8N 0700540.2E	106 FT	NO	Airport Boundary Wall With F/T
23/TKOF 05/APCH	OTHER	230602.8N 0700518.5E	171 FT	NO	Shed
23/TKOF 05/APCH	OTHER	230601.7N 0700519.4E	229 FT	LGTD	Light On Factory Shed (Shed Top 69.3 M.)
23/TKOF 05/APCH	STACK	230603.4N 0700517.9E	182 FT	NO	Chimney
23/APCH 05/TKOF	BUILDING	230702.4N 0700633.1E	123 FT	NO	Building
23/APCH 05/TKOF	BUILDING	230703.8N 0700634.7E	127 FT	NO	Sintex Tank On Building (Building Top 37.7 M.)
23/APCH 05/TKOF	OTHER	230658.5N 0700627.0E	108 FT	NO	Mobile Road Traffic (Road Elev. 27.9 M. + 5.0 M. Traffic Ht.)
23/APCH 05/TKOF	FENCE	230707.6N 0700622.5E	106 FT	NO	Airport Boundary Wall With F/T
23/APCH 05/TKOF	BUILDING	230713.2N 0700637.9E	136 FT	NO	Sintex Tank On Building (Building Top 38.2 M.)
In circling area and at AD	FENCE	230632.5N 0700537.3E	109 FT	NO	Airport Boundary Wall With F/T
In circling area and at AD	OTHER	230702.4N 0700507.1E	248 FT	NO	Shed (Welspun)
In circling area and at AD	STACK	230703.3N 0700459.0E	483 FT	NO	Chimney (Welspun)

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM08)	Marking/LGT	Remarks
In circling area and at AD	STACK	230706.2N 0700454.6E	428 FT	NO	Chimney
In circling area and at AD	OTHER	230701.0N 0700457.9E	304 FT	NO	Factory Shed
In circling area and at AD	STACK	230703.9N 0700455.2E	317 FT	NO	Chimney On Shed (Shed Top 93.5 M.)
In circling area and at AD	STACK	230650.6N 0700454.7E	297 FT	NO	Chimney
In circling area and at AD	STACK	230659.6N 0700441.7E	277 FT	NO	Chimney (Welspun)
In circling area and at AD	STACK	230658.0N 0700441.5E	304 FT	NO	Chimney (Welspun)
In circling area and at AD	STACK	230656.9N 0700442.0E	280 FT	NO	Chimney (Welspun)
In circling area and at AD	STACK	230657.4N 0700441.2E	265 FT	NO	Chimney (Welspun)
In circling area and at AD	STACK	230556.8N 0700529.6E	246 FT	NO	Chimney
In circling area and at AD	STACK	230651.6N 0700425.0E	399 FT	NO	Chimney
In circling area and at AD	STACK	230651.3N 0700424.1E	397 FT	NO	Chimney
In circling area and at AD	STACK	230621.5N 0700444.2E	271 FT	NO	Chimney
In circling area and at AD	OTHER	230619.7N 0700444.7E	268 FT	NO	Factory Shed
In circling area and at AD	STACK	230539.8N 0700500.1E	238 FT	NO	Chimney
In circling area and at AD	TOWER	230548.5N 0700417.8E	258 FT	NO	Tower
In circling area and at AD	OTHER	230650.1N 0700558.2E	130 FT	NO	Bushes On Hillock
In circling area and at AD	FENCE	230656.6N 0700608.3E	108 FT	NO	Airport Boundary Wall With F/T
In circling area and at AD	FENCE	230705.7N 0700620.0E	106 FT	NO	Airport Boundary Wall With F/T
In circling area and at AD	TOWER	230728.2N 0700641.2E	237 FT	NO	Mobile Tower
In circling area and at AD	POLE	230639.4N 0700602.2E	101 FT	NO	Light Pole
In circling area and at AD	OTHER	230653.2N 0700601.1E	133 FT	NO	Bushes On Hillock
In circling area and at AD	GATE	230652.3N 0700602.8E	108 FT	NO	Gate
In circling area and at AD	TOWER	230546.9N 0700722.3E	247 FT	NO	Tower
In circling area and at AD	OTHER	230541.1N 0700634.9E	249 FT	NO	Mast
In circling area and at AD	OTHER	230824.7N 0700551.4E	278 FT	NO	Mast
In circling area and at AD	OTHER	230719.4N 0700445.4E	254 FT	NO	Mast

VAKE AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Kandla, Class 3
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	0600-1800 IST
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Ahmedabad 9 and 24 Hr
4	Availability of the trend forecast for the aerodrome and interval of issuance	NIL
5	Information on how briefing and/or consultation is provided	NIL
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form English
7	Charts and other information displayed or available for briefing or consultation	NIL
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Barometer/DIWE/Thermometer Anemometer/Wind Wane.
9	The air traffic services unit(s) provided with meteorological information	Kandla ATC and ACS
10	Additional information, e.g. concerning any limitation of service.	Documentation provided A/R

VAKE AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
05	50.04 DEG	1524 x 30 M	21/F/C/W/T Asphalt	THR: 230628.79N 0700540.84E RWY END: 230700.60N 0700621.89E
23	230.04 DEG	1524 x 30 M	21/F/C/W/T Asphalt	THR: 230700.60N 0700621.89E RWY END: 230628.79N 0700540.84E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 97.0FT TDZ: 97.0FT				1644 x 300 M
THR: 97.0FT TDZ: 97.0FT				1644 x 300 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
90M x 90M			Elevation in EGM08
90M x 90M			Elevation in EGM08

VAKE AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
05	1524	1524	1524	1524	
23	1524	1524	1524	1524	

VAKE AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
05	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG	
23	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	1524 M 60 M White LIH	Red		NIL
	1524 M 60 M White LIH	Red		NIL

VAKE AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building, FLG W&G EV2SEC
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	200M East of ARP,LGTD
		Anemometer	Anemometer AVBL on TWR building. Unlighted.

3	Taxiway edge and taxiway centre line lights;	Edge	AVBL
		Centre Line	NIL
4	Secondary power supply including switch-over time;	To all LGT, Switch over time-15 SEC	
5	Remarks	Apron edge LGT and Flood LGT	

VAKE AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	--
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	--
4	True bearings of FATO;	--
5	Declared distances available	--
6	Approach and FATO lighting;	--
7	Remarks	--

VAKE AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	Not established
2	Vertical limits	Not established
3	Airspace classification	G
4	Call sign and language(s) of the air traffic services unit providing service;	Kandla Tower, English
5	Transition altitude	4000 FT
6	Hours of applicability	
7	Remarks	ACFT to coordinate for climb/descend with Bhuj/Jamnagar ATC.

VAKE AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
TWR	Kandla Tower	118.600 MHZ	
TWR	Kandla Tower	124.350 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	MAIN
	HO	BACKUP

VAKE AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
NDB	KD	335 kHz	HO
DME	KND	CH124X	HO

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
230641.0N 0700612.9E			
230641.3N 0700613.9E	119 FT		1. Vertical datum: EGM08

VAKE AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VAKE AD 2.21 NOISE ABATEMENT PROCEDURES

VAKE AD 2.22 FLIGHT PROCEDURES

VAKE AD 2.23 ADDITIONAL INFORMATION

VAKE AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart
2. Aircraft Parking/Docking Chart
3. Aerodrome Obstacle Chart – (Operating Limitations) Type A RWY 05
4. Aerodrome Obstacle Chart – (Operating Limitations) Type A RWY 23
5. Instrument Approach Chart - RNP Z Procedure RWY 05 (CAT A/B) (LPV Only) (08 August 2024)
6. Tabular Description - RNP Z Procedure RWY 05 (CAT A/B) (08 August 2024)

7. FAS Data Block Table - RNP Z Procedure RWY 05 (08 August 2024)
8. Instrument Approach Chart - RNP Z Procedure RWY 23 (CAT A/B) (LPV Only) (08 August 2024)
9. Tabular Description - RNP Z Procedure RWY 23 (08 August 2024)
10. FAS Data Block Table - RNP Z Procedure RWY 23 (08 August 2024)
11. Instrument Approach Chart - RNP Y Procedure RWY 05 (CAT A/B) (17 April 2025)
12. Tabular Description - RNP Y Procedure RWY 05 (17 April 2025)
13. Instrument Approach Chart - RNP Y Procedure RWY 23 (CAT A/B) (17 April 2025)
14. Tabular Description - RNP Y Procedure RWY 23 (17 April 2025)

VAKE AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3