AD 2. AERODROMES

VOKN AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOKN - KANNUR INTERNATIONAL AIRPORT, MATTANNUR, KANNUR

VOKN AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	115457N 0753245E 257.78 DEG /1611 M from beginning of RWY 07. ARP Elevation: 332.20 FT	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	3.3 KM west from Mattannur Bus Stand.	
3	Aerodrome elevation and reference temperature	344 FT / 35.0 DEG C	
4	Magnetic variation, date of information and annual change	2.00 DEG W (2010) /0.0333 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Chief Operations Officer, Kannur International Airport Ltd. Anjarakandy Road, Mattannur, Kannur Dist, Kerala-670702,	
		Telephone:	(91) 490 2481000 -1333
		Fax:	(91) 490 2482464
		AFS:	-----
		Email:	coo@kannurairport.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	i. All Elevations in EGM 08. ii. Website: kannurairport.aero	

VOKN AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	H24
2	Custom and immigration	H24
3	Health and sanitation	H24
4	AIS briefing office	H24
5	ATS reporting office (ARO)	H24
6	MET Briefing office	H24
7	Air Traffic Service	H24
8	Fuelling	H24
9	Handling	H24
10	Security	H24
11	De-icing	NIL
12	Remarks	NIL

VOKN AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	AVBL
2	Fuel and Oil types	JET A1

3	Fuelling facilities and capacity	BKFFPL (BPCL-KIAL Fuel Farm Private Ltd.); 06 Refuelling Bowsers (4 nos. 16000 Ltrs, & 01 nos. 25000 Ltrs, 01 nos. 18000 Ltrs) A/G ATF Tank Capacity: 2 X 450 KL U/G ATF Tank Capacity: 2 X 45 KL. Contact No: +91- 9188481450
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VOKN AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city. Nearest at 6 KM.
2	Restaurant(s) at or in the vicinity of aerodrome	At AD and in the city.
3	Transportation possibilities	Buses, Taxies available
4	Medical Facilities	First Aid at Aerodrome. Hospitals in the city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: AVBL Post office: AVBL
6	Tourist office	At AD.
7	Remarks	NIL

VOKN AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7 Scalable to CAT 9 on 4 HR PN.
2	Rescue equipment	Available as per Category.
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is B777 - 300ER. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Chief Operating Officer Tel: 0490 2481000 Extn- 1333 Email: coo@kannurairport.aero
4	Remarks	NIL

VOKN AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Sweeping machines
2	Clearance priorities	Runway 07/25 and associated taxiways
3	Remarks	No snow fall

VOKN AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer AD 2.23 Additional Information Point 6: Taxiways.
3	Location and elevation of altimeter checkpoints	Location: Available at all parking stands Elevation: Available at all parking stands

4	Location of VOR checkpoints	Established on TWY A1 and A6 115442.24 N 0753154.25 E (TWY A1) 115510.82 N 0753310.52 E (TWY A6)
5	Position of INS checkpoints	NIL
6	Remarks	For other details see AD 2.23

VOKN AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	All stands are provided with stand identification signs, Aircraft ID markings on ground and Aircraft Stand lead in lines. Taxiing guidance signage's are provided on all TWY intersections and straight sections as per ICAO Annex 14. Visual Docking Guidance System available on Stand 12L, 12, 12R, 13L, 13, 13R, 14L, 14, 14R Marshalling guidance available for parking in assigned stands through Authorized Ground Handling Agents (GHA)
2	Runway and taxiway markings and lights	RWY: Markings: RWY Designation, THR, TDZ, Centre line, Aiming point, Side stripe, Transverse Strip Lights: THR, Centre line, Edge & End lights TWY: Marking: Edge, Centre line & RWY Holding positions, Intermediate TWY holding positions, Enhanced Taxiway Centerline Lights: Only Edge lights (For TWY A3 (RET) RETIL & Centerline lights are also available)
3	Stop bars (if any)	Not Available
4	Remarks	Illuminated Signage provided for RWY, TWY, APRON and stand guidance. DTGM is provided on left shoulder of RWY 07 and 25 indicating distance to go in feet at an interval of 1000 feet (indicating '1' for 1000 feet, '2' for 2000 feet and so on). All Parking Stands have been provided with illuminated stand identification boards with respective coordinates and elevation displayed. FOLLOW ME vehicles will be provided if required.

VOKN AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
25/APCH 07/TKOF	OTHER	115649.9N 0753611.9E	610 FT	NIL	Cell Phone Mast
In circling area and at AD	ANTENNA	115426.9N 0753834.8E	1699 FT	LGTD	Antenna

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	ANTENNA	115427.1N 0753835.0E	1692 FT	NIL	Antenna
In circling area and at AD	ANTENNA	115426.5N 0753835.5E	1707 FT	NIL	Antenna
In circling area and at AD	OTHER	115619.0N 0753347.5E	723 FT	Marked/LGTD	Cell Phone Mast
In circling area and at AD	OTHER	115618.4N 0753335.1E	572 FT	Marked/LGTD	Cell Phone Mast
In circling area and at AD	OTHER	115618.7N 0753333.9E	566 FT	Marked/LGTD	Cell Phone Mast
In circling area and at AD	OTHER	115620.0N 0753332.4E	594 FT	Marked/LGTD	Cell Phone Mast
In circling area and at AD	OTHER	115617.1N 0753209.6E	514 FT	Marked/LGTD	Cell Phone Mast
In circling area and at AD	OTHER	115508.2N 0753017.6E	555 FT	Marked/LGTD	Cell Phone Mast
In circling area and at AD	OTHER	115447.6N 0753014.8E	504 FT	NIL	Cell Phone Mast
In circling area and at AD	TOWER	115628.8N 0753340.4E	512 FT	NIL	H.T. Tower
In circling area and at AD	TOWER	115625.4N 0753316.8E	496 FT	NIL	H.T. Tower
In circling area and at AD	TOWER	115631.4N 0753358.1E	517 FT	NIL	H.T. Tower
In circling area and at AD	BUILDING	115623.6N 0753212.0E	499 FT	Marked	Reena Readymix Building Top
In circling area and at AD	TREE	115505.8N 0753530.7E	565 FT	NIL	Tree on Hill
In circling area and at AD	TREE	115506.0N 0753532.2E	546 FT	NIL	Tree on Hill
In circling area and at AD	TREE	115625.0N 0753210.5E	521 FT	NIL	Tree on Hill
In circling area and at AD	NATURAL HIGHPOINT	115421.4N 0753834.3E	1547 FT	LGTD	Purulimala Hill Top
In circling area and at AD	NATURAL HIGHPOINT	115505.9N 0753530.7E	522 FT	LGTD	Edavelikal Hill Top
In circling area and at AD	OTHER	115624.8N 0753212.2E	525 FT	Marked	Chimney
In circling area and at AD	OTHER	115624.7N 0753212.2E	525 FT	Marked	Chimney
In circling area and at AD	OTHER	115624.4N 0753212.3E	522 FT	Marked	Chimney
In circling area and at AD	OTHER	115423.0N 0753834.8E	1596 FT	NIL	Tree
In circling area and at AD	OTHER	115424.2N 0753834.8E	1621 FT	NIL	Tree
In circling area and at AD	OTHER	115421.1N 0753835.3E	1570 FT	NIL	Tree

VOKN AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	AMO Thiruvananthapuram

2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Aerodrome MET office Trivandrum(VOTV) TAFs 9 hourly valid 0000-0900, 0300-1200, 0600-1500, 0900-1800, 1200-2100, 1500-2400, 1800-0300 & 2100-0600 UTC and 30 hourly TAFs valid 0000-0600 of next day, 0600-1200 of next day, 1200-1800 of next day & 1800-2400 UTC of next day
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend METAR every 30 Min and SPECI as and when issued
5	Information on how briefing and/or consultation is provided	Online briefing for pilots. Met briefing for ATS personnel from MBR
6	Types of flight documentation supplied and language(s) used in flight documentation	Charts of IMD activities and various types of cloud picture
7	Charts and other information displayed or available for briefing or consultation	Analyzed surface and upper air chart, Wind/Temp and Significant Weather Chart
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Using DWR products of DWR KOCHI. Satellite imageries through IMD website
9	The air traffic services unit(s) provided with meteorological information	KIAL ATC and ACS
10	Additional information, e.g. concerning any limitation of service.	Drishti AWMS at RWY 25 and PC based DCWIS at RWY 07 available. Instrumental RVR/Present WX Detector(PWD) system available for RWY 07.

VOKN AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCR) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
07	69.05 DEG	3050 x 45 M	Asphalt	THR: 115445.63N 0753152.53E RWY END: 115520.94N 0753326.77E
25	249.05 DEG	3050 x 45 M	Asphalt	THR: 115520.94N 0753326.77E RWY END: 115445.63N 0753152.53E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 344.1FT TDZ: 343.6FT		NIL		3170 x 280 M
THR: 316.9FT TDZ: 334.4FT		NIL		3170 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
240M x 90M		AVBL	1. PCR & SFC RWY 07: 0-193M: 1175/R/A/W/T, Concrete 193M-2857M: 1021/F/A/W/T, Asphalt 2857M-3050M: 1175/R/A/W/T, Concrete 2. Geoid Model: EGM-08
240M x 90M		AVBL	1. PCR & SFC RWY 07: 0-193M: 1175/R/A/W/T, Concrete 193M-2857M: 1021/F/A/W/T, Asphalt 2857M-3050M: 1175/R/A/W/T, Concrete 2. Geoid Model: EGM-08

VOKN AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
07	3050	3050	3050	3050	
25	3050	3050	3050	3050	

VOKN AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
07	SALS 300 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (20.34M)	
25	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (20.34M)	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
3050 M 30 M LIH	3050 M 60 M LIH	Red		Turn Pad Edge Lights-Blue available.
3050 M 30 M LIH	3050 M 60 M LIH	Red		Turn Pad Edge Lights-Blue available.

VOKN AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	- Top of the Control Tower - Green and White Flashing Lights, 20 - 30 flashes per minute During Watch Hours
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Illuminated landing 'T' provided between RWY and TWY B, at west of TWY A4
		Anemometer	Located at MET park of RWY 07 and RWY 25
3	Taxiway edge and taxiway centre line lights;	Edge	Elevated Blue lights placed within 3M from TWY edge. Lateral distance between lights are 60M on straight sections and on curved portion varies on the radius of the curve.
		Centre Line	Inset unidirectional Lights with a gap of 15M on RET (TWY – A3) available.
4	Secondary power supply including switch-over time;	UPS back up is available for all critical circuits of Aeronautical Ground Lights except for TWY edge lights. Secondary Power Supply, DG set available with 15 Sec Switch over Time	
5	Remarks	NIL	

VOKN AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	No separate landing area for Helicopters
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	Helicopters to land on runway 07/25

VOKN AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 115457N 0753245E within a 10NM radius.
2	Vertical limits	4500 FT AMSL
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Kannur Tower, English
5	Transition altitude	10000 FT
6	Hours of applicability	H24
7	Remarks	Kannur Approach Control Unit is combined with Kannur Aerodrome Control Tower.

VOKN AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available	Logon address, as appropriate	Hours of operation	Remarks
1	2	3	4	5	6	7
APP	Kannur Tower	121.175 MHZ			H24	1.Main FREQ 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
APP	Kannur Tower	121.975 MHZ			H24	1.Backup FREQ 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
TWR	Kannur Tower	118.050 MHZ			H24	NIL
TWR	Kannur Tower	121.975 MHZ			H24	BACK UP FREQUENCY
ATIS	Kannur Information	128.800 MHZ			H24	NIL
ALRS	Emergency	121.500 MHZ			H24	NIL

VOKN AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 25 CAT I	IKAN	108.900 MHz	H24
GP 25		329.300 MHz	H24
DME ILS 25	IKAN	CH26X	H24
DVOR/DME	KNR	112.600 MHz CH73X	H24

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
115442.1N 0753143.1E			
115520.9N 0753315.3E			
115521.0N 0753315.2E	335 FT		Elevations in EGM 08
115457.1N 0753201.9E	368 FT		Vertical datum: EGM08

VOKN AD 2.20 LOCAL AERODROME REGULATIONS

1. AIRCRAFT STANDS:

i. Aircraft Stands from 1 to 8 are Code-C stands & stand No.9 to 14 are of MARS (Multiple Aircraft Ramp System) type and the pattern of Taxi Lead-in-lines require nose wheel steering while taxiing into the stand.
ii. Pilots should exercise caution when manoeuvring on the apron due to the proximity of other aircraft, ground staff and equipment. Engine power should be restricted to the minimum required to reduce the adverse effect of jet blast.
iii. All Stands 01 to 14 are towards south side of Apron and are power in push back.

Stand No.	No Parking	Stand No.	No Parking	Stand No.	No Parking	Stand No.	No Parking
9	9L & 9R	10	10L & 10R	11	11L & 11R	12	12L & 12R
13	13L & 13R	14	14L & 14R	9L & 9R	9	10L &10R	10
11L &11R	11	12L &12R	12	13L &13R	13	14L &14R	14

3. PUSHBACK PROCEDURES

i. All aircraft shall contact Kannur Tower for push back and start up clearance.

ii. All code A/B/C/ D/E aircraft shall push back on Aircraft Stand Taxi Lanes only.

iii. ATC shall mention the direction of push back (e.g., Push back and start up approved, facing East on Taxilane).

iv. The push back separation requirement on apron incorporates jet blast clearance (minimum 250M behind code D/E aircraft and 80M behind code A/B/C aircraft). All stands in the apron are power in / push back.

v. Power out is not permitted from any stand.

vi. Ensuring correct pushback on Taxilane as per instructions received from ATC is the responsibility of Airline operator and Apron Control. All aircraft shall be pushed back up to the specified push back position marking (i.e., the nose wheel of the aircraft will be at the tug disconnection point marked on Aircraft Stand Taxilane) corresponding to the stand from which push back was commenced unless otherwise instructed by ATC.

vii. All aircraft parked on stand 01, 02, 03, shall push back facing east for startup and taxi via TWY C7 irrespective of runway in use.

viii. All aircraft on stand 14L,14 and 14R shall push back abeam stand 14L facing
west to taxi out via TWY C4.

4. TAXIING PROCEDURES

i. Advanced Visual Docking Guidance System (AVDGS) is available only in MARS Contact Stands: 12L, 12, 12R, 13L, 13, 13R, 14L, 14, 14R. For remaining Stands: 01 to 11R, Marshalling service will be provided by Ground Handling Agent.

ii. Apron is served with one aircraft stand taxi lane.

iii. Aircraft stand taxi lanes on 9L, 9R, 10L, 10R, 11L, 11R, 12L, 12R, 13L, 13R, 14L, 14R are broken lines painted in Yellow and are to be used by Code C type of aircraft or aircrafts with wingspan lesser than 36m.

iv. Aircraft stand taxi lane 9, 10, 11, 12, 13 and 14 are continuous lines painted in Yellow and can be used for aircrafts up to Code E Type.

v. An aircraft vacating runway via exit taxiways A3 and from Taxiway A1 is not simultaneously clear of Runway and parallel taxiway B.

vi. Rapid Exit Taxiways (RET) A3 shall not be used for departures even though RGL are provided. (No entry sign boards are provided at this point).

vii. 180-degree turn is allowed for Code A/B/C/D/E aircrafts at turn pads on the RWY THR 07 and 25.

5. TAXING OUT FROM APRON

Aircraft Pushing back in to the Taxi Lane can proceed via Taxiway C4, C 5, C 6, C 7 as per instructions from ATC.

6. TAXIING INTO APRON

All aircrafts proceeding to Aircraft Parking Stands have to follow Aircraft stand Taxi lane after entering Apron via TWY C4, C5, C6 and C 7.

7. MOVEMENT OF CODE- E AIRCRAFT:

For Code E type of Aircrafts, caution should be exercised and minimum power to be used at the intersection of Apron Taxi Lane with TWY C4, C5, C6, C7.

8. JET BLAST ABATEMENT PROCEDURES

Jet Blast prone areas on Main Apron: Apron is linked with Taxiway C4, C5, C6 and C7. The Jet blast study conducted on the critical aircraft for VOKN, B777-300ER, shows the following observations.

TAXI ROUTES	AIRCRAFT POSITION	JET BLAST PRONE AREA
Aircraft exiting Apron via TWY C7	**Taxiing – Out**	**Stands:1&2**
Aircraft entering Apron Via TWY C7 for Apron Taxi Lane	**Taxiing – In**	**East Service Road**
Aircraft exiting Apron via TWY C6	**Taxiing – Out**	**Stands : 9L &9, 10L, 10**
Aircraft exiting Apron via TWY C5	**Taxiing – Out**	**Stands : 13,13L,12R, 12, 12L, 11R,11**
Aircraft exiting Apron via TWY C4	**Taxiing – Out**	**Stands 14L, 14, 14R**

9. APRON AREA

Code D/E type aircraft are not permitted to stop while Taxiing on these Jet Blast Prone Areas to avoid jet blast damage to vehicles and aircrafts parked on the above mentioned stands. If for any reason B777-300ER type of aircraft stops on these Jet Blast Prone Areas further taxi should be continued only when the affected stands are vacant and ground movement is regulated. All Jet Blast Prone Areas are well marked with apron markings to provide adequate information for all vehicles.

10. ARRIVING AIRCRAFT

Aircraft can normally vacate the runway via designated exit taxiways as per ATC Instructions.
RWY 07 – TWY A4 or A6 to TWY B
RWY 25 – TWY A3 or A1 to TWY B

11. DEPARTING AIRCRAFT

Aircraft can normally enter the runway for departure via the following taxiways :
RWY 07 – TWY A1
RWY 25 – TWY A6

VOKN AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VOKN AD 2.22 FLIGHT PROCEDURES

NIL

VOKN AD 2.23 ADDITIONAL INFORMATION

1. Calicut airport/ (VOCL) exists at a proximity of 51.72 NM South of Kannur International Airport &
2. Mangaluru International Airport/ (VOML) exists at a proximity of 72 NM North of Kannur International Airport

AIRPORT DESIGNATION	LOCATION	RWY ORIENTATION	Distance from VOKN
VOCL	CALICUT AIRPORT	10/28	51.72 NM south of VOKN RWY
VOML	MANGALURU INTERNATIONAL AIRPORT	06/24	72 NM North of VOKN RWY

3. DISTANCE OF TAXIWAYS FROM RUNWAY THRESHOLD

TAXIWAY	FROM THRESHOLD	DISTANCE
A1	RWY 25	3050 M (10006 ft)
A3	RWY 25	2272 M (7454 ft)
A4	RWY 07	1873 M (6145 ft)
A6	RWY 07	2480 M (8136 ft)

4. GROUND HANDLING ARRANGEMENTS

All operators, operating to/from Kannur International Airport shall employ the services of ground handling agent authorized by KIAL. Operators should contact Kannur International Airport for further information on ground handling arrangements. The two Ground Handling Agents are M/s Celebi Airport Services India Pvt Ltd and M/S Air India Air Transport Services Ltd and their contact details are as follows.

General Manager – Air India Air Transport Services Ltd (AIATSL)

Telephone Number: +91 44 22561553

Mobile No.: +91 9444050784

Station Manager - Celebi Airport Services India Pvt Ltd

Mobile Number: +91 9711860606

5. AIRCRAFT STANDS:

Surface: CONCRETE

Strength: PCR 1175/R/A/W/T

Isolated Aircraft Parking Position (IAPP)

Surface: Asphalt

Strength: PCR 1021/F/A/W/T

STAND NO	LATITUDE	LONGITUDE	ELEVATION	SUITABLE FOR
1	115501.817N	0753313.995E	102.28 M (335.55 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D

2	115501.348N	0753312.744E	102.31 M (335.67 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
3	115500.879N	0753311.492E	102.33 M (335.72 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
4	115500.410N	0753310.240E	102.32 M (335.68 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
5	115459.942N	0753308.989E	102.27 M (335.52 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
6	115459.475N	0753307.737E	102.27 M (335.53 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
7	115459.005N	0753306.486E	102.32 M (335.70 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
8	115458.537N	07533 05.235E	102.32 M (335.70 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
9L	115458.414N	0753303.336E	102.15 M (335.15 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
9	115457.299N	0753303.051E	102.45 M (336.11 ft)	A300, A330-200/300, A340-200 to 600, AN12, MD11, B747-200 to 400, B757-200/300, B767-200 to 400, B777 -200/300, B787
9R	115457.430N	0753302.284E	102.34 M (335.75 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
10L	115457.476N	0753300.834E	102.24 M (335.42 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D

10	115456.361N	0753300.548E	102.53 M (336.37 ft)	A300, A330-200/300, A340-200 to 600, B747-200 to 400, B757-200/300, B767-200 to 400, B777 -200/300, B787, A318, A319, A320, A321, B717, B737 all series
10R	115456.492N	0753259.782E	102.37 M (335.87 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
11L	115456.537N	0753258.332E	102.30 M (335.63 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
11	115455.423N	0753258.046E	102.56 M (336.48 ft)	A300, A330-200/300, A340-200 to 600, AN12, MD11, B747-200 to 400, B757-200/300, B767-200 to 400, B777 -200/300, B787
11R	115455.554N	0753257.278E	102.48 M (336.22 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
12L	115455.594N	0753255.723E	102.35 M (335.79 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
12	115454.440N	0753255.392E	102.51 M (336.32 ft)	A300, A330-200/300, A340-200 to 600, AN12, MD11, B747-200 to 400, B757-200/300, B767-200 to 400, B777 -200/300, B787
12R	115454.219N	0753254.822E	102.53 M (336.37 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
13L	115454.582N	0753253.021E	102.35 M (335.78 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D

13	115453.418N	0753252.666E	102.58 M (336.53 ft)	A300, A330-200/300, A340-200 to 600, AN12, MD11, B747-200 to 400, B757-200/300, B767-200 to 400, B777 -200/300, B787
13R	1154' 53.267N	0753252.093E	102.53 M (336.39 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
14L	115453.644N	0753250.519E	102.38 M (335.88 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D
14	115452.480N	0753250.163E	102.55 M (336.45 ft)	A300, A330-200/300, A340-200 to 600, AN12, MD11, B747-200 to 400, B757-200/300, B767-200 to 400, B777 -200/300, B787
14R	115452.330N	0753249.594E	102.55 M (336.45 ft)	AT42, AT72, A318, A319, A320, A321, B717, B737 all series, CRJ200, ERJ170, 190, DH8D

6. TAXIWAYS				
Designation	Width (M)	Surface	PCR	Remarks
A1	23	Asphalt	1021/F/A/W/T	Link TWY Connecting RWY to Parallel TWY
A3	23	Asphalt	1021/F/A/W/T	Rapid Exit TWY (25)
A4	23	Asphalt	1021F/A/W/T	Link TWY Connecting RWY to Parallel TWY
A6	23	Asphalt	1021/F/A/W/T	Link TWY Connecting RWY to Parallel TWY
B	23	Asphalt	1021/F/A/W/T	Parallel TWY
C4	23	Asphalt	1021/F/A/W/T	Link TWY to Apron Taxi lane
C5	23	Asphalt	1021/F/A/W/T	Link TWY to Apron Taxi lane
C6	23	Asphalt	1021/F/A/W/T	Link TWY to Apron Taxi lane
C7	23	Asphalt	1021/F/A/W/T	Link TWY to Apron Taxi lane

D	23	Asphalt	1021/F/A/W/T	Link TWY Connecting RWY to Isolation Parking Bay

VOKN AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aerodrome Chart (17 April 2025)
2 Aerodrome Chart- Hot Spot (22 January 2026)
3 Aircraft Parking/Docking Chart (17 April 2025)
4 Aircraft Parking/Docking Chart - Isolation Aircraft Parking Position (17 April 2025)
5 Aerodrome Obstacle Chart Type- A (Operating Limitations) RWY 07/25 (22 January 2026)
6 ILS Procedure RWY 25
7 VOR Procedure RWY 07
8 VOR Procedure RWY 25
9 RNP Y Procedure RWY 07
10 Coding Table - RNP Y Procedure RWY 07
11 Coding Table - RNP Y Procedure RWY 07

VOKN AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	**2**	**3**