AD 2. AERODROMES

VAKS AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VAKS - KESHOD AIRPORT, KESHOD

VAKS AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	211854N 0701609E M. Brg. 059.75 DEG 462 M From physical extremity RWY 05	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	060 DEG, 3KM from Keshod railway station.	
3	Aerodrome elevation and reference temperature	168 FT / 32.0 DEG C	
4	Magnetic variation, date of information and annual change	0.36 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Airports Authority of India, Keshod Airport, Keshod - 362220.	
		Telephone:	(91) 2871299109 (91) 2871299105 (91) 2871299107
		Fax:	(91) 2871299105
		AFS:	VAKSYDYX
		Email:	apd_vaks@aai.aero
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	1. Aerodrome elevation in EGM 08 2. Aerodrome Reference Code: 3C (Day VFR OPS)	

VAKS AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	WED, FRI, SUN BTN 1110 UTC to 1235 UTC (Watch Hours)
2	Custom and immigration	NIL
3	Health and sanitation	As ATS
4	AIS briefing office	NIL
5	ATS reporting office (ARO)	NIL
6	MET Briefing office	As ATS
7	Air Traffic Service	Consult NOTAM for current ATS HR.
8	Fuelling	Provided by IOCL
9	Handling	NIL
10	Security	As ATS
11	De-icing	NIL
12	Remarks	i. Outside of ATS hours, services are available O/R with 48 HR PN to AD. ii. The ATS approved hourly runway traffic handling capacity is as follows: Maximum number of arrival and departure -12 (The minimum spacing between two successive arrivals shall be more than five minutes) Maximum number of arrivals only -6 Maximum number of departures only -10

VAKS AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1
3	Fuelling facilities and capacity	Refueller Capacity – 11KL. Storage – 16KL. 02 No. of Refuellers available. 01 Refueller is used as storage.
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VAKS AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the city.
2	Restaurant(s) at or in the vicinity of aerodrome	In the city.
3	Transportation possibilities	Taxis
4	Medical Facilities	First aid at AD. Primary health center in the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the city Post office: In the city
6	Tourist office	NIL
7	Remarks	NIL

VAKS AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-5
2	Rescue equipment	AVBL. as per category
3	Capability for removal of disabled aircraft	1. The Critical Aircraft of Keshod Aiprort is ATR-72. 2. Primary Responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact ‘Aerodrome Coordinator for Disabled Aircraft Removal Operations ‘for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Aerodrome Coordinator: Airport Director Email: apd_vaks @aai.aero Contact No.: 9429686790/02871-299109
4	Remarks	NIL

VAKS AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VAKS AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: APRON Surface: Concrete Strength: PCN 16/R/D/W/T

2	Designation, width, surface and strength of taxiways	Designator: TWY A Width: 15 M Surface: Asphalt Strength: PCN 21/F/C/W/T
3	Location and elevation of altimeter checkpoints	Location: Taxiway A Holding position Elevation: 163 FT (EGM 08)
4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	1. COORDINATES OF TAXI HOLDING POSITION TWY A: 211901.423N 0701609.698E, ELEV 163 FT 2. COORDINATES OF RWY/TWY INTERSECTION POINT TWY A: 211859.477N 0701611.421E, ELEV 166 FT 3. Geoid Model: EGM 08

VAKS AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Guidelines at apron
2	Runway and taxiway markings and lights	RWY Markings: THR, RWY Centerline, RWY Designation, RWY Edge, TDZ RWY Lights: RWY Edge lights, RWY End lights and Unidirectional Inset Type light for reduction in TORA/LDA of RWY 05. Blue lights provided at the end of RWY 05 for Taxi guidance. TWY Marking: TWY Centerline, Holding Positions at all TWY/ RWY intersections TWY Lights: Taxiway Edge lights
3	Stop bars (if any)	NIL
4	Remarks	Taxing guidance provided on R/T

VAKS AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
23/APCH 05/TKOF	TREE	211920.7N 0701634.2E	189 FT	NIL	Group of Trees
23/APCH 05/TKOF	TREE	211920.7N 0701640.4E	199 FT	NIL	Group of Trees
23/APCH 05/TKOF	TREE	211924.1N 0701642.2E	202 FT	NIL	Group of Trees
23/APCH 05/TKOF	TREE	211919.1N 0701640.4E	190 FT	NIL	Group of Tree
23/APCH 05/TKOF	OTHER	211917.5N 0701634.0E	178 FT	NIL	Mobile Road Traffic
23/APCH 05/TKOF	OTHER	211919.4N 0701632.1E	175 FT	NIL	Mobile Road Traffic
23/APCH 05/TKOF	OTHER	211915.5N 0701635.7E	178 FT	NIL	Mobile Road Traffic
In circling area and at AD	OTHER	211850.4N 0701558.1E	170 FT	LGTD	PAPI
In circling area and at AD	OTHER	211910.8N 0701627.6E	168 FT	LGTD	PAPI
In circling area and at AD	TREE	211913.1N 0701634.1E	191 FT	NIL	Group of Trees
In circling area and at AD	OTHER	211911.6N 0701620.7E	198 FT	LGTD	MET Antenna Light
In circling area and at AD	TREE	211910.5N 0701631.9E	188 FT	NIL	Neem Tree
In circling area and at AD	TREE	211912.6N 0701633.6E	187 FT	NIL	Neem Tree
In circling area and at AD	OTHER	211845.1N 0701553.5E	168 FT	NIL	App Light
In circling area and at AD	TREE	211912.2N 0701633.0E	190 FT	NIL	Group of Trees
In circling area and at AD	TREE	211919.9N 0701631.2E	183 FT	NIL	Group of Trees

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	TREE	211920.7N 0701632.7E	183 FT	NIL	Trees
In circling area and at AD	TREE	211918.5N 0701640.5E	192 FT	NIL	Group of Tree
In circling area and at AD	OTHER	211741.0N 0701502.3E	320 FT	LGTD	BSNL Cell Phone Mast Light
In circling area and at AD	OTHER	211745.3N 0701704.6E	352 FT	LGTD	Cell Phone Mast Light
In circling area and at AD	BUILDING	211756.1N 0701735.8E	447 FT	LGTD	Mazar on Hill Top

VAKS AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Keshod
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As per Watch Hours of ATS
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Ahmedabad 9HR
4	Availability of the trend forecast for the aerodrome and interval of issuance	As per Watch Hours, METAR issued every 30 mins
5	Information on how briefing and/or consultation is provided	Briefing is available on request by user.
6	Types of flight documentation supplied and language(s) used in flight documentation	Tabular Form English
7	Charts and other information displayed or available for briefing or consultation	NIL
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	NIL
9	The air traffic services unit(s) provided with meteorological information	Keshod ATC AND ACS
10	Additional information, e.g. concerning any limitation of service.	Documentation provided A/R.

VAKS AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
05	49.51 DEG	1371 x 45 M	30/F/B/W/T Asphalt	THR: 211846.38N 0701555.06E RWY END: 211915.32N 0701631.23E
23	229.51 DEG	1371 x 45 M	30/F/B/W/T Asphalt	THR: 211915.32N 0701631.23E RWY END: 211846.38N 0701555.06E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 167.0FT TDZ: 168.0FT	-0.08%	NIL	NIL	1491 x 150 M
THR: 162.0FT TDZ: 167.0FT	0.08%	NIL	NIL	1491 x 150 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
90M x 90M			Elevations in EGM 08
90M x 90M			Elevations in EGM 08

VAKS AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
05	1321	1321	1321	1321	
23	1371	1371	1371	1371	

VAKS AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
05	SALS 420 M LIH	Green	PAPI LEFT/3.00 DEG MEHT (28.64FT)	NIL
23	NIL	Green	PAPI LEFT/3.00 DEG MEHT (27.36FT)	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	1371 M 58 M White LIH	Red		NIL
	1371 M 58 M White LIH	Red		NIL

VAKS AD 2.15 OTHER LIGHTING SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	ON TWR, Alternate red and green flashes operational during ops.
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	300M W of ARP,Unlighted
		Anemometer	WDI is Lighted
3	Taxiway edge and taxiway centre line lights;	Edge	Available
		Centre Line	NIL
4	Secondary power supply including switch-over time;	Secondary Power supply to all lighting at AD. Switch over time :15 SEC	
5	Remarks	NIL	

VAKS AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	--
2	TLOF and/or FATO area elevation:	--
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	--
4	True bearings of FATO;	--
5	Declared distances available	--
6	Approach and FATO lighting;	--
7	Remarks	--

VAKS AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 212802N 0702359E; 213402N 0702859E; 213202N 0703459E; 211903N 0703959E; 205703N 0701559E; 210803N 0701759E then along the clockwise arc of a circle of 11NM radius centred on 211905N 0701542E to point of origin.
2	Vertical limits	FL 105
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Keshod Tower, English
5	Transition altitude	6000 FT
6	Hours of applicability	HO
7	Remarks	1.Keshod Approach Control Unit is combined with Keshod Aerodrome Control Tower. 2.ACFT to coordinate with Mumbai OCC for climb and descend.

VAKS AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
APP	Keshod Tower	118.300 MHZ	
APP	Keshod Tower	122.300 MHZ	
TWR	Keshod Tower	118.300 MHZ	
TWR	Keshod Tower	122.300 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	HO	1.Backup FREQ 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1.Main FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower
	As ATS	Backup Frequency
	As ATS	NIL

VAKS AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
NDB	KS	282 kHz	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
211905.1N 0701541.9E			

VAKS AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VAKS AD 2.21 NOISE ABATEMENT PROCEDURES

VAKS AD 2.22 FLIGHT PROCEDURES

VAKS AD 2.23 ADDITIONAL INFORMATION

All fixed wing ACFT to make 180 DEG turn only at the dumbell of RWY without locking wheels.

VAKS AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart (08 August 2024)
2. Aircraft Parking Docking Chart (08 August 2024)
3. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 05 (08 August 2024)
4. Aerodrome Obstacle Chart Type A (Operating Limitations) RWY 23 (08 August 2024)
5. Aerodrome Obstacle Chart Type B ((08 August 2024)
6. NDB RWY23 (CAT A/B) (05 DEC 2019)

VAKS AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3