AD 2. AERODROMES

VILH AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VILH - LEH AIRPORT, LEH

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VILH AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	340807N 0773243E 1.4 KM FROM DB 07, SOUTH OF RUNWAY NEAR MIDDLE MARKER	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	235 DEG/5 KM SW OF LEH CITY	
3	Aerodrome elevation and reference temperature	10839 FT / DEG C	
4	Magnetic variation, date of information and annual change	2.00 DEG E/ NIL	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station Leh UT Ladakh Pin-194101,	
		Telephone:	(91) 1982 260508 (91) 9622998772
		Fax:	(91) 1982 260508
		AFS:	
		Email:	
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	Joint User Airfield (Defence & Civil Ops)	

VILH AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	HJ
2	Custom and immigration	Not Available
3	Health and sanitation	By Respective Airline Operators and AAI
4	AIS briefing office	NOT AVAILABLE
5	ATS reporting office (ARO)	BY IAF
6	MET Briefing office	BY IAF
7	Air Traffic Service	By IAF
8	Fuelling	By IOC
9	Handling	By respective Airlines
10	Security	By UT Ladakh Police and CISF
11	De-icing	Not Available
12	Remarks	Nil

VILH AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Limited, Manual by respective airlines
2	Fuel and Oil types	ATF(K-50), Oil- Nil
3	Fuelling facilities and capacity	Indian Oil Corporation/ 9 KL Bowser

4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	Nil
6	Repair facilities for visiting aircraft	Nil
7	Remarks	Nil

VILH AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	In the City
2	Restaurant(s) at or in the vicinity of aerodrome	AT LEH CITY
3	Transportation possibilities	Taxi, buses from AD
4	Medical Facilities	FIRST AID AT AIRPORT TERMINAL, HOSPITAL AT LEH CITY
5	Bank and post office at or in the vicinity of aerodrome	Banks: AT LEH CITY
6	Tourist office	AT LEH CITY
7	Remarks	Nil

VILH AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-7
2	Rescue equipment	Available as per AD Category
3	Capability for removal of disabled aircraft	WITH RESPECTIVE AIRLINE IN CO-ORDINATION WITH IAF
4	Remarks	Nil

VILH AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Snow Clearance is carried out manually and with snow clearance vehicles
2	Clearance priorities	IAF manoeuvering /movement area snow clearance in civil apron with AAI
3	Remarks	NIL

VILH AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: Civil Apron Surface: Concrete Strength: PCN 50/R/C/W/U Dimension: 110M X 75M

2	Designation, width, surface and strength of taxiways	1. TWY A LENGTH: 50M WIDTH: 30M WITH NON LOAD BEARING(NLB) OF 3M ON EITHER SIDE SURFACE: REGID STRENGTH: TO BE EVALUATED AND NOTIFIED 2. TWY B LENGTH: 600M WIDTH: 30M WITH NON LOAD BEARING(NLB) OF 3M ON EITHER SIDE SURFACE: REGID STRENGTH: TO BE EVALUATED AND NOTIFIED 3. TWY B1 LENGTH: 60M WIDTH: 30M WITH NON LOAD BEARING(NLB) OF 3M ON EITHER SIDE SFC: REGID STRENGTH: TO BE EVALUATED AND NOTIFIED 4. TWY C LENGTH: 276M WIDTH: 30M WITH NON LOAD BEARING(NLB) OF 3M ON EITHER SIDE SURFACE: ASPHALT IV) TO BE EVALUATED AND NOTIFIED ALL TWY ARE COMPATIBLE FOR CODE D ACFT.
3	Location and elevation of altimeter checkpoints	AT CIVIL APRON
4	Location of VOR checkpoints	VOR CHECK POINT AVBL AT INTERMEDIATE TAXI HOLDING TWY B AND TWY C.
5	Position of INS checkpoints	NIL
6	Remarks	1. Stand No. 1: Elev. 10856 FT, 50/R/B/W/T 2. Stand No. 2: Elev. 10858 FT, 50/R/B/W/T

VILH AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxing guidance signs at all Intersections with TWY and RWY and at all holding positions
2	Runway and taxiway markings and lights	RWY Markings: Runway threshold, Runway designation, Runway centreline, Runway edge line, Runway touchdown zone marking, transverse stripe for RWY 25 Lights: Mobile Airfield Lighting System(MAFLS) FOR INITIAL 7000 FT OF RUNWAY 07. TWY MARKING: RUNWAY HOLDING MARKING, INTERMEDIATE HOLDING MARKING AND CENTRE LINE MARKING LIGHTS: NOT LIGHTED
3	Stop bars (if any)	NIL
4	Remarks	DTGMs installed on both shoulders of RWY at 50 ft from edge of RWY to demarcate every 1000ft of length available.

VILH AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
25/TKOF 07/APCH	NATURAL HIGHPOINT	340735.0N 0773138.0E	10788 FT	LGTD	Gompa Hill

VILH AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Air Force Met Office
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	24 Hrs Observation & 12 Hrs Forecast
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Air Force Met
4	Availability of the trend forecast for the aerodrome and interval of issuance	12 Hrs
5	Information on how briefing and/or consultation is provided	Trend type landing forecast during watch period half hourly
6	Types of flight documentation supplied and language(s) used in flight documentation	Provided
7	Charts and other information displayed or available for briefing or consultation	Tabular Form English
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Internet, Pocket Weather Tracker, DMDD, DDRWE, DSRRG, AWS, LDS, CEILOMETERS
9	The air traffic services unit(s) provided with meteorological information	ATC Leh
10	Additional information, e.g. concerning any limitation of service.	S, U, P & W

VILH AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
07	69.00 DEG	2774 x 45 M	97/F/C/X/T Asphalt	THR: 340753.62N 0773150.99E RWY END:
25	249.00 DEG	2774 x 45 M	97/F/C/X/T Asphalt	THR: 340823.00N 0773333.00E RWY END:

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 10571.0FT TDZ:	0.92%	NIL	NIL	3537 x 150 M
THR: 10839.0FT TDZ:		367 x 45 M	367 x 45	3537 x 150 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
NIL	NIL	NIL	1. True Bearing is provided up to nearest degree 2. Resolution of THR and RWY END Coordinates is up to Seconds 3. Elevation of THR and TDZ is up to nearest feet
NIL	NIL	NIL	1. True Bearing is provided up to nearest degree 2. Resolution of THR and RWY END Coordinates is up to Seconds 3. Elevation of THR and TDZ is up to nearest feet

VILH AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
07	NIL	NIL	NIL	2774	1. Take-off not permitted due to natural obstruction on take-off path. 2. RWY 07 is available only for landing. 3. TORA, TODA, ASDA not usable.
25	2774	3141	3141	NIL	1. RWY 25 is available only for departure. 2. PRE THRESHOLD AREA FOR RWY 25 IS AVAILABLE FOR DEPARTURE. 3. LDA NOT APPLICABLE 4. DECLARED DISTANCES FROM TWY 'A' INCLUDING PRE THRESHOLD AREA (+396 M): TORA: 3170 M TODA: 3537 M ASDA: 3537 M 5. DECLARED DISTANCES FROM TWY 'B' INCLUDING PRE THRESHOLD AREA (+145M) : TORA: 2919 M TODA: 3286 M ASDA: 3286 M

VILH AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
07	NIL	MAFLS LIGHTS AVAILABLE AS THRESHOLD LIGHTS	PAPI RIGHT/3.00 DEG	NIL
25	NIL	NIL	NIL	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
NIL	2134 M 60 M	NIL	NIL	1.MAFLS AVAILABLE TILL INITIAL 7000 FT FOR RUNWAY 07. 2.VARIABLE INTENSITY WHITE LIGHTS.
NIL	NIL	NIL	NIL	NIL

VILH AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On top of ATC tower 24 FPM White and Green Flashes As ATS Hrs
		IBN	Not Available
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Near ATC Tower. Lighted
		Anemometer	NIL
3	Taxiway edge and taxiway centre line lights;	Edge	
		Centre Line	
4	Secondary power supply including switch-over time;	DG Set, Change over time – 05 Minutes. 62.5 KVA	
5	Remarks	Nil	

VILH AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Centre Of Touchdown: 340758N0773223E
2	TLOF and/or FATO area elevation:	Not Available
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	300M ON APPROACH AND DEPARTURE PATH
4	True bearings of FATO;	069/249
5	Declared distances available	Not Available
6	Approach and FATO lighting;	Not Available
7	Remarks	Not Available

VILH AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	Not established
2	Vertical limits	Not established
3	Airspace classification	G
4	Call sign and language(s) of the air traffic services unit providing service;	Leh Tower, English
5	Transition altitude	24000 FT
6	Hours of applicability	HJ
7	Remarks	NIL

VILH AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	**2**	**3**	**4**
TWR	Leh Tower	120.400 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	**6**	**7**
	As ATS	NIL

VILH AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	LEH	116.900 MHz CH116X	HJ

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
340757.5N 0773230.3E	10840 FT		1. Controlling Authority: Indian Air Force 2. Limited range due to mountainous terrain. 3. Operational Hours for DVOR may be extended to meet operational requirement subject to prior intimation and coordination with IAF.

VILH AD 2.20 LOCAL AERODROME REGULATIONS

1.All landings on Runway 07 and take-offs from Runway 25 only.

2.All aircraft within 25 NM of Leh, to descend while being in visual contact with terrain below 24000 ft due mountainous terrain.

VILH AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VILH AD 2.22 FLIGHT PROCEDURES

NIL

VILH AD 2.23 ADDITIONAL INFORMATION

1. Range limitation of 25NM for UHF/VHF RT equipment due to permanent obstructions.

2 Distance Between RUNWAY EDGE AND PTT EDGE IS 50 M..

3. One non-standard temporary wind direction indicator installed on right side of approach for RWY 07 on Gompa Hill for additional wind information for all the aircraft on base leg and final approach for RWY 07 only. However, wind may vary at touchdown for RWY 07 due to topographical condition.

4. PERMANENT OBSTRUCTION :

.4.1 ARRESTER NET IS INSTALLED AT A DISTANCE OF 59 M BEHIND THRESHOLD 07 ALONGWITH ITS ASSEMBLY INSTRUMENTS.

4.2 ARRESTER BARRIER HUT, DISTANCE FROM RUNWAY EDGE 57 M, HEIGHT 3.5 M ON SOUTHERN SHOULDER ABEAM THRESHOLD 07.

4.3 RHAG ARRESTER BARRIER IS INSTALLED BOTH SIDES OF RWY AT A DISTANCE OF 304M FROM 07 THRESHOLD AND AT DISTANCE OF 1.6 M FROM RWY EDGE, HEIGHT 2.3 M.

4.4 RWY CONTROLLER HUT, DISTANCE FROM RUNWAY EDGE 50 M, HEIGHT 4.02M ON SOUTHERN SHOULDER ABEAM THRESHOLD 07.

4.5 MILITARY EQUIPMENT INSTALLED BETWEEN RUNWAY AND PTT. DISTANCE FROM THRESHOLD RWY 07 IS 1.62 KM, HEIGHT 1.2 M.

5. Standard Departure for RWY 25:

5.1. After departure turn right for point NIMU and over point NIMU, in a climbing left turn, establish W39 and contact Northern Control for en-route traffic information.

5.2. In case standard departure cannot be executed due to weather conditions, aircraft to climb on Runway Heading to at least 12000 FT (QNH) maintaining visual clearance from all the obstructions. Continuing climb and maintaining uninterrupted visual contact with terrain aircraft to initiate left turn after crossing Gompa Hill to intercept W39. Aircraft to maintain an uninterrupted visual contact with terrain until passing FL 250. Once established on ATS Route W39 and after passing FL 250, the flight plan is to be converted to IFR for en-route phase. Contact northern control for en-route traffic information.

6 All scheduled/non-scheduled operators to produce pre-payment voucher for refuelling facilities at Kargil airfield.)

7. All civil operators are to strictly ensure that no aerial/ground photography of IAF assets are taken by the crew/passengers while operating at air force station Leh.

8.Standard RWY shoulders and cleared zone not available for both runways.

9.All outstation rotary wing aircraft planning EOBT 1400 IST (1330 UTC) or after or coming for night halt to obtain positive clearance before departure due to strong surface winds and gale during afternoon.

VILH AD 2.24 CHARTS RELATED TO AN AERODROME

NIL

VILH AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3