## AD 2. AERODROMES

### VIMB AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VIMB - MORADABAD AIRPORT, MORADABAD

### VIMB AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | | |
|---|---|---|---|
| 1 | Aerodrome reference point coordinates and its site | 284910N 0785528E<br>115.15 DEG/ 623M from physical extremity of RWY 12 | |
| 2 | Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves | 18 KMS from Moradabad Railway Station | |
| 3 | Aerodrome elevation and reference temperature | 635 FT / 39.1 DEG C | |
| 4 | Magnetic variation, date of information and annual change | 0.75 DEG E (2010) /0.016 DEG E | |
| 5 | Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available) | Airport Director<br>Moradabad Airport<br>Airports Authority of India<br>Mundha Pande (Uttar Pradesh)<br>PIN - 244104 (UP), | |
| | | Telephone: | (91) 591 2330007 |
| | | Fax: | |
| | | AFS: | |
| | | Email: | apdmoradabad@aai.aero |
| 6 | Types of traffic permitted (IFR/VFR) | VFR | |
| 7 | Remarks | Geoid Model: EGM-08 | |

### VIMB AD 2.3 OPERATIONAL HOURS

| | | |
|---|---|---|
| 1 | Aerodrome Operator | 0400 - 1230 UTC Daily<br>Except Saturday, Sunday and Holidays |
| 2 | Custom and immigration | Not Applicable |
| 3 | Health and sanitation | During AD Hours |
| 4 | AIS briefing office | As ATS |
| 5 | ATS reporting office (ARO) | As ATS |
| 6 | MET Briefing office | As ATS |
| 7 | Air Traffic Service | As per NOTAM |
| 8 | Fuelling | As ATS |
| 9 | Handling | As ATS |
| 10 | Security | As ATS |
| 11 | De-icing | NO |
| 12 | Remarks | 1. Services are available on request with 24 hrs prior notice to Airport Director.<br>2. Non-Schedule flights to obtain positive clearance prior to departure. |
| | | |

### VIMB AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|---|
| 1 | Cargo-handling facilities | NIL |

| | | |
|---|---|---|
| 2 | Fuel and Oil types | JET A1<br>available on demand |
| 3 | Fuelling facilities and capacity | 01 Bouser, 15KL |
| 4 | De-icing facilities | NIL |
| 5 | Hangar space for visiting aircraft | NIL |
| 6 | Repair facilities for visiting aircraft | NIL |
| 7 | Remarks | Mooring facility: NIL |

**VIMB AD 2.5 PASSENGER FACILITIES**

| | | |
|---|---|---|
| 1 | Hotel(s) at or in the vicinity of aerodrome | In the city |
| 2 | Restaurant(s) at or in the vicinity of aerodrome | Available |
| 3 | Transportation possibilities | Taxis |
| 4 | Medical Facilities | First Aid in the terminal building and basic facilities at PHC Hospital located within 4 Kms.<br>For serious & critical cases, District Hospital located in Moradabad City about 18 kms from the airport |
| 5 | Bank and post office at or in the vicinity of aerodrome | Banks: Available In the city<br>Post office: Available In the city |
| 6 | Tourist office | Available In the city |
| 7 | Remarks | NIL |

**VIMB AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

| | | |
|---|---|---|
| 1 | Aerodrome category for fire fighting | CAT IV |
| 2 | Rescue equipment | 01 CFT and 01 Ambulance<br>(01 CFT and 01 Ambulance standby) |
| 3 | Capability for removal of disabled aircraft | 1. The critical aircraft for the Airport is 2B (B1900D).<br>2. Primary responsibility for removal of disabled aircraft rests with the airline.<br>3. The airlines may contact “Aerodrome Coordinator for Disabled Aircraft Removal Operations’ for coordinating with the agencies having Disabled Aircraft Recovery kit.<br>4. Contact details of Aerodrome Coordinator for Disabled Aircraft Removal Operations:<br>Aerodrome Coordinator: -<br>Airport Director,<br>Email: apdmoradabad@aai.aero<br>Telephone: +91-591-2330010 |
| 4 | Remarks | NIL |

**VIMB AD 2.7 SEASONAL AVAILABILITY CLEARING**

| | | |
|---|---|---|
| 1 | Type(s) of clearing equipment | NIL |
| 2 | Clearance priorities | NIL |
| 3 | Remarks | Bird activity has been observed during morning hours. |

## VIMB AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

| | | |
|---|---|---|
| 1 | Designation, surface and strength of aprons | Refer Aircraft Parking/Docking Chart |
| 2 | Designation, width, surface and strength of taxiways | Refer Aircraft Parking/Docking Chart |
| 3 | Location and elevation of altimeter checkpoints | Runway Holding Position<br>284908.43N 0785522.24E/631.56 FT |
| 4 | Location of VOR checkpoints | Not Available |
| 5 | Position of INS checkpoints | Not Available |
| 6 | Remarks | 1. Coordinates of Runway Holding Position:<br>TWY A: 284908.24N 0785522.19E/631.56 FT<br>2. Coordinates of RWY & TWY Intersection:<br>TWY A: 284910.79N 0785523.89E/633.20 FT<br>3. Geoid Model: EGM-08 |

## VIMB AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

| | | |
|---|---|---|
| 1 | Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands | Taxing guidance signs at all intersections with TWY and RWY and at all holding position, guidelines at apron. Taxiing guidance provided on R/T also |
| 2 | Runway and taxiway markings and lights | RWY<br>Markings:Designation, THR, TDZ,Aiming Point, Centre line, RWY Edge.<br>Lights Not Available<br><br>TWY<br>Marking Centre line, Edge, Runway Holding Positions at TWY A<br>Lights Not Available |
| 3 | Stop bars (if any) | NIL |
| 4 | Remarks | NIL |

## VIMB AD 2.10 AERODROME OBSTACLES

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| 30/TKOF<br>12/APCH | TREE | 284923.0N<br>0785500.5E | 673 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284920.7N<br>0785501.4E | 665 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284926.3N<br>0785457.1E | 688 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284924.4N<br>0785457.2E | 684 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284922.3N<br>0785458.6E | 682 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284923.2N<br>0785503.2E | 662 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284923.9N<br>0785501.0E | 672 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284924.1N<br>0785456.1E | 694 FT | NIL | Group of Tree |
| 30/TKOF<br>12/APCH | TREE | 284922.5N<br>0785502.6E | 671 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284842.0N<br>0785620.5E | 666 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284839.7N<br>0785621.4E | 665 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284841.1N<br>0785621.4E | 669 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284838.9N<br>0785623.6E | 681 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284835.7N<br>0785633.0E | 697 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284840.8N<br>0785623.3E | 667 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284838.2N<br>0785627.5E | 679 FT | NIL | Group of Tree |
| 30/APCH<br>12/TKOF | TREE | 284838.7N<br>0785630.4E | 706 FT | NIL | Group of Tree |

| In Approach/Take-off/Circling Area and at AD | | | | | |
|---|---|---|---|---|---|
| **1** | **2** | **3** | **4** | **5** | **6** |
| RWY/Area affected | Obstacle type | Coordinates | Elevation (EGM-08) | Marking/LGT | Remarks |
| In circling area and at AD | OTHER | 284910.9N 0785522.2E | 636 FT | NIL | Sign Board |
| In circling area and at AD | TREE | 284848.0N 0785616.4E | 686 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284840.2N 0785618.5E | 654 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284839.9N 0785619.5E | 664 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284838.2N 0785620.3E | 681 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284842.1N 0785623.8E | 664 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284909.0N 0785536.4E | 690 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284906.9N 0785541.2E | 695 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284904.3N 0785528.6E | 690 FT | NIL | Group of Tree |
| In circling area and at AD | POLE | 284901.6N 0785538.0E | 649 FT | LGTD | WDI |
| In circling area and at AD | TREE | 284924.0N 0785503.6E | 672 FT | NIL | Group of Tree |
| In circling area and at AD | TREE | 284920.8N 0785459.6E | 675 FT | NIL | Group of Tree |
| In circling area and at AD | SIGN | 284909.6N 0785524.8E | 635 FT | NIL | Sign Board |

## VIMB AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|---|---|---|
| 1 | Name of the associated meteorological office | Moradabad (Class-3) |
| 2 | Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours | During watch hour |
| 3 | Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts | Lucknow<br>9 HRS |
| 4 | Availability of the trend forecast for the aerodrome and interval of issuance | NIL |
| 5 | Information on how briefing and/or consultation is provided | NIL |
| 6 | Types of flight documentation supplied and language(s) used in flight documentation | Tabular Form<br>English |
| 7 | Charts and other information displayed or available for briefing or consultation | NIL |
| 8 | Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images; | Telephone |
| 9 | The air traffic services unit(s) provided with meteorological information | .Moradabad ATC and ACS |
| 10 | Additional information, e.g. concerning any limitation of service. | Documentation provided as requested. |

## VIMB AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| Designations | TRUE Bearings | Dimensions of RWY (M) | Strength of pavement (PCN) and associated data) and surface of runway and associated stopways | Geographical coordinates for threshold and runway end |
|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 |
| 12 | 120.51 DEG | 2112 x 30 M | 21/F/C/Y/T<br>Asphalt | THR:<br>284919.15N<br>0785507.79E<br>RWY END:<br>284844.32N<br>0785614.90E |
| 30 | 300.51 DEG | 2112 x 30 M | 21/F/C/Y/T<br>Asphalt | THR:<br>284844.32N<br>0785614.90E<br>RWY END:<br>284919.15N<br>0785507.79E |

| THR elevation and highest elevation of TDZ of precision APP RWY | Slope of runway and associated stopway | Dimensions of stopway (M) | Dimensions of clearway (M) | Dimensions of strips (M) |
|---|---|---|---|---|
| 6 | 7 | 8 | 9 | 10 |
| THR: 635.0FT<br>TDZ: 635.0FT | | | | 2232 x 80 M |
| THR: 630.0FT<br>TDZ: 630.0FT | | | | 2232 x 80 M |

| Dimensions of runway end safety areas | Location and description of arresting system (if any) | Existence of an obstacle-free zone | Remarks. |
|---|---|---|---|
| 11 | 12 | 13 | 14 |
| 30M x 60M | N/A | | a) Geoid Model: EGM-08 |
| 30M x 60M | N/A | | a) Geoid Model: EGM-08 |

## VIMB AD 2.13 DECLARED DISTANCES

| RWY Designator | Take-off run available TORA (M) | Take-off distance available TODA (M) | Accelerate distance available ASDA (M) | Landing distance available LDA (M) | Remarks (including runway entry or start point where alternative reduced declared distances have been declared) |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 12 | 2112 | 2112 | 2112 | 2112 | |
| 30 | 2112 | 2112 | 2112 | 2112 | |

## VIMB AD 2.14 APPROACH AND RUNWAY LIGHTING

| Runway Designator | Type, length and intensity of approach lighting system | Runway threshold lights, colour and wing bars | Type of visual slope indicator system | Length of runway touchdown zone lights |
|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 |
| 12 | NIL | NIL | PAPI<br>LEFT/3.00 DEG<br>MEHT<br>(12.20M) | |
| 30 | NIL | NIL | PAPI<br>LEFT/3.00 DEG<br>MEHT<br>(12.20M) | |

| Length, spacing, colour and intensity of runway centre line lights | Length, spacing, colour and intensity of runway edge lights | Colour of runway end lights and wing bars | Length and colour of stopway lights | Remarks |
|---|---|---|---|---|
| 6 | 7 | 8 | 9 | 10 |
| | | NIL | | NIL |
| | | NIL | | NIL |

## VIMB AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

| | | | |
|---|---|---|---|
| 1 | Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any) | ABN | Available |
| | | IBN | Available |
| 2 | Location and lighting (if any) of anemometer/ landing direction indicator; | LDI | Available |
| | | Anemometer | Not Available |
| 3 | Taxiway edge and taxiway centre line lights; | Edge | Not available |
| | | Centre Line | Not available |
| 4 | Secondary power supply including switch-over time; | Sub-station – I: 2 DG Set 125KVA & 250 KVA (Working) | |
| 5 | Remarks | NIL | |

## VIMB AD 2.16 HELICOPTER LANDING AREA

| | | |
|---|---|---|
| 1 | Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area | Not Established |
| 2 | TLOF and/or FATO area elevation: | Not Established |
| 3 | TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking; | Not Established |
| 4 | True bearings of FATO; | Not Established |
| 5 | Declared distances available | Not Established |
| 6 | Approach and FATO lighting; | Not Established |
| 7 | Remarks | Not Established |

## VIMB AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

| | | |
|---|---|---|
| 1 | Airspace designation, geographical coordinates and lateral limits | CTR: Area bounded by lines joining points 290000N 0790720E; 290000N 0790355E; 283700N 0790155E; 283453N 0790049E then along the clockwise arc of a circle of 15NM radius centred on 284910N 0785528E to point of origin. |
| 2 | Vertical limits | FL 55 |
| 3 | Airspace classification | D |
| 4 | Call sign and language(s) of the air traffic services unit providing service; | Moradabad Tower, English |
| 5 | Transition altitude | 4000 FT |
| 6 | Hours of applicability | HO |
| 7 | Remarks | 1. CTR only during published watch hrs.<br>2. Beyond Hours of Operations the airspace classification is Class G.<br>3. Moradabad Approach Control Unit is combined with Moradabad Aerodrome Control Tower. |

## VIMB AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

| Service Designation | Call sign | Channel(s) | SATVOICE Number(s), if available |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| APP | Moradabad Tower | 118.025 MHZ | |
| APP | Moradabad Tower | 118.625 MHZ | |
| TWR | Moradabad Tower | 118.025 MHZ | |
| TWR | Moradabad Tower | 118.625 MHZ | |

| Logon address, as appropriate | Hours of operation | Remarks |
|---|---|---|
| 5 | 6 | 7 |
| | HO | 1. Backup<br>2.Functions of Approach Control Service provided by Aerodrome Control Tower. |
| | HO | 1.Main<br>2.Functions of Approach Control Service provided by Aerodrome Control Tower. |
| | HO | Backup |
| | HO | Combined AD CTL and APCH CTL Procedural SER will be provided from Tower on PERM basis DRG published ATC watch HR. |

## VIMB AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid | Identification | Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate | Hours of operation, as appropriate; |
|---|---|---|---|
| 1 | 2 | 3 | 4 |

| Geographical coordinates of the position of the transmitting antenna | Elevation of transmitting antenna of DME/ elevation of GBAS reference point | Service volume radius from the GBAS reference point | Remarks |
|---|---|---|---|
| 5 | 6 | 7 | 8 |

## VIMB AD 2.20 LOCAL AERODROME REGULATIONS

**NIL**

## VIMB AD 2.21 NOISE ABATEMENT PROCEDURES

**NIL**

## VIMB AD 2.22 FLIGHT PROCEDURES

**NIL**

## VIMB AD 2.23 ADDITIONAL INFORMATION

**NIL**

## VIMB AD 2.24 CHARTS RELATED TO AN AERODROME

1 Aerodrome Chart (23 JANUARY 2025)
2 Aircraft Parking/Docking Chart (23 JANUARY 2025)
3 Aerodrome Obstacle Chart Type - A, (Operating Limitations) RWY 10 (23 JANUARY 2025)
4 Aerodrome Obstacle Chart Type - A, (Operating Limitations) RWY 28 (23 JANUARY 2025)
5 Aerodrome Obstacle Chart Type-B, (23 JANUARY 2025)

## VIMB AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

| Procedure | Procedure Minima | VSS Penetration |
|---|---|---|
| **1** | **2** | **3** |
| | | |