AD 2. AERODROMES

VOMY AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VOMY - MYSURU AIRPORT, MYSURU

VOMY AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	121357N 0763923E MAG. BRG. 280.30 DEG / 460 M from physical extremity of RWY 27	
2	Direction and distance of aerodrome reference point from the center of the city or town which the aerodrome serves	185 DEG South, 12 KM from railway station	
3	Aerodrome elevation and reference temperature	2397 FT / 34.0 DEG C	
4	Magnetic variation, date of information and annual change	2.00 DEG W (2010) /0.033 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	The Airport Director Airports Authority of India, Mysuru, Karnataka - 571311	
		Telephone:	(91) 821 2596802 (91) 9483506802
		Fax:	(91) 821 2596802
		AFS:	VOMYYHYX
		Email:	apdmysuru@aai.aero
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	Elevation in EGM08	

VOMY AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON-FRI 0400-1230 UTC (0930-1800 IST) SAT/SUN/Holidays: Nil
2	Custom and immigration	NIL
3	Health and sanitation	NIL
4	AIS briefing office	As Per ATS Watch Hours
5	ATS reporting office (ARO)	As Per ATS Watch Hours
6	MET Briefing office	As Per ATS Watch Hours
7	Air Traffic Service	Consult current NOTAM for HRs
8	Fuelling	As Per ATS Watch Hours
9	Handling	NIL
10	Security	24X7 provided by State Police
11	De-icing	NIL
12	Remarks	1. Outside ATS watch Hours, services are available O/R with 48HR PN to AD. 2. RWY traffic handling capacity : MAX NR OF ARR ONLY ----10 MAX NR OF DEP ONLY-----10

VOMY AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1

3	Fuelling facilities and capacity	BPCL (Inside the Airport) - JET A1 fuelling Service Storage & Capacity TK 01 (Static Tank) = 30 KL R159 Refueller = 15KL R226 Refueller = 6KL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

VOMY AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Available in the city nearest 10KM.
2	Restaurant(s) at or in the vicinity of aerodrome	Available in the city
3	Transportation possibilities	Taxis from AD
4	Medical Facilities	First aid at AD. Hospital in the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: Available in the city Post office: Available in the city
6	Tourist office	Office in the city Telephone Nos: +91-821-2423492 +91-821-2423652
7	Remarks	NIL

VOMY AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-5
2	Rescue equipment	Available as per Category
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is- ATR 72-600. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Airport Director Contact No: +91-821-2596333, +91- 9483506802 Email: apdmysuru@aai.aero
4	Remarks	NIL

VOMY AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	NIL

VOMY AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart

3	Location and elevation of altimeter checkpoints	Location: Aircraft Stands 1, 2, 3, 4 and 5. Elevation: 2338 FT
4	Location of VOR checkpoints	On TWY A and TWY L at runway holding positions.
5	Position of INS checkpoints	NIL
6	Remarks	1. Coordinates of RWY Holding Position **TWY** **Coordinates** **Elevation** TWY A 121351.70N 0763925.76E 2348 FT TWY L 121357.26N 0763929.44E 2344 FT 2. Coordinates of RWY & Taxi Intersection **TWY** **Coordinates** **Elevation** TWY-A 121354.21N 0763925.67E 2349 FT TWY-L 121354.40N 0763930.98E 2346 FT 3. Width of shoulders on TWY A: 18.04 FT (both sides) 4. All elevations in EGM08

VOMY AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiing guidance provided on R/T. Guidelines at Apron
2	Runway and taxiway markings and lights	RWY Markings: Designation, THR, TDZ, Centre line, Edge, Aiming point RWY Lighting: THR, Edge, END, Turning Point TWY Marking: Centre line Edge, Taxi holding Position on TWY A and TWY L. TWY Lighted: Edge TWY A and TWY L.
3	Stop bars (if any)	NIL
4	Remarks	NIL

VOMY AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
27/TKOF 09/APCH	OTHER	121347.9N 0763837.9E	2411 FT	NO	MOBILE ROAD TRAFFIC (ROAD ELEV. 729.9 M + 5 M MOBILE TRAFFIC)
27/TKOF 09/APCH	OTHER	121347.7N 0763836.6E	2414 FT	NO	MOBILE RAIL TRAFFIC (RAIL ELEV. 728.1 M + 7.6 M MOBILE TRAFFIC)
27/TKOF 09/APCH	TREE	121349.0N 0763835.7E	2440 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	OTHER	121349.4N 0763834.4E	2416 FT	NO	MOBILE RAIL TRAFFIC (RAIL ELEV. 728.7 M + 7.6 M MOBILE TRAFFIC)
27/TKOF 09/APCH	FENCE	121349.3N 0763835.3E	2404 FT	NO	AIRPORT BOUNDARY WALL WITH FENCE ON TOP

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
27/TKOF 09/APCH	TREE	121359.5N 0763815.0E	2453 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	TREE	121353.5N 0763817.3E	2450 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	FENCE	121347.8N 0763837.4E	2406 FT	NO	AIRPORT BOUNDARY WALL WITH FENCING ON TOP
27/TKOF 09/APCH	POLE	121348.3N 0763836.8E	2406 FT	NO	LIGHT POLE
27/TKOF 09/APCH	POLE	121348.9N 0763835.9E	2406 FT	NO	LIGHT POLE
27/TKOF 09/APCH	OTHER	121349.5N 0763835.2E	2410 FT	NO	MOBILE ROAD TRAFFIC (ROAD ELEV. 729.6 M + 5 M MOBILE TRAFFIC)
27/TKOF 09/APCH	POLE	121349.6N 0763835.0E	2405 FT	NO	LIGHT POLE
27/TKOF 09/APCH	TREE	121351.6N 0763830.7E	2424 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	TREE	121345.9N 0763822.5E	2438 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	TREE	121351.4N 0763821.8E	2450 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	TREE	121357.7N 0763820.3E	2462 FT	NO	GROUP OF TREES
27/TKOF 09/APCH	OTHER	121352.3N 0763831.3E	2418 FT	NO	MOBILE RAIL TRAFFIC (RAIL ELEV. 729.3 M + 7.6 M MOBILE TRAFFIC)
27/APCH 09/TKOF	TREE	121349.9N 0763949.9E	2394 FT	NO	GROUP OF TREES
27/APCH 09/TKOF	TREE	121350.7N 0763947.1E	2363 FT	NO	GROUP OF TREES
27/APCH 09/TKOF	POLE	121358.3N 0763940.2E	2346 FT	NO	LIGHT POLE
27/APCH 09/TKOF	TREE	121359.6N 0763945.4E	2362 FT	NO	GROUP OF TREES
In circling area and at AD	FENCE	121347.6N 0763838.1E	2405 FT	NO	AIRPORT BOUNDARY WALL WITH FENCE ON TOP
In circling area and at AD	TREE	121350.2N 0763839.2E	2405 FT	NO	BUSHES
In circling area and at AD	TREE	121347.3N 0763838.5E	2424 FT	NO	BUSHES
In circling area and at AD	POLE	121347.7N 0763837.8E	2407 FT	NO	LIGHT POLE
In circling area and at AD	TREE	121349.1N 0763946.5E	2368 FT	NO	GROUP OF TREES
In circling area and at AD	TREE	121359.8N 0763939.8E	2362 FT	NO	GROUP OF TREES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM-08)	Marking/LGT	Remarks
In circling area and at AD	TREE	121359.4N 0763903.6E	2420 FT	NO	GROUP OF TREES
In circling area and at AD	FENCE	121357.4N 0763917.9E	2365 FT	NO	AIRPORT BOUNDARY WALL WITH FENCING ON TOP
In circling area and at AD	NAVAID	121346.5N 0763907.0E	2407 FT	NO	DVOR MAIN ANTENNA
In circling area and at AD	NAVAID	121346.8N 0763906.9E	2415 FT	LGTD	DVOR DME ANTENNA
In circling area and at AD	POLE	121346.2N 0763906.8E	2425 FT	NO	L/C ROD
In circling area and at AD	OTHER	121351.0N 0763916.7E	2384 FT	LGTD	WDI
In circling area and at AD	NATURAL HIGHPOINT	121351.3N 0763919.8E	2355 FT	NO	GROUND LEVEL
In circling area and at AD	NATURAL HIGHPOINT	121350.9N 0763914.5E	2367 FT	NO	GROUND LEVEL
In circling area and at AD	NATURAL HIGHPOINT	121350.6N 0763909.3E	2378 FT	NO	GROUND LEVEL
In circling area and at AD	POLE	121357.8N 0763902.6E	2383 FT	NO	LIGHT POLE
In circling area and at AD	POLE	121357.9N 0763906.0E	2376 FT	NO	LIGHT POLE
In circling area and at AD	POLE	121357.4N 0763913.9E	2367 FT	NO	LIGHT POLE
In circling area and at AD	POLE	121357.4N 0763916.2E	2368 FT	NO	LIGHT POLE
In circling area and at AD	POLE	121357.3N 0763917.9E	2368 FT	NO	LIGHT POLE
In circling area and at AD	TREE	121357.4N 0763924.0E	2358 FT	NO	TREE
In circling area and at AD	WINDMILL	121351.6N 0763924.2E	2368 FT	LGTD	WDI
In circling area and at AD	NATURAL HIGHPOINT	121350.5N 0763905.8E	2380 FT	NO	GROUND LEVEL
In circling area and at AD	BUILDING	121621.0N 0764015.5E	3469 FT	NO	TEMPLE
In circling area and at AD	ANTENNA	121637.4N 0764015.3E	3605 FT	LGTD	CELLPHONE MAST
In circling area and at AD	ANTENNA	121625.4N 0764031.7E	3826 FT	LGTD	TV TOWER
In circling area and at AD	BUILDING	121641.9N 0764016.1E	3557 FT	NO	BUILDING
In circling area and at AD	ANTENNA	121452.7N 0763757.3E	2563 FT	LGTD	CELLPHONE MAST
In circling area and at AD	ANTENNA	121454.2N 0763757.2E	2556 FT	LGTD	CELLPHONE MAST
In circling area and at AD	ANTENNA	121614.9N 0764011.2E	3508 FT	LGTD	CELLPHONE MAST ON HILL
In circling area and at AD	ANTENNA	121628.1N 0764013.7E	3503 FT	LGTD	CELLPHONE MAST

VOMY AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	BANGALORE
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	0030 UTC to 1600 UTC + Extension
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Bengaluru 9HR Hours TAF
4	Availability of the trend forecast for the aerodrome and interval of issuance	NIL
5	Information on how briefing and/or consultation is provided	As per the Flight plan Through OLBS
6	Types of flight documentation supplied and language(s) used in flight documentation	English
7	Charts and other information displayed or available for briefing or consultation	Charts and Documents available in OLBS will be provided to operators as per their requirement
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	NIL
9	The air traffic services unit(s) provided with meteorological information	VOMY ATC TWR, Mysuru
10	Additional information, e.g. concerning any limitation of service.	Half –Hourly METAR & SPECI DRG ATC Watch HR

VOMY AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
09	87.96 DEG	1740 x 30 M	700/R/B/W/T Concrete	THR: 121352.63N 0763840.36E RWY END: 121354.64N 0763937.89E
27	267.96 DEG	1740 x 30 M	700/R/B/W/T Concrete	THR: 121354.64N 0763937.89E RWY END: 121352.63N 0763840.36E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 2397.0FT TDZ: 2397.0FT	-1.00%	NIL	NIL	1860 x 150 M
THR: 2341.0FT TDZ: 2354.0FT	1.00%	NIL	NIL	1860 x 150 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
90M x 90M		NIL	Elevation in EGM08
150M x 90M		NIL	Elevation in EGM08

VOMY AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
09	1740	1740	1740	1740	
27	1740	1740	1740	1740	

VOMY AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
09	SALS 420 M	Green	PAPI LEFT/3.00 DEG MEHT (30.00FT)	NIL
27	SALS 420 M	Green	PAPI LEFT/3.00 DEG MEHT (30.00FT)	NIL

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
	1740 M 60 M White/Yellow	Red	NIL	NIL
	1740 M 60 M White/Yellow	Red	NIL	NIL

VOMY AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	At Tower Building (11RPM) As per ATS HR
		IBN	NIL

2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Available. Lighted 87.1M S-E of intersection of RWY and TWY A
		Anemometer	Anemometer with sensors provided on top of Tower.
3	Taxiway edge and taxiway centre line lights;	Edge	Available
		Centre Line	NIL
4	Secondary power supply including switch-over time;	DG power supply with UPS for all AGL with switch over time less than 01 sec and 15 sec to all other lighting at AD including APRON flood light.	
5	Remarks	NIL	

VOMY AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not Established
2	TLOF and/or FATO area elevation:	Not Established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not Established
4	True bearings of FATO;	Not Established
5	Declared distances available	Not Established
6	Approach and FATO lighting;	Not Established
7	Remarks	NIL

VOMY AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Circular area centered on 121357N 0763923E within a 10NM radius.
2	Vertical limits	6000 FT AMSL
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Mysuru Tower, English
5	Transition altitude	6000 FT
6	Hours of applicability	
7	Remarks	Mysuru Approach Control Unit is combined with Mysuru Aerodrome Control Tower.

VOMY AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Mysuru Tower	118.250 MHZ	
APP	Mysuru Tower	124.325 MHZ	
TWR	Mysuru Tower	118.250 MHZ	
TWR	Mysuru Tower	124.325 MHZ	
ATIS	MYSURU INFORMATION	127.225 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HO	1.Main 2. Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1.Back up 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
		NIL
	As ATS	STANDBY
	HO	NIL

VOMY AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
DVOR/DME	MSR	113.700 MHz CH84X	As ATS

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
121346.5N 0763907.0E	2415 FT		Vertical datum: EGM08

VOMY AD 2.20 LOCAL AERODROME REGULATIONS

• No Aircraft shall take lock turn/ pivotal turn on the Runway to avoid pavement damage.

VOMY AD 2.21 NOISE ABATEMENT PROCEDURES

VOMY AD 2.22 FLIGHT PROCEDURES

RADIO COMMUNICATION FAILURE PROCEDURES

1.INTRODUCTION:

1.1 Radio communication failure (RCF) procedures are prescribed in ICAO PANS-ATM DOC 4444. The objective is to standardize the actions to be taken by the pilot of arriving and departing aircraft experiencing radio communication failure at Mysuru airport. Based on these provisions, following radio communication failure procedures are established, to standardize the actions to be taken by the pilot of arriving and departing aircraft at Mysuru airport.

2. GENERAL:

2.1 All Transponder equipped aircraft experiencing Radio Communication Failure shall set transponder to Mode A code 7600 as soon as practicable.

(Note: This Requirement of Setting transponder to Mode A code 7600 in no way imposes any restriction on the pilot's decision to set transponder to Mode A code 7500 or 7700. whenever required)

2.2 Immediately after the detection of RCF, the pilot shall try to communicate to Mysuru ATS unit through the standby frequency 124.325 MHz.

2.3 If unable to contact on standby frequency also, pilot shall try to communicate through adjacent units/stations frequencies (HAL 127.7 MHz, VOML 127.55MHz) company frequency or by relay through other aircraft.

2.4 Unless otherwise required, the aircraft shall avoid all Restricted and Prohibited Areas.

2.5 The pilot shall make blind transmission to ATC of all necessary reports and actions taken by the aircraft, e.g. descent, turn, joining hold, leaving for approach, FAF etc., irrespective of whether partial/complete RCF has been experienced or not.

3. ASSIGNED RUNWAY AND ITS AVAILABILITY FOR RCF AIRCRAFT:

3.1 ln case of arriving aircraft, when Runway for landing has already been advised to the aircraft by ATC, such runway shall be considered ns assigned runway. If radio communication failure occurs after the receipt of final/procedural turn or approach clearance, the aircraft may continue its approach to land on such Runway.

3.2 In the event of arriving aircraft has not been advised of any runway for landing, Runway 27 shall be considered as assigned runway for such arrival.

3.3 In the case of neighbouring adjacent ATC unit informs that the departing aircraft from Mysuru returning on account of RCF and squawking 7600. the departure runway of such aircraft shall be considered as assigned runway for landing.

3.4 Mysuru ATC shall ensure approach and runway lights of the assigned runway in 'SWITCHED ON' position for RCF aircraft irrespective of day/night/visibility/weather conditions. Approach lights in 'SWITCHED OFF' position shall indicate that the approach should be made from the opposite end of runway. Runway and Approach lights on both sides in ‘SWITCHED OFF' position shall indicate non- availability of Runway for aircraft experiencing RCF.

3.5 In strong tail wind conditions for assigned Runway, aircraft will carry out a missed approach on assigned runway and after following complete missed approach procedure for such approach, will carry out the published instrument approach procedure for the opposite runway.

4. PROCEDURE FOR ARRIVALS:

4.1 ARRIVING AIRCRAFT – In VMC

4.1.1 Continue to fly in visual meteorological conditions

4.1.2 land at the nearest suitable aerodrome.

4.1.3 Report its arrival by the most expeditious means to the appropriate air traffic control unit.

4.2 ARRIVING AIRCRAFT – In IMC

4.2.1 Maintain the last assigned speed and level, or minimum flight altitude if higher, for a period of 20 minutes following the aircraft's failure to report its position over a compulsory reporting point and thereafter adjust level and speed in accordancewith the filed flight plan; or

4.2.2 Proceed according to the current flight plan route to the appropriate designated navigation aid hold over this aid until commencement of descent.

4.2.3 Commence descent at, or as close to, the expected approach time (EAT) last received and acknowledged; or the estimated time of arrival (ETA) as per the current flight plan.

4.2.4 Complete a normal instrument approach procedure as specified for the designated navigation aid.

4.2.5 land, if possible, within 30 minutes of the estimated time of arrival (ETA) or the last acknowledged expected (EAT) approach time, whichever is later.

5. PROCEDURE FOR DEPARTURES:

5.1 DEPARTURE INTENDING TO CONTINUE TO DESTINATION: Departing aircraft experiencing RCF and intending to continue to its tiled plan destination shall

5.1.1 Continue on assigned route/Radial climbing to or maintaining cleared level as per the clearance given as far as practicable.

5.1.2 Three minutes after setting Mode A/C code 7600 or reaching cleared Flight level whichever is later; aircraft shall proceed directly to re-join the current flight plan route not later than the next significant point, maintaining cleared flight level. After joining ATS route, climb to filed Flight level and continue as per the filed night plan. (Aircraft shall avoid all Prohibited and Restricted areas)

5.2 DEPARTURE INTENDING TO LAND BACK AT MYSURU: Departing aircraft experiencing RCF and intending to land back at MYSURU airport shall

5.2.1 Continue as per ATC clearance or any assigned heading. climbing to or maintaining the cleared Flight level. However, in case the RCF is experienced below FL100, and the cleared flight level is above FL100, aircraft shall maintain FL100.

5.2.2 Three minutes after setting Mode A/C code 7600 or reaching the appropriate level as given above, whichever is later; take a turn to proceed direct to 'MSR' maintaining level.

5.2.3 Descend to MSA 4900 FT and hold over 'MSR'. Leave 'MSR' at 4900 FT to cany out any of the published instrument approach procedure for assigned runway.

5.2.4 Observe the ATC tower to follow Various Signals used by ATCO during communication failure.

VOMY AD 2.23 ADDITIONAL INFORMATION

VOMY AD 2.24 CHARTS RELATED TO AN AERODROME

1.Aerodrome Chart(16 APRIL 2026)
2.Aircraft Parking/ Docking Chart(16 APRIL 2026)
3.Aerodrome Obstacle Chart Type - A (Operating Limitations) – RWY 09
4.Aerodrome Obstacle Chart Type - A (Operating Limitations) – RWY27
5.VOR Procedure RWY 09 (Cat A/B) (DME Required)
6.VOR Procedure RWY 27 (Cat A/B) (DME Required)

VOMY AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration

1	2	3