AD 2. AERODROMES

VAPO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VAPO - PUNE AIRPORT, PUNE [INDIAN AIR FORCE]

NOTE: Aeronautical Data and Aeronautical Information published here under is as provided by Indian Air Force

VAPO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	183500N 0735510E 300 FT North of runway intersection	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	4 NM North-East of Pune Railway Station	
3	Aerodrome elevation and reference temperature	1943 FT / 38.2 DEG C	
4	Magnetic variation, date of information and annual change	0.59 DEG W (2015) /0.3333 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Senior Air Traffic Control Officer Air Force Station, Pune (Maharashtra) Pin – 411032,	
		Telephone:	(91) 20 26684434 (91) 8275619250 (91) 20-26614023
		Fax:	
		AFS:	VAPOZTZX
		Email:	niyantran-2@gov.in
6	Types of traffic permitted (IFR/VFR)	IFR/VFR	
7	Remarks	(i) Joint User Airfield (Defence & Civil Ops) (ii) Aerodrome reference code is 4D. (iii) All non-scheduled/ General Aviation movements will be subject to positive approval from IAF authority.	

VAPO AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	MON – FRI: 0145-0845 UTC SAT, SUN & HOL: NIL
2	Custom and immigration	H24
3	Health and sanitation	H24
4	AIS briefing office	As per NOTAMs
5	ATS reporting office (ARO)	H24
6	MET Briefing office	H24
7	Air Traffic Service	H24
8	Fuelling	H24
9	Handling	H24
10	Security	H24
11	De-icing	NIL
12	Remarks	1) Civil flight not permitted during Military flying block BTN 0330-0559 UTC FM MON to FRI. 2) Civil flight not permitted FM 0530-1030 UTC on Saturdays due airfield MAINT closure.

VAPO AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	Limited- Manual by arrangement with local airlines
2	Fuel and Oil types	JET A1 MWM, AV Gas.-100LL Oil: Not Available.
3	Fuelling facilities and capacity	Refueller Capacity: 16000 X 4, 11000 X 2 Discharge Rate(L/Sec): 12 L/Sec
4	De-icing facilities	Nil
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	Limited, prior arrangement with local airlines required
7	Remarks	Nil

VAPO AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Near the AD and in the city.
2	Restaurant(s) at or in the vicinity of aerodrome	At AD and in the city.
3	Transportation possibilities	State transport service (AC) as well as taxi service H24.
4	Medical Facilities	First aid at AD. Hospital in the city.
5	Bank and post office at or in the vicinity of aerodrome	Banks: Vijaya Bank and ATM counters of Vijaya Bank and Oriental Bank. 04 Money exchange counters available. Post office: Available in the city.
6	Tourist office	Not Available
7	Remarks	Nil

VAPO AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	CAT-7
2	Rescue equipment	Available as per AD category.
3	Capability for removal of disabled aircraft	A coordinated plan for removal of disabled aircraft exists. Disabled aircraft removal to be ensured by respective operator in coordination with local authorities.
4	Remarks	Nil

VAPO AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Nil
2	Clearance priorities	Nil
3	Remarks	Nil

VAPO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Designator: Civil Apron Surface: Concrete Surface Strength: Stand No. Strength 1 PCN 68/R/B/W/T 2 PCN 68/R/B/W/T 3 PCN 68/R/B/W/T 4 PCN 68/R/B/W/T 5 PCN 76/R/A/W/T 6 PCN 73/R/A/W/T 7 PCN 73/R/A/W/T 8 PCN 73/R/A/W/T 9 PCN 100/R/B/W/T 10 PCN 100/R/B/W/T

2	Designation, width, surface and strength of taxiways	Designator: LINK K Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK K1 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK K2 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK K3 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK K4 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK L Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK M Width: 75 FT Surface: Strength: PCN 63/R/C/X/T Designator: LINK P1 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK P2 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK R1 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T Designator: LINK R2 Width: 75 FT Surface: Concrete Strength: PCN 63/R/C/X/T
3	Location and elevation of altimeter checkpoints	Location: At Apron Elevation: 1930 FT
4	Location of VOR checkpoints	On Link P before entering Link P1: 105 DEG 1.1 NM RWY Holding point at Link P2: 245 DEG 0.4 NM
5	Position of INS checkpoints	Nil

6	Remarks	1. TWY R1 is a rapid exit taxiway for RWY 10 at 7000 ft from threshold RWY 10. Length is 200M 2. TWY J is connecting parallel taxi track to RWY abeam ATC. 3. TWY P1is connecting dumbbell RWY 28 to parallel taxi track. 4. TWY P2 is connecting Dumbbell RWY 10 to parallel taxi track. 5. TWY K3 is connecting RWY PTT to civil apron and is leading to aircraft stands 6 and 7.. 6. K2 is connecting parallel taxi track to civil dispersal and is leading to aircraft stand 1, 2, 3, 4 and 5. 7. TWY K4 is connecting parallel taxi track to civil dispersal and is leading to aircraft stands 8,9 and 10. 8. Rapid Exit TWY R2 for RWY 28 is at 6000 ft from threshold RWY 28. Length is 265M. 9. TWY H is connecting RWY to TWY G intersecting parallel taxi track . 10. TWY G is connecting PTT to 32 DB abeam TWY H. 11. TWY F is connecting parallel taxi track to TWY G. 12. Taxiway M is connecting RWY and PTT abeam K4 13. TWY L is connecting RWY to PTT abeam K3. 14. TWY K1 is connecting parallel taxi track to civil dispersal and is leading to aircraft stand 1. 15. TWY E is connecting parallel taxi track to 32 DB 16. Isolated Aircraft Parking Position (IAPP) on Link E link facing south. 17. Apron Elevation: 1930 FT.

VAPO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Aircraft stand ID signs available for all 10 aircraft stands. VDGS provided on stand no.1 and 2 with aerobridge facility. All bay number markings with lead in/out markings are available.
2	Runway and taxiway markings and lights	RWY Markings: RWY Designation, THR, TDZ, Centre Line, RWY Edge,Side stripe, Aiming point marking RWY Lights: RWY threshold lights, Wing Bar lights, Touchdown Zone Lights, RWY edge lights,RWY End LightsRunway centre line lights.. TWY Marking: Centre Line, CATII Holding Position Marking, Intermediate holding position, Edge. Enhanced taxiway centre line marking on P1 and P2 link. On 'P' link broken white centre line marking is painted as per IAF requirements.. TWY Lights: Standard Taxi track edge Lights TWY P1, P2, K, K1, K2, K3, L, M, R1, R2. Taxi center line lights are not installed.
3	Stop bars (if any)	RWY holding link P1, link P2, link D and link J.
4	Remarks	Nil

VAPO AD 2.10 AERODROME OBSTACLES

Note: Resolution of obstacles coordinates is up to Second only

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
28/APCH 10/APCH	BUILDING	183504.0N 0735512.0E	2002 FT	NO/LGTD	Building
28/APCH	BUILDING	183507.0N 0735541.0E	2028 FT	NO/LGTD	Building
28/APCH	ANTENNA	183458.0N 0735539.0E	1973 FT	Marked/LGTD	Antenna
28/APCH	ANTENNA	183458.0N 0735540.0E	1942 FT	Marked/LGTD	Antenna
28/APCH	NATURAL HIGHPOINT	183436.0N 0740253.0E	2287 FT	NO/NO	Hill
28/APCH	OTHER	183439.0N 0735845.0E	2050 FT	NO/LGTD	Mast
10/APCH	ANTENNA	183448.0N 0735409.0E	1965 FT	NO/LGTD	Antenna
10/APCH	ANTENNA	183610.0N 0735302.0E	2195 FT	NO/LGTD	Antenna
10/APCH	ANTENNA	183459.0N 0735414.0E	1912 FT	Marked/LGTD	Antenna
10/APCH	ANTENNA	183616.0N 0735156.0E	2218 FT	Marked/LGTD	Antenna
In circling area and at AD	NATURAL HIGHPOINT	183657.0N 0735338.0E	2513 FT	NO/NO	Hill
In circling area and at AD	OTHER	183443.0N 0735441.0E	2020 FT	NO/NO	Mast

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation	Marking/LGT	Remarks
In circling area and at AD	OTHER	183520.0N 0735454.0E	2018 FT	NO/LGTD	Mast
In circling area and at AD	OTHER	183517.0N 0735516.0E	2087 FT	NO/LGTD	Mast

VAPO AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	Met Office, Pune
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	H 24
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Met Office, Pune 12Hrs.
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend, At Interval of 30min
5	Information on how briefing and/or consultation is provided	Verbal and telephonic briefing provided. METAR is updated on IMD site also. Mobile number: 9545861127
6	Types of flight documentation supplied and language(s) used in flight documentation	Chart form, English
7	Charts and other information displayed or available for briefing or consultation	Sea level charts, upper air charts, satellite cloud imagery, Doppler Weather Radar Imagery, NWP Products of CAT and icing, Local Forecast, Current Weather, Astronomical and climatologically data.
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	LDS, AWS Input is taken from VAIRAVAL (IMD radar) & Mumbai Radar using civil internet, NWP
9	The air traffic services unit(s) provided with meteorological information	Pune ATS
10	Additional information, e.g. concerning any limitation of service.	Nil

VAPO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
10	94.00 DEG	2540 x 46 M	63/R/C/X/T Concrete 67/ F/ B/ X/ T Asphalt	THR: 183459.09N 0735423.15E RWY END: 183453.72N 0735549.60E
28	274.00 DEG	2540 x 46 M	63/R/C/X/T Concrete 67/ F/ B/ X/ T Asphalt	THR: 183453.72N 0735549.60E RWY END: 183459.09N 0735423.15E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 1913.0FT TDZ: 1918.0FT	1.00%	267 x 46 M	267 x 46	2660 x 280 M
THR: 1925.0FT TDZ: 1930.0FT	1.00%	250 x 46 M	250 x 46	2660 x 280 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
	Arresting System not available for civil flights	Obstacle free Zone available	1. Arresting Barrier is kept on lowered position during ARR and DEP of all transport aircraft. 2. RESA is not available due to arrester barrier installed at both ends of RWY 3. First 222M and last 400M of RWY 10 surface is concrete and remaining is asphalt. 4. True Bearing is provided to nearest degree. 5. Elevation of THR and TDZ is up to nearest feet.
	Arresting System not available for civil flights	Obstacle free Zone available	1. Arresting Barrier is kept on lowered position during ARR and DEP of all transport aircraft. 2. RESA not available due arrester barrier installed at both ends of RWY 3. First 400M and last 222M of RWY 28 surface is concrete and remaining is asphalt. 4. True Bearing is provided up to nearest degree 5. Elevation of THR and TDZ is up to nearest feet

VAPO AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
10	2540	2807	2807	2540	1. All Heavy aircraft to line up 60M from RWY threshold to minimize damage to Arrester Net. 2. In case a civil flight is forced to use Stopway during overrun, to exercise caution for Arrester Net (lying on ground in lowered position) as an obstruction.
28	2540	2790	2790	2540	1. All Heavy aircraft to line up 60M from RWY threshold to minimize damage to Arrester Net. 2. In case a civil flight is forced to use Stopway during overrun, to exercise caution for Arrester Net (lying on ground in lowered position) as an obstruction.

VAPO AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
10	SALS 420 M LIH	Green	PAPI RIGHT/3.00 DEG	
28	CAT II 750 M LIH	Green Available	PAPI RIGHT/3.00 DEG	900 M

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
2540 M 15 MVariable White	2540 M 60 M White LIH	RED RED	Red 46 M	Runway centerline lights between last 300M to 900M are alternate RED and WHITE. Last 300M are RED.
2540 M 15 MVariable White	2540 M 60 M White LIH	RED RED	Red 46 M	Runway centerline lights between last 300M to 900M are alternate RED and WHITE. Last 300M are RED.

VAPO AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	On top of aerodrome control tower; FPM: 24, During Night and Low visibility conditions.
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Landing 'T' is placed in front of ATC near the ARP. A landing 'T' for night ops is placed in front of ATC building.
		Anemometer	Near both RWY THR
3	Taxiway edge and taxiway centre line lights;	Edge	All taxiways
		Centre Line	Nil
4	Secondary power supply including switch-over time;	Secondary power supply available; Switch over time: 1 Sec: for inner 300m of approach lighting system, RWY threshold, RWY end, RWY center line, RWY touchdown zone and all stop bars. 15 Sec: Other parts of approach lighting system, RWY edge, TWY lights.	
5	Remarks	Nil	

VAPO AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	Not established
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	Not established
4	True bearings of FATO;	Not established
5	Declared distances available	Not established
6	Approach and FATO lighting;	Not established
7	Remarks	Helipad (H3) on P link abeam civil apron& landing can be permitted on P link abeam civil dispersal also.

VAPO AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	MCTR: Area bounded by lines joining points 185507N 0735457E; 185507N 0744315E then along the clockwise arc of a circle of 50NM radius centred on 183503N 0735457E to 174546N 0740452E; 182349N 0733731E then along the clockwise arc of a circle of 20NM radius centred on 183503N 0735457E to point of origin.
2	Vertical limits	FL 80
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Pune Tower, English
5	Transition altitude	7000 FT
6	Hours of applicability	H24
7	Remarks	1. VAR-37 is Pune LFA. When active, not to be entered without prior coordination with Pune ATC. 2. Controlling Unit: IAF Pune

VAPO AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Pune Approach	121.300 MHZ	
TWR	Pune Tower	123.500 MHZ	
ATIS	Pune Information	114.600 MHZ	
ACC	Pune Control	118.800 MHZ	
ALRS	Emergency Frequency	121.500 MHZ	
ALRS	Emergency Frequency	243.000 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	H24	NIL
	H24	NIL
	H24	Updated Hourly
	H24	NIL
	H24	UHF
	H24	UHF

VAPO AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
LOC 28 CAT II	IPUN	108.700 MHz	H24
GP 28		330.500 MHz	H24
DME ILS 28	IPUN	CH24X	H24
DVOR/DME	PPN	114.600 MHz CH93X	H24

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
183459.0N 0735414.0E			Resolution of Coordinates is up to Second
183458.0N 0735539.0E			Resolution of Coordinates is up to Second
183458.0N 0735539.0E	1943 FT		1. Collocated with GP 28 2. Resolution of Coordinates is up to Second
183504.4N 0735444.8E	1957 FT		Controlling Authority: Indian Air Force

VAPO AD 2.20 LOCAL AERODROME REGULATIONS

1. All ACFT to exercise caution while exiting Civil Apron from TWY N to avoid exerting excess thrust on ground service equipment parked in eastern side ramp equipment area.
2. Parallel Taxi Track is also being used for Landing and Take-off for fighter class Aircraft. Centre line of Parallel Taxi Track is marked with white broken lines, dimensions are 3M Length, 0.3M Width with spacing of 3M. Taxi exit markings are provided at each link connected with Parallel Taxi Track. Parallel Taxi Track Centre line markings are non standard specifications and not in compliance with ICAO Annex 14. All aircraft to comply with non standard markings for taxi guidance while manoeuvering on Parallel Taxi Track. All airline operator to brief crew to exercise caution on the markings on Parallel Taxi Track. Aircraft on APCH of RWY 10/28 to be cautious and not mistake Parallel Taxi Track as RWY.
3. All aircraft to strictly follow TWY marking to avoid Non Load Bearing drain covers at 28 Dispersal, marked in red and white with yellow border.

VAPO AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VAPO AD 2.22 FLIGHT PROCEDURES

1. DEPARTURE PROCEDURE

1.1 Pilot shall complete all mandatory pre departure checks before entering the active runway for departure so that the aircraft is in a position to take off immediately upon receipt of take-off clearance.

1.2 When the aircraft is issued with a line up and take-off clearance at taxi holding position it shall be in a position to line up and affect an immediate take off in one continuous movement.

1.3 When the aircraft is issued with a takeoff clearance after lining up on the runway, it shall commence take off roll immediately upon receipt of take of clearance.

1.4 If the Controller observes a delay in respect of the departing aircraft in commencing its take off run after issuance of take-

off clearance, the take-off clearance will be cancelled and the aircraft be advised to vacate the runways immediately at the nearest taxiway to make way for the subsequent arrival or departure.

1.5 Level restrictions for departing traffic: Based on LOA between Mumbai and Pune ATC, the following shall be adhered:

(a) W28 (Westbound Flights): All traffic departing from Pune via W-28 towards Mumbai are generally cleared to climb to FL 80. Further climb above FL80 shall be effected only after achieving positive two-way communication with Mumbai Approach on VHF 127.9 MHz/124.65 MHz or when explicitly cleared by Pune ATC.

(b) W28 (East bound Flights)/ W-67/ J-2: All traffic departing on given routes are generally cleared to climb to FL 130. Further climb above FL130 shall only be effected after achieving positive two-way communication with Mumbai Approach on VHF133.425 MHz/ 132.7 MHz /125.35 MHz or when explicitly cleared by Pune ATC.

1.6 Restrictions due to aerodrome proximity of Danger/Restricted areas around aerodrome:

(a) All departing aircraft from Runway 28 shall climb to at least 5000 Feet before commencing left turn to avoid overflying VAD-19.

(b) Helicopter operations to helipads located within LFA (VAR-37) shall be conducted on prior clearance from Pune ATC.

1.7 Direct Routings through VAR-37 (Pune LFA)

(a) Considering the military flying operations, all flights including low level traffic intending to route through VAR-37 shall do so only after achieving prior coordination with Pune ATC.

2. ARRIVAL PROCEDURES

2.1 Procedural controlling may be exercised for controllers training during periods of light density traffic. Relevant notice with adequate time will be given on RT and or ATIS. No Civil Aircraft landing and take-off is permitted when RVR is less than 350M

2.2 Arriving aircraft may be given direct routing with prior coordination with Pune.
No aircraft to route direct unless explicitly cleared by Pune ATC.

2.3 Arriving VFR flights to obtain prior necessary briefing for levels and routing from Pune Radar.

VAPO AD 2.23 ADDITIONAL INFORMATION

1. Glider/Micro light flying activities. Operations restricted to day light.

1.1 Hadapsar Glidrome: 166 DEG/ 10.4 NM. Area of Ops: 3 NM around glider drome up to 5000FT AGL. Not to be over flown below 6000Ft AMSL when glider drome is active.

1.2 NDA Khadakwasla: Aerodrome at 232 DEG/ 12NM. Area of Ops 10 Km around aerodrome up to 7000 Ft AMSL. Not to be over flown below 8000 FT AMSL when aerodrome is active. Not to be over flown below 6000 FT AMSL when aerodrome is not active.

2. Operation readiness Platform is available at the beginning of the runway for parking of fighter aircraft prior to takeoff. All scheduled and non-scheduled aircraft to exercise caution while lining up to ensure jet wake is not directed towards fighter aircrafts to avoid any foreign object damage.

3. Rowing Channel with similar orientation is located 291 DEG/4NM, left of approach path for RWY 10. While conducting visual approach for RWY 10, all aircrew to exercise caution for not to wrongly identify it as runway.

4. All 180 DEG turns to be executed on concrete portion of RWY only. No 180 DEG turn permitted on flexible surface of RWY by any type of aircraft. All pilot to exercise caution.

5. All civil non-sked flights operating to Pune Airport to take positive clearance from Pune ATC and parking clearance from Airports Authority of India. All operators are to strictly comply with.

6. Service road across taxiways K2, K3 and K4 leads to civil dispersal. Service road crosses across taxiways K2, K3 and K4. All aircraft to exercise caution and look out for vehicular traffic while taxing to/from civil dispersal.

7. Permanent obstruction. CFT shed on northern shoulder of RWY. Distance 129 M from RWY edge and 368M from threshold of RWY 10. Obstruction marked with day obstruction marking only. All pilots to exercise caution while landing/take-off.

8. Permanent obstruction of CFT shed on southern shoulder of RWY. Distance from threshold of RWY 28 is 385 M and distance from RWY edge is 119 M. obstruction marked with day marking.

9. Permanent obstruction. RWY controller hut on southern shoulder of RWY. Distance 107m from RWY centreline and 307m from threshold of RWY 28. Height 7.75m. Obstruction marked with day and night marking. All pilots to exercise caution. RWY controller hut on northern shoulder of runway distance 105 m from runway centre line and 275 m from threshold of RWY 10. Height 7.75m. Obstruction marked with day and night marking. All pilots to exercise caution

10. Dispersal named 28 dispersal is exclusively for fighter operation. Dispersal is bounded by RWY on North, parallel taxi track on South, link R1 on West and link P1 on East. White bay markings and white broken TWY centreline marking extend from link R1 to link P1 due operational reasons. Civil and military transport aircraft to exercise caution and follow continuous yellow TWY centerline on link P1. All sked and non-sked aircraft exercise caution while lining up to ensure jet wake is not directed towards parked fighter aircrafts to avoid any foreign object damage.

11. Permanent obstruction of arrester barrier huts on northern shoulder of rwy. Distance from threshold of RWY 28 is 45 ft and distance from RWY edge is 145 ft. Obstruction marked with day marking.

12. Permanent obstruction of arrester barrier huts on northern shoulder of undershoot of RWY 10. Distance from threshold of RWY 10 is 45 ft and distance from RWY edge is 130 ft. Obstruction marked with day marking.

13. All pushback in coordination with Apron Management.
14. Rapid exit taxiway R2 will be given to ac after landing for taxi in at the discretion of ATC tower due surface deterioration
15. All helicopters operating within 25 NM PPN to take positive clearance from Pune ATC and preferably to pass movement to Pune ATC one day prior.
16.All helicopters to switch off SSR mode C within 15 NM of PPN and to follow standard helicopter routing

17. **Speed control Procedure:**

(a) Speed control Procedure under non-Radar environment shall be as specified in ENR1.1 para 2.5 of eAIP India.

(b) Speed control procedure under Radar environment refer ENR 1.6 para 8 of eAIP India

18.**ATC surveillance service.**

(a) Radar vectors may be provided to arriving and departing ac by Pune radar as and when radar available.

(b) Radar vectoring altitude:

i) 3500 FT – Within 10 NM from PPN.

ii) 4000 FT – Radial 360 DEG to 140 DEG (10 NM to 20 NM).

iii) 5000 FT – Radial 360 DEG to 140 DEG (20 NM to 30 NM).

iv) 6000 FT – Radial 360 DEG to 140 DEG (30 NM to 40 NM).

v) 7000 FT – Radial 360 DEG to 140 DEG (beyond 40 NM and up to outer limit of VAR-37).

vi) 5000 FT – Radial 250 DEG to 360 DEG (20 NM to 30 NM).

vii) 6000 FT – Radial 250 DEG to 360 DEG (30 NM to 40 NM).

viii) 7000 FT – Radial 250 DEG to 360 DEG (beyond 40 NM and up to outer limit of VAR-37).

ix) 6000 FT – Radial 140 DEG to 250 DEG (10 NM to 20 NM).

x) 7000 FT – Radial 140 DEG to 250 DEG (beyond 20 NM and up to outer limit of VAR-37).

xi) 5000FT - Radial 250 DEG TO 360 DEG (10NM to 20NM)

Note: All BRGS and DIST FM ARP of VAPO AP.

19.**Danger/Prohibited area around Pune** :

i) Dehu Road Ordinance Factory: BRG 299DEG DIST 22KM.

Flying below 500FT AMSL,prohibitted.

ii) Dighi Field Frng Range: BRG 325DEG DIST 4.5 KM.

Active daily.

Safety HGT: 2000FT AGL.

iii) Bhose Camp Field Frng Range BRG 342DEG 26KM.

Active daily.

Safety HGT: 3000FT AGL.

iv) Pashan Field Frng Range: BRG 243DEG DIST 12KM.

Day Timings FM MON TO FRI ACT BTN 0300-1140 UTC, NGT on MON and FRI BTN 1300-1630 UTC

Safety HGT 5000FT AGL)

VAPO AD 2.24 CHARTS RELATED TO AN AERODROME

1	ILS (Z) Procedure RWY 28
2	ILS (CAT II) Procedure RWY 28
3	VOR Procedure RWY 10(27 November 2025)
4	VOR (Z) Procedure RWY 28
5	VOR (Y) Procedure RWY 28
6	SID RWY 10
7	SID RWY 28
8	Aerodrome Parking and Docking Chart(22 JAN 2026)

VAPO AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	2	3