AD 2. AERODROMES

VERK AD 2.1 AERODROME LOCATION INDICATOR AND NAME

VERK - ROURKELA AIRPORT, ROURKELA

VERK AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Aerodrome reference point coordinates and its site	221522N 0844853E In front of Tower.	
2	Direction and distance of aerodrome reference point from the centre of the city or town which the aerodrome serves	10 KM West of Rourkela Railway Station	
3	Aerodrome elevation and reference temperature	673 FT / 45.0 DEG C	
4	Magnetic variation, date of information and annual change	0.50 DEG W (2010) /0.0166 DEG E	
5	Name of aerodrome operator, address, telephone, telefax, e-mail address, AFS address, website (if available)	Steel Authority of India Limited Rourkela Steel Plant Rourkela -769011.,	
		Telephone:	(91) 661 2602601 (91) 661 2646318 (91) 8895500885
		Fax:	(91) 661 2646318
		AFS:	
		Email:	bijaykumar.raut@sailrsp.co.in
6	Types of traffic permitted (IFR/VFR)	VFR	
7	Remarks	Vertical Reference System: EGM08	

VERK AD 2.3 OPERATIONAL HOURS

1	Aerodrome Operator	ALL WEEK DAYS 0915-1115 UTC (1445-1645 IST)
2	Custom and immigration	NIL
3	Health and sanitation	Available
4	AIS briefing office	AS ATS
5	ATS reporting office (ARO)	AS ATS
6	MET Briefing office	AS ATS
7	Air Traffic Service	AS ATS
8	Fuelling	AS ATS (by IOCL)
9	Handling	AS ATS
10	Security	AS ATS
11	De-icing	NIL
12	Remarks	NIL

VERK AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel and Oil types	JET A1 ATF
3	Fuelling facilities and capacity	30KL

4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	Nil

VERK AD 2.5 PASSENGER FACILITIES

1	Hotel(s) at or in the vicinity of aerodrome	Budget and premium hotels are available In the city
2	Restaurant(s) at or in the vicinity of aerodrome	In the City
3	Transportation possibilities	Auto, Taxi
4	Medical Facilities	In the city
5	Bank and post office at or in the vicinity of aerodrome	Banks: In the city Post office: In the city
6	Tourist office	NIL
7	Remarks	Nil

VERK AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	Aerodrome category for fire fighting	Within ATS HR: CAT-4
2	Rescue equipment	Available as per AD category
3	Capability for removal of disabled aircraft	1. The critical aircraft for the airport is ATR 72-600. 2. Primary responsibility for removal of disabled aircraft rests with the concerned airline. 3. The airlines may contact 'Aerodrome Coordinator for Disabled Aircraft Removal Operations' for coordinating with the agencies having Disabled Aircraft Recovery Kit. 4. Contact Details of Aerodrome Coordinator for Disabled Aircraft Removal Operations: Aerodrome coordinator: ACCOUNTABLE EXECUTIVE Email : rsp.verkaex@sail.in Contact No: +91-8895500885
4	Remarks	Nil

VERK AD 2.7 SEASONAL AVAILABILITY CLEARING

1	Type(s) of clearing equipment	Not available
2	Clearance priorities	Not available
3	Remarks	Nil

VERK AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Designation, surface and strength of aprons	Refer Aircraft Parking/Docking Chart
2	Designation, width, surface and strength of taxiways	Refer Aircraft Parking/Docking Chart
3	Location and elevation of altimeter checkpoints	Location Elevation Bay Nr 1 198.12M Bay Nr 2 197.51M

4	Location of VOR checkpoints	NIL
5	Position of INS checkpoints	NIL
6	Remarks	NIL

VERK AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand identification signs, taxiway guidelines and visual docking/parking guidance system at aircraft stands	Taxiway guidelines available upto stands. Parking guidance by Marshallers
2	Runway and taxiway markings and lights	RWY Markings: Runway Designation, Threshold, Aiming Point, Touchdown zone, Centreline and Edge. Lights NIL TWY Marking: Taxiway Center line, Edge, Runway Holding Position. Lights: NIL
3	Stop bars (if any)	NIL
4	Remarks	NIL

VERK AD 2.10 AERODROME OBSTACLES

In Approach/Take-off/Circling Area and at AD					
1	**2**	**3**	**4**	**5**	**6**
RWY/Area affected	Obstacle type	Coordinates	Elevation (EGM08)	Marking/LGT	Remarks
27/TKOF 09/APCH	TREE	221523.0N 0844815.0E	676 FT	NIL	Group of Tree
27/TKOF 09/APCH	TREE	221520.4N 0844815.4E	700 FT	NIL	Group of Tree
27/TKOF 09/APCH	TREE	221521.4N 0844814.7E	690 FT	NIL	Group of Tree
27/TKOF 09/APCH	TREE	221520.6N 0844813.2E	697 FT	NIL	Group of Tree
27/TKOF 09/APCH	TREE	221523.9N 0844813.8E	678 FT	NIL	Group of Tree
27/TKOF 09/APCH	TREE	221524.6N 0844813.0E	685 FT	NIL	Group of Tree
27/TKOF 09/APCH	TREE	221525.2N 0844811.4E	677 FT	NIL	Group of Tree
27/TKOF 09/APCH	FENCE	221524.3N 0844819.2E	652 FT	NIL	Fencing
27/APCH 09/TKOF	OTHER	221455.9N 0845018.8E	823 FT	LGTD	Cell Phone Mast
27/APCH 09/TKOF	OTHER	221446.0N 0845028.3E	843 FT	LGTD	Cell Phone Mast
27/APCH 09/TKOF	OTHER	221444.1N 0845037.2E	837 FT	LGTD	Cell Phone Mast

VERK AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Name of the associated meteorological office	IMD Established. MET data from ROURKELA airport
2	Hours of service and, where applicable, the designation of the responsible meteorological office outside these hours	As ATS, Current weather observation will be recorded during off hours of Airport operation.
3	Office responsible for preparation of TAFs and periods of validity and interval of issuance of the forecasts	Kolkata
4	Availability of the trend forecast for the aerodrome and interval of issuance	Trend Half hourly METARs
5	Information on how briefing and/or consultation is provided	DPTIMD website- http://www.imd.gov.in, Email, FAX, MFI, HPCS, all at AMO, VEBS.
6	Types of flight documentation supplied and language(s) used in flight documentation	English
7	Charts and other information displayed or available for briefing or consultation	NOT AVAILABLE
8	Supplementary equipment available for providing information on meteorological conditions, e.g. weather radar and receiver for satellite images;	Radar not available, present weather observation to pass
9	The air traffic services unit(s) provided with meteorological information	VERK MET
10	Additional information, e.g. concerning any limitation of service.	NIL

VERK AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations	TRUE Bearings	Dimensions of RWY (M)	Strength of pavement (PCN) and associated data) and surface of runway and associated stopways	Geographical coordinates for threshold and runway end
1	2	3	4	5
09	90.30 DEG	1760 x 30 M	16/F/D/Y/T Macadam	THR: 221523.43N 0844825.67E RWY END: 221523.93N 0844924.14E
27	270.30 DEG	1760 x 30 M	16/F/D/Y/T Macadam	THR: 221523.93N 0844924.14E RWY END: 221523.39N 0844820.61E

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 651.0FT TDZ:		NIL	NIL	1880 x 80 M

THR elevation and highest elevation of TDZ of precision APP RWY	Slope of runway and associated stopway	Dimensions of stopway (M)	Dimensions of clearway (M)	Dimensions of strips (M)
6	7	8	9	10
THR: 672.0FT TDZ:		NIL	NIL	1880 x 80 M

Dimensions of runway end safety areas	Location and description of arresting system (if any)	Existence of an obstacle-free zone	Remarks.
11	12	13	14
60M x 60M		NIL	Vertical Reference System: EGM08
NIL		NIL	Vertical Reference System: EGM08

VERK AD 2.13 DECLARED DISTANCES

RWY Designator	Take-off run available TORA (M)	Take-off distance available TODA (M)	Accelerate distance available ASDA (M)	Landing distance available LDA (M)	Remarks (including runway entry or start point where alternative reduced declared distances have been declared)
1	2	3	4	5	6
09	1760	1760	1760	1675	1. Threshold displaced by 85M 2. The declared distances of RWY 09 are considered as 1760M after considering 60M runway strip from total length of Runway in the beginning of RWY 09
27	1675	1675	1675	1760	The LDA of RWY 27 is considered as 1760M after considering 60M runway strip at the end of RWY 27 (beginning of RWY 09). Hence there is no displacement for RWY 27.

VERK AD 2.14 APPROACH AND RUNWAY LIGHTING

Runway Designator	Type, length and intensity of approach lighting system	Runway threshold lights, colour and wing bars	Type of visual slope indicator system	Length of runway touchdown zone lights
1	2	3	4	5
09	NIL	NIL	NIL	NIL
27			NIL	

Length, spacing, colour and intensity of runway centre line lights	Length, spacing, colour and intensity of runway edge lights	Colour of runway end lights and wing bars	Length and colour of stopway lights	Remarks
6	7	8	9	10
NIL	NIL	NIL	NIL	NIL
				NIL

VERK AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Location, characteristics and hours of operation of aerodrome beacon/identification beacon (if any)	ABN	Available
		IBN	NIL
2	Location and lighting (if any) of anemometer/ landing direction indicator;	LDI	Available& Lighted
		Anemometer	Available
3	Taxiway edge and taxiway centre line lights;	Edge	Not Available
		Centre Line	Not Available
4	Secondary power supply including switch-over time;	Less than 15 Second	
5	Remarks	NIL	

VERK AD 2.16 HELICOPTER LANDING AREA

1	Geographical coordinates of the geometric centre of touchdown and lift-off (TLOF) or of each threshold of final approach and take-off (FATO) area	Not established
2	TLOF and/or FATO area elevation:	---
3	TLOF and FATO area dimensions to the nearest metre or foot, surface type, bearing strength and marking;	---
4	True bearings of FATO;	---
5	Declared distances available	---
6	Approach and FATO lighting;	---
7	Remarks	---

VERK AD 2.17 AIR TRAFFIC SERVICE AIRSPACE

1	Airspace designation, geographical coordinates and lateral limits	CTR: Area bounded by lines joining points 220246N 0843505E then along the clockwise arc of a circle of 18NM radius centred on 221522N 0844853E to 221415N 0850822E to point of origin.
2	Vertical limits	FL 85
3	Airspace classification	D
4	Call sign and language(s) of the air traffic services unit providing service;	Rourkela Tower, English
5	Transition altitude	6000 FT
6	Hours of applicability	AS ATS
7	Remarks	1. CTR available during published operational hours. 2. Airspace classified as Class D 3. Beyond operational hours airspace classification is Class G. 4.Rourkela Approach Control Unit is combined with Rourkela Aerodrome Control Tower

VERK AD 2.18 AIR TRAFFIC SERVICES COMMUNICATION FACILITIES

Service Designation	Call sign	Channel(s)	SATVOICE Number(s), if available
1	2	3	4
APP	Rourkela Tower	118.750 MHZ	
APP	Rourkela Tower	118.875 MHZ	
TWR	Rourkela Tower	118.750 MHZ	
TWR	Rourkela Tower	118.875 MHZ	

Logon address, as appropriate	Hours of operation	Remarks
5	6	7
	HO	1.Main FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	1.Backup FREQ 2.Functions of Approach Control Service provided by Aerodrome Control Tower.
	HO	MAIN
	HO	BACKUP.

VERK AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aids, magnetic variation and type of supported operation for ILS/ MLS, basic GNSS, SBAS and GBAS, and for VOR/ILS/MLS station used for technical lineup of the aid	Identification	Frequency(ies), Channel number(s), Service provider, and reference path identifier(s) (RPI), as appropriate	Hours of operation, as appropriate;
1	2	3	4
NIL	NIL	NIL	NIL

Geographical coordinates of the position of the transmitting antenna	Elevation of transmitting antenna of DME/ elevation of GBAS reference point	Service volume radius from the GBAS reference point	Remarks
5	6	7	8
NIL	NIL	NIL	NIL

VERK AD 2.20 LOCAL AERODROME REGULATIONS

NIL

VERK AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

VERK AD 2.22 FLIGHT PROCEDURES

NIL

VERK AD 2.23 ADDITIONAL INFORMATION

NIL

VERK AD 2.24 CHARTS RELATED TO AN AERODROME

1. Aerodrome Chart
2. Aircraft Parking Docking Chart
3. Aerodrome Obstacle Chart – (Operating Limitations) Type A RWY 09
4. Aerodrome Obstacle Chart – (Operating Limitations) Type A RWY 27
5. Aerodrome Obstacle Chart Type - B

VERK AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION

Procedure	Procedure Minima	VSS Penetration
1	**2**	**3**